

RF EXPOSURE EVALUATION

MPE-Based Exemption

Applicable Standard

According to subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

According to KDB 447498 D04 v01 Interim General RF Exposure Guidance

MPE-Based Exemption:

General frequency and separation-distance dependent MPE-based effective radiated power(ERP) thresholds are in Table B.1 [Table 1 of § 1.1307(b)(3)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2 f$.
1,500-100,000	$19.2 R^2$.

R is the minimum separation distance in meters

f = frequency in MHz

For multiple RF sources: Multiple RF sources are exempt if:

in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation:

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

Result

Mode	Frequency (MHz)	Tune up conducted power [#] (dBm)	Antenna Gain [#]		ERP		Evaluation Distance (m)	ERP Limit (mW)
			(dBi)	(dBd)	(dBm)	(mW)		
BT	2402-2480	8.5	0.92	-1.23	7.27	5.33	0.2	768
BLE	2402-2480	4.5	0.92	-1.23	3.27	2.12	0.2	768
2.4G Wi-Fi	2412-2462	24.5	0.92	-1.23	23.27	212.32	0.2	768
5.2G Wi-Fi	5180-5240	14.5	4.02	1.87	16.37	43.35	0.2	768
5.3G Wi-Fi	5260-5320	16.5	4.79	2.64	19.14	82.04	0.2	768
5.6G Wi-Fi	5500-5720	16.5	5.20	3.05	19.55	90.16	0.2	768
5.8G Wi-Fi	5745-5825	15.5	5.56	3.41	18.91	77.80	0.2	768

Note: 1. The tune up conducted power and antenna gain was declared by the applicant.
 2. 0dBd=2.15dBi
 3. The BT and 5G Wi-Fi can transmit at same time, the BT/5G and 2.4G Wi-Fi cannot transmit at same time.

Simultaneous transmitting consideration (worst case):

The ratio= $ERP_{BT}/limit + ERP_{5G\ Wi-Fi}/limit = 5.33/768 + 90.16/768 = 0.124 < 1.0$

So simultaneous exposure is compliant.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliant