

TEST REPORT

Applicant Name: YEALINK(XIAMEN) NETWORK TECHNOLOGY CO.,LTD.
Address: No.666 Hu'an Rd. Huli District Xiamen City, Fujian, P.R. China
Report Number: 2501X19230E-RFD
FCC ID: T2C-MP55E2
IC: 10741A-MP55E2

Test Standard (s)

FCC PART 15.407;
RSS-GEN ISSUE 5, FEBRUARY 2021 AMENDMENT 2; RSS-247 ISSUE 3, AUGUST 2023

Sample Description

Product Type: Smart Business Phone
Model No.: MP55 E2
Multiple Model(s) No.: N/A
Trade Mark: **Yealink**
Date Received: 2025/09/12
Issue Date: 2025/10/30

Test Result:	Pass▲
--------------	-------

▲ In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

Ruby Huang

Ruby Huang
RF Engineer

Approved By:

Nancy Wang

Nancy Wang
RF Supervisor

Note: The information marked * is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included.
This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.
This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP or any agency of the U.S. Government.
This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk "▼".

Bay Area Compliance Laboratories Corp. (Shenzhen)

5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China
Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	3
GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION	6
SUMMARY OF TEST RESULTS	11
TEST EQUIPMENT LIST	12
REQUIREMENTS AND TEST PROCEDURES	14
CONDUCTED EMISSIONS	14
UNDESIRABLE EMISSION & RESTRICTED BANDS	17
EMISSION BANDWIDTH & 99% OCCUPIED BANDWIDTH	23
TRANSMITTER OUTPUT POWER	26
POWER SPECTRAL DENSITY	28
ADDITIONAL REQUIREMENTS	30
DUTY CYCLE	32
ANTENNA REQUIREMENT	33
TEST DATA AND RESULTS	35
CONDUCTED EMISSIONS	35
UNDESIRABLE EMISSION	38
RF CONDUCTED DATA	301
26dB ATTENUATED BELOW THE CHANNEL POWER	301
EMISSION BANDWIDTH	303
99% OCCUPIED BANDWIDTH	317
MAXIMUM CONDUCTED OUTPUT POWER	331
POWER SPECTRAL DENSITY	335
DUTY CYCLE	349
RF EXPOSURE EVALUATION	351
EUT PHOTOGRAPHS	354
TEST SETUP PHOTOGRAPHS	355

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	2501X19230E-RFD	Original Report	2025/10/30

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

HVIN	MP55E2
FVIN	176.15.252.57
Frequency Range	5150-5250MHz; 5250-5350MHz; 5470-5725MHz; 5725-5850MHz
Mode	802.11a/n20/n40/ac20/ac40/ax20/ax40
Maximum Conducted Average Output Power	5150-5250MHz: 14.17dBm; 5250-5350MHz: 16.37dBm 5470-5725MHz: 16.24dBm; 5725-5850MHz: 15.04dBm
EIRP	5150-5250MHz: 18.19dBm
Modulation Technique	OFDM, OFDMA
Antenna Specification[#]	5150-5250MHz::4.02dBi; 5250-5350MHz:4.79dBi 5470-5725MHz: 5.20dBi; 5725-5850MHz: 5.56dBi (provided by the applicant)
Voltage Range	DC 5V from adapter or DC 48V from POE
Sample serial number	39TF-1 for Conducted and Radiated Emissions Test 39TF-3 for RF Conducted Test (Assigned by BACL, Shenzhen)
Adapter Information	Adapter 1: Model: YLPS052000B1-US Input:100-240V,50/60Hz,0.5A Output:5V/2A Adapter 2: Model: YLPS052000C1-US Input:100-240V,50/60Hz,0.5A Output:5V/2A Adapter 3: Model: YLPS052000E1-US Input:100-240V,50/60Hz,0.5A Output:5V/2A
Note: 1. The 5600-5650MHz was disabled by software for Canada. 2. The EUT powered by three adapters or POE, the worst case power supply was selected to test for AC line conducted and radiated emission below 1GHz according to BT report test result.	

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and E of the Federal Communication Commissions rules and RSS-GEN Issue 5, February 2021 Amendment 2 and RSS-247 Issue 3, August 2023 of the Innovation, Science and Economic Development Canada rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2020 + Cor.1-2023 ▼, RSS-Gen and RSS-247.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Each test item follows test standards and with no deviation.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		109.2kHz(k=2, 95% level of confidence)
RF Frequency		56.6Hz(k=2, 95% level of confidence)
RF output power, conducted		0.86dB(k=2, 95% level of confidence)
Unwanted Emission, conducted		1.60dB(k=2, 95% level of confidence)
Power Spectral Density		0.90dB(k=2, 95% level of confidence)
AC Power Lines Conducted Emissions	9kHz-150kHz	3.63dB(k=2, 95% level of confidence)
	150kHz-30MHz	3.66dB(k=2, 95% level of confidence)
Radiated Emissions	9kHz - 30MHz	3.60dB(k=2, 95% level of confidence)
	30MHz~200MHz (Horizontal)	5.32dB(k=2, 95% level of confidence)
	30MHz~200MHz (Vertical)	5.43dB(k=2, 95% level of confidence)
	200MHz~1000MHz (Horizontal)	5.77dB(k=2, 95% level of confidence)
	200MHz~1000MHz (Vertical)	5.73dB(k=2, 95% level of confidence)
	1GHz - 6GHz	5.34dB(k=2, 95% level of confidence)
	6GHz - 18GHz	5.40dB(k=2, 95% level of confidence)
18GHz - 40GHz		5.64dB(k=2, 95% level of confidence)
Temperature		±1°C
Humidity		±1%
Supply voltages		±0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 715558, the FCC Designation No. : CN5045.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0023.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode, which was provided by manufacturer.

For 5150-5250MHz Band, 6 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	44	5220
38	5190	46	5230
40	5200	48	5240

For 802.11a/ac20/ax20 mode: channel 36, 40, 48 were tested

For 802.11ac40/ax40 mode: channel 38, 46 were tested

For 5250-5350MHz Band, 6 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
52	5260	60	5300
54	5270	62	5310
56	5280	64	5320

For 802.11a/ac20/ax20 mode: channel 52, 56, 64 were tested;

For 802.11ac40/ax40 mode: channel 54, 62 were tested

For 5470-5725MHz Band, 18 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
100	5500	124*	5620
102	5510	126*	5630
104	5520	128*	5640
108	5540	132	5660
110	5550	134	5670
112	5560	136	5680
116	5580	140	5700
118*	5590	142	5710
120*	5600	144	5720

For 802.11a, 802.11ac20 mode: channel 100, 116, 140, 144 were tested

For 802.11ac40 mode: channel 102, 110, 134, 142 were tested

*The 5600-5650MHz was disabled by software for Canada.

For 5725-5850MHz Band, 7 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	159	5795
151	5755	161	5805
153	5765	165	5825
157	5785	/	/

For 802.11a/ac20/ax20 mode: channel 149, 157, 165 were tested

For 802.11ac40/ax40 mode: channel 151, 159 were tested

EUT Exercise Software

Exercise Software [#]	AuthenticationTool.exe			
5150-5250 MHz Band				
Mode	Test Channels	Test Frequency (MHz)	Data rate	Power Level [#]
802.11a	Low	5180	6Mbps	16
	Middle	5200	6Mbps	16
	High	5240	6Mbps	16
802.11ac-VHT20	Low	5180	MCS0	16
	Middle	5200	MCS0	16
	High	5240	MCS0	16
802.11ac-VHT40	Low	5190	MCS0	16
	High	5230	MCS0	16
802.11ax-HE20	Low	5180	MCS0	16
	Middle	5200	MCS0	16
	High	5240	MCS0	16
802.11ax-HE40	Low	5190	MCS0	16
	High	5230	MCS0	16
5250-5350 MHz Band				
Mode	Test Channels	Test Frequency (MHz)	Data rate	Power Level [#]
802.11a	Low	5260	6Mbps	16
	Middle	5280	6Mbps	16
	High	5320	6Mbps	16
802.11ac-VHT20	Low	5260	MCS0	16
	Middle	5280	MCS0	16
	High	5320	MCS0	16
802.11ac-VHT40	Low	5270	MCS0	16
	High	5310	MCS0	16
802.11ax-HE20	Low	5260	MCS0	16
	Middle	5280	MCS0	16
	High	5320	MCS0	16
802.11ax-HE40	Low	5270	MCS0	16
	High	5310	MCS0	16

5470-5725 MHz Band				
Mode	Test Channels	Test Frequency (MHz)	Data rate	Power Level [#]
802.11a	Low	5500	6Mbps	16
	Middle	5580	6Mbps	16
	High	5700	6Mbps	16
	Cross	5720	6Mbps	16
802.11ac-VHT20	Low	5500	MCS0	16
	Middle	5580	MCS0	16
	High	5700	MCS0	16
	Cross	5720	MCS0	16
802.11ac-VHT40	Low	5510	MCS0	16
	Middle	5550	MCS0	16
	High	5670	MCS0	16
	Cross	5710	MCS0	16
802.11ax-HE20	Low	5500	MCS0	16
	Middle	5580	MCS0	16
	High	5700	MCS0	16
	Cross	5720	MCS0	16
802.11ax-HE40	Low	5510	MCS0	16
	Middle	5550	MCS0	16
	High	5670	MCS0	16
	Cross	5710	MCS0	16
5725-5850 MHz Band				
Mode	Test Channels	Test Frequency (MHz)	Data rate	Power Level [#]
802.11a	Low	5745	6Mbps	16
	Middle	5785	6Mbps	16
	High	5825	6Mbps	16
802.11ac-VHT20	Low	5745	MCS0	16
	Middle	5785	MCS0	16
	High	5825	MCS0	16
802.11ac-VHT40	Low	5755	MCS0	16
	High	5795	MCS0	16
802.11ax-HE20	Low	5745	MCS0	16
	Middle	5785	MCS0	16
	High	5825	MCS0	16
802.11ax-HE40	Low	5755	MCS0	16
	High	5795	MCS0	16

Note:

1. The worst-case data rates are determined to be as follows for each mode based upon investigation by measuring the power and PSD across all data rates bandwidths, and modulations.
2. The n20/n40 mode was reduced test as identical parameter with ac20/ac40 mode.
3. For 802.11 ax modes, the device not support partial RU mode.

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
DELL	Notebook	Latitude E6410	37K4X AOO
Grandstream	Router	GWN7665	C074AD251F0A
YEALINK	Headset	Unknown	Unknown
Kingston	USB disk	Unknown	Unknown
TP-Link	POE	TL170S	422B230000460

External I/O Cable


Cable Description	Length (m)	From Port	To
Unshielded un-detachable AC cable	1.2	Receptacle	AC Mains
Unshielded un-detachable DC cable	1.5	EUT	Adapter
Unshielded un-detachable Audio cable	1.2	EUT	Headset
Unshielded detachable RJ45 cable	5.0	EUT	Notebook
Unshielded detachable RJ45 cable	5.0	EUT/POE	Router
Unshielded detachable AC cable	1.5	POE	LISN
Unshielded detachable RJ45 cable	1.0	POE	EUT

Block Diagram of Test Setup


For Conducted Emissions:



For Radiated Emissions below 1GHz:



For Radiated Emissions above 1GHz:



SUMMARY OF TEST RESULTS

Test Rules	Test Rules	Description of Test	Result
FCC §1.1307(b) (3), §2.1091	/	MPE-Based Exemption	Compliant
/	RSS-102 § 6.6	Field reference level exposure exemption limits	Compliant
FCC §15.203	RSS-Gen §6.8	Antenna Requirement	Compliant
FCC §15.207(a)	RSS-Gen §8.8	Conducted Emissions	Compliant
FCC §15.205& §15.209 &§15.407(b)	RSS-Gen §8.10& RSS-247§6.2	Undesirable Emission& Restricted Bands	Compliant
FCC §15.407(a) (e)	RSS- Gen§6.7, RSS-247 § 6.2	Emission Bandwidth & 99% Occupied Bandwidth	Compliant
FCC §15.407(a)	RSS-247 §6.2	Conducted Transmitter Output Power	Compliant
FCC §15.407 (a)	RSS-247 §6.2	Power Spectral Density	Compliant
FCC §15.407 (h)	RSS-247 §6.2	Transmit Power Control (TPC)	Not Applicable
FCC §15.407 (h)	RSS-247 §6.3	Dynamic Frequency Selection (DFS)	Compliant*
/	RSS-247 §6.4	Additional requirement	Compliant
C63.10 §11.6	C63.10 §11.6	Duty Cycle	/

Compliant*: Please refer to the DFS report 2501X19230E-RFE.

Not Applicable: For 5250-5350MHz/5470-5725MHz, the maximum EIRP is 21.44dBm<27dBm (500mW).

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2025/09/01	2026/08/31
Rohde & Schwarz	LISN	ENV216	101613	2025/09/18	2026/09/17
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2025/09/18	2026/09/17
Unknown	CE Cable	Unknown	UF A210B-1-0720-504504	2025/09/18	2026/09/17
Audix	EMI Test software	E3	191218 V9(c)	NCR	NCR
Radiated Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESR3	102455	2025/09/01	2026/08/31
Sonoma instrument	Pre-amplifier	310N	186238	2025/09/08	2026/09/07
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2023/07/20	2026/07/19
Unknown	Chamber A Cable	Cable A3	Cable A3	2025/09/08	2026/09/07
Unknown	Chamber A Cable	Cable A4	Cable A4	2025/09/08	2026/09/07
BACL	Active Loop Antenna	1313-1A	4031911	2024/05/14	2027/05/13
Unknown	Chamber A Cable	Cable A2	Cable A2	2025/09/08	2026/09/07
Unknown	Chamber A Cable	Cable A1	Cable A1	2025/09/08	2026/09/07
Audix	EMI Test software	E3	19821b(V9)	NCR	NCR
Rohde&Schwarz	Spectrum Analyzer	FSV40	101605	2025/09/01	2026/08/31
A.H.System	Preamplifier	PAM-0118P	489	2025/09/08	2026/09/07
Schwarzbeck	Horn Antenna	BBHA9120D(1201)	1143	2023/07/26	2026/07/25
Unknown	Chamber B Cable	Cable B1	Cable B1	2025/09/08	2026/09/07
Unknown	Chamber B Cable	Cable B2	Cable B2	2025/09/08	2026/09/07
Unknown	Chamber B Cable	Cable B3	Cable B3	2025/09/08	2026/09/07
JD	Filter Switch Unit	DT7220FSU	DS79906	2025/08/12	2026/08/11
JD	Multiplex Switch Test Control Set	DT7220SCU	DS79903	2025/08/12	2026/08/11
A.H.System	Pre-amplifier	PAM-1840VH	190	2025/09/08	2026/09/07
Electro-Mechanics Co	Horn Antenna	3116	9510-2270	2023/09/18	2026/09/17
UTIFLEX	Chamber B Cable	Cable B4	Cable B4	2025/09/17	2026/09/16
Audix	EMI Test software	E3	191218 V9(c)	NCR	NCR

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
RF Conducted Test					
R&S	Spectrum Analyzer	FSV40	101942	2025/09/01	2026/08/31
ANRITSU	Microwave peak power sensor	MA24418A	12622	2025/09/01	2026/08/31
Unknown	10dB Attenuator	Unknown	F-03-EM190	2025/06/26	2026/06/25

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

REQUIREMENTS AND TEST PROCEDURES

Conducted Emissions

Applicable Standard

FCC §15.207 & RSS-Gen §8.8

Unless stated otherwise in the applicable RSS, for radio apparatus that are designed to be connected to the public utility AC power network, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the range 150 kHz to 30 MHz shall not exceed the limits in table 4, as measured using a 50 μ H / 50 Ω line impedance stabilization network. This requirement applies for the radio frequency voltage measured between each power line and the ground terminal of each AC power-line mains cable of the EUT.

For an EUT that connects to the AC power lines indirectly, through another device, the requirement for compliance with the limits in table 4 shall apply at the terminals of the AC power-line mains cable of a representative support device, while it provides power to the EUT. The lower limit applies at the boundary between the frequency ranges. The device used to power the EUT shall be representative of typical applications.


Table 4 - AC Power Lines Conducted Emission Limits		
Frequency range (MHz)	Conducted limit (dB μ V)	
	Quasi-Peak	Average
0.15 – 0.5	66 to 56 ¹	56 to 46 ¹
0.5 – 5	56	46
5 – 30	60	50

Note 1: The level decreases linearly with the logarithm of the frequency.

For an EUT with a permanent or detachable antenna operating between 150 kHz and 30 MHz, the AC power-line conducted emissions must be measured using the following configurations:

- Perform the AC power-line conducted emissions test with the antenna connected to determine compliance with the limits of table 4 outside the transmitter's fundamental emission band.
- Retest with a dummy load instead of the antenna to determine compliance with the limits of table 4 within the transmitter's fundamental emission band. For a detachable antenna, remove the antenna and connect a suitable dummy load to the antenna connector. For a permanent antenna, remove the antenna and terminate the RF output with a dummy load or network that simulates the antenna in the fundamental frequency band.

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2020 measurement procedure. The specification used was with the FCC Part 15.207 & RSS-247/RSS-Gen limits.

The spacing between the peripherals was 10 cm.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN; the other related equipments were connected to the other LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and Average detection mode.

Factor & Over Limit Calculation

The factor is calculated by adding LISN VDF (Voltage Division Factor) and Cable Loss. The basic equation is as follows:

$$\text{Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over limit of -7 dB means the emission is 7 dB below the limit. The equation for calculation is as follows:

$$\begin{aligned}\text{Over Limit} &= \text{Level} - \text{Limit} \\ \text{Level} &= \text{Read Level} + \text{Factor}\end{aligned}$$

Note: The term "cable loss" refers to the combination of a cable and a 10dB transient limiter (attenuator).

Undesirable Emission & Restricted Bands

Applicable Standard

FCC §15.407 (b); §15.209; §15.205;

(b) Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band:
 - (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209.

According to RSS-247§6.2

Frequency band 5150-5250 MHz

6.2.1.2 Unwanted emission limits

For transmitters with operating frequencies in the band 5150-5250 MHz, all emissions outside the band 5150-5350 MHz shall not exceed -27 dBm/MHz e.i.r.p. Any unwanted emissions that fall into the band 5250-5350 MHz shall be attenuated below the channel power by at least 26 dB, when measured using a resolution bandwidth between 1 and 5% of the occupied bandwidth (i.e. 99% bandwidth), above 5250 MHz. The 26 dB bandwidth may fall into the 5250-5350 MHz band; however, if the occupied bandwidth also falls within the 5250-5350 MHz band, the transmission is considered as intentional and the devices shall comply with all requirements in the band 5250-5350 MHz including implementing dynamic frequency selection (DFS) and TPC, on the portion of the emission that resides in the 5250-5350 MHz band.

Frequency band 5250-5350 MHz

6.2.2.2 Unwanted emission limits

Devices shall comply with the following:

- a. All emissions outside the band 5250-5350 MHz shall not exceed -27 dBm/MHz e.i.r.p.; or
- b. All emissions outside the band 5150-5350 MHz shall not exceed -27 dBm/MHz e.i.r.p. and its power shall comply with the spectral power density for operation within the band 5150-5250 MHz. The device, except devices installed in vehicles, shall be labelled or include in the user manual the following text “for indoor use only.”

Frequency band 5470-5600 MHz and 5650-5725 MHz

6.2.3.2 Unwanted emission limits

Emissions outside the band 5470-5725 MHz shall not exceed -27 dBm/MHz e.i.r.p. However, devices with bandwidth overlapping the band edge of 5725 MHz can meet the emission limit of -27 dBm/MHz e.i.r.p. at 5850 MHz instead of 5725 MHz.

Frequency band 5725-5850 MHz

6.2.4.3 Unwanted emission limits

Devices operating in the band 5725-5850 MHz shall have e.i.r.p. of unwanted emissions comply with the following:

- a. 27 dBm/MHz at frequencies from the band edges decreasing linearly to 15.6 Bm/MHz at 5 MHz above or below the band edges;
- b. 15.6 dBm/MHz at 5 MHz above or below the band edges decreasing linearly to 10 dBm/MHz at 25 MHz above or below the band edges;
- c. 10 dBm/MHz at 25 MHz above or below the band edges decreasing linearly to -27 dBm/MHz at 75 MHz above or below the band edges; and
- d. -27 dBm/MHz at frequencies more than 75 MHz above or below the band edges.

According to RSS-Gen §8.10

Restricted frequency bands, identified in table 7, are designated primarily for safety-of-life services (distress calling and certain aeronautical activities), certain satellite downlinks, radio astronomy and some government uses. Except where otherwise indicated, the following conditions related to the restricted frequency bands apply:

- a. The transmit frequency, including fundamental components of modulation, of license-exempt radio apparatus shall not fall within the restricted frequency bands listed in table 7 except for apparatus compliant with RSS-287.
- b. Unwanted emissions that fall into restricted frequency bands listed in table 7 shall comply with the limits specified in table 5 and table 6.
- c. Unwanted emissions that do not fall within the restricted frequency bands listed in table 7 shall comply either with the limits specified in the applicable RSS or with those specified in table 5 and table 6.



Table 5 – General field strength limits at frequencies above 30 MHz


Frequency (MHz)	Field strength (µV/m at 3 m)
30 – 88	100
88 – 216	150
216 – 960	200
Above 960	500

Table 6 – General field strength limits at frequencies below 30 MHz

Frequency	Magnetic field strength (H-Field) (µA/m)	Measurement distance (m)
9 - 490 kHz ^{Note 1}	6.37/F (F in kHz)	300
490 - 1705 kHz	63.7/F (F in kHz)	30
1.705 - 30 MHz	0.08	30


Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

EUT Setup**9 kHz-30MHz:****30MHz-1GHz:**

Above 1 GHz:

The setup of EUT is according with per ANSI C63.10-2020 measurement procedure. The specification used was with the FCC 15.209, FCC 15.407, RSS-247 and RSS-Gen limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

Unwanted emissions fall into the band 5250-5350 MHz:**EMI Test Receiver & Spectrum Analyzer Setup**

The system was investigated from 9 kHz to 40 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

9 kHz-1GHz:

Frequency Range	RBW	Video B/W	IF B/W	Measurement	Detector
9 kHz – 150 kHz	/	/	200 Hz	QP	QP
	300 Hz	1 kHz	/	PK	Peak
150 kHz – 30 MHz	/	/	9 kHz	QP	QP
	10 kHz	30 kHz	/	PK	Peak
30 MHz – 1000 MHz	/	/	120 kHz	QP	QP
	100 kHz	300 kHz	/	PK	Peak

1-40GHz:

Pre-scan

Measurement	Duty cycle	RBW	Video B/W	Detector
PK	Any	1MHz	3 MHz	Peak
AV	>98%	1MHz	1 kHz	Peak
	<98%	1MHz	≥1/Ton	Peak

Final measurement for emission identified during pre-scan

Measurement	Duty cycle	RBW	Video B/W	Detector
PK	Any	1MHz	3 MHz	Peak
AV	>98%	1MHz	10 Hz	Peak
	<98%	1MHz	≥1/Ton	Peak

Note: Ton is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

Unwanted emissions fall into the band 5250-5350 MHz:

Frequency Range	RBW	Video B/W	Measurement
5250-5350 MHz	(1%-5%)* 99% Bandwidth	3*RBW	Peak

Note: The limit was calculated by attenuated below the channel power by at least 26 dB per RSS-247 §6.2.1.2

Test Procedure

Radiated Spurious Emission

During the radiated emission test, the adapter was connected to the AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all the installation combinations.

All final data was recorded in Quasi-peak detection mode except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz, average detection modes for frequency bands 9–90 kHz and 110–490 kHz, peak and average detection modes for frequencies above 1 GHz.

For 9 kHz-30MHz, the report shall list the six emissions with the smallest margin relative to the limit, for each of the three antenna orientations (parallel, perpendicular, and ground-parallel) unless the margin is greater than 20 dB.

According to ANSI C63.10-2020,9.2.1: For field strength measurements made at other than the distance specified by the limit, extrapolate the measured field strength to the field strength at the distance specified by the limit using an inverse distance correction factor (20 dB/decade of distance)

$$E_{\text{SpecLimit}} = E_{\text{Meas}} + 20 \log \left(\frac{d_{\text{Meas}}}{d_{\text{SpecLimit}}} \right)$$

where

$E_{\text{SpecLimit}}$	is the field strength of the emission at the distance specified by the limit, in dBμV/m
E_{Meas}	is the field strength of the emission at the measurement distance, in dBμV/m
d_{Meas}	is the measurement distance, in m
$d_{\text{SpecLimit}}$	is the distance specified by the limit, in m

So the extrapolation factor of 1m is $20 \cdot \log(1.5/3) = -6.0$ dB, for 18-40GHz range, the limit of 1.5m distance was added by 6.0dB from limit of 3m to compared with the result measurement at 1.5m distance.

Factor & Over Limit/Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned} \text{Over Limit} &= \text{Level} - \text{Limit}; \text{Margin} = \text{Limit} - \text{Corrected Amplitude} \\ \text{Level} / \text{Corrected Amplitude} &= \text{Read Level} + \text{Factor} \end{aligned}$$

Emission Bandwidth & 99% Occupied Bandwidth

Applicable Standard

According to FCC §15.407(a) (13), the maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band are made over a reference bandwidth of 500 kHz or the 26 dB emission bandwidth of the device, whichever is less. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

According to FCC §15.407(e), Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

According to RSS-247 § 6.2.4.2, For equipment operating in the band 5725-5850 MHz, the minimum 6 dB bandwidth shall be at least 500 kHz.

According to RSS-Gen § 6.7, the occupied bandwidth or the “99% emission bandwidth” is defined as the frequency range between two points, one above and the other below the carrier frequency, within which 99% of the total transmitted power of the fundamental transmitted emission is contained. The occupied bandwidth shall be reported for all equipment in addition to the specified bandwidth required in the applicable RSSs.

In some cases, the “x dB bandwidth” is required, which is defined as the frequency range between two points, one at the lowest frequency below and one at the highest frequency above the carrier frequency, at which the maximum power level of the transmitted emission is attenuated x dB below the maximum in-band power level of the modulated signal, where the two points are on the outskirts of the in-band emission.

The following conditions shall be observed for measuring the occupied bandwidth and x dB bandwidth:

- The transmitter shall be operated at its maximum carrier power measured under normal test conditions.
- The span of the spectrum analyzer shall be set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency, but small enough to avoid having other emissions (e.g. on adjacent channels) within the span.
- The detector of the spectrum analyzer shall be set to “Sample”. However, a peak, or peak hold, may be used in place of the sampling detector since this usually produces a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold (or “Max Hold”) may be necessary to determine the occupied / x dB bandwidth if the device is not transmitting continuously.
- The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the actual occupied / x dB bandwidth and the video bandwidth (VBW) shall not be smaller than three times the RBW value. Video averaging is not permitted.

Note: It may be necessary to repeat the measurement a few times until the RBW and VBW are in compliance with the above requirement.

For the 99% emission bandwidth, the trace data points are recovered and directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached, and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded. The difference between the two recorded frequencies is the occupied bandwidth (or the 99% emission bandwidth).

Test Procedure

According to ANSI C63.10-2020 Section 12.5.1 & 12.5.2 & 12.5.3

12.5.1 Emission bandwidth for the band 5.725 GHz to 5.85 GHz

The following procedure shall be used for measuring this bandwidth:

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max-hold.
- e) Sweep = No faster than coupled (auto) time.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

12.5.2 Emission bandwidth for all other bands

The procedure for this method is as follows:

- a) Set RBW = shall be in the range of 1% to 5% of the emission bandwidth.
- b) Set the VBW > RBW.
- c) Detector = peak.
- d) Trace mode = max-hold.
- e) Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the instrument. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is in the range of 1% to 5%.

12.5.3 Occupied bandwidth

See 6.9.3 for the measurement procedure for OBW.


The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth:

- a) The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be at least three times the RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (\text{OBW}/\text{RBW})]$ below the reference level. Specific guidance is given in 4.1.6.2.
- d) Step a) through step c) might require iteration to adjust within the specified range.
- e) Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max-hold mode (until the trace stabilizes) shall be used.

f) Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.

g) If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.

h) The occupied bandwidth shall be reported by providing spectral plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).



Note: Offset (10.5dB) = Attenuator (10dB) + Cable loss (0.5dB)

Transmitter Output Power

Applicable Standard

According to FCC §15.407(a)

For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple colocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

According to RSS-247 §6.2:

Frequency band 5150-5250 MHz

For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed 30 mW or $1.76 + 10 \log 10B$, dBm, whichever is less. Devices shall implement transmitter power control (TPC) in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.

For other devices, the maximum e.i.r.p. shall not exceed 200 mW or $10 + 10 \log 10B$, dBm, whichever power is less. B is the 99% emission bandwidth in megahertz. The e.i.r.p. spectral density shall not exceed 10 dBm in any 1.0 MHz band.

Frequency band 5250-5350 MHz

6.2.2.1(a) The maximum conducted output power shall not exceed 250 mW or $11 + 10 \log_{10} B$, dBm, whichever is less. The power spectral density shall not exceed 11 dBm in any 1.0 MHz band;

6.2.2.1(b) The maximum e.i.r.p. shall not exceed 1.0 W or $17 + 10 \log_{10} B$, dBm, whichever is less. B is the 99% emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

Frequency band 5470-5600 MHz and 5650-5725MHz

6.2.3.1 The maximum conducted output power shall not exceed 250 mW or $11 + 10 \log_{10} B$, dBm, whichever is less. The power spectral density shall not exceed 11 dBm in any 1.0 MHz band.

The maximum e.i.r.p. shall not exceed 1.0 W or $17 + 10 \log_{10} B$, dBm, whichever is less. B is the 99% emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.


Frequency band 5725-5850 MHz

6.2.4.2 The maximum conducted output power shall not exceed 1 W. The output power spectral density shall not exceed 30 dBm in any 500 kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the output power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed point-to-point operations exclude the use of point-to-multipointFootnote3 systems, omnidirectional applications and multiple collocated transmitters transmitting the same information.

Test Procedure

According to ANSI C63.10-2020 Section 12.4.3.2 Method PM-G

- a. Place the EUT on a bench and set it in transmitting mode.
- b. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.



Note 1: A short RF cable with low cable loss connected to the EUT antenna port, which was provided by client or lab, the cable loss was add with offset into test equipment, the total offset consists of attenuator and/or RF cable and/or power splitter loss

Note 2: Offset (10.5dB) = Attenuator (10dB) + Cable loss (0.5dB)

Power Spectral Density

According to FCC §15.407(a)

For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple colocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

According to RSS-247 §6.2:

Frequency band 5150-5250 MHz

For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed 30 mW or $1.76 + 10 \log 10B$, dBm, whichever is less. Devices shall implement transmitter power control (TPC) in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.

For other devices, the maximum e.i.r.p. shall not exceed 200 mW or $10 + 10 \log 10B$, dBm, whichever power is less. B is the 99% emission bandwidth in megahertz. The e.i.r.p. spectral density shall not exceed 10 dBm in any 1.0 MHz band.

Frequency band 5250-5350 MHz

6.2.2.1(a) The maximum conducted output power shall not exceed 250 mW or $11 + 10 \log 10B$, dBm, whichever is less. The power spectral density shall not exceed 11 dBm in any 1.0 MHz band;

Frequency band 5470-5600 MHz and 5650-5725MHz


6.2.3.1 The maximum conducted output power shall not exceed 250 mW or $11 + 10 \log_{10} B$, dBm, whichever is less. The power spectral density shall not exceed 11 dBm in any 1.0 MHz band.

Frequency band 5725-5850 MHz

6.2.4.2 The maximum conducted output power shall not exceed 1 W. The output power spectral density shall not exceed 30 dBm in any 500 kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the output power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed point-to-point operations exclude the use of point-to-multipointFootnote3 systems, omnidirectional applications and multiple collocated transmitters transmitting the same information.

Test Procedure

According to ANSI C63.10-2020 Clause 12.6 Method SA-2 should be applied



Note 1: A short RF cable with low cable loss connected to the EUT antenna port, which was provided by client or lab, the cable loss was add with offset into test equipment, the total offset consists of attenuator and/or RF cable and/or power splitter loss

Note 2: Offset (10.5dB) = Attenuator (10dB) + Cable loss (0.5dB)

Additional Requirements

Applicable Standard

According to RSS-247 Clause 6.4 Additional requirement

The following requirements shall apply:

- a. The device shall automatically discontinue transmission in cases of absence of information to transmit, or operational failure. A description on how this is done shall accompany the application for equipment certification. Note that this is not intended to prohibit transmission of control or signalling information or the use of repetitive codes where required by the technology.
- b. All LE-LAN devices must contain security features to protect against modification of software by unauthorized parties.

Manufacturers must implement security features in any digitally modulated devices capable of operating in any of the frequency ranges within the 5 GHz band, so that third parties are not able to reprogram the device to operate outside the parameters for which the device was certified. The software must prevent the user from operating the transmitter with operating frequencies, output power, modulation types or other radio frequency parameters outside those that were approved for the device. Manufacturers may use various means, including the use of a private network that allows only authenticated users to download software, electronic signatures in software or coding in hardware that is decoded by software to verify that new software can be legally loaded into a device to meet these requirements and must describe the methods in their application for equipment certification.

Manufacturers must take steps to ensure that DFS functionality cannot be disabled by the operator of the LE-LAN device.

- c. The user manual for LE-LAN devices shall contain instructions related to the restrictions mentioned in the above sections, namely that:
 - i. the device for operation in the band 5150–5250 MHz is only for indoor use to reduce the potential for harmful interference to co-channel mobile satellite systems;
 - ii. for devices with detachable antenna(s), the maximum antenna gain permitted for devices in the bands 5250-5350 MHz and 5470-5725 MHz shall be such that the equipment still complies with the e.i.r.p. limit;
 - iii. for devices with detachable antenna(s), the maximum antenna gain permitted for devices in the band 5725-5850 MHz shall be such that the equipment still complies with the e.i.r.p. limits as appropriate; and
 - iv. where applicable, antenna type(s), antenna models(s), and worst-case tilt angle(s) necessary to remain compliant with the e.i.r.p. elevation mask requirement set forth in section 6.2.2.3 shall be clearly indicated.

Result**Pass**

RSS-247 Clause 6.4 a):

The device shall automatically discontinue transmission in cases of absence of information to transmit, or operation failure. Please refer to declaration.

RSS-247 Clause 6.4 b):

The device must contain security features to protect against modification of software by unauthorized parties. Please refer to declaration.

RSS-247 Clause 6.4 c):

1. Compliant, please refer to the User Manual.
2. Compliant, The device operates on 5250-5350MHz/5470-5600MHz&5650-5725MHz, the EIRP meet the requirement.
3. Compliant, The device operates on 5725-5850MHz, the EIRP meet the requirement.
4. Compliant, please refer to the antenna information and output power section.


Duty Cycle

Test Procedure

According to ANSI C63.10-2020 Section 12.2

Measurements of duty cycle and transmission duration shall be performed using one of the following techniques:

- a) A diode detector and an oscilloscope that together have a sufficiently short response time to permit accurate measurements of the ON and OFF times of the transmitted signal.
- b) The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:
 - 1) Set the center frequency of the instrument to the center frequency of the transmission.
 - 2) Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.
 - 3) Set $VBW \geq RBW$. Set detector = peak or average.
 - 4) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if $T \leq 16.7 \mu s$.)



Note: Offset (10.5dB) = Attenuator (10dB) + Cable loss (0.5dB)

ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location:

This radio transmitter [enter the device's ISCED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

Antenna Connector Construction

The EUT has one internal antenna arrangement, which was permanently attached, fulfill the requirement of this section. Please refer to the EUT photos.

Antenna Type	Antenna Gain [#]	Impedance	Frequency Range
PCB	4.02	50Ω	5150-5250MHz
	4.79	50Ω	5250-5350MHz
	5.20	50Ω	5470-5725MHz
	5.56	50Ω	5725-5850MHz


Result: Compliant

TEST DATA AND RESULTS

Conducted Emissions

Temperature (°C)	26.2	Relative Humidity (%)	60
ATM Pressure (kPa)	100.7	Test engineer	Macy.shi
Test date	2025.10.18		
EUT operation mode	Transmitting (Maximum output power mode, 802.11ax20 5320MHz		
Note:	Worst case is POE		

AC 120V 60 Hz, Line



Condition: Line


Project : 2501X19230E-RF

tester : Macy.shi Note:5G WIFI Transmitting

Setting : RBW:9kHz

	Freq	Read Level	LISN Level	Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.151	22.48	42.20	9.70	10.02	55.96	-13.76	Average
2	0.151	35.32	55.04	9.70	10.02	65.96	-10.92	QP
3	0.419	26.37	46.18	9.78	10.03	47.47	-1.29	Average
4	0.419	32.94	52.75	9.78	10.03	57.47	-4.72	QP
5	0.440	25.92	45.74	9.79	10.03	47.06	-1.32	Average
6	0.440	32.75	52.57	9.79	10.03	57.06	-4.49	QP
7	4.001	7.17	27.28	9.90	10.21	46.00	-18.72	Average
8	4.001	20.74	40.85	9.90	10.21	56.00	-15.15	QP
9	16.744	19.05	39.35	9.90	10.40	50.00	-10.65	Average
10	16.744	24.34	44.64	9.90	10.40	60.00	-15.36	QP
11	29.137	17.31	37.74	9.90	10.53	50.00	-12.26	Average
12	29.137	23.58	44.01	9.90	10.53	60.00	-15.99	QP

AC 120V 60 Hz, Neutral



Condition: neutral

Project : 2501X19230E-RF

tester : Macy.shi Note:5G WIFI Transmitting

Setting : RBW:9kHz


	Freq	Read Level	Level	LISN Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.153	20.36	39.98	9.60	10.02	55.83	-15.85	Average
2	0.153	30.99	50.61	9.60	10.02	65.83	-15.22	QP
3	0.429	26.24	45.87	9.60	10.03	47.27	-1.40	Average
4	0.429	32.77	52.40	9.60	10.03	57.27	-4.87	QP
5	0.451	24.44	44.07	9.60	10.03	46.86	-2.79	Average
6	0.451	30.34	49.97	9.60	10.03	56.86	-6.89	QP
7	4.036	8.50	28.31	9.60	10.21	46.00	-17.69	Average
8	4.036	20.91	40.72	9.60	10.21	56.00	-15.28	QP
9	20.135	19.69	39.82	9.70	10.43	50.00	-10.18	Average
10	20.135	24.88	45.01	9.70	10.43	60.00	-14.99	QP
11	27.563	15.03	35.24	9.70	10.51	50.00	-14.76	Average
12	27.563	22.42	42.63	9.70	10.51	60.00	-17.37	QP

Undesirable Emission

Temperature (°C)	24.2&24.8-25.1	Relative Humidity (%)	51&50-52
ATM Pressure (kPa):	100.9&100.8-101.2	Test engineer:	Anson Su&Zenos Qiao, Wing K Ji
Test date:	Below 1GHz:2025.10.16 Above 1GHz: 2025.10.28-2025.10.29		
EUT operation mode:	Below 1GHz: Transmitting (Maximum output power mode, 802.11ax20 5320MHz Above 1GHz: Transmitting		
Note:	1. For the radiated spurious emission below 30MHz, only the worst case (parallel) was recorded. 2. For the radiated spurious emission below 1GHz, When the test result of peak was less than the limit of QP/Average more than 6dB, just peak value was recorded. 3. After pre-scan in the X, Y and Z axes of orientation, the worst case z-axis of orientation were recorded. 4. The spurious emission from 9 kHz-30MHz of IC RSS-GEN standard, the unit of final result on the test plots are dBμV/m, so the limit should be added by 51,5 dB from dBμA/m to dBμV/m. 5. Worst case is Adapter 1.		

Below 1GHz:


9kHz-150kHz



Site : Chamber A
Condition : 3m
Project Number : 2501X19230E-RF
Test Mode : 5G WIFI Transmitting
Detector: Peak RBW/VBW: 0.3/1kHz
Tester : Anson Su

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.011	32.02	24.62	56.64	126.39	-69.75	Peak
2	0.015	31.38	27.16	58.54	124.19	-65.65	Peak
3	0.026	29.27	29.54	58.81	119.33	-60.52	Peak
4	0.046	26.81	28.28	55.09	114.33	-59.24	Peak
5	0.073	24.08	27.19	51.27	110.32	-59.05	Peak
6	0.129	20.31	19.28	39.59	105.41	-65.82	Peak


150kHz-30MHz



Site : Chamber A
Condition : 3m
Project Number : 2501X19230E-RF
Test Mode : 5G WIFI Transmitting
Detector: Peak RBW/VBW: 10/30kHz
Tester : Anson Su

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.320	9.82	38.05	47.87	97.51	-49.64	Peak
2	0.653	4.51	37.89	42.40	71.25	-28.85	Peak
3	1.172	0.72	40.36	41.08	66.07	-24.99	Peak
4	2.338	-1.79	37.28	35.49	69.54	-34.05	Peak
5	3.509	-2.43	34.28	31.85	69.54	-37.69	Peak
6	24.303	-3.13	55.73	52.60	69.54	-16.94	Peak


30MHz-1GHz_Horizontal



Site : Chamber A
Condition : 3m Horizontal
Project Number : 2501X19230E-RF
Test Mode : 5G WIFI Transmitting
Detector: Peak RBW/VBW: 100/300kHz
Tester : Anson Su

	Freq Factor		Read Level		Limit	Over	Remark
	MHz	dB/m	dBuV	dBuV/m	Line	Limit	
1	39.71	-12.17	46.14	33.97	40.00	-6.03	Peak
2	40.92	-13.02	46.11	33.09	40.00	-6.91	QP
3	41.90	-13.79	46.80	33.01	40.00	-6.99	QP
4	59.68	-18.15	51.14	32.99	40.00	-7.01	Peak
5	159.57	-12.72	45.94	33.22	43.50	-10.28	Peak
6	275.52	-11.33	50.45	39.12	46.00	-6.88	Peak

30MHz-1GHz_Vertical



Site : Chamber A
Condition : 3m Vertical
Project Number : 2501X19230E-RF
Test Mode : 5G WIFI Transmitting
Detector: Peak RBW/VBW: 100/300kHz
Tester : Anson Su

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	30.03	-5.97	45.29	39.32	40.00	-0.68	QP
2	30.88	-6.41	45.03	38.62	40.00	-1.38	QP
3	31.61	-6.84	43.80	36.96	40.00	-3.04	QP
4	33.46	-7.90	47.30	39.40	40.00	-0.60	QP
5	34.35	-8.49	44.15	35.66	40.00	-4.34	QP
6	36.40	-9.80	45.03	35.23	40.00	-4.77	QP
7	37.75	-10.80	47.60	36.80	40.00	-3.20	QP
8	38.84	-11.57	49.41	37.84	40.00	-2.16	QP
9	39.49	-12.01	51.00	38.99	40.00	-1.01	QP
10	40.36	-12.62	51.99	39.37	40.00	-0.63	QP
11	41.57	-13.52	52.05	38.53	40.00	-1.47	QP
12	42.14	-13.96	51.59	37.63	40.00	-2.37	QP
13	43.45	-14.84	51.02	36.18	40.00	-3.82	QP

Above 1GHz:**5150-5250 MHz**

Frequency (MHz)	Reading (dBμV)	PK/Ave	Polar (H/V)	Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
802.11a							
Low Channel							
10360	50.16	PK	H	2.53	52.69	68.2	-15.51
10360	49.5	PK	V	2.53	52.03	68.2	-16.17
Middle Channel							
10400	51.26	PK	H	2.55	53.81	68.2	-14.39
10400	50.6	PK	V	2.55	53.15	68.2	-15.05
High Channel							
10480	49.93	PK	H	2.25	52.18	68.2	-16.02
10480	49.27	PK	V	2.25	51.52	68.2	-16.68
802.11ac20							
Low Channel							
10360	49.3	PK	H	2.53	51.83	68.2	-16.37
10360	49.79	PK	V	2.53	52.32	68.2	-15.88
Middle Channel							
10400	50.4	PK	H	2.55	52.95	68.2	-15.25
10400	50.89	PK	V	2.55	53.44	68.2	-14.76
High Channel							
10480	49.07	PK	H	2.25	51.32	68.2	-16.88
10480	49.56	PK	V	2.25	51.81	68.2	-16.39
802.11ac40							
Low Channel							
10380	48.54	PK	H	2.54	51.08	68.2	-17.12
10380	49.03	PK	V	2.54	51.57	68.2	-16.63
High Channel							
10460	49.54	PK	H	2.32	51.86	68.2	-16.34
10460	50.03	PK	V	2.32	52.35	68.2	-15.85
802.11ax20							
Low Channel							
10360	49.36	PK	H	2.53	51.89	68.2	-16.31
10360	49.53	PK	V	2.53	52.06	68.2	-16.14
Middle Channel							
10400	50.46	PK	H	2.55	53.01	68.2	-15.19
10400	50.63	PK	V	2.55	53.18	68.2	-15.02
High Channel							
10480	49.13	PK	H	2.25	51.38	68.2	-16.82
10480	49.3	PK	V	2.25	51.55	68.2	-16.65

Frequency (MHz)	Reading (dB μ V)	PK/Ave	Polar (H/V)	Factor (dB/m)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
802.11ax40							
Low Channel							
10380	49.18	PK	H	2.54	51.72	68.2	-16.48
10380	48.49	PK	V	2.54	51.03	68.2	-17.17
High Channel							
10460	50.18	PK	H	2.32	52.5	68.2	-15.7
10460	49.49	PK	V	2.32	51.81	68.2	-16.39

5250-5350MHz

Frequency (MHz)	Reading (dB μ V)	PK/Ave	Polar (H/V)	Factor (dB/m)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
802.11a							
Low Channel							
10520	50.02	PK	H	2.18	52.2	68.2	-16
10520	49.68	PK	V	2.18	51.86	68.2	-16.34
Middle Channel							
10560	49.31	PK	H	2.18	51.49	68.2	-16.71
10560	48.97	PK	V	2.18	51.15	68.2	-17.05
High Channel							
10640	49.27	PK	H	2.59	51.86	74	-22.14
10640	48.93	PK	V	2.59	51.52	74	-22.48
802.11ac20							
Low Channel							
10520	50.19	PK	H	2.18	52.37	68.2	-15.83
10520	50.24	PK	V	2.18	52.42	68.2	-15.78
Middle Channel							
10560	49.48	PK	H	2.18	51.66	68.2	-16.54
10560	49.53	PK	V	2.18	51.71	68.2	-16.49
High Channel							
10640	49.44	PK	H	2.59	52.03	74	-21.97
10640	49.49	PK	V	2.59	52.08	74	-21.92
802.11ac40							
Low Channel							
10540	50.81	PK	H	2.18	52.99	68.2	-15.21
10540	50.98	PK	V	2.18	53.16	68.2	-15.04
High Channel							
10620	49.54	PK	H	2.38	51.92	74	-22.08
10620	49.71	PK	V	2.38	52.09	74	-21.91

Frequency (MHz)	Reading (dB μ V)	PK/Ave	Polar (H/V)	Factor (dB/m)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
802.11ax20							
Low Channel							
10520	49.65	PK	H	2.18	51.83	68.2	-16.37
10520	49.34	PK	V	2.18	51.52	68.2	-16.68
Middle Channel							
10560	48.94	PK	H	2.18	51.12	68.2	-17.08
10560	48.63	PK	V	2.18	50.81	68.2	-17.39
High Channel							
10640	48.9	PK	H	2.59	51.49	74	-22.51
10640	48.59	PK	V	2.59	51.18	74	-22.82
802.11ax40							
Low Channel							
10540	50.33	PK	H	2.18	52.51	68.2	-15.69
10540	50.17	PK	V	2.18	52.35	68.2	-15.85
High Channel							
10620	49.06	PK	H	2.38	51.44	74	-22.56
10620	48.9	PK	V	2.38	51.28	74	-22.72

5470-5725MHz

Frequency (MHz)	Reading (dB μ V)	PK/Ave	Polar (H/V)	Factor (dB/m)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
802.11a							
Low Channel							
11000	48.77	PK	H	4.29	53.06	74	-20.94
11000	48.52	PK	V	4.29	52.81	74	-21.19
Middle Channel							
11160	49.61	PK	H	3.5	53.11	74	-20.89
11160	49.36	PK	V	3.5	52.86	74	-21.14
High Channel							
11400	50.37	PK	H	3.32	53.69	74	-20.31
11400	50.12	PK	V	3.32	53.44	74	-20.56
Cross Channel							
11440	50.19	PK	H	3.42	53.61	74	-20.39
11440	50.03	PK	V	3.42	53.45	74	-20.55

Frequency (MHz)	Reading (dBμV)	PK/Ave	Polar (H/V)	Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
802.11ac20							
Low Channel							
11000	48.51	PK	H	4.29	52.8	74	-21.2
11000	48.83	PK	V	4.29	53.12	74	-20.88
Middle Channel							
11160	49.89	PK	H	3.5	53.39	74	-20.61
11160	49.04	PK	V	3.5	52.54	74	-21.46
High Channel							
11400	50.11	PK	H	3.32	53.43	74	-20.57
11400	50.43	PK	V	3.32	53.75	74	-20.25
Cross Channel							
11440	49.92	PK	H	3.42	53.34	74	-20.66
11440	50.13	PK	V	3.42	53.55	74	-20.45
802.11ac40							
Low Channel							
11020	48.75	PK	H	4.1	52.85	74	-21.15
11020	49.07	PK	V	4.1	53.17	74	-20.83
Middle Channel							
11100	49.25	PK	H	3.34	52.59	74	-21.41
11100	49.57	PK	V	3.34	52.91	74	-21.09
High Channel							
11340	48.52	PK	H	3.46	51.98	74	-22.02
11340	48.84	PK	V	3.46	52.3	74	-21.7
Cross Channel							
11420	48.22	PK	H	3.37	51.59	74	-22.41
11420	48.51	PK	V	3.37	51.88	74	-22.12
802.11ax20							
Low Channel							
11000	48.86	PK	H	4.29	53.15	74	-20.85
11000	48.58	PK	V	4.29	52.87	74	-21.13
Middle Channel							
11160	49.7	PK	H	3.5	53.2	74	-20.8
11160	49.42	PK	V	3.5	52.92	74	-21.08
High Channel							
11400	50.46	PK	H	3.32	53.78	74	-20.22
11400	50.18	PK	V	3.32	53.5	74	-20.5
Cross Channel							
11440	50.23	PK	H	3.42	53.65	74	-20.35
11440	50.03	PK	V	3.42	53.45	74	-20.55

Frequency (MHz)	Reading (dBμV)	PK/Ave	Polar (H/V)	Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
802.11ax40							
Low Channel							
11020	48.7	PK	H	4.1	52.8	74	-21.2
11020	48.53	PK	V	4.1	52.63	74	-21.37
Middle Channel							
11100	49.2	PK	H	3.34	52.54	74	-21.46
11100	49.03	PK	V	3.34	52.37	74	-21.63
High Channel							
11340	48.47	PK	H	3.46	51.93	74	-22.07
11340	48.3	PK	V	3.46	51.76	74	-22.24
Cross Channel							
11420	48.16	PK	H	3.37	51.53	74	-22.47
11420	48.09	PK	V	3.37	51.46	74	-22.54

5725-5850MHz

Frequency (MHz)	Reading (dBμV)	PK/Ave	Polar (H/V)	Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
802.11a							
Low Channel							
11490	48.2	PK	H	3.54	51.74	74	-22.26
11490	47.5	PK	V	3.54	51.04	74	-22.96
Middle Channel							
11570	49.27	PK	H	3.29	52.56	74	-21.44
11570	48.57	PK	V	3.29	51.86	74	-22.14
High Channel							
11650	50.16	PK	H	3.44	53.6	74	-20.4
11650	49.46	PK	V	3.44	52.9	74	-21.1
802.11ac20							
Low Channel							
11490	47.81	PK	H	3.54	51.35	74	-22.65
11490	47.67	PK	V	3.54	51.21	74	-22.79
Middle Channel							
11570	48.88	PK	H	3.29	52.17	74	-21.83
11570	48.74	PK	V	3.29	52.03	74	-21.97
High Channel							
11650	49.77	PK	H	3.44	53.21	74	-20.79
11650	49.63	PK	V	3.44	53.07	74	-20.93

Frequency (MHz)	Reading (dBμV)	PK/Ave	Polar (H/V)	Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
802.11ac40							
Low Channel							
11510	48.58	PK	H	3.53	52.11	74	-21.89
11510	48.44	PK	V	3.53	51.97	74	-22.03
High Channel							
11590	49.32	PK	H	3.21	52.53	74	-21.47
11590	49.18	PK	V	3.21	52.39	74	-21.61
802.11ax20							
Low Channel							
11490	47.63	PK	H	3.54	51.17	74	-22.83
11490	48.31	PK	V	3.54	51.85	74	-22.15
Middle Channel							
11570	48.7	PK	H	3.29	51.99	74	-22.01
11570	49.38	PK	V	3.29	52.67	74	-21.33
High Channel							
11650	49.59	PK	H	3.44	53.03	74	-20.97
11650	50.27	PK	V	3.44	53.71	74	-20.29
802.11ax40							
Low Channel							
11510	48.4	PK	H	3.53	51.93	74	-22.07
11510	49.08	PK	V	3.53	52.61	74	-21.39
High Channel							
11590	49.14	PK	H	3.21	52.35	74	-21.65
11590	49.82	PK	V	3.21	53.03	74	-20.97

Note:

Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Factor + Reading


Margin = Corrected. Amplitude - Limit

The other spurious emission which is in the noise floor level was not recorded.

The test result of peak was less than the limit of average, so just peak values were recorded.

Test plots:**Band Edge**


Left Band edge_Horizontal_Peak_802.11a_5180MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_Band1_A_5180

		Read		Limit	Over	Remark
Freq Factor		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5083.083	7.68	50.04	57.72	74.00	-16.28 Peak
2	5150.000	7.47	48.13	55.60	74.00	-18.40 Peak


Left Band edge_Horizontal_Average_802.11a_5180MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_Band1_A_5180

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4933.125	7.38	37.26	44.64	54.00	-9.36 Average
2	5150.000	7.47	36.58	44.05	54.00	-9.95 Average


Left Band edge_Vertical_Peak_802.11a_5180MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_Band1_A_5180

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5091.553	7.69	50.20	57.89	74.00	-16.11 Peak
2	5150.000	7.47	47.84	55.31	74.00	-18.69 Peak


Left Band edge_Vertical_Average_802.11a_5180MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_Band1_A_5180

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	4938.611	7.38	37.14	44.52	54.00	-9.48 Average
2	5150.000	7.47	36.45	43.92	54.00	-10.08 Average


Right Band edge_Horizontal_Peak_802.11a_5240MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_Band1_A_5240

Freq Factor		Read Level		Limit	Over	Remark
				Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5350.000	8.37	48.69	57.06	74.00	-16.94 Peak
2	5446.350	8.78	50.44	59.22	74.00	-14.78 Peak


Right Band edge_Horizontal_Average_802.11a_5240MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_Band1_A_5240

Freq Factor		Read Level		Limit	Over	Remark
				Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5350.000	8.37	36.42	44.79	54.00	-9.21 Average
2	5458.987	8.89	36.73	45.62	54.00	-8.38 Average


Right Band edge_Vertical_Peak_802.11a_5240MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_Band1_A_5240

Freq Factor		Read Level		Limit	Over	Remark
				Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5350.000	8.37	48.52	56.89	74.00	-17.11 Peak
2	5444.700	8.79	50.59	59.38	74.00	-14.62 Peak


Right Band edge_Vertical_Average_802.11a_5240MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_Band1_A_5240

Freq Factor		Read Level		Limit	Over	Remark
				Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5350.000	8.37	36.40	44.77	54.00	-9.23 Average
2	5459.850	8.90	36.75	45.65	54.00	-8.35 Average


Left Band edge_Horizontal_Peak_802.11ac20_5180MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_Band1_AC20_5180

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 4964.502	7.44	50.82	58.26	74.00	-15.74	Peak
2 5150.000	7.47	48.46	55.93	74.00	-18.07	Peak


Left Band edge_Horizontal_Average_802.11ac20_5180MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_Band1_AC20_5180

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4934.087	7.38	37.64	45.02	54.00	-8.98 Average
2	5150.000	7.47	36.78	44.25	54.00	-9.75 Average


Left Band edge_Vertical_Peak_802.11ac20_5180MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_Band1_AC20_5180

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	4979.325	7.53	50.78	58.31	74.00	-15.69 Peak
2	5150.000	7.47	47.76	55.23	74.00	-18.77 Peak


Left Band edge_Vertical_Average_802.11ac20_5180MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_Band1_AC20_5180

Freq Factor		Read		Limit	Over	Remark
MHz	dB/m	Level	Level	Line	Limit	
		dBuV	dBuV/m	dBuV/m	dB	
1	4938.804	7.38	37.32	44.70	54.00	-9.30 Average
2	5150.000	7.47	36.69	44.16	54.00	-9.84 Average


Right Band edge_Horizontal_Peak_802.11ac20_5240MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_Band1_AC20_5240

Freq Factor		Read Level		Limit	Over	Remark
				Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5350.000	8.37	47.45	55.82	74.00	-18.18 Peak
2	5443.013	8.78	50.37	59.15	74.00	-14.85 Peak


Right Band edge_Horizontal_Average_802.11ac20_5240MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_Band1_AC20_5240

Freq Factor		Read Level		Limit	Over	Remark
				Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5350.000	8.37	36.35	44.72	54.00	-9.28 Average
2	5459.550	8.90	36.77	45.67	54.00	-8.33 Average


Right Band edge_Vertical_Peak_802.11ac20_5240MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_Band1_AC20_5240

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 5350.000	8.37	47.44	55.81	74.00	-18.19	Peak
2 5421.450	8.72	50.56	59.28	74.00	-14.72	Peak


Right Band edge_Vertical_Average_802.11ac20_5240MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_Band1_AC20_5240

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5350.000	8.37	36.44	44.81	54.00	-9.19 Average
2	5459.250	8.90	36.78	45.68	54.00	-8.32 Average


Left Band edge_Horizontal_Peak_802.11ac40_5190MHz



Condition : Horizontal
 Project No. : 2501X19230E-RF
 Tester : Wing K Ji
 Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
 Note : 5GWiFi_Band1_AC40_5190

Freq Factor		Read		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4855.163	7.12	50.42	57.54	74.00	-16.46 Peak
2	5150.000	7.47	47.43	54.90	74.00	-19.10 Peak


Left Band edge_Horizontal_Average_802.11ac40_5190MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_Band1_AC40_5190

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5052.186	7.74	36.59	44.33	54.00	-9.67 Average
2	5150.000	7.47	36.49	43.96	54.00	-10.04 Average


Left Band edge_Vertical_Peak_802.11ac40_5190MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_Band1_AC40_5190

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5075.768	7.68	49.82	57.50	74.00	-16.50 Peak
2	5150.000	7.47	47.90	55.37	74.00	-18.63 Peak


Left Band edge_Vertical_Average_802.11ac40_5190MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_Band1_AC40_5190

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5056.614	7.72	36.52	44.24	54.00	-9.76	Average
2	5150.000	7.47	36.47	43.94	54.00	-10.06	Average


Right Band edge_Horizontal_Peak_802.11ac40_5230MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_Band1_AC40_5230

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5350.000	8.37	48.30	56.67	74.00	-17.33 Peak
2	5458.875	8.87	50.12	58.99	74.00	-15.01 Peak


Right Band edge_Horizontal_Average_802.11ac40_5230MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_Band1_AC40_5230

Freq Factor		Read Level		Limit	Over	Remark
				Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5350.000	8.37	36.27	44.64	54.00	-9.36 Average
2	5459.737	8.90	36.81	45.71	54.00	-8.29 Average


Right Band edge_Vertical_Peak_802.11ac40_5230MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_Band1_AC40_5230

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5350.000	8.37	48.05	56.42	74.00	-17.58 Peak
2	5428.313	8.65	50.42	59.07	74.00	-14.93 Peak


Right Band edge_Vertical_Average_802.11ac40_5230MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_Band1_AC40_5230

Freq Factor		Read Level		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5350.000	8.37	36.41	44.78	54.00	-9.22 Average
2	5459.850	8.90	36.87	45.77	54.00	-8.23 Average


Left Band edge_Horizontal_Peak_802.11ax20_5180MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_Band1_AX20_5180

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	4728.401	7.07	50.76	57.83	74.00	-16.17 Peak
2	5150.000	7.47	49.30	56.77	74.00	-17.23 Peak


Left Band edge_Horizontal_Average_802.11ax20_5180MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_Band1_AX20_5180

Freq Factor		Read Level		Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 5147.763	7.46	37.75	45.21	54.00	-8.79	Average
2 5150.000	7.47	36.52	43.99	54.00	-10.01	Average


Left Band edge_Vertical_Peak_802.11ax20_5180MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_Band1_AX20_5180

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	4917.340	7.39	51.63	59.02	74.00	-14.98 Peak
2	5150.000	7.47	48.08	55.55	74.00	-18.45 Peak


Left Band edge_Vertical_Average_802.11ax20_5180MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_Band1_AX20_5180

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	4937.264	7.38	37.69	45.07	54.00	-8.93 Average
2	5150.000	7.47	36.77	44.24	54.00	-9.76 Average


Right Band edge_Horizontal_Peak_802.11ax20_5240MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_Band1_AX20_5240

Freq Factor		Read Level		Limit	Over	Remark
				Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5350.000	8.37	47.45	55.82	74.00	-18.18 Peak
2	5432.513	8.67	50.57	59.24	74.00	-14.76 Peak


Right Band edge_Horizontal_Average_802.11ax20_5240MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_Band1_AX20_5240

Freq Factor		Read Level		Limit	Over	Remark
				Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5350.000	8.37	37.69	46.06	54.00	-7.94 Average
2	5455.950	8.86	38.53	47.39	54.00	-6.61 Average


Right Band edge_Vertical_Peak_802.11ax20_5240MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_Band1_AX20_5240

Freq Factor		Read Level		Limit	Over	Remark
				Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5350.000	8.37	48.03	56.40	74.00	-17.60 Peak
2	5456.925	8.86	50.73	59.59	74.00	-14.41 Peak


Right Band edge_Vertical_Average_802.11ax20_5240MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_Band1_AX20_5240

Freq Factor		Read Level		Limit	Over	Remark
				Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5350.000	8.37	37.46	45.83	54.00	-8.17 Average
2	5450.587	8.79	38.61	47.40	54.00	-6.60 Average


Left Band edge_Horizontal_Peak_802.11ax40_5190MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_Band1_AX40_5190

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5086.740	7.71	50.60	58.31	74.00	-15.69 Peak
2	5150.000	7.47	47.90	55.37	74.00	-18.63 Peak

Left Band edge_Horizontal_Average_802.11ax40_5190MHz



Condition : Horizontal

Project No. : 2501X19230E-RF


Tester : Wing K Ji

Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak

Note : 5GWiFi_Band1_AX40_5190

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5058.058	7.72	36.48	44.20	54.00	-9.80	Average
2	5150.000	7.47	36.63	44.10	54.00	-9.90	Average


Left Band edge_Vertical_Peak_802.11ax40_5190MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_Band1_AX40_5190

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5048.529	7.73	50.23	57.96	74.00	-16.04 Peak
2	5150.000	7.47	48.41	55.88	74.00	-18.12 Peak


Left Band edge_Vertical_Average_802.11ax40_5190MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_Band1_AX40_5190

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5149.303	7.47	36.83	44.30	54.00	-9.70 Average
2	5150.000	7.47	36.51	43.98	54.00	-10.02 Average


Right Band edge_Horizontal_Peak_802.11ax40_5230MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_Band1_AX40_5230

Freq Factor		Read Level		Limit	Over	Remark
				Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5350.000	8.37	49.52	57.89	74.00	-16.11 Peak
2	5459.250	8.90	50.39	59.29	74.00	-14.71 Peak


Right Band edge_Horizontal_Average_802.11ax40_5230MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_Band1_AX40_5230

Freq Factor		Read Level		Limit	Over	Remark
				Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5350.000	8.37	36.32	44.69	54.00	-9.31 Average
2	5458.875	8.87	36.78	45.65	54.00	-8.35 Average


Right Band edge_Vertical_Peak_802.11ax40_5230MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_Band1_AX40_5230

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5350.000	8.37	48.55	56.92	74.00	-17.08 Peak
2	5444.663	8.79	51.03	59.82	74.00	-14.18 Peak


Right Band edge_Vertical_Average_802.11ax40_5230MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_Band1_AX40_5230

Freq Factor		Read Level		Limit	Over	Remark
				Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5350.000	8.37	36.56	44.93	54.00	-9.07 Average
2	5458.350	8.87	36.86	45.73	54.00	-8.27 Average


Left Band edge_Horizontal_Peak_802.11a_5260MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B2_A_5260

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	4896.313	7.38	50.11	57.49	74.00	-16.51 Peak
2	5150.000	7.47	46.86	54.33	74.00	-19.67 Peak


Left Band edge_Horizontal_Average_802.11a_5260MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_B2_A_5260

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5055.156	7.72	36.52	44.24	54.00	-9.76 Average
2	5150.000	7.47	36.55	44.02	54.00	-9.98 Average


Left Band edge_Vertical_Peak_802.11a_5260MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B2_A_5260

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5048.675	7.73	50.25	57.98	74.00	-16.02 Peak
2	5150.000	7.47	47.35	54.82	74.00	-19.18 Peak


Left Band edge_Vertical_Average_802.11a_5260MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_B2_A_5260

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5045.487	7.68	36.63	44.31	54.00	-9.69 Average
2	5150.000	7.47	36.33	43.80	54.00	-10.20 Average


Right Band edge_Horizontal_Peak_802.11a_5320MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B2_A_5320

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5350.000	8.37	47.42	55.79	74.00	-18.21 Peak
2	5456.750	8.86	50.16	59.02	74.00	-14.98 Peak

Right Band edge_Horizontal_Average_802.11a_5320MHz



Condition : Horizontal

Project No. : 2501X19230E-RF


Tester : Wing K Ji

Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak

Note : 5GWiFi_B2_A_5320

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5350.000	8.37	36.65	45.02	54.00	-8.98	Average
2	5457.920	8.87	36.79	45.66	54.00	-8.34	Average


Right Band edge_Vertical_Peak_802.11a_5320MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B2_A_5320

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5350.000	8.37	47.35	55.72	74.00	-18.28 Peak
2	5352.132	8.37	52.48	60.85	74.00	-13.15 Peak


Right Band edge_Vertical_Average_802.11a_5320MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_B2_A_5320

Freq Factor		Read Level		Limit	Over	Remark
				Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5350.000	8.37	36.75	45.12	54.00	-8.88 Average
2	5459.382	8.90	36.77	45.67	54.00	-8.33 Average


Left Band edge_Horizontal_Peak_802.11ac20_5260MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B2_AC20_5260

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	4999.906	7.63	50.27	57.90	74.00	-16.10 Peak
2	5150.000	7.47	48.24	55.71	74.00	-18.29 Peak


Left Band edge_Horizontal_Average_802.11ac20_5260MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_B2_AC20_5260

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5051.862	7.74	36.41	44.15	54.00	-9.85 Average
2	5150.000	7.47	36.55	44.02	54.00	-9.98 Average


Left Band edge_Vertical_Peak_802.11ac20_5260MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B2_AC20_5260

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5147.381	7.46	50.68	58.14	74.00	-15.86 Peak
2	5150.000	7.47	47.90	55.37	74.00	-18.63 Peak


Left Band edge_Vertical_Average_802.11ac20_5260MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_B2_AC20_5260

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5071.413	7.68	36.52	44.20	54.00	-9.80 Average
2	5150.000	7.47	36.26	43.73	54.00	-10.27 Average


Right Band edge_Horizontal_Peak_802.11ac20_5320MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B2_AC20_5320

Freq Factor		Read Level		Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 5350.000	8.37	50.98	59.35	74.00	-14.65	Peak
2 5402.768	8.66	50.81	59.47	74.00	-14.53	Peak


Right Band edge_Horizontal_Average_802.11ac20_5320MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_B2_AC20_5320

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5350.000	8.37	36.78	45.15	54.00	-8.85 Average
2	5453.435	8.83	36.90	45.73	54.00	-8.27 Average


Right Band edge_Vertical_Peak_802.11ac20_5320MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B2_AC20_5320

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5350.000	8.37	48.21	56.58	74.00	-17.42 Peak
2	5398.087	8.62	50.76	59.38	74.00	-14.62 Peak


Right Band edge_Vertical_Average_802.11ac20_5320MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_B2_AC20_5320

Freq Factor		Read Level		Limit	Over	Remark
		Level		Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5350.000	8.37	36.78	45.15	54.00	-8.85 Average
2	5458.115	8.87	36.91	45.78	54.00	-8.22 Average


Left Band edge_Horizontal_Peak_802.11ac40_5270MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B2_AC40_5270

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	4894.825	7.38	50.40	57.78	74.00	-16.22 Peak
2	5150.000	7.47	47.50	54.97	74.00	-19.03 Peak


Left Band edge_Horizontal_Average_802.11ac40_5270MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_B2_AC40_5270

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5053.987	7.73	36.45	44.18	54.00	-9.82 Average
2	5150.000	7.47	36.42	43.89	54.00	-10.11 Average


Left Band edge_Vertical_Peak_802.11ac40_5270MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B2_AC40_5270

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5136.438	7.40	50.31	57.71	74.00	-16.29 Peak
2	5150.000	7.47	49.06	56.53	74.00	-17.47 Peak


Left Band edge_Vertical_Average_802.11ac40_5270MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_B2_AC40_5270

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5049.844	7.75	36.55	44.30	54.00	-9.70 Average
2	5150.000	7.47	36.37	43.84	54.00	-10.16 Average


Right Band edge_Horizontal_Peak_802.11ac40_5310MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B2_AC40_5310

Freq Factor		Read Level		Limit	Over	Remark
				Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5350.000	8.37	49.77	58.14	74.00	-15.86 Peak
2	5350.442	8.37	55.81	64.18	74.00	-9.82 Peak


Right Band edge_Horizontal_Average_802.11ac40_5310MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_B2_AC40_5310

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5350.000	8.37	37.55	45.92	54.00	-8.08 Average
2	5350.638	8.37	37.74	46.11	54.00	-7.89 Average


Right Band edge_Vertical_Peak_802.11ac40_5310MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B2_AC40_5310

Freq Factor		Read Level		Limit	Over	Remark
				Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5350.000	8.37	53.56	61.93	74.00	-12.07 Peak
2	5350.248	8.37	56.44	64.81	74.00	-9.19 Peak


Right Band edge_Vertical_Average_802.11ac40_5310MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_B2_AC40_5310

Freq Factor		Read Level		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5350.000	8.37	37.59	45.96	54.00	-8.04 Average
2	5350.345	8.37	37.96	46.33	54.00	-7.67 Average


Left Band edge_Horizontal_Peak_802.11ax20_5260MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B2_AX20_5260

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5051.119	7.75	50.01	57.76	74.00	-16.24 Peak
2	5150.000	7.47	48.29	55.76	74.00	-18.24 Peak

Left Band edge_Horizontal_Average_802.11ax20_5260MHz



Condition : Horizontal

Project No. : 2501X19230E-RF


Tester : Wing K Ji

Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak

Note : 5GWiFi_B2_AX20_5260

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5063.550	7.71	36.45	44.16	54.00	-9.84 Average
2	5150.000	7.47	36.29	43.76	54.00	-10.24 Average


Left Band edge_Vertical_Peak_802.11ax20_5260MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B2_AX20_5260

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	4943.487	7.37	50.41	57.78	74.00	-16.22 Peak
2	5150.000	7.47	47.89	55.36	74.00	-18.64 Peak


Left Band edge_Vertical_Average_802.11ax20_5260MHz



Condition : Vertical
 Project No. : 2501X19230E-RF
 Tester : Wing K Ji
 Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
 Note : 5GWiFi_B2_AX20_5260

Freq Factor		Read		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 5047.506	7.70	36.48	44.18	54.00	-9.82	Average
2 5150.000	7.47	36.40	43.87	54.00	-10.13	Average


Right Band edge_Horizontal_Peak_802.11ax20_5320MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B2_AX20_5320

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5350.000	8.37	48.97	57.34	74.00	-16.66 Peak
2	5351.808	8.37	52.07	60.44	74.00	-13.56 Peak


Right Band edge_Horizontal_Average_802.11ax20_5320MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_B2_AX20_5320

Freq Factor		Read Level		Limit	Over	Remark
				Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5350.000	8.37	37.08	45.45	54.00	-8.55 Average
2	5352.295	8.37	37.47	45.84	54.00	-8.16 Average


Right Band edge_Vertical_Peak_802.11ax20_5320MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B2_AX20_5320

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5350.000	8.37	48.21	56.58	74.00	-17.42 Peak
2	5364.645	8.42	51.35	59.77	74.00	-14.23 Peak


Right Band edge_Vertical_Average_802.11ax20_5320MHz



Condition : Vertical
 Project No. : 2501X19230E-RF
 Tester : Wing K Ji
 Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
 Note : 5GWiFi_B2_AX20_5320

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 5350.000	8.37	37.09	45.46	54.00	-8.54	Average
2 5352.067	8.37	37.92	46.29	54.00	-7.71	Average


Left Band edge_Horizontal_Peak_802.11ax40_5270MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B2_AX40_5270

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	4891.319	7.35	50.63	57.98	74.00	-16.02 Peak
2	5150.000	7.47	48.26	55.73	74.00	-18.27 Peak


Left Band edge_Horizontal_Average_802.11ax40_5270MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_B2_AX40_5270

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5054.094	7.73	36.48	44.21	54.00	-9.79 Average
2	5150.000	7.47	36.47	43.94	54.00	-10.06 Average


Left Band edge_Vertical_Peak_802.11ax40_5270MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B2_AX40_5270

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	4893.550	7.37	50.33	57.70	74.00	-16.30 Peak
2	5150.000	7.47	48.38	55.85	74.00	-18.15 Peak


Left Band edge_Vertical_Average_802.11ax40_5270MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_B2_AX40_5270

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5069.075	7.69	36.53	44.22	54.00	-9.78 Average
2	5150.000	7.47	36.34	43.81	54.00	-10.19 Average


Right Band edge_Horizontal_Peak_802.11ax40_5310MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B2_AX40_5310

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5350.000	8.37	52.98	61.35	74.00	-12.65 Peak
2	5350.800	8.37	55.62	63.99	74.00	-10.01 Peak


Right Band edge_Horizontal_Average_802.11ax40_5310MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_B2_AX40_5310

Freq Factor		Read Level		Limit	Over	Remark
				Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5350.000	8.37	37.82	46.19	54.00	-7.81 Average
2	5350.085	8.37	37.97	46.34	54.00	-7.66 Average


Right Band edge_Vertical_Peak_802.11ax40_5310MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B2_AX40_5310

Freq Factor		Read Level		Limit	Over	Remark
				Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5350.000	8.37	51.28	59.65	74.00	-14.35 Peak
2	5351.612	8.37	56.82	65.19	74.00	-8.81 Peak


Right Band edge_Vertical_Average_802.11ax40_5310MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_B2_AX40_5310

Freq Factor		Read Level		Limit	Over	Remark
				Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5350.000	8.37	37.97	46.34	54.00	-7.66 Average
2	5350.377	8.37	38.11	46.48	54.00	-7.52 Average


Left Band edge_Horizontal_Peak_802.11a_5500MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B3_A_5500

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 5460.000	8.90	48.07	56.97	74.00	-17.03 Peak
2 5468.938	9.01	51.63	60.64	68.20	-7.56 Peak
3 5470.000	9.03	48.57	57.60	68.20	-10.60 Peak


Left Band edge_Horizontal_Average_802.11a_5500MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_B3_A_5500

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 5460.000	8.90	36.68	45.58	54.00	-8.42 Average


Left Band edge_Vertical_Peak_802.11a_5500MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B3_A_5500

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 5460.000	8.90	47.96	56.86	74.00	-17.14 Peak
2 5469.109	9.01	51.55	60.56	68.20	-7.64 Peak
3 5470.000	9.03	48.39	57.42	68.20	-10.78 Peak


Left Band edge_Vertical_Average_802.11a_5500MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_B3_A_5500

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 5460.000	8.90	36.80	45.70	54.00	-8.30 Average


Right Band edge_Horizontal_Peak_802.11a_5700MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B3_A_5700

Freq Factor		Read Level		Limit	Over	Remark
				Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 5725.000	9.68	48.58	58.26	68.20	-9.94	Peak
2 5744.269	9.93	50.93	60.86	68.20	-7.34	Peak


Right Band edge_Vertical_Peak_802.11a_5700MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B3_A_5700

	Freq Factor		Read		Limit	Over	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5725.000	9.68	48.66	58.34	68.20	-9.86	Peak
2	5725.650	9.68	55.40	65.08	68.20	-3.12	Peak


Left Band edge_Horizontal_Peak_802.11ac20_5500MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B3_AC20_5500

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 5460.000	8.90	50.37	59.27	74.00	-14.73 Peak
2 5469.297	9.01	50.86	59.87	68.20	-8.33 Peak
3 5470.000	9.03	49.70	58.73	68.20	-9.47 Peak


Left Band edge_Horizontal_Average_802.11ac20_5500MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_B3_AC20_5500

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5460.000	8.90	36.63	45.53	54.00	-8.47 Average


Left Band edge_Vertical_Peak_802.11ac20_5500MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B3_AC20_5500

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 5460.000	8.90	47.34	56.24	74.00	-17.76 Peak
2 5466.875	8.99	53.67	62.66	68.20	-5.54 Peak
3 5470.000	9.03	48.38	57.41	68.20	-10.79 Peak


Left Band edge_Vertical_Average_802.11ac20_5500MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_B3_AC20_5500

Freq Factor		Read Level		Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 5460.000	8.90	36.92	45.82	54.00	-8.18	Average


Right Band edge_Horizontal_Peak_802.11ac20_5700MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B3_AC20_5700

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5725.000	9.68	48.49	58.17	68.20	-10.03 Peak
2	5725.828	9.68	51.22	60.90	68.20	-7.30 Peak


Right Band edge_Vertical_Peak_802.11ac20_5700MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B3_AC20_5700

	Freq	Factor	Read		Limit	Over	Remark
			Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5725.000	9.68	49.34	59.02	68.20	-9.18	Peak
2	5725.697	9.68	52.96	62.64	68.20	-5.56	Peak


Left Band edge_Horizontal_Peak_802.11ac40_5510MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B3_AC40_5510

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5460.000	8.90	49.32	58.22	74.00	-15.78	Peak
2	5469.563	9.02	56.10	65.12	68.20	-3.08	Peak
3	5470.000	9.03	50.68	59.71	68.20	-8.49	Peak


Left Band edge_Horizontal_Average_802.11ac40_5510MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_B3_AC40_5510

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5460.000	8.90	36.95	45.85	54.00	-8.15	Average


Left Band edge_Vertical_Peak_802.11ac40_5510MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B3_AC40_5510

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 5460.000	8.90	48.67	57.57	74.00	-16.43 Peak
2 5468.594	9.01	55.81	64.82	68.20	-3.38 Peak
3 5470.000	9.03	50.02	59.05	68.20	-9.15 Peak


Left Band edge_Vertical_Average_802.11ac40_5510MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_B3_AC40_5510

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 5460.000	8.90	37.30	46.20	54.00	-7.80	Average


Right Band edge_Horizontal_Peak_802.11ac40_5670MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B3_AC40_5670

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5725.000	9.68	49.98	59.66	68.20	-8.54 Peak
2	5743.425	9.93	51.17	61.10	68.20	-7.10 Peak


Right Band edge_Vertical_Peak_802.11ac40_5670MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B3_AC40_5670

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5725.000	9.68	48.43	58.11	68.20	-10.09 Peak
2	5735.458	9.78	51.14	60.92	68.20	-7.28 Peak


Left Band edge_Horizontal_Peak_802.11ax20_5500MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B3_AX20_5500

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5460.000	8.90	48.12	57.02	74.00	-16.98	Peak
2	5469.141	9.01	50.10	59.11	68.20	-9.09	Peak
3	5470.000	9.03	48.78	57.81	68.20	-10.39	Peak


Left Band edge_Horizontal_Average_802.11ax20_5500MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_B3_AX20_5500

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5460.000	8.90	36.91	45.81	54.00	-8.19	Average


Left Band edge_Vertical_Peak_802.11ax20_5500MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B3_AX20_5500

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5460.000	8.90	49.24	58.14	74.00	-15.86	Peak
2	5461.359	8.91	50.67	59.58	68.20	-8.62	Peak
3	5470.000	9.03	48.48	57.51	68.20	-10.69	Peak


Left Band edge_Vertical_Average_802.11ax20_5500MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_B3_AX20_5500

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 5460.000	8.90	36.84	45.74	54.00	-8.26 Average


Right Band edge_Horizontal_Peak_802.11ax20_5700MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B3_AX20_5700

Freq Factor		Read Level		Limit	Over	Remark
				Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5725.000	9.68	48.69	58.37	68.20	-9.83 Peak
2	5732.550	9.71	51.07	60.78	68.20	-7.42 Peak


Right Band edge_Vertical_Peak_802.11ax20_5700MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B3_AX20_5700

	Freq	Factor	Read		Limit	Over	Remark
			Level	Level			
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5725.000	9.68	49.48	59.16	68.20	-9.04	Peak
2	5726.560	9.69	52.30	61.99	68.20	-6.21	Peak


Left Band edge_Horizontal_Peak_802.11ax40_5510MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B3_AX40_5510

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5460.000	8.90	48.73	57.63	74.00	-16.37	Peak
2	5465.375	8.96	54.22	63.18	68.20	-5.02	Peak
3	5470.000	9.03	48.57	57.60	68.20	-10.60	Peak


Left Band edge_Horizontal_Average_802.11ax40_5510MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_B3_AX40_5510

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 5460.000	8.90	37.08	45.98	54.00	-8.02	Average


Left Band edge_Vertical_Peak_802.11ax40_5510MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B3_AX40_5510

			Read		Limit	Over	
	Freq	Factor	Level	Level	Line	Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5460.000	8.90	49.16	58.06	74.00	-15.94	Peak
2	5466.359	8.98	53.77	62.75	68.20	-5.45	Peak
3	5470.000	9.03	49.77	58.80	68.20	-9.40	Peak


Left Band edge_Vertical_Average_802.11ax40_5510MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : 5GWiFi_B3_AX40_5510

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 5460.000	8.90	37.28	46.18	54.00	-7.82 Average


Right Band edge_Horizontal_Peak_802.11ax40_5670MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B3_AX40_5670

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 5725.000	9.68	48.12	57.80	68.20	-10.40	Peak
2 5741.115	9.89	50.62	60.51	68.20	-7.69	Peak


Right Band edge_Vertical_Peak_802.11ax40_5670MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B3_AX40_5670

	Freq	Factor	Read		Limit	Over	Remark
			Level	Level			
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5725.000	9.68	48.80	58.48	68.20	-9.72	Peak
2	5727.071	9.68	51.21	60.89	68.20	-7.31	Peak


Left Band edge_Horizontal_Peak_802.11a_5745MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B4_A_5745

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5610.558	8.99	50.57	59.56	68.20	-8.64	Peak
2	5672.929	9.57	50.43	60.00	85.21	-25.21	Peak
3	5719.541	9.72	51.31	61.03	110.67	-49.64	Peak
4	5721.744	9.70	52.26	61.96	114.78	-52.82	Peak


Left Band edge_Vertical_Peak_802.11a_5745MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B4_A_5745

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5628.111	9.18	50.58	59.76	68.20	-8.44	Peak
2	5684.460	9.52	50.78	60.30	93.74	-33.44	Peak
3	5716.645	9.67	54.42	64.09	109.86	-45.77	Peak
4	5724.819	9.68	55.47	65.15	121.79	-56.64	Peak


Right Band edge_Horizontal_Peak_802.11a_5825MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B4_A_5825

			Read		Limit	Over	
	Freq	Factor	Level	Level	Line	Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5851.701	10.45	50.74	61.19	118.32	-57.13	Peak
2	5857.022	10.36	51.28	61.64	110.23	-48.59	Peak
3	5920.279	10.69	50.83	61.52	71.68	-10.16	Peak
4	5929.973	10.72	51.18	61.90	68.20	-6.30	Peak


Right Band edge_Vertical_Peak_802.11a_5825MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B4_A_5825

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 5850.072	10.48	54.27	64.75	122.04	-57.29 Peak
2 5860.199	10.31	51.86	62.17	109.34	-47.17 Peak
3 5923.002	10.70	51.05	61.75	69.67	-7.92 Peak
4 5948.845	10.78	50.42	61.20	68.20	-7.00 Peak


Left Band edge_Horizontal_Peak_802.11ac20_5745MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B4_AC20_5745

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5648.764	9.33	50.13	59.46	68.20	-8.74	Peak
2	5681.513	9.54	50.43	59.97	91.56	-31.59	Peak
3	5719.361	9.72	51.05	60.77	110.62	-49.85	Peak
4	5721.642	9.70	52.98	62.68	114.55	-51.87	Peak


Left Band edge_Vertical_Peak_802.11ac20_5745MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B4_AC20_5745

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5633.185	9.23	50.66	59.89	68.20	-8.31	Peak
2	5679.489	9.54	50.86	60.40	90.06	-29.66	Peak
3	5718.772	9.71	55.11	64.82	110.46	-45.64	Peak
4	5723.333	9.70	56.76	66.46	118.40	-51.94	Peak


Right Band edge_Horizontal_Peak_802.11ac20_5825MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B4_AC20_5825

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5850.134	10.48	50.28	60.76	121.89	-61.13	Peak
2	5868.139	10.51	50.81	61.32	107.12	-45.80	Peak
3	5887.114	10.72	50.71	61.43	96.21	-34.78	Peak
4	5933.995	10.73	51.18	61.91	68.20	-6.29	Peak


Right Band edge_Vertical_Peak_802.11ac20_5825MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B4_AC20_5825

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5851.310	10.46	52.58	63.04	119.21	-56.17	Peak
2	5869.790	10.57	51.40	61.97	106.66	-44.69	Peak
3	5911.122	10.67	51.71	62.38	78.44	-16.06	Peak
4	5941.998	10.76	50.91	61.67	68.20	-6.53	Peak


Left Band edge_Horizontal_Peak_802.11ac40_5755MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B4_AC40_5755

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5637.643	9.26	51.04	60.30	68.20	-7.90	Peak
2	5653.249	9.36	50.31	59.67	70.61	-10.94	Peak
3	5719.643	9.72	54.96	64.68	110.70	-46.02	Peak
4	5722.462	9.70	53.77	63.47	116.41	-52.94	Peak


Left Band edge_Vertical_Peak_802.11ac40_5755MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B4_AC40_5755

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 5620.090	9.09	50.25	59.34	68.20	-8.86 Peak
2 5677.951	9.54	50.13	59.67	88.92	-29.25 Peak
3 5719.413	9.72	59.54	69.26	110.64	-41.38 Peak
4 5721.437	9.71	58.82	68.53	114.08	-45.55 Peak


Right Band edge_Horizontal_Peak_802.11ac40_5795MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B4_AC40_5795

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 5850.640	10.47	50.95	61.42	120.74	-59.32 Peak
2 5874.985	10.59	51.01	61.60	105.20	-43.60 Peak
3 5882.950	10.65	50.77	61.42	99.30	-37.88 Peak
4 5933.890	10.73	50.77	61.50	68.20	-6.70 Peak


Right Band edge_Vertical_Peak_802.11ac40_5795MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B4_AC40_5795

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5850.280	10.47	50.41	60.88	121.56	-60.68	Peak
2	5868.955	10.54	50.96	61.50	106.89	-45.39	Peak
3	5886.595	10.72	51.07	61.79	96.59	-34.80	Peak
4	5944.645	10.76	50.67	61.43	68.20	-6.77	Peak


Left Band edge_Horizontal_Peak_802.11ax20_5745MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B4_AX20_5745

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 5637.592	9.26	50.15	59.41	68.20	-8.79 Peak
2 5695.171	9.55	50.37	59.92	101.64	-41.72 Peak
3 5713.724	9.64	50.85	60.49	109.04	-48.55 Peak
4 5724.384	9.69	52.66	62.35	120.80	-58.45 Peak


Left Band edge_Vertical_Peak_802.11ax20_5745MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B4_AX20_5745

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5635.619	9.24	50.26	59.50	68.20	-8.70	Peak
2	5682.000	9.53	50.55	60.08	91.92	-31.84	Peak
3	5718.029	9.69	53.00	62.69	110.25	-47.56	Peak
4	5724.973	9.68	55.80	65.48	122.14	-56.66	Peak


Right Band edge_Horizontal_Peak_802.11ax20_5825MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B4_AX20_5825

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5854.712	10.40	50.66	61.06	111.46	-50.40	Peak
2	5865.272	10.45	50.99	61.44	107.92	-46.48	Peak
3	5901.284	10.64	50.78	61.42	85.71	-24.29	Peak
4	5949.319	10.78	51.12	61.90	68.20	-6.30	Peak


Right Band edge_Vertical_Peak_802.11ax20_5825MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B4_AX20_5825

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5850.794	10.46	54.23	64.69	120.39	-55.70	Peak
2	5871.047	10.57	50.99	61.56	106.31	-44.75	Peak
3	5900.851	10.64	50.60	61.24	86.03	-24.79	Peak
4	5939.213	10.75	50.84	61.59	68.20	-6.61	Peak


Left Band edge_Horizontal_Peak_802.11ax40_5755MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B4_AX40_5755

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 5603.587	8.99	50.49	59.48	68.20	-8.72 Peak
2 5656.580	9.41	50.25	59.66	73.09	-13.43 Peak
3 5718.926	9.71	51.70	61.41	110.50	-49.09 Peak
4 5723.461	9.69	53.91	63.60	118.69	-55.09 Peak


Left Band edge_Vertical_Peak_802.11ax40_5755MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B4_AX40_5755

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5628.623	9.18	51.55	60.73	68.20	-7.47	Peak
2	5690.277	9.50	50.29	59.79	98.03	-38.24	Peak
3	5719.438	9.72	55.44	65.16	110.64	-45.48	Peak
4	5723.948	9.70	60.09	69.79	119.80	-50.01	Peak


Right Band edge_Horizontal_Peak_802.11ax40_5795MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B4_AX40_5795

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 5850.820	10.46	50.73	61.19	120.33	-59.14 Peak
2 5871.723	10.58	51.23	61.81	106.12	-44.31 Peak
3 5918.725	10.69	51.21	61.90	72.83	-10.93 Peak
4 5932.990	10.73	50.81	61.54	68.20	-6.66 Peak

Right Band edge_Vertical_Peak_802.11ax40_5795MHz




Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Wing K Ji
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi_B4_AX40_5795

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5850.842	10.46	51.60	62.06	120.28	-58.22	Peak
2	5871.002	10.57	51.09	61.66	106.32	-44.66	Peak
3	5884.143	10.67	51.09	61.76	98.41	-36.65	Peak
4	5928.850	10.71	51.35	62.06	68.20	-6.14	Peak

1-18GHz (Listed with the worst harmonic margin test plot)


1-7GHz Horizontal 802.11a 5200MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band1-A-5200

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	6879.250	-3.12	55.53	52.41	68.20	-15.79 Peak


1-7GHz_Vertical_802.11a_5200MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band1-A-5200

Freq Factor		Read Level		Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	6760.750	-3.24	55.34	52.10	68.20	-16.10 Peak


7-18GHz_Horizontal_Peak_802.11a_5200MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band1-A-5200

Freq Factor		Read	Limit	Over	Remark
MHz	dB/m	Level	Level	Line	
		dBuV	dBuV/m	dBuV/m	dB
1 10400.000	2.55	51.26	53.81	68.20	-14.39 Peak
2 17928.500	12.85	49.17	62.02	74.00	-11.98 Peak


7-18GHz_Horizontal_Average_802.11a_5200MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 5GWiFi-Band1-A-5200

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 17998.630	13.19	34.31	47.50	54.00	-6.50	Average


7-18GHz_Vertical_Peak_802.11a_5200MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band1-A-5200

Freq Factor		Read	Limit	Over	Remark
MHz	dB/m	Level	Level	Line	
		dBuV	dBuV/m	dBuV/m	dB
1 10400.000	2.55	50.60	53.15	68.20	-15.05 Peak
2 17950.500	12.95	48.28	61.23	74.00	-12.77 Peak


7-18GHz_Vertical_Average_802.11a_5200MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 5GWiFi-Band1-A-5200

Freq Factor		Read Level		Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 17994.500	13.17	34.22	47.39	54.00	-6.61	Average


1-7GHz_Horizontal_802.11ac20_5200MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band1-AC20-5200

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 6483.250	-2.92	56.90	53.98	68.20	-14.22	Peak


1-7GHz_Vertical_802.11ac20_5200MHz



Condition : Vertical
 Project No. : 2501X19230E-RF
 Tester : Zenos Qiao
 Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
 Note : 5GWiFi-Band1-AC20-5200

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 6654.250	-2.99	55.63	52.64	68.20	-15.56 Peak


7-18GHz_Horizontal_Peak_802.11ac20_5200MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band1-AC20-5200

Freq Factor		Read	Limit	Over	Remark
MHz	dB/m	Level	Level	Line	
		dBuV	dBuV/m	dBuV/m	dB
1 10400.000	2.55	50.40	52.95	68.20	-15.25 Peak
2 17929.880	12.86	49.06	61.92	74.00	-12.08 Peak


7-18GHz_Horizontal_Average_802.11ac20_5200MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 5GWiFi-Band1-AC20-5200

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 17997.250	13.19	34.22	47.41	54.00	-6.59	Average


7-18GHz_Vertical_Peak_802.11ac20_5200MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band1-AC20-5200

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	10400.000	2.55	50.89	53.44	68.20	-14.76	Peak
2	17931.250	12.86	49.36	62.22	74.00	-11.78	Peak


7-18GHz_Vertical_Average_802.11ac20_5200MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 5GWiFi-Band1-AC20-5200

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 17998.630	13.20	34.26	47.46	54.00	-6.54	Average


1-7GHz_Horizontal_802.11ac40_5230MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band1-AC40-5230

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	6541.750	-3.03	56.65	53.62	68.20	-14.58 Peak


1-7GHz_Vertical_802.11ac40_5230MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band1-AC40-5230

Freq Factor		Read Level		Limit	Over	Remark
				Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 6500.500	-2.95	56.12	53.17	68.20	-15.03	Peak


7-18GHz_Horizontal_Peak_802.11ac40_5230MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band1-AC40-5230

Freq Factor		Read	Limit	Over	Remark
MHz	dB/m	Level	Level	Line	
		dBuV	dBuV/m	dBuV/m	dB
1 10460.000	2.32	49.54	51.86	68.20	-16.34 Peak
2 17957.380	12.99	48.58	61.57	74.00	-12.43 Peak


7-18GHz_Horizontal_Average_802.11ac40_5230MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 5GWiFi-Band1-AC40-5230

Freq Factor		Read	Limit	Over	Remark
MHz	dB/m	Level	Level	Line	
		dBuV	dBuV/m	dBuV/m	dB
1 17998.630	13.19	34.28	47.47	54.00	-6.53 Average


7-18GHz_Vertical_Peak_802.11ac40_5230MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band1-AC40-5230

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 10460.000	2.32	50.03	52.35	68.20	-15.85 Peak
2 17839.130	11.58	49.79	61.37	74.00	-12.63 Peak


7-18GHz_Vertical_Average_802.11ac40_5230MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 5GWiFi-Band1-AC40-5230

Freq Factor		Read Level		Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 17998.250	13.20	34.21	47.41	54.00	-6.59	Average


1-7GHz_Horizontal_802.11ax20_5200MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band1-AX20-5200

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	6797.500	-3.35	56.67	53.32	68.20	-14.88	Peak


1-7GHz_Vertical_802.11ax20_5200MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band1-AX20-5200

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	6512.500	-2.98	56.11	53.13	68.20	-15.07 Peak


7-18GHz_Horizontal_Peak_802.11ax20_5200MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band1-AX20-5200

Freq Factor		Read	Limit	Over	Remark
MHz	dB/m	Level	Level	Line	
		dBuV	dBuV/m	dBuV/m	dB
1 10400.000	2.55	50.46	53.01	68.20	-15.19 Peak
2 17916.130	12.78	48.73	61.51	74.00	-12.49 Peak


7-18GHz_Horizontal_Average_802.11ax20_5200MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 5GWiFi-Band1-AX20-5200

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 17997.250	13.19	34.17	47.36	54.00	-6.64 Average


7-18GHz_Vertical_Peak_802.11ax20_5200MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band1-AX20-5200

Freq Factor		Read	Limit	Over	Remark
MHz	dB/m	Level	Level	Line	
		dBuV	dBuV/m	dBuV/m	dB
1 10400.000	2.55	50.63	53.18	68.20	-15.02 Peak
2 17978.000	13.10	48.68	61.78	74.00	-12.22 Peak


7-18GHz_Vertical_Average_802.11ax20_5200MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 5GWiFi-Band1-AX20-5200

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 17998.630	13.19	34.25	47.44	54.00	-6.56	Average


1-7GHz_Horizontal_802.11ax40_5230MHz



Condition : Horizontal
 Project No. : 2501X19230E-RF
 Tester : Zenos Qiao
 Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
 Note : 5GWiFi-Band1-AX40-5230

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 6415.750	-2.88	56.28	53.40	68.20	-14.80 Peak


1-7GHz_Vertical_802.11ax40_5230MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band1-AX40-5230

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 6489.250	-2.94	56.20	53.26	68.20	-14.94	Peak


7-18GHz_Horizontal_Peak_802.11ax40_5230MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band1-AX40-5230

Freq Factor		Read	Limit	Over	Remark
MHz	dB/m	Level	Level	Line	
		dBuV	dBuV/m	dBuV/m	dB
1 10460.000	2.32	50.18	52.50	68.20	-15.70 Peak
2 17953.250	12.97	48.07	61.04	74.00	-12.96 Peak


7-18GHz_Horizontal_Average_802.11ax40_5230MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 5GWiFi-Band1-AX40-5230

Freq Factor		Read Level		Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 17998.250	13.20	34.18	47.38	54.00	-6.62	Average


7-18GHz_Vertical_Peak_802.11ax40_5230MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band1-AX40-5230

Freq Factor		Read	Limit	Over	Remark
MHz	dB/m	Level	Level	Line	
		dBuV	dBuV/m	dBuV/m	dB
1 10460.000	2.32	49.49	51.81	68.20	-16.39 Peak
2 17979.380	13.10	48.45	61.55	74.00	-12.45 Peak


7-18GHz_Vertical_Average_802.11ax40_5230MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 5GWiFi-Band1-AX40-5230

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 17998.630	13.20	34.23	47.43	54.00	-6.57 Average


1-7GHz_Horizontal_802.11a_5260MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band2-A-5260

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	6578.500	-3.08	55.49	52.41	68.20	-15.79 Peak


1-7GHz_Vertical_802.11a_5260MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band2-A-5260

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 6444.250	-2.87	55.70	52.83	68.20	-15.37 Peak


7-18GHz_Horizontal_Peak_802.11a_5260MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band2-A-5260

Freq Factor		Read	Limit	Over	Remark
MHz	dB/m	Level	Level	Line	
		dBuV	dBuV/m	dBuV/m	dB
1 10520.000	2.18	50.02	52.20	68.20	-16.00 Peak
2 17967.000	13.03	48.52	61.55	74.00	-12.45 Peak


7-18GHz_Horizontal_Average_802.11a_5260MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 5GWiFi-Band2-A-5260

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 17994.500	13.17	34.21	47.38	54.00	-6.62 Average


7-18GHz_Vertical_Peak_802.11a_5260MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band2-A-5260

Freq Factor		Read	Limit	Over	Remark
MHz	dB/m	Level	Level	Line	
		dBuV	dBuV/m	dBuV/m	dB
1 10520.000	2.18	49.68	51.86	68.20	-16.34 Peak
2 17906.500	12.74	49.79	62.53	74.00	-11.47 Peak


7-18GHz_Vertical_Average_802.11a_5260MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 5GWiFi-Band2-A-5260

Freq Factor		Read Level		Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 17990.380	13.15	34.28	47.43	54.00	-6.57	Average


1-7GHz_Horizontal_802.11ac20_5260MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band2-AC20-5260

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	6568.000	-3.07	56.18	53.11	68.20	-15.09 Peak


1-7GHz_Vertical_802.11ac20_5260MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band2-AC20-5260

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	6422.500	-2.87	55.49	52.62	68.20	-15.58 Peak


7-18GHz_Horizontal_Peak_802.11ac20_5260MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band2-AC20-5260

Freq Factor		Read	Limit	Over	Remark
MHz	dB/m	Level	Level	Line	
		dBuV	dBuV/m	dBuV/m	dB
1 10520.000	2.18	50.19	52.37	68.20	-15.83 Peak
2 17950.500	12.95	48.75	61.70	74.00	-12.30 Peak


7-18GHz_Horizontal_Average_802.11ac20_5260MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 5GWiFi-Band2-AC20-5260

Freq Factor		Read Level		Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 17994.500	13.17	34.22	47.39	54.00	-6.61	Average


7-18GHz_Vertical_Peak_802.11ac20_5260MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band2-AC20-5260

Freq Factor		Read	Limit	Over	Remark
MHz	dB/m	Level	Level	Line	
		dBuV	dBuV/m	dBuV/m	dB
1 10520.000	2.18	50.24	52.42	68.20	-15.78 Peak
2 17920.250	12.80	49.73	62.53	74.00	-11.47 Peak


7-18GHz_Vertical_Average_802.11ac20_5260MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 5GWiFi-Band2-AC20-5260

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 17986.250	13.12	34.25	47.37	54.00	-6.63	Average


1-7GHz_Horizontal_802.11ac40_5270MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band2-AC40-5270

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	6247.000	-3.88	55.99	52.11	68.20	-16.09	Peak


1-7GHz_Vertical_802.11ac40_5270MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band2-AC40-5270

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	6401.500	-2.89	55.33	52.44	68.20	-15.76	Peak


7-18GHz_Horizontal_Peak_802.11ac40_5270MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band2-AC40-5270

Freq Factor		Read	Limit	Over	Remark
MHz	dB/m	Level	Level	Line	
		dBuV	dBuV/m	dBuV/m	dB
1 10540.000	2.18	50.81	52.99	68.20	-15.21 Peak
2 17914.750	12.77	48.77	61.54	74.00	-12.46 Peak


7-18GHz_Horizontal_Average_802.11ac40_5270MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 5GWiFi-Band2-AC40-5270

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 17995.880	13.18	34.26	47.44	54.00	-6.56 Average


7-18GHz_Vertical_Peak_802.11ac40_5270MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band2-AC40-5270

Freq Factor		Read	Limit	Over	Remark
MHz	dB/m	Level	Level	Line	
		dBuV	dBuV/m	dBuV/m	dB
1 10540.000	2.18	50.98	53.16	68.20	-15.04 Peak
2 17914.750	12.77	48.60	61.37	74.00	-12.63 Peak


7-18GHz_Vertical_Average_802.11ac40_5270MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 5GWiFi-Band2-AC40-5270

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 17995.880	13.18	34.13	47.31	54.00	-6.69 Average


1-7GHz_Horizontal_802.11ax20_5260MHz



Condition : Horizontal
 Project No. : 2501X19230E-RF
 Tester : Zenos Qiao
 Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
 Note : 5GWiFi-Band2-AX20-5260

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 6485.500	-2.92	55.51	52.59	68.20	-15.61 Peak


1-7GHz_Vertical_802.11ax20_5260MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band2-AX20-5260

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	6773.500	-3.29	55.94	52.65	68.20	-15.55 Peak


7-18GHz_Horizontal_Peak_802.11ax20_5260MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band2-AX20-5260

Freq Factor		Read		Limit	Over	Remark
MHz	dB/m	Level	Level	Line	Limit	
		dBuV	dBuV/m	dBuV/m	dB	
1 10520.000	2.18	49.65	51.83	68.20	-16.37	Peak
2 17953.250	12.97	48.79	61.76	74.00	-12.24	Peak


7-18GHz_Horizontal_Average_802.11ax20_5260MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 5GWiFi-Band2-AX20-5260

Freq Factor		Read Level		Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 17994.500	13.17	34.29	47.46	54.00	-6.54	Average


7-18GHz_Vertical_Peak_802.11ax20_5260MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band2-AX20-5260

Freq Factor		Read	Limit	Over	Remark
MHz	dB/m	Level	Level	Line	
		dBuV	dBuV/m	dBuV/m	dB
1 10520.000	2.18	49.34	51.52	68.20	-16.68 Peak
2 17972.500	13.07	49.23	62.30	74.00	-11.70 Peak


7-18GHz_Vertical_Average_802.11ax20_5260MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 5GWiFi-Band2-AX20-5260

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 17995.880	13.18	34.23	47.41	54.00	-6.59	Average


1-7GHz_Horizontal_802.11ax40_5270MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band2-AX40-5270

Freq Factor		Read Level		Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	6462.250	-2.89	55.24	52.35	68.20	-15.85 Peak


1-7GHz_Vertical_802.11ax40_5270MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band2-AX40-5270

Freq Factor		Read Level		Limit	Over	Remark
				Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 6778.750	-3.29	56.66	53.37	68.20	-14.83	Peak


7-18GHz_Horizontal_Peak_802.11ax40_5270MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band2-AX40-5270

Freq Factor		Read	Limit	Over	Remark
MHz	dB/m	Level	Level	Line	
		dBuV	dBuV/m	dBuV/m	dB
1 10540.000	2.18	50.33	52.51	68.20	-15.69 Peak
2 17960.130	13.00	48.86	61.86	74.00	-12.14 Peak


7-18GHz_Horizontal_Average_802.11ax40_5270MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 5GWiFi-Band2-AX40-5270

Freq Factor		Read Level		Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 17997.250	13.19	34.26	47.45	54.00	-6.55	Average


7-18GHz_Vertical_Peak_802.11ax40_5270MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band2-AX40-5270

Freq Factor		Read	Limit	Over	Remark
MHz	dB/m	Level	Level	Line	
		dBuV	dBuV/m	dBuV/m	dB
1 10540.000	2.18	50.17	52.35	68.20	-15.85 Peak
2 17979.380	13.10	48.52	61.62	74.00	-12.38 Peak


7-18GHz_Vertical_Average_802.11ax40_5270MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 5GWiFi-Band2-AX40-5270

Freq Factor		Read	Limit	Over	Remark
MHz	dB/m	Level	Level	Line	
		dBuV	dBuV/m	dBuV/m	dB
1 17998.630	13.19	34.24	47.43	54.00	-6.57 Average


1-7GHz_Horizontal_802.11a_5700MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band3-A-5700

Freq Factor		Read Level		Limit	Over	Remark
				Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	6956.500	-2.73	55.03	52.30	68.20	-15.90 Peak


1-7GHz_Vertical_802.11a_5700MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band3-A-5700

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 6808.750	-3.32	55.98	52.66	68.20	-15.54 Peak


7-18GHz_Horizontal_Peak_802.11a_5700MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band3-A-5700

Freq Factor		Read	Limit	Over	Remark
MHz	dB/m	Level	Level	Line	
		dBuV	dBuV/m	dBuV/m	dB
1 11400.000	3.32	50.37	53.69	74.00	-20.31 Peak
2 17918.880	12.79	48.96	61.75	74.00	-12.25 Peak


7-18GHz_Horizontal_Average_802.11a_5700MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 5GWiFi-Band3-A-5700

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 17998.630	13.19	34.21	47.40	54.00	-6.60 Average


7-18GHz_Vertical_Peak_802.11a_5700MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band3-A-5700

Freq Factor		Read		Limit	Over	Remark
MHz	dB/m	Level	Level	Line	Limit	
		dBuV	dBuV/m	dBuV/m	dB	
1 11400.000	3.32	50.12	53.44	74.00	-20.56	Peak
2 17998.630	13.19	48.05	61.24	74.00	-12.76	Peak


7-18GHz_Vertical_Average_802.11a_5700MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 5GWiFi-Band3-A-5700

Freq Factor		Read Level		Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 17998.630	13.19	34.26	47.45	54.00	-6.55	Average


1-7GHz_Horizontal_802.11ac20_5700MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band3-AC20-5700

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	6460.000	-2.89	56.57	53.68	68.20	-14.52	Peak


1-7GHz_Vertical_802.11ac20_5700MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band3-AC20-5700

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	6551.500	-3.05	55.21	52.16	68.20	-16.04 Peak


7-18GHz_Horizontal_Peak_802.11ac20_5700MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band3-AC20-5700

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	11400.000	3.32	50.11	53.43	74.00	-20.57	Peak
2	17906.500	12.74	49.09	61.83	74.00	-12.17	Peak


7-18GHz_Horizontal_Average_802.11ac20_5700MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 5GWiFi-Band3-AC20-5700

Freq Factor		Read Level		Limit	Over	Remark
				Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 17990.380	13.15	34.20	47.35	54.00	-6.65	Average


7-18GHz_Vertical_Peak_802.11ac20_5700MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band3-AC20-5700

Freq Factor		Read	Limit	Over	Remark
MHz	dB/m	Level	Level	Line	
		dBuV	dBuV/m	dBuV/m	dB
1 11400.000	3.32	50.43	53.75	74.00	-20.25 Peak
2 17971.130	13.06	48.22	61.28	74.00	-12.72 Peak


7-18GHz_Vertical_Average_802.11ac20_5700MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 5GWiFi-Band3-AC20-5700

Freq Factor		Read Level		Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 17991.750	13.16	34.27	47.43	54.00	-6.57	Average


1-7GHz_Horizontal_802.11ac40_5510MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band3-AC40-5510

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	6441.250	-2.87	56.18	53.31	68.20	-14.89	Peak


1-7GHz_Vertical_802.11ac40_5510MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band3-AC40-5510

Freq Factor		Read Level		Limit	Over	Remark
				Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 6447.250	-2.87	56.71	53.84	68.20	-14.36	Peak


7-18GHz_Horizontal_Peak_802.11ac40_5510MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band3-AC40-5510

Freq Factor		Read	Limit	Over	Remark
MHz	dB/m	Level	Level	Line	
		dBuV	dBuV/m	dBuV/m	dB
1 11020.000	4.10	48.75	52.85	74.00	-21.15 Peak
2 17984.880	13.12	48.50	61.62	74.00	-12.38 Peak


7-18GHz_Horizontal_Average_802.11ac40_5510MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 5GWiFi-Band3-AC40-5510

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 17995.880	13.18	34.18	47.36	54.00	-6.64	Average


7-18GHz_Vertical_Peak_802.11ac40_5510MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band3-AC40-5510

Freq Factor		Read Level		Limit	Over	Remark
				Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 11020.000	4.10	49.07	53.17	74.00	-20.83	Peak
2 17927.130	12.84	49.09	61.93	74.00	-12.07	Peak


7-18GHz_Vertical_Average_802.11ac40_5510MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 5GWiFi-Band3-AC40-5510

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 17995.880	13.18	34.24	47.42	54.00	-6.58	Average


1-7GHz Horizontal 802.11ax20 5700MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band3-AX20-5700

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	6560.500	-3.06	55.35	52.29	68.20	-15.91	Peak


1-7GHz_Vertical_802.11ax20_5700MHz



Condition : Vertical
 Project No. : 2501X19230E-RF
 Tester : Zenos Qiao
 Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
 Note : 5GWiFi-Band3-AX20-5700

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 6438.250	-2.88	55.66	52.78	68.20	-15.42	Peak


7-18GHz_Horizontal_Peak_802.11ax20_5700MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band3-AX20-5700

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	11400.000	3.32	50.46	53.78	74.00	-20.22	Peak
2	17991.750	13.16	48.93	62.09	74.00	-11.91	Peak


7-18GHz_Horizontal_Average_802.11ax20_5700MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 5GWiFi-Band3-AX20-5700

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 17998.250	13.20	34.29	47.49	54.00	-6.51	Average


7-18GHz_Vertical_Peak_802.11ax20_5700MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band3-AX20-5700

Freq Factor		Read	Limit	Over	Remark
MHz	dB/m	Level	Level	Line	
		dBuV	dBuV/m	dBuV/m	dB
1 11400.000	3.32	50.18	53.50	74.00	-20.50 Peak
2 17868.000	12.11	48.61	60.72	74.00	-13.28 Peak


7-18GHz_Vetical_Average_802.11ax20_5700MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 5GWiFi-Band3-AX20-5700

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 17993.130	13.17	34.19	47.36	54.00	-6.64	Average


1-7GHz_Horizontal_802.11ax40_5510MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band3-AX40-5510

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 6799.750	-3.36	55.83	52.47	68.20	-15.73 Peak


1-7GHz_Vertical_802.11ax40_5510MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band3-AX40-5510

Freq Factor		Read Level		Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	6472.000	-2.91	55.75	52.84	68.20	-15.36 Peak


7-18GHz_Horizontal_Peak_802.11ax40_5510MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band3-AX40-5510

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 11020.000	4.10	48.70	52.80	74.00	-21.20	Peak
2 17910.630	12.75	48.57	61.32	74.00	-12.68	Peak


7-18GHz_Horizontal_Average_802.11ax40_5510MHz



Condition : Horizontal
 Project No. : 2501X19230E-RF
 Tester : Zenos Qiao
 Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
 Note : 5GWiFi-Band3-AX40-5510

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 17978.000	13.10	34.23	47.33	54.00	-6.67 Average


7-18GHz_Vertical_Peak_802.11ax40_5510MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band3-AX40-5510

Freq Factor		Read		Limit	Over	Remark
MHz	dB/m	Level	Level	Line	Limit	
		dBuV	dBuV/m	dBuV/m	dB	
1 11020.000	4.10	48.53	52.63	74.00	-21.37	Peak
2 17984.880	13.12	48.88	62.00	74.00	-12.00	Peak


7-18GHz_Vetical_Average_802.11ax40_5510MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 5GWiFi-Band3-AX40-5510

Freq Factor		Read Level		Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 17986.250	13.12	34.34	47.46	54.00	-6.54	Average


1-7GHz_Horizontal_802.11a_5825MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band4-A-5825

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	6460.000	-2.89	55.70	52.81	68.20	-15.39 Peak


1-7GHz_Vertical_802.11a_5825MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band4-A-5825

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 6712.750	-3.32	55.93	52.61	68.20	-15.59 Peak


7-18GHz_Horizontal_Peak_802.11a_5825MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band4-A-5825

Freq Factor		Read		Limit	Over	Remark
MHz	dB/m	Level	Level	Line	Limit	
		dBuV	dBuV/m	dBuV/m	dB	
1 11650.000	3.44	50.16	53.60	74.00	-20.40	Peak
2 17884.500	12.42	49.74	62.16	74.00	-11.84	Peak


7-18GHz_Horizontal_Average_802.11a_5825MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 5GWiFi-Band4-A-5825

Freq Factor		Read	Limit	Over	Remark
MHz	dB/m	Level	Level	Line	
		dBuV	dBuV/m	dBuV/m	dB
1 17993.130	13.17	34.30	47.47	54.00	-6.53 Average


7-18GHz_Vertical_Peak_802.11a_5825MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band4-A-5825

Freq Factor		Read		Limit	Over	Remark
MHz	dB/m	Level	Level	Line	Limit	
		dBuV	dBuV/m	dBuV/m	dB	
1 11650.000	3.44	49.46	52.90	74.00	-21.10	Peak
2 17868.000	12.11	49.09	61.20	74.00	-12.80	Peak


7-18GHz_Vertical_Average_802.11a_5825MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 5GWiFi-Band4-A-5825

Freq Factor		Read Level		Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 17968.380	13.05	34.28	47.33	54.00	-6.67	Average


1-7GHz_Horizontal_802.11ac20_5825MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band4-AC20-5825

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 6877.000	-3.12	55.92	52.80	68.20	-15.40 Peak


1-7GHz_Vertical_802.11ac20_5825MHz



Condition : Vertical
 Project No. : 2501X19230E-RF
 Tester : Zenos Qiao
 Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
 Note : 5GWiFi-Band4-AC20-5825

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 6514.000	-2.97	55.59	52.62	68.20	-15.58 Peak


7-18GHz_Horizontal_Peak_802.11ac20_5825MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band4-AC20-5825

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	11650.000	3.44	49.77	53.21	74.00	-20.79	Peak
2	17991.750	13.16	47.86	61.02	74.00	-12.98	Peak


7-18GHz_Horizontal_Average_802.11ac20_5825MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 5GWiFi-Band4-AC20-5825

Freq	Factor	Read		Limit	Over	Remark
		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 17993.130	13.17	34.28	47.45	54.00	-6.55	Average


7-18GHz_Vertical_Peak_802.11ac20_5825MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band4-AC20-5825

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	11650.000	3.44	49.63	53.07	74.00	-20.93	Peak
2	17953.250	12.97	49.15	62.12	74.00	-11.88	Peak


7-18GHz_Vertical_Average_802.11ac20_5825MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 5GWiFi-Band4-AC20-5825

Freq	Factor	Read		Limit	Over	Remark
		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 17995.880	13.18	34.19	47.37	54.00	-6.63	Average


1-7GHz_Horizontal_802.11ac40_5795MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band4-AC40-5795

Freq		Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz		dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	6469.750	-2.91	57.01	54.10	68.20	-14.10	Peak


1-7GHz_Vertical_802.11ac40_5795MHz



Condition : Vertical
 Project No. : 2501X19230E-RF
 Tester : Zenos Qiao
 Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
 Note : 5GWiFi-Band4-AC40-5795

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	6455.500	-2.88	55.59	52.71	68.20	-15.49	Peak


7-18GHz_Horizontal_Peak_802.11ac40_5795MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band4-AC40-5795

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	11590.000	3.21	49.32	52.53	74.00	-21.47	Peak
2	17976.630	13.09	48.59	61.68	74.00	-12.32	Peak


7-18GHz_Horizontal_Average_802.11ac40_5795MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 5GWiFi-Band4-AC40-5795

Freq	Factor	Read		Limit	Over	Remark
		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 17998.630	13.19	34.27	47.46	54.00	-6.54	Average


7-18GHz_Vertical_Peak_802.11ac40_5795MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band4-AC40-5795

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	11590.000	3.21	49.18	52.39	74.00	-21.61	Peak
2	17883.130	12.39	49.05	61.44	74.00	-12.56	Peak


7-18GHz_Vertical_Average_802.11ac40_5795MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 5GWiFi-Band4-AC40-5795

Freq Factor		Read Level		Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 17998.630	13.19	34.16	47.35	54.00	-6.65	Average


1-7GHz_Horizontal_802.11ax20_5825MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band4-AX20-5825

	Freq	Factor	Read		Limit	Over	Remark
			Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	6394.750	-2.94	55.19	52.25	68.20	-15.95	Peak


1-7GHz_Vertical_802.11ax20_5825MHz



Condition : Vertical
 Project No. : 2501X19230E-RF
 Tester : Zenos Qiao
 Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
 Note : 5GWiFi-Band4-AX20-5825

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 6888.250	-3.11	55.84	52.73	68.20	-15.47 Peak


7-18GHz_Horizontal_Peak_802.11ax20_5825MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band4-AX20-5825

Freq Factor		Read		Limit	Over	Remark
MHz	dB/m	Level	Level	Line	Limit	
		dBuV	dBuV/m	dBuV/m	dB	
1 11650.000	3.44	49.59	53.03	74.00	-20.97	Peak
2 17891.380	12.54	48.67	61.21	74.00	-12.79	Peak


7-18GHz_Horizontal_Average_802.11ax20_5825MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 5GWiFi-Band4-AX20-5825

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 17975.250	13.08	34.41	47.49	54.00	-6.51 Average


7-18GHz_Vertical_Peak_802.11ax20_5825MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band4-AX20-5825

Freq Factor		Read	Limit	Over	Remark
MHz	dB/m	Level	Level	Line	
		dBuV	dBuV/m	dBuV/m	dB
1 11650.000	3.44	50.27	53.71	74.00	-20.29 Peak
2 17997.250	13.19	48.56	61.75	74.00	-12.25 Peak


7-18GHz_Vertical_Average_802.11ax20_5825MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 5GWiFi-Band4-AX20-5825

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	17989.000	13.14	34.25	47.39	54.00	-6.61	Average


1-7GHz_Horizontal_802.11ax40_5795MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band4-AX40-5795

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	6544.000	-3.03	55.75	52.72	68.20	-15.48	Peak


1-7GHz_Vertical_802.11ax40_5795MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band4-AX40-5795

Freq Factor		Read	Limit	Over	Remark
MHz	dB/m	Level	Level	Line	
		dBuV	dBuV/m	dBuV/m	dB
1	6513.250	-2.97	56.20	53.23	68.20 -14.97 Peak


7-18GHz_Horizontal_Peak_802.11ax40_5795MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band4-AX40-5795

Freq	Factor	Read		Limit	Over	Remark
		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 11590.000	3.21	49.14	52.35	74.00	-21.65	Peak
2 17921.630	12.81	48.71	61.52	74.00	-12.48	Peak


7-18GHz_Horizontal_Average_802.11ax40_5795MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : 5GWiFi-Band4-AX40-5795

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 17997.250	13.19	34.28	47.47	54.00	-6.53	Average


7-18GHz_Vertical_Peak_802.11ax40_5795MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band4-AX40-5795

Freq Factor		Read	Limit	Over	Remark
MHz	dB/m	Level	Level	Line	
		dBuV	dBuV/m	dBuV/m	dB
1 11590.000	3.21	49.82	53.03	74.00	-20.97 Peak
2 17987.630	13.13	48.33	61.46	74.00	-12.54 Peak

7-18GHz_Vetical_Average_802.11ax40_5795MHz




Condition : Vertical
 Project No. : 2501X19230E-RF
 Tester : Zenos Qiao
 Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
 Note : 5GWiFi-Band4-AX40-5795

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 17998.630	13.19	34.20	47.39	54.00	-6.61	Average

18-40GHz (Only Listed with the worst harmonic margin test plot)


18-40GHz_Horizontal_802.11a_5200MHz



Condition : Horizontal
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band1-A-5200

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 39889.980	22.25	36.84	59.09	80.00	-20.91	Peak

18-40GHz_Vertical_802.11a_5200MHz



Condition : Vertical
Project No. : 2501X19230E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band1-A-5200

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 38855.860	22.25	36.81	59.06	80.00	-20.94	Peak

RF Conducted data**26dB attenuated below the channel power****Test Information:**

Sample No.:	39TF-3	Test Date:	2025/10/04
Test Site:	RF	Test Mode:	Transmitting
Tester:	Kungfumaster Liang	Test Result:	Pass

Environmental Conditions:


Temperature: (°C)	24.8	Relative Humidity: (%)	51	ATM Pressure: (kPa)	101.3
-----------------------------	------	----------------------------------	----	-------------------------------	-------

Test Data:**5150-5250MHz**

Mode	Test Frequency (MHz)	Result (dBm)	Limit (dBm)	Verdict
802.11a	5240	-27.05	-12.18	Pass
802.11ac20	5240	-25.31	-12.11	Pass
802.11ac40	5230	-30.79	-12.08	Pass
802.11ax20_RU_FULL	5240	-25.58	-12.02	Pass
802.11ax40_RU_FULL	5230	-29.96	-11.94	Pass


5150-5250MHz

802.11a_5240MHz




ProjectNo.:2501X19230E-RF Tester:Kungfumaister Liang
Date: 4.OCT.2025 10:40:07

802.11ac20_5240MHz




ProjectNo.:2501X19230E-RF Tester:Kungfumaister Liang
Date: 4.OCT.2025 10:56:03

802.11ac40_5230MHz




ProjectNo.:2501X19230E-RF Tester:Kungfumaister Liang
Date: 4.OCT.2025 11:04:27

802.11ax20_5240MHz_RU_FULL



ProjectNo.:2501X19230E-RF Tester:Kungfumaister Liang
Date: 4.OCT.2025 11:18:33

802.11ax40_5230MHz_RU_FULL



ProjectNo.:2501X19230E-RF Tester:Kungfumaister Liang
Date: 4.OCT.2025 11:26:24

Emission Bandwidth**Test Information:**

Sample No.:	39TF-3	Test Date:	2025/10/04
Test Site:	RF	Test Mode:	Transmitting
Tester:	Kungfumaster Liang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	24.8	Relative Humidity: (%)	51	ATM Pressure: (kPa)	101.3
-----------------------------	------	----------------------------------	----	-------------------------------	-------

Test Data:**26dB Emission Bandwidth
5150-5250MHz**

Mode	Test Frequency (MHz)	Result (MHz)
802.11a	5180	22.551
	5200	22.310
	5240	22.485
802.11ac20	5180	22.406
	5200	22.416
	5240	22.705
802.11ac40	5190	41.542
	5230	41.241
802.11ax20_RU_FULL	5180	22.847
	5200	22.511
	5240	22.720
802.11ax40_RU_FULL	5190	41.642
	5230	41.742

5250-5350MHz

Mode	Test Frequency (MHz)	Result (MHz)
802.11a	5260	22.273
	5280	22.104
	5320	22.158
802.11ac20	5260	22.573
	5280	22.536
	5320	22.741
802.11ac40	5270	41.141
	5310	41.542
802.11ax20_RU_FULL	5260	22.675
	5280	22.714
	5320	22.889
802.11ax40_RU_FULL	5270	41.542
	5310	41.542

5470-5725MHz

Mode	Test Frequency (MHz)	Result (MHz)
802.11a	5500	21.944
	5580	22.003
	5700	22.168
	5720	22.039
802.11ac20	5500	22.370
	5580	22.284
	5700	22.451
	5720	22.481
802.11ac40	5510	41.041
	5550	41.241
	5670	41.241
	5710	41.241
802.11ax20_RU_FULL	5500	22.979
	5580	22.838
	5700	22.445
	5720	22.856
802.11ax40_RU_FULL	5510	41.642
	5550	41.341
	5670	41.842
	5710	41.441

**6dB Emission Bandwidth
5725-5850MHz**

Mode	Test Frequency (MHz)	Result (MHz)	Limit (MHz)	Verdict
802.11a	5745	16.517	0.5	Pass
	5785	16.517	0.5	Pass
	5825	16.517	0.5	Pass
802.11ac20	5745	17.768	0.5	Pass
	5785	17.868	0.5	Pass
	5825	17.718	0.5	Pass
802.11ac40	5755	36.537	0.5	Pass
	5795	36.537	0.5	Pass
802.11ax20_RU_FULL	5745	19.119	0.5	Pass
	5785	19.269	0.5	Pass
	5825	19.269	0.5	Pass
802.11ax40_RU_FULL	5755	38.338	0.5	Pass
	5795	38.238	0.5	Pass