



APPENDIX I RADIO FREQUENCY EXPOSURE

LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

EUT Specification

EUT	150Mbps Wireless N ADSL2+ Modem Router								
Model	DL4312; DL4312D								
RF Module	Realtek	Model:	RTL8188ER-CG						
Model Discrepancy	All the model numbers (list on this report) are identical, just for marketing purpose only except Antenna. <table border="1"><thead><tr><th>Model Number</th><th>Antenna</th></tr></thead><tbody><tr><td>DL4312</td><td>Fixed</td></tr><tr><td>DL4312D</td><td>Detachable</td></tr></tbody></table>			Model Number	Antenna	DL4312	Fixed	DL4312D	Detachable
Model Number	Antenna								
DL4312	Fixed								
DL4312D	Detachable								
Frequency band (Operating)	☒ 802.11b/g/n HT20: 2.412GHz ~ 2.462GHz 802.11n HT40: 2.422GHz ~ 2.452GHz ☐ Others								
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation) ☐ Others								
Exposure classification	☐ Occupational/Controlled exposure (S = 5mW/cm ²) ☒ General Population/Uncontrolled exposure (S=1mW/cm ²)								
Antenna Specification	2.4GHz: Antenna Gain : 5.00 dBi (Numeric gain 3.16)								
Maximum Average output power	IEEE 802.11b Mode: 12.43 dBm (17.498 mW) IEEE 802.11g Mode: 13.86 dBm (24.322 mW) IEEE 802.11n HT 20 Mode: 13.67 dBm (23.281 mW) IEEE 802.11n HT 40 Mode: 13.66 dBm (23.227 mW)								
Maximum Tune up Power	IEEE 802.11b Mode: 13.00 dBm (19.953 mW) IEEE 802.11g Mode: 15.00 dBm (31.623 mW) IEEE 802.11n HT 20 Mode: 14.00 dBm (25.119 mW) IEEE 802.11n HT 40 Mode: 15.00 dBm (31.623 mW)								
Evaluation applied	☒ MPE Evaluation* ☐ SAR Evaluation ☐ N/A								



Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	2014/04/28	Initial Issue	ALL	Scott Hsu



TEST RESULTS

No non-compliance noted.

Calculation

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{377}$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377 d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P / 1000) \times G}{377 \times (d / 100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \textbf{Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

**Maximum Permissible Exposure**

Substituting the MPE safe distance using $d = 20$ cm into Equation 1:

$$S = 0.000199 \times P \times G$$

Where P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

IEEE 802.11b mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
11	2462	19.953	3.16	20	0.0125	1

IEEE 802.11g mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
6	2437	31.623	3.16	20	0.0199	1

IEEE 802.11n HT20 mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
6	2437	25.119	3.16	20	0.0158	1

IEEE 802.11n HT40 mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
6	2437	31.623	3.16	20	0.0199	1