

IEEE C95.1**KDB 447498 D03****47 C.F.R. Part 1, Subpart I, Section 1.1310****47 C.F.R. Part 2, Subpart J, Section 2.1091****RF EXPOSURE REPORT****For****300Mbps Wireless N VDSL2+ Modem Router****Model: DL4323U****Trade Name: netis****Issued for****NETIS SYSTEMS CO., LTD****4F & 5F, R&D Building, Oriental Cyberport, High-Tech Industrial Park,
Nanshan, Shenzhen, China****Issued by****Compliance Certification Services Inc.****Hsinchu Lab.****NO. 989-1, Wenshan Rd., Shangshan Village,
Qionglin Township, Hsinchu County 30741, Taiwan (R.O.C.)****<http://www.ccsrf.com>****service@ccsrf.com****Issued Date: October 28, 2015**

Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF or any government agencies. The test results of this report relate only to the tested sample identified in this report.



Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	10/28/2015	Initial Issue	All Page	Gloria Chang



TABLE OF CONTENTS

1. LIMIT	4
2. EUT SPECIFICATION.....	4
3. TEST RESULTS	5
4. MAXIMUM PERMISSIBLE EXPOSURE.....	6

1. Limit

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

2. EUT Specification

Product Name	300Mbps Wireless N VDSL2+ Modem Router
Model Number	DL4323U
Identify Number	T150925D02
Received Date	September 25, 2015
Frequency band (Operating)	☒ 802.11b/g/gn HT20: 2412MHz ~ 2462MHz 802.11gn HT40: 2422MHz ~ 2452MHz ☐ Others
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation) ☐ Others
Exposure classification	☐ Occupational/Controlled exposure ($S = 5\text{mW}/\text{cm}^2$) ☒ General Population/Uncontrolled exposure ($S=1\text{mW}/\text{cm}^2$)
Antenna Specification	Dipole Antenna × 2(Fixed) : Antenna 1 Gain : 5.26 dBi (Numeric gain: 3.36) Antenna 2 Gain : 5.26 dBi (Numeric gain: 3.36) Dipole Antenna × 2(Detachable) : Antenna 1 Gain : 5.19 dBi (Numeric gain: 3.30) Antenna 2 Gain : 5.19 dBi (Numeric gain: 3.30)
Maximum Peak output power	IEEE 802.11b Mode: 19.59 dBm (90.991 mW) IEEE 802.11g Mode: 25.66 dBm (368.129 mW) IEEE 802.11gn HT 20 Mode: 26.83 dBm (481.948 mW) IEEE 802.11gn HT 40 Mode: 25.06 dBm (320.627 mW)
Evaluation applied	☒ MPE Evaluation* ☐ SAR Evaluation ☐ N/A

3. Test Results

No non-compliance noted.

Calculation

$$\text{Given } E = \frac{\sqrt{30 \times P \times G}}{d} \quad \& \quad S = \frac{E^2}{377}$$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in watts / meter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377 d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \textbf{Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

4. Maximum Permissible Exposure

Substituting the MPE safe distance using $d = 20$ cm into Equation 1:

$$S = 0.000199 \times P \times G$$

Where

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

IEEE 802.11b mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm ²)
2462	90.991	3.36	20	0.0608	1

IEEE 802.11g mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm ²)
2437	368.129	3.36	20	0.2461	1

IEEE 802.11gn HT20 mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm ²)
2412	481.948	3.36	20	0.3222	1

IEEE 802.11gn HT40 mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm ²)
2422	320.627	3.36	20	0.2144	1