

RF Exposure evaluation

FCC ID: T58E3R

Exposure category: General population/uncontrolled environment

EUT Type: Production Unit

Device Type: Mobile Device

1. Reference

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

KDB447498 D01: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies

2. Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

3. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

4. Antenna Information

NEO X can only use antennas certificated as follows provided by manufacturer;

Internal Identification	Antenna Identification in Internal photos	Antenna type and antenna number	Operate frequency band	Maximum antenna gain
Antenna 0	2.4G/5G Wifi Chain 0	External antenna	2.4GHz – 2.5 GHz 5.1GHz – 5.8 GHz	2.00 dBi
Antenna 1	2.4G/5G Wifi Chain 1	External antenna	2.4GHz – 2.5 GHz 5.1GHz – 5.8 GHz	2.00 dBi

5. Conducted power

[2.4GHz WLAN]

Mode	Channel	Frequency	Peak Conducted Output Power (dBm)	
			Antenna0	Antenna1
<i>IEEE 802.11b</i>	1	2412	18.38	17.12
	7	2437	19.04	17.81
	13	2462	18.51	17.53
<i>IEEE 802.11g</i>	1	2412	20.94	19.60
	7	2437	21.26	20.40
	13	2462	20.83	20.14
<i>IEEE 802.11n HT20</i>	1	2412	20.70	19.69
	7	2437	21.05	20.54
	13	2462	20.67	20.25
<i>IEEE 802.11n HT40</i>	3	2422	20.46	19.68
	7	2437	20.41	19.87
	11	2452	19.91	19.52

[5GHz WLAN Band 1]

Mode	Channel	Frequency	Average Conducted Output Power (dBm)	
			Antenna0	Antenna1
IEEE 802.11a	36	5180	11.63	11.30
	40	5200	12.04	12.67
	48	5240	12.75	13.74
IEEE 802.11n HT20	36	5180	11.14	9.96
	40	5200	11.71	10.96
	48	5240	12.55	12.17
IEEE 802.11ac VHT20	36	5180	11.19	10.04
	40	5200	11.67	11.02
	48	5240	12.57	12.20
IEEE 802.11n HT40	38	5190	11.03	10.22
	46	5230	12.11	11.72
IEEE 802.11ac VHT40	38	5190	10.95	10.27
	46	5230	12.06	11.78
IEEE 802.11ac VHT80	42	5210	11.58	10.94

[5GHz WLAN Band 3]

Mode	Channel	Frequency	Average Conducted Output Power (dBm)	
			Antenna0	Antenna1
IEEE 802.11a	149	5745	13.30	8.78
	157	5785	13.85	9.04
	165	5825	14.35	8.63
IEEE 802.11n HT20	149	5745	13.20	7.21
	157	5785	13.83	7.58
	165	5825	14.31	8.59
IEEE 802.11ac VHT20	149	5745	13.20	7.21
	157	5785	13.84	7.56
	165	5825	14.29	8.52
IEEE 802.11n HT40	151	5755	13.52	7.25
	159	5795	13.79	7.27
IEEE 802.11ac VHT40	151	5755	13.43	7.20
	159	5795	13.78	7.50
IEEE 802.11ac VHT80	155	5775	13.58	7.08

6. Manufacturing Tolerance

2.4GHz WLAN

IEEE 802.11b (Peak)						
Frequency (MHz)	Antenna 0			Antenna 1		
	2412	2437	2462	2412	2437	2462
Target (dBm)	19.0	19.0	19.0	18.0	18.0	18.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
IEEE 802.11g (Peak)						
Frequency (MHz)	Antenna 0			Antenna 1		
	2412	2437	2462	2412	2437	2462
Target (dBm)	21.0	21.0	21.0	20.0	20.0	20.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
IEEE 802.11n HT20 (Peak)						
Frequency (MHz)	Antenna 0			Antenna 1		
	2412	2437	2462	2412	2437	2462
Target (dBm)	21.0	21.0	21.0	20.0	20.0	20.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
IEEE 802.11n HT40 (Peak)						
Frequency (MHz)	Antenna 0			Antenna 1		
	2422	2437	2452	2422	2437	2452
Target (dBm)	20.0	20.0	20.0	19.0	19.0	19.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0

5GHz WLAN Band 1

IEEE 802.11a (Average)						
Frequency (MHz)	Antenna 0			Antenna 1		
	5180	5200	5240	5180	5200	5240
Target (dBm)	11.0	12.0	12.0	11.0	12.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)						
Frequency (MHz)	Antenna 0			Antenna 1		
	5180	5200	5240	5180	5200	5240
Target (dBm)	11.0	11.0	12.0	10.0	10.0	12.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
IEEE 802.11ac VHT20 (Average)						
Frequency (MHz)	Antenna 0			Antenna 1		
	5180	5200	5240	5180	5200	5240
Target (dBm)	11.0	11.0	12.0	10.0	11.0	12.0

Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
IEEE 802.11n HT40 (Average)						
Frequency (MHz)	Antenna 0			Antenna 1		
	5190	5230		5190	5230	
Target (dBm)	11.0	12.0		10.0	11.0	
Tolerance $\pm$ (dB)	1.0	1.0		1.0	1.0	
IEEE 802.11ac VHT40 (Average)						
Frequency (MHz)	Antenna 0			Antenna 1		
	5190	5230		5190	5230	
Target (dBm)	11.0	12.0		10.0	11.0	
Tolerance $\pm$ (dB)	1.0	1.0		1.0	1.0	
IEEE 802.11ac VHT80 (Average)						
Frequency (MHz)	Antenna 0			Antenna 1		
	5210			5210		
Target (dBm)	11.0			10.0		
Tolerance $\pm$ (dB)	1.0			1.0		

5GHz WLAN Band 3

IEEE 802.11a (Average)						
Frequency (MHz)	Antenna 0			Antenna 1		
	5745	5785	5825	5745	5785	5825
Target (dBm)	14.0	14.0	14.0	9.0	9.0	9.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)						
Frequency (MHz)	Antenna 0			Antenna 1		
	5745	5785	5825	5745	5785	5825
Target (dBm)	14.0	14.0	14.0	8.0	8.0	8.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
IEEE 802.11ac VHT20 (Average)						
Frequency (MHz)	Antenna 0			Antenna 1		
	5745	5785	5825	5745	5785	5825
Target (dBm)	14.0	14.0	14.0	8.0	8.0	8.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
IEEE 802.11n HT40 (Average)						
Frequency (MHz)	Antenna 0			Antenna 1		
	5755	5795		5755	5795	
Target (dBm)	14.0	14.0		8.0	8.0	
Tolerance $\pm$ (dB)	1.0	1.0		1.0	1.0	
IEEE 802.11ac VHT40 (Average)						
Frequency (MHz)	Antenna 0			Antenna 1		
	5755	5795		5755	5795	
Target (dBm)	14.0	14.0		8.0	8.0	
Tolerance $\pm$ (dB)	1.0	1.0		1.0	1.0	

IEEE 802.11ac VHT80 (Average)		
Frequency (MHz)	Antenna 0	Antenna 1
	5775	5775
Target (dBm)	14.0	8.0
Tolerance $\pm$ (dB)	1.0	1.0

7. Standalone MPE Result

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r=20\text{cm}$, as well as the gain of the used antenna is 3dBi, the RF power density can be obtained.

2.4GHz WLAN

Antenna 0

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW					
IEEE 802.11b	20.00	100.0000	2.00	1.5849	100%	0.0315	1.0000
IEEE 802.11g	22.00	158.4893	2.00	1.5849	100%	0.0500	1.0000
IEEE 802.11n HT20	22.00	158.4893	2.00	1.5849	100%	0.0500	1.0000
IEEE 802.11n HT40	21.00	125.8925	2.00	1.5849	100%	0.0397	1.0000

Antenna 1

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW					
IEEE 802.11b	19.00	79.4328	2.00	1.5849	100%	0.0250	1.0000
IEEE 802.11g	21.00	125.8925	2.00	1.5849	100%	0.0397	1.0000
IEEE 802.11n HT20	21.00	125.8925	2.00	1.5849	100%	0.0397	1.0000
IEEE 802.11n HT40	20.00	100.0000	2.00	1.5849	100%	0.0315	1.0000

5GHz WLAN Band 1

Antenna 0

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW					
IEEE 802.11a	13.00	19.9526	2.00	1.5849	100%	0.0063	1.0000
IEEE 802.11n HT20	13.00	19.9526	2.00	1.5849	100%	0.0063	1.0000
IEEE 802.11ac VHT20	13.00	19.9526	2.00	1.5849	100%	0.0063	1.0000
IEEE 802.11n HT40	13.00	19.9526	2.00	1.5849	100%	0.0063	1.0000
IEEE 802.11ac VHT40	13.00	19.9526	2.00	1.5849	100%	0.0063	1.0000
IEEE 802.11ac VHT80	12.00	15.8489	2.00	1.5849	100%	0.0050	1.0000

Antenna 1

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW					
IEEE 802.11a	14.00	25.1189	2.00	1.5849	100%	0.0079	1.0000
IEEE 802.11n HT20	13.00	19.9526	2.00	1.5849	100%	0.0063	1.0000
IEEE 802.11ac VHT20	13.00	19.9526	2.00	1.5849	100%	0.0063	1.0000
IEEE 802.11n HT40	12.00	15.8489	2.00	1.5849	100%	0.0050	1.0000
IEEE 802.11ac VHT40	12.00	15.8489	2.00	1.5849	100%	0.0050	1.0000
IEEE 802.11ac VHT80	11.00	12.5893	2.00	1.5849	100%	0.0040	1.0000

5GHz WLAN Band 3

Antenna 0

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW					
IEEE 802.11a	15.00	31.6228	2.00	1.5849	100%	0.0100	1.0000
IEEE 802.11n HT20	15.00	31.6228	2.00	1.5849	100%	0.0100	1.0000
IEEE 802.11ac VHT20	15.00	31.6228	2.00	1.5849	100%	0.0100	1.0000
IEEE 802.11n HT40	15.00	31.6228	2.00	1.5849	100%	0.0100	1.0000
IEEE 802.11ac VHT40	15.00	31.6228	2.00	1.5849	100%	0.0100	1.0000
IEEE 802.11ac VHT80	15.00	31.6228	2.00	1.5849	100%	0.0100	1.0000

Antenna 1

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW					
IEEE 802.11a	10.00	10.0000	2.00	1.5849	100%	0.0032	1.0000
IEEE 802.11n HT20	9.00	7.9433	2.00	1.5849	100%	0.0025	1.0000
IEEE 802.11ac VHT20	9.00	7.9433	2.00	1.5849	100%	0.0025	1.0000
IEEE 802.11n HT40	9.00	7.9433	2.00	1.5849	100%	0.0025	1.0000
IEEE 802.11ac VHT40	9.00	7.9433	2.00	1.5849	100%	0.0025	1.0000
IEEE 802.11ac VHT80	9.00	7.9433	2.00	1.5849	100%	0.0025	1.0000

Remark:

1. Output power (Average) including turn-up tolerance;
2. Output power was adjust to duty cycle at 100% if measured duty cycle less than 98%;
3. MPE evaluate distance is 20cm from user manual provide by manufacturer.

8. Summary simultaneous transmission information

Synchronization transmitting between WIFI Ant0 and Ant1

Modulation Type	Work Frequency Band	Transmit Antenna		Antenna 0 Antenna 1 Synchronization transmit
		Antenna 0	Antenna 1	
IEEE 802.11a	5.8G/5.2GHz	Yes	Yes	No
IEEE 802.11b	2.4GHz	Yes	Yes	No
IEEE 802.11g	2.4GHz	Yes	Yes	No
IEEE 802.11n HT20	2.4GHz	Yes	Yes	Yes
IEEE 802.11n HT20	5.8G/5.2GHz	Yes	Yes	Yes
IEEE 802.11n HT40	2.4GHz	Yes	Yes	Yes
IEEE 802.11n HT40	5.8G/5.2GHz	Yes	Yes	Yes
IEEE 802.11ac VHT20	5.8G/5.2GHz	Yes	Yes	Yes
IEEE 802.11ac VHT40	5.8G/5.2GHz	Yes	Yes	Yes
IEEE 802.11ac VHT80	5.8G/5.2GHz	Yes	Yes	Yes

9. Summary simultaneous transmission results

Antenna 0 and Antenna 1 for 2.4G WLAN

Modulation Type	MPE _{Antenna0} (mW/cm ²)	MPE _{Antenna1} (mW/cm ²)	ΣMPE ratios	Limit	Results
IEEE 802.11n HT20	0.0500	0.0397	0.0897	1.0	PASS
IEEE 802.11n HT40	0.0397	0.0315	0.0712	1.0	PASS

Antenna 0 and Antenna 1 for 5G WLAN Band 1

Modulation Type	MPE _{Antenna0} (mW/cm ²)	MPE _{Antenna1} (mW/cm ²)	ΣMPE ratios	Limit	Results
IEEE 802.11n HT20	0.0063	0.0063	0.0126	1.0	PASS
IEEE 802.11ac VHT20	0.0063	0.0063	0.0126	1.0	PASS
IEEE 802.11n HT40	0.0063	0.0050	0.0113	1.0	PASS
IEEE 802.11ac VHT40	0.0063	0.0050	0.0113	1.0	PASS
IEEE 802.11ac VHT80	0.0050	0.0040	0.0090	1.0	PASS

Antenna 0 and Antenna 1 for 5G WLAN Band 3

Modulation Type	MPE _{Antenna0} (mW/cm ²)	MPE _{Antenna1} (mW/cm ²)	ΣMPE ratios	Limit	Results
IEEE 802.11n HT20	0.0100	0.0025	0.0125	1.0	PASS
IEEE 802.11ac VHT20	0.0100	0.0025	0.0125	1.0	PASS
IEEE 802.11n HT40	0.0100	0.0025	0.0125	1.0	PASS

IEEE 802.11ac VHT40	0.0100	0.0025	0.0125	1.0	PASS
IEEE 802.11ac VHT80	0.0100	0.0025	0.0125	1.0	PASS

10. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----THE END OF REPORT-----