



Shenzhen CTL Testing Technology Co., Ltd.
Tel: +86-755-89486194 E-mail: ctl@ctl-lab.com

TEST REPORT

FCC PART 15 SUBPART E 15.407

Report Reference No. : CTL2108095041-WF02

Compiled by:
(position+printed name+signature)

Happy Guo
(File administrators)

Happy Guo

Tested by:
(position+printed name+signature)

Gary Gao
(Test Engineer)

Gary Gao

Approved by:
(position+printed name+signature)

Ivan Xie
(Manager)

Ivan Xie

Product Name : AX1800 Dual-Band Wireless Router

Model/Type reference : N6

List Model(s)..... : N/A

Trade Mark..... : N/A

FCC ID..... : T58N6R

Applicant's name : NETIS SYSTEMS CO., LTD

Address of applicant : Floor 8, Building B, TongFang Information Harbor, No.11
Langshan Road, Nanshan District, Shenzhen, China

Test Firm..... : Shenzhen CTL Testing Technology Co., Ltd.

Address of Test Firm : Floor 1-A, Baisha Technology Park, No.3011, Shahexi Road,
Nanshan District, Shenzhen, China 518055

Test specification..... :

Standard : 47 CFR FCC Part 15 Subpart E 15.407

TRF Originator : Shenzhen CTL Testing Technology Co., Ltd.

Master TRF..... : Dated 2011-01

Date of receipt of test item : Aug. 09, 2021

Date of sampling..... : Aug. 09, 2021

Date of Test Date..... : Aug. 13, 2021- Nov. 02, 2021

Date of Issue : Nov. 03, 2021

Result..... : Pass

Shenzhen CTL Testing Technology Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTL Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTL Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

TEST REPORT

Test Report No. :	CTL2108095041-WF02	Nov. 03, 2021
		Date of issue

Equipment under Test : AX1800 Dual-Band Wireless Router

Sample No. CTL2108095041-S001

Model /Type : N6

Listed Models : N/A

Applicant : **NETIS SYSTEMS CO., LTD**

Address : Floor 8, Building B, TongFang Information Harbor,
No.11 Langshan Road, Nanshan District, Shenzhen,
China

Manufacturer : **NETIS SYSTEMS CO., LTD**

Address : Floor 8, Building B, TongFang Information Harbor,
No.11 Langshan Road, Nanshan District, Shenzhen,
China

Test result	Pass *
-------------	--------

* In the configuration tested, the EUT complied with the standards specified page 5.

The test results presented in this report relate only to the object tested.

This report shall not be reproduced, except in full, without the written approval of the issuing testing laboratory.

**** Modified History ****

[illegible]

Table of Contents**Page**

1. SUMMARY	5
1.1. TEST STANDARDS	5
1.2. TEST DESCRIPTION	5
1.3. TEST FACILITY	6
1.4. STATEMENT OF THE MEASUREMENT UNCERTAINTY	6
2. GENERAL INFORMATION	8
2.1. ENVIRONMENTAL CONDITIONS	8
2.2. GENERAL DESCRIPTION OF EUT	8
2.3. DESCRIPTION OF TEST MODES AND TEST FREQUENCY	9
2.4. EQUIPMENTS USED DURING THE TEST	10
2.5. RELATED SUBMITTAL(s) / GRANT (s)	11
2.6. MODIFICATIONS	11
3. TEST CONDITIONS AND RESULTS	12
3.1. CONDUCTED EMISSIONS TEST	12
3.2. RADIATED EMISSIONS	15
3.3. MAXIMUM CONDUCTED AVERAGE OUTPUT POWER	24
3.4. POWER SPECTRAL DENSITY	25
3.5. EMISSION BANDWIDTH (26dBm BANDWIDTH)	27
3.6. MINIMUM EMISSION BANDWIDTH (6dBm BANDWIDTH)	28
3.7. FREQUENCY STABILITY	29
3.8. ANTENNA REQUIREMENT	30
4. TEST SETUP PHOTOS OF THE EUT	31
5. PHOTOS OF THE EUT	32

1. SUMMARY

1.1. TEST STANDARDS

The tests were performed according to following standards:

[FCC Rules Part 15 Subpart E](#)—Unlicensed National Information Infrastructure Devices

[ANSI C63.10:2013](#) : American National Standard for Testing Unlicensed Wireless Devices

[KDB789033 D02](#): General UNII Test Procedures New Rules v02r01

[KDB 662911 D01 v02r01](#): Emissions Testing of Transmitters with Multiple Outputs in the Same Band

1.2. Test Description

FCC Requirement		
FCC Part 15.207	AC Power Conducted Emission	PASS
FCC Part 15.407(a)	Emission Bandwidth(26dBm Bandwidth)	PASS ^{Note1}
FCC Part 15.407(e)	Minimum Emission Bandwidth(6dBm Bandwidth)	PASS ^{Note2}
FCC Part 15.407(a)	Maximum Conducted Output Power	PASS
FCC Part 15.407(a)	Peak Power Spectral Density	PASS
FCC Part 15.407(g)	Frequency Stability	PASS
FCC Part 15.407(b)	Undesirable emission	PASS
FCC Part 15.407(b)/15.205/15.209	Radiated Emissions	PASS
FCC Part 15.407(h)	Dynamic Frequency Selection	N/A
FCC Part 15.203	Antenna requirement	PASS

Note 1: Apply to U-NII 1, U-NII 2A, and U-NII 2C band.

Note 2: Apply to U-NII 3 band only.

Note 3: N/A means not applicable in this report.

1.3. Test Facility

1.3.1 Address of the test laboratory

Shenzhen CTL Testing Technology Co., Ltd.

Floor 1-A, Baisha Technology Park, No. 3011, Shahexi Road, Nanshan, Shenzhen 518055 China

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.10:2013 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

1.3.2 Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L7497

Shenzhen CTL Testing Technology Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No. 4343.01

Shenzhen CTL Testing Technology Co., Ltd, EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

IC Registration No.: 9618B

CAB identifier: CN0041

The 3m alternate test site of Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements with Registration No.: 9618B on Jan. 22, 2019.

FCC-Registration No.: 399832

Designation No.: CN1216

Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 399832, December 08, 2017.

1.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements" and is documented in the Shenzhen CTL Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CTL laboratory is reported:

Test	Measurement Uncertainty	Notes
Transmitter power conducted	±0.57 dB	(1)
Transmitter power Radiated	±2.20 dB	(1)
Conducted spurious emission 9KHz-40 GHz	±2.20 dB	(1)
Occupied Bandwidth	±0.01ppm	(1)
Radiated Emission 30~1000MHz	±4.10dB	(1)
Radiated Emission Above 1GHz	±4.32dB	(1)

Conducted Disturbance0.15~30MHz	$\pm 3.20\text{dB}$	(1)
---------------------------------	---------------------	-----

- (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

2. GENERAL INFORMATION

2.1. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature:	25°C
Relative Humidity:	55 %
Air Pressure:	101 kPa

2.2. General Description of EUT

Product Name:	AX1800 Dual-Band Wireless Router			
Model/Type reference:	N6			
Power supply:	DC 12V from adapter			
Adapter information 1:	Model: DJ18W-1201500U Input:100-240~ 50/60Hz 0.6A Max Output:12.0V===1.5A 18.0W			
Adapter information 2:	Model: KL-WA120150-D Input:100-240~ 50/60Hz 0.7A Output:12.0V===1.5A			
Hardware version:	PB-7516-M04G-00			
Software version:	V1.0			
WIFI				
Supported type:	20MHz system	40MHz system	80MHz system	160MHz system
	802.11a 802.11n 802.11ac 802.11ax	802.11n 802.11ac 802.11ax	802.11ac 802.11ax	N/A
Operation frequency:	5180-5240MHz 5745-5825MHz	5190-5230MHz 5755MHz,5795MHz	5210MHz; 5775MHz	N/A
Modulation:	OFDM	OFDM	OFDM	N/A
Channel number:	9	4	2	N/A
Channel separation:	20MHz	40MHz	80MHz	N/A
MIMO	Support MIMO 2*2			
Antenna gain:	Antenna 1: 5.0 dBi Antenna 2: 5.0 dBi			
Directional gain:	8.01dBi			

Note1: For more details, please refer to the user's manual of the EUT.

Note2: *Directional gain* = $G_{ANT} + 10 \log(N_{ANT}/N_{SS})$ dBi, where N_{SS} = the number of independent spatial streams of data and G_{ANT} is the antenna gain in dBi. For this devices $N_{SS} = 1$.

2.3. Description of Test Modes and Test Frequency

The Applicant provides communication tools software(QATool_Dbg)to control the EUT for staying in continuous transmitting and receiving mode for testing.

All test performed at the low, middle and high of operational frequency range of each mode.

Operation Frequency List WIFI on 5G Band:

Operating band	20MHz		40MHz		80MHz	
	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
U-NII 1 (5150MHz-5250MHz)	36	5180	38	5190	42	5210
	40	5200				
	44	5220	46	5230		
	48	5240				
U-NII 3 (5725MHz-5850MHz)	149	5745	151	5755	155	5775
	153	5765				
	157	5785	159	5795		
	161	5805				
	165	5825	--	--	--	--

Note:

1. "--"Means no channel(s) available any more.
2. The line display in grey is those Channels/Frequencies select to test in this report for each operation mode.

Data Rate Used:

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate
Maximum Conducted Output Power Power Spectral Density Emission Bandwidth(26dBm Bandwidth) Minimum Emission Bandwidth(6dBm Bandwidth) Undesirable emission Frequency Stability	11a/OFDM	6 Mbps
	11n(20MHz), 11ac(20MHz), 11ax(20MHz)/OFDM	MCS0
	11n(40MHz), 11ac(40MHz) 11ax(40MHz)/OFDM	MCS0
	11ac(80MHz), 11ax(80MHz)/OFDM	MCS0

2.4. Equipments Used during the Test

Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
LISN	R&S	ESH2-Z5	860014/010	2021/05/15	2022/05/14
Bilog Antenna	Sunol Sciences Corp.	JB1	A061713	2021/04/08	2022/04/07
EMI Test Receiver	R&S	ESCI	1166.5950.03	2021/05/18	2022/05/17
Spectrum Analyzer	Agilent	E4407B	MY41440676	2021/05/14	2022/05/13
Spectrum Analyzer	Agilent	N9020A	US46220290	2021/05/14	2022/05/13
Spectrum Analyzer	Keysight	N9020A	MY53420874	2021/05/14	2022/05/13
Controller	EM Electronics	EM 1000	060859	2021/05/19	2022/05/18
Horn Antenna	Ocean Microwave	OBH100400	26999002	2020/11/28	2021/11/27
Horn Antenna	Sunol Sciences Corp.	DRH-118	A062013	2021/05/19	2022/05/18
Active Loop Antenna	Da Ze	ZN30900A	/	2021/05/19	2022/05/18
Amplifier	Agilent	8449B	3008A02306	2021/05/15	2022/05/14
Amplifier	Agilent	8447D	2944A10176	2021/05/15	2022/05/14
Temperature/Humidity Meter	Gangxing	CTH-608	02	2021/05/16	2022/05/15
Power Sensor	Agilent	U2021XA	MY55130004	2021/05/14	2022/05/13
Power Sensor	Agilent	U2021XA	MY55130006	2021/05/14	2022/05/13
Spectrum Analyzer	RS	FSP	1164.4391.38	2021/05/15	2022/05/14

The calibration interval was one year

2.5. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended to comply with Section 15.407 of the FCC Part 15, Subpart E Rules.

2.6. Modifications

No modifications were implemented to meet testing criteria.

3. TEST CONDITIONS AND RESULTS

3.1. Conducted Emissions Test


LIMIT

According to FCC CFR Title 47 Part 15 Subpart C Section 15.207, AC Power Line Conducted Emissions Limits for Licence-Exempt Radio Apparatus as below:

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION



TEST PROCEDURE

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system; a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10:2013.
2. Support equipment, if needed, was placed as per ANSI C63.10:2013.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10:2013.
4. The adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5. All support equipments received AC power from a second LISN, if any.
6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.


TEST RESULTS

Temperature	22.8°C	Humidity	56%
Test Engineer	Gary Gao	Configurations	WLAN5G

Remark:

- Both adapter 1 and adapter 2 list in section 2.2 was test with EUT, only the worst case of adapter 1 was reported as below:
- All WIFI operation modes were tested at Low, Middle, and High channel; only the worst result of 802.11AC20 CH48 was reported as below:
- Both 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz power supply have been tested, only the worst result of 120 VAC, 60 Hz was reported as below:

Test Mode	WIFI	Line:	L																																																																																																																																		
Conducted Emission Measurement File :2021 CE Data :#9874 Date: 2021/10/23 Time: 17:55:46 <table><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB)</th><th>Level (dBuV)</th><th>Limit (dBuV)</th><th>Margin (dB)</th><th>Detector</th><th>P/F</th><th>Remark</th></tr></thead><tbody><tr><td>1</td><td>0.1500</td><td>46.30</td><td>10.04</td><td>56.34</td><td>66.00</td><td>9.66</td><td>peak</td><td>P</td><td></td></tr><tr><td>2</td><td>0.2895</td><td>33.02</td><td>10.03</td><td>43.05</td><td>60.54</td><td>17.49</td><td>peak</td><td>P</td><td></td></tr><tr><td>3</td><td>0.2895</td><td>18.06</td><td>10.03</td><td>28.09</td><td>50.54</td><td>22.45</td><td>AVG</td><td>P</td><td></td></tr><tr><td>4</td><td>0.4650</td><td>21.20</td><td>10.04</td><td>31.24</td><td>46.60</td><td>15.36</td><td>AVG</td><td>P</td><td></td></tr><tr><td>5</td><td>0.4695</td><td>25.84</td><td>10.04</td><td>35.88</td><td>56.52</td><td>20.64</td><td>peak</td><td>P</td><td></td></tr><tr><td>6</td><td>1.0905</td><td>12.24</td><td>10.06</td><td>22.30</td><td>46.00</td><td>23.70</td><td>AVG</td><td>P</td><td></td></tr><tr><td>7</td><td>1.9635</td><td>26.40</td><td>10.07</td><td>36.47</td><td>56.00</td><td>19.53</td><td>peak</td><td>P</td><td></td></tr><tr><td>8</td><td>2.3685</td><td>26.59</td><td>10.08</td><td>36.67</td><td>56.00</td><td>19.33</td><td>peak</td><td>P</td><td></td></tr><tr><td>9</td><td>2.4135</td><td>16.72</td><td>10.09</td><td>26.81</td><td>46.00</td><td>19.19</td><td>AVG</td><td>P</td><td></td></tr><tr><td>10</td><td>3.4260</td><td>14.59</td><td>10.13</td><td>24.72</td><td>46.00</td><td>21.28</td><td>AVG</td><td>P</td><td></td></tr><tr><td>11</td><td>3.5070</td><td>26.16</td><td>10.14</td><td>36.30</td><td>56.00</td><td>19.70</td><td>peak</td><td>P</td><td></td></tr><tr><td>12</td><td>27.8115</td><td>17.48</td><td>10.82</td><td>28.30</td><td>50.00</td><td>21.70</td><td>AVG</td><td>P</td><td></td></tr></tbody></table> Site LAB Limit: FCC Part15 CE-Class B_QP EUT: AX1800 Dual-Band Wireless Router M/N: N6 Mode: WORKING Note: DJ18W-1201500U Company name:NETIS SYSTEMS CO., LTD Phase: L1 Power: AC120V/60Hz Temperature: 25(C) Humidity: 56 %RH				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark	1	0.1500	46.30	10.04	56.34	66.00	9.66	peak	P		2	0.2895	33.02	10.03	43.05	60.54	17.49	peak	P		3	0.2895	18.06	10.03	28.09	50.54	22.45	AVG	P		4	0.4650	21.20	10.04	31.24	46.60	15.36	AVG	P		5	0.4695	25.84	10.04	35.88	56.52	20.64	peak	P		6	1.0905	12.24	10.06	22.30	46.00	23.70	AVG	P		7	1.9635	26.40	10.07	36.47	56.00	19.53	peak	P		8	2.3685	26.59	10.08	36.67	56.00	19.33	peak	P		9	2.4135	16.72	10.09	26.81	46.00	19.19	AVG	P		10	3.4260	14.59	10.13	24.72	46.00	21.28	AVG	P		11	3.5070	26.16	10.14	36.30	56.00	19.70	peak	P		12	27.8115	17.48	10.82	28.30	50.00	21.70	AVG	P	
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark																																																																																																																												
1	0.1500	46.30	10.04	56.34	66.00	9.66	peak	P																																																																																																																													
2	0.2895	33.02	10.03	43.05	60.54	17.49	peak	P																																																																																																																													
3	0.2895	18.06	10.03	28.09	50.54	22.45	AVG	P																																																																																																																													
4	0.4650	21.20	10.04	31.24	46.60	15.36	AVG	P																																																																																																																													
5	0.4695	25.84	10.04	35.88	56.52	20.64	peak	P																																																																																																																													
6	1.0905	12.24	10.06	22.30	46.00	23.70	AVG	P																																																																																																																													
7	1.9635	26.40	10.07	36.47	56.00	19.53	peak	P																																																																																																																													
8	2.3685	26.59	10.08	36.67	56.00	19.33	peak	P																																																																																																																													
9	2.4135	16.72	10.09	26.81	46.00	19.19	AVG	P																																																																																																																													
10	3.4260	14.59	10.13	24.72	46.00	21.28	AVG	P																																																																																																																													
11	3.5070	26.16	10.14	36.30	56.00	19.70	peak	P																																																																																																																													
12	27.8115	17.48	10.82	28.30	50.00	21.70	AVG	P																																																																																																																													



Remark: Level(dBuV)=Reading(dBuV) + Factor(dB)

Margin=Limit(dBuV/m)- Level(dBuV/m)

3.2. Radiated Emissions

Limit

The maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Undesirable emission limits

Requirement	Limit(EIRP)	Limit (Field strength at 3m) ^{Note1}
15.407(b)(1)	PK:-27(dBm/MHz)	PK:68.2(dBμV/m)
15.407(b)(2)		
15.407(b)(3)		
15.407(b)(4)		

Note1: The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000\sqrt{30P}}{3} \mu\text{V/m, where P is the eirp (Watts)}$$


- (5) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209
- (6) In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a)

Radiated emission limits


Frequency (MHz)	Distance (Meters)	Radiated (dBμV/m)	Radiated (μV/m)
0.009-0.49	3	$20\log(2400/F(\text{KHz}))+40\log(300/3)$	$2400/F(\text{KHz})$
0.49-1.705	3	$20\log(24000/F(\text{KHz}))+40\log(30/3)$	$24000/F(\text{KHz})$
1.705-30	3	$20\log(30)+40\log(30/3)$	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

TEST CONFIGURATION


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



Test Procedure

- Below 1GHz measurement the EUT is placed on a turntable which is 0.8m above ground plane, and above 1GHz measurement EUT was placed on a low permittivity and low loss tangent turn table which is 1.5m above ground plane.
- Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT
- And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- Repeat above procedures until all frequency measurements have been completed.
- Radiated emission test frequency band from 9KHz to 40GHz.
- The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
9KHz-30MHz	Active Loop Antenna	3
30MHz-1GHz	Bilog Antenna	3
1GHz-18GHz	Horn Antenna	3
18GHz-25GHz	Horn Antennna	1

- Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
9KHz-150KHz	RBW=200Hz/VBW=3KHz, Sweep time=Auto	QP
150KHz-30MHz	RBW=9KHz/VBW=100KHz, Sweep time=Auto	QP
30MHz-1GHz	RBW=120KHz/VBW=1000KHz, Sweep time=Auto	QP
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak

TEST RESULTS

Temperature	22.8°C	Humidity	56%
Test Engineer	Gary Gao	Configurations	WLAN5G

Remark:

- Both adapter 1 and adapter 2 list in section 2.2 was test with EUT, only the worst case of adapter 1 was reported as below:
- This test was performed with EUT in X, Y, Z position and the worse case was found when EUT in X position.
- All WIFI operation modes have been tested for below 1GHz test, only the worst case 802.11ac20 CH48 of U-NII 1 band was recorded.
- All WIFI operation modes have been tested for above 1GHz test, only the worst case 802.11ac20 mode was recorded.
- All WIFI operation modes have been tested for U-NII 3 bandedge test, only the worst case of 802.11ac20 mode was recorded.
- Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, and the emission levels from 9kHz to 30MHz are attenuated 20dB below the limit and not recorded in report.

For 30MHz-1GHz

Horizontal

Radiated Emission Measurement


File :20160121

Data :#2085

Date: 2021/10/23

Time: 18:45:46

80.0 dBuV/m



Site CTL 966 Chamber 2

Polarization: **Horizontal**

Temperature: 26(C)

Limit: FCC_PART15_B_03m_QP

Test Voltage: AC120V/60Hz

Humidity: 60 %

EUT: AX1800 Dual-Band Wireless Router

Distance: 3m

M/N: N6

Mode: WORKING

Note: DJ18W-1201500U

Comany name: NETIS SYSTEMS CO., LTD

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	38.0114	48.87	-17.32	31.55	40.00	8.45	peak	300	284	P	
2	48.1625	46.13	-15.66	30.47	40.00	9.53	peak	400	359	P	
3	76.6461	53.70	-21.53	32.17	40.00	7.83	peak	400	271	P	
4	500.3009	49.30	-10.38	38.92	46.00	7.08	peak	100	136	P	
5	628.3745	45.40	-7.91	37.49	46.00	8.51	peak	200	84	P	
6	755.3872	44.29	-5.73	38.56	46.00	7.44	peak	100	250	P	

Vertical

Radiated Emission Measurement


File :20160121

Data :#2086

Date: 2021/10/23

Time: 18:51:27

80.0 dBuV/m



Site CTL 966 Chamber 2

Polarization: **Vertical**

Temperature: 26(C)

Limit: FCC_PART15_B_03m_QP

Test Voltage: AC120V/60Hz

Humidity: 60 %

EUT: AX1800 Dual-Band Wireless Router

Distance: 3m

M/N: N6

Mode: WORKING

Note: DJ18W-1201500U

Comany name: NETIS SYSTEMS CO., LTD

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	35.7490	52.60	-18.04	34.56	40.00	5.44	peak	100	261	P	
2	46.0970	48.91	-15.80	33.11	40.00	6.89	peak	100	171	P	
3	56.8913	51.71	-16.20	35.51	40.00	4.49	peak	100	103	P	
4	75.3141	57.72	-21.46	36.26	40.00	3.74	peak	200	347	P	
5	250.3010	55.40	-15.57	39.83	46.00	6.17	peak	100	37	P	
6	755.3872	47.46	-5.73	41.73	46.00	4.27	peak	100	299	P	

Remark: Level(dBuV)=Reading(dBuV) + Factor(dB)

Margin= Limit(dBuV/m)-Level(dBuV/m)


Tested Channel	Frequency (MHz)	Emission Level (dBuV/m)	Detector Mode	ANT Pol	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre amplifier (dB)	Correction Factor (dB/m)
149 (5745MHz)	11490.00	56.44	PK	H	68.20	11.76	57.12	39.69	12.90	53.27	-0.68
	11490.00	48.75	AV	H	54.00	5.25	49.43	39.69	12.90	53.27	-0.68
	--	--	--	--	--	--	--	--	--	--	--
157 (5785MHz)	11570.00	57.18	PK	H	68.20	11.02	57.61	39.71	13.05	53.19	-0.43
	11570.00	49.08	AV	H	54.00	4.92	49.51	39.71	13.05	53.19	-0.43
	--	--	--	--	--	--	--	--	--	--	--
165 (5825MHz)	11650.00	60.57	PK	H	68.20	7.63	60.75	39.73	13.19	53.10	-0.18
	11650.00	51.24	AV	H	54.00	2.76	51.42	39.73	13.19	53.10	-0.18
	--	--	--	--	--	--	--	--	--	--	--



REMARKS:

1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
3. Margin value = Limit value- Emission level.
4. --Other emission levels are attenuated 20dB below the limit and not recorded in report.
5. RBW1MHz VBW3MHz Peak detector is for PK value; RBW 1MHz VBW10Hz Peak detector is for AV value.

Band Edge Test Plots of U-NII 3

802.11ac (VHT20) mode





3.3. Maximum Conducted Average Output Power

Limit

FCC requirement:

For the band 5.15-5.25 GHz.

- (i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi.
- (ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi.
- (iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.
- (iv) For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi.


For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W

Test Procedure

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Spectrum Analyzer.

Test Configuration



Test Results

Raw data reference to Annex for FCC 5G WIFI Appendix B.

3.4. Power Spectral Density

Limit

FCC requirement:

For the band 5.15-5.25 GHz.

- (i) For an outdoor access point operating in the band 5.15 - 5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 MHz band.^{note1}
- (ii) For an indoor access point operating in the band 5.15 - 5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 MHz band.^{note1}
- (iii) For fixed point-to-point access points operating in the band 5.15 - 5.25 GHz, transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi.
- (iv) For mobile and portable client devices in the 5.15 - 5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 MHz band.^{note1}

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands

The maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band.

For the band 5.725 - 5.85 GHz


The maximum power spectral density shall not exceed 30 dBm in any 500 kHz band.^{note1, note2}

Note1: If transmitting antennas of directional gain greater than 6 dBi are used, the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Note2: Fixed point - to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information.

Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW = 1MHz for U-NII 1, U-NII 2A, U-NII C band and 300KHz for U-NII 3 band.
3. Set the VBW $\geq 3 \times$ RBW.
4. Set the span to encompass the entire EBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum power level.

Test Configuration**Test Results**

Raw data reference to Annex for FCC 5G WIFI Appendix C.

3.5. Emission Bandwidth (26dBm Bandwidth)


Limit

N/A

Test Procedure

1. Set resolution bandwidth (RBW) = approximately 1 % of the EBW.
2. Set the video bandwidth (VBW) > RBW.
3. Detector = Peak.
4. Trace mode = Max hold.
5. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW / EBW ratio is approximately 1 %.

Test Configuration



Test Results

Raw data reference to Annex for FCC 5G WIFI Appendix A1, Appendix A2.

3.6. Minimum Emission Bandwidth (6dBm Bandwidth)


Limit

Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

Test Procedure

1. Set resolution bandwidth (RBW) = 100 kHz
2. Set the video bandwidth 3 x RBW.
3. Detector = Peak.
4. Trace mode = Max hold.
5. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Test Configuration



Test Results


Raw data reference to Annex for FCC 5G WIFI Appendix A3.

3.7. Frequency Stability

LIMIT

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the users manual.

TEST CONFIGURATION



TEST PROCEDURE

Frequency Stability under Temperature Variations:

The equipment under test was connected to an external AC or DC power supply and input rated voltage. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. The EUT was placed inside the temperature chamber. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 20°C operating frequency as reference frequency. Turn EUT off and set the chamber temperature to -30°C. After the temperature stabilized for approximately 30 minutes recorded the frequency. Repeat step measure with 10°C increased per stage until the highest temperature of +50°C reached.

Frequency Stability under Voltage Variations:

Set chamber temperature to 20°C. Use a variable AC power supply / DC power source to power the EUT and set the voltage to rated voltage. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency.

Reduce the input voltage to specify extreme voltage variation ($\pm 15\%$) and endpoint, record the maximum frequency change.

TEST RESULTS

The worst data reference to Annex for FCC 5G WIFI Appendix D.

3.8. Antenna Requirement

Standard Applicable


For intentional device, according to FCC 47 CFR Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Test Result:

The device used two External Omni antenna, it is soldered on the PCB and the maximum gain is 5dBi with Directional gain 8.01dBi.

4. Test Setup Photos of the EUT



5. Photos of the EUT

Reference to the test report No. CTL2108095041-WF01

***** End of Report *****