FCC RF EXPOSURE REPORT

FCC ID: T58WF2122R

Project No.	**: 1411C071**
Equipment	**: 300Mbps Wireless N USB Adapter**
Model	**: WF2122**
Applicant	**: NETIS SYSTEMS CO., LTD**
Address	**: 4F&5F R&D Building，Oriental Cyberport, High-Tech Industrial Park, Nanshan, Shenzhen, China**
According:	**: FCC Guidelines for Human Exposure IEEE C95.1**

BTL INC.

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, China.

TEL: +86-769-8318-3000 FAX: +86-769-8319-6000

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain(dBi)
1	N/A	N/A	Dipole	N/A	5.00
2	N/A	N/A	Dipole	N/A	5.00

GENERAL CONCULUSION:

Maximum measured transmitter power:

OutputPower (dBm)	Output Power (mW)	Limit (mW)
9.98	9.95	10

According to FCC KDB447498 V05, Appendix A, SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm
The maximum measured output peak power of this EUT is 9.95mW, less than 10mW at 5mm distance.

Conclusion: No SAR evaluation required since transmitter power is below FCC threshold