
From: Schneider, Joel [mailto:JSchneider@tuvam.com]
Sent: 07/12/2006 10:51 AM
To: Dward ATCB; Murphy, Jolene
Cc: Rupp, Susan
Subject: RE: T5V01EXEMIC_ATCB003647

The formula used to calculate the ERP was $E(\text{dBuV/m}) = 106.92 + \text{ERP}(\text{dBk}) - 20 \log D(\text{km})$.
 $109 \text{ dBuV/m} = 106.92 + \text{ERP}(\text{dBk}) - 20 \log .003 \text{ m}$
 $\text{ERP} = 14.5 \text{ mW, or } 11.6 \text{ dBm}$
 $\text{EIRP} = 11.6 + 2.15, \text{ or } 13.75 \text{ dBm, this would be}$
within 1 dB of SAR report

Substitution method, done as documented in Appendix C of test report, verified ERP/EIRP calculation, but only ERP reported as that is what is requested by Part 15 Subpart D.

-----Original Message-----

From: Dward ATCB [mailto:dward@atcb.com]
Sent: Tuesday, July 11, 2006 3:31 PM
To: Murphy, Jolene
Cc: Schneider, Joel; Rupp, Susan
Subject: RE: T5V01EXEMIC_ATCB003647

Please see comment
Thanks

*Dennis Ward
Evaluation Engineer
American TCB
Certification Resource for the Wireless Industry www.atcb.com
703-847-4700 fax 703-847-6888
direct - 703-880-4841
cell - 209-769-8316*

NOTICE: This E-Mail message and any attachment may contain privileged or company proprietary information. If you received this message in error, please return to the sender.