

TEST REPORT

Applicant Name : RTX Hong Kong Ltd.
Address : 8/F Corporation Square, 8 Lam Lok Street, Kowloon Bay,
Kowloon, Hong Kong
Report Number : RA230310-11484E-RFA1
FCC ID: T7HX7452
IC: 4979B-X7452

Test Standard (s)

FCC PART 15D; RSS-GEN ISSUE 5, FEBRUARY 2021 AMENDMENT 2; RSS-213, ISSUE 3,
MARCH 2015

Sample Description


Product Type: Wireless headset base station
Model No.: CB8421
Multiple Model(s) No.: N/A
Trade Mark: poly
Date Received: 2023/03/10
Report Date: 2023/05/05

Test Result:	Pass*
--------------	-------

* In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

Approved By:



Roger Ling
EMC Engineer



Candy Li
EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk "★". Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China

Tel: +86 755-26503290

Fax: +86 755-26503290

Web: www.atc-lab.com

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	4
GENERAL INFORMATION.....	5
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
OBJECTIVE	5
TEST METHODOLOGY	6
MEASUREMENT UNCERTAINTY	6
TEST FACILITY	6
SYSTEM TEST CONFIGURATION	7
DESCRIPTION OF TEST CONFIGURATION	7
EQUIPMENT MODIFICATIONS	7
SUPPORT EQUIPMENT LIST AND DETAILS	7
EXTERNAL I/O CABLE.....	7
BLOCK DIAGRAM OF TEST SETUP	8
SUMMARY OF TEST RESULTS	9
TEST EQUIPMENT LIST	10
FCC §1.1310 & §2.1091 – MAXIMUM PERMISSIBLE EXPOSURE (MPE)	12
APPLICABLE STANDARD	12
RSS-102 § 2.5.2 –EXEMPTION LIMITS FOR ROUTINE EVALUATION-RF EXPOSURE EVALUATION	14
APPLICABLE STANDARD	14
§ 15.317, § 15.203 & RSS-GEN §6.8 ANTENNA REQUIREMENT	15
APPLICABLE STANDARD	15
ANTENNA CONNECTOR CONSTRUCTION	15
§ 15.315, § 15.207 & RSS-213 §5.4 CONDUCTED EMISSIONS.....	16
APPLICABLE STANDARD	16
EUT SETUP	16
EMI TEST RECEIVER SETUP.....	17
TEST PROCEDURE	17
FACTOR & MARGIN CALCULATION	17
TEST DATA	17
§ 15.323 (A) & RSS-213 §5.5 EMISSION BANDWIDTH.....	36
APPLICABLE STANDARD	36
TEST PROCEDURE	36
TEST DATA	37
§ 15.319 (C) & RSS-213 §5.6 PEAK TRANSMIT POWER	47
APPLICABLE STANDARD	47
TEST PROCEDURE	47
TEST DATA	48
§ 15.319 (D) & RSS-213 §5.7 POWER SPECTRAL DENSITY	60
APPLICABLE STANDARD	60
TEST PROCEDURE	60
TEST DATA	61

§ 15.323 (D) & RSS-213 §5.8 EMISSION INSIDE AND OUTSIDE THE SUB-BAND	71
APPLICABLE STANDARD	71
TEST PROCEDURE	72
TEST DATA	72
§ 15.323 (F) & RSS-213 §5.3 FREQUENCY STABILITY	135
APPLICABLE STANDARD	135
TEST PROCEDURE	135
TEST DATA	136
§ 15.323 (C)(E)§ 15.319 (F) & RSS-213 §5.1&§5.2 SPECIFIC REQUIREMENTS FOR UPCS DEVICE	137
APPLICABLE STANDARD	137
TEST PROCEDURE	137
TEST DATA	137
1) AUTOMATIC DISCONTINUATION OF TRANSMISSION.....	138
2) MONITORING TIME	138
3) LOWER MONITORING THRESHOLD.....	138
4) MAXIMUM TRANSMIT PERIOD	139
5) SYSTEM ACKNOWLEDGEMENT	139
6) LEAST INTERFERED CHANNEL (LIC)	140
7) RANDOM WAITING	142
8) MONITORING BANDWIDTH AND REACTION TIME	143
9) MONITORING ANTENNA.....	144
10) MONITORING THRESHOLD RELAXATION	144
11) DUPLEX CONNECTIONS.....	144
12) ALTERNATIVE MONITORING INTERVAL	146
13) FAIR ACCESS	147
14) FRAME REPETITION STABILITY FRAME PERIOD AND JITTER	147

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	RA230310-11484E-RFA1	Original Report	2023-05-05

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

HVIN	CB8421
FVIN	Panther_Rev_A_RC7
Frequency Range	1921.536-1928.448 MHz
Maximum conducted peak output power	19.56dBm
Modulation Technique	GFSK, $\pi/2$ -DBPSK, $\pi/4$ -DQPSK, $\pi/8$ -D8PSK
Antenna Specification*	-3dBi (It is provided by the applicant)
Voltage Range	DC 9.0V from adapter
Sample serial number	Conducted and Radiated Emissions: 231A-1 for IC7, 231A-2 for IC10, 231A-3 for IC12 RF Conducted Test: 231A-7 for IC7 (Assigned by ATC)
Sample/EUT Status	Good condition
Adapter Information	Model:SSA-090100 Input: AC 100-240V,50/60Hz,0.3A Output: DC9.0V,1.0A,9.0W

Note: For poly LCD bord, the device has three IC options in the MCU-PIC16LF1516: IC7, IC10 and IC12. They are made by the same IC manufacturer Microchip and they are used the same software. The different is about the IC package only, the IC7 is QFN28, the IC10 is SSOP28 and the IC12 is SOIC28.

Objective

The tests were performed in order to determine the compliance of the EUT with FCC Part 15-Subpart D, section 15.207, 15.315, 15.317, 15.319 and 15.323 rules. The EMI measurements were performed according to the measurement procedure described in ANSI C63.17 – 2013 and RSS-213 Issue 3, 2GHz License-Exempt Personal Communications Service Devices (PCS) OF THE Canadian Department of Industry rules and RSS-GEN ISSUE 5, FEBRUARY 2021 AMENDMENT 2 of the Innovation, Science and Economic Development Canada rules.

This is a CIIPC(for FCC)/C3PC(forISED C) application of the device; the differences between the original device and the current one are as follows:

1. Add three modulation types: $\pi/2$ -DBPSK, $\pi/4$ -DQPSK, $\pi/8$ -D8PSK.

Based on above difference listed, the modifications will impact all the test items, so in this report, all the test items were performed, test data for the GFSK modulation please refer the report: SZNS220727-34190E-RFA issued on 2022/12/02.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.17 - 2013, American National Standard Methods of Measurement of the Electromagnetic and Operational Compatibility of Unlicensed Personal Communications Services (UPCS) Devices.

All emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		5%
RF output power, conducted		0.73dB
Unwanted Emission, conducted		1.6dB
Emissions, Radiated	30MHz - 1GHz	4.28dB
	1GHz- 18GHz	4.98dB
	18GHz- 26.5GHz	5.06dB
Temperature		1°C
Humidity		6%
Supply voltages		0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the Floor 1, KuMaKe Building, Dongzhou Community, Guangming Street, Guangming District, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189. Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 429 7.01.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0016. The Registration Number is 30241.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured to testing mode which is provided by the manufacturer.

Equipment Modifications

“CMD” exercise software was used and power level was default.


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
DELL	PC	Latitude	11429208685
poly	IP Phone	VVX 150	Unknown

External I/O Cable

Cable Description	Length (m)	From Port	To
Un-shielding Un-Detachable DC Cable	1.8	Adapter	EUT
Un-shielding Detachable RJ45 Cable	1.0	EUT	IP Phone
Un-shielding Detachable Type-C Cable	1.0	EUT	PC

For conducted emission:



SUMMARY OF TEST RESULTS

FCC Rules	ISED Rules	Description of Test	Result
§ 1.1310 & §2.1091	RSS-102 § 2.5.2	Maximum Permissible Exposure(MPE) & Exemption Limits For Routine Evaluation-RF Exposure Evaluation	Compliant
§ 15.317, § 15.203	RSS-Gen §6.8	Antenna Requirement	Compliant
§ 15.315, § 15.207	RSS-213 §5.4	Conducted Emission	Compliant
§ 15.323 (a)	RSS-213 §5.5	Emission Bandwidth	Compliant
§ 15.319 (c)	RSS-213 §5.6	Peak Transmit Power	Compliant
§ 15.319 (d)	RSS-213 §5.7	Power Spectral Density	Compliant
§ 15.323 (d)	RSS-213 §5.8	Emission Inside and Outside the sub-band	Compliant
/	RSS-213 §5.8	Radiated Emission	Compliant
§ 15.323 (f)	RSS-213 §5.3	Frequency Stability	Compliant
§ 15.323 (c)(e) § 15.319 (f)	RSS-213 §5.1&§5.2	Specific Requirements for UPCS	Compliant

Note: EUT have two antennas and cannot transmit simultaneously, pre-scan output power of the two antennas, the worst case antenna 1 was select to test.

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde& Schwarz	EMI Test Receiver	ESCI	100784	2022/11/25	2023/11/24
Rohde & Schwarz	L.I.S.N.	ENV216	101314	2022/11/25	2023/11/24
Anritsu Corp	50 Coaxial Switch	MP59B	6100237248	2022/12/07	2023/12/06
Unknown	RF Coaxial Cable	No.17	N0350	2022/11/25	2023/11/24
Conducted Emission Test Software: e3 19821b (V9)					
Radiated Emissions Test					
Rohde& Schwarz	Test Receiver	ESR	102725	2022/11/25	2023/11/24
Rohde&Schwarz	Spectrum Analyzer	FSV40	101949	2022/11/25	2023/11/24
SONOMA INSTRUMENT	Amplifier	310 N	186131	2022/11/08	2023/11/07
A.H. Systems, inc.	Preamplifier	PAM-0118P	135	2022/11/08	2023/11/07
Quinstar	Amplifier	QLW-18405536-J0	15964001002	2022/11/08	2023/11/07
Schwarzbeck	Bilog Antenna	VULB9163	9163-323	2021/07/06	2024/07/05
Schwarzbeck	Horn Antenna	BBHA9120D	837	2023/02/22	2026/02/21
Schwarzbeck	HORN ANTENNA	BBHA9170	9170-359	2022/12/26	2025/12/25
Radiated Emission Test Software: e3 19821b (V9)					
Unknown	RF Coaxial Cable	No.10	N050	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.11	N1000	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.12	N040	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.13	N300	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.14	N800	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.15	N600	2022/11/25	2023/11/24
Wainwright	High Pass Filter	WHKX3.6/18 G-10SS	5	2022/11/25	2023/11/24

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
RF Conducted test					
Rohde&Schwarz	Spectrum Analyzer	FSV-40	101948	2022/11/25	2023/11/24
WEINSCHTEL	10dB Attenuator	5324	AU 3842	2022/11/25	2023/11/24
AGILENT	Vector Signal Generator	N5182B	MY53052129	2022/11/25	2023/11/24
AGILENT	Vector Signal Generator	N5182A	MY50143401	2022/10/24	2023/10/23
Mini-Circuits	Power Splitter	DC-18000MHz	SF10944151S	2022/11/25	2023/11/24
HP	Frequency Counter	53132A	MY40009475	2023/02/24	2024/02/23
BACL	Temp. & Humid. Chamber	BTH-150-40	30192	2023/02/09	2024/02/08
Manson	DC Power Source	KPS-6604	ATCS-205	NCR	NCR
Fluke	Multi Meter	45	7664009	2022/11/25	2023/11/24

* **Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1310 & §2.1091 – MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to KDB 447498 D04 Interim General RF Exposure Guidance v01, clause 2.1.4 –MPE-Based Exemption:

An alternative to the SAR-based exemption is provided in § 1.1307(b)(3)(i)(C), for a much wider frequency range, from 300 kHz to 100 GHz, applicable for separation distances greater or equal to $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. The MPE-based test exemption condition is in terms of ERP, defined as the product of the maximum antenna gain and the delivered maximum time-averaged power. For this case, a RF source is an RF exempt device if its ERP (watts) is no more than a frequency-dependent value, as detailed tabular form in Appendix B. These limits have been derived based on the basic specifications on Maximum Permissible Exposure (MPE) considered for the FCC rules in § 1.1310(e)(1).

Table to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2f$.
1,500-100,000	$19.2R^2$.

f = frequency in MHz;

R = minimum separation distance from the body of a nearby person (appropriate units, e.g., m);

For multiple RF sources: Multiple RF sources are exempt if:

in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

Where:

a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(B) of this section for P_{th}, including existing exempt transmitters and those being added.

b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(C) of this section for Threshold ERP, including existing exempt transmitters and those being added.

c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.

P_i = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).

$P_{th,i}$ = the exemption threshold power (P_{th}) according to paragraph (b)(3)(i)(B) of this section for fixed, mobile, or portable RF source i.

ERP_j = the ERP of fixed, mobile, or portable RF source j.

ERP_{th,j} = exemption threshold ERP for fixed, mobile, or portable RF source j, at a distance of at least $\lambda/2\pi$ according to the applicable formula of paragraph (b)(3)(i)(C) of this section.

Evaluated_k = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.

Exposure Limit_k = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k, as applicable from § 1.1310 of this chapter.

Test result

For worst case:

Mode	Frequency (MHz)	Tune up conducted power	Antenna Gain		ERP		Evaluation Distance (m)	ERP Limit (mW)
		(dBm)	(dBi)	(dBd)	(dBm)	(mW)		
BT	2402-2480	4.0	-1.0	-3.15	0.85	1.216	0.2	768
DECT	1920-1930	20.0	-3.0	-5.15	14.85	30.55	0.2	768

Note 1: The tune-up power was declared by the applicant.

Note 2: 0dBd=2.15dBi.

Note 3: The DECT function can transmit at the same time with the BT function.

Simultaneous transmitting consideration (worst case):

The ratio= $ERP_{DECT}/limit + ERP_{BT}/limit = 30.55/768 + 1.216/768 = 0.041 < 1.0$

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliant.

RSS-102 § 2.5.2 –EXEMPTION LIMITS FOR ROUTINE EVALUATION-RF EXPOSURE EVALUATION

Applicable Standard

According to RSS-102 § (2.5.2):

2.5.2 Exemption Limits for Routine Evaluation — RF Exposure Evaluation

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz⁶ and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $22.48/f^{0.5}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

Calculated Data:

For worst case:

Mode	Frequency (MHz)	Maximum tune-up conducted power	Antenna Gain	Maximum tune-up EIRP		Evaluation Distance (cm)	Limit (W)
		(dBm)	(dBi)	(dBm)	(W)		
DECT	1920-1930	20.0	-3.0	17.0	0.050	20	2.30

Result: The RF Exposure evaluation can be exempted.

§ 15.317, § 15.203 & RSS-Gen §6.8 ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location:

This radio transmitter [enter the device's ISED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device. Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

Antenna Connector Construction

The EUT has two integral antenna arrangements which were permanently attached and the gain is -3dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Type	Antenna Gain	Impedance
Integral	-3dBi	50 Ω

§ 15.315, § 15.207 & RSS-213 §5.4 CONDUCTED EMISSIONS

Applicable Standard

FCC§15.315, an unlicensed PCS device that is designed to be connected to the public utility (AC) power line must meet the limits specified in §15.207.


A radio apparatus that is designed to be connected to the public utility (AC) power line shall ensure that the radio frequency voltage, which is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz-30 MHz, shall not exceed the limits in the below table.

Unless the requirements applicable to a given device state otherwise, for any radio apparatus equipped to operate from the public utility AC power supply either directly or indirectly (such as with a battery charger), the radio frequency voltage of emissions conducted back onto the AC power lines in the frequency range of 0.15 MHz to 30 MHz shall not exceed the limits shown in below table. The more stringent limit applies at the frequency range boundaries.

Table - AC Power Lines Conducted Emission Limits		
Frequency range (MHz)	Conducted limit (dBμV)	
	Quasi-Peak	Average**
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

Note: *Decreases with the logarithm of the frequency
 ** A linear average detector is required

EUT Setup



- Note:** 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC 15.315, FCC 15.207 and RSS-Gen limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Factor & Margin Calculation

The Factor is calculated by adding the LISN Insertion Loss, Cable Loss. The basic equation is as follows:

$$\text{Factor} = \text{LISN Insertion Loss} + \text{Cable Loss}$$

The “**Over Limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a over limit of -7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\begin{aligned}\text{Over Limit} &= \text{Level} - \text{Limit} \\ \text{Level} &= \text{Read level} + \text{Factor}\end{aligned}$$

Test Data

Environmental Conditions

Temperature:	23 °C
Relative Humidity:	49 %
ATM Pressure:	101.0 kPa


The testing was performed by jerry on 2023-04-24.

EUT operation mode: Transmitting (worst case is Low channel)

For IC 7(QFN28):


$\pi/2$ -DBPSK

AC 120V/60 Hz, Line



	Freq	Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.156	9.98	26.76	36.74	55.65	-18.91	Average
2	0.156	9.98	31.38	41.36	65.65	-24.29	QP
3	0.215	9.99	19.09	29.08	53.00	-23.92	Average
4	0.215	9.99	26.42	36.41	63.00	-26.59	QP
5	0.479	10.06	15.12	25.18	46.36	-21.18	Average
6	0.479	10.06	22.38	32.44	56.36	-23.92	QP
7	0.550	10.10	28.21	38.31	46.00	-7.69	Average
8	0.550	10.10	35.78	45.88	56.00	-10.12	QP
9	2.123	10.32	14.42	24.74	46.00	-21.26	Average
10	2.123	10.32	22.21	32.53	56.00	-23.47	QP
11	11.988	13.29	20.55	33.84	50.00	-16.16	Average
12	11.988	13.29	27.62	40.91	60.00	-19.09	QP


AC 120V/60 Hz, Neutral




	Freq	Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.159	10.18	27.78	37.96	55.50	-17.54	Average
2	0.159	10.18	33.53	43.71	65.50	-21.79	QP
3	0.213	10.20	23.18	33.38	53.07	-19.69	Average
4	0.213	10.20	29.38	39.58	63.07	-23.49	QP
5	0.322	10.27	22.36	32.63	49.65	-17.02	Average
6	0.322	10.27	28.31	38.58	59.65	-21.07	QP
7	0.550	10.23	32.21	42.44	46.00	-3.56	Average
8	0.550	10.23	37.46	47.69	56.00	-8.31	QP
9	2.036	10.01	19.27	29.28	46.00	-16.72	Average
10	2.036	10.01	28.04	38.05	56.00	-17.95	QP
11	11.422	13.00	21.50	34.50	50.00	-15.50	Average
12	11.422	13.00	26.71	39.71	60.00	-20.29	QP

$\pi/4$ -DQPSK

AC 120V/60 Hz, Line




	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.171	9.98	24.80	34.78	54.91	-20.13	Average
2	0.171	9.98	30.64	40.62	64.91	-24.29	QP
3	0.293	10.01	16.89	26.90	50.45	-23.55	Average
4	0.293	10.01	23.44	33.45	60.45	-27.00	QP
5	0.324	10.02	18.84	28.86	49.59	-20.73	Average
6	0.324	10.02	24.77	34.79	59.59	-24.80	QP
7	0.544	10.09	29.49	39.58	46.00	-6.42	Average
8	0.544	10.09	36.08	46.17	56.00	-9.83	QP
9	4.858	10.79	19.31	30.10	46.00	-15.90	Average
10	4.858	10.79	26.01	36.80	56.00	-19.20	QP
11	12.624	13.54	21.08	34.62	50.00	-15.38	Average
12	12.624	13.54	27.41	40.95	60.00	-19.05	QP

AC 120V/60 Hz, Neutral


	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.167	10.18	30.09	40.27	55.09	-14.82	Average
2	0.167	10.18	33.84	44.02	65.09	-21.07	QP
3	0.272	10.24	19.86	30.10	51.05	-20.95	Average
4	0.272	10.24	24.60	34.84	61.05	-26.21	QP
5	0.326	10.27	22.31	32.58	49.54	-16.96	Average
6	0.326	10.27	28.05	38.32	59.54	-21.22	QP
7	0.549	10.23	32.40	42.63	46.00	-3.37	Average
8	0.549	10.23	37.66	47.89	56.00	-8.11	QP
9	3.547	10.29	22.38	32.67	46.00	-13.33	Average
10	3.547	10.29	27.72	38.01	56.00	-17.99	QP
11	7.581	11.46	22.45	33.91	50.00	-16.09	Average
12	7.581	11.46	28.29	39.75	60.00	-20.25	QP

$\pi/8$ -D8PSK

AC 120V/60 Hz, Line



	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.159	9.98	24.54	34.52	55.52	-21.00	Average
2	0.159	9.98	31.77	41.75	65.52	-23.77	QP
3	0.217	9.99	16.93	26.92	52.95	-26.03	Average
4	0.217	9.99	24.21	34.20	62.95	-28.75	QP
5	0.320	10.02	20.17	30.19	49.72	-19.53	Average
6	0.320	10.02	26.54	36.56	59.72	-23.16	QP
7	0.557	10.10	26.49	36.59	46.00	-9.41	Average
8	0.557	10.10	33.98	44.08	56.00	-11.92	QP
9	3.507	10.50	20.45	30.95	46.00	-15.05	Average
10	3.507	10.50	26.79	37.29	56.00	-18.71	QP
11	12.060	13.32	22.54	35.86	50.00	-14.14	Average
12	12.060	13.32	28.39	41.71	60.00	-18.29	QP


AC 120V/60 Hz, Neutral

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.162	10.18	25.60	35.78	55.35	-19.57	Average
2	0.162	10.18	32.38	42.56	65.35	-22.79	QP
3	0.212	10.20	22.64	32.84	53.12	-20.28	Average
4	0.212	10.20	29.54	39.74	63.12	-23.38	QP
5	0.464	10.35	19.38	29.73	46.63	-16.90	Average
6	0.464	10.35	23.87	34.22	56.63	-22.41	QP
7	0.545	10.24	31.79	42.03	46.00	-3.97	Average
8	0.545	10.24	38.04	48.28	56.00	-7.72	QP
9	3.514	10.28	21.65	31.93	46.00	-14.07	Average
10	3.514	10.28	28.10	38.38	56.00	-17.62	QP
11	12.607	13.49	21.74	35.23	50.00	-14.77	Average
12	12.607	13.49	27.09	40.58	60.00	-19.42	QP


For IC10(SSOP28):

 $\pi/2$ -DBPSK

AC 120V/60 Hz, Line




	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBUV	dBUV	dBUV	dB	
1	0.165	9.98	25.90	35.88	55.22	-19.34	Average
2	0.165	9.98	32.24	42.22	65.22	-23.00	QP
3	0.295	10.01	17.46	27.47	50.38	-22.91	Average
4	0.295	10.01	23.04	33.05	60.38	-27.33	QP
5	0.321	10.02	20.08	30.10	49.67	-19.57	Average
6	0.321	10.02	26.03	36.05	59.67	-23.62	QP
7	0.545	10.10	29.65	39.75	46.00	-6.25	Average
8	0.545	10.10	36.30	46.40	56.00	-9.60	QP
9	3.243	10.47	17.41	27.88	46.00	-18.12	Average
10	3.243	10.47	24.68	35.15	56.00	-20.85	QP
11	12.092	13.34	21.81	35.15	50.00	-14.85	Average
12	12.092	13.34	28.46	41.80	60.00	-18.20	QP

AC 120V/60 Hz, Neutral


	Freq	Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.155	10.18	30.70	40.88	55.75	-14.87	Average
2	0.155	10.18	33.22	43.40	65.75	-22.35	QP
3	0.211	10.20	24.30	34.50	53.17	-18.67	Average
4	0.211	10.20	29.63	39.83	63.17	-23.34	QP
5	0.318	10.27	22.78	33.05	49.77	-16.72	Average
6	0.318	10.27	29.16	39.43	59.77	-20.34	QP
7	0.546	10.24	32.25	42.49	46.00	-3.51	Average
8	0.546	10.24	37.87	48.11	56.00	-7.89	QP
9	2.028	10.01	15.77	25.78	46.00	-20.22	Average
10	2.028	10.01	23.33	33.34	56.00	-22.66	QP
11	9.451	12.14	21.12	33.26	50.00	-16.74	Average
12	9.451	12.14	26.99	39.13	60.00	-20.87	QP

$\pi/4$ -DQPSK

AC 120V/60 Hz, Line




	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.154	10.36	9.83	20.19	55.77	-35.58	Average
2	0.154	10.36	20.43	30.79	65.77	-34.98	QP
3	0.212	10.30	6.80	17.10	53.13	-36.03	Average
4	0.212	10.30	17.82	28.12	63.13	-35.01	QP
5	0.312	10.42	8.21	18.63	49.92	-31.29	Average
6	0.312	10.42	18.32	28.74	59.92	-31.18	QP
7	0.539	10.59	19.37	29.96	46.00	-16.04	Average
8	0.539	10.59	29.84	40.43	56.00	-15.57	QP
9	3.486	10.51	11.34	21.85	46.00	-24.15	Average
10	3.486	10.51	20.95	31.46	56.00	-24.54	QP
11	12.565	10.37	11.33	21.70	50.00	-28.30	Average
12	12.565	10.37	21.97	32.34	60.00	-27.66	QP

AC 120V/60 Hz, Neutral


	Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.156	10.28	14.42	24.70	55.70	-31.00	Average
2	0.156	10.28	21.61	31.89	65.70	-33.81	QP
3	0.287	10.35	12.07	22.42	50.62	-28.20	Average
4	0.287	10.35	19.73	30.08	60.62	-30.54	QP
5	0.353	10.39	11.35	21.74	48.89	-27.15	Average
6	0.353	10.39	18.96	29.35	58.89	-29.54	QP
7	0.551	10.47	24.80	35.27	46.00	-10.73	Average
8	0.551	10.47	33.36	43.83	56.00	-12.17	QP
9	3.484	10.53	15.40	25.93	46.00	-20.07	Average
10	3.484	10.53	23.77	34.30	56.00	-21.70	QP
11	5.177	10.51	15.71	26.22	50.00	-23.78	Average
12	5.177	10.51	24.15	34.66	60.00	-25.34	QP

$\pi/8$ -D8PSK

AC 120V/60 Hz, Line



	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.168	10.34	6.27	16.61	55.04	-38.43	Average
2	0.168	10.34	18.49	28.83	65.04	-36.21	QP
3	0.300	10.41	8.07	18.48	50.24	-31.76	Average
4	0.300	10.41	17.68	28.09	60.24	-32.15	QP
5	0.367	10.46	6.29	16.75	48.56	-31.81	Average
6	0.367	10.46	16.45	26.91	58.56	-31.65	QP
7	0.547	10.60	20.46	31.06	46.00	-14.94	Average
8	0.547	10.60	30.74	41.34	56.00	-14.66	QP
9	4.958	10.55	10.47	21.02	46.00	-24.98	Average
10	4.958	10.55	20.54	31.09	56.00	-24.91	QP
11	12.116	10.41	11.75	22.16	50.00	-27.84	Average
12	12.116	10.41	22.28	32.69	60.00	-27.31	QP


AC 120V/60 Hz, Neutral

	Freq	Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.154	10.27	13.79	24.06	55.81	-31.75	Average
2	0.154	10.27	20.80	31.07	65.81	-34.74	QP
3	0.271	10.34	12.87	23.21	51.08	-27.87	Average
4	0.271	10.34	20.24	30.58	61.08	-30.50	QP
5	0.312	10.37	12.76	23.13	49.92	-26.79	Average
6	0.312	10.37	20.81	31.18	59.92	-28.74	QP
7	0.548	10.47	25.42	35.89	46.00	-10.11	Average
8	0.548	10.47	33.99	44.46	56.00	-11.54	QP
9	3.511	10.54	15.80	26.34	46.00	-19.66	Average
10	3.511	10.54	24.09	34.63	56.00	-21.37	QP
11	7.606	10.56	15.42	25.98	50.00	-24.02	Average
12	7.606	10.56	24.01	34.57	60.00	-25.43	QP


For IC12 (SOIC28):

 $\pi/2$ -DBPSK

AC 120V/60 Hz, Line




	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.170	9.98	26.65	36.63	54.98	-18.35	Average
2	0.170	9.98	31.86	41.84	64.98	-23.14	QP
3	0.293	10.01	16.56	26.57	50.43	-23.86	Average
4	0.293	10.01	23.08	33.09	60.43	-27.34	QP
5	0.328	10.02	18.16	28.18	49.50	-21.32	Average
6	0.328	10.02	25.11	35.13	59.50	-24.37	QP
7	0.553	10.10	28.26	38.36	46.00	-7.64	Average
8	0.553	10.10	35.59	45.69	56.00	-10.31	QP
9	4.929	10.81	19.58	30.39	46.00	-15.61	Average
10	4.929	10.81	26.31	37.12	56.00	-18.88	QP
11	11.980	13.29	21.11	34.40	50.00	-15.60	Average
12	11.980	13.29	27.95	41.24	60.00	-18.76	QP

AC 120V/60 Hz, Neutral


	Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.166	10.18	30.35	40.53	55.14	-14.61	Average
2	0.166	10.18	33.82	44.00	65.14	-21.14	QP
3	0.222	10.20	16.12	26.32	52.75	-26.43	Average
4	0.222	10.20	22.66	32.86	62.75	-29.89	QP
5	0.497	10.37	19.84	30.21	46.05	-15.84	Average
6	0.497	10.37	27.27	37.64	56.05	-18.41	QP
7	0.542	10.25	31.25	41.50	46.00	-4.50	Average
8	0.542	10.25	37.15	47.40	56.00	-8.60	QP
9	2.213	10.04	17.48	27.52	46.00	-18.48	Average
10	2.213	10.04	23.32	33.36	56.00	-22.64	QP
11	7.586	11.47	22.22	33.69	50.00	-16.31	Average
12	7.586	11.47	28.12	39.59	60.00	-20.41	QP

$\pi/4$ -DQPSK

AC 120V/60 Hz, Line




	Freq	Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.154	10.36	10.01	20.37	55.76	-35.39	Average
2	0.154	10.36	20.48	30.84	65.76	-34.92	QP
3	0.292	10.39	8.37	18.76	50.46	-31.70	Average
4	0.292	10.39	17.66	28.05	60.46	-32.41	QP
5	0.340	10.45	8.44	18.89	49.20	-30.31	Average
6	0.340	10.45	17.86	28.31	59.20	-30.89	QP
7	0.552	10.60	19.66	30.26	46.00	-15.74	Average
8	0.552	10.60	30.03	40.63	56.00	-15.37	QP
9	4.883	10.55	11.45	22.00	46.00	-24.00	Average
10	4.883	10.55	21.26	31.81	56.00	-24.19	QP
11	11.838	10.43	11.68	22.11	50.00	-27.89	Average
12	11.838	10.43	21.78	32.21	60.00	-27.79	QP

AC 120V/60 Hz, Neutral


	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.160	10.28	12.16	22.44	55.44	-33.00	Average
2	0.160	10.28	20.18	30.46	65.44	-34.98	QP
3	0.277	10.35	11.36	21.71	50.92	-29.21	Average
4	0.277	10.35	18.96	29.31	60.92	-31.61	QP
5	0.363	10.40	10.81	21.21	48.66	-27.45	Average
6	0.363	10.40	18.62	29.02	58.66	-29.64	QP
7	0.549	10.47	25.14	35.61	46.00	-10.39	Average
8	0.549	10.47	33.83	44.30	56.00	-11.70	QP
9	3.537	10.54	15.71	26.25	46.00	-19.75	Average
10	3.537	10.54	23.96	34.50	56.00	-21.50	QP
11	7.324	10.54	15.67	26.21	50.00	-23.79	Average
12	7.324	10.54	23.55	34.09	60.00	-25.91	QP

$\pi/8$ -D8PSK

AC 120V/60 Hz, Line



	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.152	10.37	8.13	18.50	55.91	-37.41	Average
2	0.152	10.37	19.88	30.25	65.91	-35.66	QP
3	0.214	10.30	7.29	17.59	53.04	-35.45	Average
4	0.214	10.30	17.86	28.16	63.04	-34.88	QP
5	0.337	10.44	8.17	18.61	49.29	-30.68	Average
6	0.337	10.44	17.62	28.06	59.29	-31.23	QP
7	0.543	10.59	20.09	30.68	46.00	-15.32	Average
8	0.543	10.59	30.55	41.14	56.00	-14.86	QP
9	3.523	10.52	11.45	21.97	46.00	-24.03	Average
10	3.523	10.52	21.13	31.65	56.00	-24.35	QP
11	11.721	10.44	11.57	22.01	50.00	-27.99	Average
12	11.721	10.44	22.08	32.52	60.00	-27.48	QP

AC 120V/60 Hz, Neutral

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.156	10.28	14.41	24.69	55.70	-31.01	Average
2	0.156	10.28	21.40	31.68	65.70	-34.02	QP
3	0.299	10.35	12.06	22.41	50.27	-27.86	Average
4	0.299	10.35	20.19	30.54	60.27	-29.73	QP
5	0.322	10.37	12.67	23.04	49.65	-26.61	Average
6	0.322	10.37	20.50	30.87	59.65	-28.78	QP
7	0.546	10.47	25.57	36.04	46.00	-9.96	Average
8	0.546	10.47	34.08	44.55	56.00	-11.45	QP
9	3.556	10.54	15.64	26.18	46.00	-19.82	Average
10	3.556	10.54	23.89	34.43	56.00	-21.57	QP
11	7.576	10.56	15.25	25.81	50.00	-24.19	Average
12	7.576	10.56	23.55	34.11	60.00	-25.89	QP


§ 15.323 (a) & RSS-213 §5.5 EMISSION BANDWIDTH

Applicable Standard

Operation shall be contained within the 1920–1930 MHz band. The emission bandwidth shall be less than 2.5 MHz and greater than 50 kHz.

The emission bandwidth is measured in accordance with ANSI C63.17 sub-clause 6.1.3 using the setup below:

Test Setup 1:



The width, in Hz, of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, that is 26 dB down relative to the maximum level of the modulated carrier. It is based on the use of measurement instrumentation employing a peak detector function with an instrument resolution bandwidth approximately equal to 1% of the emission band-width of the device under measurement. [Extraction from 47 CFR 15, subpart D, 15.303 (C)].

Test Procedure

Using the manufacturer's information on occupied bandwidth set the spectrum analyzer as follows:

Resolution bandwidth	1.0% of the emission bandwidth (as close as possible)
Video bandwidth	>3 times the resolution bandwidth
Number of sweeps	sufficient to stability the trace
Detection mode	peak detection with maximum hold

EBW:

The emission bandwidth (x dB) is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated x dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth in the range of 1% to 5% of the anticipated emission bandwidth, and a video bandwidth at least 3x the resolution bandwidth.

OBW:

- The transmitter shall be operated at its maximum carrier power measured under normal test conditions.
- The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts.
- The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the occupied bandwidth (OBW) and video bandwidth (VBW) shall be approximately 3x RBW.

Test Data**Environmental Conditions**

Temperature:	27.8 °C
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa

The testing was performed by Mike Xiao on 2023-04-13.

Test mode: Transmitting

 $\pi/2$ -DBPSK

Channel	Center Frequency (MHz)	99% Emission Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)	Limit
Low	1921.536	1.439	1.700	50 kHz ~ 2.5 MHz
Middle	1924.992	1.439	1.700	50 kHz ~ 2.5 MHz
High	1928.448	1.436	1.700	50 kHz ~ 2.5 MHz

 $\pi/4$ -DQPSK

Channel	Center Frequency (MHz)	99% Emission Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)	Limit
Low	1921.536	1.415	1.691	50 kHz ~ 2.5 MHz
Middle	1924.992	1.418	1.687	50 kHz ~ 2.5 MHz
High	1928.448	1.418	1.696	50 kHz ~ 2.5 MHz

 $\pi/8$ -D8PSK


Channel	Center Frequency (MHz)	99% Emission Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)	Limit
Low	1921.536	1.427	1.704	50 kHz ~ 2.5 MHz
Middle	1924.992	1.430	1.700	50 kHz ~ 2.5 MHz
High	1928.448	1.430	1.700	50 kHz ~ 2.5 MHz

Test Result: Pass. *Please refer to the following plots.*

Antenna 1


$\pi/2$ -DBPSK

26 dB Emission Bandwidth-Low Channel




Date: 13.APR.2023 22:29:06

26 dB Emission Bandwidth-Middle Channel




Date: 13.APR.2023 22:33:47

26 dB Emission Bandwidth-High Channel




Date: 13.APR.2023 22:37:43

99% Emission Bandwidth-Low Channel




Date: 13.APR.2023 22:28:47

99% Emission Bandwidth-Middle Channel



Date: 13.APR.2023 22:33:18


99% Emission Bandwidth--High Channel



Date: 13.APR.2023 22:37:26


$\pi/4$ -DQPSK

26 dB Emission Bandwidth-Low Channel




Date: 13.APR.2023 22:43:27

26 dB Emission Bandwidth-Middle Channel




Date: 13.APR.2023 22:47:53

26 dB Emission Bandwidth-High Channel




Date: 13.APR.2023 22:51:56

99% Emission Bandwidth-Low Channel




Date: 13.APR.2023 22:42:58

99% Emission Bandwidth-Middle Channel



Date: 13.APR.2023 22:47:34


99% Emission Bandwidth--High Channel



Date: 13.APR.2023 22:51:37


$\pi/8$ -D8PSK

26 dB Emission Bandwidth-Low Channel




Date: 13.APR.2023 22:58:17

26 dB Emission Bandwidth-Middle Channel




Date: 13.APR.2023 23:02:52

26 dB Emission Bandwidth-High Channel




Date: 13.APR.2023 23:06:47

99% Emission Bandwidth-Low Channel




Date: 13.APR.2023 22:57:59

99% Emission Bandwidth-Middle Channel



Date: 13.APR.2023 23:02:34

99% Emission Bandwidth--High Channel



Date: 13.APR.2023 23:06:29

§ 15.319 (c) & RSS-213 §5.6 PEAK TRANSMIT POWER

Applicable Standard

The peak power output as measured over an interval of time equal to the frame rate or transmission burst of the device under all conditions of modulation. Usually this parameter is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used[47 CFR 15, subpart D, 15.303].

The peak transmit power is according to ANSI C63.17-2013 §6.1.2

Per FCC Part15.319 (c) Peak transmit power shall not exceed 100 microwatts multiplied by the square root of the emission bandwidth in hertz. Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage. The measurement results shall be properly adjusted for any instrument limitations, such as detector response times, limited resolution bandwidth capability when compared to the emission bandwidth, sensitivity, etc., so as to obtain a true peak measurement for the emission in question over the full bandwidth of the channel.

Per FCC Part15.319 (e), the peak transmit power shall be reduced by the amount in decibels that the maximum directional gain of the antenna exceeds 3 dBi.

Calculation of Peak Transmit Power Limit:

$$\text{Peak Transmit Power Limit} = 100\mu\text{W} \times (\text{EBW})^{1/2}$$


EBW is the transmit emission bandwidth in Hz determined in the other test item:

Peak transmit power shall not exceed 100 μW multiplied by the square root of the occupied bandwidth in hertz. The peak transmit power shall be reduced by the amount in decibels that the maximum directional gain of the antenna exceeds 3 dBi.

Test Procedure

Using the manufacturer's information on occupied bandwidth set the spectrum analyzer as follows:

RBW	$\geq$ Emission bandwidth
Video bandwidth	$\geq$ RBW
Span	Zero
Center frequency	Nominal center frequency of channels
Amplitude scale	Log (linear may be used if analyzer has sufficient linear dynamic range and accuracy)
Detection	Peak detection
Trigger	Video
Sweep rate	Sufficiently rapid to permit the transmit pulse to be resolved accurately



Test Data**Environmental Conditions**

Temperature:	27.8 °C
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa

The testing was performed by Mike Xiao on 2023-04-13.

Test mode: Transmitting:

Test Result: Pass

Please refer to the following table and plots.

 $\pi/2$ -DBPSK

ANT 1:

Channel	Frequency (MHz)	Peak Transmit Power (dBm)	FCC Limit (dBm)	ISED Limit (dBm)
Low	1921.536	19.49	21.15	20.79
Middle	1924.992	19.43	21.15	20.79
High	1928.448	19.38	21.15	20.79
For FCC: EBW _{Low channel} = 1700000Hz, EBW _{Middle channel} = 1700000 Hz, EBW _{High channel} = 1700000 Hz Peak Transmit Power Limit = $100(\text{EBW})^{1/2} \mu\text{W}$				
For ISED: EBW _{Low channel} = 1439000Hz, EBW _{Middle channel} = 1439000 Hz, EBW _{High channel} = 1436000 Hz Peak Transmit Power Limit = $100(\text{EBW})^{1/2} \mu\text{W}$				

ANT 2:

Channel	Frequency (MHz)	Peak Transmit Power (dBm)	FCC Limit (dBm)	ISED Limit (dBm)
Low	1921.536	19.31	21.15	20.79
Middle	1924.992	19.26	21.15	20.79
High	1928.448	19.22	21.15	20.79
For FCC: EBW _{Low channel} = 1700000Hz, EBW _{Middle channel} = 1700000 Hz, EBW _{High channel} = 1700000 Hz Peak Transmit Power Limit = $100(\text{EBW})^{1/2} \mu\text{W}$				
For ISED: EBW _{Low channel} = 1439000Hz, EBW _{Middle channel} = 1439000 Hz, EBW _{High channel} = 1436000 Hz Peak Transmit Power Limit = $100(\text{EBW})^{1/2} \mu\text{W}$				

$\pi/4$ -DQPSK

ANT 1:

Channel	Frequency (MHz)	Peak Transmit Power (dBm)	FCC Limit (dBm)	ISED Limit (dBm)
Low	1921.536	19.25	21.14	20.75
Middle	1924.992	19.23	21.14	20.76
High	1928.448	19.16	21.15	20.76
For FCC: EBW _{Low channel} = 1691000Hz, EBW _{Middle channel} = 1687000 Hz, EBW _{High channel} = 1696000 Hz Peak Transmit Power Limit = $100(\text{EBW})^{1/2} \mu\text{W}$				
For ISED: EBW _{Low channel} = 1415000Hz, EBW _{Middle channel} = 1418000 Hz, EBW _{High channel} = 1418000 Hz Peak Transmit Power Limit = $100(\text{EBW})^{1/2} \mu\text{W}$				

ANT 2:

Channel	Frequency (MHz)	Peak Transmit Power (dBm)	FCC Limit (dBm)	ISED Limit (dBm)
Low	1921.536	19.09	21.14	20.75
Middle	1924.992	19.05	21.14	20.76
High	1928.448	18.99	21.15	20.76
For FCC: EBW _{Low channel} = 1691000Hz, EBW _{Middle channel} = 1687000 Hz, EBW _{High channel} = 1696000 Hz Peak Transmit Power Limit = $100(\text{EBW})^{1/2} \mu\text{W}$				
For ISED: EBW _{Low channel} = 1415000Hz, EBW _{Middle channel} = 1418000 Hz, EBW _{High channel} = 1418000 Hz Peak Transmit Power Limit = $100(\text{EBW})^{1/2} \mu\text{W}$				

$\pi/8$ -D8PSK

ANT 1:

Channel	Frequency (MHz)	Peak Transmit Power (dBm)	FCC Limit (dBm)	ISED Limit (dBm)
Low	1921.536	19.02	21.16	20.77
Middle	1924.992	18.93	21.15	20.78
High	1928.448	18.93	21.15	20.78
For FCC: $EBW_{\text{Low channel}} = 1704000\text{Hz}$, $EBW_{\text{Middle channel}} = 1700000\text{ Hz}$, $EBW_{\text{High channel}} = 1700000\text{ Hz}$ Peak Transmit Power Limit = $100(EBW)^{1/2} \mu\text{W}$				
For ISED: $EBW_{\text{Low channel}} = 1427000\text{Hz}$, $EBW_{\text{Middle channel}} = 1430000\text{ Hz}$, $EBW_{\text{High channel}} = 1430000\text{ Hz}$ Peak Transmit Power Limit = $100(EBW)^{1/2} \mu\text{W}$				


ANT 2:

Channel	Frequency (MHz)	Peak Transmit Power (dBm)	FCC Limit (dBm)	ISED Limit (dBm)
Low	1921.536	18.83	21.16	20.77
Middle	1924.992	18.78	21.15	20.78
High	1928.448	18.73	21.15	20.78
For FCC: $EBW_{\text{Low channel}} = 1704000\text{Hz}$, $EBW_{\text{Middle channel}} = 1700000\text{ Hz}$, $EBW_{\text{High channel}} = 1700000\text{ Hz}$ Peak Transmit Power Limit = $100(EBW)^{1/2} \mu\text{W}$				
For ISED: $EBW_{\text{Low channel}} = 1427000\text{Hz}$, $EBW_{\text{Middle channel}} = 1430000\text{ Hz}$, $EBW_{\text{High channel}} = 1430000\text{ Hz}$ Peak Transmit Power Limit = $100(EBW)^{1/2} \mu\text{W}$				


Antenna 1:

$\pi/2$ -DBPSK


Low Channel



Middle Channel




High Channel



Date: 13.APR.2023 21:58:23


Antenna 2:

Low Channel




Date: 13.APR.2023 22:02:39

Middle Channel



Date: 13.APR.2023 22:03:00

High Channel




Date: 13.APR.2023 22:03:27

$\pi/4$ -DQPSK


Antenna 1:

Low Channel




Date: 13.APR.2023 21:58:46

Middle Channel



Date: 13.APR.2023 21:59:08


High Channel



Date: 13.APR.2023 21:59:29


Antenna 2:

Low Channel




Date: 13.APR.2023 22:03:57

Middle Channel



Date: 13.APR.2023 22:04:18

High Channel




Date: 13.APR.2023 22:04:38

$\pi/8$ -D8PSK


Antenna 1:

Low Channel




Date: 13.APR.2023 21:59:51

Middle Channel



Date: 13.APR.2023 22:00:12


High Channel



Date: 13.APR.2023 22:00:32


Antenna 2:

Low Channel




Date: 13.APR.2023 22:05:01

Middle Channel



Date: 13.APR.2023 22:05:29

High Channel



Date: 13.APR.2023 22:05:49

§ 15.319 (d) & RSS-213 §5.7 POWER SPECTRAL DENSITY

Applicable Standard

The average pulse energy in a 3 kHz bandwidth is divided by the pulse duration.

The power spectral density shall not exceed 3mW in any 3 kHz bandwidth as measured with a spectrum analyzer having a resolution bandwidth of 3 kHz.


The power spectral density is measured in accordance with ANSI C63.17-2013 Clause 6.1.5.

The peak-hold power spectral density of transmitters shall not exceed 12 mW per any 3 kHz bandwidth. As an alternative to the peak-hold power spectral density, the time-averaged power spectral density may be measured and it shall not exceed 3 mW per any 3 kHz bandwidth.

Test Procedure

Using the manufacturer's information on occupied bandwidth set the spectrum analyzer as follows:

RBW	3 kHz
Video bandwidth	$\geq 3 \times \text{RBW}$
Span	Zero span at frequency with the maximum level (frequency determined in 6.1.3 if the same type of signal (continuous versus burst) was used in 6.1.3)
Center frequency	Spectral peak as determined in 6.1.3
Sweep time	For burst signals, sufficient to include essentially all of the maximum length burst at the output of a 3 kHz filter (e.g., maximum input burst duration plus 600 μs). For continuous signals, 20 ms.
Amplitude scale	Log power
Detection	Sample detection and averaged for a minimum of 100 sweeps
Trigger	External or internal



Test Data**Environmental Conditions**

Temperature:	27.8 °C
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa

The testing was performed by Mike Xiao on 2023-04-13 and 2023-04-14.

Test Result: Pass

Please refer to following table and plots

Test mode: Transmitting

 $\pi/2$ -DBPSK

Channel	Frequency (MHz)	Power Spectral Density		Limit (mW/3kHz)
		(dBm/3kHz)	(mW/3kHz)	
Low	1921.536	-5.03	0.31	3
Middle	1924.992	-4.81	0.33	3
High	1928.448	-4.92	0.32	3

 $\pi/4$ -DQPSK


Channel	Frequency (MHz)	Power Spectral Density		Limit (mW/3kHz)
		(dBm/3kHz)	(mW/3kHz)	
Low	1921.536	-2.53	0.56	3
Middle	1924.992	-2.64	0.54	3
High	1928.448	-2.72	0.53	3

 $\pi/8$ -D8PSK


Channel	Frequency (MHz)	Power Spectral Density		Limit (mW/3kHz)
		(dBm/3kHz)	(mW/3kHz)	
Low	1921.536	-5.15	0.31	3
Middle	1924.992	-5.18	0.30	3
High	1928.448	-5.05	0.31	3

Antenna 1

$\pi/2$ -DBPSK
Low Channel




Date: 13.APR.2023 23:21:05




Date: 14.APR.2023 00:02:29

Middle Channel




Date: 14.APR.2023 00:23:45




Date: 14.APR.2023 00:34:39

High Channel




Date: 14.APR.2023 00:27:01




Date: 14.APR.2023 00:42:35

$\pi/4$ -DQPSK
Low Channel




Date: 13.APR.2023 23:22:19




Date: 14.APR.2023 00:08:52

Middle Channel




Date: 14.APR.2023 00:24:19




Date: 14.APR.2023 00:36:30

High Channel





Date: 14.APR.2023 00:27:41




Date: 14.APR.2023 00:44:17


$\pi/8$ -D8PSK
Low Channel



Middle Channel




Date: 14.APR.2023 00:24:58




Date: 14.APR.2023 00:38:14

High Channel



Date: 14.APR.2023 00:28:12



Date: 14.APR.2023 00:45:47

§ 15.323 (d) & RSS-213 §5.8 EMISSION INSIDE AND OUTSIDE THE SUB-BAND

Applicable Standard

Emissions inside the sub-band must comply with the following emission mask:

1. In the bands between 1B and 2B measured from the center of the emission bandwidth the total power emitted by the device shall be at least 30 dB below the transmit power permitted for that device;
2. in the bands between 2B and 3B measured from the center of the emission bandwidth the total power emitted by an intentional radiator shall be at least 50 dB below the transmit power permitted for that radiator;
3. in the bands between 3B and the sub-band edge the total power emitted by an intentional radiator in the measurement bandwidth shall be at least 60 dB below the transmit power permitted for that radiator.

Where B = emission bandwidth

Emission Outside the sub-band shall be attenuated below a reference power of 112 mw (20.5 dBm) as follows:

1. 30 dB between the sub-band and 1.25 MHz above or below the sub-band;
2. 50 dB between 1.25 and 2.5 MHz above or below the sub-band;
3. 60 dB at 2.5 MHz or greater above or below the sub-band.

Emissions outside the 1920-1930 MHz Band

Emissions outside the 1920-1930 MHz band shall be attenuated below a reference power of 112 milliwatts (-9.5 dBW) by at least:

- 30 dB between the band edges and 1.25 MHz above and below the band edges;
- 50 dB between 1.25 MHz and 2.5 MHz above or below the band edges; and
- 60 dB at 2.5 MHz or greater above or below the band edges.

Emissions inside the 1920-1930 MHz Band

Emissions inside the 1920-1930 MHz band shall be attenuated below the transmit power permitted for that device, as follows:

- 30 dB between the frequencies 1B and 2B measured from the centre of the occupied bandwidth;
- 50 dB between the frequencies 2B and 3B measured from the centre of the occupied bandwidth; and
- 60 dB between the frequencies 3B and band edge, where B is the occupied bandwidth in hertz.

Test Procedure

According to ANSI C63.17.2013 Clause 6.1.6.


In-band emission:

Spectrum analyzer settings for measuring in-band emission

RBW	Approximately 1% of the emission bandwidth (B)
Video bandwidth	$3 \times \text{RBW}$
Sweep time	The sweep time shall be sufficiently slow that the swept frequency rate shall not exceed one RBW per three transmit bursts.
Number of sweeps	Sufficient to stabilize the trace
Amplitude scale	Log
Detection	Peak detection and max hold enabled
Span	Approximately equal to $3.5 B$

Out-band emission:

RBW	30kHz
Video bandwidth	100kHz
Center frequency	Nominal center frequency of channels
Amplitude scale	Log (linear may be used if analyzer has sufficient linear dynamic range and accuracy)
Detection	Peak detection



Test Data

Environmental Conditions

Temperature:	24~26°C
Relative Humidity:	56~60%
ATM Pressure:	101.0 kPa

The testing was performed by Jimi Zheng on 2023-04-22 for below 1GHz, by Jason Liu on 2023-04-10 for above 1GHz and Mike Xiao on 2023-04-13 and 2023-04-18 for RF conducted.

Test mode: Transmitting


Test Result: Pass

Please refer to following plots

$\pi/2$ -DBPSK


FCC:

Low Channel (Unwanted Emission inside the Sub-band)




Date: 13.APR.2023 22:29:34

Middle Channel (Unwanted Emission inside the Sub-band)



Date: 13.APR.2023 22:34:16


High Channel (Unwanted Emission inside the Sub-band)



Date: 13.APR.2023 22:38:14


ISED:

Low Channel (Unwanted Emission inside the Sub-band)




Date: 18.APR.2023 20:43:59

Middle Channel (Unwanted Emission inside the Sub-band)




Date: 18.APR.2023 20:44:39

High Channel (Unwanted Emission inside the Sub-band)




Date: 18.APR.2023 20:45:21


Low Channel (Unwanted Emission outside the Sub-band)




Date: 13.APR.2023 22:30:04




Date: 13.APR.2023 22:30:54




Date: 13.APR.2023 22:31:12




Date: 13.APR.2023 22:31:42




Middle Channel (Unwanted Emission outside the Sub-band)







Date: 13.APR.2023 22:35:25



Date: 13.APR.2023 22:35:43




Date: 13.APR.2023 22:36:13




Date: 13.APR.2023 22:36:45


High Channel (Unwanted Emission outside the Sub-band)




Date: 13.APR.2023 22:38:52




Date: 13.APR.2023 22:39:12



Date: 13.APR.2023 22:39:41



Date: 13.APR.2023 22:40:20




Date: 13.APR.2023 22:40:54

$\pi/4$ -DQPSK


FCC:

Low Channel (Unwanted Emission inside the Sub-band)




Date: 13.APR.2023 22:43:58

Middle Channel (Unwanted Emission inside the Sub-band)



Date: 13.APR.2023 22:48:22


High Channel (Unwanted Emission inside the Sub-band)



Date: 13.APR.2023 22:52:24


ISED:

Low Channel (Unwanted Emission inside the Sub-band)




Date: 18.APR.2023 20:47:25

Middle Channel (Unwanted Emission inside the Sub-band)




Date: 18.APR.2023 20:48:02

High Channel (Unwanted Emission inside the Sub-band)




Date: 18.APR.2023 20:48:42


Low Channel (Unwanted Emission outside the Sub-band)




Date: 13.APR.2023 22:44:26




Date: 13.APR.2023 22:44:55



Date: 13.APR.2023 22:45:25




Date: 13.APR.2023 22:46:04




Date: 13.APR.2023 22:46:38


Middle Channel (Unwanted Emission outside the Sub-band)





Date: 13.APR.2023 22:49:00




Date: 13.APR.2023 22:49:30




Date: 13.APR.2023 22:49:59




High Channel (Unwanted Emission outside the Sub-band)




Date: 13.APR.2023 22:53:15




Date: 13.APR.2023 22:53:33



Date: 13.APR.2023 22:54:02



Date: 13.APR.2023 22:54:41




Date: 13.APR.2023 22:55:26


$\pi/8$ -D8PSK

FCC:


Low Channel (Unwanted Emission inside the Sub-band)



Middle Channel (Unwanted Emission inside the Sub-band)




High Channel (Unwanted Emission inside the Sub-band)



Date: 13.APR.2023 23:07:08


ISED:

Low Channel (Unwanted Emission inside the Sub-band)




Date: 18.APR.2023 20:51:33

Middle Channel (Unwanted Emission inside the Sub-band)




Date: 18.APR.2023 20:51:02

High Channel (Unwanted Emission inside the Sub-band)




Date: 18.APR.2023 20:50:10



Low Channel (Unwanted Emission outside the Sub-band)




Date: 13.APR.2023 22:59:25




Date: 13.APR.2023 22:59:55






Date: 13.APR.2023 23:01:29


Middle Channel (Unwanted Emission outside the Sub-band)




Date: 13.APR.2023 23:03:41




Date: 13.APR.2023 23:04:11



Date: 13.APR.2023 23:04:39




Date: 13.APR.2023 23:05:18




Date: 13.APR.2023 23:05:52


High Channel (Unwanted Emission outside the Sub-band)




Date: 13.APR.2023 23:07:36




Date: 13.APR.2023 23:08:05



Date: 13.APR.2023 23:08:34



Date: 13.APR.2023 23:09:13



Date: 13.APR.2023 23:10:00


For IC7(QFN28):

30MHz-1GHz: (Low channel was worst case)

Note: When the test result of peak was less than the limit of QP more than 6dB, just peak value were recorded.


$\pi/2$ -DBPSK

Horizontal




	Freq Factor		Read	Level	Limit	Over	Remark
	MHz	dB/m	Level	dBuV/m	Line	Limit	
1	62.186	-11.50	32.57	21.07	40.00	-18.93	Peak
2	172.902	-13.29	46.57	33.28	43.50	-10.22	Peak
3	196.855	-11.56	45.30	33.74	43.50	-9.76	Peak
4	328.607	-8.06	46.27	38.21	46.00	-7.79	Peak
5	435.590	-5.70	45.04	39.34	46.00	-6.66	Peak
6	800.382	-0.36	36.39	36.03	46.00	-9.97	Peak

Vertical




$\pi/4$ -DQPSK

Horizontal



	Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	62.213	-11.51	33.11	21.60	40.00	-18.40	Peak
2	164.908	-14.15	46.14	31.99	43.50	-11.51	Peak
3	190.906	-11.43	46.79	35.36	43.50	-8.14	Peak
4	362.985	-7.60	44.96	37.36	46.00	-8.64	Peak
5	435.590	-5.70	44.96	39.26	46.00	-6.74	Peak
6	800.382	-0.36	36.54	36.18	46.00	-9.82	Peak


Vertical



	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	37.433	-10.94	38.81	27.87	40.00	-12.13	Peak
2	62.213	-11.51	43.56	32.05	40.00	-7.95	Peak
3	84.888	-15.67	46.62	30.95	40.00	-9.05	Peak
4	174.883	-13.13	47.68	34.55	43.50	-8.95	Peak
5	435.590	-5.70	42.91	37.21	46.00	-8.79	Peak
6	644.837	-1.88	36.19	34.31	46.00	-11.69	Peak


$\pi/8$ -D8PSK

Horizontal



	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	54.931	-10.28	34.42	24.14	40.00	-15.86	Peak
2	101.912	-11.58	29.32	17.74	43.50	-25.76	Peak
3	250.082	-10.75	34.75	24.00	46.00	-22.00	Peak
4	500.082	-4.25	36.67	32.42	46.00	-13.58	Peak
5	600.110	-2.43	36.35	33.92	46.00	-12.08	Peak
6	800.382	-0.36	35.47	35.11	46.00	-10.89	Peak

Vertical




	Freq	Factor	Read Level	Limit Level	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	38.871	-10.62	33.90	23.28	40.00	-16.72 Peak
2	67.055	-13.38	38.15	24.77	40.00	-15.23 Peak
3	148.376	-15.36	36.83	21.47	43.50	-22.03 Peak
4	200.073	-11.41	35.23	23.82	43.50	-19.68 Peak
5	500.082	-4.25	42.49	38.24	46.00	-7.76 Peak
6	600.110	-2.43	37.95	35.52	46.00	-10.48 Peak

For IC10(SSOP28):

30MHz-1GHz: (Low channel was worst case)


$\pi/2$ -DBPSK

Horizontal



	Freq		Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz		dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	54.739	-10.29		33.82	23.53	40.00	-16.47	Peak
2	157.697	-14.55		42.97	28.42	43.50	-15.08	Peak
3	236.645	-10.95		37.76	26.81	46.00	-19.19	Peak
4	359.501	-7.66		39.43	31.77	46.00	-14.23	Peak
5	500.082	-4.25		38.27	34.02	46.00	-11.98	Peak
6	653.372	-1.63		36.15	34.52	46.00	-11.48	Peak


Vertical



	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	37.630	-10.89	40.12	29.23	40.00	-10.77	Peak
2	53.085	-10.18	41.82	31.64	40.00	-8.36	Peak
3	157.145	-14.65	49.14	34.49	43.50	-9.01	Peak
4	241.570	-10.81	37.98	27.17	46.00	-18.83	Peak
5	500.082	-4.25	43.12	38.87	46.00	-7.13	Peak
6	600.110	-2.43	39.48	37.05	46.00	-8.95	Peak


$\pi/4$ -DQPSK

Horizontal



	Freq	Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	41.132	-10.16	30.25	20.09	40.00	-19.91	Peak
2	55.318	-10.25	34.38	24.13	40.00	-15.87	Peak
3	146.759	-15.46	43.65	28.19	43.50	-15.31	Peak
4	173.585	-13.22	43.19	29.97	43.50	-13.53	Peak
5	330.919	-7.93	35.51	27.58	46.00	-18.42	Peak
6	600.110	-2.43	39.54	37.11	46.00	-8.89	Peak


Vertical



	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	34.806	-11.60	44.75	33.15	40.00	-6.85	Peak
2	67.557	-13.63	45.61	31.98	40.00	-8.02	Peak
3	144.588	-15.51	48.82	33.31	43.50	-10.19	Peak
4	175.498	-13.10	48.23	35.13	43.50	-8.37	Peak
5	323.746	-8.31	37.57	29.26	46.00	-16.74	Peak
6	500.082	-4.25	40.40	36.15	46.00	-9.85	Peak


$\pi/8$ -D8PSK

Horizontal



	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	34.821	-11.59	32.15	20.56	40.00	-19.44	Peak
2	55.293	-10.26	35.45	25.19	40.00	-14.81	Peak
3	145.032	-15.51	43.11	27.60	43.50	-15.90	Peak
4	175.344	-13.10	42.61	29.51	43.50	-13.99	Peak
5	328.751	-8.05	37.29	29.24	46.00	-16.76	Peak
6	600.110	-2.43	41.39	38.96	46.00	-7.04	Peak

Vertical




	Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	30.705	-12.32	43.94	31.62	40.00	-8.38	Peak
2	53.740	-10.30	38.86	28.56	40.00	-11.44	Peak
3	149.093	-15.33	47.60	32.27	43.50	-11.23	Peak
4	175.114	-13.11	48.34	35.23	43.50	-8.27	Peak
5	324.883	-8.27	37.87	29.60	46.00	-16.40	Peak
6	595.916	-2.64	41.58	38.94	46.00	-7.06	Peak

For IC12 (SOIC28):

30MHz-1GHz: (Low channel was worst case)


$\pi/2$ -DBPSK

Horizontal



Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	63.341	-11.91	34.62	22.71	40.00	-17.29 Peak
2	161.899	-14.28	40.92	26.64	43.50	-16.86 Peak
3	207.213	-11.84	36.41	24.57	43.50	-18.93 Peak
4	291.036	-9.30	36.96	27.66	46.00	-18.34 Peak
5	359.816	-7.67	37.32	29.65	46.00	-16.35 Peak
6	500.082	-4.25	37.62	33.37	46.00	-12.63 Peak


Vertical



	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	38.112	-10.79	33.99	23.20	40.00	-16.80	Peak
2	66.820	-13.27	37.28	24.01	40.00	-15.99	Peak
3	155.637	-14.87	48.79	33.92	43.50	-9.58	Peak
4	200.337	-11.43	38.64	27.21	43.50	-16.29	Peak
5	500.082	-4.25	40.06	35.81	46.00	-10.19	Peak
6	600.110	-2.43	36.40	33.97	46.00	-12.03	Peak


$\pi/4$ -DQPSK

Horizontal



	Freq	Factor	Read Level	Limit Level	Over Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	55.318	-10.25	35.76	25.51	40.00	-14.49	Peak
2	140.650	-15.48	44.38	28.90	43.50	-14.60	Peak
3	182.160	-12.51	47.34	34.83	43.50	-8.67	Peak
4	250.082	-10.75	44.56	33.81	46.00	-12.19	Peak
5	359.344	-7.65	38.71	31.06	46.00	-14.94	Peak
6	500.082	-4.25	40.52	36.27	46.00	-9.73	Peak


Vertical



	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	34.821	-11.59	42.88	31.29	40.00	-8.71	Peak
2	63.480	-11.96	44.22	32.26	40.00	-7.74	Peak
3	141.578	-15.52	49.06	33.54	43.50	-9.96	Peak
4	167.090	-13.87	50.59	36.72	43.50	-6.78	Peak
5	253.281	-10.65	39.12	28.47	46.00	-17.53	Peak
6	580.703	-3.31	40.52	37.21	46.00	-8.79	Peak


$\pi/8$ -D8PSK

Horizontal



	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	55.293	-10.26	35.80	25.54	40.00	-14.46	Peak
2	141.640	-15.52	43.61	28.09	43.50	-15.41	Peak
3	181.283	-12.62	48.21	35.59	43.50	-7.91	Peak
4	250.082	-10.75	42.41	31.66	46.00	-14.34	Peak
5	500.082	-4.25	41.08	36.83	46.00	-9.17	Peak
6	600.110	-2.43	38.29	35.86	46.00	-10.14	Peak

Vertical



	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	38.922	-10.61	41.45	30.84	40.00	-9.16	Peak
2	63.480	-11.96	44.39	32.43	40.00	-7.57	Peak
3	142.013	-15.54	49.88	34.34	43.50	-9.16	Peak
4	167.898	-13.79	49.24	35.45	43.50	-8.05	Peak
5	250.082	-10.75	39.50	28.75	46.00	-17.25	Peak
6	500.082	-4.25	41.73	37.48	46.00	-8.52	Peak

Above 1GHz: (worst case is IC7 (QFN28)) **$\pi/2$ -DBPSK**

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Corrected. Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave		Height (m)	Polar (H/V)				
Low Channel(1921.536MHz)									
1921.536	122.03	PK	224	2.2	H	-12.53	109.50	\	\
1921.536	122.69	PK	84	2.1	V	-12.53	110.16	\	\
3843.07	60.92	PK	158	2.1	H	-9.17	51.75	74	-22.25
3843.07	60.72	PK	56	2	V	-9.17	51.55	74	-22.45
Middle Channel(1924.992MHz)									
1924.992	121.93	PK	178	2	H	-12.41	109.52	\	\
1924.992	122.77	PK	357	2	V	-12.41	110.36	\	\
3849.98	61.10	PK	50	1.9	H	-9.17	51.93	74	-22.07
3849.98	60.47	PK	25	1.9	V	-9.17	51.30	74	-22.70
High Channel(1928.448MHz)									
1928.448	121.00	PK	310	1.2	H	-12.29	108.71	\	\
1928.448	122.09	PK	170	2	V	-12.29	109.80	\	\
3856.9	60.66	PK	88	1.2	H	-9.12	51.54	74	-22.46
3856.9	60.44	PK	65	2.5	V	-9.12	51.32	74	-22.68

Field Strength of Average							
Frequency (MHz)	Peak Measurement @3m (dBμV/m)	Polar (H/V)	Duty Cycle Correction Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15D		
					Limit (dBμV/m)	Margin (dB)	Comment
Low Channel(1921.536MHz)							
1921.536	109.50	H	-28.19	81.31	\	\	Fundamental
1921.536	110.16	V	-28.19	81.97	\	\	Fundamental
3843.07	51.75	H	-28.19	23.56	54	-30.44	Harmonic
3843.07	51.55	V	-28.19	23.36	54	-30.64	Harmonic
Middle Channel(1924.992MHz)							
1924.992	109.52	H	-28.19	81.33	\	\	Fundamental
1924.992	110.36	V	-28.19	82.17	\	\	Fundamental
3849.98	51.93	H	-28.19	23.74	54	-30.26	Harmonic
3849.98	51.30	V	-28.19	23.11	54	-30.89	Harmonic
High Channel(1928.448MHz)							
1928.448	108.71	H	-28.19	80.52	\	\	Fundamental
1928.448	109.8	V	-28.19	81.61	\	\	Fundamental
3856.9	51.54	H	-28.19	23.35	54	-30.65	Harmonic
3856.9	51.32	V	-28.19	23.13	54	-30.87	Harmonic

Note:

Corrected. Amplitude = Corrected Factor + Reading

Margin = Corrected. Amplitude - Limit

Average level= Peak level+ Duty Cycle Corrected Factor

Other emissions which more than 20dB below limit or in noise floor level was not recorded.

Duty cycle:


Ton1 =0.3913ms

Tp = 10.0435 ms


Duty cycle = Ton/Tp = 0.3913/10.0435=0.03896

Duty Cycle Corrected Factor = 20lg (Duty cycle) = 20lg0.03896 = -28.19

Duty cycle



Date: 13.APR.2023 22:32:49



Date: 13.APR.2023 22:32:58

$\pi/4$ -DQPSK

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Corrected. Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave		Height (m)	Polar (H/V)				
Low Channel(1921.536MHz)									
1921.54	121.11	PK	140	1.8	H	-12.53	108.58	\	\
1921.54	121.57	PK	229	1.7	V	-12.53	109.04	\	\
3843.07	61.04	PK	125	1.3	H	-9.17	51.87	74	-22.13
3843.07	60.65	PK	91	2.3	V	-9.17	51.48	74	-22.52
Middle Channel(1924.992MHz)									
1924.99	121.05	PK	303	1.2	H	-12.41	108.64	\	\
1924.99	121.74	PK	130	1.2	V	-12.41	109.33	\	\
3849.98	60.19	PK	158	1	H	-9.17	51.02	74	-22.98
3849.98	60.69	PK	6	1	V	-9.17	51.52	74	-22.48
High Channel(1928.448MHz)									
1928.45	121.23	PK	330	1.9	H	-12.29	108.94	\	\
1928.45	121.91	PK	172	1.6	V	-12.29	109.62	\	\
3856.9	60.67	PK	36	2	H	-9.12	51.55	74	-22.45
3856.9	60.93	PK	298	1.6	V	-9.12	51.81	74	-22.19

Field Strength of Average							
Frequency (MHz)	Peak Measurement @3m (dBμV/m)	Polar (H/V)	Duty Cycle Correction Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15D		
					Limit (dBμV/m)	Margin (dB)	Comment
Low Channel(1921.536MHz)							
1921.54	108.58	H	-28.22	80.36	\	\	Fundamental
1921.54	109.04	V	-28.22	80.82	\	\	Fundamental
3843.07	51.87	H	-28.22	23.65	54	-30.35	Harmonic
3843.07	51.48	V	-28.22	23.26	54	-30.74	Harmonic
Middle Channel(1924.992MHz)							
1924.99	108.64	H	-28.22	80.42	\	\	Fundamental
1924.99	109.33	V	-28.22	81.11	\	\	Fundamental
3849.98	51.02	H	-28.22	22.80	54	-31.20	Harmonic
3849.98	51.52	V	-28.22	23.30	54	-30.70	Harmonic
High Channel(1928.448MHz)							
1928.45	108.94	H	-28.22	80.72	\	\	Fundamental
1928.45	109.62	V	-28.22	81.40	\	\	Fundamental
3856.9	51.55	H	-28.22	23.33	54	-30.67	Harmonic
3856.9	51.81	V	-28.22	23.59	54	-30.41	Harmonic

Note:

Corrected. Amplitude = Corrected Factor + Reading

Margin = Corrected. Amplitude - Limit

Average level= Peak level+ Duty Cycle Corrected Factor

Other emissions which more than 20dB below limit or in noise floor level was not recorded.

Duty cycle:


Ton1 =0.3913ms

Tp = 10.087 ms


Duty cycle = Ton/Tp = 0.3913/10.087=0.0388

Duty Cycle Corrected Factor = 20lg (Duty cycle) = 20lg0.0388 = -28.22

Duty cycle



Date: 13.APR.2023 22:46:53



Date: 13.APR.2023 22:47:05

$\pi/8$ -D8PSK

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Corrected. Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave		Height (m)	Polar (H/V)				
Low Channel(1921.536MHz)									
1921.54	121.47	PK	354	2.3	H	-12.53	108.94	\	\
1921.54	119.87	PK	63	1.5	V	-12.53	107.34	\	\
3843.07	60.86	PK	232	2	H	-9.17	51.69	74	-22.31
3843.07	60.91	PK	130	1.4	V	-9.17	51.74	74	-22.26
Middle Channel(1924.992MHz)									
1924.99	122.06	PK	300	2.1	H	-12.41	109.65	\	\
1924.99	120.29	PK	174	2.1	V	-12.41	107.88	\	\
3849.98	60.71	PK	187	1.8	H	-9.17	51.54	74	-22.46
3849.98	60.76	PK	207	1.8	V	-9.17	51.59	74	-22.41
High Channel(1928.448MHz)									
1928.45	122.14	PK	358	2.5	H	-12.29	109.85	\	\
1928.45	119.94	PK	280	1.9	V	-12.29	107.65	\	\
3856.9	60.49	PK	340	2.4	H	-9.12	51.37	74	-22.63
3856.9	61.08	PK	5	1.7	V	-9.12	51.96	74	-22.04

Field Strength of Average							
Frequency (MHz)	Peak Measurement @3m (dBμV/m)	Polar (H/V)	Duty Cycle Correction Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15D		
					Limit (dBμV/m)	Margin (dB)	Comment
Low Channel(1921.536MHz)							
1921.54	108.94	H	-28.19	80.75	\	\	Fundamental
1921.54	107.34	V	-28.19	79.15	\	\	Fundamental
3843.07	51.69	H	-28.19	23.50	54	-30.50	Harmonic
3843.07	51.74	V	-28.19	23.55	54	-30.45	Harmonic
Middle Channel(1924.992MHz)							
1924.99	109.65	H	-28.19	81.46	\	\	Fundamental
1924.99	107.88	V	-28.19	79.69	\	\	Fundamental
3849.98	51.54	H	-28.19	23.35	54	-30.65	Harmonic
3849.98	51.59	V	-28.19	23.40	54	-30.60	Harmonic
High Channel(1928.448MHz)							
1928.45	109.85	H	-28.19	81.66	\	\	Fundamental
1928.45	107.65	V	-28.19	79.46	\	\	Fundamental
3856.9	51.37	H	-28.19	23.18	54	-30.82	Harmonic
3856.9	51.96	V	-28.19	23.77	54	-30.23	Harmonic

Note:

Corrected. Amplitude = Corrected Factor + Reading

Margin = Corrected. Amplitude - Limit

Average level= Peak level+ Duty Cycle Corrected Factor

Other emissions which more than 20dB below limit or in noise floor level was not recorded.

Duty cycle:


Ton1 =0.3913ms

Tp = 10.0435 ms


Duty cycle = Ton/Tp = 0.3913/10.0435=0.03896

Duty Cycle Corrected Factor = 20lg (Duty cycle) = 20lg0.0389 = -28.19

Duty cycle



Date: 13.APR.2023 23:01:55




Date: 13.APR.2023 23:02:06


1 GHz - 18 GHz: (Pre-Scan plots)

$\pi/2$ -DBPSK, Middle channel

Horizontal




Vertical




18-20GHz: (Pre-Scan plots)

$\pi/2$ -DBPSK, Middle channel

Horizontal



Vertical



§ 15.323 (f) & RSS-213 §5.3 FREQUENCY STABILITY

Applicable Standard

Per §15.323(f), the frequency stability of the carrier frequency of the intentional radiator shall be maintained within ± 10 ppm over 1 hour or the interval between channel access monitoring, whichever is shorter. The frequency stability shall be maintained over a temperature variation of -20°C to $+50^{\circ}\text{C}$ at normal supply voltage, and over a variation in the primary supply voltage of 85 percent to 115 percent of the rated supply voltage at a temperature of 20°C . For equipment that is capable only of operating from a battery, the frequency stability tests shall be performed using a new battery without any further requirement to vary supply voltage

According to RSS-213 Issue 3 (2015-03) § (5.3):

The carrier frequency stability shall be maintained within ± 10 ppm ($\pm 0.001\%$).

According to RSS-Gen Issue 4 (2014-11) § (8.11):

Transmitter frequency stability for licence-exempt radio apparatus shall be measured in accordance with Section 6.11. For licence-exempt radio apparatus, the frequency stability shall be measured at temperatures of -20°C (-4°F), $+20^{\circ}\text{C}$ ($+68^{\circ}\text{F}$) and $+50^{\circ}\text{C}$ ($+122^{\circ}\text{F}$) instead of at the temperatures specified in Section 6.11.

Test Procedure


This procedure should be carried out for each of the following test cases:

Temperature	Supply Voltage
20°C	85-115% or new batteries
-20°C	Normal
$+50^{\circ}\text{C}$	Normal

During test, the equipment shall be placed in the boxes and set the temperature to the specified requirement until the thermal balance has been reached.

Using the mean carrier frequency at 20°C and at nominal supply voltage as the reference, the mean carrier frequency shall be maintained within ± 10 ppm at the two extreme temperatures (or as declared by the manufacturer) and at normal temperature (typically 20°C) at the two extreme supply voltages.

This test does not apply to a EUT that is capable only of operating from a battery.



Test Data**Environmental Conditions**

Temperature:	27.8 °C
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa

The testing was performed by Mike Xiao on 2023-04-13 and 2023-05-05.

Test Result: Pass

Test mode: Transmitting

 $\pi/2$ -DBPSK

Temperature (°C)	Voltage (V _{AC} ☒ , V _{DC} ☐)	Channel Frequency (MHz)	Measurement (MHz)	Measured Frequency Offset (ppm)	Limit (ppm)
-20	120	1924.992	1924.983987	-4.16	±10
20	102	1924.992	1924.983933	-4.19	±10
	138	1924.992	1924.984018	-4.15	±10
50	120	1924.992	1924.983958	-4.18	±10

 $\pi/4$ -DQPSK

Temperature (°C)	Voltage (V _{AC} ☒ , V _{DC} ☐)	Channel Frequency (MHz)	Measurement (MHz)	Measured Frequency Offset (ppm)	Limit (ppm)
-20	120	1924.992	1924.975974	-8.33	±10
20	102	1924.992	1924.975924	-8.35	±10
	138	1924.992	1924.975977	-8.32	±10
50	120	1924.992	1924.975995	-8.31	±10

 $\pi/8$ -D8PSK

Temperature (°C)	Voltage (V _{AC} ☒ , V _{DC} ☐)	Channel Frequency (MHz)	Measurement (MHz)	Measured Frequency Offset (ppm)	Limit (ppm)
-20	120	1924.992	1924.992000	0.00	±10
20	102	1924.992	1924.992006	0.00	±10
	138	1924.992	1924.991980	-0.01	±10
50	120	1924.992	1924.991980	-0.01	±10

§ 15.323 (c)(e) § 15.319 (f) & RSS-213 §5.1&§5.2 SPECIFIC REQUIREMENTS FOR UPCS DEVICE

Applicable Standard

FCC§15.323(c)(e) & §15.319(f) Specific Requirements for UPCS device.

ANSI C63.17 2013 §6.2 Frequency and time stability and §7.Monitoring tests and §8.Time and spectrum window access procedure.

According to RSS-213 §5.1&§5.2 type of modulation and access protocol


Equipment certified under this standard shall use digital modulation.

In order to provide equitable access to the radio frequency spectrum, the licence-exempt PCS device must possess an access protocol.

Test Procedure

Measurement method according to ANSI C63.17- 2013

Test configuration as below



Test Data

Environmental Conditions

Temperature:	27.8 °C
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa

The testing was performed by Mike Xiao on 2023-04-13.

Test Result: Pass

Please see the below data

1) Automatic Discontinuation of Transmission

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. The provisions in this section are not intended to preclude transmission of control and signaling information or use of repetitive codes used by certain digital technologies to complete frame or burst intervals.

Test result:

The following tests were performed after a connection had been established with Headset.

Test condition	Reaction of EUT	Pass/Fail
Adapter removed from EUT	Connection break down	Pass

2) Monitoring Time

Immediately prior to initiating transmission, devices must monitor the combined time and spectrum window in which they intend to transmit. For a period of at least 10 milliseconds for systems designed to use a 10 milliseconds or shorter frame period or at least 20 milliseconds for systems designed to use a 20 milliseconds frame period

Test procedure:

Measurement method is in according to ANSI C63.17 -2013 clause 7.3.3.

RF signal generators apply uniform CW interference on all system carriers except two carriers (designated f_1 and f_2), each at level $T_L + U_M$. EUT can only transmit on these two carriers.

Test result:

This requirement is covered by the results of Least Interfered Channel (LIC).

Interference (Refer to ANSI C63.17 clause 7.3.3)	Reaction of EUT	Results
a) Apply the interference on f_1 at level $T_L + U_M + 20\text{dB}$ and no interference on f_2 . Initiate transmission and verify the transmission only on f_2 . Then terminate it.	EUT transmits on f_2	Pass
b) Apply the interference on f_2 at level $T_L + U_M + 20\text{dB}$ and immediately remove all interference from f_1 . The EUT should immediately attempt transmission on f_1 (but at least 20 ms after the interference on f_2 is applied), verify the transmission only on f_1 .	EUT transmission f_1	Pass

3) Lower Monitoring Threshold

The monitoring threshold must not be more than 30 dB above the thermal noise power for a bandwidth equivalent to the emission bandwidth used by the device.

Test procedure:

Measurement method according to ANSI C63.17 -2013 clause 7.3.1

Test result:

Not applicable because the EUT has more 40 defined duplex system access channels and meet the provision of the Least Interfered Channel (LIC).

4) Maximum Transmit Period

If no signal above the threshold level is detected, transmission may commence and continue with the same emission bandwidth in the monitored time and spectrum windows without further monitoring. However, occupation of the same combined time and spectrum windows by a device or group of cooperating devices continuously over a period of time longer than 8 hours is not permitted without repeating the access criteria.

Test procedure:

The test procedure is as follows:

- a) Activate the EUT and initiate a communication channel with the companion device, and start a timer or frame counter.
- b) The centre frequency of spectrum analyzer was set to the carrier frequency and SPAN was set to ZERO. The spectrum analyzer was used to monitor the time and spectrum window of the communication channel.
- c) Stop the timer at the end of the EUT transmission on the current time and frequency window (measure the time until the EUT changes to a different slot).

Test result:

Repetition of Access Criteria	Measured Maximum Transmission Time (Second)	Limit (Second)	Results
First	18270	28,800	Pass
Second	18270	28,800	Pass

5) System Acknowledgement

Once access to specific combined time and spectrum windows is obtained an acknowledgment from a system participant must be received by the initiating transmitter within one second or transmission must cease.

Periodic acknowledgments must be received at least every 30 seconds or transmission must cease. Channels used exclusively for control and signaling information may transmit continuously for 30 seconds without receiving an acknowledgment, at which time the access criteria must be repeated.

Test procedure:

Measurement method according to ANSI C63.17 2013 clause 8.1, 8.2, 8.2.1

During testing initial transmission without acknowledgement, the signal from the EUT to the companion device is blocked by the circulator.

The test of the transmission time after loss of acknowledgements is performed by cutting off the signal from the companion device by a RF switch and measuring the time until the EUT stops transmitting.

Test result:

Test	Time taken (second)	Limit (second)	Result
Initial Connection acknowledgement	0.39	1	Pass
Change of access criteria for control information	N/A	30	N/A
Transmission cease time after loss of acknowledgement	4.16	30	Pass

Note: N/A=Not Applicable

6) Least Interfered Channel (LIC)

If access to spectrum is not available as determined by the above, and a minimum of 20 duplex system access channels are defined for the system, the time and spectrum windows with the lowest power level may be accessed.

A device utilizing the provisions of this paragraph (5) must have monitored all access channels defined for its system within the last 10 seconds and must verify, within the 20 milliseconds (40 milliseconds for devices designed to use a 20 millisecond frame period) immediately preceding actual channel access, that the detected power of the selected time and spectrum windows is no higher than the previously detected value.

The power measurement resolution bandwidth for this comparison must be accurate to within 6 dB. No device or group of cooperating devices located within 1 metre of each other shall during any frame period occupy more than 6 MHz of aggregate bandwidth, or alternatively, more than one third of the time and spectrum windows defined by the system.

Calculation of monitoring threshold limits for isochroous devices:

Lower threshold: $T_L = -174 + 10\log_{10}B + M_L + P_{MAX} - P_{EUT}$ (dBm)

Where: B=Emission bandwidth (Hz)

M_L = dB the threshold may exceed thermal noise (30 for T_L)

$P_{MAX} = 5\log_{10}B - 10$ (dBm)

P_{EUT} = Transmitted power (dBm)

Calculated thresholds:

Monitor Threshold	B(MHz)	M _L (dB)	P _{MAX} (dBm)	P _{EUT} (dBm)	Threshold (dBm)
Lower threshold	1.704	30	21.16	19.89	-80.41

Note: 1. The upper threshold is applicable as the EUT utilizes more than 20 duplex system channels

Test procedure:

Measurement method according to ANSI C63.17 clause 7.3.2, 7.3.3

C63.17 clause 7.3.2, LIC procedure test:

4. Allow EUT transmission on only two carrier frequencies, which will be designated f_1 and f_2 .
 5. Apply interference to the EUT on f_1 at a level of $TL + UM + 7$ dB and on f_2 at a level of $TL + UM$. Initiate transmission. The EUT should transmit on f_2 . Terminate the connection. Repeat five times. If the EUT transmits once on f_1 , the test failed.
 6. Apply interference to the EUT on f_1 at a level of $TL + UM$ and on f_2 at a level of $TL + UM + 7$ dB. Initiate transmission. The EUT should transmit on f_1 . Terminate the connection. Repeat five times. If the EUT transmits once on f_2 , the test failed.
 7. Apply interference to the EUT on f_1 at a level of $TL + UM + 1$ dB and on f_2 at a level of $TL + UM - 6$ dB. Initiate transmission. If the EUT transmits on f_2 , terminate the connection. Repeat five times. If the EUT transmits once on f_1 , the test failed.
- e) Apply interference to the EUT on f_1 at a level of $TL + UM - 6$ dB and on f_2 at a level of $TL + UM + 1$ dB. Initiate transmission. If the EUT transmits on f_1 , terminate the connection. Repeat five times. If the EUT transmits once on f_2 , the test failed.

C63.17 clause 7.3.3, Selected channel confirmation:

- a) Allow EUT transmission on only two carrier frequencies, which will be designated f_1 and f_2 . This limitation to carriers f_1 and f_2 is performed preferably by administration commands for the EUT, or alternatively by applying by a multicarrier interference generator uniform interference on all system carriers except f_1 and f_2 , at a level of $TL + UM + 20$ dB in-band per carrier. Set the interference level to the EUT on f_1 to a level of $TL + UM + 20$ dB, and let there be no interference applied on f_2 .
- b) Initiate transmission and verify that the EUT transmits on f_2 . If a connection was made, terminate it.
- c) Apply interference on f_2 at a level of $TL + UM + 20$ dB in-band, and immediately remove all interference from f_1 and immediately (but not sooner than 20 ms after the interference on f_2 is applied) cause the EUT to attempt transmission. The EUT should now transmit on f_1 , if it transmits.
- d) If the EUT transmits on f_2 , it fails.

Test result:**1) LIC procedure test:**

Interference (Refer to ANSI C63.17 clause 7.3.3)	Reaction of EUT	Results
a) Apply the interference on f_1 at level $T_L+U_M+7\text{dB}$ and the interference on f_2 at level T_L+U_M . Initiate transmission and verify the transmission only on f_2 . Repeat 5 times.	EUT transmits on f_2	Pass
b) Apply the interference on f_1 at level T_L+U_M and the interference on f_2 at level $T_L+U_M+7\text{dB}$. Initiate transmission and verify the transmission only on f_1 . Repeat 5 times.	EUT transmits on f_1	Pass
c) Apply the interference on f_1 at level $T_L+U_M+1\text{dB}$ the interference on f_2 at level $T_L+U_M-6\text{dB}$. Initiate transmission and verify the transmission only on f_2 . Repeat 5 times.	EUT transmits on f_2	Pass
d) Apply the interference on f_1 at level $T_L+U_M-6\text{dB}$ and the interference on f_2 at level $T_L+U_M+1\text{dB}$. Initiate transmission and verify the transmission only on f_1 . Repeat 5 times.	EUT transmits on f_1	Pass

2) Selected channel confirmation:

Interference (Refer to ANSI C63.17 clause 7.3.4)	Reaction of EUT	Results
a) Apply the interference on f_1 at level T_U+U_M and no interference on f_2 . Initiate transmission and verify the transmission only on f_2 . Then terminate it.	EUT transmits on f_2	Pass
b) Apply the interference on f_2 at level T_L+U_M and immediately remove all interference from f_1 . The EUT should immediately attempt transmission on f_1 (but at least 20 ms after the interference on f_2 is applied), verify the transmission only on f_1 .	EUT transmission f_1	Pass

7) Random waiting

If the selected combined time and spectrum windows are unavailable, the device may either monitor and select different windows or seek to use the same window after waiting an amount of time, randomly chosen from a uniform random distribution between 10 and 150 milliseconds, commencing when the channel becomes available.

Test procedure:

This test is for EUTs that transmit control and signaling channels and that use the provisions of FCC §15.323(c)(6) & IC RSS-213 5.2(6), thus to verify that the EUT (if in deferral) waits for a channel to go clear, then implements a 10 ms to 150 ms hold off prior to using the channel. FCC §15.323(c)(6) is not restrictive for EUTs that use the LIC and offer 20 or more duplex communications channels, as a combined time and spectrum window cannot become unavailable as there is no threshold limit. Test method according to ANSI C63.17 2013 clause 8.1.2 or 8.1.3

8. Restrict operation of the EUT to a single carrier designated f_1 . For TDMA system, further restrict EUT transmission to a single timeslot of the usable timeslots available in the TDMA frame structure and synchronize the interference so as to occur centered within the timeslot.

9. Activate the EUT with no interference present. The EUT must transmit on f_1 . Then apply CW interference on f_1 . The interference level shall be at $TL + UM$ as appropriate for EUTs that do or do not meet the requirements for using the upper threshold. The EUT must stop transmitting within 30 s.
 10. Cancel the interference. Measure the time interval between the end of the interference transmission and the beginning of transmission by the EUT.
- d) Repeat step b) and step c) 100 times. If the measured time intervals vary uniformly between 10 ms and 150 ms, the EUT passes the test.

Note: This is Not Applicable

8) Monitoring Bandwidth and Reaction Time

The monitoring system bandwidth must be equal to or greater than the emission bandwidth of the intended transmission and have a maximum reaction time less than $50\sqrt{1.25/\text{emission bandwidth in MHz}}$ microseconds for signals at the applicable threshold level but shall not be required to be less than 50 microseconds.

Note: Testing of the monitoring system bandwidth is not required if the designed bandwidth from the manufacturer is available and given in the test report.

The maximum reaction time of the monitor shall be less than $50\sqrt{1.25/\text{occupied bandwidth in MHz}}$ μs for signals at the applicable threshold level but shall not be required to be less than 50 μs .

If a signal of 6 dB or more above the threshold level is detected, the maximum reaction time shall be $35\sqrt{1.25/\text{occupied bandwidth in MHz}}$ μs but shall not be required to be less than 35 μs .

Test procedure:

Measurement method according to ANSI C63.17 2013 clause 7.4 & 7.5

11. Restrict the EUT to a single transmit carrier frequency f_1 , and verify that the EUT can establish a connection with no interference applied on f_1 .
 12. Apply time-synchronized, pulsed interference on f_1 at the pulsed level $TL + UM$, verify that the EUT does not establish a connection when the width of the interference pulse exceeds the largest of 50 μs and $50\sqrt{1.25/B}$ μs , where B is the emission bandwidth of the EUT in megahertz.
- c) With the channel interference level 6 dB above $TL + UM$, verify that the EUT does not establish a connection when the width of the interference pulse exceeds the largest of 35 μs and $35\sqrt{1.25/B}$ μs , where B is the emission bandwidth of the EUT in megahertz.

Test Pulse width Equation (μs)	B(bandwidth) (MHz)	Pulse width (μs)	Limit (μs)
$50 (1.25/B)^{1/2}$	1.704	42.82	50
$35 (1.25/B)^{1/2}$	1.704	29.98	35

Test result:**1) Monitoring Bandwidth:**

The antenna of the EUT used for monitoring is the same interior antenna that used for transmission, so the monitoring system bandwidth is equal to the emission bandwidth of the intended transmission

2) Reaction Time Test:

No.	Interference Pulse width (μs)	Reaction of EUT	Observing time (μs)	Result
1	50μs with level T_L+U_M	No transmission	27.24	Pass
2	35μs with level $T_L+U_M+6\text{dB}$	No transmission	22.82	Pass

9) Monitoring Antenna

The monitoring system shall use the same antenna used for transmission, or an antenna that yields equivalent reception at that location.

Test procedure:

Measurement method according to ANSI C63.17 -2013 paragraph 4

Test result:

The antenna of the EUT used for transmission is the same interior antenna that used for monitoring.

10) Monitoring threshold relaxation

Devices that have a power output lower than the maximum permitted under the rules can increase their monitoring detection threshold by one decibel for each one decibel that the transmitter power is below the maximum permitted.

Test procedure:

Measurement method according to ANSI C63.17 -2013 clause 7.4 & paragraph 4

Test result:

This requirement is covered by the results of Least Interfered Channel (LIC).

11) Duplex Connections

An initiating device may attempt to establish a duplex connection by monitors both its intended transmit and receive time and spectrum windows. If both the intended transmit and receive time and spectrum windows meet the access criteria, then the initiating device can initiate a transmission in the intended transmit time and spectrum window. If the power detected by the responding device can be decoded as a duplex connection signal from the initiating device, then the responding device may immediately begin transmitting on the receive time and spectrum window monitored by the initiating device.

Test procedure:

This test validates proper operation of an EUT that operates according to the provisions of FCC §15.323(c)(10) using a check of both transmit and receive channels on one end of the link to qualify both ends of the link for transmissions. Test method according to ANSI C63.17 clause 8.3.2 Validation of dual access criteria check for EUTs that implement the upper threshold

13. Adjust the path loss between the EUT and its companion device such that the received signal to the EUT from the companion device is at least 40 dB above $TL + UM$.
 14. Restrict the EUT and its companion device to operation at a single carrier f_1 for TDMA systems and on f_1 and f_2 and corresponding duplex carriers for FDMA systems. Verify that the EUT and its companion device can establish a connection on a time/spectrum window on the enabled carrier(s). Terminate the connection.
- c) Apply interference to the EUT on the EUT's *transmit* time/spectrum windows at $TL + UM$ per carrier on all time/spectrum windows except for one, which has interference at least 10 dB below TL . Adjust the interference to the EUT on its *receive* time/spectrum windows such that a single time/spectrum window has interference at least 10 dB below TL , and the interference on the other time/spectrum windows is at $TL + UM + 7$ dB. The interference to the companion device should be at least 10 dB below TL on all active time/spectrum windows. The interference-free *receive* time/spectrum window must not be the duplex mate of the interference-free *transmit* time/spectrum window.
- d) Cause the EUT to attempt to establish a connection. The connection should be made on the interference-free *receive* time/spectrum window and its duplex mate. Otherwise, the EUT fails the test.
- e) If a connection exists, terminate it. Reduce the interference on the EUT's *receive* time/spectrum windows to a level of $TL + UM$ per carrier on all time/spectrum windows except for one, which has interference at least 10 dB below TL . Raise the interference on the EUT's *transmit* time/spectrum windows to a level of $TL + UM + 7$ dB, maintaining one time/spectrum window with interference at least 10 dB below TL . The interference to the companion device should be at least 10 dB below TL on all active time/spectrum windows. Again, the interference-free *transmit* and *receive* time/spectrum windows should not constitute a duplex pair if the system designates a specific duplex pairing for time/spectrum windows.
- f) Cause the EUT to attempt to establish a connection. The connection should be made on the interference-free *transmit* time/spectrum window and its duplex mate. Otherwise, the system fails the test.
- g) Terminate the connection and raise the interference to the EUT on all of the EUT's *transmit* and *receive* time/spectrum windows to $TU + UM$ per carrier on all time/spectrum windows except for a single *transmit* time/spectrum window and a single *receive* time/spectrum window, which shall have interference at least 10 dB below TL . The low-interference *transmits* and *receives* time/spectrum windows shall not constitute a duplex pair. Adjust the path loss between the EUT and its companion device such that the received signal to the EUT from the companion device is at least 30 dB above TU . Cause the EUT to attempt to establish a connection. If a connection is established, the test fails.

Test result:

Not applicable for FP

12) Alternative monitoring interval

An initiating device that is prevented from monitoring during its intended transmit window due to monitoring system blocking from the transmissions of a co-located (within one meter) transmitter of the same system, may monitor the portions of the time and spectrum windows in which they intend to receive over a period of at least 10 milliseconds. The monitored time and spectrum window must total at least 50 percent of the 10 millisecond frame interval and the monitored spectrum must be within 1.25 MHz of the center frequency of channel(s) already occupied by that device or co-located co-operating devices. If the access criteria is met for the intended receive time and spectrum window under the above conditions, then transmission in the intended transmit window by the initiating device may commence.

Test procedure:

This test validates the ability of the EUT to distinguish between same-system and other-system interference for purposes of satisfying the requirement of 47CFR15.323(c) (11). Test method according to ANSI C63.17 2013 clause 8.4

15. Adjust the path loss between the EUT and its companion device such that the received signal to the EUT from the companion device is at least 30 dB above TL .
16. Restrict the EUT and its companion device to operation at a single carrier f_1 for TDMA systems and on f_1 and f_2 and corresponding duplex carriers for FDMA systems. Verify that the EUT and its companion device can establish a connection.
17. Apply interference at $TL + UM$ per carrier to the EUT on all *transmit* time/spectrum windows on the enabled carrier(s). The interference must use the same physical layer parameters (modulation, frame format, etc.) as the EUT transmissions, but with a system identifier different from that used by the EUT and the companion device. Ensure that the interference level at the companion device is at least 10 dB below TL . Apply no interference to the *receive* time/spectrum windows on the enabled carriers.

d) Cause the EUT to attempt to establish a connection. If a connection is established, the test fails.

Test result:

Interference (Refer to ANSI C63.17 § 8.4)	Reaction of EUT	Results
a) Only a single carrier f_1 for EUT TDMA systems and on f_1 and f_2 and corresponding duplex carriers for FDMA systems.	EUT can transmit	Pass
b) Apply interference with same parameters as EUT transmissions on all Tx windows with level $TL+UM$ on the enabled carrier(s) and no interference on the Rx windows on the enabled carriers.	No connection is established	Pass

IC:

Not appropriate, as the system always monitor both the transmit and receive time/spectrum windows, it is not a co-located device.

13) Fair Access

The provisions of FCC §15.323 (c) & paragraphs 5.2 (10) or (11) shall not be used to extend the range of spectrum occupied over space or time for the purpose of denying fair access to spectrum to other devices.

Test result:

The manufacturer declares that this device does not use any mechanisms as provided by FCC §15.323(c)(10) or (11) & IC RSS-213 5.2(10) and (11) to extend the range of spectrum occupied over space or time for the purpose of denying fair access to spectrum to other device.

14) Frame Repetition Stability Frame Period and Jitter

The frame period (a set of consecutive time slots in which the position of each time slot can be identified by reference to a synchronizing source) of an intentional radiator operating in these sub-bands shall be 20 milliseconds or 10 milliseconds/X where X is a positive whole number. Each device that implements time division for the purposes of maintaining a duplex connection on a given frequency carrier shall maintain a frame repetition rate with a frequency stability of at least 50 parts per million (ppm). Each device which further divides access in time in order to support multiple communication links on a given frequency carrier shall maintain a frame repetition rate with a frequency stability of at least 10 ppm. The jitter (time-related, abrupt, spurious variations in the duration of the frame interval) introduced at the two ends of such a communication link shall not exceed 25 microseconds for any two consecutive transmissions. Transmissions shall be continuous in every time and spectrum window during the frame period defined for the device.

Test procedure:

Measurement method according to ANSI C63.17 2013 clause 6.2.2, 6.2.3

Test result:

Frame Period and Jitter:

Max. pos. Jitter (μ s)	Max. neg. Jitter (μ s)	Frame period (ms)	Limit	
			Frame Period (ms)	Jitter (μ s)
0.03	-0.02	10.22	20 or 10/X	25

Note: X is a positive whole number.

***** END OF REPORT *****