

TEST REPORT

Test report no.: 1-9320-25-02-04_TR1-R02



Deutsche
Akkreditierungsstelle
D-PL-12047-01-00

Testing laboratory

cetecom advanced GmbH

Untertuerkheimer Strasse 6 – 10

66117 Saarbruecken / Germany

Phone: + 49 681 5 98 - 0

Fax: + 49 681 5 98 - 9075

Internet: <https://cetecomadvanced.com>

e-mail: mail@cetecomadvanced.com

Accredited Testing Laboratory:

The testing laboratory (area of testing) is accredited according to DIN EN ISO/IEC 17025 (2018-03) by the Deutsche Akkreditierungsstelle GmbH (DAkkS).

The accreditation is valid for the scope of testing procedures as stated in the accreditation certificate with the registration number:

D-PL-12047-01-00.

ISED Testing Laboratory Recognized Listing Number: DE0001

FCC designation number: DE0002

Applicant

Panasonic Industrial Devices Europe GmbH

Zeppelinstrasse 19

21337 Lüneburg / GERMANY

Phone: +49-4131-899-0

Contact: Marcus Nottorf

e-mail: marcus.nottorf@eu.panasonic.com

Manufacturer

Panasonic Industrial Devices Europe GmbH

Zeppelinstrasse 19

21337 Lüneburg / GERMANY

Test standard/s

FCC 47 CFR Part 15

FCC - Title 47 of the Code of Federal Regulations; Chapter I; Part 15 – Radio frequency devices

RSS-247:Issue 4 (2025-07)

RSS-247 – Digital Transmission Systems, Frequency Hopping Systems and Licence-Exempt Local Area Network Devices in 902-928 MHz, 2400-2483.5 MHz, 5150-5350 MHz, and 5470-5895 MHz bands

For further applied test standards please refer to section 3 of this test report.

Test Item

Kind of test item: WiFi / BLE Module

Model name: PAN W602-2B

FCC ID: T7V-W602

ISED certification number: 216Q-W602

Frequency: UNII bands: 5150 MHz to 5250 MHz; 5250 MHz to 5350 MHz; 5470 MHz to 5725 MHz; 5725 MHz to 5850 MHz

Technology tested: WLAN

Antenna: Two different external antennas

Power supply: 3.3 V DC by PCB

Temperature range: -40°C to +85°C

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

Test report authorized:

cn=Michael Dorongovski-Kerbusch, o,
ou,
email=michael.dorongovski@cetecom
advanced.com, c=DE
2026.07.08 10:53:37 +02'00'

Michael Dorongovski
Lab Manager
Regulatory Services Radio

Test performed:

cn=David Lang, o=cetecom advanced GmbH,
ou=LNG-230530,
email=david.lang@cetecomadvanced.com,
c=DE
2026.07.08 11:07:28 +02'00'

David Lang
Coordinator Area
Regulatory Services Radio

1 Table of contents

1	Table of contents.....	2
2	General information.....	3
2.1	Notes and disclaimer.....	3
2.2	Application details.....	3
2.3	Test laboratories sub-contracted.....	3
3	Test standard/s, references and accreditations.....	4
4	Reporting statements of conformity – decision rule.....	5
5	Test environment.....	5
6	Test item.....	6
6.1	General description.....	6
6.2	Additional information.....	6
7	Description of the test setup.....	7
7.1	Shielded semi anechoic chamber.....	8
7.2	Shielded fully anechoic chamber.....	9
7.3	Radiated measurements > 18 GHz.....	11
8	Sequence of testing.....	12
8.1	Sequence of testing radiated spurious 9 kHz to 30 MHz.....	12
8.2	Sequence of testing radiated spurious 30 MHz to 1 GHz.....	13
8.3	Sequence of testing radiated spurious 1 GHz to 18 GHz.....	14
8.4	Sequence of testing radiated spurious above 18 GHz.....	15
9	Measurement uncertainty.....	16
10	Summary of measurement results.....	17
11	Additional comments.....	18
12	Measurement results.....	20
12.1	Identify worst case data rate.....	20
12.2	Antenna gain.....	21
12.3	Maximum output power.....	22
12.4	Maximum output power according to FCC requirements.....	22
12.5	Maximum output power according to ISED requirements.....	24
12.6	Power spectral density.....	25
12.7	Power spectral density according to FCC requirements.....	25
12.8	Power spectral density according to ISED requirements.....	27
12.9	Band edge compliance radiated (2JF1002P antenna).....	28
12.10	Band edge compliance radiated (Taoglas GW.51.5153 antenna).....	34
12.11	Spurious emissions radiated below 30 MHz (2JF1002P antenna).....	40
12.12	Spurious emissions radiated below 30 MHz (Taoglas GW.51.5153 antenna).....	45
12.13	Spurious emissions radiated 30 MHz to 1 GHz (2JF1002P antenna).....	50
12.14	Spurious emissions radiated 30 MHz to 1 GHz (Taoglas GW.51.5153 antenna).....	55
12.15	Spurious emissions radiated 1 GHz to 40 GHz (2JF1002P antenna).....	60
12.16	Spurious emissions radiated 1 GHz to 40 GHz (Taoglas GW.51.5153 antenna).....	67
12.17	Observations.....	74
13	Glossary.....	74
14	Document history.....	75

2 General information

2.1 Notes and disclaimer

The test results of this test report relate exclusively to the test item specified in this test report. cetecom advanced GmbH does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item.

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of cetecom advanced GmbH.

The testing service provided by cetecom advanced GmbH has been rendered under the current "General Terms and Conditions for cetecom advanced GmbH".

cetecom advanced GmbH will not be liable for any loss or damage resulting from false, inaccurate, inappropriate or incomplete product information provided by the customer.

Under no circumstances does the cetecom advanced GmbH test report include any endorsement or warranty regarding the functionality, quality or performance of any other product or service provided.

Under no circumstances does the cetecom advanced GmbH test report include or imply any product or service warranties from cetecom advanced GmbH, including, without limitation, any implied warranties of merchantability, fitness for purpose, or non-infringement, all of which are expressly disclaimed by cetecom advanced GmbH.

All rights and remedies regarding vendor's products and services for which cetecom advanced GmbH has prepared this test report shall be provided by the party offering such products or services and not by cetecom advanced GmbH.

In no case this test report can be considered as a Letter of Approval.

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

This test report replaces the test report with the number 1-9320-25-02-04_TR1-R01 and dated 2026-06-30.

2.2 Application details

Date of receipt of order:	2026-05-11
Date of receipt of test item:	2026-05-29
Start of test:*	2026-05-29
End of test:*	2026-06-26
Person(s) present during the test:	-/-

*Date of each measurement, if not shown in the plot, can be requested. Dates are stored in the measurement software.

2.3 Test laboratories sub-contracted

None

3 Test standard/s, references and accreditations


Test standard	Date	Description
FCC 47 CFR Part 15	-/-	FCC - Title 47 of the Code of Federal Regulations; Chapter I; Part 15 – Radio frequency devices
RSS-247:Issue 4 (2025-07)	2025-07-24	RSS-247 – Digital Transmission Systems, Frequency Hopping Systems and Licence-Exempt Local Area Network Devices in 902-928 MHz, 2400-2483.5 MHz, 5150-5350 MHz, and 5470-5895 MHz bands
RSS-Gen:Issue 5 (2018-04) + Amendment 1 (2019-03) + Amendment 2 (2021-02)	2021-02-01	General Requirements for Compliance of Radio Apparatus

Guidance	Version	Description
KDB 789033 D02	v02r01	Guidelines for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices - Part 15, Subpart E
ANSI C63.10-2020	-/-	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
ANSI/USEMCSC C63.10a-2024 Amendment 1	2024-08-08	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices Amendment 1
ANSI/USEMCSC C63.10a-2024 Amendment 1 Errata	2024-11-18	Errata to American National Standard for Procedures for Compliance Testing of Unlicensed Wireless Devices Amendment 1
KDB 174176 D01	V01r02	Correction Sheet AC POWER LINE CONDUCTED EMISSIONS FREQUENTLY ASKED QUESTIONS

4 Reporting statements of conformity – decision rule

Only the measured values related to their corresponding limits will be used to decide whether the equipment under test meets the requirements of the test standards listed in chapter 3.

The measurement uncertainty is mentioned in this test report, see chapter 9, but is not taken into account - neither to the limits nor to the measurement results. Measurement results with a smaller margin to the corresponding limits than the measurement uncertainty have a potential risk of more than 5% that the decision might be wrong."



5 Test environment

Temperature	:	T_{nom} T_{max} T_{min}	+20 °C during room temperature tests No tests under extreme environmental conditions required. No tests under extreme environmental conditions required.
Relative humidity content	:		49 %
Barometric pressure	:		1021 hpa
Power supply	:	V_{nom} V_{max} V_{min}	3.3 V DC by PCB No tests under extreme environmental conditions required. No tests under extreme environmental conditions required.

6 Test item

6.1 General description

Kind of test item	:	WiFi / BLE Module
Model name	:	PAN W602-2B
HMN	:	N/A
PMN	:	PAN W602-2C PAN W602-2B
HVIN	:	ENWF9215A ENWF9215C
FVIN	:	N/A
S/N serial number	:	Board 2: Taoglas GW.51.5153 antenna Board 8: 2J Antennas 2JF1002P antenna
Hardware status	:	03
Software status	:	01
Firmware status	:	TBD
Frequency band	:	UNII bands: 5150 MHz to 5250 MHz; 5250 MHz to 5350 MHz; 5470 MHz to 5725 MHz; 5725 MHz to 5850 MHz
Type of radio transmission : Use of frequency spectrum :	:	OFDM, OFDMA
Type of modulation	:	(D)BPSK, (D)QPSK, 16 – QAM, 64 – QAM
Number of channels	:	24 with 20 MHz channel bandwidth
Antenna	:	Two different external antennas; Taoglas GW.51.5153 antenna & 2JF1002P antenna. Band specific gains can be found in section 12.2 of this document.
Power supply	:	3.3 V DC by PCB
Temperature range	:	-40°C to +85°C

6.2 Additional information

The content of the following annexes is defined in the QA. It may be that not all of the listed annexes are necessary for this report, thus some values in between may be missing.

Test setup and EUT photos are included in test report: 1-9320-25-02-01_TR1-A101-R01
1-9320-25-02-01_TR1-A102-R01

7 Description of the test setup

Typically, the calibrations of the test apparatus are commissioned to and performed by an accredited calibration laboratory. The calibration intervals are determined in accordance with the DIN EN ISO/IEC 17025. In addition to the external calibrations, the laboratory executes comparison measurements with other calibrated test systems or effective verifications. Weekly chamber inspections and range calibrations are performed. Where possible, RF generating and signaling equipment as well as measuring receivers and analyzers are connected to an external high-precision 10 MHz reference (GPS-based or rubidium frequency standard).

In order to simplify the identification of the equipment used at some special tests, some items of test equipment and ancillaries can be provided with an identifier or number in the equipment list below (Lab/Item).


Each block diagram listed can contain several test setup configurations. All devices belonging to a test setup are identified with the same letter syntax. For example: Column Setup and all devices with an A.

Agenda: Kind of Calibration

k/cal	calibration / calibrated	EK	limited calibration
Ne/cnn	not required (k, ev, izw, zw not required)	zw	cyclical maintenance (external cyclical maintenance)
Ev/chk	periodic self verification	izw	internal cyclical maintenance
Ve	long-term stability recognized	g	blocked for accredited testing
vlk!	Attention: extended calibration interval		
NK!	Attention: not calibrated	*)	next calibration ordered / currently in progress
cpu	check prior usage		

7.1 Shielded semi anechoic chamber

The radiated measurements are performed in vertical and horizontal plane in the frequency range from 30 MHz to 1 GHz in semi-anechoic chambers. The EUT is positioned on a non-conductive support with a height of 0.80 m above a conductive ground plane that covers the whole chamber. The receiving antennas are conform to specifications ANSI C63. These antennas can be moved over the height range between 1.0 m and 4.0 m in order to search for maximum field strength emitted from EUT. The measurement distances between EUT and receiving antennas are indicated in the test setups for the various frequency ranges. For each measurement, the EUT is rotated in all three axes until the maximum field strength is received. The wanted and unwanted emissions are received by spectrum analyzers where the detector modes and resolution bandwidths over various frequency ranges are set according to requirement ANSI C63.



Measurement distance: tri-log antenna 10 meter
EMC32 software version: 10.59.00

$FS = UR + CL + AF$

(FS-field strength; UR-voltage at the receiver; CL-loss of the cable; AF-antenna factor)

Example calculation:


$FS [dB\mu V/m] = 12.35 [dB\mu V/m] + 1.90 [dB] + 16.80 [dB/m] = 31.05 [dB\mu V/m] \quad (35.69 \mu V/m)$

Equipment table:

Equipment table:

No.	Setup	Equipment	Type	Manufacturer	Serial No.	INV. No.	Kind of Calibration	Last Calibration	Next Calibration
1	A	Switch-Unit	Switch-Unit 3488A	Hewlett Packard	2719A14505	50160	cpu	-/-	-/-
2	A	Positioning Controller	Positioning Controller 2090	ETS-Lindgren GmbH Taufkirchen	64672	50280	cnn	-/-	-/-
3	A	TRILOG Broadband Antenna	TRILOG Broadband Antenna VULB9163	Schwarzbeck MESS-ELEKTRONIK OHG Schönaun	1029	50403	cal	07.11.2025	30.11.2027
4	A	EMI Test Receiver	EMI Test Receiver ESR3 9kHz-3.6GHz	Rohde & Schwarz Messgerätebau GmbH Memmingen	102587	50417	cal	08.12.2025	31.12.2026

7.2 Shielded fully anechoic chamber



Measurement distance: horn antenna 3 meter; loop antenna 3 meter

$FS = UR + CA + AF$

(FS-field strength; UR-voltage at the receiver; CA-loss of the signal path; AF-antenna factor)

Example calculation:


$FS [dB\mu V/m] = 40.0 [dB\mu V/m] + (-35.8) [dB] + 32.9 [dB/m] = 37.1 [dB\mu V/m] (71.61 \mu V/m)$

Equipment table:

No.	Setup	Equipment	Type	Manufacturer	Serial No.	INV. No.	Kind of Calibration	Last Calibration	Next Calibration
1	A, B	Signal- and Spectrum Analyzer	Signal- and Spectrum Analyzer FSW26	Rohde & Schwarz Messgerätebau GmbH Memmingen	101455	40114	cal	08.12.2025	31.12.2026
2	A, B	Double-Ridged Waveguide Horn Antenna	Double-Ridged Waveguide Horn Antenna 3115	EMCO Elektronik GmbH Gilching	8812-3089	40344	cal	09.07.2024	31.07.2026
3	B	Highpass Filter	Highpass Filter WHK1.1/15G-10SS	Wainwright Instruments GmbH Andechs	37	40362	cnn	-/-	-/-
4	A, B	Highpass Filter	Highpass Filter WHKX7.0/18G-8SS	Wainwright Instruments GmbH Andechs	18	40364	cpu	-/-	-/-
5	A, B	Band Reject Filter	Band Reject Filter WRCG2400/2483-2375/2505-50/10SS	Wainwright Instruments GmbH Andechs	26	40367	cpu	-/-	-/-
6	A, B	Broadband Amplifier 0.5-18 GHz	Broadband Amplifier 0.5-18 GHz CBLU5184540	MEC Import: CERNEX	22050	40374	cpu	-/-	-/-
7	A, B	4U RF Switch Platform	4U RF Switch Platform L4491A	Agilent Technologies Deutschland GmbH Böblingen	MY50000032	40376	cnn	-/-	-/-
8	B	Highpass Filter	Highpass Filter WHKX2.6/18G-10SS	Wainwright Instruments GmbH Andechs	12	40377	cnn	-/-	-/-
9	A, B	NEXIO EMV-Software	NEXIO EMV-Software BAT EMC V2022.0.32.0	MEC Import: Nexio		40383	cnn	-/-	-/-

10	A, B	Anechoic chamber	Anechoic chamber	MEC Import: TDK		40385	cnn	-/-	-/-
11	A	Band Reject Filter	Band Reject Filter WRCJV12-5120- 5150-5350-5380- 40SS	Wainwright Instruments GmbH Andechs	5	40395	cpu	-/-	-/-
12	A	Band Reject Filter	Band Reject Filter WRCJV12-5695- 5725-5850-5880- 40SS	Wainwright Instruments GmbH Andechs	5	40396	cpu	-/-	-/-
13	A	Band Reject Filter	Band Reject Filter WRCJV16-5440- 5470-5725-5755- 40SS	Wainwright Instruments GmbH Andechs	9	40397	cpu	-/-	-/-
14	A, B	RF-Amplifier	RF-Amplifier AMF- 6F06001800-30-10P- R	MEC Import: NARDA-MITEQ Inc	2011572	40400	cpu	-/-	-/-
15	A, B	Active Loop Antenna	Active Loop Antenna 6502	EMCO Elektronik GmbH Gilching	2210	50044	cal	07.07.2025	31.07.2027
16	A, B	TRILOG Broadband Antenna	TRILOG Broadband Antenna VULB9163	Schwarzbeck MESS- ELEKTRONIK OHG Schönau	318	50284	cal	09.02.2026	29.02.2028

7.3 Radiated measurements > 18 GHz



Measurement distance: horn antenna 50 cm

FS = UR + CA + AF

(FS-field strength; UR-voltage at the receiver; CA-loss signal path & distance correction; AF-antenna factor)

Example calculation:

FS [dBμV/m] = 40.0 [dBμV/m] + (-60.1) [dB] + 36.74 [dB/m] = 16.64 [dBμV/m] (6.79 μV/m)

Equipment table:

No.	Setup	Equipment	Type	Manufacturer	Serial No.	INV. No.	Kind of Calibration	Last Calibration	Next Calibration
1	A	Horn Antenna 18,0-40,0 GHz	Horn Antenna 18,0-40,0 GHz LHAF180	MEC Import: Microw.Devel	39180-103-021	40170	cal	16.01.2026	31.01.2028
2	A	Low Noise Amplifier, Broadband 18-50 GHz	Low Noise Amplifier, Broadband 18-50 GHz BZT-180050000-550835-SL2525-SL	MEC Import: B&Z Technologies	27887-27889	40789	cpu	-/-	-/-
3	A	Signal- and Spectrum Analyzer	Signal- and Spectrum Analyzer FSW50	Rohde & Schwarz Messgerätebau GmbH Memmingen	101560	40011	cal	18.12.2025	31.12.2026

8 Sequence of testing

8.1 Sequence of testing radiated spurious 9 kHz to 30 MHz

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, it is placed on a table with 0.8 m height.
- If the EUT is a floor standing device, it is placed directly on the turn table.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.10.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 3 m (see ANSI C 63.10) – see test details.
- EUT is set into operation.

Premeasurement*

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 1 m.
- At each turntable position the analyzer sweeps with positive-peak detector to find the maximum of all emissions.

Final measurement

- Identified emissions during the pre-measurement are maximized by the software by rotating the turntable from 0° to 360°.
- Loop antenna is rotated about its vertical axis for maximum response at each azimuth about the EUT. (For certain applications, the loop antenna plane may also need to be positioned horizontally at the specified distance from the EUT)
- The final measurement is done in the position (turntable and elevation) causing the highest emissions with quasi-peak (as described in ANSI C 63.10).
- Final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. A plot with the graph of the premeasurement and the limit is stored.

*)Note: The sequence will be repeated three times with different EUT orientations.

8.2 Sequence of testing radiated spurious 30 MHz to 1 GHz

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.10.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 10 m or 3 m (see ANSI C 63.10) – see test details.
- EUT is set into operation.

Premeasurement

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 m to 3 m.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

Final measurement

- The final measurement is performed for at least six highest peaks according to the requirements of the ANSI C63.4.
- Based on antenna and turntable positions at which the peak values are measured the software maximize the peaks by changing turntable position $\pm 45^\circ$ and antenna height between 1 and 4 m.
- The final measurement is done with quasi-peak detector (as described in ANSI C 63.10).
- Final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement with marked maximum final results and the limit is stored.

8.3 Sequence of testing radiated spurious 1 GHz to 18 GHz

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, a 2-axis positioner with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed directly on the turn table.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.10.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 3 m (see ANSI C 63.10) – see test details.
- EUT is set into operation.

Premeasurement

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height is 1.5 m.
- At each turntable position and antenna polarization the analyzer sweeps with positive peak detector to find the maximum of all emissions.

Final measurement

- The final measurement is performed for at least six highest peaks according to the requirements of the ANSI C63.4.
- Based on antenna and turntable positions at which the peak values are measured the software maximizes the peaks by rotating the turntable from 0° to 360°. This measurement is repeated for different EUT-table positions (0° to 150° in 30°-steps) and for both antenna polarizations.
- The final measurement is done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and RMS detector (as described in ANSI C 63.10).
- Final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement with marked maximum final results and the limit is stored.

8.4 Sequence of testing radiated spurious above 18 GHz

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.10.
- The AC power port of the EUT (if available) is connected to a power outlet.
- The measurement distance is as appropriate (e.g. 0.5 m).
- The EUT is set into operation.

Premeasurement

- The test antenna is handheld and moved carefully over the EUT to cover the EUT's whole sphere and different polarizations of the antenna.

Final measurement

- The final measurement is performed at the position and antenna orientation causing the highest emissions with Peak and RMS detector (as described in ANSI C 63.10).
- Final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement and the limit is stored.

9 Measurement uncertainty

Measurement uncertainty		
Test case	Uncertainty	
Antenna gain	± 3 dB	
Power spectral density	± 1.56 dB	
DTS bandwidth	± 100 kHz (depends on the used RBW)	
Occupied bandwidth	± 100 kHz (depends on the used RBW)	
Maximum output power conducted	± 1.56 dB	
Detailed spurious emissions @ the band edge - conducted	± 1.56 dB	
Band edge compliance radiated	± 3 dB	
Spurious emissions conducted	> 3.6 GHz	± 1.56 dB
	> 7 GHz	± 1.56 dB
	> 18 GHz	± 2.31 dB
	≥ 40 GHz	± 2.97 dB
Spurious emissions radiated below 30 MHz	± 3 dB	
Spurious emissions radiated 30 MHz to 1 GHz	± 4.1 dB	
Spurious emissions radiated 1 GHz to 12.75 GHz	± 3.7 dB	
Spurious emissions radiated above 12.75 GHz	± 4.5 dB	
Spurious emissions conducted below 30 MHz (AC conducted)	± 2.6 dB	

10 Summary of measurement results

☐	No deviations from the technical specifications were ascertained
☐	There were deviations from the technical specifications ascertained
☒	This test report is only a partial test report. The content and verdict of the performed test cases are listed below.

TC Identifier	Description	Verdict	Date	Remark
RF-Testing	CFR Title 47 Part 15 RSS 247, Issue 4	See table	2026-07-08	-/-

Test specification clause	Test case	C	NC	NA	NP	Remark
-/-	Output power verification (cond.)	-/-				Declared
-/-	Antenna gain	-/-				Declared
U-NII Part 15	Duty cycle	-/-				-/-
§15.407(a) RSS - 247 (6.2.x.1)	Maximum output power (conducted & radiated)	☒	☐	☐	☐	-/-
§15.407(a) RSS - 247 (6.2.x.1)	Power spectral density	☒	☐	☐	☐	-/-
RSS - 247 (6.2.4.1)	Spectrum bandwidth 6dB bandwidth	☐	☐	☐	☒	-/-
§15.407(a) RSS - 247 (6.2.x.2)	Spectrum bandwidth 26dB bandwidth	☐	☐	☐	☒	-/-
RSS Gen clause 6.6	Spectrum bandwidth 99% bandwidth	-/-				-/-
§15.205 RSS - 247 (6.2.x.2)	Band edge compliance radiated	☒	☐	☐	☐	-/-
§15.407(b) RSS - 247 (6.2.x.2)	TX spurious emissions radiated	☒	☐	☐	☐	-/-
§15.209(a) RSS-Gen	Spurious emissions radiated < 30 MHz	☒	☐	☐	☐	-/-
§15.107(a) §15.207	Spurious emissions conducted emissions< 30 MHz	☒	☐	☐	☐	-/-
§15.407 RSS - 247 (6.3)	DFS	-/-				See report 1-9318-25-02-05

Notes:

C:	Compliant	NC:	Not compliant	NA:	Not applicable	NP:	Not performed
-----------	-----------	------------	---------------	------------	----------------	------------	---------------

11 Additional comments

Reference documents: DFS report: 1-9318-25-02-05_TR1-R01
 Main report : 1-9318-25-02-04_TR1-R01
 Customer_Questionnaire_1-9318-25-01.docx
 rf_ant_ant162442dt-2001a2_summary_en.pdf

Co-applicable documents: 1-9318-25-02-04_TR1-A201-R02.pdf (all tests)
 1-9318-25-02-04_TR1-A202-R01.pdf (PSD tests with additional RU configurations)

Special test descriptions: Power settings:

Mode	All channels
OFDM / a – mode	Default
OFDM / nHT20 – mode	Default
OFDM / ac VHT20 – mode	Default
OFDM / ax HE20 – mode	Default
OFDM / ax HE20 – mode ER	Default
OFDM / ax HE20 – mode RU0, RU8, RU37, RU40, RU53, RU54, RU61	Default

Configuration descriptions: The DUT has been controlled using a web GUI (radiated) and batch files (conducted). Only 20 MHz bandwidth is supported.

Configuration descriptions: None

EUT selection:

☐ Only one device available

☐ Devices selected by the customer

☒ Devices selected by the laboratory (Randomly)

Provided channels:

Channels with 20 MHz channel bandwidth:

U-NII-1 & U-NII-2A (5150 MHz to 5250 MHz & 5250 MHz to 5350 MHz) channel number & center frequency								
channel	36	40	44	48	52	56	60	64
f _c / MHz	5180	5200	5220	5240	5260	5280	5300	5320

U-NII-2C (5470 MHz to 5725 MHz) channel number & center frequency											
channel	100	104	108	112	116	120	124	128	132	136	140
f _c / MHz	5500	5520	5540	5560	5580	5600	5620	5640	5660	5680	5700

U-NII-3 (5725 MHz to 5850 MHz) channel number & center frequency					
channel	149	153	157	161	165
f _c / MHz	5745	5765	5785	5805	5825

Note: The channels used for the tests were marked in bold in the list.

Test mode:

- ☐ No test mode available.
Iperf is used to transmit data to a companion device
- ☒ Special software is used.
EUT is transmitting pseudo random data by itself

Antennas and transmit operating modes:

- ☒ Operating mode 1 (single antenna)
- Equipment with 1 antenna,
 - Equipment with 2 diversity antennas operating in switched diversity mode by which at any moment in time only 1 antenna is used,
 - Smart antenna system with 2 or more transmit/receive chains, but operating in a mode where only 1 transmit/receive chain is used)
- ☐ Operating mode 2 (multiple antennas, no beamforming)
- Equipment operating in this mode contains a smart antenna system using two or more transmit/receive chains simultaneously but without beamforming.
- ☐ Operating mode 3 (multiple antennas, with beamforming)
- Equipment operating in this mode contains a smart antenna system using two or more transmit/receive chains simultaneously with beamforming.
In addition to the antenna assembly gain (G), the beamforming gain (Y) may have to be taken into account when performing the measurements.

12 Measurement results

12.1 Identify worst case data rate

Worst case data rates declared by the manufacturer.

OFDM – mode	Modulation scheme / bandwidth					
	U-NII-1 & U-NII-2A		U-NII-2C		U-NII-3	
	lowest channel	highest channel	lowest channel	highest channel	lowest channel	highest channel
a – mode	6 Mbit/s	6 Mbit/s	6 Mbit/s	6 Mbit/s	6 Mbit/s	6 Mbit/s
n HT20 – mode	MCS0	MCS0	MCS0	MCS0	MCS0	MCS0
ac VHT20 – mode	MCS0	MCS0	MCS0	MCS0	MCS0	MCS0
ax HE20 – mode	MCS0	MCS0	MCS0	MCS0	MCS0	MCS0

12.2 Antenna gain

Antenna gains as declared by the manufacturer:

Limits:

Antenna Gain
6 dBi / > 6 dBi output power and power density reduction required

Results: All values are extracted from the antenna datasheet.

2JF1002P antenna:

U-NII-1 (5150 MHz to 5250 MHz)	Antenna gain		
	Lowest channel	Middle channel	Highest channel
Gain / dBi (declared)	6.6		
U-NII-2A (5250 MHz to 5350 MHz)	Antenna gain		
	Lowest channel	Middle channel	Highest channel
Gain / dBi (declared)	7.3		
U-NII-2C (5470 MHz to 5725 MHz)	Antenna gain		
	Lowest channel	Middle channel	Highest channel
Gain / dBi (declared)	8.0		
U-NII-3 (5725 MHz to 5850 MHz)	Antenna gain		
	Lowest channel	Middle channel	Highest channel
Gain / dBi (declared)	6.6		

Taoglas GW.51.5153 antenna:

U-NII-1 (5150 MHz to 5250 MHz)	Antenna gain		
	Lowest channel	Middle channel	Highest channel
Gain / dBi (declared)	3.9		
U-NII-2A (5250 MHz to 5350 MHz)	Antenna gain		
	Lowest channel	Middle channel	Highest channel
Gain / dBi (declared)	4.5		
U-NII-2C (5470 MHz to 5725 MHz)	Antenna gain		
	Lowest channel	Middle channel	Highest channel
Gain / dBi (declared)	5.5		
U-NII-3 (5725 MHz to 5850 MHz)	Antenna gain		
	Lowest channel	Middle channel	Highest channel
Gain / dBi (declared)	3.8		

12.3 Maximum output power

12.4 Maximum output power according to FCC requirements

Measurement:

Measurement parameter	
According to: KDB789033 D02, E.2.e.	
External result file(s)	1-9318-25-02-04_TR1-A201-R02.pdf FCC Part 15.407 Max Output Power and PSD
Used test setup:	See sub clause 7.4 – A
Measurement uncertainty:	See chapter 9

Limits:

Limits	
Radiated output power	Conducted output power
Band 5150 MHz – 5250 MHz	
For an outdoor access point: Conducted power + 6 dBi antenna gain For an indoor access point: Conducted power + 6 dBi antenna gain For fixed point-to-point access points Conducted power + 23 dBi antenna gain For client devices Conducted power + 6 dBi antenna gain (If the Antenna gain is greater than the Limit: 1dB reduction in the max. conducted output power for each 1 dB of antenna gain in excess of the Limit)	For an outdoor access point: output power $\leq 1\text{W}/30\text{dBm}$ The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm) For an indoor access point output power $\leq 1\text{W}/30\text{dBm}$ For fixed point-to-point access points output power $\leq 1\text{W}/30\text{dBm}$ For client devices output power $\leq 250\text{ mW}/24\text{dBm}$
Band 5250MHz – 5350 MHz	
Conducted power + 6 dBi antenna gain (Antenna gain higher than the Limit: 1dB reduction in the max. conducted output power for each 1 dB of antenna gain in excess of the Limit)	Output power $\leq$ lesser of 250mW or $11\text{dBm} + 10\log B$ (B is the 26 dB emission bandwidth in megahertz)
Band 5470MHz – 5725 MHz	
Conducted power + 6 dBi antenna gain (Antenna gain higher than the Limit: 1dB reduction in the max. conducted output power for each 1 dB of antenna gain in excess of the Limit)	Output power $\leq$ lesser of 250mW or $11\text{dBm} + 10\log B$ (B is the 26 dB emission bandwidth in megahertz)
Band 5725MHz – 5850 MHz	
Conducted power + 6 dBi antenna gain (Antenna gain higher than the Limit: 1dB reduction in the max. conducted output power for each 1 dB of antenna gain in excess of the Limit Exception: fixed point-to-point U-NII devices, no corresponding reduction in transmitter conducted power)	output power $\leq 1\text{W}/30\text{dBm}$

Results:

Conducted power [dBm]	Ch36	Ch40	Ch48	Ch52	Ch56	Ch64	Ch100	Ch120	Ch140	Ch149	Ch157	Ch165
a-mode	10.6	11.8	12.3	12.3	12.4	11.8	11.3	11.6	11.7	10.8	11.2	12.0
nHT20-mode	10.5	11.8	12.3	12.2	12.3	11.7	10.3	11.5	11.7	10.8	11.2	12.0
acVHT-mode	10.5	11.8	12.3	12.2	12.4	11.8	10.3	11.5	11.7	10.9	11.2	12.0
axHE20-SU-mode	10.6	11.9	12.3	12.3	12.4	11.8	10.5	11.6	11.3	10.6	11.1	11.8

Note¹: Values leveraged from module report 1-9318-25-02-04.

Note²: The conducted output power limit is reduced by 2 dB to consider the 8 dBi antenna gain of the 2JF1002P antenna.

12.5 Maximum output power according to ISED requirements

Description:

Measurement of the maximum output power conducted + radiated

Measurement:

Note: Values in this chapter are leveraged from module report 1-9318-25-02-04.

Measurement parameter	
External result file(s)	1-9318-25-02-04_TR1-A201-R02.pdf ISED Max Output Power and PSD

Limits:

Radiated output power	Conducted output power for mobile equipment
The lesser one of 200 mW or 10 dBm + 10 log Bandwidth 5.150-5.250 GHz 1 W or 17 dBm + 10 log Bandwidth 5.250-5.350 GHz 1 W or 17 dBm + 10 log Bandwidth 5.470-5.725 GHz (where Bandwidth is the 99% Bandwidth [MHz]) Conducted power + 6dBi antenna gain 5.725-5.825 GHz	The lesser one of 250mW or 11 dBm + 10 log Bandwidth 5.250-5.350 GHz 250mW or 11 dBm + 10 log Bandwidth 5.470-5.725 GHz (where Bandwidth is the 99% Bandwidth [MHz]) 1W 5.725-5.825 GHz

Results:

Conducted power [dBm]	Ch36	Ch40	Ch48	Ch52	Ch56	Ch64	Ch100	Ch120	Ch140	Ch149	Ch157	Ch165
a-mode	10.0	11.8	12.3	12.2	12.4	11.7	10.2	11.5	11.7	10.8	11.2	12.0
nHT20-mode	10.4	11.6	12.2	12.2	12.3	11.7	10.2	11.4	11.6	10.7	11.1	11.9
acVHT20-mode	10.4	11.8	12.2	12.2	12.4	11.7	10.3	11.5	11.6	10.8	11.1	11.9
axHE20-SU-mode	10.5	11.9	12.3	12.3	12.4	11.8	10.4	11.6	11.5	10.6	10.9	11.8

2JF1002P antenna:

Radiated power [dBm]	Ch36	Ch40	Ch48	Ch52	Ch56	Ch64	Ch100	Ch120	Ch140	Ch149	Ch157	Ch165
a-mode	16.6	18.4	18.9	19.5	19.7	19.0	18.2	19.5	19.7	17.4	17.8	18.6
nHT20-mode	17.0	18.2	18.8	19.5	19.6	19.0	18.2	19.4	19.6	17.3	17.7	18.5
acVHT20-mode	17.0	18.4	18.8	19.5	19.7	19.0	18.3	19.5	19.6	17.4	17.7	18.5
axHE20-SU-mode	17.1	18.5	18.9	19.6	19.7	19.1	18.4	19.6	19.5	17.2	17.5	18.4

Note¹: The output power limit is reduced by 2 dB to consider the 8 dBi antenna gain of the 2JF1002P antenna.

Taoglas GW.51.5153 antenna:

Radiated power [dBm]	Ch36	Ch40	Ch48	Ch52	Ch56	Ch64	Ch100	Ch120	Ch140	Ch149	Ch157	Ch165
a-mode	13.9	15.7	16.2	16.7	16.9	16.2	15.7	17.0	17.2	14.6	15.0	15.8
nHT20-mode	14.3	15.5	16.1	16.7	16.8	16.2	15.7	16.9	17.1	14.5	14.9	15.7
acVHT20-mode	14.3	15.7	16.1	16.7	16.9	16.2	15.8	17.0	17.1	14.6	14.9	15.7
axHE20-SU-mode	14.4	15.8	16.2	16.8	16.9	16.3	15.9	17.1	17.0	14.4	14.7	15.6

Note²: The highest gain of 5.5 dBi is considered for e.i.r.p calculations over all bands.

12.6 Power spectral density

12.7 Power spectral density according to FCC requirements

Measurement:

Note: Values in this chapter are leveraged from module report 1-9318-25-02-04.

Measurement parameter	
According to: KDB789033 D02, F.	
External result file(s)	1-9318-25-02-04_TR1-A201-R02.pdf 1-9318-25-02-04_TR1-A202-R01.pdf FCC Part 15.407 Max Output Power and PSD

Limits:

Power Spectral Density
Band 5150 MHz – 5250 MHz
For an outdoor access point power spectral density conducted ≤ 17 dBm in any 1 MHz band* For an indoor access point power spectral density conducted ≤ 17 dBm in any 1 MHz band* For fixed point-to-point access points power spectral density conducted ≤ 17 dBm in any 1 MHz band** For client devices point power spectral density conducted ≤ 11 dBm in any 1 MHz band* *If transmitting antennas of directional gain greater than 6 dBi are used the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi **Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi.
Band 5250MHz – 5350 MHz
power spectral density conducted ≤ 11 dBm in any 1 MHz band* *If transmitting antennas of directional gain greater than 6 dBi are used the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi
Band 5470MHz – 5725 MHz
power spectral density conducted ≤ 11 dBm in any 1 MHz band* *If transmitting antennas of directional gain greater than 6 dBi are used the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi
Band 5725MHz – 5850 MHz
power spectral density conducted ≤ 30 dBm in any 500 kHz band If transmitting antennas of directional gain greater than 6 dBi are used the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi

Results:

Power Spectral Density [dBm/MHz]	Ch36	Ch40	Ch48	Ch52	Ch56	Ch64	Ch100	Ch120	Ch140	Ch149	Ch157	Ch165
a-mode	0.1	1.3	1.8	1.8	1.9	1.2	-0.2	1.1	1.2	-2.7	-2.2	-1.4
nHT20-mode	-0.3	0.9	1.4	1.4	1.5	0.9	-0.7	0.7	0.9	-3.0	-2.6	-1.8
acVHT20-mode	-0.4	1.0	1.4	1.4	1.6	0.9	-0.6	0.7	0.9	-2.9	-2.6	-1.8
axHE20-SU-mode	-0.6	0.7	1.1	1.2	1.3	0.6	-0.7	0.2	0.4	-3.5	-3.0	-2.3

Note¹: The conducted output power limit is reduced by 2 dB to consider the 8 dBi antenna gain of the 2JF1002P antenna.

12.8 Power spectral density according to ISED requirements

Description:

Measurement of the power spectral density of a digital modulated system. The measurement is repeated at the lowest, middle and highest channel.

Measurement:

Note: Values in this chapter are leveraged from module report 1-9318-25-02-04.

Measurement parameter	
External result file(s)	1-9318-25-02-04_TR1-A201-R02.pdf ISED Max Output Power and PSD

Limits:

Power Spectral Density
power spectral density e.i.r.p. ≤ 10 dBm in any 1 MHz band (band 5150 – 5250 MHz)
power spectral density conducted ≤ 11 dBm in any 1 MHz band (band 5250 – 5350 MHz)
power spectral density conducted ≤ 11 dBm in any 1 MHz band (band 5470 – 5725 MHz)
power spectral density conducted ≤ 30 dBm in any 500 kHz band (band 5725 – 5850 MHz)

Results:

Power Spectral Density [dBm/MHz] e.i.r.p. for channel 36-48 conducted for all other channels	Ch36	Ch40	Ch48	Ch52	Ch56	Ch64	Ch100	Ch120	Ch140	Ch149	Ch157	Ch165
a-mode	6.2	7.9	8.4	1.8	1.9	1.3	-0.2	1.1	1.3	-2.6	-2.2	-1.4
nHT20-mode	6.2	7.4	8.0	1.4	1.5	0.9	-0.7	0.6	0.9	-3.0	-2.6	-1.8
acVHT20-mode	6.2	7.6	8.0	1.4	1.6	0.9	-0.6	0.7	0.9	-2.9	-2.5	-1.8
axHE20-SU-mode	6.0	7.4	7.8	1.2	1.4	0.7	-0.8	0.5	0.4	-3.6	-3.1	-2.3

12.9 Band edge compliance radiated (2JF1002P antenna)

Description:

Measurement of the radiated band edge compliance. The EUT is turned in the position that results in the maximum level at the band edge. Then a sweep over the corresponding restricted band is performed. The EUT is set to the lowest channel for the lower restricted band and to the highest channel for the upper restricted band. Measurement distance is 3m.

Measurement:

Measurement parameter	
Detector:	Peak / RMS
Sweep time:	Auto
Resolution bandwidth:	1 MHz
Video bandwidth:	$\geq 3 \times \text{RBW}$
Span:	See plots!
Trace mode:	Max Hold
Test setup:	See sub clause 7.2 – A
Measurement uncertainty:	See chapter 9

Limits:


Band Edge Compliance Radiated
In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 5.205(c)).
74 dB μ V/m (peak) 54 dB μ V/m (average)

Results:


Mode	Nominal bandwidth	Frequency (MHz)	Emission (MHz)	Highest emission level(s) next to the band edge (dBµV/m)	
				Peak	Average
11a	20MHz	5180	5150	59.3	45.9
		5320	5350	59.1	46.6
		5500	5460	56.5	45.4
11n	20MHz	5180	5150	58.4	45.9
		5320	5350	62.1	46.1
		5500	5460	56.8	45.3
11ac	20MHz	5180	5150	59.4	45.9
		5320	5350	65.0	47.0
		5500	5460	56.6	45.2
11ax	20MHz	5180	5150	59.8	45.8
		5320	5350	65.2	46.8
		5500	5640	57.4	45.9
11ax-ER	20MHz	5180	5150	56.3	45.0
		5320	5350	55.8	44.5
		5500	5460	56.2	44.8
11ax-TB26	20MHz	5180	5150	56.0	44.8
		5320	5350	55.8	44.3
		5500	5640	56.0	44.5
11ax-TB52	20MHz	5180	5150	57.1	44.7
		5320	5350	57.3	44.6
		5500	5460	56.1	44.5
11ax-TB106	20MHz	5180	5150	56.8	45.1
		5320	5350	57.9	45.2
		5500	5460	56.3	44.7

Plots:


a-mode :




nHT20-mode :




acVHT20-mode :




axHE20-mode :




ax-ER-mode :




axTB26-mode :



axTB52-mode :



axTB106-mode :



12.10 Band edge compliance radiated (Taoglas GW.51.5153 antenna)

Description:

Measurement of the radiated band edge compliance. The EUT is turned in the position that results in the maximum level at the band edge. Then a sweep over the corresponding restricted band is performed. The EUT is set to the lowest channel for the lower restricted band and to the highest channel for the upper restricted band. Measurement distance is 3m.

Measurement:

Measurement parameter	
Detector:	Peak / RMS
Sweep time:	Auto
Resolution bandwidth:	1 MHz
Video bandwidth:	$\geq 3 \times \text{RBW}$
Span:	See plots!
Trace mode:	Max Hold
Test setup:	See sub clause 7.2 – A
Measurement uncertainty:	See chapter 9

Limits:


Band Edge Compliance Radiated
In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 5.205(c)).
74 dB μ V/m (peak) 54 dB μ V/m (average)

Results:


Mode	Nominal bandwidth	Frequency (MHz)	Emission (MHz)	Highest emission level(s) next to the band edge (dBµV/m)	
				Peak	Average
11a	20MHz	5180	5150	59.6	46.2
		5320	5350	58.8	47.2
		5500	5460	56.2	45.0
11n	20MHz	5180	5150	62.7	46.7
		5320	5350	59.9	47.3
		5500	5460	57.3	45.0
11ac	20MHz	5180	5150	62.1	46.8
		5320	5350	60.8	47.6
		5500	5460	57.8	46.3
11ax	20MHz	5180	5150	64.1	46.5
		5320	5350	57.7	45.6
		5500	5640	57.5	46.0
11ax-ER	20MHz	5180	5150	56.8	45.2
		5320	5350	56.6	44.6
		5500	5460	56.3	44.8
11ax-TB26	20MHz	5180	5150	56.4	44.9
		5320	5350	56.4	44.5
		5500	5640	56.3	44.8
11ax-TB52	20MHz	5180	5150	57.0	45.0
		5320	5350	56.6	44.5
		5500	5460	56.9	44.7
11ax-TB106	20MHz	5180	5150	56.7	45.4
		5320	5350	56.3	44.7
		5500	5460	56.5	44.7

Plots:


a-mode :




nHT20-mode :




acVHT20-mode :




axHE20-mode :




ax-ER-mode :




axTB26-mode :



axTB52-mode :



axTB106-mode :



12.11 Spurious emissions radiated below 30 MHz (2JF1002P antenna)

Description:

Measurement of the radiated spurious emissions in transmit mode below 30 MHz. The limits are re-calculated to a measurement distance of 3 m with 40 dB/decade according CFR Part 2.

Measurement:

Measurement parameter	
Detector:	Peak / Quasi Peak
Sweep time:	Auto
Video bandwidth:	F < 150 kHz: 200 Hz F > 150 kHz: 9 kHz
Resolution bandwidth:	F < 150 kHz: 1 kHz F > 150 kHz: 100 kHz
Span:	9 kHz to 30 MHz
Trace mode:	Max Hold
Test setup:	See sub clause 7.2 – C
Measurement uncertainty:	See chapter 9


Limits:

Spurious Emissions Radiated < 30 MHz		
Frequency (MHz)	Field Strength (μV/m)	Measurement distance
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30


Results:

Spurious Emissions Radiated < 30 MHz [dBμV/m]		
F [MHz]	Detector	Level [dBμV/m]
All detected emissions are more than 20 dB below the limit.		


Plots: a-mode




Plot 33: 5700 MHz, 9 kHz to 30 MHz




Plot 34: 5745 MHz, 9 kHz to 30 MHz




Plot 35: 5785 MHz, 9 kHz to 30 MHz




Plot 36: 5845 MHz, 9 kHz to 30 MHz




Plots: axHE20-mode


Plot 45: 5700 MHz, 9 kHz to 30 MHz




Plot 46: 5745 MHz, 9 kHz to 30 MHz



Plot 47: 5785 MHz, 9 kHz to 30 MHz



Plot 48: 5845 MHz, 9 kHz to 30 MHz



12.12 Spurious emissions radiated below 30 MHz (Taoglas GW.51.5153 antenna)

Description:

Measurement of the radiated spurious emissions in transmit mode below 30 MHz. The limits are re-calculated to a measurement distance of 3 m with 40 dB/decade according CFR Part 2.

Measurement:


Measurement parameter	
Detector:	Peak / Quasi Peak
Sweep time:	Auto
Video bandwidth:	F < 150 kHz: 200 Hz F > 150 kHz: 9 kHz
Resolution bandwidth:	F < 150 kHz: 1 kHz F > 150 kHz: 100 kHz
Span:	9 kHz to 30 MHz
Trace mode:	Max Hold
Test setup:	See sub clause 7.2 – C
Measurement uncertainty:	See chapter 9

Limits:


Spurious Emissions Radiated < 30 MHz		
Frequency (MHz)	Field Strength (μV/m)	Measurement distance
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30

Results:


Spurious Emissions Radiated < 30 MHz [dBμV/m]		
F [MHz]	Detector	Level [dBμV/m]
All detected emissions are more than 20 dB below the limit.		

Plots: a-mode


Plot 57: 5700 MHz, 9 kHz to 30 MHz




Plot 58: 5745 MHz, 9 kHz to 30 MHz




Plot 59: 5785 MHz, 9 kHz to 30 MHz




Plot 60: 5845 MHz, 9 kHz to 30 MHz




Plots: axHE20-mode




Plot 69: 5700 MHz, 9 kHz to 30 MHz




Plot 70: 5745 MHz, 9 kHz to 30 MHz



Plot 71: 5785 MHz, 9 kHz to 30 MHz



Plot 72: 5845 MHz, 9 kHz to 30 MHz



12.13 Spurious emissions radiated 30 MHz to 1 GHz (2JF1002P antenna)

Description:

Measurement of the radiated spurious emissions and cabinet radiations below 1 GHz.

Measurement:


Measurement parameter	
Detector:	Quasi Peak
Sweep time:	Auto
Resolution bandwidth:	120 kHz
Video bandwidth:	500 kHz
Span:	30 MHz to 1 GHz
Test setup:	See sub clause 7.1 – A
Measurement uncertainty:	See chapter 9

Limits:

TX Spurious Emissions Radiated		
§15.209 / RSS-247		
Frequency (MHz)	Field Strength (dB μ V/m)	Measurement distance
30 - 88	30.0	10
88 – 216	33.5	10
216 – 960	36.0	10
Above 960	54.0	3
§15.407		
Outside the restricted bands!	-27 dBm / MHz	


Plots: 20 MHz channel bandwidth

Plot 1: 30 MHz to 1 GHz; vertical & horizontal polarization; U-NII-1; all channels and modes




Results:


Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
45.175880	16.33	30.00	13.67	1000.0	120.000	170.0	V	179.0	14.2
56.056300	23.41	30.00	6.59	1000.0	120.000	170.0	V	263.0	15.4
60.214540	23.90	30.00	6.10	1000.0	120.000	107.0	V	190.0	13.6
688.554320	10.45	36.00	25.55	1000.0	120.000	170.0	H	190.0	21.7
939.884620	13.39	36.00	22.61	1000.0	120.000	170.0	H	171.0	24.8
954.436960	13.39	36.00	22.61	1000.0	120.000	158.0	H	-7.0	24.8

Plot 2: 30 MHz to 1 GHz; vertical & horizontal polarization; U-NII-2A; all channels and modes**Results:**

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
42.204680	14.18	30.00	15.82	1000.0	120.000	170.0	V	190.0	13.9
57.765060	23.79	30.00	6.21	1000.0	120.000	106.0	V	190.0	14.6
60.738940	22.60	30.00	7.40	1000.0	120.000	151.0	V	280.0	13.1
701.400300	11.61	36.00	24.39	1000.0	120.000	140.0	H	173.0	21.8
764.699200	13.49	36.00	22.51	1000.0	120.000	109.0	H	170.0	23.3
901.221060	13.48	36.00	22.52	1000.0	120.000	170.0	H	10.0	24.8

Plot 3: 30 MHz to 1 GHz; vertical & horizontal polarization; U-NII-2C; all channels and modes**Results:**

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
42.219740	16.51	30.00	13.49	1000.0	120.000	105.0	V	100.0	13.9
45.859820	17.38	30.00	12.62	1000.0	120.000	103.0	V	261.0	14.2
56.298180	23.11	30.00	6.89	1000.0	120.000	106.0	V	176.0	15.3
60.257160	21.67	30.00	8.33	1000.0	120.000	170.0	V	91.0	13.5
684.099460	10.55	36.00	25.45	1000.0	120.000	153.0	V	173.0	21.7
884.275400	12.84	36.00	23.16	1000.0	120.000	170.0	H	190.0	24.5

Plot 4: 30 MHz to 1 GHz; vertical & horizontal polarization; U-NII-3; all channels and modes**Results:**

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
57.096460	24.44	30.00	5.56	1000.0	120.000	124.0	V	190.0	14.9
60.164620	22.76	30.00	7.24	1000.0	120.000	132.0	V	280.0	13.6
765.210280	12.51	36.00	23.49	1000.0	120.000	170.0	H	264.0	23.3
831.196300	12.66	36.00	23.34	1000.0	120.000	170.0	V	190.0	23.8
910.243300	12.96	36.00	23.04	1000.0	120.000	105.0	H	-3.0	24.8
942.438900	13.61	36.00	22.39	1000.0	120.000	170.0	H	173.0	24.8

12.14 Spurious emissions radiated 30 MHz to 1 GHz (Taoglas GW.51.5153 antenna)

Description:

Measurement of the radiated spurious emissions and cabinet radiations below 1 GHz.

Measurement:


Measurement parameter	
Detector:	Quasi Peak
Sweep time:	Auto
Resolution bandwidth:	120 kHz
Video bandwidth:	500 kHz
Span:	30 MHz to 1 GHz
Test setup:	See sub clause 7.1 – A
Measurement uncertainty:	See chapter 9

Limits:

TX Spurious Emissions Radiated		
§15.209 / RSS-247		
Frequency (MHz)	Field Strength (dB μ V/m)	Measurement distance
30 - 88	30.0	10
88 – 216	33.5	10
216 – 960	36.0	10
Above 960	54.0	3
§15.407		
Outside the restricted bands!	-27 dBm / MHz	


Plots: 20 MHz channel bandwidth

Plot 5: 30 MHz to 1 GHz; vertical & horizontal polarization; U-NII-1; all channels and modes




Results:


Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
54.858620	27.76	30.00	2.24	1000.0	120.000	118.0	V	280.0	14.6
59.965300	15.30	30.00	14.70	1000.0	120.000	102.0	V	263.0	13.8
583.398160	7.13	36.00	28.87	1000.0	120.000	170.0	V	-9.0	20.9
686.455860	8.56	36.00	27.44	1000.0	120.000	170.0	H	100.0	21.7
727.543740	14.62	36.00	21.38	1000.0	120.000	152.0	V	10.0	22.5
874.564920	11.92	36.00	24.08	1000.0	120.000	170.0	V	100.0	24.5

Plot 6: 30 MHz to 1 GHz; vertical & horizontal polarization; all channels and modes**Results:**

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
42.335740	14.91	30.00	15.09	1000.0	120.000	110.0	V	280.0	13.9
54.921560	25.94	30.00	4.06	1000.0	120.000	109.0	V	10.0	14.6
60.494600	12.62	30.00	17.38	1000.0	120.000	101.0	V	280.0	13.3
683.336280	8.65	36.00	27.35	1000.0	120.000	170.0	H	10.0	21.7
836.704540	11.42	36.00	24.58	1000.0	120.000	170.0	V	100.0	23.9
919.109140	11.92	36.00	24.08	1000.0	120.000	170.0	V	190.0	24.8

Plot 7: 30 MHz to 1 GHz; vertical & horizontal polarization; U-NII-2C; all channels and modes**Results:**

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
42.340060	18.59	30.00	11.41	1000.0	120.000	170.0	V	182.0	13.9
54.709580	26.96	30.00	3.04	1000.0	120.000	125.0	V	100.0	14.6
658.666980	9.25	36.00	26.75	1000.0	120.000	125.0	H	261.0	21.6
727.106620	17.10	36.00	18.90	1000.0	120.000	124.0	H	261.0	22.4
853.321180	14.26	36.00	21.74	1000.0	120.000	102.0	H	4.0	24.2
919.820920	11.20	36.00	24.80	1000.0	120.000	109.0	V	190.0	24.8

Plot 8: 30 MHz to 1 GHz; vertical & horizontal polarization; U-NII-3; all channels and modes**Results:**

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
41.848640	15.99	30.00	14.01	1000.0	120.000	170.0	V	81.0	13.9
46.086300	17.44	30.00	12.56	1000.0	120.000	170.0	V	180.0	14.3
54.877740	26.25	30.00	3.75	1000.0	120.000	101.0	V	-9.0	14.6
638.573140	9.65	36.00	26.35	1000.0	120.000	131.0	H	10.0	21.5
776.601040	10.61	36.00	25.39	1000.0	120.000	124.0	H	190.0	23.2
956.887500	11.74	36.00	24.26	1000.0	120.000	170.0	V	100.0	24.8

12.15 Spurious emissions radiated 1 GHz to 40 GHz (2JF1002P antenna)

Description:

Measurement of the radiated spurious emissions and cabinet radiations from 1 GHz to 40 GHz.

Measurement:

Measurement parameter	
Detector:	Peak / AVG
Sweep time:	Auto
Resolution bandwidth:	1 MHz
Video bandwidth:	3 MHz
Span:	1 GHz to 40 GHz
Test setup:	See sub clause 7.2 – B See sub clause 7.3 – A
Measurement uncertainty:	See chapter 9

Limits:

TX Spurious Emissions Radiated		
§15.209 / RSS-247		
Frequency (MHz)	Field Strength (dB μ V/m)	Measurement distance
Above 960	54.0	3
§15.407		
Outside the restricted bands!	-27 dBm / MHz	

Results: 20 MHz channel bandwidth OFDM

TX Spurious Emissions Radiated [dB μ V/m] / dBm								
U-NII-1 (5150 MHz to 5250 MHz)								
Lowest channel			Middle channel			Highest channel		
F [MHz]	Detector	Level [dB μ V/m]	F [MHz]	Detector	Level [dB μ V/m]	F [MHz]	Detector	Level [dB μ V/m]
-/-	Peak		-/-	Peak		-/-	Peak	
	AVG			AVG			AVG	
For emissions above 18 GHz please take look at the plots.			For emissions above 18 GHz please take look at the plots.			For emissions above 18 GHz please take look at the plots.		

TX Spurious Emissions Radiated [dB μ V/m] / dBm								
U-NII-2A (5250 MHz to 5350 MHz)								
Lowest channel			Middle channel			Highest channel		
F [MHz]	Detector	Level [dB μ V/m]	F [MHz]	Detector	Level [dB μ V/m]	F [MHz]	Detector	Level [dB μ V/m]
-/-	Peak		-/-	Peak		-/-	Peak	
	AVG			AVG			AVG	
For emissions above 18 GHz please take look at the plots.			For emissions above 18 GHz please take look at the plots.			For emissions above 18 GHz please take look at the plots.		

TX Spurious Emissions Radiated [dB μ V/m] / dBm								
U-NII-2C (5470 MHz to 5725 MHz)								
Lowest channel			Middle channel			Highest channel		
F [MHz]	Detector	Level [dB μ V/m]	F [MHz]	Detector	Level [dB μ V/m]	F [MHz]	Detector	Level [dB μ V/m]
-/-	Peak		-/-	Peak		7600	Peak	51.3
	AVG			AVG			AVG	48.0
For emissions above 18 GHz please take look at the plots.			For emissions above 18 GHz please take look at the plots.			For emissions above 18 GHz please take look at the plots.		

TX Spurious Emissions Radiated [dB μ V/m] / dBm								
U-NII-3 (5725 MHz to 5850 MHz)								
Lowest channel			Middle channel			Highest channel		
F [MHz]	Detector	Level [dB μ V/m]	F [MHz]	Detector	Level [dB μ V/m]	F [MHz]	Detector	Level [dB μ V/m]
7660	Peak	51.4	7713	Peak	52.2	-/-	Peak	
	AVG	48.3		AVG	49.2		AVG	
For emissions above 18 GHz please take look at the plots.			For emissions above 18 GHz please take look at the plots.			For emissions above 18 GHz please take look at the plots.		

Results: 20 MHz channel bandwidth OFDMA


TX Spurious Emissions Radiated [dB μ V/m] / dBm								
U-NII-1 (5150 MHz to 5250 MHz)								
Lowest channel			Middle channel			Highest channel		
F [MHz]	Detector	Level [dB μ V/m]	F [MHz]	Detector	Level [dB μ V/m]	F [MHz]	Detector	Level [dB μ V/m]
-/-	Peak		-/-	Peak		-/-	Peak	
	AVG			AVG			AVG	
For emissions above 18 GHz please take look at the plots.			For emissions above 18 GHz please take look at the plots.			For emissions above 18 GHz please take look at the plots.		

TX Spurious Emissions Radiated [dB μ V/m] / dBm								
U-NII-2A (5250 MHz to 5350 MHz)								
Lowest channel			Middle channel			Highest channel		
F [MHz]	Detector	Level [dB μ V/m]	F [MHz]	Detector	Level [dB μ V/m]	F [MHz]	Detector	Level [dB μ V/m]
-/-	Peak		-/-	Peak		-/-	Peak	
	AVG			AVG			AVG	
For emissions above 18 GHz please take look at the plots.			For emissions above 18 GHz please take look at the plots.			For emissions above 18 GHz please take look at the plots.		


TX Spurious Emissions Radiated [dB μ V/m] / dBm								
U-NII-2C (5470 MHz to 5725 MHz)								
Lowest channel			Middle channel			Highest channel		
F [MHz]	Detector	Level [dB μ V/m]	F [MHz]	Detector	Level [dB μ V/m]	F [MHz]	Detector	Level [dB μ V/m]
7333	Peak	50.2	7466	Peak	50.0	7600	Peak	51.7
	AVG	46.3		AVG	45.9		AVG	48.4
For emissions above 18 GHz please take look at the plots.			For emissions above 18 GHz please take look at the plots.			For emissions above 18 GHz please take look at the plots.		

TX Spurious Emissions Radiated [dB μ V/m] / dBm								
U-NII-3 (5725 MHz to 5850 MHz)								
Lowest channel			Middle channel			Highest channel		
F [MHz]	Detector	Level [dB μ V/m]	F [MHz]	Detector	Level [dB μ V/m]	F [MHz]	Detector	Level [dB μ V/m]
7660	Peak	51.5	7713	Peak	53.4	-/-	Peak	
	AVG	48.4		AVG	50.8		AVG	
For emissions above 18 GHz please take look at the plots.			For emissions above 18 GHz please take look at the plots.			For emissions above 18 GHz please take look at the plots.		


Plots: a-mode




Plot 9: 5700 MHz, 1 GHz to 18 GHz




Plot 10: 5745 MHz, 1 GHz to 18 GHz




Plot 11: 5785 MHz, 1 GHz to 18 GHz




Plot 12: 5845 MHz, 1 GHz to 18 GHz




Plot 13: All channels, 18 GHz to 40 GHz (Max Hold)




-/-

Plots: axHE20-mode


Plot 9: 5700 MHz, 1 GHz to 18 GHz




Plot 10: 5745 MHz, 1 GHz to 18 GHz




Plot 11: 5785 MHz, 1 GHz to 18 GHz



Plot 12: 5845 MHz, 1 GHz to 18 GHz



Plot 13: All channels, 18 GHz to 40 GHz (Max Hold)



-/-

12.16 Spurious emissions radiated 1 GHz to 40 GHz (Taoglas GW.51.5153 antenna)

Description:

Measurement of the radiated spurious emissions and cabinet radiations from 1 GHz to 40 GHz.

Measurement:

Measurement parameter	
Detector:	Quasi Peak below 1 GHz (alternative Peak) Peak above 1 GHz / RMS
Sweep time:	Auto
Resolution bandwidth:	1 MHz
Video bandwidth:	3 MHz
Span:	1 GHz to 40 GHz
Trace mode:	Max Hold / Average with 100 counts + 20 log (1 / X) for duty cycle lower than 100 %
Test setup:	See sub clause 7.2 – B See sub clause 7.3 – A
Measurement uncertainty:	See chapter 9

Limits:

TX Spurious Emissions Radiated		
§15.209 / RSS-247		
Frequency (MHz)	Field Strength (dBµV/m)	Measurement distance
Above 960	54.0	3
§15.407		
Outside the restricted bands!	-27 dBm / MHz	

Results: 20 MHz channel bandwidth OFDM

TX Spurious Emissions Radiated [dB μ V/m] / dBm								
U-NII-1 (5150 MHz to 5250 MHz)								
Lowest channel			Middle channel			Highest channel		
F [MHz]	Detector	Level [dB μ V/m]	F [MHz]	Detector	Level [dB μ V/m]	F [MHz]	Detector	Level [dB μ V/m]
-/-	Peak		-/-	Peak		-/-	Peak	
	AVG			AVG			AVG	
For emissions above 18 GHz please take look at the plots.			For emissions above 18 GHz please take look at the plots.			For emissions above 18 GHz please take look at the plots.		

TX Spurious Emissions Radiated [dB μ V/m] / dBm								
U-NII-2A (5250 MHz to 5350 MHz)								
Lowest channel			Middle channel			Highest channel		
F [MHz]	Detector	Level [dB μ V/m]	F [MHz]	Detector	Level [dB μ V/m]	F [MHz]	Detector	Level [dB μ V/m]
-/-	Peak		-/-	Peak		-/-	Peak	
	AVG			AVG			AVG	
For emissions above 18 GHz please take look at the plots.			For emissions above 18 GHz please take look at the plots.			For emissions above 18 GHz please take look at the plots.		

TX Spurious Emissions Radiated [dB μ V/m] / dBm								
U-NII-2C (5470 MHz to 5725 MHz)								
Lowest channel			Middle channel			Highest channel		
F [MHz]	Detector	Level [dB μ V/m]	F [MHz]	Detector	Level [dB μ V/m]	F [MHz]	Detector	Level [dB μ V/m]
7332	Peak	51.7	7466	Peak	52.2	7600	Peak	51.3
	AVG	48.4		AVG	49.2		AVG	48.0
For emissions above 18 GHz please take look at the plots.			For emissions above 18 GHz please take look at the plots.			For emissions above 18 GHz please take look at the plots.		

TX Spurious Emissions Radiated [dB μ V/m] / dBm								
U-NII-3 (5725 MHz to 5850 MHz)								
Lowest channel			Middle channel			Highest channel		
F [MHz]	Detector	Level [dB μ V/m]	F [MHz]	Detector	Level [dB μ V/m]	F [MHz]	Detector	Level [dB μ V/m]
7660	Peak	53.6	7713	Peak	54.2	-/-	Peak	
	AVG	50.6		AVG	52.0		AVG	
For emissions above 18 GHz please take look at the plots.			For emissions above 18 GHz please take look at the plots.			For emissions above 18 GHz please take look at the plots.		

Results: 20 MHz channel bandwidth OFDMA


TX Spurious Emissions Radiated [dB μ V/m] / dBm								
U-NII-1 (5150 MHz to 5250 MHz)								
Lowest channel			Middle channel			Highest channel		
F [MHz]	Detector	Level [dB μ V/m]	F [MHz]	Detector	Level [dB μ V/m]	F [MHz]	Detector	Level [dB μ V/m]
-/-	Peak		-/-	Peak		-/-	Peak	
	AVG			AVG			AVG	
For emissions above 18 GHz please take look at the plots.			For emissions above 18 GHz please take look at the plots.			For emissions above 18 GHz please take look at the plots.		

TX Spurious Emissions Radiated [dB μ V/m] / dBm								
U-NII-2A (5250 MHz to 5350 MHz)								
Lowest channel			Middle channel			Highest channel		
F [MHz]	Detector	Level [dB μ V/m]	F [MHz]	Detector	Level [dB μ V/m]	F [MHz]	Detector	Level [dB μ V/m]
-/-	Peak		-/-	Peak		-/-	Peak	
	AVG			AVG			AVG	
For emissions above 18 GHz please take look at the plots.			For emissions above 18 GHz please take look at the plots.			For emissions above 18 GHz please take look at the plots.		


TX Spurious Emissions Radiated [dB μ V/m] / dBm								
U-NII-2C (5470 MHz to 5725 MHz)								
Lowest channel			Middle channel			Highest channel		
F [MHz]	Detector	Level [dB μ V/m]	F [MHz]	Detector	Level [dB μ V/m]	F [MHz]	Detector	Level [dB μ V/m]
7333	Peak	52.9	7466	Peak	52.2	7600	Peak	54.1
	AVG	50.3		AVG	49.0		AVG	51.6
For emissions above 18 GHz please take look at the plots.			For emissions above 18 GHz please take look at the plots.			For emissions above 18 GHz please take look at the plots.		

TX Spurious Emissions Radiated [dB μ V/m] / dBm								
U-NII-3 (5725 MHz to 5850 MHz)								
Lowest channel			Middle channel			Highest channel		
F [MHz]	Detector	Level [dB μ V/m]	F [MHz]	Detector	Level [dB μ V/m]	F [MHz]	Detector	Level [dB μ V/m]
7660	Peak	54.2	7713	Peak	55.1	7766	Peak	54.0
	AVG	52.0		AVG	53.0		AVG	51.7
For emissions above 18 GHz please take look at the plots.			For emissions above 18 GHz please take look at the plots.			For emissions above 18 GHz please take look at the plots.		


Plots: a-mode




Plot 9: 5700 MHz, 1 GHz to 18 GHz




Plot 10: 5745 MHz, 1 GHz to 18 GHz




Plot 11: 5785 MHz, 1 GHz to 18 GHz



Plot 12: 5845 MHz, 1 GHz to 18 GHz




Plot 13: All channels, 18 GHz to 40 GHz (Max Hold)




-/-


Plots: axHE20-mode




Plot 9: 5700 MHz, 1 GHz to 18 GHz




Plot 10: 5745 MHz, 1 GHz to 18 GHz




Plot 11: 5785 MHz, 1 GHz to 18 GHz



Plot 12: 5845 MHz, 1 GHz to 18 GHz



Plot 13: All channels, 18 GHz to 40 GHz (Max Hold)



-/-

12.17 Observations

No observations except those reported with the single test cases have been made.

13 Glossary

AVG	Average
C	Compliant
C/N₀	Carrier to noise-density ratio, expressed in dB-Hz
CAC	Channel availability check
CW	Clean wave
DC	Duty cycle
DFS	Dynamic frequency selection
DSSS	Dynamic sequence spread spectrum
DUT	Device under test
EMC	Electromagnetic Compatibility
EUT	Equipment under test
FCC	Federal Communications Commission
FCC ID	Combination of Grantee Code and Equipment Product Code
FHSS	Frequency hopping spread spectrum
FVIN	Firmware version identification number
HMN	Host marketing name
HVIN	Hardware version identification number
HW	Hardware
ISED	Innovation, Science and Economic Development Canada
Inv. No.	Inventory number
MC	Modulated carrier
NA	Not applicable
NC	Not compliant
NOP	Non occupancy period
NP	Not performed
OBW	Occupied bandwidth
OC	Operating channel
OCW	Operating channel bandwidth
OFDM	Orthogonal frequency division multiplexing
OOB	Out of band
OP	Occupancy period
PER	Packet error rate
PMN	Product marketing name
PP	Positive peak
QP	Quasi peak
RLAN	Radio local area network
S/N or SN	Serial number
SW	Software
UUT	Unit under test
WLAN	Wireless local area network

14 Document history

Version	Applied changes	Date of release
R01	Initial release	2026-06-30
R02	Values in chapter 12.5 corrected	2026-07-08

END OF TEST REPORT