



Maximum Permissible Exposure (MPE) & Exposure evaluation

Report identification number: 1-0450/20-01-08 MPE (FCC_ISED)

Certification numbers and labeling requirements	
FCC ID	T7V9520
ISED number	216Q-9520
HVIN (Hardware Version Identification Number)	ENW49D01A1KF, ENW49D02A1KF
PMN (Product Marketing Name)	PAN9520
FVIN (Firmware Version Identification Number)	-/-
HMN (Host Marketing Name)	-/-

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

Document authorised:



cn=Alexander Hnatovskiy, o=CTC advanced
GmbH, ou=HNA-161129,
email=Alexander.Hnatovskiy@ctcadvanced.
com, c=DE
2021.06.01 11:51:16 +02'00'

Alexander Hnatovskiy
Lab Manager
Radio Communications & EMC



cn=Marco Scigliano, o=CTC advanced
GmbH, ou=SCI-161125,
email=marco.scigliano@ctcadvanced.com,
c=DE
2021.06.01 11:49:31 +02'00'

Marco Scigliano
Testing Manager
Radio Communications & EMC

EUT technologies:

Technologies:	Max. measured Peak-EIRP [dBm]:
WLAN 2450 MHz	25.4

NOTE: Test results taken from CTC advanced GmbH report 1-0450/20-01-07

Prediction of MPE limit at given distance - FCC

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4\pi R^2$$

where: S = Power density
 P = Power input to the antenna
 G = Antenna gain
 R = Distance to the center of radiation of the antenna
 PG = Output Power including antenna gain

The table below is excerpted from Table 1B of 47 CFR 1.1310 titled "Limits for Maximum Permissible Exposure (MPE), Limits for General Population/Uncontrolled Exposure"

Frequency Range (MHz)	Power Density (mW/cm ²)	Averaging Time (minutes)
300 -1500	f/1500	30
1500 - 100000	1.0	30

where f = Frequency (MHz)

Prediction: worst case

Technologies:	WLAN	
Frequency (MHz)	2450	
PG Declared max power (EIRP)	25.4	dBm
R Distance	20	cm
S MPE limit for uncontrolled exposure	1	mW/cm ²
Calculated Power density:	0.0690	mW/cm ²
Calculated percentage of Limit:	6.90%	

This prediction demonstrates the following:

The power density levels for FCC at a distance of 20 cm are below the maximum levels allowed by regulations.

Prediction of MPE limit at given distance - ISED

RSS-102, Issue 5, 2.5.2

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $4.49/f^{0.5}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

Prediction: worst case

		WLAN	
	Frequency	2450	MHz
R	Distance	20	cm
PG	Maximum EIRP	25.4	dBm
PG	Maximum EIRP	346.7	mW
	Exclusion Limit from above:	2.71	W
	Calculated percentage of Limit:	12.78%	

Conclusion: RF exposure evaluation is not required.