

FCC SAR exemption letter according KDB 447498 D01 v06

For SOMMER Antriebs- und Funktechnik GmbH, Hans-Boeckler Straße 27, 73230 Kirchheim/Teck, Germany, Wireless Keypad, Telecody+

Declared minimum distance to human body according to customer = 0 mm according external document "MPE Information Requirements (Telecody+ S11098)" provided by customer.

According to KDB 447498 D01 General RF Exposure Guidance V06 SAR testing can be exempted if the following exclusion threshold are met:

4.3. General SAR test exclusion guidance

4.3.1. Standalone SAR test exclusion considerations

- a) For 100 MHz to 6 GHz and *test separation distances* ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f_{\text{GHz}}}] \leq 3.0$ for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR,³⁰ where

- f_{GHz} is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation³¹
- The result is rounded to one decimal place for comparison
- The values 3.0 and 7.5 are referred to as *numeric thresholds* in step b) below

The test exclusions are applicable only when the minimum *test separation distance* is ≤ 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

$P_{\text{threshold}}$ calculation based on external document "MPE Information Requirements (Telecody+ S11098)" provided by customer.

$P_{\text{threshold}} = \text{Maximum Rated Conducted Output Power (dBm)} + \text{Tune-Up Tolerance} - \text{Maximum Path Loss to Antenna}$

$P_{\text{threshold_DUT}} = 1 \text{ mW} * 10^{((+2 \text{ dBm} + 1 \text{ dB} - 0 \text{ dB})/10)} \leq 2 \text{ mW}$

FCC General SAR test exclusion acc. KDB 447498 D01 v06					
Frequency (MHz)	Max. power incl. Tune-up tolerance (mW)	Threshold 1-g SAR Limit < 3.0	Threshold 10-g SAR Limit < 7.5	1-G SAR Exemption fulfilled	10-g SAR Exemption fulfilled
922.5	1.9953	0.3833	0.3833	yes	yes
min. test separation distance (mm)			5		

The user manual must list the given usage position.


 ninovic.
 perez@cetecom.
 com
 2022.02.18 11:03:37
 +01'00'

Dipl.-Ing. Ninovic Perez


 martin.
 nunier@cetecom.
 com
 2022.02.17 13:27:05
 +01'00'

B.Eng. Martin Nunier