



Test Report No.: PSZ-QSZ2510291415RF11



VARIANT FCC TEST REPORT (PART 96)



Applicant:	BARTEC
Address:	Max-Eyth-Str.16 , 97980 Bad Mergentheim, Germany

Manufacturer or Supplier:	BARTEC
Address:	Max-Eyth-Str.16 , 97980 Bad Mergentheim, Germany
Product:	Smartscanner / Smartphone
Brand Name:	BARTEC
Model Name:	SP9EX1/SC9EX1/SP9EX2/SC9EX2
FCC ID:	TBUSX9EX
Date of tests:	Dec. 20, 2025 ~ Jan. 05, 2026

The tests have been carried out according to the requirements of the following standard:

☒ **47 CFR FCC Part 96**

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Carl Xie Engineer / Mobile Department	Approved by Simon Wang Manager / Mobile Department
	
Date: Jan. 05, 2026	Date: Jan. 05, 2026

BOOMWAVE TEST (SHENZHEN) CO., LTD. tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report. The results documented in this report apply only the tested sample, under the conditions and modes of operation as described herein. It is the manufacturer's responsibility assure that additional production units of the model are manufactured with identical electrical and mechanical components. All sample tested were in good operating condition throughout the entire test program. Measurement Uncertainties are published for informational purposes only and were not taken into account unless noted otherwise. Without written approval of BOOMWAVE TEST (SHENZHEN) CO., LTD., the test report shall not be reproduced except in full.



Test Report No.: PSZ-QSZ2510291415RF11

TABLE OF CONTENTS

RELEASE CONTROL RECORD	3
1 SUMMARY OF TEST RESULTS	4
1.1 MEASUREMENT UNCERTAINTY	6
1.2 TEST SITE AND INSTRUMENTS	7
2 GENERAL INFORMATION	9
2.1 GENERAL DESCRIPTION OF EUT	9
2.2 CONFIGURATION OF SYSTEM UNDER TEST	12
2.3 DESCRIPTION OF SUPPORT UNITS	13
2.4 TEST ITEM AND TEST CONFIGURATION	13
2.5 GENERAL DESCRIPTION OF APPLIED STANDARDS	14
4 INFORMATION ON THE TESTING LABORATORIES	15
5 MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB ..	16



Test Report No.: PSZ-QSZ2510291415RF11

RELEASE CONTROL RECORD

ISSUE NO.	DESCRIPTION	DATE ISSUED
PSU-QSU2312140113RF05	Original release	Jul. 26, 2024
PSZ-QSZ2510291415RF11	Based on the original report, new product update HW, for specific changes please refer to the Product ASSY release notes document provided by the applicant. In this report verify power and RSE worst case. The verify results of conducted power are similar or lower. The verify results of part96 RSE worst case is (n48 10M_CH641666) (the data please refer to report PSZ-QSZ2510291415RF12), So this report all data please refer to original report.	Jan. 05, 2026



Test Report No.: PSZ-QSZ2510291415RF11

1 SUMMARY OF TEST RESULTS

47 CFR FCC PART 96			
FCC CLAUSE	TEST ITEM	RESULT	TEST LAB*
2.1046 96.41(b)	Maximum Peak Output Power and Maximum EIRP	See note2	--
2.1051 96.41(e)	Conducted Band Edge	See note2	--
2.1049	Occupied Bandwidth	See note2	--
2.1055	Frequency Stability	See note2	--
2.1051 96.41(e)	Conducted Spurious Emissions	See note2	--
2.1053 96.41(e)	Radiated Spurious Emissions	See note2	--
96.41(g)	Peak-to-Average Power Ratio	See note2	--
§96.47	End User Device additional Irequirement	See note3	--




NOTE:

1. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
2. Please refer to original report (Report No.: PSU-QSU2312140113RF05, FCC ID: TBUSX9EX).
3. The differences between original and new product do not affect the tests in Section 96.47, therefore all test data please refers to original report: FG441204A (Model name: SP9EX1/SC9EX1/SP9EX2/SC9EX2, FCC ID: TBUSX9EX).
4. In this report, for specific changes please refer to the documentation provided by the applicant (REV_F SC9EX1_SP9EX1_SC9EX2_SP9EX2 PCBA HW release notes (Ver. 6.0), REV_F SC9EX1_SP9EX1_SC9EX2_SP9EX2 Product ASSY release notes (Ver. 1.0) and SC9EX1_SP9EX1_SC9EX2_SP9EX2 SW release notes (Ver. 6.0)).
5. The differences between SC9EX1 and SP9EX1 the presence of the barcode scanner module and the "bump" on the back cover that model SC9EX1 incorporates the barcode scanner module, no differences on the PCBA between the variants(model:SP9EX1). We verified power and RSE worst case on parent product SC9EX1 and SP9EX1 variant, only the worst-case(SC9EX1) results are shown in the report.



Test Report No.: PSZ-QSZ2510291415RF11

6. The devices BARTEC SP9EX1 Smartphone and BARTEC SP9EX2 Smartphone share the same hardware and software. The same applies for the devices BARTEC SC9EX1 Smartscanner and BARTEC SC9EX2 Smartscanner. The only difference are the hazardous area marking of the devices, see table for clarification.

BARTEC SP9EX1 Smartphone	BARTEC SP9EX2 Smartphone
BARTEC SP9EX1 Type: 17-S19P-****/***** Mfr: BARTEC GmbH Max-Eyth-Straße 16 97980 Bad Mergentheim, DE www.bartec.com   UL 24 ATEX 3153X II 1G Ex ia IIC T4 Ga II 2D Ex ia IIC T135°C Db IP64 IECEx UL 24.0004X Class I, Div 1, Groups A, B, C and D; Class II, Div 1, Groups E, F and G; Class III, T4 Zone 0, AEx ia IIC T4 Ga Zone 21, AEx ia IIC T135°C Db Zone 0, Ex ia IIC T4 Ga Zone 21, Ex ia IIC T135°C Db -20° < Ta < +55°C QR-code S/N: TTTTYYSSSSSS MFD: MONTHYY reserved for logos of country approvals USB port: USB-PD compatible – 5-20 Vdc / max 3 A DC-In port: 12 Vdc / max 1.5 A USB Um = 20 V / DCin Um = 12 V WARNING/ATTENTION: Use only replaceable battery pack BARTEC GmbH type: 17-S1Z0-0020/**** Utiliser uniquement la batterie BARTEC GmbH type: 17-S1Z0-0020/**** INTRINSICALLY SAFE/SECURITE INTRINSEQUE Warning - Substitution of components may impair intrinsic safety. Avertissement - La substitution des composants peut nuire à la sécurité intrinsèque.	BARTEC SP9EX2 Type: B7-S29P-****/***** Mfr: BARTEC GmbH Max-Eyth-Straße 16 97980 Bad Mergentheim, DE www.bartec.com   UL 24 ATEX xxxxxx II 3G Ex ic IIC T4 Gc II 3D Ex ic IIC T135°C Dc IP64 IECEx UL 24.xxxxx Class I, Div 2, Groups A, B, C and D; Class II, Div 2, Groups E, F and G; Class III, T4 Zone 2, AEx ic IIC T4 Gc Zone 22, AEx ic IIC T135°C Dc Zone 2, Ex ic IIC T4 Gc Zone 22, Ex ic IIC T135°C Dc -20° < Ta < +55°C QR-code S/N: TTTTYYSSSSSS MFD: MONTHYY reserved for logos of country approvals USB port: USB-PD compatible – 5-20 Vdc / max 3 A DC-In port: 12 Vdc / max 1.5 A USB Um = 20 V / DCin Um = 12 V WARNING/ATTENTION: Use only replaceable battery pack BARTEC GmbH type: B7-A2Z0-0098/**** Utiliser uniquement la batterie BARTEC GmbH type: B7-A2Z0-0098/**** INTRINSICALLY SAFE/SECURITE INTRINSEQUE Warning - Substitution of components may impair intrinsic safety. Avertissement - La substitution des composants peut nuire à la sécurité intrinsèque.
BARTEC SC9EX1 Smartscanner	BARTEC SC9EX2 Smartscanner
BARTEC SC9EX1 Type: 17-S19C-****/***** Mfr: BARTEC GmbH Max-Eyth-Straße 16 97980 Bad Mergentheim, DE www.bartec.com   UL 24 ATEX 3153X II 1G Ex ia op is IIC T4 Ga II 2D Ex ia op is IIC T135°C Db IP64 IECEx UL 24.0004X Class I, Div 1, Groups A, B, C and D; Class II, Div 1, Groups E, F and G; Class III, T4 Zone 0, AEx ia op is IIC T4 Ga Zone 21, AEx ia op is IIC T135°C Db Zone 0, Ex ia op is IIC T4 Ga Zone 21, Ex ia op is IIC T135°C Db -20° < Ta < +55°C QR-code S/N: TTTTYYSSSSSS MFD: MONTHYY reserved for logos of country approvals USB port: USB-PD compatible – 5-20 Vdc / max 3 A DC-In port: 12 Vdc / max 1.5 A USB Um = 20 V / DCin Um = 12 V WARNING/ATTENTION: Use only replaceable battery pack BARTEC GmbH type: 17-S1Z0-0020/**** Utiliser uniquement la batterie BARTEC GmbH type: 17-S1Z0-0020/**** INTRINSICALLY SAFE/SECURITE INTRINSEQUE Warning - Substitution of components may impair intrinsic safety. Avertissement - La substitution des composants peut nuire à la sécurité intrinsèque.	BARTEC SC9EX2 Type: B7-S29C-****/***** Mfr: BARTEC GmbH Max-Eyth-Straße 16 97980 Bad Mergentheim, DE www.bartec.com   UL 24 ATEX xxxxxx II 3G Ex ic op is IIC T4 Gc II 3D Ex ic op is IIC T135°C Dc IP64 IECEx UL 24.xxxxx Class I, Div 2, Groups A, B, C and D; Class II, Div 2, Groups E, F and G; Class III, T4 Zone 2, AEx ic op is IIC T4 Gc Zone 22, AEx ic op is IIC T135°C Dc Zone 2, Ex ic op is IIC T4 Gc Zone 22, Ex ic op is IIC T135°C Dc -20° < Ta < +55°C QR-code S/N: TTTTYYSSSSSS MFD: MONTHYY reserved for logos of country approvals USB port: USB-PD compatible – 5-20 Vdc / max 3 A DC-In port: 12 Vdc / max 1.5 A USB Um = 20 V / DCin Um = 12 V WARNING/ATTENTION: Use only replaceable battery pack BARTEC GmbH type: B7-A2Z0-0098/**** Utiliser uniquement la batterie BARTEC GmbH type: B7-A2Z0-0098/**** INTRINSICALLY SAFE/SECURITE INTRINSEQUE Warning - Substitution of components may impair intrinsic safety. Avertissement - La substitution des composants peut nuire à la sécurité intrinsèque.

*Test Lab Information Reference

Lab A:

Boomwave Test (Shenzhen) Co., Ltd.

Lab Address:

Rm B38, Warehouse A5(Chiwan #1), #3 Chiwan 4th Rd, Chiwan Comm, Zhaoshang St, Nanshan Dist, Shenzhen, Guangdong, Shenzhen, China

Accredited Test Lab Cert 7607.01

The FCC Site Registration No. is 646781; The Designation No. is CN1429.

Boomwave Test (Shenzhen) Co.,
Ltd.

Rm B38, Warehouse A5(Chiwan #1), #3 Chiwan 4th
Rd, Chiwan Comm, Zhaoshang St, Nanshan Dist,
Shenzhen, Guangdong, Shenzhen, China

Mobile: +86 15118052731
Email:shimin.wang@boomwavelab.com



Test Report No.: PSZ-QSZ2510291415RF11

1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	UNCERTAINTY
Effective Radiated Power	$\pm 1.48\text{dB}$
Frequency Stability	$\pm 39.27\text{Hz}$
Radiated emissions (9KHz~30MHz)	$\pm 2.68\text{dB}$
Radiated emissions & Radiated Power (30MHz~1GHz)	$\pm 4.98\text{dB}$
Radiated emissions & Radiated Power (1GHz ~6GHz)	$\pm 4.70\text{dB}$
Radiated emissions (6GHz ~18GHz)	$\pm 4.60\text{dB}$
Radiated emissions (18GHz ~40GHz)	$\pm 4.12\text{dB}$
Conducted emissions	$\pm 4.01\text{ dB}$
Occupied Channel Bandwidth	$\pm 21.7\text{KHz}$
Band Edge Measurements	$\pm 1.48\text{dB}$
Peak to average ratio	$\pm 0.76\text{dB}$

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.



Test Report No.: PSZ-QSZ2510291415RF11

1.2 TEST SITE AND INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	Euroshieldpn-CT0001143-1216	2025/7/3	2026/7/2
BiConiLog Antenna	ETS-LINDGREN	3143B	161965	2025/7/17	2026/7/16
Horn Antenna	SCHWARZBECK	BBHA9120D	3297	2025/9/27	2026/9/26
Horn Antenna	STEATITE	QWH-SL-18-40-K-SG QMS-00361	15433	2025/7/19	2026/7/18
Preamplifier	Tonscend	TPA184045	AP24L8060388	2025/7/3	2026/7/2
MXE EMI Receiver	keysight	N9038B	MY50018017	2025/7/1	2026/6/30
MXG Vector Signal Generator	Keysight	N5183B	MY59100137	2025/6/30	2026/6/29
Preamplifier	Tonscend	TPA001330	806JSAPO40804251015	2025/6/30	2026/6/29
Preamplifier	Tonscend	TPA011845	AP24L8060392	2025/6/30	2026/6/29
Attenuator 6DB	SHX	TS2-6-6-A	230927166	2025/6/30	2026/6/29
Attenuator 6DB	SHX	TS2-6-6-A	230927165	2025/6/30	2026/6/29
Active Receive Loop Antenna	SCHWARZBECK	FMZB 1519 B	00173	2025/6/30	2026/6/29
Temp. & Humi. Recorder	Kejian	HTC-01	157246	2025/7/2	2026/7/1
HIGH pass FILTER_1-18	EWT	EWT-57-0222	EWT-57-0222	2025/6/30	2026/6/29
HIGH pass FILTER_7-18	EWT	EWT-57-0223	EWT-57-0223	2025/6/30	2026/6/29
HIGH pass FILTER_3-18	EWT	EWT-57-0221	EWT-57-0221	2025/6/30	2026/6/29
DC~1GHz Lowpass Filter	EWT	EWT-56-0649	EWT-56-0649	2025/7/3	2026/7/2
Cable 1	N/A	N/A	N/A	2025/9/28	2026/9/27
Cable 2	N/A	N/A	N/A	2025/9/28	2026/9/27
Cable 3	N/A	N/A	N/A	2025/9/28	2026/9/27
Wireless communication integrated tester	Rohde&Schwarz	CMW500	182016	2025/6/30	2026/6/29
EXA Signal Analyzer	KEYSIGHT	N9010B	MY62170156	2025/6/30	2026/6/29
RF Control Unit	Tonscend	JS0806-1	21K8060504	2025/6/16	2026/6/15
DC Power Supply	AGILENT	HMP2020	100598	2025/7/1	2026/6/30
10dB attenuator	JFW INDUSTRIES INC	50HF-010-SMA	50HF-010-SMA-1	2025/6/30	2026/6/29
10dB attenuator	JFW INDUSTRIES INC	50HF-010-SMA	50HF-010-SMA-2	2025/6/30	2026/6/29
hygrothermograph	Anymetrers	----	TH101B	2025/7/22	2026/7/21
Temperature Box	zhongkemeiqi	MA22040172	MQ-DTH50F-2	2025/7/1	2026/6/30
power divider	WOKEN	71688	204-003180-01	2025/6/30	2026/6/29



Test Report No.: PSZ-QSZ2510291415RF11

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GREGT/CHINA and NIM/CHINA.
2. The test was performed in 3m Semi-anechoic Chamber and RF Oven Room.
3. The horn antenna is used only for the measurement of emission frequency above 1GHz if tested.
4. The FCC Site Registration No. is 646781; The Designation No. is CN1429.



Test Report No.: PSZ-QSZ2510291415RF11

2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Smartscanner / Smartphone	
BRAND NAME	BARTEC	
MODEL NAME	SP9EX1/SC9EX1/SP9EX2/SC9EX2	
NOMINAL VOLTAGE	5.0V/9.0V/12.0Vdc (adapter) 3.2V/3.8V/4.2V/dc (battery)	
MODULATION TECHNOLOGY	LTE	QPSK, 16QAM, 64QAM, 256QAM
FREQUENCY RANGE	LTE Band 48 Channel Bandwidth: 5MHz	3552.5MHz ~ 3697.5MHz
	LTE Band 48 Channel Bandwidth: 10MHz	3555MHz ~ 3695MHz
	LTE Band 48 Channel Bandwidth: 15MHz	3557.5MHz ~ 3692.5MHz
	LTE Band 48 Channel Bandwidth: 20MHz	3560MHz ~ 3690MHz
EMISSION DESIGNATOR	LTE Band 48 Channel Bandwidth: 5MHz	QPSK: 4M49G7D
		16QAM: 4M49W7D
		64QAM: 4M49W7D
	LTE Band 48 Channel Bandwidth: 10MHz	QPSK: 8M96G7D
		16QAM: 8M96W7D
		64QAM: 8M96W7D
	LTE Band 48 Channel Bandwidth: 15MHz	QPSK: 13M4G7D
		16QAM: 13M5W7D
		64QAM: 13M4W7D
	LTE Band 48 Channel Bandwidth: 20MHz	QPSK: 17M9G7D
		16QAM: 17M9W7D
		64QAM: 18M0W7D
MAX. EIRP POWER	LTE Band 48 Channel Bandwidth: 5MHz	195.88mW
	LTE Band 48 Channel Bandwidth: 10MHz	197.7mW
	LTE Band 48 Channel Bandwidth: 15MHz	196.79mW
	LTE Band 48 Channel Bandwidth: 20MHz	199.07mW
ANTENNA GAIN	☒ Provided by client	



Test Report No.: PSZ-QSZ2510291415RF11

	Main TX/RX ANT5: IFA Antenna with 0.9dBi gain for LTE 48 RX ANT SEC ANT3: IFA Antenna with 1.7dBi gain for LTE 48 RX ANT PRIM. MIMO ANT1: IFA Antenna with -0.6dBi gain for LTE 48 RX ANT SEC. MIMO ANT4: IFA Antenna with 1.5dBi gain for LTE 48
ANTENNA TYPE	IFA Antenna
HW VERSION	F
SW VERSION	AWG1.250822.030 15030
I/O PORTS	Refer to user's manual
DATA CABLE	USB cable: non-shielded cable, with w/o ferrite core, 0.8 meter
EXTREME TEMPERATURE	-20℃-60 ℃
EXTREME VOLTAGE	3.2V – 4.2V

NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. The EUT incorporates a SISO function. Physically, the EUT provides one completed transmitters and four receivers.

MODULATION MODE	TX FUNCTION
LTE	1TX/4RX

3. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
4. For Band Edge and Emission Mask: The all BW combinations were tested. Combination pairs of the same BW are considered generally equivalent. The RB combinations were selected such that the signal is active closest to the band limit, as this is the worst case.
5. For Out of Band Emissions: The all combination was tested. The highest power RB combination was selected as worst case.
6. Output power measurements were measured on QPSK, 16QAM, 64QAM and 256QAM modulations. And tests other than output power are performed only in worst-case QPSK and 16QAM, 64QAM modes.




Test Report No.: PSZ-QSZ2510291415RF11

7. List of Accessory:

ACCESSORIES	BRAND	MANUFACTURER	MODEL	SPECIFICATION
Display(AMOLED)	EDO	Everdisplay Optronics Co., Ltd.	E611FCC74.A	N/A
Back cover	IV Techmould	N/A	N/A	N/A
Bezel	IV Techmould	N/A	N/A	N/A
Photo/Video Camera 1	Sunny Optical	N/A	F48N03A (Auto focus)	N/A
Photo/Video Camera 2	TrulyOpto	N/A	CSF208-B8BF-E(Fix focus)	N/A
CPU	Qualcomm	N/A	QCM6490	N/A
UFS	Kioxia	N/A	THGJFAT0T44BAIL	N/A
BT/WLAN Module	Murata	N/A	LBEE5QG2CX-830	N/A
NFC chipset	NXP	N/A	SN110TUK1	N/A
Battery	BARTEC	N/A	17-S1Z0-0020/****	4300 mAh, 3.68V
USB-C Cable	BARTEC	N/A	G7-A0Z0-0010	Length: 0.8m

Test Report No.: PSZ-QSZ2510291415RF11

2.2 CONFIGURATION OF SYSTEM UNDER TEST FOR RADIATION EMISSION TEST





Test Report No.: PSZ-QSZ2510291415RF11

2.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Adapter	N/A	N/A	N/A	N/A
2	DC Source	HYELEC	HY3010B	551016	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	DC Line: Unshielded, Detachable, 1.0m;
2	USB Line: non-shielded, Detachable 0.8m;

2.4 TEST ITEM AND TEST CONFIGURATION

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case was found when positioned on Y-plane for EIRP and X-axis for radiated emission. Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	DESCRIPTION
A	EUT + Adapter + USB Cable with LTE link
B	EUT + DC Supply with LTE link



Test Report No.: PSZ-QSZ2510291415RF11

2.5 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 96

KDB 971168 D02 Power Meas License Digital Systems v02r02

ANSI/TIA/EIA-603-E 2016

ANSI 63.26-2015

NOTE: All test items have been performed and recorded as per the above standards.



Test Report No.: PSZ-QSZ2510291415RF11

4 INFORMATION ON THE TESTING LABORATORIES

We, Boomwave Test (Shenzhen) co., Ltd., were founded in 2025 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

Boomwave Test (Shenzhen) Co., Ltd.

Lab Address:

Rm B38, Warehouse A5(Chiwan #1), #3 Chiwan 4th Rd, Chiwan Comm, Zhaoshang St, Nanshan Dist, Shenzhen, Guangdong, Shenzhen, China

Accredited Test Lab Cert 7607.01

Shenzhen EMC/RF Lab:

Mobile: +86 15118052731

Email: shimin.wang@boomwavelab.com



Test Report No.: PSZ-QSZ2510291415RF11

5 MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

--END--