# FCC Test Report

| | | |
|---|---|---|
| Equipment | : | AC5400 Wireless Tri-Band MU-MIMO Gigabit Router |
| Brand Name | : | TP-Link |
| Model No. | : | Archer C5400 |
| FCC ID | : | TE7C5400V2 |
| Standard | : | 47 CFR FCC Part 15.407 |
| Operating Band | : | 5150 MHz -- 5250 MHz<br>5250 MHz -- 5350 MHz<br>5470 MHz -- 5725 MHz<br>5725 MHz -- 5850 MHz |
| Applicant | : | TP-Link Technologies Co., Ltd.<br>Building 24 (floors 1,3,4,5) and 28 (floors1-4)<br>Central Science and Technology Park,Nanshan<br>Shenzhen, 518057 China |
| Manufacturer | : | TP-Link Technologies Co., Ltd.<br>Building 24 (floors 1,3,4,5) and 28 (floors1-4)<br>Central Science and Technology Park,Nanshan<br>Shenzhen, 518057 China |
| Function | : | ☐ Outdoor; ☒ Indoor; ☐ Fixed P2P<br>☐ Client |
| TPC Function | : | ☒ With TPC ☐ Without TPC |

The product sample received on Oct. 28, 2015 and completely tested on Jun. 13, 2017. We, SPORTON, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2013 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Cliff Chang
SPORTON INTERNATIONAL INC.

Testing Laboratory
1190

# Table of Contents

**1 GENERAL DESCRIPTION ..... 5**

1.1 Information ..... 5
1.2 Testing Applied Standards ..... 10
1.3 Testing Location Information ..... 10
1.4 Measurement Uncertainty ..... 11

**2 TEST CONFIGURATION OF EUT ..... 12**

2.1 Test Channel Mode ..... 12
2.2 The Worst Case Measurement Configuration ..... 13
2.3 EUT Operation during Test ..... 14
2.4 Accessories ..... 14
2.5 Support Equipment ..... 15
2.6 Test Setup Diagram ..... 16

**3 TRANSMITTER TEST RESULT ..... 19**

3.1 Emission Bandwidth ..... 19
3.2 Maximum Conducted Output Power ..... 20
3.3 Peak Power Spectral Density ..... 22
3.4 Unwanted Emissions ..... 25
3.5 Frequency Stability ..... 29

**4 TEST EQUIPMENT AND CALIBRATION DATA ..... 30**

**APPENDIX A. TEST RESULTS OF EMISSION BANDWIDTH**

**APPENDIX B. TEST RESULTS OF MAXIMUM CONDUCTED OUTPUT POWER**

**APPENDIX C. TEST RESULTS OF PEAK POWER SPECTRAL DENSITY**

**APPENDIX D. TEST RESULTS OF UNWANTED EMISSIONS**

**APPENDIX E. TEST RESULTS OF FREQUENCY STABILITY**

**APPENDIX F. TEST PHOTOS**

**PHOTOGRAPHS OF EUT V01**

# Summary of Test Result

| Conformance Test Specifications | | | |
|---|---|---|---|
| **Report Clause** | **Ref. Std. Clause** | **Description** | **Result** |
| 1.1.3 | 15.203 | Antenna Requirement | Complied |
| 3.1 | 15.407(a) | Emission Bandwidth | Complied |
| 3.2 | 15.407(a) | Maximum Conducted Output Power | Complied |
| 3.3 | 15.407(a) | Peak Power Spectral Density | Complied |
| 3.4 | 15.407(b) | Unwanted Emissions | Complied |
| 3.5 | 15.407(g) | Frequency Stability | Complied |

# Revision History

| Report No. | Version | Description | Issued Date |
|---|---|---|---|
| FR5N0101-05AB | Rev. 01 | Initial issue of report | Nov. 03, 2017 |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

# 1 General Description

## 1.1 Information

### 1.1.1 RF General Information

| Frequency Range (MHz) | IEEE Std. 802.11 | Ch. Frequency (MHz) | Channel Number |
|---|---|---|---|
| 5150-5250 | a, n (HT20), ac (VHT20) | 5180-5240 | 36-48 [4] |
| 5250-5350 | | 5260-5320 | 52-64 [4] |
| 5470-5725 | | 5500-5700 | 100-140 [11] |
| 5725-5850 | | 5745-5825 | 149-165 [5] |
| 5150-5250 | n (HT40), ac (VHT40) | 5190-5230 | 38-46 [2] |
| 5250-5350 | | 5270-5310 | 54-62 [2] |
| 5470-5725 | | 5510-5670 | 102-134 [5] |
| 5725-5850 | | 5755-5795 | 151-159 [2] |
| 5150-5250 | ac (VHT80) | 5210 | 42 [1] |
| 5250-5350 | | 5290 | 58 [1] |
| 5470-5725 | | 5530-5610 | 106-122 [2] |
| 5725-5850 | | 5775 | 155 [1] |

| Band | Mode | BWch (MHz) | Nant |
|---|---|---|---|
| 5.15-5.25GHz | 802.11a | 20 | 4TX |
| 5.15-5.25GHz | 802.11n HT20 | 20 | 4TX |
| 5.15-5.25GHz | 802.11n HT20-BF | 20 | 4TX |
| 5.15-5.25GHz | 802.11ac VHT20 | 20 | 4TX |
| 5.15-5.25GHz | 802.11ac VHT20-BF | 20 | 4TX |
| 5.15-5.25GHz | 802.11n HT40 | 40 | 4TX |
| 5.15-5.25GHz | 802.11n HT40-BF | 40 | 4TX |
| 5.15-5.25GHz | 802.11ac VHT40 | 40 | 4TX |
| 5.15-5.25GHz | 802.11ac VHT40-BF | 40 | 4TX |
| 5.15-5.25GHz | 802.11ac VHT80 | 80 | 4TX |
| 5.15-5.25GHz | 802.11ac VHT80-BF | 80 | 4TX |
| 5.15-5.25GHz | 802.11ac VHT80+80 | 80 | 4TX(Port 1/2) |
| 5.25-5.35GHz | 802.11a | 20 | 4TX |
| 5.25-5.35GHz | 802.11n HT20 | 20 | 4TX |
| 5.25-5.35GHz | 802.11n HT20-BF | 20 | 4TX |
| 5.25-5.35GHz | 802.11ac VHT20 | 20 | 4TX |
| 5.25-5.35GHz | 802.11ac VHT20-BF | 20 | 4TX |
| 5.25-5.35GHz | 802.11n HT40 | 40 | 4TX |
| 5.25-5.35GHz | 802.11n HT40-BF | 40 | 4TX |

| | | | |
|---|---|---|---|
| 5.25-5.35GHz | 802.11ac VHT40 | 40 | 4TX |
| 5.25-5.35GHz | 802.11ac VHT40-BF | 40 | 4TX |
| 5.25-5.35GHz | 802.11ac VHT80 | 80 | 4TX |
| 5.25-5.35GHz | 802.11ac VHT80-BF | 80 | 4TX |
| 5.25-5.35GHz | 802.11ac VHT80+80 | 80 | 4TX(Port 3/4) |
| 5.47-5.725GHz | 802.11a | 20 | 4TX |
| 5.47-5.725GHz | 802.11n HT20 | 20 | 4TX |
| 5.47-5.725GHz | 802.11n HT20-BF | 20 | 4TX |
| 5.47-5.725GHz | 802.11ac VHT20 | 20 | 4TX |
| 5.47-5.725GHz | 802.11ac VHT20-BF | 20 | 4TX |
| 5.47-5.725GHz | 802.11n HT40 | 40 | 4TX |
| 5.47-5.725GHz | 802.11n HT40-BF | 40 | 4TX |
| 5.47-5.725GHz | 802.11ac VHT40 | 40 | 4TX |
| 5.47-5.725GHz | 802.11ac VHT40-BF | 40 | 4TX |
| 5.47-5.725GHz | 802.11ac VHT80 | 80 | 4TX |
| 5.47-5.725GHz | 802.11ac VHT80-BF | 80 | 4TX |
| 5.47-5.725GHz | 802.11ac VHT80+80 | 80 | 4TX |
| 5725-5850GHz | 802.11a | 20 | 4TX |
| 5725-5850GHz | 802.11n HT20 | 20 | 4TX |
| 5725-5850GHz | 802.11n HT20-BF | 20 | 4TX |
| 5725-5850GHz | 802.11ac VHT20 | 20 | 4TX |
| 5725-5850GHz | 802.11ac VHT20-BF | 20 | 4TX |
| 5725-5850GHz | 802.11n HT40 | 40 | 4TX |
| 5725-5850GHz | 802.11n HT40-BF | 40 | 4TX |
| 5725-5850GHz | 802.11ac VHT40 | 40 | 4TX |
| 5725-5850GHz | 802.11ac VHT40-BF | 40 | 4TX |
| 5725-5850GHz | 802.11ac VHT80 | 80 | 4TX |
| 5725-5850GHz | 802.11ac VHT80-BF | 80 | 4TX |
| 5725-5850GHz | 802.11ac VHT80+80 | 80 | 4TX |

Note:
- 11a, HT20 and HT40 use a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM modulation.
- VHT20, VHT40 and VHT80 use a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM modulation.
- BWch is the nominal channel bandwidth.
- Nss-Min is the minimum number of spatial streams.
- Nant is the number of outputs. e.g., 2(2,3) means have 2 outputs for port 2 and port 3. 2 means have 2 outputs for port 1 and port 2.

### 1.1.2 Table for 80+80 MHz Mode

| Type | Channel No. | Frequency |
|---|---|---|
| 1 | 42+58 | 5210+5290 MHz |
| 2 | 106+122 | 5530+5610 MHz |

### 1.1.3 Antenna Information

| Ant. | Brand | Model Name | Antenna Type | Connector | Gain (dBi) | |
|---|---|---|---|---|---|---|
| | | | | | 2.4GHz | 5GHz |
| 1 | TP-LINK | 3101500737 | PCB Antenna | I-PEX | 1.8 | 1.8 |
| 2 | TP-LINK | 3101500737 | PCB Antenna | I-PEX | 1.8 | 1.8 |
| 3 | TP-LINK | 3101500737 | PCB Antenna | I-PEX | 1.8 | 1.8 |
| 4 | TP-LINK | 3101500737 | PCB Antenna | I-PEX | 1.8 | 1.8 |
| 5 | TP-LINK | 3101500734 | PCB Antenna | I-PEX | - | 1.8 |
| 6 | TP-LINK | 3101500734 | PCB Antenna | I-PEX | - | 1.8 |
| 7 | TP-LINK | 3101500734 | PCB Antenna | I-PEX | - | 1.8 |
| 8 | TP-LINK | 3101500734 | PCB Antenna | I-PEX | - | 1.8 |

Note: 1.The EUT has eight antennas.
2.The EUT has three radios. (Radio 1 supports 5GHz band 1 and band 2 WLAN function, Radio 2 supports 5GHz band 3 and band 4 WLAN function and Radio 3 supports 2.4GHz WLAN function.)
3.The EUT supports WLAN (4TX, 4RX):
Chain 1 (Port 1), Chain 2 (Port 2), Chain 3 (Port 3) and Chain 4 (Port 4) could transmit/receive simultaneously.

### 1.1.4 Mode Test Duty Cycle

| Mode | DC | DCF(dB) | T(s) | VBW(Hz) ≥ 1/T |
|---|---|---|---|---|
| 802.11a | 0.982 | 0.079 | n/a (DC>=0.98) | n/a (DC>=0.98) |
| 802.11ac VHT20 | 0.986 | 0.061 | n/a (DC>=0.98) | n/a (DC>=0.98) |
| 802.11ac VHT20-BF | 0.889 | 0.511 | 3.823m | 300 |
| 802.11ac VHT40 | 0.959 | 0.182 | 947.5u | 3k |
| 802.11ac VHT40-BF | 0.961 | 0.173 | 3.685m | 300 |
| 802.11ac VHT80 | 0.907 | 0.424 | 455u | 3k |
| 802.11ac VHT80+80 | 0.845 | 0.731 | 247.5u | 10k |
| 802.11ac VHT80-BF | 0.925 | 0.339 | 5.093m | 300 |
| 802.11ac VHT80+80 | 0.785 | 1.051 | 236.875u | 10k |

### 1.1.5 EUT Operational Condition

| | | | | |
|---|---|---|---|---|
| **EUT Power Type** | From power adapter | | | |
| **Beamforming Function** | ☒ | With beamforming for 802.11n/ac in 2.4GHz/5GHz. | ☐ | Without beamforming |
| | Note: 802.11ac VHT80+80 MHz mode supports non-beamforming function only. | | | |
| **Weather Band** | ☒ | With 5600~5650MHz | ☐ | Without 5600~5650MHz |
| **Test Software Version** | Mtool_3_0_0_1 (Version 1.363.6.0) | | | |

### 1.1.6 Table for Class II Change

This product is an extension of original one reported under Sporton project number: FR5N0101-01AB

Below is the table for the change of the product with respect to the original one.

<table>
<tr><th>Modifications</th><th>Performance Checking</th></tr>
<tr><td>1. Adding 5GHz band 2 and Band 3 (5250~5350 MHz, 5470~5725 MHz) for this device.<br>2. Adding two types (Type 1: 5210+5290, Type 2: 5530+5610) of 80+80 MHz mode, and they supports non-beamforming function only.</td><td>1. Emission Bandwidth.<br>2. Maximum Conducted Output Power.<br>3. Peak Power Spectral Density.<br>4. Unwanted Emissions.<br>5. Frequency Stability Above 1GHz.</td></tr>
<tr><td>3. Updating chip version to "BCM4366 C0" from "BCM4366 B1".<br>The difference between original version and new version as below:
<table>
<tr><th>Version</th><th>Description</th></tr>
<tr><td>BCM4366 B1 (Original)</td><td>Single User Multiple Input Multiple Output</td></tr>
<tr><td>BCM4366 C0 (New)</td><td>Multi-User Multiple-Input Multiple-Output</td></tr>
</table></td><td>Unwanted Emissions Below 1GHz.<br>Note: After verified does not affect the other test results.</td></tr>
<tr><td>4. Changing applicant’s company to “TP-Link Technologies Co., Ltd.” from “TP-LINK TECHNOLOGIES CO., LTD.”.<br>5. Changing brand name to “TP-Link” from “TP-LINK”.<br>6. Changing FCC ID to “TE7C5400V2” from “TE7C5400”.</td><td>It does not need to re-test.</td></tr>
</table>

## 1.2 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR FCC Part 15
- ANSI C63.10-2013
- FCC KDB 789033 D02 v01r04
- FCC KDB 644545 D03 v01
- FCC KDB 662911 D01 v02r01

## 1.3 Testing Location Information

| Testing Location | | | | | | | |
|---|---|---|---|---|---|---|---|
| ☐ | HWA YA | ADD | : | No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. | | | |
| | | TEL | : | 886-3-327-3456 | FAX | : | 886-3-318-0055 |
| ☒ | JHUBEI | ADD | : | No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. | | | |
| | | TEL | : | 886-3-656-9065 | FAX | : | 886-3-656-9085 |

| Test Condition | Test Site No. | Test Engineer | Test Environment | Test Date |
|---|---|---|---|---|
| RF Conducted | TH01-CB | Brian Sun / Peter Lin | 26°C / 74% | Jun. 09, 2017 |
| Radiated | 03CH01-CB | Joy Tseng | 22°C / 54% | Jun. 06, 2017~Jun. 13, 2017 |

Test site Designation No. TW0006 with FCC
Test site registered number IC 4086D with Industry Canada.

## 1.4 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

| Test Items | Uncertainty | Remark |
|---|---|---|
| Radiated Emission (30MHz ~ 1,000MHz) | 3.6 dB | Confidence levels of 95% |
| Radiated Emission (1GHz ~ 18GHz) | 3.7 dB | Confidence levels of 95% |
| Radiated Emission (18GHz ~ 40GHz) | 3.5 dB | Confidence levels of 95% |
| Conducted Emission | 1.7 dB | Confidence levels of 95% |
| Output Power Measurement | 1.33 dB | Confidence levels of 95% |
| Power Density Measurement | 1.27 dB | Confidence levels of 95% |
| Bandwidth Measurement | $9.74 \times 10^{-8}$ | Confidence levels of 95% |
| Frequency Stability | $6.06 \times 10^{-8}$ | Confidence levels of 95% |

# 2 Test Configuration of EUT

## 2.1 Test Channel Mode

| Mode | Power Setting |
|---|---|
| 802.11a_(6Mbps)_4TX | - |
| 5260MHz | 60 |
| 5300MHz | 61 |
| 5320MHz | 61 |
| 5500MHz | 49 |
| 5580MHz | 48 |
| 5700MHz | 51 |
| 802.11ac VHT20_Nss1,(MCS0)_4TX | - |
| 5260MHz | 61 |
| 5300MHz | 62 |
| 5320MHz | 63 |
| 5500MHz | 49 |
| 5580MHz | 49 |
| 5700MHz | 52 |
| 802.11ac VHT40_Nss1,(MCS0)_4TX | - |
| 5270MHz | 70 |
| 5310MHz | 69 |
| 5510MHz | 60 |
| 5550MHz | 59 |
| 5670MHz | 58 |
| 802.11ac VHT80_Nss1,(MCS0)_4TX | - |
| 5290MHz | 69 |
| 5530MHz | 55 |
| 5610MHz | 66 |
| 802.11ac VHT20-BF_Nss1,(MCS0)_4TX | - |
| 5260MHz | 60 |
| 5300MHz | 61 |
| 5320MHz | 62 |
| 5500MHz | 50 |
| 5580MHz | 49 |
| 5700MHz | 52 |
| 802.11ac VHT40-BF_Nss1,(MCS0)_4TX | - |
| 5270MHz | 62 |
| 5310MHz | 63 |
| 5510MHz | 54 |
| 5550MHz | 53 |
| 5670MHz | 52 |
| 802.11ac VHT80-BF_Nss1,(MCS0)_4TX | - |

| Mode | Power Setting |
|---|---|
| 5290MHz | 62 |
| 5530MHz | 59 |
| 5610MHz | 59 |
| 802.11ac VHT80+80_Nss1,(MCS0)_4TX | - |
| #5210MHz,5290MHz | 60 |
| 802.11ac VHT80+80_Nss1,(MCS0)_4TX | - |
| 5210MHz,#5290MHz | 60 |
| 802.11ac VHT80+80_Nss1,(MCS0)_4TX | - |
| #5530MHz,#5610MHz | 58 |

Note:
- VHT20/VHT40 covers HT20/HT40, due to same modulation. The power setting for 802.11n HT20 and HT40 are the same or lower than 802.11ac VHT20 and VHT40.
- There are two modes of EUT, one is beamforming function, and the other is non-beamforming function for 802.11n/ac. All the results have been recorded in this report.

## 2.2 The Worst Case Measurement Configuration

| The Worst Case Mode for Following Conformance Tests | |
|---|---|
| **Tests Item** | Emission Bandwidth<br>Maximum Conducted Output Power<br>Peak Power Spectral Density<br>Frequency Stability |
| **Test Condition** | Conducted measurement at transmit chains |

| The Worst Case Mode for Following Conformance Tests | |
|---|---|
| **Tests Item** | Unwanted Emissions |
| **Test Condition** | Radiated measurement<br>If EUT consist of multiple antenna assembly (multiple antenna are used in EUT regardless of spatial multiplexing MIMO configuration), the radiated test should be performed with highest antenna gain of each antenna type. |
| **Operating Mode < 1GHz** | Normal Link |
| The EUT for Unwanted Emissions test was performed at Z axis and Y axis position for below 1GHz and the worst case was found from Z axis. So the measurement will follow this same test configuration. | |
| 1 | EUT in Z axis |
| **Operating Mode > 1GHz** | CTX |
| 1 | EUT in Y axis + folded the antenna |
| 2 | EUT in Z axis + folded the antenna |
| 3 | EUT in Y axis + antenna in 90° |
| 4 | EUT in Z axis + antenna in 90° |
| Mode 4 has been evaluated to be the worst case after evaluating. Consequently, measurement will follow this same test mode. | |

| The Worst Case Mode for Following Conformance Tests | |
|---|---|
| **Tests Item** | Simultaneous Transmission Analysis - Co-location RF Exposure Evaluation |
| **Operating Mode** | |
| 1 | 2.4GHz WLAN + 5GHz WLAN Band1/Band2 + 5GHz WLAN Band 3/Band4 |
| Refer to Sporton Test Report No.: FA5N0101-05 for Co-location RF Exposure Evaluation. | |

## 2.3 EUT Operation during Test

For CTX Mode:

non-beamforming mode:

The EUT was programmed to be in continuously transmitting mode.

beamforming mode:

For Conducted Mode:

The EUT was programmed to be in continuously transmitting mode.

For Radiated Mode:

During the test, the following programs under WIN XP were executed.
The program was executed as follows:
1. During the test, the EUT operation to normal function.
2. Executed command fixed test channel under DOS、LanTest20.
3. Executed "Lantest.exe" to link with the remote workstation to transmit and receive packet by RX Device and transmit duty cycle no less than 98%.

For Normal Link:

During the test, the EUT operation to normal function.

## 2.4 Accessories

| Accessories | | | | |
|---|---|---|---|---|
| **Equipment Name** | **Brand Name** | **Model Name** | **Rating** | **Remark** |
| Adapter | Huntkey | HKA06012050-7G | Input: 100-240Vac, 50/60Hz, 1.5A<br>Output: 12.0Vdc, 5.0A | Cable<br>(Non-shieided, 1.4m) |
| **Other** | | | | |
| Power cable*1: Non-shieided, 1.8m | | | | |

## 2.5 Support Equipment

**For Test Site No: 03CH01-CB (below 1GHz)**

| Support Equipment | | | | |
|---|---|---|---|---|
| **No.** | **Equipment** | **Brand Name** | **Model Name** | **FCC ID** |
| 1 | Notebook*2 | DELL | E4300 | DoC |
| 2 | Notebook*3 | Apple | Mac Book | DoC |
| 3 | Flash disk | Silicon Power | Touch 835 | DoC |
| 4 | Flash disk3.0 | Silicon Power | B06 | DoC |

**For Test Site No: 03CH01-CB (above 1GHz) <For Non-Beamforming Mode> and TH01-CB**

| Support Equipment | | | | |
|---|---|---|---|---|
| **No.** | **Equipment** | **Brand Name** | **Model Name** | **FCC ID** |
| 1 | Notebook | DELL | E4300 | DoC |

**For Test Site No: 03CH01-CB (above 1GHz) <For Beamforming Mode>**

| Support Equipment | | | | |
|---|---|---|---|---|
| **No.** | **Equipment** | **Brand Name** | **Model Name** | **FCC ID** |
| 1 | Notebook*2 | DELL | E4300 | DoC |
| 2 | WLAN module (RX Device) | Boardcom | BCM943162ZP | QDS-BRCM1075 |

## 2.6 Test Setup Diagram

**Test Setup Diagram - Radiated Test < 1GHz**




| Item | Connection | Shielded | Length |
|---|---|---|---|
| 1 | RJ-45 cable | No | 10m |
| 2 | RJ-45 cable | No | 10m |
| 3 | Power cable | No | 3.2m |
| 4 | RJ-45 cable*3 | No | 1.5m |

**Test Setup Diagram - Radiated Test > 1GHz**

**<For Non-Beamforming Mode>**




| Item | Connection | Shielded | Length |
|---|---|---|---|
| 1 | RJ-45 cable | No | 10m |
| 2 | Power cable | No | 3.2m |

**Test Setup Diagram - Radiated Test > 1GHz**

**<For Beamforming Mode>**




| Item | Connection | Shielded | Length |
|---|---|---|---|
| 1 | RJ-45 cable | No | 10m |
| 2 | RJ-45 cable | No | 10m |
| 3 | Power cable | No | 3.2m |

# 3 Transmitter Test Result

## 3.1 Emission Bandwidth

### 3.1.1 Emission Bandwidth Limit

| Emission Bandwidth Limit | |
|---|---|
| **UNII Devices** | |
| ☐ | For the 5.15-5.25 GHz band, N/A |
| ☒ | For the 5.25-5.35 GHz band, the maximum conducted output power shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in MHz. |
| ☒ | For the 5.47-5.725 GHz band, the maximum conducted output power shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in MHz. |
| ☐ | For the 5.725-5.85 GHz band, 6 dB emission bandwidth ≥ 500kHz. |
| **LE-LAN Devices** | |
| ☐ | For the band 5.15-5.25 GHz, the maximum e.i.r.p. shall not exceed 200 mW or 10 + 10 log B, dBm, whichever power is less. B is the 99% emission bandwidth in MHz. |
| ☐ | For the 5.25-5.35 GHz band, the maximum e.i.r.p. shall not exceed 1.0 W or 17 + 10 log B, dBm, whichever power is less. B is the 99% emission bandwidth in MHz |
| ☐ | For the 5.47-5.6 GHz band and 5.65-5.725 GHz band, the maximum e.i.r.p. shall not exceed 1.0 W or 17 + 10 log B, dBm, whichever power is less. B is the 99% emission bandwidth in MHz |
| ☐ | For the 5.725-5.85 GHz band, 6 dB emission bandwidth ≥ 500kHz. |

### 3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

### 3.1.3 Test Procedures

| Test Method | | |
|---|---|---|
| ▪ | For the emission bandwidth shall be measured using one of the options below: | |
| | ☒ | Refer as FCC KDB 789033, clause C for EBW and clause D for OBW measurement. |
| | ☐ | Refer as ANSI C63.10, clause 6.9.1 for occupied bandwidth testing. |
| | ☒ | Refer as IC RSS-Gen, clause 4.6 for bandwidth testing. |

### 3.1.4 Test Setup

**Emission Bandwidth**




### 3.1.5 Test Result of Emission Bandwidth

Refer as Appendix A

## 3.2 Maximum Conducted Output Power

### 3.2.1 Maximum Conducted Output Power Limit

| Maximum Conducted Output Power Limit | |
|---|---|
| **UNII Devices** | |
| ☐ | For the 5.15-5.25 GHz band: |
| | ▪ Outdoor AP: the maximum conducted output power ($P_{Out}$) shall not exceed the lesser of 1 W. If $G_{TX}$ > 6 dBi, then $P_{Out}$ = 30 – ($G_{TX}$ – 6). e.i.r.p. at any elevation angle above 30 degrees ≤ 125mW [21dBm] |
| | ▪ Indoor AP: the maximum conducted output power ($P_{Out}$) shall not exceed the lesser of 1 W. If $G_{TX}$ > 6 dBi, then $P_{Out}$ = 30 – ($G_{TX}$ – 6) |
| | ▪ Point-to-point AP: the maximum conducted output power ($P_{Out}$) shall not exceed the lesser of 1 W If $G_{TX}$ > 23 dBi, then $P_{Out}$ = 30 – ($G_{TX}$ – 23). |
| | ▪ Mobile or Portable Client: the maximum conducted output power ($P_{Out}$) shall not exceed the lesser of 250 mW. If $G_{TX}$ > 6 dBi, then $P_{Out}$ = 24 – ($G_{TX}$ – 6). |
| ☒ | For the 5.25-5.35 GHz band, the maximum conducted output power ($P_{Out}$) shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in MHz. If $G_{TX}$ > 6 dBi, then $P_{Out}$ = 24 – ($G_{TX}$ – 6). |
| ☒ | For the 5.47-5.725 GHz band, the maximum conducted output power ($P_{Out}$) shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in MHz. If $G_{TX}$ > 6 dBi, then $P_{Out}$ = 24 – ($G_{TX}$ – 6). |
| ☐ | For the 5.725-5.85 GHz band: |
| | ▪ Point-to-multipoint systems (P2M): the maximum conducted output power ($P_{Out}$) shall not exceed the lesser of 1 W. If $G_{TX}$ > 6 dBi, then $P_{Out}$ = 30 – ($G_{TX}$ – 6). |
| | ▪ Point-to-point systems (P2P): the maximum conducted output power ($P_{Out}$) shall not exceed the lesser of 1 W. |
| **LE-LAN Devices** | |
| ☐ | For the 5.15-5.25 GHz band, the maximum e.i.r.p. shall not exceed 200 mW or 10 + 10 log B, dBm, whichever power is less. B is the 99% emission bandwidth in MHz. |
| ☐ | For the 5.25-5.35 GHz band, the maximum e.i.r.p. shall not exceed 1.0 W or 17 + 10 log B, dBm, whichever power is less. B is the 99% emission bandwidth in MHz |
| ☐ | For the 5.47-5.6 GHz band and 5.65-5.725 GHz band, the maximum e.i.r.p. shall not exceed 1.0 W or 17 + 10 log B, dBm, whichever power is less. B is the 99% emission bandwidth in MHz |
| ☐ | For the 5.725-5.85 GHz band: |
| | ▪ Point-to-multipoint systems (P2M): the maximum conducted output power ($P_{Out}$) shall not exceed the lesser of 1 W. If $G_{TX}$ > 6 dBi, then $P_{Out}$ = 30 – ($G_{TX}$ – 6). |
| | ▪ Point-to-point systems (P2P): the maximum conducted output power ($P_{Out}$) shall not exceed the lesser of 1 W. |
| **$P_{Out}$** = maximum conducted output power in dBm,<br>**$G_{TX}$** = the maximum transmitting antenna directional gain in dBi. | |

### 3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

### 3.2.3 Test Procedures

| Test Method | |
|---|---|
| ▪ Maximum Conducted Output Power | |
| | Average over on/off periods with duty factor |
| | ☐ Refer as FCC KDB 789033, clause E Method SA-2 (spectral trace averaging). |
| | ☐ Refer as FCC KDB 789033, clause E Method SA-2 Alt. (RMS detection with slow sweep speed) |
| | Wideband RF power meter and average over on/off periods with duty factor |
| | ☒ Refer as FCC KDB 789033, clause E Method PM-G (using an RF average power meter). |
| ▪ For conducted measurement. | |
| | ▪ If the EUT supports multiple transmit chains using options given below:<br>Refer as FCC KDB 662911, In-band power measurements. Using the measure-and-sum approach, measured all transmit ports individually. Sum the power (in linear power units e.g., mW) of all ports for each individual sample and save them. |
| | ▪ If multiple transmit chains, EIRP calculation could be following as methods:<br>$P_{total} = P_1 + P_2 + \ldots + P_n$<br>(calculated in linear unit [mW] and transfer to log unit [dBm])<br>$EIRP_{total} = P_{total} + DG$ |

### 3.2.4 Test Setup

| RF Output Power (Power Meter) |
|---|
| |

### 3.2.5 Test Result of Maximum Conducted Output Power

Refer as Appendix B

## 3.3 Peak Power Spectral Density

### 3.3.1 Peak Power Spectral Density Limit

| Peak Power Spectral Density Limit | |
|---|---|
| **UNII Devices** | |
| ☐ | For the 5.15-5.25 GHz band: |
| | ▪ Outdoor AP: the peak power spectral density (PPSD) shall not exceed the lesser of 17dBm/MHz. If $G_{TX}$ > 6 dBi, then $P_{Out}$ = 17 – ($G_{TX}$ – 6). |
| | ▪ Indoor AP: the peak power spectral density (PPSD) shall not exceed the lesser of 17dBm/MHz. If $G_{TX}$ > 6 dBi, then $P_{Out}$ = 17 – ($G_{TX}$ – 6). |
| | ▪ Point-to-point AP: the peak power spectral density (PPSD) shall not exceed the lesser of 17dBm/MHz. If $G_{TX}$ > 23 dBi, then $P_{Out}$ = 17 – ($G_{TX}$ – 23). |
| | ▪ Mobile or Portable Client: the peak power spectral density (PPSD) ≤ 11 dBm/MHz. If $G_{TX}$ > 6 dBi, then PPSD= 11 – ($G_{TX}$ – 6).. |
| ☒ | For the 5.25-5.35 GHz band, the peak power spectral density (PPSD) ≤ 11 dBm/MHz. If $G_{TX}$ > 6 dBi, then PPSD= 11 – ($G_{TX}$ – 6). |
| ☒ | For the 5.47-5.725 GHz band, the peak power spectral density (PPSD) ≤ 11 dBm/MHz. If $G_{TX}$ > 6 dBi, then PPSD= 11 – ($G_{TX}$ – 6). |
| ☐ | For the 5.725-5.85 GHz band: |
| | ▪ Point-to-multipoint systems (P2M): the peak power spectral density (PPSD) ≤ 30 dBm/500kHz. If $G_{TX}$ > 6 dBi, then PPSD= 30 – ($G_{TX}$ – 6). |
| | ▪ Point-to-point systems (P2P): the peak power spectral density (PPSD) ≤ 30 dBm/500kHz. |
| **LE-LAN Devices** | |
| ☐ | For the 5.15-5.25 GHz band, the peak power spectral density (PPSD) ≤ 4 dBm/MHz and the e.i.r.p. peak power spectral density (PPSD) ≤ 10 dBm/MHz. |
| ☐ | For the 5.25-5.35 GHz band, the peak power spectral density (PPSD) ≤ 11 dBm/MHz and the e.i.r.p. peak power spectral density (PPSD) ≤ 17 dBm/MHz. |
| | ▪ e.i.r.p. greater than 200 mW shall comply with the following e.i.r.p. at different elevations, where θ is the angle above the local horizontal plane (of the Earth) as shown below:<br>-13 dBW/MHz for 0° ≤ θ < 8° ; -13 − 0.716 (θ-8) dBW/MHz for 8° ≤ θ < 40°<br>-35.9 − 1.22 (θ-40) dBW/MHz for 40° ≤ θ ≤ 45° ; -42 dBW/MHz for θ > 45° |
| ☐ | For the 5.47-5.6 GHz band and 5.65-5.725 GHz band, the peak power spectral density (PPSD) ≤ 11 dBm/MHz and the e.i.r.p. peak power spectral density (PPSD) ≤ 17 dBm/MHz. |
| ☐ | For the 5.725-5.85 GHz band: |
| | ▪ Point-to-multipoint systems (P2M): the peak power spectral density (PPSD) ≤ 30 dBm/500kHz. If $G_{TX}$ > 6 dBi, then PPSD= 30 – ($G_{TX}$ – 6). |
| | ▪ Point-to-point systems (P2P): the peak power spectral density (PPSD) ≤ 30 dBm/500kHz. |
| **PPSD** = peak power spectral density that he same method as used to determine the conducted output power shall be used to determine the power spectral density. And power spectral density in dBm/MHz<br>**$G_{TX}$** = the maximum transmitting antenna directional gain in dBi. | |

### 3.3.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

### 3.3.3 Test Procedures

| Test Method | | | |
|---|---|---|---|
| ▪ Peak power spectral density procedures that the same method as used to determine the conducted output power shall be used to determine the peak power spectral density and use the peak search function on the spectrum analyzer to find the peak of the spectrum. For the peak power spectral density shall be measured using below options: | | | |
| | ☐ Refer as FCC KDB 789033, F)5) power spectral density can be measured using resolution bandwidths < 1 MHz provided that the results are integrated over 1 MHz bandwidth | | |
| | [duty cycle ≥ 98% or external video / power trigger] | | |
| | ☒ Refer as FCC KDB 789033, clause E Method SA-1 (spectral trace averaging). | | |
| | ☐ Refer as FCC KDB 789033, clause E Method SA-1 Alt. (RMS detection with slow sweep speed) | | |
| | duty cycle < 98% and average over on/off periods with duty factor | | |
| | ☒ Refer as FCC KDB 789033, clause E Method SA-2 (spectral trace averaging). | | |
| | ☐ Refer as FCC KDB 789033, clause E Method SA-2 Alt. (RMS detection with slow sweep speed) | | |
| ▪ For conducted measurement. | | | |
| | ▪ If the EUT supports multiple transmit chains using options given below: | | |
| | | ☒ Option 1: Measure and sum the spectra across the outputs. Refer as FCC KDB 662911, In-band power spectral density (PSD). Sample all transmit ports simultaneously using a spectrum analyzer for each transmit port. Where the trace bin-by-bin of each transmit port summing can be performed. (i.e., in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 and that from the first spectral bin of output 3, and so on up to the NTX output to obtain the value for the first frequency bin of the summed spectrum.). Add up the amplitude (power) values for the different transmit chains and use this as the new data trace. | |
| | | ☐ Option 2: Measure and sum spectral maxima across the outputs. With this technique, spectra are measured at each output of the device at the required resolution bandwidth. The maximum value (peak) of each spectrum is determined. These maximum values are then summed mathematically in linear power units across the outputs. These operations shall be performed separately over frequency spans that have different out-of-band or spurious emission limits, | |
| | | ☐ Option 3: Measure and add 10 log(N) dB, where N is the number of transmit chains. Refer as FCC KDB 662911, In-band power spectral density (PSD). Performed at each transmit chains and each transmit chains shall be compared with the limit have been reduced with 10 log(N). Or each transmit chains shall be add 10 log(N) to compared with the limit. | |
| | ▪ | If multiple transmit chains, EIRP PPSD calculation could be following as methods:<br>$PPSD_{total} = PPSD_1 + PPSD_2 + \ldots + PPSD_n$<br>(calculated in linear unit [mW] and transfer to log unit [dBm])<br>$EIRP_{total} = PPSD_{total} + DG$ | |

### 3.3.4 Test Setup

| Power Spectral Density |
|---|
|   |

### 3.3.5 Test Result of Peak Power Spectral Density

Refer as Appendix C

## 3.4 Unwanted Emissions

### 3.4.1 Transmitter Radiated Unwanted Emissions Limit

| Unwanted emissions below 1 GHz and restricted band emissions above 1GHz limit | | | |
|---|---|---|---|
| **Frequency Range (MHz)** | **Field Strength (uV/m)** | **Field Strength (dBuV/m)** | **Measure Distance (m)** |
| 0.009~0.490 | 2400/F(kHz) | 48.5 - 13.8 | 300 |
| 0.490~1.705 | 24000/F(kHz) | 33.8 - 23 | 30 |
| 1.705~30.0 | 30 | 29 | 30 |
| 30~88 | 100 | 40 | 3 |
| 88~216 | 150 | 43.5 | 3 |
| 216~960 | 200 | 46 | 3 |
| Above 960 | 500 | 54 | 3 |

Note 1: Test distance for frequencies at or above 30 MHz, measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Note 2: Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.

Note 3: Using the distance of 1m during the test for above 18 GHz, and the test value to correct for the distance factor at 3m.

| Un-restricted band emissions above 1GHz Limit | |
|---|---|
| **Operating Band** | **Limit** |
| 5.15 - 5.25 GHz | e.i.r.p. -27 dBm [68.2 dBuV/m@3m] |
| 5.25 - 5.35 GHz | e.i.r.p. -27 dBm [68.2 dBuV/m@3m] |
| 5.47 - 5.725 GHz | e.i.r.p. -27 dBm [68.2 dBuV/m@3m] |
| 5.725 - 5.85 GHz | all emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge. |

Note 1: Measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

### 3.4.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

### 3.4.3 Test Procedures

| Test Method | | | |
|---|---|---|---|
| ▪ Measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 m for frequencies above 30 MHz, unless it can be further demonstrated that measurements at a distance of 30 m or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements). | | | |
| ▪ The average emission levels shall be measured in [duty cycle ≥ 98 or duty factor]. | | | |
| ▪ For the transmitter unwanted emissions shall be measured using following options below: | | | |
| | ▪ Refer as FCC KDB 789033, clause H)2) for unwanted emissions into non-restricted bands. | | |
| | ▪ Refer as FCC KDB 789033, clause H)1) for unwanted emissions into restricted bands. | | |
| | | ☐ | Refer as FCC KDB 789033, H)6) Method AD (Trace Averaging). |
| | | ☒ | Refer as FCC KDB 789033, H)6) Method VB (Reduced VBW). |
| | | ☐ | Refer as ANSI C63.10, clause 4.2.3.2.3 (Reduced VBW). VBW ≥ 1/T, where T is pulse time. |
| | | ☐ | Refer as ANSI C63.10, clause 4.2.3.2.4 average value of pulsed emissions. |
| | | ☒ | Refer as FCC KDB 789033, clause H)5) measurement procedure peak limit. |
| | | ☐ | Refer as ANSI C63.10, clause 4.2.3.2.2 measurement procedure peak limit. |
| ▪ For radiated measurement. | | | |
| | ▪ Refer as ANSI C63.10, clause 6.4 for radiated emissions below 30 MHz and test distance is 3m. | | |
| | ▪ Refer as ANSI C63.10, clause 6.5 for radiated emissions 30 MHz to 1 GHz and test distance is 3m. | | |
| | ▪ Refer as ANSI C63.10, clause 6.6 for radiated emissions above 1GHz. | | |
| ▪ The any unwanted emissions level shall not exceed the fundamental emission level. | | | |
| ▪ All amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported. | | | |

### 3.4.4 Test Setup

**Transmitter Radiated Unwanted Emissions**

**9kHz ~30MHz**




**30MHz~1GHz**



**Above 1GHz**




### 3.4.5 Transmitter Unwanted Emissions (Below 30MHz)

All amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

### 3.4.6 Test Result of Transmitter Unwanted Emissions

Refer as Appendix D

# 3.5 Frequency Stability

## 3.5.1 Frequency Stability Limit

| Frequency Stability Limit |
|---|
| **UNII Devices** |
| ▪ In-band emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual. |
| **LE-LAN Devices** |
| ▪ N/A |
| **IEEE Std. 802.11** |
| ▪ The transmitter center frequency tolerance shall be ± 20 ppm maximum for the 5 GHz band and ± 25 ppm maximum for the 2.4 GHz band. |

## 3.5.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

## 3.5.3 Test Procedures

| Test Method | |
|---|---|
| ▪ Refer as ANSI C63.10, clause 6.8 for frequency stability tests | |
| | ▪ Frequency stability with respect to ambient temperature |
| | ▪ Frequency stability when varying supply voltage |
| | ▪ Extreme temperature is 0˚C~40˚C. |

## 3.5.4 Test Setup

**Frequency Stability**




## 3.5.5 Test Result of Frequency Stability

Refer as Appendix E

# 4 Test Equipment and Calibration Data

| Instrument | Manufacturer | Model No. | Serial No. | Characteristics | Calibration Date | Calibration Due Date | Remark |
|---|---|---|---|---|---|---|---|
| BILOG ANTENNA with 6dB Attenuator | TESEQ & EMCI | CBL6112D & N-6-06 | 37880 & AT-N0609 | 20MHz ~ 2GHz | Aug. 30, 2016 | Aug. 29, 2017 | Radiation (03CH01-CB) |
| Horn Antenna | EMCO | 3115 | 00075790 | 750MHz ~ 18GHz | Nov. 10, 2016 | Nov. 09, 2017 | Radiation (03CH01-CB) |
| Horn Antenna | Schwarzbeck | BBHA 9170 | BBHA9170252 | 15GHz ~ 40GHz | Jul. 25, 2016 | Jul. 24, 2017 | Radiation (03CH01-CB) |
| Pre-Amplifier | EMCI | EMC330N | 980332 | 20MHz ~ 3GHz | May 02, 2017 | May 01, 2018 | Radiation (03CH01-CB) |
| Pre-Amplifier | Agilent | 8449B | 3008A02310 | 1GHz ~ 26.5GHz | Jan. 16, 2017 | Jan. 15, 2018 | Radiation (03CH01-CB) |
| Pre-Amplifier | MITEQ | TTA1840-35-HG | 1864479 | 18GHz ~ 40GHz | Jun. 28, 2016 | Jun. 27, 2017 | Radiation (03CH01-CB) |
| Spectrum Analyzer | R&S | FSP40 | 100056 | 9kHz ~ 40GHz | Nov. 22, 2016 | Nov. 21, 2017 | Radiation (03CH01-CB) |
| EMI Test | R&S | ESCS | 100355 | 9kHz ~ 2.75GHz | May 06, 2017 | May 05, 2018 | Radiation (03CH01-CB) |
| RF Cable-low | Woken | Low Cable-16+17 | N/A | 30 MHz ~ 1 GHz | Oct. 24, 2016 | Oct. 23, 2017 | Radiation (03CH01-CB) |
| RF Cable-high | Woken | High Cable-16 | N/A | 1 GHz ~ 18 GHz | Oct. 24, 2016 | Oct. 23, 2017 | Radiation (03CH01-CB) |
| RF Cable-high | Woken | High Cable-16+17 | N/A | 1 GHz ~ 18 GHz | Oct. 24, 2016 | Oct. 23, 2017 | Radiation (03CH01-CB) |
| RF Cable-high | Woken | High Cable-40G#1 | N/A | 18GHz ~ 40 GHz | Oct. 24, 2016 | Oct. 23, 2017 | Radiation (03CH01-CB) |
| RF Cable-high | Woken | High Cable-40G#2 | N/A | 18GHz ~ 40 GHz | Oct. 24, 2016 | Oct. 23, 2017 | Radiation (03CH01-CB) |
| Loop Antenna | Teseq | HLA 6120 | 24155 | 9kHz - 30 MHz | Mar. 16, 2016* | Mar. 15, 2018* | Radiation (03CH01-CB) |
| Spectrum analyzer | R&S | FSV40 | 100979 | 9kHz~40GHz | Dec. 26, 2016 | Dec. 25, 2017 | Conducted (TH01-CB) |
| Temp. and Humidity Chamber | Ten Billion | TTH-D3SP | TBN-931011 | -30~100 degree | Jun. 02, 2017 | Jun. 01, 2018 | Conducted (TH01-CB) |
| RF Cable-high | Woken | RG402 | High Cable-6 | 1 GHz – 26.5 GHz | Oct. 24, 2016 | Oct. 23, 2017 | Conducted (TH01-CB) |
| RF Cable-high | Woken | RG402 | High Cable-7 | 1 GHz –26.5 GHz | Oct. 24, 2016 | Oct. 23, 2017 | Conducted (TH01-CB) |
| RF Cable-high | Woken | RG402 | High Cable-8 | 1 GHz –26.5 GHz | Oct. 24, 2016 | Oct. 23, 2017 | Conducted (TH01-CB) |
| RF Cable-high | Woken | RG402 | High Cable-9 | 1 GHz –26.5 GHz | Oct. 24, 2016 | Oct. 23, 2017 | Conducted (TH01-CB) |
| RF Cable-high | Woken | RG402 | High Cable-10 | 1 GHz –26.5 GHz | Oct. 24, 2016 | Oct. 23, 2017 | Conducted (TH01-CB) |

| Instrument | Manufacturer | Model No. | Serial No. | Characteristics | Calibration Date | Calibration Due Date | Remark |
|---|---|---|---|---|---|---|---|
| Power Sensor | Agilent | U2021XA | MY53410001 | 50MHz~18GHz | Nov. 22, 2016 | Nov. 21, 2017 | Conducted (TH01-CB) |

Note: Calibration Interval of instruments listed above is one year.
"*" Calibration Interval of instruments listed above is two years.
N.C.R. means Non-Calibration required.

## 802.11a, 802.11ac VHT20, 802.11ac VHT40, 802.11ac VHT80
## Summary

| Mode | Max-N dB (Hz) | Max-OBW (Hz) | ITU-Code | Min-N dB (Hz) | Min-OBW (Hz) |
|---|---|---|---|---|---|
| 802.11a_(6Mbps)_4TX | - | - | - | - | - |
| 5.25-5.35GHz | 21.675M | 16.642M | 16M6D1D | 21.125M | 16.542M |
| 5.47-5.725GHz | 21.675M | 16.667M | 16M7D1D | 21.275M | 16.567M |
| 802.11ac VHT20_Nss1,(MCS0)_4TX | - | - | - | - | - |
| 5.25-5.35GHz | 21.95M | 17.766M | 17M8D1D | 21.225M | 17.716M |
| 5.47-5.725GHz | 21.925M | 17.791M | 17M8D1D | 21.475M | 17.716M |
| 802.11ac VHT40_Nss1,(MCS0)_4TX | - | - | - | - | - |
| 5.25-5.35GHz | 40.35M | 36.232M | 36M2D1D | 39.5M | 36.132M |
| 5.47-5.725GHz | 40.5M | 36.332M | 36M3D1D | 39.65M | 36.182M |
| 802.11ac VHT80_Nss1,(MCS0)_4TX | - | - | - | - | - |
| 5.25-5.35GHz | 82M | 75.762M | 75M8D1D | 81.2M | 75.462M |
| 5.47-5.725GHz | 82.2M | 75.962M | 76M0D1D | 81.2M | 75.562M |
| 802.11ac VHT20-BF_Nss1,(MCS0)_4TX | - | - | - | - | - |
| 5.25-5.35GHz | 21.85M | 17.791M | 17M8D1D | 21.475M | 17.691M |
| 5.47-5.725GHz | 21.9M | 17.816M | 17M8D1D | 21.475M | 17.691M |
| 802.11ac VHT40-BF_Nss1,(MCS0)_4TX | - | - | - | - | - |
| 5.25-5.35GHz | 40.35M | 36.282M | 36M3D1D | 39.55M | 36.182M |
| 5.47-5.725GHz | 40.55M | 36.332M | 36M3D1D | 39.65M | 36.182M |
| 802.11ac VHT80-BF_Nss1,(MCS0)_4TX | - | - | - | - | - |
| 5.25-5.35GHz | 81.9M | 75.762M | 75M8D1D | 81.1M | 75.562M |
| 5.47-5.725GHz | 82.3M | 75.962M | 76M0D1D | 81.1M | 75.662M |

**Max-N dB** = Maximum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
**Max-OBW** = Maximum 99% occupied bandwidth;
**Min-N dB** = Minimum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
**Min-OBW** = Minimum 99% occupied bandwidth;

## Result

| Mode | Result | Limit (Hz) | Port 1-N dB (Hz) | Port 1-OBW (Hz) | Port 2-N dB (Hz) | Port 2-OBW (Hz) | Port 3-N dB (Hz) | Port 3-OBW (Hz) | Port 4-N dB (Hz) | Port 4-OBW (Hz) |
|---|---|---|---|---|---|---|---|---|---|---|
| 802.11a_(6Mbps)_4TX | - | - | - | - | - | - | - | - | - | - |
| 5260MHz | Pass | Inf | 21.6M | 16.592M | 21.45M | 16.617M | 21.425M | 16.592M | 21.4M | 16.617M |
| 5300MHz | Pass | Inf | 21.575M | 16.567M | 21.35M | 16.567M | 21.125M | 16.592M | 21.275M | 16.542M |
| 5320MHz | Pass | Inf | 21.45M | 16.542M | 21.675M | 16.642M | 21.3M | 16.567M | 21.375M | 16.567M |
| 5500MHz | Pass | Inf | 21.675M | 16.567M | 21.45M | 16.567M | 21.35M | 16.567M | 21.275M | 16.567M |
| 5580MHz | Pass | Inf | 21.525M | 16.592M | 21.675M | 16.617M | 21.325M | 16.592M | 21.525M | 16.617M |
| 5700MHz | Pass | Inf | 21.6M | 16.667M | 21.575M | 16.592M | 21.45M | 16.567M | 21.425M | 16.567M |
| 802.11ac VHT20_Nss1,(MCS0)_4TX | - | - | - | - | - | - | - | - | - | - |
| 5260MHz | Pass | Inf | 21.8M | 17.766M | 21.425M | 17.716M | 21.45M | 17.741M | 21.55M | 17.766M |
| 5300MHz | Pass | Inf | 21.95M | 17.766M | 21.5M | 17.741M | 21.55M | 17.741M | 21.575M | 17.766M |
| 5320MHz | Pass | Inf | 21.825M | 17.766M | 21.475M | 17.766M | 21.225M | 17.741M | 21.825M | 17.741M |
| 5500MHz | Pass | Inf | 21.8M | 17.716M | 21.475M | 17.716M | 21.65M | 17.741M | 21.65M | 17.741M |
| 5580MHz | Pass | Inf | 21.8M | 17.791M | 21.6M | 17.741M | 21.65M | 17.766M | 21.55M | 17.741M |
| 5700MHz | Pass | Inf | 21.925M | 17.716M | 21.55M | 17.741M | 21.6M | 17.741M | 21.6M | 17.741M |
| 802.11ac VHT40_Nss1,(MCS0)_4TX | - | - | - | - | - | - | - | - | - | - |
| 5270MHz | Pass | Inf | 40.35M | 36.232M | 39.5M | 36.232M | 39.75M | 36.182M | 39.95M | 36.232M |
| 5310MHz | Pass | Inf | 40.15M | 36.182M | 39.5M | 36.132M | 39.75M | 36.232M | 39.7M | 36.182M |
| 5510MHz | Pass | Inf | 40.35M | 36.232M | 39.65M | 36.232M | 39.9M | 36.182M | 39.85M | 36.182M |
| 5550MHz | Pass | Inf | 40.5M | 36.232M | 39.8M | 36.282M | 40.1M | 36.232M | 39.7M | 36.282M |
| 5670MHz | Pass | Inf | 40.4M | 36.232M | 39.85M | 36.232M | 40.2M | 36.282M | 39.8M | 36.332M |
| 802.11ac VHT80_Nss1,(MCS0)_4TX | - | - | - | - | - | - | - | - | - | - |
| 5290MHz | Pass | Inf | 82M | 75.762M | 81.2M | 75.662M | 81.3M | 75.462M | 81.4M | 75.762M |
| 5530MHz | Pass | Inf | 81.4M | 75.762M | 81.8M | 75.662M | 81.2M | 75.562M | 81.6M | 75.762M |
| 5610MHz | Pass | Inf | 82M | 75.962M | 82.2M | 75.762M | 81.8M | 75.762M | 81.4M | 75.562M |
| 802.11ac VHT20-BF_Nss1,(MCS0)_4TX | - | - | - | - | - | - | - | - | - | - |
| 5260MHz | Pass | Inf | 21.85M | 17.791M | 21.6M | 17.741M | 21.525M | 17.741M | 21.475M | 17.716M |
| 5300MHz | Pass | Inf | 21.75M | 17.741M | 21.55M | 17.716M | 21.5M | 17.766M | 21.6M | 17.741M |
| 5320MHz | Pass | Inf | 21.85M | 17.741M | 21.525M | 17.741M | 21.55M | 17.691M | 21.575M | 17.741M |
| 5500MHz | Pass | Inf | 21.9M | 17.816M | 21.55M | 17.741M | 21.575M | 17.741M | 21.775M | 17.691M |
| 5580MHz | Pass | Inf | 21.9M | 17.766M | 21.475M | 17.716M | 21.55M | 17.716M | 21.575M | 17.741M |
| 5700MHz | Pass | Inf | 21.825M | 17.766M | 21.525M | 17.766M | 21.6M | 17.716M | 21.7M | 17.766M |
| 802.11ac VHT40-BF_Nss1,(MCS0)_4TX | - | - | - | - | - | - | - | - | - | - |
| 5270MHz | Pass | Inf | 40.35M | 36.182M | 39.9M | 36.232M | 39.9M | 36.182M | 39.6M | 36.232M |
| 5310MHz | Pass | Inf | 40.15M | 36.182M | 39.55M | 36.282M | 40.05M | 36.182M | 39.65M | 36.282M |
| 5510MHz | Pass | Inf | 40.55M | 36.282M | 39.8M | 36.232M | 40M | 36.332M | 39.8M | 36.232M |
| 5550MHz | Pass | Inf | 40.3M | 36.232M | 39.65M | 36.282M | 39.9M | 36.282M | 39.8M | 36.232M |
| 5670MHz | Pass | Inf | 40.35M | 36.282M | 39.95M | 36.332M | 39.65M | 36.282M | 39.95M | 36.182M |

| Mode | Result | Limit (Hz) | Port 1-N dB (Hz) | Port 1-OBW (Hz) | Port 2-N dB (Hz) | Port 2-OBW (Hz) | Port 3-N dB (Hz) | Port 3-OBW (Hz) | Port 4-N dB (Hz) | Port 4-OBW (Hz) |
|---|---|---|---|---|---|---|---|---|---|---|
| 802.11ac VHT80-BF_Nss1,(MCS0)_4TX | - | - | - | - | - | - | - | - | - | - |
| 5290MHz | Pass | Inf | 81.9M | 75.762M | 81.1M | 75.762M | 81.2M | 75.562M | 81.3M | 75.662M |
| 5530MHz | Pass | Inf | 82.3M | 75.662M | 81.4M | 75.662M | 81.5M | 75.662M | 81.1M | 75.762M |
| 5610MHz | Pass | Inf | 81.8M | 75.762M | 81.5M | 75.862M | 81.6M | 75.862M | 81.3M | 75.962M |

**Port X-N dB** = Port **X** 6dB down bandwidth for 5.725-5.85GHz band / 26dB down bandwidth for other band
**Port X-OBW** = Port **X** 99% occupied bandwidth;

## 802.11a_(6Mbps)_4TX — EBW

### 5260MHz




| 26dB(Hz) | Fl-26dB(Hz) | Fh-26dB(Hz) | OBW(Hz) | Fl-OBW(Hz) | Fh-OBW(Hz) | Limit(Hz) | Port |
|---|---|---|---|---|---|---|---|
| 21.6M | 5.24915G | 5.27075G | 16.592M | 5.251679G | 5.268271G | Inf | 1 |
| 21.45M | 5.24925G | 5.2707G | 16.617M | 5.251679G | 5.268296G | Inf | 2 |
| 21.425M | 5.2493G | 5.270725G | 16.592M | 5.251654G | 5.268246G | Inf | 3 |
| 21.4M | 5.24925G | 5.27065G | 16.617M | 5.251654G | 5.268271G | Inf | 4 |

## 802.11a_(6Mbps)_4TX — EBW

### 5300MHz




| 26dB(Hz) | Fl-26dB(Hz) | Fh-26dB(Hz) | OBW(Hz) | Fl-OBW(Hz) | Fh-OBW(Hz) | Limit(Hz) | Port |
|---|---|---|---|---|---|---|---|
| 21.575M | 5.289225G | 5.3108G | 16.567M | 5.291654G | 5.308221G | Inf | 1 |
| 21.35M | 5.289275G | 5.310625G | 16.567M | 5.291679G | 5.308246G | Inf | 2 |
| 21.125M | 5.289325G | 5.31045G | 16.592M | 5.291654G | 5.308246G | Inf | 3 |
| 21.275M | 5.2894G | 5.310675G | 16.542M | 5.291679G | 5.308221G | Inf | 4 |

## 802.11a_(6Mbps)_4TX — EBW

### 5320MHz




| 26dB(Hz) | Fl-26dB(Hz) | Fh-26dB(Hz) | OBW(Hz) | Fl-OBW(Hz) | Fh-OBW(Hz) | Limit(Hz) | Port |
|---|---|---|---|---|---|---|---|
| 21.45M | 5.309225G | 5.330675G | 16.542M | 5.311679G | 5.328221G | Inf | 1 |
| 21.675M | 5.309025G | 5.3307G | 16.642M | 5.311604G | 5.328246G | Inf | 2 |
| 21.3M | 5.309275G | 5.330575G | 16.567M | 5.311629G | 5.328196G | Inf | 3 |
| 21.375M | 5.30925G | 5.330625G | 16.567M | 5.311654G | 5.328221G | Inf | 4 |

## 802.11a_(6Mbps)_4TX — EBW

### 5500MHz




| 26dB(Hz) | Fl-26dB(Hz) | Fh-26dB(Hz) | OBW(Hz) | Fl-OBW(Hz) | Fh-OBW(Hz) | Limit(Hz) | Port |
|---|---|---|---|---|---|---|---|
| 21.675M | 5.489125G | 5.5108G | 16.567M | 5.491679G | 5.508246G | Inf | 1 |
| 21.45M | 5.4892G | 5.51065G | 16.567M | 5.491679G | 5.508246G | Inf | 2 |
| 21.35M | 5.48935G | 5.5107G | 16.567M | 5.491679G | 5.508246G | Inf | 3 |
| 21.275M | 5.4893G | 5.510575G | 16.567M | 5.491654G | 5.508221G | Inf | 4 |

## 802.11a_(6Mbps)_4TX — EBW

### 5580MHz




| 26dB(Hz) | Fl-26dB(Hz) | Fh-26dB(Hz) | OBW(Hz) | Fl-OBW(Hz) | Fh-OBW(Hz) | Limit(Hz) | Port |
|---|---|---|---|---|---|---|---|
| 21.525M | 5.56915G | 5.590675G | 16.592M | 5.571679G | 5.588271G | Inf | 1 |
| 21.675M | 5.5691G | 5.590775G | 16.617M | 5.571654G | 5.588271G | Inf | 2 |
| 21.325M | 5.569325G | 5.59065G | 16.592M | 5.571654G | 5.588246G | Inf | 3 |
| 21.525M | 5.569275G | 5.5908G | 16.617M | 5.571654G | 5.588271G | Inf | 4 |

## 802.11a_(6Mbps)_4TX — EBW

### 5700MHz




| 26dB(Hz) | Fl-26dB(Hz) | Fh-26dB(Hz) | OBW(Hz) | Fl-OBW(Hz) | Fh-OBW(Hz) | Limit(Hz) | Port |
|---|---|---|---|---|---|---|---|
| 21.6M | 5.689125G | 5.710725G | 16.667M | 5.691604G | 5.708271G | Inf | 1 |
| 21.575M | 5.6891G | 5.710675G | 16.592M | 5.691629G | 5.708221G | Inf | 2 |
| 21.45M | 5.6893G | 5.71075G | 16.567M | 5.691654G | 5.708221G | Inf | 3 |
| 21.425M | 5.68925G | 5.710675G | 16.567M | 5.691654G | 5.708221G | Inf | 4 |

## 802.11ac VHT20_Nss1,(MCS0)_4TX — EBW

### 5260MHz




| 26dB(Hz) | Fl-26dB(Hz) | Fh-26dB(Hz) | OBW(Hz) | Fl-OBW(Hz) | Fh-OBW(Hz) | Limit(Hz) | Port |
|---|---|---|---|---|---|---|---|
| 21.8M | 5.249175G | 5.270975G | 17.766M | 5.251104G | 5.268871G | Inf | 1 |
| 21.425M | 5.249275G | 5.2707G | 17.716M | 5.251129G | 5.268846G | Inf | 2 |
| 21.45M | 5.2493G | 5.27075G | 17.741M | 5.251104G | 5.268846G | Inf | 3 |
| 21.55M | 5.249175G | 5.270725G | 17.766M | 5.251054G | 5.268821G | Inf | 4 |

## 802.11ac VHT20_Nss1,(MCS0)_4TX — EBW

### 5300MHz




| 26dB(Hz) | Fl-26dB(Hz) | Fh-26dB(Hz) | OBW(Hz) | Fl-OBW(Hz) | Fh-OBW(Hz) | Limit(Hz) | Port |
|---|---|---|---|---|---|---|---|
| 21.95M | 5.28895G | 5.3109G | 17.766M | 5.291054G | 5.308821G | Inf | 1 |
| 21.5M | 5.2892G | 5.3107G | 17.741M | 5.291079G | 5.308821G | Inf | 2 |
| 21.55M | 5.2892G | 5.31075G | 17.741M | 5.291079G | 5.308821G | Inf | 3 |
| 21.575M | 5.28915G | 5.310725G | 17.766M | 5.291079G | 5.308846G | Inf | 4 |

## 802.11ac VHT20_Nss1,(MCS0)_4TX — EBW

### 5320MHz




| 26dB(Hz) | Fl-26dB(Hz) | Fh-26dB(Hz) | OBW(Hz) | Fl-OBW(Hz) | Fh-OBW(Hz) | Limit(Hz) | Port |
|---|---|---|---|---|---|---|---|
| 21.825M | 5.309075G | 5.3309G | 17.766M | 5.311079G | 5.328846G | Inf | 1 |
| 21.475M | 5.309175G | 5.33065G | 17.766M | 5.311054G | 5.328821G | Inf | 2 |
| 21.225M | 5.3093G | 5.330525G | 17.741M | 5.311079G | 5.328821G | Inf | 3 |
| 21.825M | 5.30905G | 5.330875G | 17.741M | 5.311054G | 5.327796G | Inf | 4 |

## 802.11ac VHT20_Nss1,(MCS0)_4TX

**EBW**

### 5500MHz




| 26dB(Hz) | Fl-26dB(Hz) | Fh-26dB(Hz) | OBW(Hz) | Fl-OBW(Hz) | Fh-OBW(Hz) | Limit(Hz) | Port |
|---|---|---|---|---|---|---|---|
| 21.8M | 5.489175G | 5.510975G | 17.716M | 5.491104G | 5.508821G | Inf | 1 |
| 21.475M | 5.4893G | 5.510775G | 17.716M | 5.491104G | 5.508821G | Inf | 2 |
| 21.65M | 5.48925G | 5.5109G | 17.741M | 5.491104G | 5.508846G | Inf | 3 |
| 21.65M | 5.489125G | 5.510775G | 17.741M | 5.491104G | 5.508846G | Inf | 4 |

## 802.11ac VHT20_Nss1,(MCS0)_4TX

**EBW**

### 5580MHz




| 26dB(Hz) | Fl-26dB(Hz) | Fh-26dB(Hz) | OBW(Hz) | Fl-OBW(Hz) | Fh-OBW(Hz) | Limit(Hz) | Port |
|---|---|---|---|---|---|---|---|
| 21.8M | 5.569075G | 5.590875G | 17.791M | 5.571054G | 5.588846G | Inf | 1 |
| 21.6M | 5.569125G | 5.590725G | 17.741M | 5.571079G | 5.588821G | Inf | 2 |
| 21.65M | 5.569075G | 5.590725G | 17.766M | 5.571079G | 5.588846G | Inf | 3 |
| 21.55M | 5.5692G | 5.59075G | 17.741M | 5.571079G | 5.588821G | Inf | 4 |

## 802.11ac VHT20_Nss1,(MCS0)_4TX

**EBW**

### 5700MHz




| 26dB(Hz) | Fl-26dB(Hz) | Fh-26dB(Hz) | OBW(Hz) | Fl-OBW(Hz) | Fh-OBW(Hz) | Limit(Hz) | Port |
|---|---|---|---|---|---|---|---|
| 21.925M | 5.68895G | 5.710875G | 17.716M | 5.691079G | 5.708796G | Inf | 1 |
| 21.55M | 5.6892G | 5.71075G | 17.741M | 5.691079G | 5.708821G | Inf | 2 |
| 21.6M | 5.6892G | 5.7108G | 17.741M | 5.691079G | 5.708821G | Inf | 3 |
| 21.6M | 5.689125G | 5.710725G | 17.741M | 5.691079G | 5.708821G | Inf | 4 |

## 802.11ac VHT40_Nss1,(MCS0)_4TX — EBW

### 5270MHz




| 26dB(Hz) | Fl-26dB(Hz) | Fh-26dB(Hz) | OBW(Hz) | Fl-OBW(Hz) | Fh-OBW(Hz) | Limit(Hz) | Port |
|---|---|---|---|---|---|---|---|
| 40.35M | 5.2498G | 5.29015G | 36.232M | 5.251909G | 5.288141G | Inf | 1 |
| 39.5M | 5.25025G | 5.28975G | 36.232M | 5.251859G | 5.288091G | Inf | 2 |
| 39.75M | 5.25015G | 5.2899G | 36.182M | 5.251859G | 5.288041G | Inf | 3 |
| 39.95M | 5.25015G | 5.2901G | 36.232M | 5.251859G | 5.288091G | Inf | 4 |

## 802.11ac VHT40_Nss1,(MCS0)_4TX — EBW

### 5310MHz




| 26dB(Hz) | Fl-26dB(Hz) | Fh-26dB(Hz) | OBW(Hz) | Fl-OBW(Hz) | Fh-OBW(Hz) | Limit(Hz) | Port |
|---|---|---|---|---|---|---|---|
| 40.15M | 5.2899G | 5.33005G | 36.182M | 5.291859G | 5.328041G | Inf | 1 |
| 39.5M | 5.2901G | 5.3296G | 36.132M | 5.291859G | 5.327991G | Inf | 2 |
| 39.75M | 5.28995G | 5.3297G | 36.232M | 5.291759G | 5.327991G | Inf | 3 |
| 39.7M | 5.29G | 5.3297G | 36.182M | 5.291859G | 5.328041G | Inf | 4 |

## 802.11ac VHT40_Nss1,(MCS0)_4TX — EBW

### 5510MHz




| 26dB(Hz) | Fl-26dB(Hz) | Fh-26dB(Hz) | OBW(Hz) | Fl-OBW(Hz) | Fh-OBW(Hz) | Limit(Hz) | Port |
|---|---|---|---|---|---|---|---|
| 40.35M | 5.4899G | 5.53025G | 36.232M | 5.491859G | 5.528091G | Inf | 1 |
| 39.65M | 5.4902G | 5.52985G | 36.232M | 5.491859G | 5.528091G | Inf | 2 |
| 39.9M | 5.49015G | 5.53005G | 36.182M | 5.491909G | 5.528091G | Inf | 3 |
| 39.85M | 5.4901G | 5.52995G | 36.182M | 5.491909G | 5.528091G | Inf | 4 |

## 802.11ac VHT40_Nss1,(MCS0)_4TX — EBW

### 5550MHz




| 26dB(Hz) | Fl-26dB(Hz) | Fh-26dB(Hz) | OBW(Hz) | Fl-OBW(Hz) | Fh-OBW(Hz) | Limit(Hz) | Port |
|---|---|---|---|---|---|---|---|
| 40.5M | 5.5297G | 5.5702G | 36.232M | 5.531809G | 5.568041G | Inf | 1 |
| 39.8M | 5.53005G | 5.56985G | 36.282M | 5.531809G | 5.568091G | Inf | 2 |
| 40.1M | 5.52995G | 5.57005G | 36.232M | 5.531759G | 5.567991G | Inf | 3 |
| 39.7M | 5.53G | 5.5697G | 36.282M | 5.531759G | 5.568041G | Inf | 4 |

## 802.11ac VHT40_Nss1,(MCS0)_4TX — EBW

### 5670MHz




| 26dB(Hz) | Fl-26dB(Hz) | Fh-26dB(Hz) | OBW(Hz) | Fl-OBW(Hz) | Fh-OBW(Hz) | Limit(Hz) | Port |
|---|---|---|---|---|---|---|---|
| 40.4M | 5.6498G | 5.6902G | 36.232M | 5.651859G | 5.688091G | Inf | 1 |
| 39.85M | 5.65G | 5.68985G | 36.232M | 5.651809G | 5.688041G | Inf | 2 |
| 40.2M | 5.6499G | 5.6901G | 36.282M | 5.651809G | 5.688091G | Inf | 3 |
| 39.8M | 5.6501G | 5.6899G | 36.332M | 5.651759G | 5.688091G | Inf | 4 |

## 802.11ac VHT80_Nss1,(MCS0)_4TX — EBW

### 5290MHz




| 26dB(Hz) | Fl-26dB(Hz) | Fh-26dB(Hz) | OBW(Hz) | Fl-OBW(Hz) | Fh-OBW(Hz) | Limit(Hz) | Port |
|---|---|---|---|---|---|---|---|
| 82M | 5.2492G | 5.3312G | 75.762M | 5.252119G | 5.327881G | Inf | 1 |
| 81.2M | 5.2492G | 5.3304G | 75.662M | 5.252019G | 5.327681G | Inf | 2 |
| 81.3M | 5.2493G | 5.3306G | 75.462M | 5.252119G | 5.327581G | Inf | 3 |
| 81.4M | 5.2491G | 5.3305G | 75.762M | 5.252119G | 5.327881G | Inf | 4 |

## 802.11ac VHT80_Nss1,(MCS0)_4TX — EBW

### 5530MHz




| 26dB(Hz) | Fl-26dB(Hz) | Fh-26dB(Hz) | OBW(Hz) | Fl-OBW(Hz) | Fh-OBW(Hz) | Limit(Hz) | Port |
|---|---|---|---|---|---|---|---|
| 81.4M | 5.4894G | 5.5708G | 75.762M | 5.492119G | 5.567881G | Inf | 1 |
| 81.8M | 5.4892G | 5.571G | 75.662M | 5.492219G | 5.567881G | Inf | 2 |
| 81.2M | 5.4894G | 5.5706G | 75.562M | 5.492119G | 5.567681G | Inf | 3 |
| 81.6M | 5.4891G | 5.5707G | 75.762M | 5.492019G | 5.567781G | Inf | 4 |

## 802.11ac VHT80_Nss1,(MCS0)_4TX — EBW

### 5610MHz




| 26dB(Hz) | Fl-26dB(Hz) | Fh-26dB(Hz) | OBW(Hz) | Fl-OBW(Hz) | Fh-OBW(Hz) | Limit(Hz) | Port |
|---|---|---|---|---|---|---|---|
| 82M | 5.569G | 5.651G | 75.962M | 5.572019G | 5.647981G | Inf | 1 |
| 82.2M | 5.5691G | 5.6513G | 75.762M | 5.572019G | 5.647781G | Inf | 2 |
| 81.8M | 5.5691G | 5.6509G | 75.762M | 5.572019G | 5.647781G | Inf | 3 |
| 81.4M | 5.5691G | 5.6505G | 75.562M | 5.572119G | 5.647681G | Inf | 4 |

## 802.11ac VHT20-BF_Nss1,(MCS0)_4TX — EBW

### 5260MHz




| 26dB(Hz) | Fl-26dB(Hz) | Fh-26dB(Hz) | OBW(Hz) | Fl-OBW(Hz) | Fh-OBW(Hz) | Limit(Hz) | Port |
|---|---|---|---|---|---|---|---|
| 21.85M | 5.2491G | 5.27095G | 17.791M | 5.251079G | 5.268871G | Inf | 1 |
| 21.6M | 5.249225G | 5.270825G | 17.741M | 5.251104G | 5.268846G | Inf | 2 |
| 21.525M | 5.249275G | 5.2708G | 17.741M | 5.251104G | 5.268846G | Inf | 3 |
| 21.475M | 5.249225G | 5.2707G | 17.716M | 5.251129G | 5.268846G | Inf | 4 |

## 802.11ac VHT20-BF_Nss1,(MCS0)_4TX — EBW

### 5300MHz







| 26dB(Hz) | Fl-26dB(Hz) | Fh-26dB(Hz) | OBW(Hz) | Fl-OBW(Hz) | Fh-OBW(Hz) | Limit(Hz) | Port |
|---|---|---|---|---|---|---|---|
| 21.75M | 5.2891G | 5.31085G | 17.741M | 5.291104G | 5.308846G | Inf | 1 |
| 21.55M | 5.2892G | 5.31075G | 17.716M | 5.291079G | 5.308796G | Inf | 2 |
| 21.5M | 5.2892G | 5.3107G | 17.766M | 5.291079G | 5.308846G | Inf | 3 |
| 21.6M | 5.28915G | 5.31075G | 17.741M | 5.291079G | 5.308821G | Inf | 4 |

## 802.11ac VHT20-BF_Nss1,(MCS0)_4TX — EBW

### 5320MHz







| 26dB(Hz) | Fl-26dB(Hz) | Fh-26dB(Hz) | OBW(Hz) | Fl-OBW(Hz) | Fh-OBW(Hz) | Limit(Hz) | Port |
|---|---|---|---|---|---|---|---|
| 21.85M | 5.309025G | 5.330875G | 17.741M | 5.311054G | 5.328796G | Inf | 1 |
| 21.525M | 5.30915G | 5.330675G | 17.741M | 5.311054G | 5.328796G | Inf | 2 |
| 21.55M | 5.309075G | 5.330625G | 17.691M | 5.311079G | 5.328771G | Inf | 3 |
| 21.575M | 5.309125G | 5.3307G | 17.741M | 5.311054G | 5.328796G | Inf | 4 |

## 802.11ac VHT20-BF_Nss1,(MCS0)_4TX — EBW

### 5500MHz







| 26dB(Hz) | Fl-26dB(Hz) | Fh-26dB(Hz) | OBW(Hz) | Fl-OBW(Hz) | Fh-OBW(Hz) | Limit(Hz) | Port |
|---|---|---|---|---|---|---|---|
| 21.9M | 5.48905G | 5.51095G | 17.816M | 5.491054G | 5.508871G | Inf | 1 |
| 21.55M | 5.489175G | 5.510725G | 17.741M | 5.491104G | 5.508846G | Inf | 2 |
| 21.575M | 5.48925G | 5.510825G | 17.741M | 5.491104G | 5.508846G | Inf | 3 |
| 21.775M | 5.489025G | 5.5108G | 17.691M | 5.491129G | 5.508821G | Inf | 4 |

## 802.11ac VHT20-BF_Nss1,(MCS0)_4TX — EBW

### 5580MHz







| 26dB(Hz) | Fl-26dB(Hz) | Fh-26dB(Hz) | OBW(Hz) | Fl-OBW(Hz) | Fh-OBW(Hz) | Limit(Hz) | Port |
|---|---|---|---|---|---|---|---|
| 21.9M | 5.569025G | 5.590925G | 17.766M | 5.571054G | 5.588821G | Inf | 1 |
| 21.475M | 5.56925G | 5.590725G | 17.716M | 5.571104G | 5.588821G | Inf | 2 |
| 21.55M | 5.569125G | 5.590675G | 17.716M | 5.571104G | 5.588821G | Inf | 3 |
| 21.575M | 5.569125G | 5.5907G | 17.741M | 5.571079G | 5.588821G | Inf | 4 |

## 802.11ac VHT20-BF_Nss1,(MCS0)_4TX — EBW

### 5700MHz







| 26dB(Hz) | Fl-26dB(Hz) | Fh-26dB(Hz) | OBW(Hz) | Fl-OBW(Hz) | Fh-OBW(Hz) | Limit(Hz) | Port |
|---|---|---|---|---|---|---|---|
| 21.825M | 5.68905G | 5.710875G | 17.766M | 5.691054G | 5.708821G | Inf | 1 |
| 21.525M | 5.689225G | 5.71075G | 17.766M | 5.691054G | 5.708821G | Inf | 2 |
| 21.6M | 5.6891G | 5.7107G | 17.716M | 5.691104G | 5.708821G | Inf | 3 |
| 21.7M | 5.689125G | 5.710825G | 17.766M | 5.691054G | 5.708821G | Inf | 4 |

## 802.11ac VHT40-BF_Nss1,(MCS0)_4TX — EBW

### 5270MHz







| 26dB(Hz) | Fl-26dB(Hz) | Fh-26dB(Hz) | OBW(Hz) | Fl-OBW(Hz) | Fh-OBW(Hz) | Limit(Hz) | Port |
|---|---|---|---|---|---|---|---|
| 40.35M | 5.2498G | 5.29015G | 36.182M | 5.251909G | 5.288091G | Inf | 1 |
| 39.9M | 5.25025G | 5.29015G | 36.232M | 5.251859G | 5.288091G | Inf | 2 |
| 39.9M | 5.25G | 5.2899G | 36.182M | 5.251859G | 5.288041G | Inf | 3 |
| 39.6M | 5.2501G | 5.2897G | 36.232M | 5.251859G | 5.288091G | Inf | 4 |

## 802.11ac VHT40-BF_Nss1,(MCS0)_4TX — EBW

### 5310MHz




| 26dB(Hz) | Fl-26dB(Hz) | Fh-26dB(Hz) | OBW(Hz) | Fl-OBW(Hz) | Fh-OBW(Hz) | Limit(Hz) | Port |
|---|---|---|---|---|---|---|---|
| 40.15M | 5.28985G | 5.33G | 36.182M | 5.291859G | 5.328041G | Inf | 1 |
| 39.55M | 5.29015G | 5.3297G | 36.282M | 5.291809G | 5.328091G | Inf | 2 |
| 40.05M | 5.2898G | 5.32985G | 36.182M | 5.291809G | 5.327991G | Inf | 3 |
| 39.65M | 5.2901G | 5.32975G | 36.282M | 5.291759G | 5.328041G | Inf | 4 |

## 802.11ac VHT40-BF_Nss1,(MCS0)_4TX — EBW

### 5510MHz




| 26dB(Hz) | Fl-26dB(Hz) | Fh-26dB(Hz) | OBW(Hz) | Fl-OBW(Hz) | Fh-OBW(Hz) | Limit(Hz) | Port |
|---|---|---|---|---|---|---|---|
| 40.55M | 5.4898G | 5.53035G | 36.282M | 5.491859G | 5.528141G | Inf | 1 |
| 39.8M | 5.4903G | 5.5301G | 36.232M | 5.491859G | 5.528091G | Inf | 2 |
| 40M | 5.49G | 5.53G | 36.332M | 5.491809G | 5.528141G | Inf | 3 |
| 39.8M | 5.4901G | 5.5299G | 36.232M | 5.491809G | 5.528041G | Inf | 4 |

## 802.11ac VHT40-BF_Nss1,(MCS0)_4TX — EBW

### 5550MHz




| 26dB(Hz) | Fl-26dB(Hz) | Fh-26dB(Hz) | OBW(Hz) | Fl-OBW(Hz) | Fh-OBW(Hz) | Limit(Hz) | Port |
|---|---|---|---|---|---|---|---|
| 40.3M | 5.52975G | 5.57005G | 36.232M | 5.531809G | 5.568041G | Inf | 1 |
| 39.65M | 5.53015G | 5.5698G | 36.282M | 5.531809G | 5.568091G | Inf | 2 |
| 39.9M | 5.53G | 5.5699G | 36.282M | 5.531759G | 5.568041G | Inf | 3 |
| 39.8M | 5.5301G | 5.5699G | 36.232M | 5.531809G | 5.568041G | Inf | 4 |

## 802.11ac VHT40-BF_Nss1,(MCS0)_4TX — EBW

### 5670MHz







| 26dB(Hz) | Fl-26dB(Hz) | Fh-26dB(Hz) | OBW(Hz) | Fl-OBW(Hz) | Fh-OBW(Hz) | Limit(Hz) | Port |
|---|---|---|---|---|---|---|---|
| 40.35M | 5.6499G | 5.69025G | 36.282M | 5.651759G | 5.688041G | Inf | 1 |
| 39.95M | 5.6499G | 5.68985G | 36.332M | 5.651709G | 5.688041G | Inf | 2 |
| 39.65M | 5.65005G | 5.6897G | 36.282M | 5.651859G | 5.688141G | Inf | 3 |
| 39.95M | 5.6501G | 5.69005G | 36.182M | 5.651859G | 5.688041G | Inf | 4 |

## 802.11ac VHT80-BF_Nss1,(MCS0)_4TX — EBW

### 5290MHz







| 26dB(Hz) | Fl-26dB(Hz) | Fh-26dB(Hz) | OBW(Hz) | Fl-OBW(Hz) | Fh-OBW(Hz) | Limit(Hz) | Port |
|---|---|---|---|---|---|---|---|
| 81.9M | 5.2493G | 5.3312G | 75.762M | 5.252119G | 5.327881G | Inf | 1 |
| 81.1M | 5.2495G | 5.3306G | 75.762M | 5.252019G | 5.327781G | Inf | 2 |
| 81.2M | 5.2494G | 5.3306G | 75.562M | 5.252119G | 5.327681G | Inf | 3 |
| 81.3M | 5.2494G | 5.3307G | 75.662M | 5.252019G | 5.327681G | Inf | 4 |

## 802.11ac VHT80-BF_Nss1,(MCS0)_4TX — EBW

### 5530MHz







| 26dB(Hz) | Fl-26dB(Hz) | Fh-26dB(Hz) | OBW(Hz) | Fl-OBW(Hz) | Fh-OBW(Hz) | Limit(Hz) | Port |
|---|---|---|---|---|---|---|---|
| 82.3M | 5.4887G | 5.571G | 75.662M | 5.492219G | 5.567881G | Inf | 1 |
| 81.4M | 5.4893G | 5.5707G | 75.662M | 5.492219G | 5.567881G | Inf | 2 |
| 81.5M | 5.4893G | 5.5708G | 75.662M | 5.492019G | 5.567681G | Inf | 3 |
| 81.1M | 5.4895G | 5.5706G | 75.762M | 5.492019G | 5.567781G | Inf | 4 |

**802.11ac VHT80-BF_Nss1,(MCS0)_4TX** **EBW**

**5610MHz**




| 26dB(Hz) | Fl-26dB(Hz) | Fh-26dB(Hz) | OBW(Hz) | Fl-OBW(Hz) | Fh-OBW(Hz) | Limit(Hz) | Port |
|---|---|---|---|---|---|---|---|
| 81.8M | 5.569G | 5.6508G | 75.762M | 5.572019G | 5.647781G | Inf | 1 |
| 81.5M | 5.5693G | 5.6508G | 75.862M | 5.572019G | 5.647881G | Inf | 2 |
| 81.6M | 5.5691G | 5.6507G | 75.862M | 5.572019G | 5.647881G | Inf | 3 |
| 81.3M | 5.5693G | 5.6506G | 75.962M | 5.571919G | 5.647881G | Inf | 4 |

## 802.11ac VHT80+80
## Summary

| Mode | Max-N dB (Hz) | Max-OBW (Hz) | ITU-Code | Min-N dB (Hz) | Min-OBW (Hz) |
|---|---|---|---|---|---|
| 802.11ac VHT80+80_Nss1,(MCS0)_4TX | - | - | - | - | - |
| 5.15-5.25GHz | 81.1M | 75.862M | 75M9D1D | 80.8M | 75.762M |
| 802.11ac VHT80+80_Nss1,(MCS0)_4TX | - | - | - | - | - |
| 5.25-5.35GHz | 81.1M | 75.562M | 75M6D1D | 80.4M | 75.562M |
| 802.11ac VHT80+80_Nss1,(MCS0)_4TX | - | - | - | - | - |
| 5.47-5.725GHz | 81.15M | 75.862M | 75M9D1D | 79.95M | 75.712M |

**Max-N dB** = Maximum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
**Max-OBW** = Maximum 99% occupied bandwidth;
**Min-N dB** = Minimum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
**Min-OBW** = Minimum 99% occupied bandwidth;

## Result

| Mode | Result | Limit (Hz) | Port 1-N dB (Hz) | Port 1-OBW (Hz) | Port 2-N dB (Hz) | Port 2-OBW (Hz) | Port 3-N dB (Hz) | Port 3-OBW (Hz) | Port 4-N dB (Hz) | Port 4-OBW (Hz) |
|---|---|---|---|---|---|---|---|---|---|---|
| 802.11ac VHT80+80_Nss1,(MCS0)_4TX | - | - | - | - | - | - | - | - | - | - |
| #5210MHz,5290MHz | Pass | Inf | 81.1M | 75.762M | 80.8M | 75.862M | | | | |
| 802.11ac VHT80+80_Nss1,(MCS0)_4TX | - | - | - | - | - | - | - | - | - | - |
| 5210MHz,#5290MHz | Pass | Inf | | | | | 81.1M | 75.562M | 80.4M | 75.562M |
| 802.11ac VHT80+80_Nss1,(MCS0)_4TX | - | - | - | - | - | - | - | - | - | - |
| #5530MHz,#5610MHz | Pass | Inf | 81.15M | 75.862M | 80.55M | 75.712M | 81M | 75.712M | 79.95M | 75.712M |

**Port X-N dB** = Port **X** 6dB down bandwidth for 5.725-5.85GHz band / 26dB down bandwidth for other band
**Port X-OBW** = Port **X** 99% occupied bandwidth;

## 802.11ac VHT80+80_Nss1,(MCS0)_4TX #5210MHz,5290MHz

EBW




| 26dB(Hz) | Fl-26dB(Hz) | Fh-26dB(Hz) | OBW(Hz) | Fl-OBW(Hz) | Fh-OBW(Hz) | Limit(Hz) | Port |
|---|---|---|---|---|---|---|---|
| 81.1M | 5.1696G | 5.2507G | 75.762M | 5.172119G | 5.247881G | Inf | 1 |
| 80.8M | 5.1696G | 5.2504G | 75.862M | 5.172219G | 5.248081G | Inf | 2 |

## 802.11ac VHT80+80_Nss1,(MCS0)_4TX 5210MHz,#5290MHz

EBW




| 26dB(Hz) | Fl-26dB(Hz) | Fh-26dB(Hz) | OBW(Hz) | Fl-OBW(Hz) | Fh-OBW(Hz) | Limit(Hz) | Port |
|---|---|---|---|---|---|---|---|
| 81.1M | 5.2493G | 5.3304G | 75.562M | 5.252019G | 5.327581G | Inf | 3 |
| 80.4M | 5.2498G | 5.3302G | 75.562M | 5.252219G | 5.327781G | Inf | 4 |

## 802.11ac VHT80+80_Nss1,(MCS0)_4TX #5530MHz,#5610MHz

EBW




| 26dB(Hz) | Fl-26dB(Hz) | Fh-26dB(Hz) | OBW(Hz) | Fl-OBW(Hz) | Fh-OBW(Hz) | Limit(Hz) | Port |
|---|---|---|---|---|---|---|---|
| 81.15M | 5.4895G | 5.57065G | 75.862M | 5.492091G | 5.567954G | Inf | 1 |
| 80.55M | 5.4895G | 5.57005G | 75.712M | 5.492091G | 5.567804G | Inf | 2 |
| 81M | 5.5696G | 5.6506G | 75.712M | 5.572151G | 5.647864G | Inf | 3 |
| 79.95M | 5.57005G | 5.65G | 75.712M | 5.572151G | 5.647864G | Inf | 4 |

## 802.11a, 802.11ac VHT20, 802.11ac VHT40, 802.11ac VHT80 Summary

| Mode | Total Power (dBm) | Total Power (W) |
|---|---|---|
| 802.11a_(6Mbps)_4TX | - | - |
| 5.25-5.35GHz | 21.76 | 0.14997 |
| 5.47-5.725GHz | 21.82 | 0.15205 |
| 802.11ac VHT20_Nss1,(MCS0)_4TX | - | - |
| 5.25-5.35GHz | 21.98 | 0.15776 |
| 5.47-5.725GHz | 21.99 | 0.15812 |
| 802.11ac VHT40_Nss1,(MCS0)_4TX | - | - |
| 5.25-5.35GHz | 23.79 | 0.23933 |
| 5.47-5.725GHz | 23.87 | 0.24378 |
| 802.11ac VHT80_Nss1,(MCS0)_4TX | - | - |
| 5.25-5.35GHz | 23.78 | 0.23878 |
| 5.47-5.725GHz | 23.77 | 0.23823 |
| 802.11ac VHT20-BF_Nss1,(MCS0)_4TX | - | - |
| 5.25-5.35GHz | 21.82 | 0.15205 |
| 5.47-5.725GHz | 21.95 | 0.15668 |
| 802.11ac VHT40-BF_Nss1,(MCS0)_4TX | - | - |
| 5.25-5.35GHz | 22.12 | 0.16293 |
| 5.47-5.725GHz | 22.14 | 0.16368 |
| 802.11ac VHT80-BF_Nss1,(MCS0)_4TX | - | - |
| 5.25-5.35GHz | 22.06 | 0.16069 |
| 5.47-5.725GHz | 22.02 | 0.15922 |

## Result

| Mode | Result | DG | Port 1 | Port 2 | Port 3 | Port 4 | Total Power | Power Limit |
|---|---|---|---|---|---|---|---|---|
| | | (dBi) | (dBm) | (dBm) | (dBm) | (dBm) | (dBm) | (dBm) |
| 802.11a_(6Mbps)_4TX | - | - | - | - | - | - | - | - |
| 5260MHz | Pass | 1.80 | 14.69 | 15.05 | 15.03 | 17.07 | 21.59 | 23.98 |
| 5300MHz | Pass | 1.80 | 14.86 | 15.36 | 15.10 | 17.22 | 21.76 | 23.98 |
| 5320MHz | Pass | 1.80 | 14.40 | 14.92 | 14.51 | 16.83 | 21.30 | 23.98 |
| 5500MHz | Pass | 1.80 | 16.27 | 16.49 | 15.48 | 14.51 | 21.77 | 23.98 |
| 5580MHz | Pass | 1.80 | 16.48 | 16.72 | 15.19 | 14.41 | 21.82 | 23.98 |
| 5700MHz | Pass | 1.80 | 16.79 | 15.21 | 15.75 | 14.16 | 21.60 | 23.98 |
| 802.11ac VHT20_Nss1,(MCS0)_4TX | - | - | - | - | - | - | - | - |
| 5260MHz | Pass | 1.80 | 14.88 | 15.10 | 15.35 | 17.45 | 21.85 | 23.98 |
| 5300MHz | Pass | 1.80 | 15.11 | 15.87 | 15.28 | 17.25 | 21.98 | 23.98 |
| 5320MHz | Pass | 1.80 | 15.24 | 15.47 | 15.00 | 17.16 | 21.83 | 23.98 |
| 5500MHz | Pass | 1.80 | 16.29 | 16.64 | 15.49 | 14.13 | 21.76 | 23.98 |
| 5580MHz | Pass | 1.80 | 16.65 | 16.86 | 15.37 | 14.18 | 21.91 | 23.98 |
| 5700MHz | Pass | 1.80 | 17.14 | 15.83 | 16.02 | 14.51 | 21.99 | 23.98 |
| 802.11ac VHT40_Nss1,(MCS0)_4TX | - | - | - | - | - | - | - | - |
| 5270MHz | Pass | 1.80 | 17.13 | 17.04 | 17.50 | 19.07 | 23.79 | 23.98 |
| 5310MHz | Pass | 1.80 | 16.66 | 16.85 | 17.02 | 18.76 | 23.43 | 23.98 |
| 5510MHz | Pass | 1.80 | 18.87 | 17.76 | 18.43 | 15.08 | 23.78 | 23.98 |
| 5550MHz | Pass | 1.80 | 19.21 | 17.49 | 18.25 | 14.94 | 23.76 | 23.98 |
| 5670MHz | Pass | 1.80 | 19.00 | 17.43 | 18.38 | 16.05 | 23.87 | 23.98 |
| 802.11ac VHT80_Nss1,(MCS0)_4TX | - | - | - | - | - | - | - | - |
| 5290MHz | Pass | 1.80 | 16.99 | 17.50 | 17.69 | 18.67 | 23.78 | 23.98 |
| 5530MHz | Pass | 1.80 | 15.81 | 15.27 | 15.05 | 12.96 | 20.91 | 23.98 |
| 5610MHz | Pass | 1.80 | 18.62 | 18.12 | 17.95 | 15.85 | 23.77 | 23.98 |
| 802.11ac VHT20-BF_Nss1,(MCS0)_4TX | - | - | - | - | - | - | - | - |
| 5260MHz | Pass | 7.82 | 15.32 | 15.25 | 15.07 | 17.05 | 21.77 | 22.16 |
| 5300MHz | Pass | 7.82 | 15.22 | 15.30 | 15.35 | 17.03 | 21.82 | 22.16 |
| 5320MHz | Pass | 7.82 | 15.28 | 15.40 | 14.88 | 17.12 | 21.78 | 22.16 |
| 5500MHz | Pass | 7.82 | 16.39 | 16.51 | 15.69 | 14.50 | 21.86 | 22.16 |
| 5580MHz | Pass | 7.82 | 16.65 | 16.90 | 15.31 | 14.40 | 21.95 | 22.16 |
| 5700MHz | Pass | 7.82 | 17.24 | 15.52 | 16.03 | 14.47 | 21.95 | 22.16 |
| 802.11ac VHT40-BF_Nss1,(MCS0)_4TX | - | - | - | - | - | - | - | - |
| 5270MHz | Pass | 7.82 | 15.40 | 15.01 | 15.77 | 17.35 | 22.00 | 22.16 |
| 5310MHz | Pass | 7.82 | 15.45 | 15.79 | 15.69 | 17.22 | 22.12 | 22.16 |
| 5510MHz | Pass | 7.82 | 17.44 | 16.14 | 16.17 | 13.40 | 22.04 | 22.16 |
| 5550MHz | Pass | 7.82 | 17.48 | 16.12 | 16.57 | 13.29 | 22.14 | 22.16 |
| 5670MHz | Pass | 7.82 | 17.28 | 15.52 | 16.39 | 14.12 | 22.00 | 22.16 |
| 802.11ac VHT80-BF_Nss1,(MCS0)_4TX | - | - | - | - | - | - | - | - |
| 5290MHz | Pass | 7.82 | 15.39 | 15.67 | 16.04 | 16.89 | 22.06 | 22.16 |
| 5530MHz | Pass | 7.82 | 16.72 | 16.18 | 16.53 | 13.90 | 21.98 | 22.16 |
| 5610MHz | Pass | 7.82 | 16.85 | 16.33 | 16.13 | 14.32 | 22.02 | 22.16 |

**DG** = Directional Gain; **Port X** = Port X output power

## 802.11ac VHT80+80
## Summary

| Mode | Total Power (dBm) | Total Power (W) |
|---|---|---|
| 802.11ac VHT80+80_Nss1,(MCS0)_4TX | - | - |
| 5.15-5.25GHz | 18.33 | 0.06808 |
| 802.11ac VHT80+80_Nss1,(MCS0)_4TX | - | - |
| 5.25-5.35GHz | 18.15 | 0.06531 |
| 802.11ac VHT80+80_Nss1,(MCS0)_4TX | - | - |
| 5.47-5.725GHz | 21.83 | 0.15241 |

## Result

| Mode | Result | DG | Port 1 | Port 2 | Port 3 | Port 4 | Total Power | Power Limit |
|---|---|---|---|---|---|---|---|---|
| | | (dBi) | (dBm) | (dBm) | (dBm) | (dBm) | (dBm) | (dBm) |
| 802.11ac VHT80+80_Nss1,(MCS0)_4TX | - | - | - | - | - | - | - | - |
| #5210MHz,5290MHz | Pass | 1.80 | 15.44 | 15.20 | | | 18.33 | 30.00 |
| 802.11ac VHT80+80_Nss1,(MCS0)_4TX | - | - | - | - | - | - | - | - |
| 5210MHz,#5290MHz | Pass | 1.80 | | | 15.25 | 15.03 | 18.15 | 23.98 |
| 802.11ac VHT80+80_Nss1,(MCS0)_4TX | - | - | - | - | - | - | - | - |
| #5530MHz,#5610MHz | Pass | 1.80 | 16.02 | 16.08 | 15.57 | 15.54 | 21.83 | 23.98 |

**DG** = Directional Gain; **Port X** = Port X output power

## 802.11a, 802.11ac VHT20, 802.11ac VHT40, 802.11ac VHT80 Summary

| Mode | PD (dBm/RBW) |
|---|---|
| 802.11a_(6Mbps)_4TX | - |
| 5.25-5.35GHz | 9.16 |
| 5.47-5.725GHz | 9.16 |
| 802.11ac VHT20_Nss1,(MCS0)_4TX | - |
| 5.25-5.35GHz | 9.14 |
| 5.47-5.725GHz | 9.13 |
| 802.11ac VHT40_Nss1,(MCS0)_4TX | - |
| 5.25-5.35GHz | 8.25 |
| 5.47-5.725GHz | 8.23 |
| 802.11ac VHT80_Nss1,(MCS0)_4TX | - |
| 5.25-5.35GHz | 5.47 |
| 5.47-5.725GHz | 5.27 |
| 802.11ac VHT20-BF_Nss1,(MCS0)_4TX | - |
| 5.25-5.35GHz | 9.13 |
| 5.47-5.725GHz | 9.15 |
| 802.11ac VHT40-BF_Nss1,(MCS0)_4TX | - |
| 5.25-5.35GHz | 6.49 |
| 5.47-5.725GHz | 6.54 |
| 802.11ac VHT80-BF_Nss1,(MCS0)_4TX | - |
| 5.25-5.35GHz | 3.34 |
| 5.47-5.725GHz | 3.15 |

**RBW** = 500kHz for 5.725-5.85GHz band / 1MHz for other band;

## Result

| Mode | Result | DG (dBi) | Port 1 (dBm/RBW) | Port 2 (dBm/RBW) | Port 3 (dBm/RBW) | Port 4 (dBm/RBW) | PD (dBm/RBW) | PD Limit (dBm/RBW) |
|---|---|---|---|---|---|---|---|---|
| 802.11a_(6Mbps)_4TX | - | - | - | - | - | - | - | - |
| 5260MHz | Pass | 7.82 | 2.16 | 2.47 | 2.40 | 4.63 | 8.99 | 9.18 |
| 5300MHz | Pass | 7.82 | 2.27 | 3.04 | 2.78 | 4.56 | 9.16 | 9.18 |
| 5320MHz | Pass | 7.82 | 1.89 | 2.56 | 2.45 | 4.50 | 8.93 | 9.18 |
| 5500MHz | Pass | 7.82 | 3.78 | 3.96 | 2.90 | 1.93 | 9.16 | 9.18 |
| 5580MHz | Pass | 7.82 | 3.75 | 4.03 | 2.59 | 1.60 | 9.03 | 9.18 |
| 5700MHz | Pass | 7.82 | 4.31 | 2.90 | 3.22 | 1.81 | 9.08 | 9.18 |
| 802.11ac VHT20_Nss1,(MCS0)_4TX | - | - | - | - | - | - | - | - |
| 5260MHz | Pass | 7.82 | 2.26 | 2.42 | 2.54 | 4.55 | 9.00 | 9.18 |
| 5300MHz | Pass | 7.82 | 2.31 | 2.89 | 2.72 | 4.57 | 9.14 | 9.18 |
| 5320MHz | Pass | 7.82 | 2.43 | 3.04 | 2.42 | 4.63 | 9.14 | 9.18 |
| 5500MHz | Pass | 7.82 | 3.56 | 3.99 | 2.82 | 1.69 | 9.05 | 9.18 |
| 5580MHz | Pass | 7.82 | 3.90 | 4.20 | 2.65 | 1.68 | 9.13 | 9.18 |
| 5700MHz | Pass | 7.82 | 4.30 | 2.80 | 3.27 | 1.63 | 9.04 | 9.18 |
| 802.11ac VHT40_Nss1,(MCS0)_4TX | - | - | - | - | - | - | - | - |
| 5270MHz | Pass | 7.82 | 1.11 | 1.68 | 2.37 | 3.69 | 8.25 | 9.18 |
| 5310MHz | Pass | 7.82 | 1.13 | 1.56 | 1.77 | 3.36 | 8.01 | 9.18 |
| 5510MHz | Pass | 7.82 | 3.51 | 2.26 | 2.95 | -0.64 | 8.23 | 9.18 |
| 5550MHz | Pass | 7.82 | 3.61 | 1.96 | 2.77 | -0.68 | 8.11 | 9.18 |
| 5670MHz | Pass | 7.82 | 3.59 | 1.98 | 2.83 | 0.38 | 8.22 | 9.18 |
| 802.11ac VHT80_Nss1,(MCS0)_4TX | - | - | - | - | - | - | - | - |
| 5290MHz | Pass | 7.82 | -0.98 | -0.44 | -0.51 | 0.43 | 5.47 | 9.18 |
| 5530MHz | Pass | 7.82 | -2.29 | -3.04 | -2.69 | -5.49 | 2.63 | 9.18 |
| 5610MHz | Pass | 7.82 | 0.16 | -0.15 | -0.59 | -2.68 | 5.27 | 9.18 |
| 802.11ac VHT20-BF_Nss1,(MCS0)_4TX | - | - | - | - | - | - | - | - |
| 5260MHz | Pass | 7.82 | 2.49 | 2.66 | 2.39 | 4.48 | 9.04 | 9.18 |
| 5300MHz | Pass | 7.82 | 2.46 | 2.77 | 2.59 | 4.26 | 8.99 | 9.18 |
| 5320MHz | Pass | 7.82 | 2.68 | 2.93 | 2.37 | 4.64 | 9.13 | 9.18 |
| 5500MHz | Pass | 7.82 | 3.73 | 3.96 | 2.92 | 1.92 | 9.15 | 9.18 |
| 5580MHz | Pass | 7.82 | 3.94 | 4.23 | 2.62 | 1.65 | 9.12 | 9.18 |
| 5700MHz | Pass | 7.82 | 4.29 | 2.87 | 3.41 | 1.57 | 9.09 | 9.18 |
| 802.11ac VHT40-BF_Nss1,(MCS0)_4TX | - | - | - | - | - | - | - | - |
| 5270MHz | Pass | 7.82 | 0.00 | -0.47 | 0.18 | 1.69 | 6.36 | 9.18 |
| 5310MHz | Pass | 7.82 | -0.28 | 0.19 | 0.37 | 1.74 | 6.49 | 9.18 |
| 5510MHz | Pass | 7.82 | 1.70 | 0.57 | 1.27 | -2.37 | 6.54 | 9.18 |
| 5550MHz | Pass | 7.82 | 1.78 | 0.31 | 1.05 | -2.34 | 6.39 | 9.18 |
| 5670MHz | Pass | 7.82 | 1.51 | -0.05 | 0.75 | -1.75 | 6.18 | 9.18 |
| 802.11ac VHT80-BF_Nss1,(MCS0)_4TX | - | - | - | - | - | - | - | - |
| 5290MHz | Pass | 7.82 | -3.11 | -2.69 | -2.43 | -1.82 | 3.34 | 9.18 |
| 5530MHz | Pass | 7.82 | -1.91 | -2.51 | -1.80 | -4.85 | 3.15 | 9.18 |
| 5610MHz | Pass | 7.82 | -2.13 | -2.35 | -2.86 | -4.68 | 3.07 | 9.18 |

**DG** = Directional Gain; **RBW** = 500kHz for 5.725-5.85GHz band / 1MHz for other band;
**PD** = trace bin-by-bin of each transmits port summing can be performed maximum power density; **Port X** = Port X power density;

## 802.11a_(6Mbps)_4TX PSD

### 5260MHz




| Sum | PD | Port 1 | Port 2 | Port 3 | Port 4 |
|---|---|---|---|---|---|
| (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) |
| 8.99 | 8.99 | 2.16 | 2.47 | 2.40 | 4.63 |

## 802.11a_(6Mbps)_4TX PSD

### 5300MHz




| Sum | PD | Port 1 | Port 2 | Port 3 | Port 4 |
|---|---|---|---|---|---|
| (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) |
| 9.16 | 9.16 | 2.27 | 3.04 | 2.78 | 4.56 |

## 802.11a_(6Mbps)_4TX PSD

### 5320MHz




| Sum | PD | Port 1 | Port 2 | Port 3 | Port 4 |
|---|---|---|---|---|---|
| (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) |
| 8.93 | 8.93 | 1.89 | 2.56 | 2.45 | 4.50 |

## 802.11a_(6Mbps)_4TX PSD

### 5500MHz




| Sum | PD | Port 1 | Port 2 | Port 3 | Port 4 |
|---|---|---|---|---|---|
| (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) |
| 9.16 | 9.16 | 3.78 | 3.96 | 2.90 | 1.93 |

## 802.11a_(6Mbps)_4TX PSD

### 5580MHz




| Sum | PD | Port 1 | Port 2 | Port 3 | Port 4 |
|---|---|---|---|---|---|
| (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) |
| 9.03 | 9.03 | 3.75 | 4.03 | 2.59 | 1.60 |

## 802.11a_(6Mbps)_4TX PSD

### 5700MHz




| Sum | PD | Port 1 | Port 2 | Port 3 | Port 4 |
|---|---|---|---|---|---|
| (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) |
| 9.08 | 9.08 | 4.31 | 2.90 | 3.22 | 1.81 |

## 802.11ac VHT20_Nss1,(MCS0)_4TX PSD

### 5260MHz




| Sum | PD | Port 1 | Port 2 | Port 3 | Port 4 |
|---|---|---|---|---|---|
| (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) |
| 9.00 | 9.00 | 2.26 | 2.42 | 2.54 | 4.55 |

## 802.11ac VHT20_Nss1,(MCS0)_4TX PSD

### 5300MHz




| Sum | PD | Port 1 | Port 2 | Port 3 | Port 4 |
|---|---|---|---|---|---|
| (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) |
| 9.14 | 9.14 | 2.31 | 2.89 | 2.72 | 4.57 |

## 802.11ac VHT20_Nss1,(MCS0)_4TX PSD

### 5320MHz




| Sum | PD | Port 1 | Port 2 | Port 3 | Port 4 |
|---|---|---|---|---|---|
| (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) |
| 9.14 | 9.14 | 2.43 | 3.04 | 2.42 | 4.63 |

## 802.11ac VHT20_Nss1,(MCS0)_4TX PSD

### 5500MHz




| Sum | PD | Port 1 | Port 2 | Port 3 | Port 4 |
|---|---|---|---|---|---|
| (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) |
| 9.05 | 9.05 | 3.56 | 3.99 | 2.82 | 1.69 |

## 802.11ac VHT20_Nss1,(MCS0)_4TX PSD

### 5580MHz




| Sum | PD | Port 1 | Port 2 | Port 3 | Port 4 |
|---|---|---|---|---|---|
| (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) |
| 9.13 | 9.13 | 3.90 | 4.20 | 2.65 | 1.68 |

## 802.11ac VHT20_Nss1,(MCS0)_4TX PSD

### 5700MHz




| Sum | PD | Port 1 | Port 2 | Port 3 | Port 4 |
|---|---|---|---|---|---|
| (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) |
| 9.04 | 9.04 | 4.30 | 2.80 | 3.27 | 1.63 |

## 802.11ac VHT40_Nss1,(MCS0)_4TX PSD

### 5270MHz




| Sum | PD | Port 1 | Port 2 | Port 3 | Port 4 |
|---|---|---|---|---|---|
| (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) |
| 8.25 | 8.25 | 1.11 | 1.68 | 2.37 | 3.69 |

## 802.11ac VHT40_Nss1,(MCS0)_4TX PSD

### 5310MHz




| Sum | PD | Port 1 | Port 2 | Port 3 | Port 4 |
|---|---|---|---|---|---|
| (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) |
| 8.01 | 8.01 | 1.13 | 1.56 | 1.77 | 3.36 |

## 802.11ac VHT40_Nss1,(MCS0)_4TX PSD

### 5510MHz




| Sum | PD | Port 1 | Port 2 | Port 3 | Port 4 |
|---|---|---|---|---|---|
| (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) |
| 8.23 | 8.23 | 3.51 | 2.26 | 2.95 | -0.64 |

## 802.11ac VHT40_Nss1,(MCS0)_4TX PSD

### 5550MHz




| Sum | PD | Port 1 | Port 2 | Port 3 | Port 4 |
|---|---|---|---|---|---|
| (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) |
| 8.11 | 8.11 | 3.61 | 1.96 | 2.77 | -0.68 |

## 802.11ac VHT40_Nss1,(MCS0)_4TX PSD

### 5670MHz




| Sum | PD | Port 1 | Port 2 | Port 3 | Port 4 |
|---|---|---|---|---|---|
| (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) |
| 8.22 | 8.22 | 3.59 | 1.98 | 2.83 | 0.38 |

## 802.11ac VHT80_Nss1,(MCS0)_4TX PSD

### 5290MHz




| Sum | PD | Port 1 | Port 2 | Port 3 | Port 4 |
|---|---|---|---|---|---|
| (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) |
| 5.47 | 5.47 | -0.98 | -0.44 | -0.51 | 0.43 |

## 802.11ac VHT80_Nss1,(MCS0)_4TX PSD

### 5530MHz




| Sum | PD | Port 1 | Port 2 | Port 3 | Port 4 |
|---|---|---|---|---|---|
| (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) |
| 2.63 | 2.63 | -2.29 | -3.04 | -2.69 | -5.49 |

## 802.11ac VHT80_Nss1,(MCS0)_4TX PSD

### 5610MHz




| Sum | PD | Port 1 | Port 2 | Port 3 | Port 4 |
|---|---|---|---|---|---|
| (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) |
| 5.27 | 5.27 | 0.16 | -0.15 | -0.59 | -2.68 |

## 802.11ac VHT20-BF_Nss1,(MCS0)_4TX PSD

### 5260MHz




| Sum | PD | Port 1 | Port 2 | Port 3 | Port 4 |
|---|---|---|---|---|---|
| (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) |
| 9.04 | 9.04 | 2.49 | 2.66 | 2.39 | 4.48 |

## 802.11ac VHT20-BF_Nss1,(MCS0)_4TX PSD

### 5300MHz




| Sum | PD | Port 1 | Port 2 | Port 3 | Port 4 |
|---|---|---|---|---|---|
| (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) |
| 8.99 | 8.99 | 2.46 | 2.77 | 2.59 | 4.26 |

## 802.11ac VHT20-BF_Nss1,(MCS0)_4TX PSD

### 5320MHz




| Sum | PD | Port 1 | Port 2 | Port 3 | Port 4 |
|---|---|---|---|---|---|
| (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) |
| 9.13 | 9.13 | 2.68 | 2.93 | 2.37 | 4.64 |

## 802.11ac VHT20-BF_Nss1,(MCS0)_4TX PSD

### 5500MHz




| Sum | PD | Port 1 | Port 2 | Port 3 | Port 4 |
|---|---|---|---|---|---|
| (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) |
| 9.15 | 9.15 | 3.73 | 3.96 | 2.92 | 1.92 |

## 802.11ac VHT20-BF_Nss1,(MCS0)_4TX PSD

### 5580MHz




| Sum | PD | Port 1 | Port 2 | Port 3 | Port 4 |
|---|---|---|---|---|---|
| (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) |
| 9.12 | 9.12 | 3.94 | 4.23 | 2.62 | 1.65 |

## 802.11ac VHT20-BF_Nss1,(MCS0)_4TX PSD

### 5700MHz




| Sum | PD | Port 1 | Port 2 | Port 3 | Port 4 |
|---|---|---|---|---|---|
| (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) |
| 9.09 | 9.09 | 4.29 | 2.87 | 3.41 | 1.57 |

## 802.11ac VHT40-BF_Nss1,(MCS0)_4TX PSD

### 5270MHz




| Sum | PD | Port 1 | Port 2 | Port 3 | Port 4 |
|---|---|---|---|---|---|
| (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) |
| 6.36 | 6.36 | 0.00 | -0.47 | 0.18 | 1.69 |

## 802.11ac VHT40-BF_Nss1,(MCS0)_4TX PSD

### 5310MHz




| Sum | PD | Port 1 | Port 2 | Port 3 | Port 4 |
|---|---|---|---|---|---|
| (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) |
| 6.49 | 6.49 | -0.28 | 0.19 | 0.37 | 1.74 |

## 802.11ac VHT40-BF_Nss1,(MCS0)_4TX PSD

### 5510MHz




| Sum | PD | Port 1 | Port 2 | Port 3 | Port 4 |
|---|---|---|---|---|---|
| (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) |
| 6.54 | 6.54 | 1.70 | 0.57 | 1.27 | -2.37 |

## 802.11ac VHT40-BF_Nss1,(MCS0)_4TX PSD

### 5550MHz




| Sum | PD | Port 1 | Port 2 | Port 3 | Port 4 |
|---|---|---|---|---|---|
| (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) |
| 6.39 | 6.39 | 1.78 | 0.31 | 1.05 | -2.34 |

## 802.11ac VHT40-BF_Nss1,(MCS0)_4TX PSD

### 5670MHz




| Sum | PD | Port 1 | Port 2 | Port 3 | Port 4 |
|---|---|---|---|---|---|
| (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) |
| 6.18 | 6.18 | 1.51 | -0.05 | 0.75 | -1.75 |

## 802.11ac VHT80-BF_Nss1,(MCS0)_4TX PSD

### 5290MHz




| Sum | PD | Port 1 | Port 2 | Port 3 | Port 4 |
|---|---|---|---|---|---|
| (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) |
| 3.34 | 3.34 | -3.11 | -2.69 | -2.43 | -1.82 |

## 802.11ac VHT80-BF_Nss1,(MCS0)_4TX PSD

### 5530MHz




| Sum | PD | Port 1 | Port 2 | Port 3 | Port 4 |
|---|---|---|---|---|---|
| (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) |
| 3.15 | 3.15 | -1.91 | -2.51 | -1.80 | -4.85 |

**802.11ac VHT80-BF_Nss1,(MCS0)_4TX** **PSD**

**5610MHz**




| Sum | PD | Port 1 | Port 2 | Port 3 | Port 4 |
|---|---|---|---|---|---|
| (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) |
| 3.07 | 3.07 | -2.13 | -2.35 | -2.86 | -4.68 |

## 802.11ac VHT80+80
## Summary

| Mode | PD (dBm/RBW) |
|---|---|
| 802.11ac VHT80+80_Nss1,(MCS0)_4TX | - |
| 5.15-5.25GHz | -0.27 |
| 802.11ac VHT80+80_Nss1,(MCS0)_4TX | - |
| 5.25-5.35GHz | -0.32 |
| 802.11ac VHT80+80_Nss1,(MCS0)_4TX | - |
| 5.47-5.725GHz | 0.70 |

**RBW** = 500kHz for 5.725-5.85GHz band / 1MHz for other band;

## Result

| Mode | Result | DG (dBi) | Port 1 (dBm/RBW) | Port 2 (dBm/RBW) | Port 3 (dBm/RBW) | Port 4 (dBm/RBW) | PD (dBm/RBW) | PD Limit (dBm/RBW) |
|---|---|---|---|---|---|---|---|---|
| 802.11ac VHT80+80_Nss1,(MCS0)_4TX | - | - | - | - | - | - | - | - |
| #5210MHz,5290MHz | Pass | 4.81 | -3.27 | -3.28 | | | -0.27 | 17.00 |
| 802.11ac VHT80+80_Nss1,(MCS0)_4TX | - | - | - | - | - | - | - | - |
| 5210MHz,#5290MHz | Pass | 4.81 | | | -3.53 | -3.04 | -0.32 | 11.00 |
| 802.11ac VHT80+80_Nss1,(MCS0)_4TX | - | - | - | - | - | - | - | - |
| #5530MHz,#5610MHz | Pass | 7.82 | -2.11 | -2.38 | -2.41 | -3.06 | 0.70 | 9.18 |

**DG** = Directional Gain; **RBW** = 500kHz for 5.725-5.85GHz band / 1MHz for other band;
**PD** = trace bin-by-bin of each transmits port summing can be performed maximum power density; **Port X** = Port X power density;

## 802.11ac VHT80+80_Nss1,(MCS0)_4TX PSD

### #5210MHz,5290MHz




| Sum | PD | Port 1 | Port 2 |
|---|---|---|---|
| (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) |
| -0.27 | -0.27 | -3.27 | -3.28 |

## 802.11ac VHT80+80_Nss1,(MCS0)_4TX PSD

### 5210MHz,#5290MHz




| Sum | PD | Port 1 | Port 2 | Port 3 | Port 4 |
|---|---|---|---|---|---|
| (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) |
| -0.32 | -0.32 | | | -3.53 | -3.04 |

## 802.11ac VHT80+80_Nss1,(MCS0)_4TX PSD

### #5530MHz,#5610MHz




| Sum | PD | Port 1 | Port 2 | Port 3 | Port 4 |
|---|---|---|---|---|---|
| (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) | (dBm/RBW) |
| 0.70 | 0.70 | -2.11 | -2.38 | -2.41 | -3.06 |

| RSE below 1GHz Result | | | |
|---|---|---|---|
| **Operating Mode** | 1 | **Polarization** | Horizontal |
| **Operating Function** | Normal Link | | |




| | Freq | Level | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | A/Pos | T/Pos | Remark | Pol/Phase |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | | |
| 1 | 34.85 | 36.19 | 40.00 | -3.81 | 39.50 | 2.16 | 23.11 | 28.58 | 125 | 36 | QP | HORIZONTAL |
| 2 | 157.07 | 31.38 | 43.50 | -12.12 | 41.16 | 2.39 | 16.02 | 28.19 | 100 | 0 | Peak | HORIZONTAL |
| 3 | 205.57 | 31.24 | 43.50 | -12.26 | 41.78 | 2.52 | 14.98 | 28.04 | 100 | 0 | Peak | HORIZONTAL |
| 4 | 746.83 | 37.78 | 46.00 | -8.22 | 37.07 | 4.14 | 25.76 | 29.19 | 100 | 0 | Peak | HORIZONTAL |
| 5 | 889.42 | 38.09 | 46.00 | -7.91 | 35.98 | 4.52 | 26.43 | 28.84 | 100 | 0 | Peak | HORIZONTAL |
| 6 | 894.27 | 39.67 | 46.00 | -6.33 | 37.54 | 4.53 | 26.43 | 28.83 | 100 | 0 | Peak | HORIZONTAL |

Note 1: “>20dB” means emission levels that exceed the level of 20 dB below the applicable limit.
Note 2: “N/F” means Nothing Found emissions (No emissions were detected.)

| RSE below 1GHz Result | | | |
|---|---|---|---|
| **Operating Mode** | 1 | **Polarization** | Vertical |
| **Operating Function** | Normal Link | | |




| | Freq | Level | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | A/Pos | T/Pos | Remark | Pol/Phase |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | | |
| 1 | 30.97 | 36.43 | 40.00 | -3.57 | 38.90 | 2.11 | 24.00 | 28.58 | 150 | 117 | QP | VERTICAL |
| 2 | 33.88 | 35.99 | 40.00 | -4.01 | 39.10 | 2.15 | 23.32 | 28.58 | 125 | 99 | QP | VERTICAL |
| 3 | 46.49 | 34.66 | 40.00 | -5.34 | 45.10 | 2.15 | 15.98 | 28.57 | 156 | 301 | QP | VERTICAL |
| 4 | 72.68 | 32.16 | 40.00 | -7.84 | 46.07 | 2.19 | 12.39 | 28.49 | 300 | 360 | Peak | VERTICAL |
| 5 | 144.46 | 31.75 | 43.50 | -11.75 | 40.87 | 2.32 | 16.79 | 28.23 | 300 | 360 | Peak | VERTICAL |
| 6 | 724.52 | 39.56 | 46.00 | -6.44 | 39.39 | 4.07 | 25.36 | 29.26 | 300 | 360 | Peak | VERTICAL |

Note 1: “>20dB” means emission levels that exceed the level of 20 dB below the applicable limit.
Note 2: “N/F” means Nothing Found emissions (No emissions were detected.)

## 802.11a, 802.11ac VHT20, 802.11ac VHT40, 802.11ac VHT80
## Summary

| Mode | Result | Type | Freq (Hz) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Factor (dB) | Dist (m) | Pol. (H/V) | Azimuth (°) | Height (m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 802.11ac VHT20-BF_Nss1,(MCS0)_4TX | - | - | - | - | - | - | - | - | - | - | - | - |
| 5.25-5.35GHz | Pass | AV | 5.350005G | 53.98 | 54.00 | -0.02 | 5.03 | 3 | V | 1 | 1.50 | - |

## 802.11a_(6Mbps)_4TX

## 5260MHz_TX




20170606
EUT Z_4TX
Setting 110
04-M-01-10
FSP(100142)
Radio 1

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 5.149995G | 51.21 | 54.00 | -2.79 | 4.64 | 3 | V | 21 | 2.38 | - |
| AV | 5.256G | 117.51 | Inf | -Inf | 4.91 | 3 | V | 21 | 2.38 | - |
| AV | 5.350005G | 53.47 | 54.00 | -0.53 | 5.03 | 3 | V | 21 | 2.38 | - |
| PK | 5.145G | 65.85 | 74.00 | -8.15 | 4.63 | 3 | V | 21 | 2.38 | - |
| PK | 5.256G | 128.86 | Inf | -Inf | 4.91 | 3 | V | 21 | 2.38 | - |
| PK | 5.350005G | 69.50 | 74.00 | -4.50 | 5.03 | 3 | V | 21 | 2.38 | - |
| PK | 5.507G | 60.41 | 68.20 | -7.79 | 5.60 | 3 | V | 21 | 2.38 | - |

## 802.11a_(6Mbps)_4TX

## 5260MHz_TX




20170606
EUT Z_4TX
Setting 110
04-M-01
FSP(100142)
Radio 1

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 15.78266G | 47.23 | 54.00 | -6.77 | 17.04 | 3 | V | 279 | 2.02 | - |
| PK | 15.78304G | 61.28 | 74.00 | -12.72 | 17.04 | 3 | V | 279 | 2.02 | - |

## 802.11a_(6Mbps)_4TX

## 5260MHz_TX




20170606
EUT Z_4TX
Setting 110
04-M-01
FSP(100142)
Radio 1

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 15.78046G | 47.05 | 54.00 | -6.95 | 17.04 | 3 | H | 96 | 1.92 | - |
| PK | 15.78042G | 60.56 | 74.00 | -13.44 | 17.04 | 3 | H | 96 | 1.92 | - |

## 802.11a_(6Mbps)_4TX

## 5300MHz_TX




20170606
EUT Z_4TX
Setting 96
04-M-01-10
FSP(100142)
Radio 1

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 5.144G | 48.49 | 54.00 | -5.51 | 4.62 | 3 | V | 143 | 2.37 | - |
| AV | 5.2952G | 114.95 | Inf | -Inf | 4.96 | 3 | V | 143 | 2.37 | - |
| AV | 5.350005G | 53.55 | 54.00 | -0.45 | 5.03 | 3 | V | 143 | 2.37 | - |
| PK | 5.1432G | 60.57 | 74.00 | -13.43 | 4.62 | 3 | V | 143 | 2.37 | - |
| PK | 5.2952G | 124.77 | Inf | -Inf | 4.96 | 3 | V | 143 | 2.37 | - |
| PK | 5.3512G | 69.00 | 74.00 | -5.00 | 5.03 | 3 | V | 143 | 2.37 | - |
| PK | 5.484G | 59.95 | 68.20 | -8.25 | 5.48 | 3 | V | 143 | 2.37 | - |

## 802.11a_(6Mbps)_4TX

## 5300MHz_TX




20170606
EUT Z_4TX
Setting 96
04-M-01-10
FSP(100142)
Radio 1

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 10.60364G | 44.28 | 54.00 | -9.72 | 14.92 | 3 | V | 94 | 1.60 | - |
| AV | 15.90408G | 47.15 | 54.00 | -6.85 | 16.95 | 3 | V | 118 | 1.63 | - |
| PK | 10.60432G | 57.84 | 74.00 | -16.16 | 14.92 | 3 | V | 94 | 1.60 | - |
| PK | 15.89656G | 61.14 | 74.00 | -12.86 | 16.95 | 3 | V | 118 | 1.63 | - |

## 802.11a_(6Mbps)_4TX

## 5300MHz_TX




20170606
EUT Z_4TX
Setting 96
04-M-01-10
FSP(100142)
Radio 1

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 10.60986G | 44.21 | 54.00 | -9.79 | 14.93 | 3 | H | 348 | 1.28 | - |
| AV | 15.90338G | 47.22 | 54.00 | -6.78 | 16.95 | 3 | H | 75 | 1.08 | - |
| PK | 10.601G | 58.04 | 74.00 | -15.96 | 14.91 | 3 | H | 348 | 1.28 | - |
| PK | 15.90498G | 61.04 | 74.00 | -12.96 | 16.95 | 3 | H | 75 | 1.08 | - |

## 802.11a_(6Mbps)_4TX

## 5320MHz_TX




20170606
EUT Z_4TX
Setting 84
04-M-01-10
FSP(100142)
Radio 1

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 5.1248G | 46.31 | 54.00 | -7.69 | 4.55 | 3 | V | 62 | 2.28 | - |
| AV | 5.316G | 110.63 | Inf | -Inf | 4.99 | 3 | V | 62 | 2.28 | - |
| AV | 5.3512G | 53.89 | 54.00 | -0.11 | 5.03 | 3 | V | 62 | 2.28 | - |
| PK | 5.1208G | 60.10 | 74.00 | -13.90 | 4.54 | 3 | V | 62 | 2.28 | - |
| PK | 5.316G | 121.82 | Inf | -Inf | 4.99 | 3 | V | 62 | 2.28 | - |
| PK | 5.352G | 71.68 | 74.00 | -2.32 | 5.03 | 3 | V | 62 | 2.28 | - |
| PK | 5.4944G | 59.92 | 68.20 | -8.28 | 5.53 | 3 | V | 62 | 2.28 | - |

## 802.11a_(6Mbps)_4TX

## 5320MHz_TX




20170606
EUT Z_4TX
Setting 84
04-M-01
FSP(100142)
Radio 1

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 10.63804G | 43.06 | 54.00 | -10.94 | 14.98 | 3 | V | 50 | 1.23 | - |
| AV | 15.955G | 46.55 | 54.00 | -7.45 | 16.91 | 3 | V | 157 | 1.52 | - |
| PK | 10.64196G | 57.32 | 74.00 | -16.68 | 14.98 | 3 | V | 50 | 1.23 | - |
| PK | 15.9649G | 60.70 | 74.00 | -13.30 | 16.90 | 3 | V | 157 | 1.52 | - |

## 802.11a_(6Mbps)_4TX

## 5320MHz_TX




20170606
EUT Z_4TX
Setting 84
04-M-01
FSP(100142)
Radio 1

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 10.63986G | 43.05 | 54.00 | -10.95 | 14.98 | 3 | H | 110 | 1.29 | - |
| AV | 15.95514G | 46.48 | 54.00 | -7.52 | 16.91 | 3 | H | 314 | 1.72 | - |
| PK | 10.64142G | 57.42 | 74.00 | -16.58 | 14.98 | 3 | H | 110 | 1.29 | - |
| PK | 15.96432G | 61.09 | 74.00 | -12.91 | 16.90 | 3 | H | 314 | 1.72 | - |

## 802.11a_(6Mbps)_4TX

## 5500MHz_TX




20170606
EUT Z_4TX
Setting 73
04-M-01-10
FSP(100142)
Radio 2

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 5.46G | 50.84 | 54.00 | -3.16 | 5.37 | 3 | V | 238 | 1.27 | - |
| AV | 5.4696G | 53.44 | 54.00 | -0.56 | 5.41 | 3 | V | 238 | 1.27 | - |
| AV | 5.5048G | 111.23 | Inf | -Inf | 5.59 | 3 | V | 238 | 1.27 | - |
| PK | 5.3336G | 59.26 | 68.20 | -8.94 | 5.01 | 3 | V | 238 | 1.27 | - |
| PK | 5.464G | 71.79 | 74.00 | -2.21 | 5.39 | 3 | V | 238 | 1.27 | - |
| PK | 5.5048G | 124.37 | Inf | -Inf | 5.59 | 3 | V | 238 | 1.27 | - |
| PK | 5.46G | 63.35 | 74.00 | -10.65 | 5.37 | 3 | V | 238 | 1.27 | - |

## 802.11a_(6Mbps)_4TX

## 5500MHz_TX




20170606
EUT Z_4TX
Setting 73
04-M-01
FSP(100142)
Radio 2

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 11.0048G | 41.95 | 54.00 | -12.05 | 15.60 | 3 | V | 293 | 2.10 | - |
| PK | 11.00294G | 56.02 | 74.00 | -17.98 | 15.60 | 3 | V | 293 | 2.10 | - |

## 802.11a_(6Mbps)_4TX

## 5500MHz_TX




20170606
EUT Z_4TX
Setting 73
04-M-01
FSP(100142)
Radio 2

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 11.00452G | 42.10 | 54.00 | -11.90 | 15.60 | 3 | H | 231 | 2.13 | - |
| PK | 11.00276G | 56.99 | 74.00 | -17.01 | 15.60 | 3 | H | 231 | 2.13 | - |

## 802.11a_(6Mbps)_4TX

## 5580MHz_TX




20170606
EUT Z_4TX
Setting 83
04-M-01-10
FSP(100142)
Radio 2

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 5.46G | 48.86 | 54.00 | -5.14 | 5.37 | 3 | V | 253 | 1.51 | - |
| AV | 5.4696G | 49.37 | 54.00 | -4.63 | 5.41 | 3 | V | 253 | 1.51 | - |
| AV | 5.5764G | 113.67 | Inf | -Inf | 5.99 | 3 | V | 253 | 1.51 | - |
| PK | 5.3484G | 58.81 | 68.20 | -9.39 | 5.02 | 3 | V | 253 | 1.51 | - |
| PK | 5.4696G | 61.92 | 74.00 | -12.08 | 5.41 | 3 | V | 253 | 1.51 | - |
| PK | 5.574G | 125.53 | Inf | -Inf | 5.97 | 3 | V | 253 | 1.51 | - |
| PK | 5.8176G | 65.61 | 74.00 | -8.39 | 6.50 | 3 | V | 253 | 1.51 | - |
| PK | 5.46G | 61.68 | 74.00 | -12.32 | 5.37 | 3 | V | 253 | 1.51 | - |
| AV | 5.8176G | 53.92 | 54.00 | -0.08 | 6.50 | 3 | V | 253 | 1.51 | - |

## 802.11a_(6Mbps)_4TX

## 5580MHz_TX




20170606
EUT Z_4TX
Setting 83
04-M-01
FSP(100142)
Radio 2

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 11.15964G | 42.12 | 54.00 | -11.88 | 15.67 | 3 | V | 249 | 1.62 | - |
| PK | 11.1585G | 55.96 | 74.00 | -18.04 | 15.67 | 3 | V | 249 | 1.62 | - |

## 802.11a_(6Mbps)_4TX

## 5580MHz_TX




20170606
EUT Z_4TX
Setting 83
04-M-01
FSP(100142)
Radio 2

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 11.15614G | 42.10 | 54.00 | -11.90 | 15.67 | 3 | H | 270 | 1.12 | - |
| PK | 11.16158G | 56.02 | 74.00 | -17.98 | 15.67 | 3 | H | 270 | 1.12 | - |

## 802.11a_(6Mbps)_4TX

## 5700MHz_TX




20170606
EUT Z_4TX
Setting 68
04-M-01-10
FSP(100142)
Radio 2

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 5.4576G | 51.76 | 54.00 | -2.24 | 5.36 | 3 | V | 262 | 1.89 | - |
| AV | 5.4684G | 51.87 | 54.00 | -2.13 | 5.41 | 3 | V | 262 | 1.89 | - |
| AV | 5.694G | 108.80 | Inf | -Inf | 6.24 | 3 | V | 262 | 1.89 | - |
| AV | 5.7288G | 53.66 | 54.00 | -0.34 | 6.29 | 3 | V | 262 | 1.89 | - |
| PK | 5.4576G | 63.77 | 74.00 | -10.23 | 5.36 | 3 | V | 262 | 1.89 | - |
| PK | 5.4684G | 64.20 | 74.00 | -9.80 | 5.41 | 3 | V | 262 | 1.89 | - |
| PK | 5.694G | 118.33 | Inf | -Inf | 6.24 | 3 | V | 262 | 1.89 | - |
| PK | 5.7252G | 73.89 | 74.00 | -0.11 | 6.29 | 3 | V | 262 | 1.89 | - |

## 802.11a_(6Mbps)_4TX

## 5700MHz_TX




20170606
EUT Z_4TX
Setting 68
04-M-01
FSP(100142)
Radio 2

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 11.40464G | 42.79 | 54.00 | -11.21 | 15.79 | 3 | V | 162 | 1.16 | - |
| PK | 11.40156G | 56.32 | 74.00 | -17.68 | 15.78 | 3 | V | 162 | 1.16 | - |

## 802.11a_(6Mbps)_4TX

## 5700MHz_TX




20170606
EUT Z_4TX
Setting 68
04-M-01
FSP(100142)
Radio 2

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 11.39852G | 42.98 | 54.00 | -11.02 | 15.78 | 3 | H | 191 | 2.08 | - |
| PK | 11.4023G | 56.29 | 74.00 | -17.71 | 15.79 | 3 | H | 191 | 2.08 | - |

## 802.11ac VHT20_Nss1,(MCS0)_4TX

## 5260MHz_TX




20170606
EUT Z_4TX
Setting 110
04-M-01-10
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 5.146G | 51.50 | 54.00 | -2.50 | 4.63 | 3 | V | 305 | 2.18 | - |
| AV | 5.266G | 118.03 | Inf | -Inf | 4.92 | 3 | V | 305 | 2.18 | - |
| AV | 5.3512G | 53.56 | 54.00 | -0.44 | 5.03 | 3 | V | 305 | 2.18 | - |
| PK | 5.1472G | 65.48 | 74.00 | -8.52 | 4.63 | 3 | V | 305 | 2.18 | - |
| PK | 5.2612G | 128.66 | Inf | -Inf | 4.92 | 3 | V | 305 | 2.18 | - |
| PK | 5.3512G | 69.52 | 74.00 | -4.48 | 5.03 | 3 | V | 305 | 2.18 | - |
| PK | 5.5432G | 60.18 | 68.20 | -8.02 | 5.80 | 3 | V | 305 | 2.18 | - |

## 802.11ac VHT20_Nss1,(MCS0)_4TX

## 5260MHz_TX




20170606
EUT Z_4TX
Setting 110
04-M-01
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 15.78394G | 46.99 | 54.00 | -7.01 | 17.04 | 3 | V | 168 | 2.19 | - |
| PK | 15.78482G | 61.08 | 74.00 | -12.92 | 17.04 | 3 | V | 168 | 2.19 | - |

## 802.11ac VHT20_Nss1,(MCS0)_4TX

## 5260MHz_TX




20170606
EUT Z_4TX
Setting 110
04-M-01
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 15.78308G | 46.77 | 54.00 | -7.23 | 17.04 | 3 | H | 229 | 1.29 | - |
| PK | 15.78368G | 60.24 | 74.00 | -13.76 | 17.04 | 3 | H | 229 | 1.29 | - |

## 802.11ac VHT20_Nss1,(MCS0)_4TX

## 5300MHz_TX




20170606
EUT Z_4TX
Setting 95
04-M-01-10
FSP(100142)
Radio 1

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 5.1448G | 48.82 | 54.00 | -5.18 | 4.63 | 3 | V | 299 | 2.13 | - |
| AV | 5.3064G | 115.67 | Inf | -Inf | 4.98 | 3 | V | 299 | 2.13 | - |
| AV | 5.350005G | 53.94 | 54.00 | -0.06 | 5.03 | 3 | V | 299 | 2.13 | - |
| PK | 5.14G | 60.43 | 74.00 | -13.57 | 4.61 | 3 | V | 299 | 2.13 | - |
| PK | 5.3056G | 126.30 | Inf | -Inf | 4.98 | 3 | V | 299 | 2.13 | - |
| PK | 5.350005G | 69.03 | 74.00 | -4.97 | 5.03 | 3 | V | 299 | 2.13 | - |
| PK | 5.492G | 60.00 | 68.20 | -8.20 | 5.52 | 3 | V | 299 | 2.13 | - |

## 802.11ac VHT20_Nss1,(MCS0)_4TX

## 5300MHz_TX




20170606
EUT Z_4TX
Setting 95
04-M-01
FSP(100142)
Radio 1

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 10.60756G | 44.17 | 54.00 | -9.83 | 14.93 | 3 | V | 198 | 2.01 | - |
| AV | 15.89596G | 46.99 | 54.00 | -7.01 | 16.95 | 3 | V | 267 | 1.79 | - |
| PK | 10.60402G | 57.60 | 74.00 | -16.40 | 14.92 | 3 | V | 198 | 2.01 | - |
| PK | 15.90488G | 60.35 | 74.00 | -13.65 | 16.95 | 3 | V | 267 | 1.79 | - |

## 802.11ac VHT20_Nss1,(MCS0)_4TX

## 5300MHz_TX




20170606
EUT Z_4TX
Setting 95
04-M-01
FSP(100142)
Radio 1

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 10.60394G | 44.22 | 54.00 | -9.78 | 14.92 | 3 | H | 181 | 1.53 | - |
| AV | 15.89622G | 47.04 | 54.00 | -6.96 | 16.95 | 3 | H | 262 | 2.19 | - |
| PK | 10.60056G | 57.97 | 74.00 | -16.03 | 14.91 | 3 | H | 181 | 1.53 | - |
| PK | 15.9001G | 61.12 | 74.00 | -12.88 | 16.95 | 3 | H | 262 | 2.19 | - |

## 802.11ac VHT20_Nss1,(MCS0)_4TX

## 5320MHz_TX




20170606
EUT Z_4TX
Setting 80
04-M-01-10
FSP(100142)
Radio 1

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 5.1416G | 46.54 | 54.00 | -7.46 | 4.61 | 3 | V | 129 | 1.71 | - |
| AV | 5.316G | 111.93 | Inf | -Inf | 4.99 | 3 | V | 129 | 1.71 | - |
| AV | 5.3512G | 53.76 | 54.00 | -0.24 | 5.03 | 3 | V | 129 | 1.71 | - |
| PK | 5.1472G | 59.47 | 74.00 | -14.53 | 4.63 | 3 | V | 129 | 1.71 | - |
| PK | 5.316G | 123.68 | Inf | -Inf | 4.99 | 3 | V | 129 | 1.71 | - |
| PK | 5.3504G | 73.25 | 74.00 | -0.75 | 5.03 | 3 | V | 129 | 1.71 | - |
| PK | 5.52G | 60.17 | 68.20 | -8.03 | 5.67 | 3 | V | 129 | 1.71 | - |

## 802.11ac VHT20_Nss1,(MCS0)_4TX

## 5320MHz_TX




20170606
EUT Z_4TX
Setting 80
04-M-01
FSP(100142)
Radio 1

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 10.64328G | 44.09 | 54.00 | -9.91 | 14.99 | 3 | V | 265 | 1.94 | - |
| AV | 15.9559G | 47.14 | 54.00 | -6.86 | 16.90 | 3 | V | 132 | 1.65 | - |
| PK | 10.64402G | 57.65 | 74.00 | -16.35 | 14.99 | 3 | V | 265 | 1.94 | - |
| PK | 15.95874G | 60.80 | 74.00 | -13.20 | 16.90 | 3 | V | 132 | 1.65 | - |

## 802.11ac VHT20_Nss1,(MCS0)_4TX

## 5320MHz_TX




20170606
EUT Z_4TX
Setting 80
04-M-01
FSP(100142)
Radio 1

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 10.64092G | 43.19 | 54.00 | -10.81 | 14.98 | 3 | H | 343 | 1.20 | - |
| AV | 15.95572G | 47.17 | 54.00 | -6.83 | 16.90 | 3 | H | 349 | 1.02 | - |
| PK | 10.64416G | 58.14 | 74.00 | -15.86 | 14.99 | 3 | H | 343 | 1.20 | - |
| PK | 15.95686G | 60.40 | 74.00 | -13.60 | 16.90 | 3 | H | 349 | 1.02 | - |

## 802.11ac VHT20_Nss1,(MCS0)_4TX

## 5500MHz_TX




20170607
EUT Z_4TX
Setting 72
04-M-01-10
FSP(100142)
Radio 2

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 5.459995G | 50.94 | 54.00 | -3.06 | 5.37 | 3 | V | 250 | 1.31 | - |
| AV | 5.4688G | 53.10 | 54.00 | -0.90 | 5.41 | 3 | V | 250 | 1.31 | - |
| AV | 5.5048G | 111.13 | Inf | -Inf | 5.59 | 3 | V | 250 | 1.31 | - |
| PK | 5.2192G | 59.07 | 68.20 | -9.13 | 4.86 | 3 | V | 250 | 1.31 | - |
| PK | 5.4688G | 68.79 | 74.00 | -5.21 | 5.41 | 3 | V | 250 | 1.31 | - |
| PK | 5.5048G | 122.62 | Inf | -Inf | 5.59 | 3 | V | 250 | 1.31 | - |
| PK | 5.734G | 64.86 | 74.00 | -9.14 | 6.30 | 3 | V | 250 | 1.31 | - |
| AV | 5.734G | 53.95 | 54.00 | -0.05 | 6.30 | 3 | V | 250 | 1.31 | - |
| PK | 5.4592G | 63.37 | 74.00 | -10.63 | 5.36 | 3 | V | 250 | 1.31 | - |

## 802.11ac VHT20_Nss1,(MCS0)_4TX

## 5500MHz_TX




20170607
EUT Z_4TX
Setting 72
04-M-01
FSP(100142)
Radio 2

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 11.00422G | 41.98 | 54.00 | -12.02 | 15.60 | 3 | V | 316 | 1.70 | - |
| PK | 11.00452G | 56.66 | 74.00 | -17.34 | 15.60 | 3 | V | 316 | 1.70 | - |

## 802.11ac VHT20_Nss1,(MCS0)_4TX

## 5500MHz_TX




20170607
EUT Z_4TX
Setting 72
04-M-01
FSP(100142)
Radio 2

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 11.00408G | 41.91 | 54.00 | -12.09 | 15.60 | 3 | H | 104 | 1.20 | - |
| PK | 10.99554G | 56.66 | 74.00 | -17.34 | 15.59 | 3 | H | 104 | 1.20 | - |

## 802.11ac VHT20_Nss1,(MCS0)_4TX

## 5580MHz_TX




20170607
EUT Z_4TX
Setting 79
04-M-01-10
FSP(100142)
Radio 2

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 5.46G | 49.62 | 54.00 | -4.38 | 5.37 | 3 | V | 164 | 2.40 | - |
| AV | 5.574G | 115.46 | Inf | -Inf | 5.97 | 3 | V | 164 | 2.40 | - |
| PK | 5.3388G | 59.08 | 68.20 | -9.12 | 5.01 | 3 | V | 164 | 2.40 | - |
| PK | 5.4696G | 63.70 | 68.20 | -4.50 | 5.41 | 3 | V | 164 | 2.40 | - |
| PK | 5.5848G | 125.45 | Inf | -Inf | 6.03 | 3 | V | 164 | 2.40 | - |
| PK | 5.4588G | 61.00 | 74.00 | -13.00 | 5.36 | 3 | V | 164 | 2.40 | - |
| PK | 5.82G | 67.95 | 68.20 | -0.25 | 6.52 | 3 | V | 164 | 2.40 | - |

## 802.11ac VHT20_Nss1,(MCS0)_4TX

## 5580MHz_TX




20170607
EUT Z_4TX
Setting 79
04-M-01
FSP(100142)
Radio 2

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 11.16218G | 42.83 | 54.00 | -11.17 | 15.67 | 3 | V | 351 | 1.16 | - |
| PK | 11.15858G | 57.08 | 74.00 | -16.92 | 15.67 | 3 | V | 351 | 1.16 | - |

## 802.11ac VHT20_Nss1,(MCS0)_4TX

## 5580MHz_TX




20170607
EUT Z_4TX
Setting 79
04-M-01
FSP(100142)
Radio 2

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 11.16014G | 43.03 | 54.00 | -10.97 | 15.67 | 3 | H | 272 | 1.65 | - |
| PK | 11.1578G | 56.48 | 74.00 | -17.52 | 15.67 | 3 | H | 272 | 1.65 | - |

## 802.11ac VHT20_Nss1,(MCS0)_4TX

## 5700MHz_TX




20170607
EUT Z_4TX
Setting 63
04-M-01-10
FSP(100142)
Radio 2

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 5.4576G | 50.27 | 54.00 | -3.73 | 5.36 | 3 | V | 155 | 1.37 | - |
| AV | 5.4672G | 50.78 | 54.00 | -3.22 | 5.40 | 3 | V | 155 | 1.37 | - |
| AV | 5.694G | 107.43 | Inf | -Inf | 6.24 | 3 | V | 155 | 1.37 | - |
| AV | 5.7252G | 53.83 | 54.00 | -0.17 | 6.29 | 3 | V | 155 | 1.37 | - |
| PK | 5.4576G | 62.52 | 74.00 | -11.48 | 5.36 | 3 | V | 155 | 1.37 | - |
| PK | 5.4672G | 62.13 | 74.00 | -11.87 | 5.40 | 3 | V | 155 | 1.37 | - |
| PK | 5.6964G | 120.53 | Inf | -Inf | 6.25 | 3 | V | 155 | 1.37 | - |
| PK | 5.73G | 73.55 | 74.00 | -0.45 | 6.29 | 3 | V | 155 | 1.37 | - |

## 802.11ac VHT20_Nss1,(MCS0)_4TX

## 5700MHz_TX




20170607
EUT Z_4TX
Setting 63
04-M-01
FSP(100142)
Radio 2

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 11.40328G | 42.04 | 54.00 | -11.96 | 15.79 | 3 | V | 179 | 1.91 | - |
| PK | 11.40494G | 56.17 | 74.00 | -17.83 | 15.79 | 3 | V | 179 | 1.91 | - |

## 802.11ac VHT20_Nss1,(MCS0)_4TX

## 5700MHz_TX




20170607
EUT Z_4TX
Setting 63
04-M-01
FSP(100142)
Radio 2

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 11.39512G | 42.85 | 54.00 | -11.15 | 15.78 | 3 | H | 280 | 1.85 | - |
| PK | 11.40336G | 56.15 | 74.00 | -17.85 | 15.79 | 3 | H | 280 | 1.85 | - |

## 802.11ac VHT40_Nss1,(MCS0)_4TX

## 5270MHz_TX




20170607
EUT Z_4TX
Setting 87
04-M-01-10
FSP(100142)
Radio 1

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 5.149995G | 50.25 | 54.00 | -3.75 | 4.64 | 3 | V | 90 | 2.01 | - |
| AV | 5.2652G | 111.48 | Inf | -Inf | 4.92 | 3 | V | 90 | 2.01 | - |
| AV | 5.3516G | 53.55 | 54.00 | -0.45 | 5.03 | 3 | V | 90 | 2.01 | - |
| PK | 5.1482G | 64.10 | 74.00 | -9.90 | 4.64 | 3 | V | 90 | 2.01 | - |
| PK | 5.2652G | 121.16 | Inf | -Inf | 4.92 | 3 | V | 90 | 2.01 | - |
| PK | 5.354G | 70.63 | 74.00 | -3.37 | 5.03 | 3 | V | 90 | 2.01 | - |

## 802.11ac VHT40_Nss1,(MCS0)_4TX

## 5270MHz_TX




20170607
EUT Z_4TX
Setting 87
04-M-01
FSP(100142)
Radio 1

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 15.81262G | 47.61 | 54.00 | -6.39 | 17.02 | 3 | V | 55 | 1.13 | - |
| PK | 15.80606G | 61.00 | 74.00 | -13.00 | 17.02 | 3 | V | 55 | 1.13 | - |

## 802.11ac VHT40_Nss1,(MCS0)_4TX

## 5270MHz_TX




20170607
EUT Z_4TX
Setting 87
04-M-01
FSP(100142)
Radio 1

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 15.80748G | 47.53 | 54.00 | -6.47 | 17.02 | 3 | H | 294 | 2.49 | - |
| PK | 15.80694G | 60.10 | 74.00 | -13.90 | 17.02 | 3 | H | 294 | 2.49 | - |

## 802.11ac VHT40_Nss1,(MCS0)_4TX

## 5310MHz_TX




20170607
EUT Z_4TX
Setting 69
04-M-01-10
FSP(100142)
Radio 1

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 5.1456G | 48.61 | 54.00 | -5.39 | 4.63 | 3 | V | 236 | 2.00 | - |
| AV | 5.316G | 107.65 | Inf | -Inf | 4.99 | 3 | V | 236 | 2.00 | - |
| AV | 5.3508G | 53.64 | 54.00 | -0.36 | 5.03 | 3 | V | 236 | 2.00 | - |
| PK | 5.1024G | 60.09 | 74.00 | -13.91 | 4.47 | 3 | V | 236 | 2.00 | - |
| PK | 5.316G | 116.88 | Inf | -Inf | 4.99 | 3 | V | 236 | 2.00 | - |
| PK | 5.352G | 72.15 | 74.00 | -1.85 | 5.03 | 3 | V | 236 | 2.00 | - |
| PK | 5.5812G | 61.18 | 68.20 | -7.02 | 6.01 | 3 | V | 236 | 2.00 | - |

## 802.11ac VHT40_Nss1,(MCS0)_4TX

## 5310MHz_TX




20170607
EUT Z_4TX
Setting 69
04-M-01
FSP(100142)
Radio 1

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 10.61836G | 44.91 | 54.00 | -9.09 | 14.94 | 3 | V | 173 | 1.17 | - |
| AV | 15.93134G | 47.90 | 54.00 | -6.10 | 16.92 | 3 | V | 79 | 2.27 | - |
| PK | 10.62394G | 57.44 | 74.00 | -16.56 | 14.95 | 3 | V | 173 | 1.17 | - |
| PK | 15.93332G | 60.98 | 74.00 | -13.02 | 16.92 | 3 | V | 79 | 2.27 | - |

## 802.11ac VHT40_Nss1,(MCS0)_4TX

## 5310MHz_TX




20170607
EUT Z_4TX
Setting 69
04-M-01
FSP(100142)
Radio 1

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 10.61864G | 44.98 | 54.00 | -9.02 | 14.94 | 3 | H | 120 | 1.66 | - |
| AV | 15.93008G | 48.02 | 54.00 | -5.98 | 16.93 | 3 | H | 179 | 2.36 | - |
| PK | 10.62428G | 57.94 | 74.00 | -16.06 | 14.95 | 3 | H | 120 | 1.66 | - |
| PK | 15.92916G | 60.23 | 74.00 | -13.77 | 16.93 | 3 | H | 179 | 2.36 | - |

## 802.11ac VHT40_Nss1,(MCS0)_4TX

## 5510MHz_TX




20170607
EUT Z_4TX
Setting 61
04-M-01-10
FSP(100142)
Radio 2

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 5.4572G | 52.72 | 54.00 | -1.28 | 5.35 | 3 | V | 332 | 2.00 | - |
| AV | 5.522G | 107.00 | Inf | -Inf | 5.68 | 3 | V | 332 | 2.00 | - |
| PK | 5.459995G | 66.15 | 74.00 | -7.85 | 5.37 | 3 | V | 332 | 2.00 | - |
| PK | 5.468G | 67.49 | 68.20 | -0.71 | 5.41 | 3 | V | 332 | 2.00 | - |
| PK | 5.5016G | 116.60 | Inf | -Inf | 5.57 | 3 | V | 332 | 2.00 | - |
| PK | 5.738G | 61.07 | 68.20 | -7.13 | 6.31 | 3 | V | 332 | 2.00 | - |

## 802.11ac VHT40_Nss1,(MCS0)_4TX

## 5510MHz_TX




20170607
EUT Z_4TX
Setting 61
04-M-01
FSP(100142)
Radio 2

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 11.02426G | 43.71 | 54.00 | -10.29 | 15.61 | 3 | V | 129 | 2.00 | - |
| PK | 11.01876G | 56.46 | 74.00 | -17.54 | 15.61 | 3 | V | 129 | 2.00 | - |

## 802.11ac VHT40_Nss1,(MCS0)_4TX

## 5510MHz_TX




20170607
EUT Z_4TX
Setting 61
04-M-01
FSP(100142)
Radio 2

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 11.01868G | 43.75 | 54.00 | -10.25 | 15.61 | 3 | H | 146 | 1.54 | - |
| PK | 11.01982G | 56.68 | 74.00 | -17.32 | 15.61 | 3 | H | 146 | 1.54 | - |

## 802.11ac VHT40_Nss1,(MCS0)_4TX

## 5550MHz_TX




20170607
EUT Z_4TX
Setting 82
04-M-01-10
FSP(100142)
Radio 2

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 5.46G | 52.88 | 54.00 | -1.12 | 5.37 | 3 | V | 280 | 1.50 | - |
| AV | 5.4696G | 53.68 | 54.00 | -0.32 | 5.41 | 3 | V | 280 | 1.50 | - |
| AV | 5.5452G | 112.46 | Inf | -Inf | 5.81 | 3 | V | 280 | 1.50 | - |
| AV | 5.79G | 52.24 | 54.00 | -1.76 | 6.38 | 3 | V | 280 | 1.50 | - |
| PK | 5.454G | 67.30 | 74.00 | -6.70 | 5.34 | 3 | V | 280 | 1.50 | - |
| PK | 5.4696G | 69.70 | 74.00 | -4.30 | 5.41 | 3 | V | 280 | 1.50 | - |
| PK | 5.5452G | 122.11 | Inf | -Inf | 5.81 | 3 | V | 280 | 1.50 | - |
| PK | 5.7252G | 62.84 | 74.00 | -11.16 | 6.29 | 3 | V | 280 | 1.50 | - |
| PK | 5.3124G | 58.62 | 68.20 | -9.58 | 4.98 | 3 | V | 280 | 1.50 | - |

## 802.11ac VHT40_Nss1,(MCS0)_4TX

## 5550MHz_TX




20170607
EUT Z_4TX
Setting 82
04-M-01
FSP(100142)
Radio 2

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 11.09768G | 43.84 | 54.00 | -10.16 | 15.64 | 3 | V | 20 | 2.21 | - |
| PK | 11.09514G | 56.17 | 74.00 | -17.83 | 15.64 | 3 | V | 20 | 2.21 | - |

## 802.11ac VHT40_Nss1,(MCS0)_4TX

## 5550MHz_TX




20170607
EUT Z_4TX
Setting 82
04-M-01
FSP(100142)
Radio 2

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 11.10176G | 43.89 | 54.00 | -10.11 | 15.65 | 3 | H | 300 | 1.06 | - |
| PK | 11.0978G | 56.51 | 74.00 | -17.49 | 15.64 | 3 | H | 300 | 1.06 | - |

## 802.11ac VHT40_Nss1,(MCS0)_4TX

## 5670MHz_TX




20170607
EUT Z_4TX
Setting 66
04-M-01-10
FSP(100142)
Radio 2

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 5.4384G | 48.40 | 54.00 | -5.60 | 5.26 | 3 | V | 40 | 2.00 | - |
| AV | 5.46G | 47.44 | 54.00 | -6.56 | 5.37 | 3 | V | 40 | 2.00 | - |
| AV | 5.664G | 109.23 | Inf | -Inf | 6.20 | 3 | V | 40 | 2.00 | - |
| AV | 5.7348G | 53.55 | 54.00 | -0.45 | 6.30 | 3 | V | 40 | 2.00 | - |
| PK | 5.4444G | 59.61 | 74.00 | -14.39 | 5.29 | 3 | V | 40 | 2.00 | - |
| PK | 5.4672G | 59.37 | 74.00 | -14.63 | 5.40 | 3 | V | 40 | 2.00 | - |
| PK | 5.664G | 118.99 | Inf | -Inf | 6.20 | 3 | V | 40 | 2.00 | - |
| PK | 5.7252G | 68.96 | 74.00 | -5.04 | 6.29 | 3 | V | 40 | 2.00 | - |

## 802.11ac VHT40_Nss1,(MCS0)_4TX

## 5670MHz_TX




20170607
EUT Z_4TX
Setting 66
04-M-01
FSP(100142)
Radio 2

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 11.3432G | 43.58 | 54.00 | -10.42 | 15.76 | 3 | V | 13 | 1.09 | - |
| PK | 11.33862G | 55.78 | 74.00 | -18.22 | 15.76 | 3 | V | 13 | 1.09 | - |

## 802.11ac VHT40_Nss1,(MCS0)_4TX

## 5670MHz_TX




20170607
EUT Z_4TX
Setting 66
04-M-01
FSP(100142)
Radio 2

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 11.34322G | 43.56 | 54.00 | -10.44 | 15.76 | 3 | H | 90 | 2.14 | - |
| PK | 11.34356G | 56.71 | 74.00 | -17.29 | 15.76 | 3 | H | 90 | 2.14 | - |

## 802.11ac VHT80_Nss1,(MCS0)_4TX

## 5290MHz_TX




20170607
EUT Z_4TX
Setting 70
04-M-01-10
FSP(100142)
Radio 2

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 5.1352G | 48.79 | 54.00 | -5.21 | 4.59 | 3 | V | 75 | 1.80 | - |
| AV | 5.2768G | 103.02 | Inf | -Inf | 4.94 | 3 | V | 75 | 1.80 | - |
| AV | 5.3512G | 53.58 | 54.00 | -0.42 | 5.03 | 3 | V | 75 | 1.80 | - |
| PK | 5.1412G | 60.87 | 74.00 | -13.13 | 4.61 | 3 | V | 75 | 1.80 | - |
| PK | 5.2816G | 113.09 | Inf | -Inf | 4.94 | 3 | V | 75 | 1.80 | - |
| PK | 5.356G | 73.10 | 74.00 | -0.90 | 5.03 | 3 | V | 75 | 1.80 | - |
| PK | 5.5684G | 60.66 | 68.20 | -7.54 | 5.94 | 3 | V | 75 | 1.80 | - |

## 802.11ac VHT80_Nss1,(MCS0)_4TX

## 5290MHz_TX




20170607
EUT Z_4TX
Setting 70
04-M-01
FSP(100142)
Radio 2

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 15.86812G | 48.22 | 54.00 | -5.78 | 16.97 | 3 | V | 123 | 2.17 | - |
| PK | 15.8708G | 60.95 | 74.00 | -13.05 | 16.97 | 3 | V | 123 | 2.17 | - |

## 802.11ac VHT80_Nss1,(MCS0)_4TX

## 5290MHz_TX




20170607
EUT Z_4TX
Setting 70
04-M-01
FSP(100142)
Radio 2

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 15.87252G | 48.14 | 54.00 | -5.86 | 16.97 | 3 | H | 164 | 2.08 | - |
| PK | 15.87258G | 61.27 | 74.00 | -12.73 | 16.97 | 3 | H | 164 | 2.08 | - |

## 802.11ac VHT80_Nss1,(MCS0)_4TX

## 5530MHz_TX




20170607
EUT Z_4TX
Setting 55
04-M-01-10
FSP(100142)
Radio 2

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 5.459995G | 53.54 | 54.00 | -0.46 | 5.37 | 3 | V | 281 | 1.90 | - |
| AV | 5.5396G | 101.45 | Inf | -Inf | 5.78 | 3 | V | 281 | 1.90 | - |
| PK | 5.459995G | 66.64 | 74.00 | -7.36 | 5.37 | 3 | V | 281 | 1.90 | - |
| PK | 5.4604G | 66.64 | 68.20 | -1.56 | 5.37 | 3 | V | 281 | 1.90 | - |
| PK | 5.5444G | 110.65 | Inf | -Inf | 5.81 | 3 | V | 281 | 1.90 | - |
| PK | 5.8288G | 60.65 | 68.20 | -7.55 | 6.57 | 3 | V | 281 | 1.90 | - |

## 802.11ac VHT80_Nss1,(MCS0)_4TX

## 5530MHz_TX




20170607
EUT Z_4TX
Setting 55
04-M-01
FSP(100142)
Radio 2

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 11.06488G | 43.01 | 54.00 | -10.99 | 15.63 | 3 | V | 6 | 1.56 | - |
| PK | 11.06104G | 55.71 | 74.00 | -18.29 | 15.63 | 3 | V | 6 | 1.56 | - |

## 802.11ac VHT80_Nss1,(MCS0)_4TX

## 5530MHz_TX




20170607
EUT Z_4TX
Setting 55
04-M-01
FSP(100142)
Radio 2

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 11.05566G | 43.12 | 54.00 | -10.88 | 15.63 | 3 | H | 294 | 1.84 | - |
| PK | 11.05864G | 55.65 | 74.00 | -18.35 | 15.63 | 3 | H | 294 | 1.84 | - |

## 802.11ac VHT80_Nss1,(MCS0)_4TX

## 5610MHz_TX




20170607
EUT Z_4TX
Setting 76
04-M-01-10
FSP(100142)
Radio 2

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 5.4576G | 49.90 | 54.00 | -4.10 | 5.36 | 3 | V | 90 | 1.90 | - |
| AV | 5.5968G | 107.16 | Inf | -Inf | 6.10 | 3 | V | 90 | 1.90 | - |
| AV | 5.7384G | 53.94 | 54.00 | -0.06 | 6.31 | 3 | V | 90 | 1.90 | - |
| PK | 5.3316G | 58.52 | 68.20 | -9.68 | 5.00 | 3 | V | 90 | 1.90 | - |
| PK | 5.5968G | 116.36 | Inf | -Inf | 6.10 | 3 | V | 90 | 1.90 | - |
| PK | 5.7384G | 70.88 | 74.00 | -3.12 | 6.31 | 3 | V | 90 | 1.90 | - |
| PK | 5.466G | 62.96 | 74.00 | -11.04 | 5.40 | 3 | V | 90 | 1.90 | - |

## 802.11ac VHT80_Nss1,(MCS0)_4TX

## 5610MHz_TX




20170607
EUT Z_4TX
Setting 76
04-M-01
FSP(100142)
Radio 2

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 11.22392G | 43.68 | 54.00 | -10.32 | 15.70 | 3 | V | 35 | 1.87 | - |
| PK | 11.22424G | 56.43 | 74.00 | -17.57 | 15.70 | 3 | V | 35 | 1.87 | - |

## 802.11ac VHT80_Nss1,(MCS0)_4TX

## 5610MHz_TX




20170607
EUT Z_4TX
Setting 76
04-M-01
FSP(100142)
Radio 2

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 11.21936G | 43.77 | 54.00 | -10.23 | 15.70 | 3 | H | 307 | 1.70 | - |
| PK | 11.22232G | 56.21 | 74.00 | -17.79 | 15.70 | 3 | H | 307 | 1.70 | - |

## 802.11ac VHT20-BF_Nss1,(MCS0)_4TX

## 5260MHz_TX




20170606
EUT Z_4TX
Setting 110
04-J-6-10
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 5.1424G | 53.81 | 54.00 | -0.19 | 4.62 | 3 | V | 327 | 1.92 | - |
| AV | 5.2546G | 117.93 | Inf | -Inf | 4.91 | 3 | V | 327 | 1.92 | - |
| AV | 5.3512G | 53.74 | 54.00 | -0.26 | 5.03 | 3 | V | 327 | 1.92 | - |
| PK | 5.1322G | 67.57 | 74.00 | -6.43 | 4.58 | 3 | V | 327 | 1.92 | - |
| PK | 5.254G | 128.45 | Inf | -Inf | 4.91 | 3 | V | 327 | 1.92 | - |
| PK | 5.3524G | 67.53 | 74.00 | -6.47 | 5.03 | 3 | V | 327 | 1.92 | - |

## 802.11ac VHT20-BF_Nss1,(MCS0)_4TX

## 5260MHz_TX




20170606
EUT Z_4TX
Setting 110
04-J-6
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 15.77986G | 46.21 | 54.00 | -7.79 | 17.04 | 3 | V | 216 | 2.44 | - |
| PK | 15.77818G | 60.42 | 74.00 | -13.58 | 17.05 | 3 | V | 216 | 2.44 | - |

## 802.11ac VHT20-BF_Nss1,(MCS0)_4TX

## 5260MHz_TX




20170606
EUT Z_4TX
Setting 110
04-J-6
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 15.78254G | 46.15 | 54.00 | -7.85 | 17.04 | 3 | H | 64 | 1.28 | - |
| PK | 15.78172G | 60.20 | 74.00 | -13.80 | 17.04 | 3 | H | 64 | 1.28 | - |

## 802.11ac VHT20-BF_Nss1,(MCS0)_4TX

## 5300MHz_TX




20170606
EUT Z_4TX
Setting 90
04-J-6-10
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 5.3036G | 116.39 | Inf | -Inf | 4.97 | 3 | V | 333 | 2.00 | - |
| AV | 5.350005G | 53.78 | 54.00 | -0.22 | 5.03 | 3 | V | 333 | 2.00 | - |
| PK | 5.3056G | 128.03 | Inf | -Inf | 4.98 | 3 | V | 333 | 2.00 | - |
| PK | 5.3504G | 67.99 | 74.00 | -6.01 | 5.03 | 3 | V | 333 | 2.00 | - |

## 802.11ac VHT20-BF_Nss1,(MCS0)_4TX

## 5300MHz_TX




20170606
EUT Z_4TX
Setting 90
04-J-6
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 10.60472G | 43.60 | 54.00 | -10.40 | 14.92 | 3 | V | 21 | 1.23 | - |
| PK | 10.60302G | 57.42 | 74.00 | -16.58 | 14.92 | 3 | V | 21 | 1.23 | - |

## 802.11ac VHT20-BF_Nss1,(MCS0)_4TX

## 5300MHz_TX




20170606
EUT Z_4TX
Setting 90
04-J-6
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 10.60398G | 43.97 | 54.00 | -10.03 | 14.92 | 3 | H | 68 | 2.19 | - |
| PK | 10.60234G | 57.96 | 74.00 | -16.04 | 14.92 | 3 | H | 68 | 2.19 | - |

## 802.11ac VHT20-BF_Nss1,(MCS0)_4TX

## 5320MHz_TX




20170606
EUT Z_4TX
Setting 80
04-J-6-10
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 5.3156G | 112.80 | Inf | -Inf | 4.99 | 3 | V | 1 | 1.50 | - |
| AV | 5.350005G | 53.98 | 54.00 | -0.02 | 5.03 | 3 | V | 1 | 1.50 | - |
| PK | 5.3248G | 123.24 | Inf | -Inf | 5.00 | 3 | V | 1 | 1.50 | - |
| PK | 5.3508G | 70.30 | 74.00 | -3.70 | 5.03 | 3 | V | 1 | 1.50 | - |

## 802.11ac VHT20-BF_Nss1,(MCS0)_4TX

## 5320MHz_TX




20170606
EUT Z_4TX
Setting 80
04-J-6
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 10.6431G | 43.27 | 54.00 | -10.73 | 14.99 | 3 | V | 112 | 1.46 | - |
| PK | 10.64388G | 57.44 | 74.00 | -16.56 | 14.99 | 3 | V | 112 | 1.46 | - |

## 802.11ac VHT20-BF_Nss1,(MCS0)_4TX

## 5320MHz_TX




20170606
EUT Z_4TX
Setting 80
04-J-6
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 10.63566G | 43.66 | 54.00 | -10.34 | 14.97 | 3 | H | 207 | 2.06 | - |
| PK | 10.64054G | 57.48 | 74.00 | -16.52 | 14.98 | 3 | H | 207 | 2.06 | - |

## 802.11ac VHT20-BF_Nss1,(MCS0)_4TX

## 5500MHz_TX




20170606
EUT Z_4TX
Setting 71
04-J-6-10
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 5.459995G | 51.61 | 54.00 | -2.39 | 5.37 | 3 | V | 279 | 1.50 | - |
| AV | 5.5036G | 110.01 | Inf | -Inf | 5.58 | 3 | V | 279 | 1.50 | - |
| PK | 5.455G | 63.94 | 74.00 | -10.06 | 5.34 | 3 | V | 279 | 1.50 | - |
| PK | 5.4676G | 68.17 | 68.20 | -0.03 | 5.40 | 3 | V | 279 | 1.50 | - |
| PK | 5.4988G | 122.12 | Inf | -Inf | 5.55 | 3 | V | 279 | 1.50 | - |

## 802.11ac VHT20-BF_Nss1,(MCS0)_4TX

## 5500MHz_TX




20170606
EUT Z_4TX
Setting 71
04-J-6
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 11.00484G | 42.11 | 54.00 | -11.89 | 15.60 | 3 | V | 320 | 1.64 | - |
| PK | 11.00098G | 55.99 | 74.00 | -18.01 | 15.60 | 3 | V | 320 | 1.64 | - |

## 802.11ac VHT20-BF_Nss1,(MCS0)_4TX

## 5500MHz_TX




20170606
EUT Z_4TX
Setting 71
04-J-6
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 11.00402G | 42.49 | 54.00 | -11.51 | 15.60 | 3 | H | 137 | 1.11 | - |
| PK | 10.9974G | 56.40 | 74.00 | -17.60 | 15.60 | 3 | H | 137 | 1.11 | - |

## 802.11ac VHT20-BF_Nss1,(MCS0)_4TX

## 5580MHz_TX




20170606
EUT Z_4TX
Setting 83
04-J-6-10
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 5.46G | 50.16 | 54.00 | -3.84 | 5.37 | 3 | V | 255 | 1.50 | - |
| AV | 5.575G | 114.52 | Inf | -Inf | 5.98 | 3 | V | 255 | 1.50 | - |
| PK | 5.468G | 63.29 | 68.20 | -4.91 | 5.41 | 3 | V | 255 | 1.50 | - |
| PK | 5.574G | 124.57 | Inf | -Inf | 5.97 | 3 | V | 255 | 1.50 | - |
| PK | 5.812G | 67.96 | 68.20 | -0.24 | 6.47 | 3 | V | 255 | 1.50 | - |
| PK | 5.459G | 62.61 | 74.00 | -11.39 | 5.36 | 3 | V | 255 | 1.50 | - |

## 802.11ac VHT20-BF_Nss1,(MCS0)_4TX

## 5580MHz_TX




20170606
EUT Z_4TX
Setting 83
04-J-6
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 11.15848G | 42.69 | 54.00 | -11.31 | 15.67 | 3 | V | 136 | 1.60 | - |
| PK | 11.1641G | 56.19 | 74.00 | -17.81 | 15.68 | 3 | V | 136 | 1.60 | - |

## 802.11ac VHT20-BF_Nss1,(MCS0)_4TX

## 5580MHz_TX




20170606
EUT Z_4TX
Setting 83
04-J-6
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 11.15654G | 42.31 | 54.00 | -11.69 | 15.67 | 3 | H | 11 | 2.03 | - |
| PK | 11.16102G | 56.05 | 74.00 | -17.95 | 15.67 | 3 | H | 11 | 2.03 | - |

## 802.11ac VHT20-BF_Nss1,(MCS0)_4TX

## 5700MHz_TX




20170606
EUT Z_4TX
Setting 60
04-J-6-10
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 5.6952G | 108.50 | Inf | -Inf | 6.24 | 3 | V | 282 | 1.82 | - |
| AV | 5.7252G | 53.97 | 54.00 | -0.03 | 6.29 | 3 | V | 282 | 1.82 | - |
| PK | 5.6958G | 121.15 | Inf | -Inf | 6.24 | 3 | V | 282 | 1.82 | - |
| PK | 5.7252G | 69.98 | 74.00 | -4.02 | 6.29 | 3 | V | 282 | 1.82 | - |

## 802.11ac VHT20-BF_Nss1,(MCS0)_4TX

## 5700MHz_TX




20170606
EUT Z_4TX
Setting 60
04-J-6
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 11.40262G | 42.27 | 54.00 | -11.73 | 15.79 | 3 | V | 170 | 1.71 | - |
| PK | 11.40292G | 56.54 | 74.00 | -17.46 | 15.79 | 3 | V | 170 | 1.71 | - |

## 802.11ac VHT20-BF_Nss1,(MCS0)_4TX

## 5700MHz_TX




20170606
EUT Z_4TX
Setting 60
04-J-6
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 11.40176G | 42.75 | 54.00 | -11.25 | 15.78 | 3 | H | 297 | 1.68 | - |
| PK | 11.40318G | 56.94 | 74.00 | -17.06 | 15.79 | 3 | H | 297 | 1.68 | - |

## 802.11ac VHT40-BF_Nss1,(MCS0)_4TX

## 5270MHz_TX




20170607
EUT Z_4TX
Setting 87
04-J-6-10
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 5.126G | 52.45 | 54.00 | -1.55 | 4.56 | 3 | V | 3 | 1.50 | - |
| AV | 5.2628G | 111.09 | Inf | -Inf | 4.92 | 3 | V | 3 | 1.50 | - |
| AV | 5.3534G | 53.67 | 54.00 | -0.33 | 5.03 | 3 | V | 3 | 1.50 | - |
| PK | 5.126G | 65.42 | 74.00 | -8.58 | 4.56 | 3 | V | 3 | 1.50 | - |
| PK | 5.2634G | 122.14 | Inf | -Inf | 4.92 | 3 | V | 3 | 1.50 | - |
| PK | 5.3546G | 68.20 | 74.00 | -5.80 | 5.03 | 3 | V | 3 | 1.50 | - |

## 802.11ac VHT40-BF_Nss1,(MCS0)_4TX

## 5270MHz_TX




20170607
EUT Z_4TX
Setting 87
04-J-6-10
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 15.80718G | 46.23 | 54.00 | -7.77 | 17.02 | 3 | V | 93 | 1.76 | - |
| PK | 15.8066G | 60.24 | 74.00 | -13.76 | 17.02 | 3 | V | 93 | 1.76 | - |

## 802.11ac VHT40-BF_Nss1,(MCS0)_4TX

## 5270MHz_TX




20170607
EUT Z_4TX
Setting 87
04-J-6-10
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 15.80732G | 46.27 | 54.00 | -7.73 | 17.02 | 3 | H | 199 | 1.77 | - |
| PK | 15.81374G | 60.26 | 74.00 | -13.74 | 17.02 | 3 | H | 199 | 1.77 | - |

## 802.11ac VHT40-BF_Nss1,(MCS0)_4TX

## 5310MHz_TX




20170607
EUT Z_4TX
Setting 69
04-J-6-10
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 5.3156G | 104.25 | Inf | -Inf | 4.99 | 3 | V | 321 | 1.97 | - |
| AV | 5.350005G | 51.29 | 54.00 | -2.71 | 5.03 | 3 | V | 321 | 1.97 | - |
| PK | 5.3164G | 115.04 | Inf | -Inf | 4.99 | 3 | V | 321 | 1.97 | - |
| PK | 5.352G | 73.78 | 74.00 | -0.22 | 5.03 | 3 | V | 321 | 1.97 | - |

## 802.11ac VHT40-BF_Nss1,(MCS0)_4TX

## 5310MHz_TX




20170607
EUT Z_4TX
Setting 69
04-J-6-10
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 10.6235G | 43.79 | 54.00 | -10.21 | 14.95 | 3 | V | 71 | 1.18 | - |
| PK | 10.62092G | 57.93 | 74.00 | -16.07 | 14.95 | 3 | V | 71 | 1.18 | - |

## 802.11ac VHT40-BF_Nss1,(MCS0)_4TX

## 5310MHz_TX




20170607
EUT Z_4TX
Setting 69
04-J-6-10
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 10.61698G | 43.55 | 54.00 | -10.45 | 14.94 | 3 | H | 65 | 1.27 | - |
| PK | 10.62232G | 57.32 | 74.00 | -16.68 | 14.95 | 3 | H | 65 | 1.27 | - |

## 802.11ac VHT40-BF_Nss1,(MCS0)_4TX

## 5510MHz_TX




20170607
EUT Z_4TX
Setting 58
04-J-6-10
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 5.458G | 51.73 | 54.00 | -2.27 | 5.36 | 3 | V | 0 | 1.95 | - |
| AV | 5.4696G | 53.81 | 54.00 | -0.19 | 5.41 | 3 | V | 0 | 1.95 | - |
| AV | 5.516G | 105.81 | Inf | -Inf | 5.65 | 3 | V | 0 | 1.95 | - |
| PK | 5.4596G | 64.61 | 74.00 | -9.39 | 5.37 | 3 | V | 0 | 1.95 | - |
| PK | 5.4668G | 73.06 | 74.00 | -0.94 | 5.40 | 3 | V | 0 | 1.95 | - |
| PK | 5.5184G | 116.58 | Inf | -Inf | 5.66 | 3 | V | 0 | 1.95 | - |

## 802.11ac VHT40-BF_Nss1,(MCS0)_4TX

## 5510MHz_TX




20170607
EUT Z_4TX
Setting 58
04-J-6-10
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 11.01598G | 42.30 | 54.00 | -11.70 | 15.61 | 3 | V | 203 | 1.66 | - |
| PK | 11.02398G | 56.02 | 74.00 | -17.98 | 15.61 | 3 | V | 203 | 1.66 | - |

## 802.11ac VHT40-BF_Nss1,(MCS0)_4TX

## 5510MHz_TX




20170607
EUT Z_4TX
Setting 58
04-J-6-10
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 11.01734G | 42.77 | 54.00 | -11.23 | 15.61 | 3 | H | 325 | 1.13 | - |
| PK | 11.01518G | 56.82 | 74.00 | -17.18 | 15.61 | 3 | H | 325 | 1.13 | - |

## 802.11ac VHT40-BF_Nss1,(MCS0)_4TX

## 5550MHz_TX




20170607
EUT Z_4TX
Setting 78
04-J-6-10
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 5.46G | 51.69 | 54.00 | -2.31 | 5.37 | 3 | V | 145 | 1.81 | - |
| AV | 5.469G | 53.64 | 54.00 | -0.36 | 5.41 | 3 | V | 145 | 1.81 | - |
| AV | 5.5566G | 111.49 | Inf | -Inf | 5.88 | 3 | V | 145 | 1.81 | - |
| PK | 5.4588G | 64.02 | 74.00 | -9.98 | 5.36 | 3 | V | 145 | 1.81 | - |
| PK | 5.4696G | 67.85 | 74.00 | -6.15 | 5.41 | 3 | V | 145 | 1.81 | - |
| PK | 5.5584G | 122.31 | Inf | -Inf | 5.89 | 3 | V | 145 | 1.81 | - |

## 802.11ac VHT40-BF_Nss1,(MCS0)_4TX

## 5550MHz_TX




20170607
EUT Z_4TX
Setting 78
04-J-6-10
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 11.1006G | 42.31 | 54.00 | -11.69 | 15.65 | 3 | V | 252 | 2.17 | - |
| PK | 11.10416G | 56.23 | 74.00 | -17.77 | 15.65 | 3 | V | 252 | 2.17 | - |

## 802.11ac VHT40-BF_Nss1,(MCS0)_4TX

## 5550MHz_TX




20170607
EUT Z_4TX
Setting 78
04-J-6-10
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 11.10222G | 42.66 | 54.00 | -11.34 | 15.65 | 3 | H | 45 | 1.18 | - |
| PK | 11.10378G | 56.26 | 74.00 | -17.74 | 15.65 | 3 | H | 45 | 1.18 | - |

## 802.11ac VHT40-BF_Nss1,(MCS0)_4TX

## 5670MHz_TX




20170607
EUT Z_4TX
Setting 65
04-J-6-10
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 5.6634G | 107.84 | Inf | -Inf | 6.20 | 3 | V | 359 | 2.06 | - |
| AV | 5.7888G | 53.71 | 54.00 | -0.29 | 6.38 | 3 | V | 359 | 2.06 | - |
| PK | 5.6586G | 118.13 | Inf | -Inf | 6.20 | 3 | V | 359 | 2.06 | - |
| PK | 5.736G | 70.53 | 74.00 | -3.47 | 6.30 | 3 | V | 359 | 2.06 | - |

## 802.11ac VHT40-BF_Nss1,(MCS0)_4TX

## 5670MHz_TX




20170607
EUT Z_4TX
Setting 65
04-J-6-10
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 11.34484G | 42.27 | 54.00 | -11.73 | 15.76 | 3 | V | 218 | 1.39 | - |
| PK | 11.34224G | 56.11 | 74.00 | -17.89 | 15.76 | 3 | V | 218 | 1.39 | - |

## 802.11ac VHT40-BF_Nss1,(MCS0)_4TX

## 5670MHz_TX




20170607
EUT Z_4TX
Setting 65
04-J-6-10
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 11.3441G | 42.17 | 54.00 | -11.83 | 15.76 | 3 | H | 36 | 2.37 | - |
| PK | 11.34262G | 56.18 | 74.00 | -17.82 | 15.76 | 3 | H | 36 | 2.37 | - |

## 802.11ac VHT80-BF_Nss1,(MCS0)_4TX

## 5290MHz_TX




20170607
EUT Z_4TX
Setting 69
04-J-6-10
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 5.125G | 49.78 | 54.00 | -4.22 | 4.55 | 3 | V | 3 | 1.50 | - |
| AV | 5.304G | 102.02 | Inf | -Inf | 4.97 | 3 | V | 3 | 1.50 | - |
| AV | 5.353G | 53.67 | 54.00 | -0.33 | 5.03 | 3 | V | 3 | 1.50 | - |
| PK | 5.149995G | 63.72 | 74.00 | -10.28 | 4.64 | 3 | V | 3 | 1.50 | - |
| PK | 5.306G | 112.46 | Inf | -Inf | 4.98 | 3 | V | 3 | 1.50 | - |
| PK | 5.350005G | 71.56 | 74.00 | -2.44 | 5.03 | 3 | V | 3 | 1.50 | - |

## 802.11ac VHT80-BF_Nss1,(MCS0)_4TX

## 5290MHz_TX




20170607
EUT Z_4TX
Setting 69
04-J-6-10
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 15.8662G | 46.75 | 54.00 | -7.25 | 16.98 | 3 | V | 173 | 1.16 | - |
| PK | 15.86512G | 61.63 | 74.00 | -12.37 | 16.98 | 3 | V | 173 | 1.16 | - |

## 802.11ac VHT80-BF_Nss1,(MCS0)_4TX

## 5290MHz_TX




20170607
EUT Z_4TX
Setting 69
04-J-6-10
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 15.87434G | 45.71 | 54.00 | -8.29 | 16.97 | 3 | H | 268 | 1.53 | - |
| PK | 15.86604G | 60.50 | 74.00 | -13.50 | 16.98 | 3 | H | 268 | 1.53 | - |

## 802.11ac VHT80-BF_Nss1,(MCS0)_4TX

## 5530MHz_TX




20170607
EUT Z_4TX
Setting 59
04-J-6-10
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 5.458G | 52.82 | 54.00 | -1.18 | 5.36 | 3 | V | 288 | 1.72 | - |
| AV | 5.464G | 53.77 | 54.00 | -0.23 | 5.39 | 3 | V | 288 | 1.72 | - |
| AV | 5.518G | 100.29 | Inf | -Inf | 5.66 | 3 | V | 288 | 1.72 | - |
| AV | 5.78G | 51.17 | 54.00 | -2.83 | 6.37 | 3 | V | 288 | 1.72 | - |
| PK | 5.467G | 68.19 | 74.00 | -5.81 | 5.40 | 3 | V | 288 | 1.72 | - |
| PK | 5.495G | 116.00 | Inf | -Inf | 5.54 | 3 | V | 288 | 1.72 | - |
| PK | 5.766G | 62.82 | 74.00 | -11.18 | 6.35 | 3 | V | 288 | 1.72 | - |
| PK | 5.458G | 66.43 | 74.00 | -7.57 | 5.36 | 3 | V | 288 | 1.72 | - |

## 802.11ac VHT80-BF_Nss1,(MCS0)_4TX

## 5530MHz_TX




20170607
EUT Z_4TX
Setting 59
04-J-6-10
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 11.06364G | 41.99 | 54.00 | -12.01 | 15.63 | 3 | V | 279 | 1.54 | - |
| PK | 11.06476G | 55.77 | 74.00 | -18.23 | 15.63 | 3 | V | 279 | 1.54 | - |

## 802.11ac VHT80-BF_Nss1,(MCS0)_4TX

## 5530MHz_TX




20170607
EUT Z_4TX
Setting 59
04-J-6-10
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 11.05556G | 41.62 | 54.00 | -12.38 | 15.63 | 3 | H | 87 | 1.91 | - |
| PK | 11.06314G | 55.41 | 74.00 | -18.59 | 15.63 | 3 | H | 87 | 1.91 | - |

## 802.11ac VHT80-BF_Nss1,(MCS0)_4TX

## 5610MHz_TX




20170607
EUT Z_4TX
Setting 70
04-J-6-10
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 5.46G | 46.75 | 54.00 | -7.25 | 5.37 | 3 | V | 252 | 1.49 | - |
| AV | 5.467G | 47.11 | 54.00 | -6.89 | 5.40 | 3 | V | 252 | 1.49 | - |
| AV | 5.572G | 102.19 | Inf | -Inf | 5.96 | 3 | V | 252 | 1.49 | - |
| AV | 5.788G | 53.95 | 54.00 | -0.05 | 6.38 | 3 | V | 252 | 1.49 | - |
| PK | 5.396G | 58.98 | 74.00 | -15.02 | 5.08 | 3 | V | 252 | 1.49 | - |
| PK | 5.467G | 59.05 | 74.00 | -14.95 | 5.40 | 3 | V | 252 | 1.49 | - |
| PK | 5.577G | 118.55 | Inf | -Inf | 5.99 | 3 | V | 252 | 1.49 | - |
| PK | 5.778G | 73.97 | 74.00 | -0.03 | 6.37 | 3 | V | 252 | 1.49 | - |

## 802.11ac VHT80-BF_Nss1,(MCS0)_4TX

## 5610MHz_TX




20170607
EUT Z_4TX
Setting 70
04-J-6-10
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 11.22336G | 42.36 | 54.00 | -11.64 | 15.70 | 3 | V | 152 | 1.92 | - |
| PK | 11.2181G | 56.29 | 74.00 | -17.71 | 15.70 | 3 | V | 152 | 1.92 | - |

## 802.11ac VHT80-BF_Nss1,(MCS0)_4TX

## 5610MHz_TX




20170607
EUT Z_4TX
Setting 70
04-J-6-10
FSP(100142)

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 11.22248G | 42.28 | 54.00 | -11.72 | 15.70 | 3 | H | 136 | 1.71 | - |
| PK | 11.22308G | 56.05 | 74.00 | -17.95 | 15.70 | 3 | H | 136 | 1.71 | - |

## 802.11ac VHT80+80
## Summary

| Mode | Result | Type | Freq (Hz) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Factor (dB) | Dist (m) | Pol. (H/V) | Azimuth (°) | Height (m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 802.11ac VHT80+80_Nss1,(MCS0)_4TX | - | - | - | - | - | - | - | - | - | - | - | - |
| 5.15-5.25GHz | Pass | AV | 5.137G | 53.96 | 54.00 | -0.04 | 4.60 | 3 | V | 3 | 1.50 | - |

## 802.11ac VHT80+80_Nss1,(MCS0)_4TX

## #5210MHz,5290MHz_TX




20170606
EUT Z_4TX
Setting 60
04-J-6-10
FSP(100142)
Radio 1

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 5.137G | 53.96 | 54.00 | -0.04 | 4.60 | 3 | V | 3 | 1.50 | - |
| AV | 5.245G | 98.38 | Inf | -Inf | 4.89 | 3 | V | 3 | 1.50 | - |
| AV | 5.354G | 50.25 | 54.00 | -3.75 | 5.03 | 3 | V | 3 | 1.50 | - |
| PK | 5.146G | 65.46 | 74.00 | -8.54 | 4.63 | 3 | V | 3 | 1.50 | - |
| PK | 5.226G | 108.71 | Inf | -Inf | 4.87 | 3 | V | 3 | 1.50 | - |
| PK | 5.350005G | 61.82 | 74.00 | -12.18 | 5.03 | 3 | V | 3 | 1.50 | - |

## 802.11ac VHT80+80_Nss1,(MCS0)_4TX

## #5210MHz,5290MHz_TX




20170606
EUT Z_4TX
Setting 60
04-J-6
FSP(100142)
Radio 1

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 15.62984G | 46.90 | 54.00 | -7.10 | 17.16 | 3 | V | 120 | 1.65 | - |
| PK | 15.63408G | 61.58 | 74.00 | -12.42 | 17.16 | 3 | V | 120 | 1.65 | - |

## 802.11ac VHT80+80_Nss1,(MCS0)_4TX

## #5210MHz,5290MHz_TX




20170606
EUT Z_4TX
Setting 60
04-J-6
FSP(100142)
Radio 1

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 15.6342G | 47.06 | 54.00 | -6.94 | 17.16 | 3 | H | 134 | 1.89 | - |
| PK | 15.62048G | 61.46 | 74.00 | -12.54 | 17.17 | 3 | H | 134 | 1.89 | - |

## 802.11ac VHT80+80_Nss1,(MCS0)_4TX

## 5210MHz,#5290MHz_TX




20170606
EUT Z_4TX
Setting 60
04-J-6-10
FSP(100142)
Radio 1

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 5.146G | 53.72 | 54.00 | -0.28 | 4.63 | 3 | V | 97 | 1.92 | - |
| AV | 5.305G | 98.57 | Inf | -Inf | 4.98 | 3 | V | 97 | 1.92 | - |
| AV | 5.356G | 51.08 | 54.00 | -2.92 | 5.03 | 3 | V | 97 | 1.92 | - |
| PK | 5.145G | 65.05 | 74.00 | -8.95 | 4.63 | 3 | V | 97 | 1.92 | - |
| PK | 5.305G | 110.18 | Inf | -Inf | 4.98 | 3 | V | 97 | 1.92 | - |
| PK | 5.350005G | 66.44 | 74.00 | -7.56 | 5.03 | 3 | V | 97 | 1.92 | - |

## 802.11ac VHT80+80_Nss1,(MCS0)_4TX

## 5210MHz,#5290MHz_TX




20170606
EUT Z_4TX
Setting 60
04-J-6
FSP(100142)
Radio 1

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 15.86594G | 46.76 | 54.00 | -7.24 | 16.98 | 3 | V | 360 | 1.92 | - |
| PK | 15.86958G | 61.03 | 74.00 | -12.97 | 16.97 | 3 | V | 360 | 1.92 | - |

## 802.11ac VHT80+80_Nss1,(MCS0)_4TX

## 5210MHz,#5290MHz_TX




20170606
EUT Z_4TX
Setting 60
04-J-6
FSP(100142)
Radio 1

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 15.86868G | 46.77 | 54.00 | -7.23 | 16.97 | 3 | H | 256 | 2.30 | - |
| PK | 15.87198G | 60.90 | 74.00 | -13.10 | 16.97 | 3 | H | 256 | 2.30 | - |

## 802.11ac VHT80+80_Nss1,(MCS0)_4TX

## #5530MHz,5610MHz_TX




20170606
EUT Z_4TX
Setting 58
04-J-6-10
FSP(100142)
Radio 2

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 5.459G | 53.85 | 54.00 | -0.15 | 5.36 | 3 | V | 4 | 2.01 | - |
| AV | 5.542G | 98.66 | Inf | -Inf | 5.80 | 3 | V | 4 | 2.01 | - |
| AV | 5.745G | 50.12 | Inf | -Inf | 6.32 | 3 | V | 4 | 2.01 | - |
| PK | 5.462G | 64.61 | 68.20 | -3.59 | 5.38 | 3 | V | 4 | 2.01 | - |
| PK | 5.544G | 109.86 | Inf | -Inf | 5.81 | 3 | V | 4 | 2.01 | - |
| PK | 5.755G | 61.01 | 68.20 | -7.19 | 6.33 | 3 | V | 4 | 2.01 | - |
| PK | 5.457G | 63.83 | 74.00 | -10.17 | 5.35 | 3 | V | 4 | 2.01 | - |

## 802.11ac VHT80+80_Nss1,(MCS0)_4TX

## #5530MHz,5610MHz_TX




20170606
EUT Z_4TX
Setting 58
04-J-6
FSP(100142)
Radio 2

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 11.05592G | 45.07 | 54.00 | -8.93 | 15.63 | 3 | V | 125 | 1.69 | - |
| PK | 11.06392G | 56.15 | 74.00 | -17.85 | 15.63 | 3 | V | 125 | 1.69 | - |

## 802.11ac VHT80+80_Nss1,(MCS0)_4TX

## #5530MHz,5610MHz_TX




20170606
EUT Z_4TX
Setting 58
04-J-6
FSP(100142)
Radio 2

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 11.05726G | 45.12 | 54.00 | -8.88 | 15.63 | 3 | H | 270 | 1.85 | - |
| PK | 11.06496G | 55.94 | 74.00 | -18.06 | 15.63 | 3 | H | 270 | 1.85 | - |

## 802.11ac VHT80+80_Nss1,(MCS0)_4TX

## 5530MHz,#5610MHz_TX




20170606
EUT Z_4TX
Setting 58
04-J-6-10
FSP(100142)
Radio 2

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 5.46G | 52.15 | 54.00 | -1.85 | 5.98 | 3 | V | 286 | 1.74 | - |
| AV | 5.4648G | 53.51 | 54.00 | -0.49 | 6.00 | 3 | V | 286 | 1.74 | - |
| AV | 5.5944G | 98.34 | Inf | -Inf | 6.75 | 3 | V | 286 | 1.74 | - |
| PK | 5.4588G | 62.04 | 74.00 | -11.96 | 5.97 | 3 | V | 286 | 1.74 | - |
| PK | 5.4684G | 62.36 | 74.00 | -11.64 | 6.01 | 3 | V | 286 | 1.74 | - |
| PK | 5.6232G | 108.83 | Inf | -Inf | 6.82 | 3 | V | 286 | 1.74 | - |
| PK | 5.8512G | 59.99 | 119.46 | -59.47 | 7.51 | 3 | V | 286 | 1.74 | - |

## 802.11ac VHT80+80_Nss1,(MCS0)_4TX

## 5530MHz,#5610MHz_TX




20170606
EUT Z_4TX
Setting 58
04-J-6
FSP(100142)
Radio 2

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 11.21718G | 45.72 | 54.00 | -8.28 | 15.70 | 3 | V | 147 | 2.01 | - |
| PK | 11.22366G | 56.80 | 74.00 | -17.20 | 15.70 | 3 | V | 147 | 2.01 | - |

## 802.11ac VHT80+80_Nss1,(MCS0)_4TX

## 5530MHz,#5610MHz_TX




20170606
EUT Z_4TX
Setting 58
04-J-6
FSP(100142)
Radio 2

| Type | Freq(Hz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Factor(dB) | Dist(m) | Pol.(H/V) | Azimuth(°) | Height(m) | Comments |
|---|---|---|---|---|---|---|---|---|---|---|
| AV | 11.22226G | 45.61 | 54.00 | -8.39 | 15.70 | 3 | H | 233 | 2.44 | - |
| PK | 11.22298G | 56.58 | 74.00 | -17.42 | 15.70 | 3 | H | 233 | 2.44 | - |

**Mode: 20 MHz / Port 2**

**Voltage vs. Frequency Stability**

| Voltage | Measurement Frequency (MHz) | | | |
|---|---|---|---|---|
| (V) | 5300 MHz | | | |
| | 0 Minute | 2 Minute | 5 Minute | 10 Minute |
| 126.50 | 5299.9648 | 5299.9646 | 5299.9642 | 5299.9638 |
| 110.00 | 5299.9641 | 5299.9632 | 5299.9631 | 5299.9627 |
| 93.50 | 5299.9633 | 5299.9624 | 5299.9618 | 5299.9614 |
| Max. Deviation (MHz) | 0.0367 | 0.0376 | 0.0382 | 0.0386 |
| Max. Deviation (ppm) | 6.92 | 7.09 | 7.21 | 7.28 |
| Result | Pass | | | |

**Temperature vs. Frequency Stability**

| Temperature | Measurement Frequency (MHz) | | | |
|---|---|---|---|---|
| (℃) | 5300 MHz | | | |
| | 0 Minute | 2 Minute | 5 Minute | 10 Minute |
| 0 | 5299.9613 | 5299.9611 | 5299.9602 | 5299.9595 |
| 10 | 5299.9624 | 5299.9616 | 5299.9607 | 5299.9602 |
| 20 | 5299.9641 | 5299.9631 | 5299.9627 | 5299.9620 |
| 30 | 5299.9959 | 5299.9952 | 5299.9951 | 5299.9947 |
| 40 | 5299.9966 | 5299.9963 | 5299.9956 | 5299.9948 |
| Max. Deviation (MHz) | 0.0425 | 0.0435 | 0.0438 | 0.0446 |
| Max. Deviation (ppm) | 8.02 | 8.21 | 8.26 | 8.42 |
| Result | Pass | | | |

**Voltage vs. Frequency Stability**

| Voltage | Measurement Frequency (MHz) | | | |
|---|---|---|---|---|
| (V) | 5580 MHz | | | |
| | 0 Minute | 2 Minute | 5 Minute | 10 Minute |
| 126.50 | 5579.9642 | 5579.9639 | 5579.9637 | 5579.9629 |
| 110.00 | 5579.9641 | 5579.9640 | 5579.9639 | 5579.9630 |
| 93.50 | 5579.9637 | 5579.9635 | 5579.9629 | 5579.9620 |
| Max. Deviation (MHz) | 0.0363 | 0.0365 | 0.0371 | 0.0380 |
| Max. Deviation (ppm) | 6.51 | 6.54 | 6.65 | 6.81 |
| Result | Pass | | | |

**Temperature vs. Frequency Stability**

| Temperature | Measurement Frequency (MHz) | | | |
|---|---|---|---|---|
| (℃) | 5580 MHz | | | |
| | 0 Minute | 2 Minute | 5 Minute | 10 Minute |
| 0 | 5579.9625 | 5579.9616 | 5579.9610 | 5579.9603 |
| 10 | 5579.9627 | 5579.9623 | 5579.9617 | 5579.9616 |
| 20 | 5579.9641 | 5579.9639 | 5579.9629 | 5579.9620 |
| 30 | 5579.9959 | 5579.9952 | 5579.9947 | 5579.9945 |
| 40 | 5579.9966 | 5579.9959 | 5579.9954 | 5579.9953 |
| Max. Deviation (MHz) | 0.0408 | 0.0415 | 0.0422 | 0.0432 |
| Max. Deviation (ppm) | 7.31 | 7.44 | 7.56 | 7.74 |
| Result | Pass | | | |

**Mode: 40 MHz / Port 2**

**Voltage vs. Frequency Stability**

| Voltage | Measurement Frequency (MHz) | | | |
|---|---|---|---|---|
| (V) | 5310 MHz | | | |
| | 0 Minute | 2 Minute | 5 Minute | 10 Minute |
| 126.50 | 5309.9646 | 5309.9642 | 5309.9636 | 5309.9631 |
| 110.00 | 5309.9641 | 5309.9632 | 5309.9627 | 5309.9626 |
| 93.50 | 5309.9639 | 5309.9638 | 5309.9634 | 5309.9630 |
| Max. Deviation (MHz) | 0.0361 | 0.0368 | 0.0373 | 0.0374 |
| Max. Deviation (ppm) | 6.80 | 6.93 | 7.02 | 7.04 |
| Result | Pass | | | |

**Temperature vs. Frequency Stability**

| Temperature | Measurement Frequency (MHz) | | | |
|---|---|---|---|---|
| (℃) | 5310 MHz | | | |
| | 0 Minute | 2 Minute | 5 Minute | 10 Minute |
| 0 | 5309.9625 | 5309.9616 | 5309.9611 | 5309.9608 |
| 10 | 5309.9633 | 5309.9631 | 5309.9628 | 5309.9621 |
| 20 | 5309.9641 | 5309.9634 | 5309.9624 | 5309.9617 |
| 30 | 5309.9959 | 5309.9955 | 5309.9954 | 5309.9947 |
| 40 | 5309.9975 | 5309.9969 | 5309.9964 | 5309.9955 |
| Max. Deviation (MHz) | 0.0391 | 0.0401 | 0.0407 | 0.0412 |
| Max. Deviation (ppm) | 7.36 | 7.55 | 7.66 | 7.76 |
| Result | Pass | | | |

**Voltage vs. Frequency Stability**

| Voltage | Measurement Frequency (MHz) | | | |
|---|---|---|---|---|
| (V) | 5550 MHz | | | |
| | 0 Minute | 2 Minute | 5 Minute | 10 Minute |
| 126.50 | 5549.9648 | 5549.9646 | 5549.9637 | 5549.9636 |
| 110.00 | 5549.9641 | 5549.9632 | 5549.9622 | 5549.9620 |
| 93.50 | 5549.9638 | 5549.9632 | 5549.9624 | 5549.9619 |
| Max. Deviation (MHz) | 0.0362 | 0.0368 | 0.0378 | 0.0381 |
| Max. Deviation (ppm) | 6.52 | 6.63 | 6.81 | 6.86 |
| Result | Pass | | | |

**Temperature vs. Frequency Stability**

| Temperature | Measurement Frequency (MHz) | | | |
|---|---|---|---|---|
| (℃) | 5550 MHz | | | |
| | 0 Minute | 2 Minute | 5 Minute | 10 Minute |
| 0 | 5549.9617 | 5549.9609 | 5549.9604 | 5549.9600 |
| 10 | 5549.9630 | 5549.9621 | 5549.9617 | 5549.9615 |
| 20 | 5549.9641 | 5549.9635 | 5549.9627 | 5549.9620 |
| 30 | 5549.9959 | 5549.9951 | 5549.9946 | 5549.9936 |
| 40 | 5549.9967 | 5549.9959 | 5549.9949 | 5549.9948 |
| Max. Deviation (MHz) | 0.0424 | 0.0433 | 0.0437 | 0.0443 |
| Max. Deviation (ppm) | 7.64 | 7.80 | 7.87 | 7.98 |
| Result | Pass | | | |

**Mode: 80 MHz / Port 2**

**Voltage vs. Frequency Stability**

| Voltage | Measurement Frequency (MHz) | | | |
|---|---|---|---|---|
| (V) | 5290 MHz | | | |
| | 0 Minute | 2 Minute | 5 Minute | 10 Minute |
| 126.50 | 5289.9650 | 5289.9647 | 5289.9637 | 5289.9631 |
| 110.00 | 5289.9641 | 5289.9632 | 5289.9628 | 5289.9624 |
| 93.50 | 5289.9638 | 5289.9634 | 5289.9632 | 5289.9627 |
| Max. Deviation (MHz) | 0.0362 | 0.0368 | 0.0372 | 0.0376 |
| Max. Deviation (ppm) | 6.84 | 6.96 | 7.03 | 7.11 |
| Result | Pass | | | |

**Temperature vs. Frequency Stability**

| Temperature | Measurement Frequency (MHz) | | | |
|---|---|---|---|---|
| (℃) | 5290 MHz | | | |
| | 0 Minute | 2 Minute | 5 Minute | 10 Minute |
| 0 | 5289.9606 | 5289.9603 | 5289.9597 | 5289.9595 |
| 10 | 5289.9624 | 5289.9622 | 5289.9614 | 5289.9606 |
| 20 | 5289.9641 | 5289.9634 | 5289.9633 | 5289.9628 |
| 30 | 5289.9959 | 5289.9949 | 5289.9939 | 5289.9935 |
| 40 | 5289.9961 | 5289.9952 | 5289.9944 | 5289.9943 |
| Max. Deviation (MHz) | 0.0435 | 0.0438 | 0.0447 | 0.0455 |
| Max. Deviation (ppm) | 8.22 | 8.28 | 8.45 | 8.60 |
| Result | Pass | | | |

**Voltage vs. Frequency Stability**

| Voltage | Measurement Frequency (MHz) | | | |
|---|---|---|---|---|
| (V) | 5530 MHz | | | |
| | 0 Minute | 2 Minute | 5 Minute | 10 Minute |
| 126.50 | 5529.9643 | 5529.9634 | 5529.9632 | 5529.9625 |
| 110.00 | 5529.9641 | 5529.9634 | 5529.9625 | 5529.9622 |
| 93.50 | 5529.9639 | 5529.9637 | 5529.9628 | 5529.9622 |
| Max. Deviation (MHz) | 0.0361 | 0.0366 | 0.0375 | 0.0378 |
| Max. Deviation (ppm) | 6.53 | 6.62 | 6.78 | 6.84 |
| Result | Pass | | | |

**Temperature vs. Frequency Stability**

| Temperature | Measurement Frequency (MHz) | | | |
|---|---|---|---|---|
| (℃) | 5530 MHz | | | |
| | 0 Minute | 2 Minute | 5 Minute | 10 Minute |
| 0 | 5529.9631 | 5529.9621 | 5529.9612 | 5529.9606 |
| 10 | 5529.9635 | 5529.9625 | 5529.9624 | 5529.9619 |
| 20 | 5529.9641 | 5529.9637 | 5529.9629 | 5529.9619 |
| 30 | 5529.9959 | 5529.9953 | 5529.9949 | 5529.9945 |
| 40 | 5529.9967 | 5529.9964 | 5529.9958 | 5529.9957 |
| 50 | 5529.9631 | 5529.9621 | 5529.9612 | 5529.9606 |
| Max. Deviation (MHz) | 0.0411 | 0.0420 | 0.0425 | 0.0435 |
| Max. Deviation (ppm) | 7.43 | 7.59 | 7.69 | 7.87 |
| Result | Pass | | | |