



RSE Co-location Result

Operating Mode	2	Polarization	Horizontal
Operating Function	Normal Link		

Level (dBuV/m) Date: 2016-09-12 Time: 17:58:47

Frequency (MHz)

The graph shows a frequency range from 1000 to 4000 MHz on the x-axis and a level range from 0 to 130 dBuV/m on the y-axis. Two horizontal red lines represent the FCC CLASS-B limits: PK at approximately 85 dBuV/m and AV at approximately 65 dBuV/m. A single data point is visible at 1125 MHz, with a level of approximately 40 dBuV/m, which is well below the AV limit.

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	1124.96	40.75	74.00	-33.25	49.12	3.41	24.76	36.54	168	85 Peak	HORIZONTAL
2	1125.02	34.21	54.00	-19.79	42.58	3.41	24.76	36.54	168	85 Average	HORIZONTAL

RSE Co-location Result

Operating Mode	2	Power Phase	Vertical
Operating Function	Normal Link		

Level (dBuV/m) Date: 2016-09-12 Time: 18:02:57

Frequency (MHz)

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	1124.98	34.47	54.00	-19.53	42.84	3.41	24.76	36.54	116	304 Average	VERTICAL
2	1125.01	41.11	74.00	-32.89	49.48	3.41	24.76	36.54	116	304 Peak	VERTICAL