

迪比通通讯设备有限公司

Shenzhen DBT Telecommunication Technology CO.,LTD



Antenna SPEC				
频率范围 (MHz)	Frequency Range (MHz)	GSM850/900/1800/1900	3G Band1/2/5/8	GNSS
最大增益	Peak Gain(dBi)	850 Gain: -1.8	Band1 Gain: 0.3	GPS: -1.2
		900 Gain: -1.2	Band2 Gain: 0.2	Glomass: -1.8
		1800 Gain: 0.1	Band5 Gain: -1.8	
		1900 Gain: 0.2	Band8 Gain: -1.2	
电压驻波比	VSWR	<1.5 typ. <3.0 at the band edge	<1.5 typ. <3.0 at the band edge	<1.2 typ. <1.5 at the band edge
回波损耗	Return Loss (dB)	<-15 typ. <-7 at the band edge	<-15 typ. <-7 at the band edge	<-25 typ. <-15 at the band edge
极化形式	Polarization	Linear	Linear	Linear
输入阻抗	Input Impedance	50 Ω		
最大输入功率(W)	Maximum Input Power	10W		
材料	Material	FPC		
工作温度	Operation Temperature	-40° C ~ +85° C		
储存温度	Storage Temperature	-40° C ~ +85° C		