



FCC LISTED,
REGISTRATION
NUMBER: 905266

IC LISTED,
REGISTRATION
NUMBER: IC 4621

**CENTRO DE
TECNOLOGÍA DE LAS
COMUNICACIONES, S.A.**

Parque Tecnológico de Andalucía,
c/Severo Ochoa nº 2
29590 Campanillas/ Málaga/ España
Tel. 952 61 91 00 - Fax 952 61 91 13
MÁLAGA, C.I.F. A29 507 456
Registro Mercantil Tomo 1169 Libro 82
Folio 133 Hoja MA3729

TEST REPORT

Report No.: 22541RET

TEST NAME: FCC PART 15.247 TESTING FOR BLUETOOTH RADIO DEVICE

Product : BLUETOOTH STEREO HEADSET
Trade Mark : PHILIPS
Model/type Ref. : VOX150
Manufacturer : PHILIPS PERSONNAL CONNECTIVITY
Requested by : PHILIPS PERSONNAL CONNECTIVITY
Other identification of the product : FCC ID: TF6-VOX150
IC: 135I-VOX150
Prototype
Standard(s) : USA FCC Part 15.247, 15.205, 15.209, 15.109, 15.207
CANADA RSS-210

This test report includes 2 annexes and therefore the total number of pages is 64.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, and must not be reproduced except in full without the written approval of Centro de Tecnología de las Comunicaciones, S.A. (CETECOM).

Date: 2005-07-27	Test operator A. Llamas 	Revised by: Date: J. C. Soler Consultant 	Approved by: Date: A. Rojas Technical Director 	Page: 1 of 8
------------------	--------------------------------	---	---	--------------

INDEX

1. COMPETENCE AND GUARANTEES	3
2. GENERAL CONDITIONS	3
3. CHARACTERISTICS OF THE TEST	3
3.1 TEST REQUESTED.....	3
3.2 REQUIREMENTS AND METHOD.....	3
4. IDENTIFICATION DATA SUPPLIED BY THE APPLICANT.....	4
4.1 APPLICANT.....	4
4.2 REPRESENTATIVE	4
4.3 TEST SAMPLES SUPPLIER.....	4
4.4 IDENTIFICATION OF ITEM/ITEMS TESTED	5
5. USAGE OF SAMPLES, PERIOD OF TESTING AND ENVIRONMENTAL CONDITIONS	5
5.1 USAGE OF SAMPLES	5
5.2 PERIOD OF TESTING	6
5.3 ENVIROMENTAL CONDITIONS.....	6
6. TEST RESULTS	8
7. REMARKS AND COMMENTS.....	8
8. SUMMARY.....	8

ANNEXES

ANNEX A. TEST RESULTS

ANNEX B. PHOTOGRAPHS

1. COMPETENCE AND GUARANTEES

Centro de Tecnología de las Comunicaciones (CETECOM), S.A. is a laboratory with a measurement facility in compliance with the requirements of Section 2.948 of the FCC rules and has been added to the list of facilities whose measurements data will be accepted in conjunction with applications for Certification under Parts 15 or 18 of the Commission's Rules. Registration Number: 905266.

Centro de Tecnología de las Comunicaciones (CETECOM), S.A. is a laboratory with a measurement site in compliance with the requirements of RSS 212, Issue 1 (Provisional) and has been added to the list of filed sites of the Canadian Certification and Engineering Bureau. Reference File Number: IC 4621.

In order to assure the traceability to other national and international laboratories, CETECOM has a calibration and maintenance programme for its measuring equipment.

CETECOM guarantees the reliability of the data presented in this report, which is the result of measurements and tests performed to the item under test on the date and under the conditions stated on the report and is based on the knowledge and technical facilities available at CETECOM at the time of execution of the test.

CETECOM is liable to the client for the maintenance by its personnel of the confidentiality of all information related to the item under test and the results of the test.

2. GENERAL CONDITIONS

1. This report only refers to the item that has undergone the test.
2. This report does not constitute or imply by its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without written approval of CETECOM.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of CETECOM and the Accreditation Bodies.

3. CHARACTERISTICS OF THE TEST

3.1 TEST REQUESTED

Measurements for frequency hopping spread spectrum equipment (Bluetooth) operating in the 2400 MHz -2483.5 MHz band and using, according to FCC Part 15.247.

3.2 REQUIREMENTS AND METHOD

The test has been carried out according to FCC parts 15.33, 15.35, 15.109, 15.207, 15.205, 15.209, 15.247 and the document DA 00-705:"Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems".

The testing was performed according to the procedure in ANSI C63.4. Radiated testing was performed in Cetecom's semi-anechoic chamber. This site has been fully described in a report submitted to the FCC and was accepted in a letter dated July 25, 2002.

The instrumentation used to perform the testing is listed below:

1. Semianechoic Absorber Lined Chamber IR 11. BS.
2. Control Chamber IR 12.BC.
3. Antenna mast EM 1072 NMT.
4. Rotating table EM 1084-4. ON.
5. Multi device controller ETS 2090.
6. Bilog antenna CHASE CBL6111.
7. Antenna tripod EMCO 11968C.
8. Double-ridge Guide Horn antenna 1-18 GHz HP 11966E.
9. Double-ridge Guide Horn antenna 18-40 GHz Agilent 119665J.
10. RF pre-amplifier Miteq JS4-12002600-30-5A.
11. Semianechoic Absorber Lined Chamber IR 11. BS.
12. RF pre-amplifier Miteq AFS5-04001300-15-10P-6.
13. RF pre-amplifier Schaffner CPA 9231.
14. Spectrum analyzer R&S ESIB 26.
15. Spectrum analyzer R&S FSM.
16. Transient limiter. HP 11947A.
17. Line Impedance Stabilization Network (L.I.S.N.) R&S. ESH2-Z5.

4. IDENTIFICATION DATA SUPPLIED BY THE APPLICANT

Identification data in this section has been supplied by the client.

4.1 APPLICANT

Name or Company: PHILIPS PERSONNAL CONNECTIVITY

V.A.T.: -----

Address: Route d'Angers

City: Le Mans, Cedex 9

Postal code: 72081

Country: FRANCE

Telephone: +33243411730

Fax: +33243411745

4.2 REPRESENTATIVE

Name: Mr. Daniel Chaillou

4.3 TEST SAMPLES SUPPLIER

Name or Company: Same as indicated in point 4.1.

Report No.:
22541RET

Date: 2005-07-27

Page: 4 of 8

Samples undergoing test have been selected by: **the client.**

4.4 IDENTIFICATION OF ITEM/ITEMS TESTED

Product: BLUETOOTH STEREO HEADSET

Trade mark: PHILIPS

Model: VOX 150

Manufacturer: PHILIPS PERSONAL CONNECTIVITY

Country of manufacture: ROMANIA

Manufacture site: Data not available

Description: The VOX150, Bluetooth Headset will be used together with phones and other audio devices, which are supporting Bluetooth audio features and Handsfree/Headset profile.

The Headset is usable in office, home and outdoors and vehicle environments. The Headset enables an easy, comfortable, private and secure Handsfree operation of mobile phones and other Bluetooth devices in numerous places.

5. USAGE OF SAMPLES, PERIOD OF TESTING AND ENVIRONMENTAL CONDITIONS

5.1 USAGE OF SAMPLES

Sample M/01 is formed by the following elements:

<u>Control No.</u>	<u>Description</u>	<u>Model</u>	<u>Serial No.</u>	<u>Date of reception</u>
22541/03	Headset Bluetooth	VOX 150	Prototype	05/07/2005

Sample M/02 is formed by the following elements:

<u>Control No.</u>	<u>Description</u>	<u>Model</u>	<u>Serial No.</u>	<u>Date of reception</u>
22541/06	Headset Bluetooth with connector	VOX 150	Prototype	05/07/2005

Sample S/01 is composed of the following elements:

<u>Control No.</u>	<u>Description</u>	<u>Model</u>	<u>Serial No.</u>	<u>Date of reception</u>
22541/03	Headset	BLUE VOX	Prototype	05/07/05
22541/07	AC/DC adapter	AD2880032H-F	Prototype	05/07/05
22541/08	DC-USB wire	---	---	05/07/05

Sample S/02 is composed of the following elements:

<u>Control No.</u>	<u>Description</u>	<u>Model</u>	<u>Serial No.</u>	<u>Date of reception</u>
22541/03	Headset	BLUE VOX	Prototype	05/07/05
22541/08	DC-USB wire	---	---	05/07/05

And the next auxiliary element:

<u>Control No.</u>	<u>Description</u>	<u>Model</u>	<u>Serial No.</u>	<u>Date of reception</u>
---	Portable PC (Property of Cetecom)	Armada E500	AE5P3500T 2S6DM6458	05/07/05

1. Sample M/01 has undergone following test(s).
Radiated measurements indicated in annex A.
2. Sample M/02 has undergone following test(s).
All tests indicated in annex A, except radiated measurements.
3. Samples S/01 and S/02 has undergone to the following test(s):
AC Line continuous conducted emission, power leads in annex A.

5.2 PERIOD OF TESTING

The performed test started on 2005-07-05 and finished on 2005-07-06.

The tests as detailed in this report have been performed at CETECOM.

5.3 ENVIROMENTAL CONDITIONS

In the control chamber the following limits were not exceeded during the test:

Temperature	Min. = 24 °C Max. = 24 °C
Relative humidity	Min. = 48 % Max. = 48 %
Shielding effectiveness	> 100 dB
Electric insulation	> 10 kΩ
Reference resistance to earth	< 0,5 Ω

In the semianechoic chamber (21 meters x 11 meters x 8 meters) the following limits were not exceeded during the test.

Temperature	Min. = 22 °C Max. = 22 °C
Relative humidity	Min. = 52 % Max. = 52 %
Air pressure	Min. = 1019 mbar Max. = 1019 mbar
Shielding effectiveness	> 100 dB
Electric insulation	> 10 k Ω
Reference resistance to earth	< 0,5 Ω
Normal site attenuation (NSA)	< ± 4 dB at 10 m distance between item under test and receiver antenna, (30 MHz to 1000 MHz)
Field homogeneity	More than 75% of illuminated surface is between 0 and 6 dB (26 MHz to 1000 MHz).

In the chamber for conducted measurements the following limits were not exceeded during the test:

Temperature	Min. = 22 °C Max. = 22 °C
Relative humidity	Min. = 47 % Max. = 47 %
Air pressure	Min. = 1020 mbar Max. = 1020 mbar
Shielding effectiveness	> 100 dB
Electric insulation	> 10 k Ω
Reference resistance to earth	< 0,5 Ω

6. TEST RESULTS

Abbreviations used in the VERDICT column of the following tables are:

P	Pass
F	Fail
NA	not applicable
NM	not measured

FCC PART 15 PARAGRAPH	VERDICT			
	NA	P	F	NM
15.247 Subclause (a) (1). 20 dB Bandwidth and Carrier frequency separation		P		
15.247 Subclause (a) (1) (iii). Number of hopping channels		P		
15.247 Subclause (a) (1) (iii). Time of occupancy (Dwell Time)		P		
15.247 Subclause (b). Maximum peak output power and antenna gain		P		
15.247 Subclause (d). Band-edge of conducted emissions (Transmitter)		P		
15.247 Subclause (d). Emission limitations conducted (Transmitter)		P		
15.247 Subclause (d). Emission limitations radiated (Transmitter)		P		
15.109. Receiver spurious radiation		P		
15.207. Continuous Conducted Emissions		P		

7. REMARKS AND COMMENTS

None.

8. SUMMARY

Based on the results of the performed test, stated in annex A the item under test is **IN COMPLIANCE** with the specifications listed in section 3.1 “TEST REQUESTED”.

NOTE: The results presented in this Test Report apply only to the particular item under test declared in section 4.4 “IDENTIFICATION OF ITEM/ITEMS TESTED” of this document, as presented for test on the date(s) declared in section 5, “USAGE OF SAMPLES, PERIOD OF TESTING AND ENVIRONMENTAL CONDITIONS”.

Report No.: 22541RET		Page: 8 of 8
Date: 2005-07-27		

ANNEX A

TEST RESULTS

Report No: 22541RET

Report No:
22541RET

Date: 2005-07-27

Page: 1 of 49

Annex A

INDEX

	Page
TEST CONDITIONS	3
Section 15.247 Subclause (a) (1). 20 dB Bandwidth and Carrier frequency separation....	4
Section 15.247 Subclause (a) (1) (iii). Number of hopping channels	9
Section 15.247 Subclause (a) (1) (iii). Time of occupancy (Dwell Time)	11
Section 15.247 Subclause (b). Maximum peak output power and antenna gain.....	12
Section 15.247 Subclause (d). Band-edge of conducted emissions (Transmitter)	18
Section 15.247 Subclause (d). Emission limitations conducted (Transmitter).....	22
Section 15.247 Subclause (d). Emission limitations radiated (Transmitter)	25
Section 15.109. Receiver spurious radiation	37
Section 15.207. Continuous Conducted Emission	43

Report No: 22541RET		Page: 2 of 49
Date: 2005-07-27		Annex A

TEST CONDITIONS

Power supply (V):

$$V_{\text{nominal}} = 3.7 \text{ Vdc}$$

Type of power supply = Rechargeable battery

Type of antenna = Integral antenna

Maximum Declared Gain for antenna= 0 dB

Operating Temperature Range (°C):

$$T_n = 0 \text{ to } + 35$$

TEST FREQUENCIES:

Lowest channel: 2402 MHz

Middle channel: 2441 MHz

Highest channel: 2480 MHz

The test set-up was made in accordance to the general provisions of ANSI C63.4.

CONDUCTED MEASUREMENTS

The equipment under test was set up in a shielded room and it is directly connected to the spectrum analyser via the antenna connector (sma type) provided with the test sample. No coaxial low-loss connecting cable was necessary for such connection so no cable attenuation correction was made.

RADIATED MEASUREMENTS

All radiated tests were performed in a semi-anechoic chamber. The measurement antenna is situated at a distance of 3 m for the frequency range 30 MHz-1000 MHz (30 MHz-1000 MHz Bilog antenna) and at a distance of 1m for the frequency range 1 GHz-25 GHz (1 GHz-18 GHz Double ridge horn antenna and 18 GHz-40 GHz horn antenna).

For radiated emissions in the range 1 GHz-25 GHz that is performed at a distance closer than the specified distance, an inverse proportionality factor of 20 dB per decade is used to normalize the measured data for determining compliance.

Report No: 22541RET		Page: 3 of 49
Date: 2005-07-27		Annex A

Section 15.247 Subclause (a) (1). 20 dB Bandwidth and Carrier frequency separation

SPECIFICATION

Frequency hopping system shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.


RESULTS

20 dB Bandwidth (see next 3 plots).

	Lowest frequency 2402 MHz	Middle frequency 2441 MHz	Highest frequency 2480 MHz
20 dB Spectrum bandwidth (kHz)	833.67	833.67	837.68
Measurement uncertainty (kHz)	±11		

20 dB BANDWIDTH.

Lowest Channel: 2402 MHz.



Report No:
22541RET


Date: 2005-07-27

Page: 5 of 49

Annex A

20 dB BANDWIDTH.

Middle Channel: 2441 MHz.



Report No:
22541RET


Date: 2005-07-27

Page: 6 of 49

Annex A

20 dB BANDWIDTH.

Highest Channel: 2480 MHz.




Report No:
22541RET

Date: 2005-07-27

Page: 7 of 49

Annex A

Carrier frequency separation (see next plot).



The hopping channel carrier frequencies are separated by a minimum of the 20 dB bandwidth of the hopping channel.

Verdict: PASS

Report No:
22541RET

Date: 2005-07-27

FET45_00.DOC

Page: 8 of 49

Annex A


Section 15.247 Subclause (a) (1) (iii). Number of hopping channels

SPECIFICATION

Frequency hopping system in the 2400-2483.5 MHz band shall use at least 15 non-overlapping channels.


RESULTS

The number of hopping channels is 79 (see next two plots).



Number of hopping frequencies: 39

Report No: 22541RET		Page: 9 of 49
Date: 2005-07-27		Annex A



Date: 6.JUL.2005 08:35:10

Number of hopping frequencies: 40

Total number of hopping frequencies: 79

Verdict: PASS

Report No:
22541RET

Date: 2005-07-27

Page: 10 of 49

Annex A

Section 15.247 Subclause (a) (1) (iii). Time of occupancy (Dwell Time)

SPECIFICATION

The average time of occupancy on any channel shall not be greater than 0.4 seconds (400 ms) within a period of 0.4 seconds multiplied by the number of hopping channels employed = $0.4 \times 79 = 31.6$ seconds.

RESULTS


Note: The EUT only supports packet type DH1.

1. TIME OF OCCUPANCY (DWELL TIME) FOR PACKET TYPE DH1.

The system makes worst case 1600 hops per second or 1 time slot has a length of $625\mu\text{s}$ with 79 channels. A DH1 Packet need 1 time slot for transmitting and 1 time slot for receiving. Then the system makes worst case $1600/2 = 800$ hops per second with 79 channels. So you have each channel $800/79 = 10.13$ times per second and so for a period of $0.4 \times 79 = 31.6$ seconds you have $10.13 \times 31.6 = 320.11$ times of appearance.

Each Tx-time per appearance is $448.90\mu\text{s}$ (see next plot).

So we have $320.11 \times 448.90\mu\text{s} = 143.70\text{ ms}$ per 31.6 seconds.



Date: 6.JUL.2005 08:37:36

Verdict: PASS

Report No: 22541RET		Page: 11 of 49
Date: 2005-07-27		Annex A

Section 15.247 Subclause (b). Maximum peak output power and antenna gain**SPECIFICATION**

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 hopping channels: 1 watt (30 dBm).

RESULTS

MAXIMUM PEAK OUTPUT POWER (CONDUCTED). See next plots.

	Lowest frequency 2402 MHz	Middle frequency 2441 MHz	Highest frequency 2480 MHz
Maximum peak power (dBm)	2.24	2.03	1.18
Measurement uncertainty (dB)	±1.5		

The maximum declared antenna gain for this device is 0 dBi, therefore the maximum theoretical peak radiated power (EIRP) in the three measurement channels for this device is 2.24 dBm or 1.67 mW.

The actual peak radiated power (EIRP) was measured for the lowest, middle and highest frequency (see next plots):

MAXIMUM PEAK OUTPUT POWER (RADIATED).

	Lowest frequency 2402 MHz	Middle frequency 2441 MHz	Highest frequency 2480 MHz
Correction Factor (dB)	34.96	35.10	35.24
Maximum EIRP peak power (dBm)	2.85	2.79	3.02
Measurement uncertainty (dB)	+1.98 / -1.75		

Declared peak gain: 0 dBi


The maximum directional gain of the antenna is less than 6 dBi and therefore the maximum output power is not required to be reduced from the stated values.

Verdict: PASS

Report No: 22541RET		Page: 12 of 49
Date: 2005-07-27		Annex A

PEAK OUTPUT POWER (CONDUCTED).

Lowest Channel: 2402 MHz.



Report No:
22541RET


Date: 2005-07-27

Page: 13 of 49

Annex A

PEAK OUTPUT POWER (CONDUCTED).

Middle Channel: 2441 MHz.



Report No:
22541RET


Date: 2005-07-27

Page: 14 of 49

Annex A

PEAK OUTPUT POWER (CONDUCTED).

Highest Channel: 2480 MHz.



Report No:
22541RET


Date: 2005-07-27

Page: 15 of 49

Annex A


PEAK OUTPUT POWER (RADIATED).

Lowest Channel: 2402 MHz.



PEAK OUTPUT POWER (RADIATED).

Middle Channel: 2441 MHz.



Report No:
22541RET


Date: 2005-07-27

Page: 16 of 49

Annex A

PEAK OUTPUT POWER (RADIATED).

Highest Channel: 2480 MHz.



Report No:
22541RET

Date: 2005-07-27

Page: 17 of 49

Annex A


Section 15.247 Subclause (d). Band-edge of conducted emissions (Transmitter)

SPECIFICATION

Emissions outside the frequency band in which the intentional radiator is operating shall be at least 20dB below the highest level of the desired power.

RESULTS:


1. LOW FREQUENCY SECTION 2402 MHz (HOPPING OFF). See next plot.



Verdict: PASS


Report No: 22541RET		Page: 18 of 49
Date: 2005-07-27		Annex A

2. HIGH FREQUENCY SECTION 2480 MHz (HOPPING OFF). See next plot.



Report No: 22541RET		Page: 19 of 49
Date: 2005-07-27		Annex A

3. LOW FREQUENCY SECTION (HOPPING ON). See next plot.



Verdict: PASS


Report No:
22541RET

Date: 2005-07-27

Page: 20 of 49

Annex A

4. HIGH FREQUENCY SECTION (HOPPING ON). See next plot.



Verdict: PASS

Report No:
22541RET

Date: 2005-07-27

FET45_00.DOC

Page: 21 of 49

Annex A


Section 15.247 Subclause (d). Emission limitations conducted (Transmitter)

SPECIFICATION

In any 100 kHz bandwidths outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

RESULTS:

1. LOWEST CHANNEL (2402 MHz): 30 MHz-25 GHz (see next plot).




Note: The peak above the limit is the carrier frequency.

Verdict: PASS

Report No: 22541RET		Page: 22 of 49
Date: 2005-07-27		Annex A

2. MIDDLE CHANNEL (2441 MHz): 30 MHz-25 GHz (see next plot).




Note: The peak above the limit is the carrier frequency.

Verdict: PASS

Report No: 22541RET		Page: 23 of 49
Date: 2005-07-27		Annex A

3. HIGH CHANNEL (2480 MHz): 30 MHz-25 GHz (see next plot).



Note: The peak above the limit is the carrier frequency.

Verdict: PASS

Report No: 22541RET		Page: 24 of 49
Date: 2005-07-27		Annex A

Section 15.247 Subclause (d). Emission limitations radiated (Transmitter)**SPECIFICATION**

Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)):

Frequency Range (MHz)	Field strength (µV/m)	Field strength (dBµV/m)	Measurement distance (m)
0.009-0.490	2400/F(kHz)	-	300
0.490-1.705	24000/F(kHz)	-	300
1.705 - 30.0	30	-	30
30 - 88	100	40	3
88 - 216	150	43.5	3
216 - 960	200	46	3
960 - 25000	500	54	3

The emission limits shown in the above table are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

For average radiated emission measurements above 1000 MHz, there is also a limit corresponding to 20 dB above the indicated values in the table is specified when measuring with peak detector function.

RESULTS:

The situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

All tests were performed in a semi-anechoic chamber at a distance of 3 m for the frequency range 30 MHz-1000 MHz and at distance of 1m for the frequency range 1 GHz-25 GHz.

The field strength is calculated by adding correction factor to the measured level from the spectrum analyser. This correction factor includes antenna factor, cable loss and pre-amplifiers gain.

The equipment transmits continuously in the selected channel so it is not necessary a duty cycle correction factor.

Report No: 22541RET		Page: 25 of 49
Date: 2005-07-27		Annex A

1. CHANNEL: LOWEST (2402 MHz).

Frequency range 30 MHz-1000 MHz. Spurious levels (radiated) closest to limit.

No Spurious signals were found in all the range.

Frequency range 1 GHz-25 GHz.

Spurious frequency (MHz)	Polarization	Detector	Emission Level (dB μ V/m)	Measurement Uncertainty (dB)
4804.100	V	Peak	42.30	± 4.0
4804.100	V	Average	37.48	± 4.0
9608.1333	V	Peak	55.81	± 4.0
9608.1333	V	Average	50.80	± 4.0
14411.994	V	Peak	46.21	± 4.0
14411.994	V	Average	41.00	± 4.0

Additionally, no spurious signals were found inside the restricted bands 2310-2390 MHz and 2483.5-2500 MHz.

2. CHANNEL: MIDDLE (2441 MHz).

Frequency range 30 MHz-1000 MHz. Spurious levels (radiated) closest to limit.

No spurious signals were found in all the range

Frequency range 1 GHz-25 GHz.

Spurious frequency (MHz)	Polarization	Detector	Emission Level (dB μ V/m)	Measurement Uncertainty (dB)
9764.225	V	Peak	56.62	± 4.0
9764.225	V	Average	53.74	± 4.0
14645.9369	V	Peak	44.67	± 4.0
14645.9369	V	Average	39.67	± 4.0

Additionally, no spurious signals were found inside the restricted bands 2310-2390 MHz and 2483.5-2500 MHz.

Report No: 22541RET		Page: 26 of 49
Date: 2005-07-27		Annex A

3. CHANNEL: HIGHEST (2480 MHz).

Frequency range 30 MHz-1000 MHz. Spurious levels (radiated) closest to limit.

No spurious signals were found in all the range.


Frequency range 1 GHz-25 GHz.

Spurious frequency (MHz)	Polarization	Detector	Emission Level (dB μ V/m)	Measurement Uncertainty (dB)
9920.000	V	Peak	54.34	± 4.0
9920.000	V	Average	52.27	± 4.0
14879.7745	V	Peak	44.62	± 4.0
14879.7745	V	Average	39.08	± 4.0

Additionally, no spurious signals were found inside the restricted bands 2310-2390 MHz and 2483.5-2500 MHz.

Verdict: PASS

FREQUENCY RANGE 30 MHz-1000 MHz.




(This plot is valid for all three channels).

Report No: 22541RET		Page: 28 of 49
Date: 2005-07-27		Annex A


FREQUENCY RANGE 1 GHz to 2.9 GHz.

CHANNEL: Lowest (2402 MHz).



Note: The peak above the limit is the carrier frequency.

CHANNEL: Middle (2441 MHz).



Note: The peak above the limit is the carrier frequency.


Report No:
22541RET

Date: 2005-07-27

Page: 29 of 49

Annex A

CHANNEL: Highest (2480 MHz).



Note: The peak above the limit is the carrier frequency.

Report No:
22541RET


Date: 2005-07-27

Page: 30 of 49


Annex A

FREQUENCY RANGE 2.9 GHz to 12.75 GHz.

CHANNEL: Lowest (2402 MHz).



CHANNEL: Middle (2441 MHz).



Report No:
22541RET


Date: 2005-07-27

FET45_00.DOC

Page: 31 of 49

Annex A

CHANNEL: Highest (2480 MHz).



Report No:
22541RET


Date: 2005-07-27

Page: 32 of 49

Annex A

FREQUENCY RANGE 12.75 GHz to 18 GHz.

CHANNEL: Lowest (2402 MHz).




Report No:
22541RET

Date: 2005-07-27

Page: 33 of 49

Annex A

CHANNEL: Middle (2441 MHz).




Report No:
22541RET

Page: 34 of 49

Date: 2005-07-27

Annex A

CHANNEL: Highest (2480 MHz).




Report No:
22541RET

Date: 2005-07-27

Page: 35 of 49

Annex A

FREQUENCY RANGE 18 GHz to 25 GHz.



(This plot is valid for all three channels).

Report No: 22541RET		Page: 36 of 49
Date: 2005-07-27		Annex A

Section 15.109. Receiver spurious radiation**SPECIFICATION**

The field strength shall not exceed the following values:

Frequency Range (MHz)	Field strength ($\mu\text{V/m}$)	Field strength ($\text{dB}\mu\text{V/m}$)	Measurement distance (m)
0.009-0.490	$2400/F(\text{kHz})$	-	300
0.490-1.705	$24000/F(\text{kHz})$	-	300
1.705 - 30.0	30	-	30
30 – 88	100	40	3
88 – 216	150	43.5	3
216 – 960	200	46	3
960 – 25000	500	54	3

The emission limits shown in the above table are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

For average radiated emission measurements above 1000 MHz, there is also a limit corresponding to 20 dB above the indicated values in the table is specified when measuring with peak detector function.

RESULTS:

The situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

All tests were performed in a semi-anechoic chamber at a distance of 3 m for the frequency range 30 MHz-1000 MHz and at distance of 1m for the frequency range 1 GHz-25 GHz.

The field strength is calculated by adding correction factor to the measured level from the spectrum analyser. This correction factor includes antenna factor, cable loss and pre-amplifiers gain.

Report No: 22541RET		Page: 37 of 49
Date: 2005-07-27		Annex A

1. CHANNEL: LOWEST (2402 MHz).

Frequency range 30 MHz-1000 MHz.

No spurious signals were found in all the range.

Frequency range 1 GHz-25 GHz.

No spurious signals were found in all the range.

Additionally, no spurious signals were found inside the restricted bands 2310-2390 MHz and 2483.5-2500 MHz.

2. CHANNEL: MIDDLE (2441 MHz).

Frequency range 30 MHz-1000 MHz.

No spurious signals were found in all the range.

Frequency range 1 GHz-25 GHz.

No spurious signals were found in all the range.

Additionally, no spurious signals were found inside the restricted bands 2310-2390 MHz and 2483.5-2500 MHz.

3. CHANNEL: HIGHEST (2480 MHz).

Frequency range 30 MHz-1000 MHz.

No spurious signals were found in all the range.

Frequency range 1 GHz-25 GHz.


No spurious signals were found in all the range.

Additionally, no spurious signals were found inside the restricted bands 2310-2390 MHz and 2483.5-2500 MHz.

Verdict: PASS.

Report No: 22541RET		Page: 38 of 49
Date: 2005-07-27		Annex A

FREQUENCY RANGE 30 MHz-1000 MHz.




Date: 5.JUL.2005 08:33:57

(This plot is valid for all three channels)

Report No: 22541RET		Page: 39 of 49
Date: 2005-07-27		Annex A

FREQUENCY RANGE 1 GHz-12.75 GHz.



(This plot is valid for all three channels)


Report No:
22541RET

Date: 2005-07-27

Page: 40 of 49

Annex A


FREQUENCY RANGE 12.75 GHz-18 GHz.



(This plot is valid for all three channels).

Report No: 22541RET		Page: 41 of 49
Date: 2005-07-27		Annex A

FREQUENCY RANGE 18 GHz-25 GHz.



Date: 5.JUL.2005 12:49:00

(This plot is valid for all three channels)

Report No: 22541RET		Page: 42 of 49
Date: 2005-07-27		Annex A

Section 15.207. Continuous Conducted Emission**SPECIFICATION**

The radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table:

Frequency range (MHz)	Limit (dBμV)	
	Quasi-peak	Average
0,15 to 0,5	66-56	56-46
0,5 to 5	56	46
5 to 30	60	50

OPERATING MODES OF EUT**Different tested operating modes (OM)**

- OM#02: EUT ON. Changing batteries. Linked with auxiliary GSM phone and call established with Radio Communication Tester.

TEST RESULTS

CCmmnnxx: CC, Conduction condition°; mm: sample number; nn: operation mode; xx: wire.

On the sample S/01

- OM#02.

CDmmnnxx	Description	Result
CC01020N	Interference voltage on Neutral wire	PASS
CC0102L1	Interference voltage on phase wire	PASS

On the sample S/02

- OM#02.

CDmmnnxx	Description	Result
CC02020N	Interference voltage on Neutral wire	PASS
CC0202L1	Interference voltage on phase wire	PASS

Report No: 22541RET		Page: 43 of 49
Date: 2005-07-27		Annex A


Continuous conducted emission: CC01020N (Peak and Average)

EMC32 Report

Test Information

Proyecto:	22541iem.001
Empresa:	PHILIPS
Muestra:	M/01
Modo operacion:	MO#02
Fecha:	2005-07-06 15:28
Setup:	EMI conducted
Mode:	EUT ON. Communication mode. Charging batteries. Neutral noise.

EC FCC Clase B ESIB26 CC



Report No:
22541RET

Date: 2005-07-27

FET45_00.DOC

Page: 44 of 49

Annex A


Continuous conducted emission: CC01020N (Quasi-Peak)

EMC32 Report

Test Information

Proyecto:	22541iem.001
Empresa:	PHILIPS
Muestra:	M/01
Modo operacion:	MO#02
Fecha:	2005-07-06 15:29
Setup:	EMI conducted
Mode:	EUT ON. Communication mode. Charging batteries. Neutral noise.

EC FCC Clase B ESIB26 CC



Report No:
22541RET

Date: 2005-07-27

FET45_00.DOC

Page: 45 of 49

Annex A


Continuous conducted emission: CC0102L1 (Peak and Average)

EMC32 Report

Test Information

Proyecto:	22541iem.001
Empresa:	PHILIPS
Muestra:	M/01
Modo operacion:	MO#02
Fecha:	2005-07-06 15:35
Setup:	EMI conducted
Mode:	EUT ON. Communication mode. Charging batteries. Phase noise.

EC FCC Clase B ESIB26 CC



Report No:
22541RET

Date: 2005-07-27

Page: 46 of 49

Annex A


Continuous conducted emission: CC0102L1 (Quasi-Peak)

EMC32 Report

Test Information

Proyecto:	22541iem.001
Empresa:	PHILIPS
Muestra:	M/01
Modo operacion:	MO#02
Fecha:	2005-07-27 11:36
Setup:	EMI conducted
Mode:	EUT ON. Communication mode. Charging batteries. Phase noise.

EC FCC Clase B ESIB26 CC



Report No:
22541RET

Date: 2005-07-27

FET45_00.DOC

Page: 47 of 49

Annex A


Continuous conducted emission: CC02020N (Peak and Average)

EMC32 Report

Test Information

Proyecto:	22541iem.001
Empresa:	PHILIPS
Muestra:	M/02
Modo operacion:	MO#02
Fecha:	2005-07-05 18:45
Setup:	EMI conducted
Mode:	EUT ON. Communication mode. Charging batteries. Neutral noise.

EC FCC Clase B ESIB26 CC



Report No:
22541RET

Date: 2005-07-27

FET45_00.DOC

Page: 48 of 49

Annex A


Continuous conducted emission: CC0202L1 (Peak and Average)

EMC32 Report

Test Information

Proyecto:	22541iem.001
Empresa:	PHILIPS
Muestra:	M/02
Modo operacion:	MO#02
Fecha:	2005-07-05 18:40
Setup:	EMI conducted
Mode:	EUT ON. Communication mode. Charging batteries. Phase noise.

EC FCC Clase B ESIB26 CC



Report No:
22541RET

Date: 2005-07-27

FET45_00.DOC

Page: 49 of 49

Annex A

ANNEX B

PHOTOGRAPHS **(Number of photographs: 6)**

Report No.: 22541RET

Report No.:
22541RET

Date: 2005-07-27

Page: 1 of 7

Annex B

1. Equipment (external view)



Report No.:
22541RET

Date: 2005-07-27

Page: 2 of 7

Annex B

2. Equipment for conducted measurements.



Report No.:
22541RET


Date: 2005-07-27

FET18_00.DOC

Page: 3 of 7

Annex B

3. General test set-up for radiated measurements.



Report No.:
22541RET


Date: 2005-07-27

FET18_00.DOC


Page: 4 of 7

Annex B


4. Test set-up for radiated measurements below 1 GHz.



5. Test set-up for radiated measurements above 1 GHz.



6. Test set-up for RF conducted measurements.



Report No.:
22541RET

Date: 2005-07-27

FET18_00.DOC

Page: 7 of 7

Annex B