

## ODYSSEY 2.4G DIODE LASER

POWER INPUT: 100-240V ~ 50-60HZ 1.5A  
WORKING BEAM WAVELENGTH: 810±10 NM  
810 NM POWER OUTPUT: 5 WATTS  
AIMING BEAM WAVELENGTH: 650±30 NM  
650 NM POWER OUTPUT: 3 MILLIWATTS  
WIRELESS FREQUENCY: 2.4 GHz  
FUSE: T2A / 250V  
MODEL: 595126  
MANUF DATE: MMM YYYY  
SERIAL: XXXXXX

MANUFACTURED FOR:  
IVOCLAR VIVADENT, INC.  
175 PINEVIEW DR.  
AMHERST, NY 14228  
ASSEMBLED IN USA



FCCID: TFIODYSSEY24G  
IC: 5810A-ODYSSEY 2.4G



COMPLIES WITH:  
21 CFR 1040.10 & 1040.11 EXCEPT FOR DEVIATIONS  
PURSUANT TO LASER NOTICE 50,  
DATED JULY 26, 2001

ALSO COMPLIES WITH  
IEC 60601-1:1998+A1; IEC 60601-2-22:1995;  
IEC 60825-1:1993+A1+A2

*This device complies with Part 15 of the FCC Rules.*

*Operation is subject to the following two conditions:*

- (1) This device may not cause harmful interference, and*
- (2) this device must accept any interference received, including interference that may cause undesired operation.*

PATENTS PENDING