



APPENDIX I RADIO FREQUENCY EXPOSURE

LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

EUT Specification

EUT	PIN Pad 791		
Model	PP791		
RF Module	Realtek	Model:	RTL8723BU
Model Discrepancy	N/A		
Frequency band (Operating)	☒ Bluetooth 2.1 + EDR / 4.0: 2402 ~ 2480 MHz 802.11b/g/n HT20: 2.412GHz ~ 2.462GHz 802.11n HT40: 2.422GHz ~ 2.452GHz ☐ Others		
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation) ☐ Others		
Exposure classification	☐ Occupational/Controlled exposure (S = 5mW/cm ²) ☒ General Population/Uncontrolled exposure (S=1mW/cm ²)		
Antenna Specification	2.4GHz: Antenna Gain : 2.31 dBi (Numeric gain 1.70)		
Maximum Average output power	Bluetooth Mode : 6.03 dBm (4.009 mW) IEEE 802.11b Mode: 17.90 dBm (61.660 mW) IEEE 802.11g Mode: 16.01 dBm (39.902 mW) IEEE 802.11n HT 20 Mode: 16.18 dBm (41.495 mW) IEEE 802.11n HT 40 Mode: 15.36 dBm (34.356 mW)		
Maximum Tune up Power	Bluetooth Mode : 7.00 dBm (5.012 mW) IEEE 802.11b Mode: 19.00 dBm (79.433 mW) IEEE 802.11g Mode: 17.00 dBm (50.119 mW) IEEE 802.11n HT 20 Mode: 17.00 dBm (50.119 mW) IEEE 802.11n HT 40 Mode: 16.00 dBm (39.811 mW)		
Evaluation applied	☒ MPE Evaluation* ☐ SAR Evaluation ☐ N/A		



Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	2015/5/13	Initial Issue	ALL	Kelly Cheng



TEST RESULTS

No non-compliance noted.

Calculation

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{377}$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \textbf{Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

**Maximum Permissible Exposure**

Substituting the MPE safe distance using $d = 20$ cm into Equation 1:

$$S = 0.000199 \times P \times G$$

Where P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

Bluetooth mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
79	2480	5.012	1.7	20	0.0017	1

IEEE 802.11b mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
11	2462	79.433	1.7	20	0.0269	1

IEEE 802.11g mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
6	2437	50.119	1.7	20	0.0170	1

IEEE 802.11n HT20 mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
6	2437	50.119	1.7	20	0.0170	1

IEEE 802.11n HT40 mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
3	2422	39.811	1.7	20	0.0135	1