China

10 Appendix A - General Product Information

Radiofrequency radiation exposure evaluation

This exposure evaluation is intended for **FCC ID: TFOR5GPS**

According to KDB 447498 D01v06 section 4.3.1, For frequencies between 100 MHz to 6GHz and test separation distances ≤ 50 mm, the Numeric threshold is determined as:

Step a)
[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)] · [√f(GHz)] ≤ 3.0 for 1-g SAR

>> The fundamental frequency of the EUT is 2402-2480MHz,
the test separation distance is ≤ 50mm.
(Manufacturer specified the separation distance is: 5mm)
(5mm is the worst case according to the KDB)

Step b)
>> Numeric threshold (2402MHz), mW / 5mm * √2.402GHz ≤ 3.0
Numeric threshold (2402MHz) ≤ 9.678mW

>> Numeric threshold (2440MHz), mW / 5mm * √2.440GHz ≤ 3.0
Numeric threshold (2440MHz) ≤ 9.602mW

>> Numeric threshold (2480MHz), mW / 5mm * √2.480GHz ≤ 3.0
Numeric threshold (2480MHz) ≤ 9.525mW

>> The power (measured + tune up tolerance) of EUT at 2402MHz is: 3.27dBm = 2.12mW
The power (measured + tune up tolerance) of EUT at 2440MHz is: 3.57dBm = 2.28mW
The power (measured + tune up tolerance) of EUT at 2480MHz is: 3.80dBm = 2.40mW

Which is smaller than the Numeric threshold.
Therefore, the device is exempt from stand-alone SAR test requirements.

Reviewed by:

Eric LI
EMC Project Manager

Prepared by:

Hosea CHAN
EMC Project Engineer