

1X

FCC ID TGD10300 / IC 6120A-10300
This device complies with Part 15 of the FCC rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

R293S die = 0.75 x 1.5

2X

FCC ID TGD10300 / IC 6120A-10300
This device complies with Part 15 of the FCC rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

R293S die = 0.75 x 1.5

NOTES:
Mfg.: SixB Labels — #R293S
UL and CSA approved clear polyester face stock.
High performance solvent-based acrylic adhesive.
Service Temp. Range: -65°F to +302°F (-40° C to +150° C).
Sans Serif Font 6 points.
Black Ink.

E N E R N E T Corporation
307 Dewittshire Road
Syracuse, New York 13214
(315) 449-0839 VOICE (315) 449-3056 FAX

T9000 P/N 103 FCC/IC Label

SCALE:	1X = 1:1 / 2X = 2:1	DRAWING NO.:	06006-01
DATE:	08-10-05	DRAWN BY:	B.J. Hesse
DESIGN BY:	B.J. Hesse	FILE:	'products\thermostat\drawings\enclosure\encl