

Test Report

Report Number:

F172251E3

Equipment under Test (EUT):
Handheld Density Meter
DensitoPro

Applicant:

Mettler-Toledo GmbH

Manufacturer:

Mettler-Toledo GmbH



Deutsche
Akkreditierungsstelle
D-PL-17186-01-01
D-PL-17186-01-02
D-PL-17186-01-03


References

- [1] **ANSI C63.10: 2013** American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
- [2] **FCC CFR 47 Part 15** Radio Frequency Devices
- [3] **RSS-210 Issue 9 (August 2016)** Licence-exempt Radio Apparatus (All Frequency Bands): Category I Equipment
- [4] **RSS-Gen Issue 4 (November 2014)** General Requirements for Compliance of Radio Apparatus

Test result

The requirements of the tests performed as shown in the overview (clause 4) **were fulfilled** by the equipment under test.

The complete test results are presented in the following.

Tested and written by:	Michael DINTER		26.01.2018
	Name	Signature	Date
Authorized reviewer:	Bernd STEINER		26.01.2018
	Name	Signature	Date

This test report is only valid in its original form.

Any reproduction of its contents in extracts without written permission of the accredited test laboratory PHOENIX TESTLAB GmbH is prohibited.

The test results herein refer only to the tested sample. PHOENIX TESTLAB GmbH is not responsible for any generalisations or conclusions drawn from these test results concerning further samples. Any modification of the tested samples is prohibited and leads to the invalidity of this test report. Each page necessarily contains the PHOENIX TESTLAB Logo and the TEST REPORT NUMBER.

Contents:	Page
1 Identification	4
1.1 Applicant	4
1.2 Manufacturer	4
1.3 Test Laboratory	4
1.4 EUT (Equipment Under Test)	5
1.5 Technical data of equipment.....	5
1.6 Ancillary equipment used for test.....	6
1.7 Dates.....	6
2 Operational states and test setup.....	6
3 Additional information.....	7
4 Overview	7
5 Results	8
5.1 Conducted emission measurement on ac mains (150 kHz to 30 MHz)	8
5.1.1 Method of measurement conducted emission.....	8
5.1.2 Test result (conducted emission measurement on AC mains).....	9
5.2 Radiated emissions	10
5.2.1 Method of measurement (radiated emissions)	10
5.2.2 Results preliminary measurement 9 kHz to 1 GHz.....	17
5.2.3 Result final measurement from 9 kHz to 30 MHz	20
5.2.4 Result final measurement from 30 MHz to 1 GHz	21
5.3 99 % bandwidth	23
5.3.1 Method of measurement	23
5.3.2 Test results	24
6 Test equipment.....	25
7 Report history	26
8 List of annexes	26

1 Identification

1.1 Applicant

Name:	Mettler-Toledo Gmbh
Address:	Im Langacher 44 8606 Greifensee
Country:	Switzerland
Name for contact purposes:	Pascal Fritsche
Phone:	+41 44 806 7503
Fax:	+41 44 806 7350
eMail Address:	pascal.fritsche@mt.com
Applicant represented during the test by the following person:	Martin Fend (martin.fend@mt.com)

1.2 Manufacturer

Name:	Mettler-Toledo Gmbh
Address:	Im Langacher 44 8606 Greifensee
Country:	Switzerland
Name for contact purposes:	Pascal Fritsche
Phone:	++41 44 806 7503
Fax:	++41 44 806 7350
eMail Address:	pascal.fritsche@mt.com
Manufacturer represented during the test by the following person:	Martin Fend (martin.fend@mt.com)

1.3 Test Laboratory

The tests were carried out at:

PHOENIX TESTLAB GmbH
Königswinkel 10
32825 Blomberg
Germany

accredited by Deutsche Akkreditierungsstelle GmbH (DAkkS) in compliance with DIN EN ISO/IEC 17025 under Reg. No. D-PL-17186-01-02, FCC Test Firm Accreditation with the registration number 469623, designation number DE0004 and Industry Canada Test site registration SITE# IC3469A-1.

1.4 EUT (Equipment Under Test)

Test object: *	Handheld Density Meter
Type / PMN: *	DensitoPro
FCC ID: *	THVDR001
IC-Number: *	22032-DR001
Serial number: *	P5.2.9 1700120501
PCB identifier: *	30325802D
HVIN (Hardware Version Identification Number): *	DensitoPro
FVIN (Firmware Version Identification Number): *	V0.36-MS3.6
Lowest internal frequency: *	32.768 kHz
Highest internal frequency: *	100 MHz

*: Declared by the applicant. The EUT was not labeled during the tests.

1.5 Technical data of equipment

Channel 1	RX:	13.56 MHz	TX:	13.56 MHz
-----------	-----	-----------	-----	-----------

Antenna type: *	Internal antenna				
Number of channels: *	1				
Antenna connector: *	None				
Modulation: *	AM				
Data rate: *	26.48 kBit/s				
Supply Voltage: *	U _{Nom} =	3.7 V DC	U _{Min} =	3.4 V DC	U _{Max} = 4.2 V DC
Temperature range: *	-10°C to 55°C				

*: declared by the applicant.

Ports / Connectors				
Identification	Connector		Length during test	Shielding (Yes / No)
	EUT	Ancillary		
Power supply line AC adapter	5 V DC Micro-USB	USB-A AC adapter	1.25 m *	Yes
USB	USB A	Left open	-	-
-	-	-	-	-

*only connected for the conducted emission test.

1.6 Ancillary equipment used for test

Ancillaries tested with:
Mettler Toledo SmartTag MT: 30046108 (NXP Icode SLI-X SL2S2002) Power Supply PSAI05R-050QL6 Customer P/N of MT: 30098591

1.7 Dates

Date of receipt of test sample:	27.11.2017
Start of test:	27.11.2017
End of test:	09.12.2017

2 Operational states and test setup

Description of function of the EUT:

The EUT is a Handheld Density Meter with 13.56 RFID and barcode function for professional use.

The following states were defined as the operating conditions:

During all tests the EUT was supplied by 3.7 V DC via internal battery.

During the conducted emission test the EUT was charged via AC adapter (Power Supply PSAI05R-050QL6 Customer P/N of MT: 30098591) connected to an AC mains network of 120 VAC 60 Hz.

The tests were carried out with an unmodified sample, which operates in test mode continuously reading TAG (Mettler Toledo SmartTag MT: 30046108 (NXP Icode SLI-X SL2S2002)

No spurious emission measurement of the receiver was carried out, because the co-located permanently operating transmitter.

The physical boundaries of the EUT are shown below.



3 Additional information

The EUT was not labeled as required by FCC / IC.

4 Overview

Application	Frequency range [MHz]	FCC 47 CFR Part 15 section [2]	RSS-Gen, Issue 4 [4] and RSS 210, Issue 9 [3]	Status	Refer page
Conducted emissions on supply line	0.15 – 30	15.207	8.8 [4]	Passed	8 et seq.
Radiated emissions	0.009 – 1.000	15.205 15.209	8.9 [4] 4.4 [3]	Passed	10 et seq.
99% bandwidth	13.56	-	6.4 [4]	Passed *	24 et seq.
Antenna requirement	-	15.203	8.3 [4]	Passed *	-

*: Integrated antenna only, requirement fulfilled.

5 Results


5.1 Conducted emission measurement on ac mains (150 kHz to 30 MHz)

5.1.1 Method of measurement conducted emission

This test will be carried out in a shielded chamber. Table top devices will set up on a non-conducting support with a size of 1 m by 1.5 m and a height of 80 cm above the ground plane. Floor-standing devices will be placed directly on the ground plane. The setup of the Equipment under test will be in accordance to [1].

The frequency range 150 kHz to 30 MHz will be measured with an EMI Receiver set to MAX Hold mode with peak and average detector and a resolution bandwidth of 9 kHz. A scan will be carried out on the phase (or plus pole in case of DC powered devices) of the AC mains network. If levels detected 10 dB below the appropriate limit, this emission will be measured with the average and quasi-peak detector on all lines.

Frequency range	Resolution bandwidth
150 kHz to 30 MHz	9 kHz



5.1.2 Test result (conducted emission measurement on AC mains)

Ambient temperature:	20 °C	Relative humidity:	45 %
----------------------	-------	--------------------	------


Position of EUT: The EUT was set-up on a wooden table of a height of 0.8 m.

Cable guide: The cable of the EUT was fixed on the wooden table. For further information of the cable guide refer to the pictures in annex A of this test report.

Test record: The test was carried out with an unmodified sample, which continuously reading a TAG.

Power supply: During the conducted emission test the EUT was supplied with 5 V DC by an AC/DC via AC adapter (Power Supply PSAI05R-050QL6 Customer P/N of MT: 30098591) which was connected to an AC mains network with 120 V AC / 60 Hz.

Operation states: As described in clause 2.



172251ACFCC1b

29.11.2017

Final_Result

Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	PE	Corr. (dB)
0.154500	---	32.52	55.75	23.24	5000.0	9.000	L1	FLO	9.8
0.154500	42.92	---	65.75	22.84	5000.0	9.000	L1	FLO	9.8
0.367800	---	32.42	48.55	16.14	5000.0	9.000	L1	FLO	9.9
0.367800	37.03	---	58.55	21.52	5000.0	9.000	L1	FLO	9.9
0.523500	---	33.26	46.00	12.74	5000.0	9.000	L1	FLO	9.9
0.543300	36.32	---	56.00	19.68	5000.0	9.000	L1	FLO	9.9
13.565400	---	35.49	50.00	14.51	5000.0	9.000	L1	GND	10.7
13.566300	48.83	---	60.00	11.17	5000.0	9.000	L1	GND	10.7
27.118500	29.36	---	60.00	30.64	5000.0	9.000	N	FLO	11.2
27.118500	---	19.66	50.00	30.34	5000.0	9.000	N	FLO	11.2

Measurement uncertainty: +2.76 dB / -2.76 dB

Test: Passed.

Test equipment used (refer clause 6):

9, 11 - 14

5.2 Radiated emissions

5.2.1 Method of measurement (radiated emissions)

The radiated emission measurement is subdivided into six stages.

- A preliminary measurement carried out in a fully anechoic chamber with a fixed antenna height in the frequency range 9 kHz to 1 GHz.
- A final measurement carried out on an outdoor test site without reflecting ground plane and a fixed antenna height in the frequency range 9 kHz to 30 MHz.
- A preliminary measurement carried out in a fully anechoic chamber with a fixed antenna height in the frequency range 30 MHz to 1 GHz.
- A final measurement carried out on an open area test site with reflecting ground plane and various antenna heights in the frequency range 30 MHz to 1 GHz.
- A preliminary measurement carried out in a fully anechoic chamber with a fixed antenna height in the frequency range 1 GHz to 40 GHz.
- A final measurement carried out in a fully anechoic chamber with a fixed antenna height in the frequency range 1 GHz to 40 GHz.


Preliminary measurement (9 kHz to 30 MHz):

In the first stage a preliminary measurement will be performed in a shielded room with a measuring distance of 3 meters. Table-top devices will set up on a non-conducting support with a size of 1 m by 1.5 m and a height of 80 cm. Floor-standing devices will be placed directly on the turntable/ground plane. The set up of the Equipment under test will be in accordance to [1].

The frequency range 9 kHz to 30 MHz will be monitored with a spectrum analyser while the system and its cables will be manipulated to find out the configuration with the maximum emission levels if applicable. The EMI Receiver will be set to MAX Hold mode. The EUT and the measuring antenna will be rotated around their vertical axis to found the maximum emissions.

The resolution bandwidth of the spectrum analyser will be set to the following values:

Frequency range	Resolution bandwidth
9 kHz to 150 kHz	200 Hz
150 kHz to 30 MHz	10 kHz



Preliminary measurement procedure:

Prescans were performed in the frequency range 9 kHz to 150 kHz and 150 kHz to 30 MHz.

The following procedure will be used:

- 1) Monitor the frequency range at horizontal polarisation and a EUT azimuth of 0 °.
- 2) Manipulate the system cables within the range to produce the maximum level of emission.
- 3) Rotate the EUT by 360 ° to maximize the detected signals.
- 4) Make a hardcopy of the spectrum.
- 5) Measure the frequencies of highest detected emission with a lower span and resolution bandwidth to increase the accuracy and note the frequency value.
- 6) Repeat steps 1) to 5) with the other orthogonal axes of the EUT (because of EUT is a module and might be used in a handheld equipment application).
- 7) Rotate the measuring antenna and repeat steps 1) to 5).


Final measurement (9 kHz to 30 MHz):

In the second stage a final measurement will be performed on an open area test site with no conducting ground plane in a measuring distances of 3 m, 10 m and 30 m. In the case where larger measuring distances are required the results will be extrapolated based on the values measured on the closer distances according to Section 15.31 (f) (2) [2]. The final measurement will be performed with a EMI Receiver set to Quasi Peak detector except for the frequency bands 9 kHz to 90 kHz and 110 kHz to 490 kHz where an average detector will be used according Section 15.209 (d) [2].

On the frequencies, which were detected during the preliminary measurements, the final measurement will be performed while rotating the EUT and the measuring antenna in the range of 0 ° to 360 ° around their vertical axis until the maximum value is found.

The resolution bandwidth of the EMI Receiver will be set to the following values:

Frequency range	Resolution bandwidth
9 kHz to 150 kHz	200 Hz
150 kHz to 30 MHz	9 kHz



Final measurement procedure:

The following procedure will be used:

- 1) Monitor the frequency range with the measuring antenna at vertical orientation parallel to the EUT at an azimuth of 0 °.
- 2) Rotate the EUT by 360 ° to maximize the detected signals and note the azimuth and orientation.
- 3) Rotate the measuring antenna to find the maximum and note the value.
- 4) Rotate the measuring antenna and repeat steps 1) to 3) until the maximum value is found.
- 5) Repeat steps 1) to 4) with the other orthogonal axes of the EUT (if the EUT is a module and might be used in a handheld equipment application).


Preliminary measurement (30 MHz to 1 GHz)

In the first stage a preliminary measurement will be performed in a fully anechoic chamber with a measuring distance of 3 meter. Tabletop devices will set up on a non-conducting support with a size of 1 m by 1.5 m and a height of 80 cm. Floor-standing devices will be placed directly on the turntable/ground plane. The set up of the Equipment under test will be in accordance to [1].

The frequency range 30 MHz to 1 GHz will be measured with an EMI Receiver set to MAX Hold mode and a resolution bandwidth of 120 kHz. The measurement will be performed in horizontal and vertical polarisation of the measuring antenna and while rotating the EUT in its vertical axis in the range of 0 ° to 360 °.

The resolution bandwidth of the EMI Receiver will be set to the following values:

Frequency range	Resolution bandwidth
30 MHz to 1 GHz	120 kHz



Procedure preliminary measurement:

Prescans were performed in the frequency range 30 MHz to 1 GHz.

The following procedure will be used:


1. Monitor the frequency range at horizontal polarisation and a EUT azimuth of 0 °.
2. Manipulate the system cables within the range to produce the maximum level of emission.
3. Rotate the EUT by 360 ° to maximize the detected signals.
4. Make a hardcopy of the spectrum.
5. Measure the frequency of the detected emissions with a lower span and resolution bandwidth to increase the accuracy and note the frequency value.
6. Repeat 1) to 4) with the other orthogonal axes of the EUT if handheld equipment.
7. Repeat 1) to 5) with the vertical polarisation of the measuring antenna.

Final measurement (30 MHz to 1 GHz)

A final measurement on an open area test site will be performed on selected frequencies found in the preliminary measurement. During this test the EUT will be rotated in the range of 0 ° to 360 °, the measuring antenna will be set to horizontal and vertical polarisation and raised and lowered in the range from 1 m to 4 m to find the maximum level of emissions.

The resolution bandwidth of the EMI Receiver will be set to the following values:

Frequency range	Resolution bandwidth
30 MHz to 1 GHz	120 kHz



Procedure final measurement:

The following procedure will be used:

- 1) Measure on the selected frequencies at an antenna height of 1 m and a EUT azimuth of 23 °.
- 2) Move the antenna from 1 m to 4 m and note the maximum value at each frequency.
- 3) Rotate the EUT by 45 ° and repeat 2) until an azimuth of 337 ° is reached.
- 4) Repeat 1) to 3) for the other orthogonal antenna polarization.
- 5) Move the antenna and the turntable to the position where the maximum value is detected.
- 6) Measure while moving the antenna slowly +/- 1 m.
- 7) Set the antenna to the position where the maximum value is found.
- 8) Measure while moving the turntable +/- 45 °.
- 9) Set the turntable to the azimuth where the maximum value is found.
- 10) Measure with Final detector (QP and AV) and note the value.
- 11) Repeat 5) to 10) for each frequency.
- 12) Repeat 1) to 11) for each orthogonal axes of the EUT if handheld equipment.


Preliminary and final measurement (1 GHz to 110 GHz)

This measurement will be performed in a fully anechoic chamber. Table top devices will set up on a non-conducting turn device on the height of 1.5 m. The set-up of the Equipment under test will be in accordance to [1].

The frequency range will be divided into different sub ranges depending of the frequency range of the used horn antenna. The spectrum analyser set to MAX Hold mode and a resolution bandwidth of 100 kHz. The measurement will be performed in horizontal and vertical polarisation of the measuring antenna and while rotating the EUT in its vertical axis in the range of 0 ° to 360 °. This measurement is repeated after raising the EUT in 30 ° steps according 6.6.5.4 in [1].

The resolution bandwidth of the EMI Receiver will be set to the following values:

Frequency range	Resolution bandwidth
1 GHz to 4 GHz	1 MHz
4 GHz to 12 GHz	1 MHz
12 GHz to 18 GHz	1 MHz
18 GHz to 26.5 GHz	1 MHz
26.5 GHz to 40 GHz	1 MHz
40 GHz to 60 GHz	1 MHz
50 GHz to 75 GHz	1 MHz
75 GHz to 110 GHz	1 MHz



Procedure preliminary measurement:

Prescans were performed in the frequency range 1 to 110 GHz.

The following procedure will be used:


1. Monitor the frequency range at horizontal polarisation and a EUT azimuth of 0 °.
2. Rotate the EUT by 360° to maximize the detected signals.
3. Repeat 1) to 2) with the vertical polarisation of the measuring antenna.
4. Make a hardcopy of the spectrum.
5. Repeat 1) to 4) with the EUT raised by an angle of 30° (60°, 90°, 120° and 150°) according to 6.6.5.4 in [1].
6. Measure the frequency of the detected emissions with a lower span and resolution bandwidth to increase the accuracy and note the frequency value.
7. The measurement antenna polarisation, with the according EUT position (Turntable and Turn device) which produces the highest emission for each frequency will be used for the final measurement. The six closest values to the applicable limit will be used for the final measurement.

Final measurement (1 GHz to 110 GHz)

The frequency range will be divided into different sub ranges depending of the frequency range of the used antenna. The EMI Receiver set to peak and average mode and a resolution bandwidth of 1 MHz. The measurement will be performed by rotating the turntable through 0 to 360° in the worst-case EUT orientation which was obtained during the preliminary measurements.

The resolution bandwidth of the EMI Receiver will be set to the following values:

Frequency range	Resolution bandwidth
1 GHz to 4 GHz	1 MHz
4 GHz to 12 GHz	1 MHz
12 GHz to 18 GHz	1 MHz
18 GHz to 26.5 GHz	1 MHz
26.5 GHz to 40 GHz	1 MHz
40 GHz to 60 GHz	1 MHz
50 GHz to 75 GHz	1 MHz
75 GHz to 110 GHz	1 MHz



Procedure of measurement:

The measurements were performed in the frequency range 1 GHz to 110 GHz.

The following procedure will be used:


- 1) Set the turntable and the turn device to obtain the worst-case emission for the first frequency identified in the preliminary measurements.
- 2) Set the measurement antenna polarisation to the orientation with the highest emission for the first frequency identified in the preliminary measurements.
- 3) Set the spectrum analyser to EMI mode with peak and average detector activated.
- 4) Rotate the turntable from 0° to 360° to find the EUT angle that produces the highest emissions.
- 5) Note the highest displayed peak and average values
- 6) Repeat the steps 1) to 5) for each frequency detected during the preliminary measurements.

5.2.2 Results preliminary measurement 9 kHz to 1 GHz

Ambient temperature	22 °C	Relative humidity	49 %
---------------------	-------	-------------------	------

Position of EUT:	The EUT was set-up on a non-conducting table.
Cable guide:	The cable of the EUT was fixed on the non-conducting table. For further information of the cable guide refer to the pictures in annex A of this test report.
Test record:	The tests were carried out with an unmodified sample, which continuously reading a TAG. All results are shown in the following.
Power supply:	During this test the EUT was powered by the internal battery and AC adapter.
Frequency range:	According to [2] from 9 kHz to 1 GHz.
Remark:	The measurement was carried out in the position that causes the maximum emissions as evaluated in additional pre-tests.

172251Xah1FCC: Spurious emissions from 9 kHz to 30 MHz (without AC adapter)



Except the fundamental of the EUT at no frequency was a value above the noise of the system therefore only a final measurement for the fundamental on the open area test site was carried out. No spurious emissions caused by the equipment under test were found.


The following emission was found according to [2] and [3]. (Fundamental of transmitter)

13.56 MHz

Remark: No further emissions caused by the equipment under test were found.


For information only

172251Xah1FCCac: Spurious emissions from 9 kHz to 30 MHz (with AC adapter)



Remark: The emissions below 150 KHz were caused by the AC adapter and no spurious emissions of the transmitter. Therefore these emissions had to be taken not in account.

172251ah1FCC: Spurious emissions from 30 MHz to 1000 MHz



The following frequencies were found outside and inside the restricted bands found according to FCC 47 CFR Part 15 section 15.209.

Frequency (MHz)
67.800000
70.500000
94.920000
135.600000
162.720000
596.640000

Test equipment used (refer clause 6):

1 – 6 , 9 , 10

5.2.3 Result final measurement from 9 kHz to 30 MHz

Ambient temperature	16 °C	Relative humidity	56 %
---------------------	-------	-------------------	------

Position of EUT: The EUT was set-up on a non-conducting table of a height of 0.8 m. The distance between EUT and antenna was 3 m.

Cable guide: The cable of the EUT was fixed on the non-conducting support. For further information of the cable guide refer to the pictures in annex A of this test report.

Test record: The tests were carried out with an unmodified sample, which continuously reading a TAG. All results are shown in the following.

Power supply: During this test the EUT was supplied by the internal battery and AC adapter.

Test results: The test results were calculated with the following formula:

$$\text{Result [dB}\mu\text{V/m]} = \text{reading [dB}\mu\text{V]} + \text{antenna factor [dB/m]}$$

Results with measuring distance of 3 m						
Frequency MHz	Result dB μ V/m	Limit ²⁾ dB μ V/m	Margin dB	Detector	Readings dB μ V	Antenna factor ¹⁾ dB/m
13.56	43.2	69.5	26.4	AV	22.9	20.3
Results with measuring distance of 10 m						
Measurement uncertainty: +2.2 dB / -3.6 dB						

¹⁾: Cable loss included

²⁾: Limits according to [2] and [3] extrapolated with a factor of 40dB/decade according to [2]

Remark: The emission at 13.56 MHz is the fundamental of the transmitter.

Test: Passed

Test equipment used (refer clause 6):

2, 22, 23

5.2.4 Result final measurement from 30 MHz to 1 GHz


Ambient temperature	21 °C	Relative humidity	59 %
---------------------	-------	-------------------	------

- Position of EUT: The EUT was setup on a non-conducting table of a height of 0.8 m. The distance between EUT and antenna was 3 m.
- Test record: The tests were carried out with an unmodified sample, which continuously reading a TAG. All results are shown in the following.
- Power supply: During this test the EUT was supplied by the internal battery and AC adapter.
- Test results: The test results were calculated with the following formula:

$$\text{Result [dB}\mu\text{V/m]} = \text{reading [dB}\mu\text{V]} + \text{cable loss [dB]} + \text{antenna factor [dB/m]}$$

The results of the standard subsequent measurement on the open area test site are indicated in the table below. The limits as well as the measured results (levels) refer to the above mentioned standard while taking account of the specified requirements for a 3 m measuring distance.

The measurement time with the quasi-peak measuring detector is 1 seconds.



172251ffFCC

29.11.2017

Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
67.800000	27.80	40.00	12.20	1000.0	120.000	400.0	H	92.0	13.2
70.500000	23.73	40.00	16.27	1000.0	120.000	170.0	V	202.0	14.0
94.920000	35.36	43.50	8.14	1000.0	120.000	400.0	H	124.0	18.4
135.600000	27.44	43.50	16.06	1000.0	120.000	150.0	V	316.0	20.7
162.720000	29.53	43.50	13.97	1000.0	120.000	104.0	V	318.0	19.5
596.640000	33.03	46.00	12.97	1000.0	120.000	209.0	H	205.0	29.7
Measurement uncertainty				+/- 4.8 dB					


Test: Passed

Test equipment used (refer clause 6):

12, 15 - 21

5.3 99 % bandwidth

5.3.1 Method of measurement



The following procedure will be used for the occupied bandwidth measurement according to [1]:

The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts. The resolution bandwidth shall be set to as close to 1% of the selected span as is possible without being below 1%. The video bandwidth shall be set to 3 times the resolution bandwidth. Video averaging is not permitted. Where practical, a sampling detector shall be used since a peak or, peak hold, may produce a wider bandwidth than actual.

The trace data points are recovered and are directly summed in linear terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached and that frequency recorded. The process is repeated for the highest frequency data points. This frequency is recorded.

The span between the two recorded frequencies is the occupied bandwidth.


5.3.2 Test results

Ambient temperature:	21 °C	Relative humidity:	62 %
----------------------	-------	--------------------	------

Test record: The tests were carried out with an unmodified sample, which operates in normal mode continuous reading TAG. All results are shown in the following.

Power supply: During this test the EUT was supplied by the internal battery and AC adapter.

172251_99.JPGEG: 99 % bandwidth:



F_L	F_U	BW ($F_U - F_L$)
13.301259 MHz	13.748811 MHz	447.552 kHz
Measurement uncertainty		$< 1 \cdot 10^{-7}$

Test equipment used (refer clause 6):

1, 24

6 Test equipment

No.	Test equipment	Type	Manufacturer	Serial No.	PM. No.	Cal. Date	Cal Due
1	EMI Receiver / Spectrum Analyser	ESW44	Rohde & Schwarz	101635	482467	22.06.2017	06.2019
2	loop antenna	HFH2-Z2	Rohde & Schwarz	832609/014	480059	29.02.2016	02.2018
3	Turntable	DS420 HE	Deisel	420/620/00	480315	Calibration not necessary	
4	Antenna support	AS620P	Deisel	620/375	480325	Calibration not necessary	
5	Multiple Control Unit	MCU	Maturo GmbH	MCU/043/97110 7	480832	Calibration not necessary	
6	Fully anechoic chamber M20	B83117-E2439-T232	Albatross Projects	103	480303	Calibration not necessary	
7	Antenna mast	AS615P	Deisel	615/310	480187	Calibration not necessary	
8	RF-cable No.36	Sucoflex 106B	Suhner	0587/6B / Kabel 36	480865	Calibration not necessary	
9	Software	EMC32	Rohde & Schwarz		481800	Calibration not necessary	
10	Antenna (Bilog)	CBL6112B	Schaffner EMV GmbH (-Chase)	2688	480328	19.06.2017	06.2020
11	LISN	NSLK8128	Schwarzbeck	8128155	480058	16.02.2016	02.2018
12	EMI Receiver / Spectrum Analyser	ESIB 26	Rohde & Schwarz	100292	481182	15.02.2016	02.2018
13	Shielded chamber M4	B83117-S1-X158	Siemens	190075	480088	Calibration not necessary	
14	Transient Filter Limiter	CFL 9206A	Teseq GmbH	38268	481982	18.02.2016	02.2018
15	Attenuator 6 dB	WA2-6	Weinschel	8254	410119	Calibration not necessary	
16	Open area test site M6	-	Phoenix Contact	-	480085	Calibration not necessary	
17	Antenna mast	MA240-0	Inn-Co GmbH	MA240-0/030/6600603	480086	Calibration not necessary	
18	Turntable	DS412	Deisel	412/316	480087	Calibration not necessary	
19	Controller	HD100	Deisel	100/349	480139	Calibration not necessary	
20	Antenna (Bilog)	CBL6111D	Schaffner Elektrotest GmbH / Teseq GmbH	25761	480894	19.10.2017	10.2020
21	Software	EMC32	Rohde & Schwarz	100061	481022	Calibration not necessary	
22	Outdoor test site	-	PHOENIX TESTLAB GmbH	-	480293	Calibration not necessary	
23	EMI Receiver / Spectrum Analyser	ESI 40	Rohde & Schwarz	100064/040	480355	15.02.2017	02.2018
24	Loop antenna	Loop antenna Ø = 11 cm	PHOENIX TESTLAB GmbH	-	410084	Calibration not necessary	

