



**MET Laboratories, Inc.** *Safety Certification - EMI - Telecom Environmental Simulation*  
33439 WESTERN AVENUE • UNION CITY, CALIFORNIA 94587 • PHONE (510) 489-6300 • FAX (510) 489-6372

## **Electromagnetic Compatibility Criteria Test Report**

For the

**Continental Wireless, Inc.  
R5000-L-4.9 Broadband Wireless Router**

Tested under

**The FCC Verification Rules  
Contained in Title 47 of the CFR, Part 90, Subpart Y  
for Private Land Mobile Radio Services**

**MET Report: EMCS17568-FCC90**

**June 20, 2005**

Prepared For:

**Continental Wireless, Inc.  
2355 Merritt Dr., Ste. 200  
Garland, TX 75041**

**Prepared By:**  
**MET Laboratories, Inc.**  
33439 Western Ave.  
Union City, California 94587



## Electromagnetic Compatibility Criteria Test Report

For the

**Continental Wireless, Inc.**  
**R5000-L-4.9 Broadband Wireless Router**

Tested under

**The FCC Verification Rules**  
**Contained in Title 47 of the CFR, Part 90, Subpart Y**  
**for Private Land Mobile Radio Services**

**MET Report: EMCS17568-FCC90**

Tony Permsombut, Manager  
Electromagnetic Compatibility Lab

Cheryl Anicete  
Documentation Department

**Engineering Statement:** The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is / is not capable of operation in accordance with the requirements of Part 90, Subpart Y of the FCC Rules under normal use and maintenance.

Kerwinn Corpuz  
Electromagnetic Compatibility Lab



Continental Wireless, Inc.  
R5000-L-4.9 Broadband Wireless Router

Electromagnetic Compatibility  
Report Status Sheet  
CFR Title 47, Part 90, Subpart Y

## Report Status Sheet

| Revision | Report Date   | Reason for Revision |
|----------|---------------|---------------------|
| Ø        | June 20, 2005 | Initial Issue.      |



## Table of Contents

|                                                                                                   |           |
|---------------------------------------------------------------------------------------------------|-----------|
| <b>1. Testing Summary .....</b>                                                                   | <b>1</b>  |
| <b>2. Equipment Configuration.....</b>                                                            | <b>2</b>  |
| 2.1. Overview .....                                                                               | 2         |
| 2.2. Test Site .....                                                                              | 3         |
| 2.3. Description of Test Sample .....                                                             | 3         |
| 2.4. Equipment Configuration .....                                                                | 4         |
| 2.5. Support Equipment .....                                                                      | 4         |
| 2.6. Ports and Cabling Information .....                                                          | 5         |
| 2.7. Mode of Operation .....                                                                      | 8         |
| 2.8. Method of Monitoring EUT Operation .....                                                     | 8         |
| 2.9. Modifications .....                                                                          | 8         |
| 2.9.1. Modifications to EUT .....                                                                 | 8         |
| 2.9.2. Modifications to Test Standard .....                                                       | 8         |
| 2.10. Disposition of EUT .....                                                                    | 8         |
| <b>3. Electromagnetic Compatibility RF Power Output Requirements .....</b>                        | <b>9</b>  |
| 3.1. Peak Power Output.....                                                                       | 9         |
| 3.2. Peak Power Spectral Density .....                                                            | 11        |
| <b>4. Electromagnetic Compatibility Modulation Characteristics Requirements.....</b>              | <b>15</b> |
| 4.1. Modulation Characteristics .....                                                             | 15        |
| <b>5. Electromagnetic Compatibility Occupied Bandwidth Requirements.....</b>                      | <b>16</b> |
| 5.1. Occupied Bandwidth (Emission Masks) .....                                                    | 16        |
| <b>6. Electromagnetic Compatibility Spurious Emissions at Antenna Terminal Requirements .....</b> | <b>21</b> |
| 6.1. Spurious Emissions at Antenna Terminals.....                                                 | 21        |
| <b>7. Electromagnetic Compatibility Radiated Emissions Requirements .....</b>                     | <b>28</b> |
| 7.1. Radiated Emissions (Substitution Method).....                                                | 28        |
| <b>8. Electromagnetic Compatibility Radiated Emissions Requirements .....</b>                     | <b>32</b> |
| 8.1. Frequency Stability .....                                                                    | 32        |
| <b>9. Electromagnetic Compatibility Transient Frequency Behavior Requirements .....</b>           | <b>35</b> |
| 9.1. Transient Frequency Behavior .....                                                           | 35        |
| <b>10. Test Equipment .....</b>                                                                   | <b>36</b> |
| <b>11. RF Exposure Requirements .....</b>                                                         | <b>38</b> |
| <b>12. Certification Label &amp; User's Manual Information .....</b>                              | <b>39</b> |
| 12.1. Verification Information .....                                                              | 39        |
| 12.2. Label and User's Manual Information .....                                                   | 43        |

All references to section numbers are taken directly from the standard/specification used. Only sections requiring testing or evaluation are included.



## List of Tables

|                                                       |    |
|-------------------------------------------------------|----|
| Table 1. Equipment Configuration .....                | 4  |
| Table 2. Support Equipment.....                       | 4  |
| Table 3. Ports and Cabling Information .....          | 5  |
| Table 4. Temperature Vs. Frequency Test Results ..... | 33 |
| Table 5. Frequency Vs. Voltage Test Results .....     | 33 |

## List of Figures

|                                                                             |   |
|-----------------------------------------------------------------------------|---|
| Figure 1. Block Diagram of Test Configuration (Conducted Measurements)..... | 6 |
| Figure 2. Block Diagram of Test Configuration (Radiated Emissions).....     | 7 |

## List of Photographs

|                                                                       |    |
|-----------------------------------------------------------------------|----|
| Photograph 1. RF Power Output Test Setup.....                         | 14 |
| Photograph 2. Occupied Bandwidth (Emission Mask) Test Setup.....      | 20 |
| Photograph 3. Spurious Emissions at Antenna Terminals Test Setup..... | 27 |
| Photograph 4. Radiated Emission Spurious Test Setup.....              | 31 |
| Photograph 5. Frequency Stability Test Setup .....                    | 34 |



## List of Terms and Abbreviations

|                              |                                          |
|------------------------------|------------------------------------------|
| <b>AC</b>                    | Alternating Current                      |
| <b>ACF</b>                   | Antenna Correction Factor                |
| <b>Cal</b>                   | Calibration                              |
| <b>d</b>                     | Measurement Distance                     |
| <b>dB</b>                    | Deci Bels                                |
| <b>dBm</b>                   | Deci-Bels relative to one milli watt     |
| <b>dB<math>\mu</math>V</b>   | Deci-Bels above one micro Volt           |
| <b>dB<math>\mu</math>V/m</b> | Deci-Bels above one micro Volt per meter |
| <b>DC</b>                    | Direct Current                           |
| <b>DCF</b>                   | Distance Correction Factor               |
| <b>E</b>                     | Electric Field                           |
| <b>DSL</b>                   | Digital Subscriber Line                  |
| <b>ESD</b>                   | Electrostatic Discharge                  |
| <b>EUT</b>                   | Equipment Under Test                     |
| <b>f</b>                     | Frequency                                |
| <b>FCC</b>                   | Federal Communications Commission        |
| <b>H</b>                     | Magnetic Field                           |
| <b>GHz</b>                   | Giga Hertz                               |
| <b>Hz</b>                    | Hertz                                    |
| <b>ICES</b>                  | Interference-Causing Equipment Standard  |
| <b>kHz</b>                   | kilohertz                                |
| <b>kPa</b>                   | kilopascal                               |
| <b>kV</b>                    | kilo Volt                                |
| <b>LISN</b>                  | Line Impedance Stabilization Network     |
| <b>MHz</b>                   | MegaHertz                                |
| <b><math>\mu</math>H</b>     | micro Henry                              |
| <b><math>\mu</math>F</b>     | micro Farad                              |
| <b><math>\mu</math>s</b>     | micro seconds                            |
| <b>RF</b>                    | Radio Frequency                          |
| <b>RMS</b>                   | Root-Mean-Square                         |



## 1. Testing Summary

These tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with Part 90, Subpart Y. All tests were conducted using measurement procedure ANSI TIA/EIA-603-A-2004.

|                                            |                                                           |
|--------------------------------------------|-----------------------------------------------------------|
| Type of Submission/<br>Rule Part:          | Certification / Part 90 Subpart Y                         |
| EUT:                                       | R5000-L-4.9 Broadband Wireless Router                     |
| FCC ID:                                    | TIG R5000-L-49                                            |
| Equipment Code:                            | TNB                                                       |
| Type of Modulation:                        | OFDM                                                      |
| Emission Designator:                       | 17M1G7D                                                   |
| Power Limit:                               | For High Power Device only                                |
| RF Power Output:                           | Conducted Output Power in Peak: 24.15 dBm (260 milliwatt) |
| EUT Operating<br>Frequency Range<br>(MHz): | 4950 - 4980                                               |

| Title 47 of the CFR, Part 90, Subpart Y,<br>and FCC 04-265 Reference and Test<br>Description | Conformance                                                                                                                                               |    |     | Comments                                    |
|----------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|----|-----|---------------------------------------------|
|                                                                                              | Yes                                                                                                                                                       | No | N/A |                                             |
|                                                                                              | Yes - Equipment complies with the Requirement<br>No - Equipment does not comply with the Requirement<br>N/A - Not applicable to the equipment under tests |    |     |                                             |
| 2.1046; 90.1215(a) Peak Power Output                                                         | ✓                                                                                                                                                         |    |     | Measured emissions below applicable limits. |
| 2.1046; 90.1215(a) Peak Power Spectral Density                                               | ✓                                                                                                                                                         |    |     | Measured emissions below applicable limits. |
| 2.1047(a) Modulation Characteristics                                                         |                                                                                                                                                           |    | ✓   | EUT is non-voice, data only.                |
| 2.1049; 90.210(L) Occupied Bandwidth (Emission Mask)                                         | ✓                                                                                                                                                         |    |     | Measured emissions below applicable limits. |
| 2.1051; 90.210(L) Spurious Emissions at Antenna Terminals                                    | ✓                                                                                                                                                         |    |     | Measured emissions below applicable limits. |
| 2.1053; 90.210(L) Radiated Spurious Emissions                                                | ✓                                                                                                                                                         |    |     | Measured emissions below applicable limits. |
| 2.1055(a) (1); 90.213 Frequency Stability over Temperature Variations                        | ✓                                                                                                                                                         |    |     | Measured emissions below applicable limits. |
| 2.1055(d) (2) Frequency Stability over Voltage Variations                                    | ✓                                                                                                                                                         |    |     | Measured emissions below applicable limits. |
| 90.214 Transient Frequency Behavior                                                          |                                                                                                                                                           |    | ✓   | EUT operating frequency is at 4.9 GHz.      |



## 2. Equipment Configuration

### 2.1. Overview

MET Laboratories, Inc. was contracted by Continental Wireless, Inc. to perform testing on the R5000-L-4.9 Broadband Wireless Router, under Continental Wireless, Inc. purchase order number PAG238GW.

This document describes the test setups, test methods, required test equipment, and the test limit criteria used to perform compliance testing of the Continental Wireless, Inc., R5000-L-4.9 Broadband Wireless Router.

An EMC evaluation to determine compliance of the Continental Wireless, Inc. with the requirements of Part 90, Subpart Y, was conducted. (All references are to the most current version of Title 47 of the Code of Federal Regulations in effect). In accordance with §2.1033, the following data is presented in support of the Certification of the R5000-L-4.9 Broadband Wireless Router. Continental Wireless, Inc. should retain a copy of this document and it should be kept on file for at least five years after the manufacturing of the EUT has been **permanently** discontinued.

The results obtained relate only to the item(s) tested.

|                            |                                       |
|----------------------------|---------------------------------------|
| <b>Model(s) Tested:</b>    | R5000-L-4.9 Broadband Wireless Router |
| <b>Model(s) Covered:</b>   | R5000-L-4.9 Broadband Wireless Router |
| <b>EUT Specifications:</b> | Primary Power: 120 Vac, 60 Hz         |
|                            | Secondary Power: N/A                  |
|                            | Highest Clock Frequency: 4980 MHz     |
| <b>Evaluated by:</b>       | Kerwinn Corpuz                        |
| <b>Date(s):</b>            | June 6 – 20, 2005                     |



## **2.2. Test Site**

All testing was performed at MET Laboratories, Inc., 4855 Patrick Henry Drive, Building 6, Santa Clara, California 95054. All equipment used in making physical determinations is accurate and bears recent traceability to the National Institute of Standards and Technology.

Radiated Emissions measurements were performed in a 10 meter semi-anechoic chamber (equivalent to an Open Area Test Site). In accordance with §2.948(a)(3), a complete site description is contained at MET Laboratories. In accordance with §2.948(d), MET Laboratories has been accredited by the National Voluntary Laboratory Accreditation Program (Lab Code: 100273-0).

## **2.3. Description of Test Sample**

The R5000-L-4.9 Broadband Wireless Router, Equipment Under Test (EUT) for the remainder of this document, is a wireless communications system operating in the 4940 to 4990 GHz spectrum.



## 2.4. Equipment Configuration

The EUT was set up as outlined in Figure 1, Block Diagram of Test Setup. All cards, racks, etc., incorporated as part of the EUT is included in the following list.

| Ref. ID | Name / Description                    | Model Number | Part Number | Serial Numbers | Rev. # |
|---------|---------------------------------------|--------------|-------------|----------------|--------|
| A       | Indoor Power Supply Unit              | IDU-500-RJ   | N/A         | N/A            | N/A    |
| B       | R5000-L-4.9 Broadband Wireless Router | R5000-L-4.9  | N/A         | 008285         | N/A    |

**Table 1. Equipment Configuration**

## 2.5. Support Equipment

Continental Wireless, Inc. supplied support equipment necessary for the operation and testing of the R5000-L-4.9 Broadband Wireless Router. All support equipment supplied is listed in the following Support Equipment List.

| Ref. ID | Name / Description                              | Manufacturer          | Model Number | *Customer Supplied Calibration Data |
|---------|-------------------------------------------------|-----------------------|--------------|-------------------------------------|
| C       | Laptop                                          | Dell                  | Latitude     | N/A                                 |
| D       | Spectrum Analyzer                               | Rohde & Schwarz       | ESIB 7       |                                     |
|         |                                                 | Hewlett Packard       | 8564E        | N/A                                 |
| E       | Directional coupler (for Conducted Measurement) | Narda                 | N/A          | N/A                                 |
|         |                                                 | Krytar                | 101020020    | N/A                                 |
| F       | Power Sensor (for Conducted Measurement)        | Anritsu               | MA2491A      | N/A                                 |
| G       | Power Meter (for Conducted Measurement)         | Anritsu               | ML2488A      | N/A                                 |
| H       | 10 dB Attenuator (for Conducted Measurement)    | Weinschel Corporation | 33-10-34     | N/A                                 |
| I       | 50 Ohms Terminator                              | Narda                 | 375BNM       | N/A                                 |

**Table 2. Support Equipment**

\* - The 'Customer Supplied Calibration Data' column will be marked as either not applicable, not available, or will contain the calibration date supplied by the customer.



## 2.6. Ports and Cabling Information

| Ref. ID                      | Port name on EUT | Cable Description or reason for no cable | Qty. | Length (m) | Shielded (Yes/No) | Termination Box ID & Port ID |
|------------------------------|------------------|------------------------------------------|------|------------|-------------------|------------------------------|
| <b>Conducted Measurement</b> |                  |                                          |      |            |                   |                              |
| 1                            | A, LAN           | RJ45                                     | 1    | 1          | No                | C                            |
| 2                            | A, ODU           | RJ45 / DIN                               | 1    | 1.2        | No                | B, Signal Input              |
| 3                            | A, AC PWR Input  | 18AWG AC PWR Cord                        | 1    | 1.8        | No                | AC PWR Supply                |
| 4                            | B, Antenna Port  | Coax (SMA)                               | 1    | 1          | Yes               | E                            |
| <b>Radiated Emissions</b>    |                  |                                          |      |            |                   |                              |
| 1                            | A, LAN           | RJ45                                     | 1    | 1          | No                | C                            |
| 2                            | A, ODU           | RJ45 / DIN                               | 1    | 1.2        | No                | B, Signal Input              |
| 3                            | A, AC PWR Input  | 18AWG AC PWR Cord                        | 1    | 1.8        | No                | AC PWR Supply                |
| 4                            | B, Antenna Port  | N Type                                   | N/A  | N/A        | N/A               | I                            |

Table 3. Ports and Cabling Information



## Conducted Measurement




Figure 1. Block Diagram of Test Configuration (Conducted Measurements)

## Radiated Emission




Figure 2. Block Diagram of Test Configuration (Radiated Emissions)



## **2.7. Mode of Operation**

Telnet was use to access the radio in order to change the channel frequency, bit rate and to turn on/off the transmitter. The power output was set to a fixed value which could not vary the output power.

## **2.8. Method of Monitoring EUT Operation**

A Spectrum Analyzer and a Power Meter was use to monitor the EUT's transmitter channel and power output.

## **2.9. Modifications**

### **2.9.1. Modifications to EUT**

No modifications were made to the EUT.

### **2.9.2. Modifications to Test Standard**

No modifications were made to the test standard.

## **2.10. Disposition of EUT**

The test sample including all support equipment submitted to the Electro-Magnetic Compatibility Lab for testing was returned to Continental Wireless, Inc. upon completion of testing.



### 3. Electromagnetic Compatibility RF Power Output Requirements

#### 3.1. Peak Power Output

**Test Requirement(s):** §2.1046 and §90.1215(a) with FCC 04-265 (High Power Devices)

**Test Procedures:** As required by 47 CFR 2.1046, *RF power output measurements* were made at the RF output terminals using a Directional Coupler through a Spectrum Analyzer and Power Meter.

A laptop was connected to EUT to control the RF power output and frequency channel. The EUT was connected through a Directional Coupler, a Spectrum Analyzer to monitor the frequency, and a Power Meter to measure the Peak and Average power. A 21 dB was set to Reference level Offset of the Power Meter. The EUT was set to transmit in the lowest of the operating frequency range. The EUT power was adjusted enough to produce maximum output power as specified in the owner's manual. The output power was then recorded with peak and average reading. This process was repeatedly done with the middle and the highest channel.

Note: The bit rate setting was at 6k rather than 18k due to output power measured higher with 6k.



**Test Results:** Equipment complies with 47CFR 2.1046 and 90.1215(a) with FCC 04-265 (High Power Devices). The EUT does not exceed 33 dBm at the carrier frequency.

Important note: Limit shows in Effective Radiated Power (ERP), the maximum antenna gain that can be applied is 26 dBi with the EUT maximum power output of 24.15 dBm.

All RF Power output measurements were direct connection to RF output Terminal of EUT from a Power Meter.

| RF Power Output    |                                   |                                 |                                    |
|--------------------|-----------------------------------|---------------------------------|------------------------------------|
| Frequency<br>(MHz) | EUT Channel<br>Bandwidth<br>(MHz) | Measured Peak<br>Power<br>(dBm) | Measured Average<br>Power<br>(dBm) |
| 4950               | 20                                | 23.65                           | 16.93                              |
| 4960               | 20                                | 23.65                           | 16.73                              |
| 4970               | 20                                | 23.91                           | 16.91                              |
| 4980               | 20                                | 24.15                           | 17.41                              |

**Test Engineer(s):** Kerwinn Corpuz

**Test Date(s):** 6/6/05



### 3.2. Peak Power Spectral Density

**Test Requirement(s):** §90.1215(a) with FCC 04-265 (High Power Devices)

**Test Procedures:** As required by 47 CFR 2.1046, *RF power output measurements* were made at the RF output terminals using a Directional Coupler through a Spectrum Analyzer and Power Meter.


A laptop was connected to EUT to control the RF power output and frequency channel. The EUT was connected through a Directional Coupler, a Spectrum Analyzer, and a Power Meter to monitor the output power level. An 11 dB was set to Reference level Offset of the Spectrum Analyzer and set the RBW = VBW = 1 MHz. The EUT was set to transmit in the lowest of the operating frequency range. The EUT power was adjusted at the maximum output power level. The max hold key from the Spectrum Analyzer was activated capturing the modulated envelope of the EUT. Peak Search the highest amplitude and plotted the graph. This process was repeatedly done with the middle and the highest channel.

**Test Results:** Equipment complies with 47 CFR 2.1046 and 90.1215(a) with FCC 04-265 (High Power devices). The EUT does not exceed 21 dBm/MHz at the carrier frequency.


All RF Power output measurements were direct connection to RF output Terminal of EUT from a Spectrum Analyzer.

The following pages show measurements of Peak Power Spectral Density plots which is recorded below:

| Peak Power Spectral Density |                    |                                   |                         |                |
|-----------------------------|--------------------|-----------------------------------|-------------------------|----------------|
| Plot #                      | Frequency<br>(MHz) | EUT Channel<br>Bandwidth<br>(MHz) | Measured Power<br>(dBm) | Limit<br>(dBm) |
| 1                           | 4950               | 20                                | 14.41                   | 21             |
| 2                           | 4960               | 20                                | 15.22                   | 21             |
| 3                           | 4970               | 20                                | 14.36                   | 21             |
| 4                           | 4980               | 20                                | 15.20                   | 21             |



Plot 1. PSD at 4950 MHz




Plot 2. PSD at 4960 MHz




Continental Wireless, Inc.  
R5000-L-4.9 Broadband Wireless Router

Electromagnetic Compatibility  
RF Power Output Requirements  
CFR Title 47, Part 90, Subpart Y




Plot 3. PSD at 4970 MHz



Plot 4. PSD at 4980 MHz



## RF Power Output Test Setup



Photograph 1. RF Power Output Test Setup



## 4. Electromagnetic Compatibility Modulation Characteristics Requirements

### 4.1. Modulation Characteristics

**Test Requirement(s):** §2.1047

**Test Procedures:** As required by 47 CFR 2.1047, *Modulation Characteristics measurements* were made at the RF output terminals.

**Test Results:** EUT is not required for this test.  
The EUT contain no analog voice circuitry.



## 5. Electromagnetic Compatibility Occupied Bandwidth Requirements

### 5.1. Occupied Bandwidth (Emission Mask)

**Test Requirement(s):** §2.1049 and §90.210 (L) with FCC 04-265 (Emissions Mask M)

**Test Procedures:** As required by 47 CFR 2.1049, *occupied bandwidth measurements* were made at the RF output terminals using a Directional Coupler through an Spectrum Analyzer and Power Meter monitoring the power output level.

A laptop was connected to EUT to control the RF power output and frequency channel. The EUT was connected through a Directional Coupler, a Spectrum Analyzer, and a Power Meter to monitor the output power level. The measured highest Average Power was set relative to zero dB reference. An 11 dB was set to Reference level Offset of the Spectrum Analyzer and set the RBW = at least 1% of the channel bandwidth and VBW = 30 kHz. The EUT was set to transmit in the lowest of the operating frequency range. The EUT power was adjusted at the maximum output power level. The max hold key from the Spectrum Analyzer was activated capturing the modulated envelope of the EUT. The Emission Mask limit was set to the proper channel bandwidth then plotted the graph. This process was repeatedly done with the middle and the highest channel.



Continental Wireless, Inc.  
R5000-L-4.9 Broadband Wireless Router

Electromagnetic Compatibility  
Occupied Bandwidth Requirements  
CFR Title 47, Part 90, Subpart Y

**Test Results:** Equipment complies with Section 2.1049 and 90.210(L) with FCC 04-265 (Emission Mask M). The EUT does not exceed the Emission Masks limit.

The following pages show measurements of Emission Mask plots which is recorded below:

| Emission Mask |                    |                            |
|---------------|--------------------|----------------------------|
| Plot #        | Frequency<br>(MHz) | Channel Bandwidth<br>(MHz) |
| 5             | 4950               | 20                         |
| 6             | 4960               | 20                         |
| 7             | 4970               | 20                         |
| 8             | 4980               | 20                         |


**Test Engineer(s):** Kerwinn Corpuz

**Test Date(s):** 6/6/05




Continental Wireless, Inc.  
R5000-L-4.9 Broadband Wireless Router


Electromagnetic Compatibility  
Occupied Bandwidth Requirements  
CFR Title 47, Part 90, Subpart Y




Plot 5. Emission Mask at 4950 MHz



Plot 6. Emission Mask at 4960 MHz




Plot 7. Emission Mask at 4970 MHz



Plot 8. Emission Mask at 4980 MHz



## Occupied Bandwidth (Emission Masks) Test Setup



Photograph 2. Occupied Bandwidth (Emission Mask) Test Setup



## 6. Electromagnetic Compatibility Spurious Emissions at Antenna Terminal Requirements

### 6.1. Spurious Emissions at Antenna Terminals

**Test Requirement(s):** §2.1051 and §90.210(L) with FCC 04-265 (Emission Mask M)

**Test Procedures:** As required by 47 CFR 2.1051, *spurious emissions at antenna terminal measurements* were made at the RF output terminals using a Directional Coupler through a Spectrum Analyzer and Power Meter.

A laptop was connected to EUT to control the RF power output and frequency channel. The EUT was connected through a Directional Coupler, a Spectrum Analyzer, and a Power Meter to monitor the output power level. A 1 dB was set to Reference level Offset of the Spectrum Analyzer and set the RBW = at least 1% of the channel bandwidth and VBW = 30 kHz. The Spectrum Analyzer was set to sweep 30 MHz and up to 10<sup>th</sup> harmonic of the fundamental. The Display Line of the Spectrum Analyzer was set to -33.1 dBm (50 dB below the highest average power). The EUT was set to transmit in 4960 MHz at maximum output power then plotted the graph.

The Conducted Spurious Emissions *Limit* is obtained by the following:

Measured Average Power Output of EUT: 16.91 dBm

Spur limit = 16.91 dBm – 50 dB = – 33.09 dBm



Continental Wireless, Inc.  
R5000-L-4.9 Broadband Wireless Router


Electromagnetic Compatibility  
Spurious Emissions at Antenna Terminal Requirements  
CFR Title 47, Part 90, Subpart Y

**Test Results:** Equipment complies with Section 2.1051 and 90.210(L) with FCC 04-265 (Emission Mask M). The following pages show measurements of Spurious Emission plots which is recorded below:


| Conducted Spurious Emissions |                 |                         |                              |
|------------------------------|-----------------|-------------------------|------------------------------|
| Plot #                       | Carrier Channel | Channel Frequency (MHz) | Remark:                      |
| 9                            | 2               | 4960                    | Frequency swept: 30M – 4 GHz |
| 10                           | 2               | 4960                    | Frequency swept: 4 – 8 GHz   |
| 11                           | 2               | 4960                    | Frequency swept: 8 – 12 GHz  |
| 12                           | 2               | 4960                    | Frequency swept: 12 – 16 GHz |
| 13                           | 2               | 4960                    | Frequency swept: 16 – 22 GHz |
| 14                           | 2               | 4960                    | Frequency swept: 22 – 28 GHz |
| 15                           | 2               | 4960                    | Frequency swept: 28 – 34 GHz |
| 16                           | 2               | 4960                    | Frequency swept: 34 – 40 GHz |

**Test Engineer(s):** Kerwinn Corpuz

**Test Date(s):** 6/7/05




Plot 9. Conducted Spurious Emission at Channel 2 (30 MHz – 4 GHz)




Plot 10. Conducted Spurious Emission at Channel 2 (4 GHz – 8 GHz)


Note: Emission above the limit is the fundamental frequency of 4960 MHz.




**Plot 11. Conducted Spurious Emission at Channel 2 (8 GHz – 12 GHz)**




**Plot 12. Conducted Spurious Emission at Channel 2 (12 GHz – 16 GHz)**




Plot 13. Conducted Spurious Emission at Channel 2 (16 GHz – 22 GHz)



Plot 14. Conducted Spurious Emission at Channel 2 (22 GHz – 28 GHz)




**Plot 15. Conducted Spurious Emission at Channel 2 (28 GHz – 34 GHz)**



**Plot 16. Conducted Spurious Emission at Channel 2 (34 GHz – 40 GHz)**



### Spurious Emissions at Antenna Terminals Test Setup



Photograph 3. Spurious Emissions at Antenna Terminals Test Setup



## 7. Electromagnetic Compatibility Radiated Emissions Requirements

### 7.1. Radiated Emissions (Substitution Method)

**Test Requirement(s):** §2.1053 and §90.210(L) with FCC 04-265 (Emission Mask M)

**Test Procedures:** As required by 47 CFR 2.1053, *field strength of radiated spurious measurements* were made in accordance with the procedures of TIA/EIA-603-A-2001 "Land Mobile FM or PM Communications Equipment Measurement and Performance Standards".

Radiated emission measurements were performed inside a 10 meter semi-anechoic chamber (equivalent to an Open Area Test Site). The distance between the EUT and the test antenna is 3 meter – 0.5 meter. The EUT RF ports was terminated to 50 ohm load. The EUT was set to transmit in the middle of the operating frequency range. The EUT Peak and Average output power was measured before radiated emissions were swept. To capture the full power spurious emissions, maximized each frequency by rotating the turntable to 360° and varying the test antenna from 1 to 4 meter height. Once the maximized emission is found, recorded the reading in a tabular format. These steps were repeated with horizontal polarization.

Once all emissions are collected and recorded, replaced the EUT with a substitution antenna connected to a 1.5 meter 2.92 mm(K) cable and a signal generator. All test setup on the receiving side should be the same as it was when measuring the emissions of the EUT. Repeat all steps above except that the emissions will be compared with the signal generator's amplitude. Record reading in a tabular format.

The Radiated Spurious Emissions *Limit* is obtained by the following:

Measured Average Power Output of EUT: 16.91 dBm

Spur limit = 16.91 dBm – 50 dB = – 33.09 dBm

Investigated Emissions with the EUT at vertical and horizontal position up to 40 GHz.

**Test Results:** Equipment complies with Section 2.1053 and 90.210(L) with FCC 04-265 (Emission Mask M). The following pages show measurements of emissions data sheet which is recorded in the following pages:

**Test Engineer(s):** Kerwinn Corpuz

**Test Date(s):** 06/15/2005



## Radiated Emissions (Substitution Method) Test Results

$f_o = 4950$  MHz

| Frequency<br>(MHz) | Polarization<br>V/H or SNF | Spectrum<br>Analyzer<br>(dBuV) | Signal<br>Generator<br>(dBm) | Cable<br>Loss<br>(dB) | Tx Ant.<br>Gain<br>(dBi) | EIRP<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) |
|--------------------|----------------------------|--------------------------------|------------------------------|-----------------------|--------------------------|---------------|----------------|----------------|
| 9900               | SNF                        | -                              | -                            | -                     | -                        | -             | -33.1          | -              |
| 14850              | SNF                        | -                              | -                            | -                     | -                        | -             | -33.1          | -              |
| 19800              | SNF                        | -                              | -                            | -                     | -                        | -             | -33.1          | -              |
| 24750              | SNF                        | -                              | -                            | -                     | -                        | -             | -33.1          | -              |
| 29700              | SNF                        | -                              | -                            | -                     | -                        | -             | -33.1          | -              |
| 34650              | SNF                        | -                              | -                            | -                     | -                        | -             | -33.1          | -              |
| 39600              | SNF                        | -                              | -                            | -                     | -                        | -             | -33.1          | -              |

$f_o = 4960$  MHz

| Frequency<br>(MHz) | Polarization<br>V/H or SNF | Spectrum<br>Analyzer<br>(dBuV) | Signal<br>Generator<br>(dBm) | Cable<br>Loss<br>(dB) | Tx Ant.<br>Gain<br>(dBi) | EIRP<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) |
|--------------------|----------------------------|--------------------------------|------------------------------|-----------------------|--------------------------|---------------|----------------|----------------|
| 9920               | SNF                        | -                              | -                            | -                     | -                        | -             | -33.1          | -              |
| 14880              | SNF                        | -                              | -                            | -                     | -                        | -             | -33.1          | -              |
| 19840              | SNF                        | -                              | -                            | -                     | -                        | -             | -33.1          | -              |
| 24800              | SNF                        | -                              | -                            | -                     | -                        | -             | -33.1          | -              |
| 29760              | SNF                        | -                              | -                            | -                     | -                        | -             | -33.1          | -              |
| 34720              | SNF                        | -                              | -                            | -                     | -                        | -             | -33.1          | -              |
| 39680              | SNF                        | -                              | -                            | -                     | -                        | -             | -33.1          | -              |

### Notes:

SNF = Spectrum Analyzer Noise Floor, H = horizontal and V = vertical

EIRP = SG reading - CL + Gain (dBi)

Margin = EIRP - Limit



$f_o = 4980 \text{ MHz}$

| Frequency<br>(MHz) | Polarization<br>V/H or SNF | Spectrum<br>Analyzer<br>(dBuV) | Signal<br>Generator<br>(dBm) | Cable<br>Loss<br>(dB) | Tx Ant.<br>Gain<br>(dBi) | EIRP<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) |
|--------------------|----------------------------|--------------------------------|------------------------------|-----------------------|--------------------------|---------------|----------------|----------------|
| 9960               | SNF                        | -                              | -                            | -                     | -                        | -             | -33.1          | -              |
| 14940              | SNF                        | -                              | -                            | -                     | -                        | -             | -33.1          | -              |
| 19920              | SNF                        | -                              | -                            | -                     | -                        | -             | -33.1          | -              |
| 24900              | SNF                        | -                              | -                            | -                     | -                        | -             | -33.1          | -              |
| 29880              | SNF                        | -                              | -                            | -                     | -                        | -             | -33.1          | -              |
| 34860              | SNF                        | -                              | -                            | -                     | -                        | -             | -33.1          | -              |
| 39840              | SNF                        | -                              | -                            | -                     | -                        | -             | -33.1          | -              |

**Notes:**

**SNF** = Spectrum Analyzer Noise Floor, **H** = horizontal and **V** = vertical

**EIRP** = SG reading - CL + Gain (dBi)

**Margin** = EIRP – Limit



Continental Wireless, Inc.  
R5000-L-4.9 Broadband Wireless Router

Electromagnetic Compatibility  
Radiated Emissions Requirements  
CFR Title 47, Part 90, Subpart Y

## Radiated Emissions Spurious Test Setup



**Photograph 4. Radiated Emission Spurious Test Setup**



## 8. Electromagnetic Compatibility Frequency Stability Requirements

### 8.1. Frequency Stability

**Test Requirement(s):** §2.1055 and §90.213

**Test Procedures:** As required by 47 CFR 2.1055, *Frequency Stability measurements* were made at the RF output terminals using a Directional Coupler through a Spectrum Analyzer and Power Meter.

The EUT was placed in the Environmental Chamber and support equipments are outside the chamber on a table. Set the RBW = VBW = 300 Hz to Spectrum Analyzer. The SPAN was set to 5 kHz to show the frequency values in hertz from the Spectrum Analyzer. The EUT was set to a CW signal and to transmit in the low channel of the operating frequency range. Before setting the CW signal, adjusted enough to produce maximum output power as specified in the owner's manual. Frequency drift was investigated for every 10°C increment until the unit is stabilized then recorded the reading in tabular format with the temperature range of -30° to 50°C.

Voltage supplied to EUT is 120 Vac. Reference temperature was done at 20°C.

The Frequency Stability *Limit* is obtained by the following:

Measured 99% Occupied Bandwidth: 17.08 MHz  
EUT Center Frequency: 4980 MHz  
Authorized Bottom Frequency edge: 4990 MHz

Limit =  $(17.08/2) = 8.54$ ;  $4980 + 8.54 = 4988.54$ ;  $4990 - 4988.54 = 1.46$  MHz


**Test Results:** Equipment complies with Section 2.1055 and 90.213. The following pages show measurements of 99% Occupied Bandwidth plot and Frequency Drift data sheet which is recorded below:

**Test Engineer(s):** Kerwinn Corpuz

**Test Date(s):** 06/09/2005



## Frequency Stability Test Results



Plot 17. Measured Occupied Bandwidth

**Limit:** The carrier center frequency must not drift greater than 1.46 MHz.

**Reference Freq.:** 4979.956083 MHz at 20°C

| Temperature<br>(Celsius) | Measured<br>Freq (MHz) | Drift<br>(Hz) |
|--------------------------|------------------------|---------------|
| 50                       | 4979.916269            | -39814        |
| 40                       | 4979.937644            | -18439        |
| 30                       | 4979.968353            | 12270         |
| 20                       | Reference              |               |
| 10                       | 4980.018512            | 62429         |
| 0                        | 4980.027129            | 71046         |
| -10                      | 4980.040420            | 84337         |
| -20                      | 4980.046356            | 90273         |
| -30                      | 4980.049103            | 93020         |

Table 4. Temperature Vs. Frequency Test Results

**Reference:** 120Vac at 20°Celsius

**Freq.** = 4979.956083 MHz at 20°C

| Measured<br>Voltage(dc) | Measured<br>Freq (MHz) | Drift<br>(Hz) |
|-------------------------|------------------------|---------------|
| +/-15% of nominal       |                        |               |
| 102                     | 4979.955966            | -117          |
| 138                     | 4979.955991            | -92           |

Table 5. Frequency Vs. Voltage Test Results



## Frequency Stability Test Setup



Photograph 5. Frequency Stability Test Setup



## 9. Electromagnetic Compatibility Transient Frequency Behavior Requirements

### 9.1. Transient Frequency Behavior

**Test Requirement(s):** §90.214

**Test Procedures:** As required by 47 CFR 90.214, *Transient Frequency Behavior measurements* were made at the ON/OFF switch terminal.

**Test Results:** EUT is not required for this test.  
The EUT operating frequency is at 4.9 GHz.



## 10. Test Equipment

Calibrated test equipment utilized during testing was maintained in a current state of calibration per the requirements of ANSI/NCSL Z540-1-1994 and ANSI/ISO/IEC 17025:2000.

| Test Name: RF Power Output, PPSD & Emission Masks  |                                 |                       | Test Date(s): 6/6/05 |               |              |
|----------------------------------------------------|---------------------------------|-----------------------|----------------------|---------------|--------------|
| MET Asset #                                        | Nomenclature                    | Manufacturer          | Model                | Last Cal Date | Cal Due Date |
| 1S2430                                             | Power Meter                     | Anritsu Company       | ML2488A              | 01/12/2005    | 01/12/2006   |
| 1S2432                                             | Power Sensor                    | Anritsu Company       | MA2491A              | 01/12/2005    | 01/12/2006   |
| 1S2421                                             | EMI Test Receiver               | Rhode & Schwarz       | ES1B 7               | 02/09/2005    | 02/09/2006   |
| 1S2001                                             | DC Power Supply                 | Hewlett Packard       | 6236B                | See Note      |              |
| N/A                                                | 10 dB Attenuator                | Weinschel Corporation | 33-10-34             | See Note      |              |
| 1S2034                                             | Coupler, Directional 1-20 GHz   | KRYTAR                | 101020020            | See Note      |              |
| Test Name: Spurious Emissions at Antenna Terminals |                                 |                       | Test Date(s): 6/7/05 |               |              |
| MET Asset #                                        | Nomenclature                    | Manufacturer          | Model                | Last Cal Date | Cal Due Date |
| 1S2430                                             | Power Meter                     | Anritsu Company       | ML2488A              | 01/12/2005    | 01/12/2006   |
| 1S2432                                             | Power Sensor                    | Anritsu Company       | MA2491A              | 01/12/2005    | 01/12/2006   |
| 1S2293                                             | Analyzer, Spectrum 9 kHz-40GHz  | Hewlett Packard       | 8564E                | 09/30/2004    | 09/30/2005   |
| N/A                                                | 10 dB Attenuator                | Weinschel Corporation | 33-10-34             | See Note      |              |
| 1S2041                                             | Coupler, Bi Directional Coaxial | NARDA                 | N/A                  | See Note      |              |
| 1S2034                                             | Coupler, Directional 1-20 GHz   | KRYTAR                | 101020020            | See Note      |              |
| 1S2001                                             | DC Power Supply                 | Hewlett Packard       | 6236B                | See Note      |              |
| Test Name: Frequency Stability                     |                                 |                       | Test Date(s): 6/9/05 |               |              |
| MET Asset #                                        | Nomenclature                    | Manufacturer          | Model                | Last Cal Date | Cal Due Date |
| 1S2430                                             | Power Meter                     | Anritsu Company       | ML2488A              | 01/12/2005    | 01/12/2006   |
| 1S2432                                             | Power Sensor                    | Anritsu Company       | MA2491A              | 01/12/2005    | 01/12/2006   |
| 1S2293                                             | Analyzer, Spectrum 9 kHz-40GHz  | Hewlett Packard       | 8564E                | 09/30/2004    | 09/30/2005   |
| N/A                                                | 10 dB Attenuator                | Weinschel Corporation | 33-10-34             | See Note      |              |
| 1S2034                                             | Coupler, Directional 1-20 GHz   | KRYTAR                | 101020020            | See Note      |              |
| 1S2001                                             | DC Power Supply                 | Hewlett Packard       | 6236B                | See Note      |              |
| 1S22100                                            | Digital Multi Meter             | Fluke                 | 77 Series II         | 09/22/2004    | 09/22/2005   |
| 1S2229                                             | Chamber, Temperature            | Tenny Engineering     | T63C                 | 10/21/2004    | 10/21/2005   |



Continental Wireless, Inc.  
R5000-L-4.9 Broadband Wireless Router

Electromagnetic Compatibility  
Test Equipment  
CFR Title 47, Part 90, Subpart Y

| Test Name: Radiated Emissions (Substitution Method) |                                |                 | Test Date(s): 6/15/05 |               |              |
|-----------------------------------------------------|--------------------------------|-----------------|-----------------------|---------------|--------------|
| MET Asset #                                         | Nomenclature                   | Manufacturer    | Model                 | Last Cal Date | Cal Due Date |
| 1S2263                                              | Chamber, 10 Meter              | Rantec          | N2-14                 | 07/25/2005    | 07/25/2006   |
| 1S2293                                              | Analyzer, Spectrum 9 kHz-40GHz | Hewlett Packard | 8564E                 | 09/30/2004    | 09/30/2005   |
| 1S2278                                              | Generator, Swept Signal        | Hewlett Packard | 83650B                | 06/11/2004    | 06/11/2005   |
| 1U7                                                 | Antenna, Horn                  | EMCO            | 3115                  | 02/23/2005    | 02/23/2006   |
| 1S2198                                              | Antenna, Horn                  | EMCO            | 3115                  | 06/22/2004    | 06/22/2005   |
| 1S2129                                              | Mixer, Harmonic                | Hewlett Packard | 11970K                | 03/10/2003    | 03/10/2006   |
| 1S2128                                              | Mixer, Harmonic                | Hewlett Packard | 11970A                | 03/10/2003    | 03/10/2006   |
| 1S2121                                              | Pre-Amplifier                  | Hewlett Packard | 8449B                 | 10/14/2004    | 10/14/2005   |
| N/A                                                 | 7 GHz High Pass Filter         | Micro-Tronics   | HPM13147              | See Note      |              |

Note: Functionally tested equipment is verified using calibrated instrumentation at the time of testing.



## 11. RF Exposure Requirements

**RF Exposure Requirements:** §90.1217, §1.1307(b)(1) and §1.1307(b)(2): Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines.

**RF Radiation Exposure Limit:** §1.1310: As specified in this section, the Maximum Permissible Exposure (MPE) Limit shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in Sec. 1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of Sec. 2.1093 of this chapter.

MPE Limit Calculation: EUT's operating frequencies @ 4950 - 4980 MHz; conducted power = 24.15 dBm (peak) with maximum antenna gain of 26 dBi.

Therefore, **Limit for Uncontrolled exposure: 1 mW/cm<sup>2</sup> or 10 W/m<sup>2</sup>**

Equation from page 18 of OET 65, Edition 97-01

$$S = PG / 4\pi R^2 \quad \text{or} \quad R = \sqrt{PG / 4\pi S}$$

where, S = Power Density (10 W/m<sup>2</sup>)

P = Power Input to antenna (0.26 Watts)

G = Antenna Gain (398 numeric)

R = distance to the center of radiation of the antenna (in meter)

$$R = \sqrt{0.26W * 398dB / 4 * 3.14 * (10 W/m^2)} = \sqrt{103.48 / 125.6637} = 0.9075 \text{ meter}$$

The distance between the human and the RF antenna should not be less than 0.9075 meter.



## 12. Certification Label & User's Manual Information

### 12.1. Certification Information

The following is extracted from Title 47 of the Code of Federal Regulations, Part 2, Subpart I — Marketing of Radio frequency devices:

#### § 2.801 Radio-frequency device defined.

As used in this part, a radio-frequency device is any device which in its operation is capable of Emitting radio-frequency energy by radiation, conduction, or other means. Radio- frequency devices include, but are not limited to:

- (a) The various types of radio communication transmitting devices described throughout this chapter.
- (b) *The incidental, unintentional and intentional radiators defined in Part 15 of this chapter.*
- (c) The industrial, scientific, and medical equipment described in Part 18 of this chapter.
- (d) Any part or component thereof which in use emits radio-frequency energy by radiation, conduction, or other means.

#### § 2.803 Marketing of radio frequency devices prior to equipment authorization.

- (a) Except as provided elsewhere in this chapter, no person shall sell or lease, or offer for sale or lease (including advertising for sale or lease), or import, ship or distribute for the purpose of selling or leasing or offering for sale or lease, any radio frequency device unless:
  - (1) In the case of a device subject to certification, such device has been authorized by the Commission in accordance with the rules in this chapter and is properly identified and labeled as required by §2.925 and other relevant sections in this chapter; or
  - (2) In the case of a device that is not required to have a grant of equipment authorization issued by the Commission, but which must comply with the specified technical standards prior to use, such device also complies with all applicable administrative (including verification of the equipment or authorization under a Declaration of Conformity, where required), technical, labeling and identification requirements specified in this chapter.
- (d) Notwithstanding the provisions of paragraph (a) of this section, the offer for sale solely to business, commercial, industrial, scientific or medical users (but not an offer for sale to other parties or to end users located in a residential environment) of a radio frequency device that is in the conceptual, developmental, design or pre-production stage is permitted prior to equipment authorization or, for devices not subject to the equipment authorization requirements, prior to a determination of compliance with the applicable technical requirements *provided* that the prospective buyer is advised in writing at the time of the offer for sale that the equipment is subject to the FCC rules and that the equipment will comply with the appropriate rules before delivery to the buyer or to centers of distribution.



- (e)(1) Notwithstanding the provisions of paragraph (a) of this section, prior to equipment authorization or determination of compliance with the applicable technical requirements any radio frequency device may be operated, but not marketed, for the following purposes and under the following conditions:
- (i) *Compliance testing;*
  - (ii) Demonstrations at a trade show provided the notice contained in paragraph (c) of this section is displayed in a conspicuous location on, or immediately adjacent to, the device;
  - (iii) Demonstrations at an exhibition conducted at a business, commercial, industrial, scientific or medical location, but excluding locations in a residential environment, provided the notice contained in paragraphs (c) or (d) of this section, as appropriate, is displayed in a conspicuous location on, or immediately adjacent to, the device;
  - (iv) Evaluation of product performance and determination of customer acceptability, provided such operation takes place at the manufacturer's facilities during developmental, design or pre-production states; or
  - (v) Evaluation of product performance and determination of customer acceptability where customer acceptability of a radio frequency device cannot be determined at the manufacturer's facilities because of size or unique capability of the device, provided the device is operated at a business, commercial, industrial, scientific or medical user's site, but not at a residential site, during the development, design or pre-production stages.
- (e)(2) For the purpose of paragraphs (e)(1)(iv) and (e)(1)(v) of this section, the term *manufacturer's facilities* includes the facilities of the party responsible for compliance with the regulations and the manufacturer's premises, as well as the facilities of other entities working under the authorization of the responsible party in connection with the development and manufacture, but not the marketing, of the equipment.
- (f) For radio frequency devices subject to verification and sold solely to business, commercial, industrial, scientific and medical users (excluding products sold to other parties or for operation in a residential environment), parties responsible for verification of the devices shall have the option of ensuring compliance with the applicable technical specifications of this chapter at each end user's location after installation, provided that the purchase or lease agreement includes a provision that such a determination of compliance be made and is the responsibility of the party responsible for verification of the equipment.



**The following is extracted from Title 47 of the Code of Federal Regulations, Part 2, Subpart Y — Equipment Authorization Procedures:**

**§ 2.901 Basis and Purpose**

- (a) In order to carry out its responsibilities under the Communications Act and the various treaties and international regulations, and in order to promote efficient use of the radio spectrum, the Commission has developed technical standards for radio frequency equipment and parts or components thereof. The technical standards applicable to individual types of equipment are found in that part of the rules governing the service wherein the equipment is to be operated.<sup>1</sup> *In addition to the technical standards provided, the rules governing the service may require that such equipment be verified by the manufacturer or importer, be authorized under a Declaration of Conformity, or receive an equipment authorization from the Commission by one of the following procedures: certification or registration.*
- (b) The following sections describe the verification procedure, the procedure for a Declaration of Conformity, and the procedures to be followed in obtaining certification from the Commission and the conditions attendant to such a grant, whichever is applicable.

**§ 2.902 Certification.**

- (a) Certification is an equipment authorization issued by the Commission, based on representation and test data submitted by the applicant.
- (b) Certification attaches to all units subsequently marketed by the grantee which are identical (see Section 2.908) to the sample tested except for permissive changes or other variations authorized by the Commission pursuant to Section 2.1043.

---

<sup>1</sup> In this case, the equipment is subject to the rules of Part 15. More specifically, the equipment falls under Subpart B (of Part 15), which deals with unintentional radiators.



**§ 2.948 Description of measurement facilities.**

- (a) Each party making measurements of equipment that is subject to an equipment authorization under Part 15 or Part 18 of this chapter, regardless of whether the measurements are filed with the Commission or kept on file by the party responsible for compliance of equipment marketed within the U.S. or its possessions, shall compile a description of the measurement facilities employed.
  - (1) If the measured equipment is subject to the verification procedure, the description of the measurement facilities shall be retained by the party responsible for verification of the equipment.
    - (i) *If the equipment is verified through measurements performed by an independent laboratory, it is acceptable for the party responsible for verification of the equipment to rely upon the description of the measurement facilities retained by or placed on file with the Commission by that laboratory. In this situation, the party responsible for the verification of the equipment is not required to retain a duplicate copy of the description of the measurement facilities.*
    - (ii) If the equipment is verified based on measurements performed at the installation site of the equipment, no specific site calibration data is required. It is acceptable to retain the description of the measurement facilities at the site at which the measurements were performed.
  - (2) If the equipment is to be authorized by the Commission under the certification procedure, the description of the measurement facilities shall be filed with the Commission's Laboratory in Columbia, Maryland. The data describing the measurement facilities need only be filed once but must be updated as changes are made to the measurement facilities or as otherwise described in this section. At least every three years, the organization responsible for filing the data with the Commission shall certify that the data on file is current.



## 12.2. Label and User's Manual Information

The following is extracted from Title 47 of the Code of Federal Regulations, Part 15, Subpart A — General:

### § 15.19 Labeling requirements.

(a) *In addition to the requirements in Part 2 of this chapter, a device subject to certification or verification shall be labeled as follows:*

- (1) Receivers associated with the operation of a licensed radio service, e.g., FM broadcast under Part 73 of this chapter, land mobile operation under Part 90, etc., shall bear the following statement in a conspicuous location on the device:

This device complies with Part 15 of the FCC Rules. Operation is subject to the condition that this device does not cause harmful interference.

- (2) A stand-alone cable input selector switch, shall bear the following statement in a conspicuous location on the device:

This device is verified to comply with Part 15 of the FCC Rules for use with cable television service.

- (3) All other devices shall bear the following statement in a conspicuous location on the device:

*This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.*

- (4) Where a device is constructed in two or more sections connected by wires and marketed together, the statement specified under paragraph (a) of this section is required to be affixed only to the main control unit.
- (5) When the device is so small or for such use that it is not practicable to place the statement specified under paragraph (a) of this section on it, the information required by this paragraph shall be placed in a prominent location in the instruction manual or pamphlet supplied to the user or, alternatively, shall be placed on the container in which the device is marketed. However, the FCC identifier or the unique identifier, as appropriate, must be displayed on the device.



**§ 15.21 Information to user.**

The users manual or instruction manual for an intentional or unintentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

The following is extracted from Title 47 of the Code of Federal Regulations, Part 15, Subpart B — Unintentional Radiators:

**§ 15.105 Information to the user.**

- (a) For a Class B digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual:

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a residential environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.



Continental Wireless, Inc.  
R5000-L-4.9 Broadband Wireless Router

Electromagnetic Compatibility  
Certification Label & User's Manual Information  
CFR Title 47, Part 90, Subpart Y

---

# End of Report