



RF EXPOSURE REPORT

REPORT NO.: SA941122H03

MODEL NO.: BSAP-1540

ACCORDING: FCC Guidelines for Human Exposure
IEEE C95.1

APPLICANT: Bluesocket, Inc.

ADDRESS: 10 North Avenue Burlington, MA 01803

ISSUED BY: Advance Data Technology Corporation

LAB LOCATION: No. 81-1, Lu Liao Keng, 9 Ling, Wu Lung
Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien,
Taiwan, R.O.C.



RF Exposure Measurement

1. Introduction

In this document, we try to prove the safety of radiation harmfulness to the human body for our product. The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The Gain of the antenna used in this product is measured in a Fully Anechoic Chamber (FAC) calibrated for antenna measurement in ADT, and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis transmission formula is a far field assumption, the calculated result of that is an over-prediction for near field power density. We will take that as the worst case to specify the safety range.

2. RF Exposure Limit

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
(A)Limits For Occupational / Control Exposures				
300-1500	...	...	F/300	6
1500-100,000	...	...	5	6
(B)Limits For General Population / Uncontrolled Exposure				
300-1500	...	...	F/1500	6
1500-100,000	...	...	1.0	30

F = Frequency in MHz



3. Friis Formula

Friis transmission formula : $P_d = (P_{out} * G) / (4 * \pi * r^2)$

where

P_d = power density in mW/cm^2

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, $1 mW/cm^2$. If we know the maximum Gain of the antenna and the total power input to the antenna, through the calculation, we will know the MPE value at distance 20cm.

Ref. : David K. Cheng, *Field and Wave Electromagnetics*, Second Edition,
Page 640, Eq. (11-133).

4 EUT Operating condition

The software provided by Manufacturer enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

5. Classification

This is a stand alone radio device. So under normal use condition, it is easy to be re-located in the place where at least 20 cm far away from the body of the user. Warning statement to the user for keeping at least 20cm or more separation distance with the antenna should be included in users manual. So, this device is classified as **Mobile Device**.



6 Test Results

6.1 Antenna Gain

For 2.4GHz

Antenna 1: The maximum Gain of the antenna is 5dBi or 3.162(numeric).

Antenna 2: The maximum Gain of the antenna is 5dBi or 3.162(numeric).

Antenna 3: The maximum Gain of the antenna is 3dBi or 1.995(numeric).

Antenna 4: The maximum Gain of the antenna is 7dBi or 5.012(numeric).

Antenna 5: The maximum Gain of the antenna is 3dBi or 1.995(numeric).

For 5GHz

Antenna 1: The maximum Gain of the antenna is 3dBi or 1.995(numeric).

Antenna 2: The maximum Gain of the antenna is 8dBi or 6.310(numeric).

Antenna 3: The maximum Gain of the antenna is 5dBi or 3.162 (numeric).

For 2.4GHz				
No.	Model No.	Gain (dBi)	Antenna Type	Antenna Connector
1	S2403BPX	5 dBi	2.400-2.500 GHz Special Purpose Omni Antenna	Reverse SMA
2	SR2405135D/ SR24135DA	5 dBi	PCS/DCS and 2.4 GHz Wide Angle Coverage Directional Antennas	Reverse SMA
3	S24493DS	3 dBi	Dual Band, Tri-mode 802.11b/a/g Spatial Diversity Omnidirectional Antenna	Reverse SMA
4	S24497P	7 dBi	Dual Band, Tri-mode Directional Antenna	Reverse SMA
5	FDS_2FED01+I3G	3 dBi	Dual Band Antenna, Dipole	MMCX
For 5GHz				
No.	Model No.	Gain (dBi)	Antenna Type	Antenna Connector
1	S24493DS	3 dBi	Dual Band, Tri-mode 802.11b/a/g Spatial Diversity Omnidirectional Antenna	Reverse SMA
2	S24497P	8 dBi	Dual Band, Tri-mode Directional Antenna	Reverse SMA
3	FDS_2FED01+I3G	5 dBi	Dual Band Antenna, Dipole	MMCX
Note:				
1. All of the above antennas are outdoor Antenna except the antenna model No.: FDS_2FED01+I3G.				

6.2 Output Power Into Antenna & RF Exposure value at distance 20cm:

For 2.4GHz

802.11b:

Antenna 1

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	123.027	0.077	1.0
6	2437	138.038	0.087	1.0
11	2462	56.234	0.035	1.0

Antenna 2

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	123.027	0.077	1.0
6	2437	138.038	0.087	1.0
11	2462	56.234	0.035	1.0

Antenna 3

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	123.027	0.049	1.0
6	2437	138.038	0.055	1.0
11	2462	56.234	0.022	1.0

Antenna 4

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	123.027	0.123	1.0
6	2437	138.038	0.138	1.0
11	2462	56.234	0.056	1.0

Antenna 5

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	123.027	0.049	1.0
6	2437	138.038	0.055	1.0
11	2462	56.234	0.022	1.0



802.11g:

Antenna 1

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	70.795	0.045	1.0
6	2437	245.471	0.154	1.0
11	2462	36.308	0.023	1.0

Antenna 2

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	70.795	0.071	1.0
6	2437	245.471	0.245	1.0
11	2462	36.308	0.036	1.0

Antenna 3

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	70.795	0.028	1.0
6	2437	245.471	0.097	1.0
11	2462	36.308	0.014	1.0

Antenna 4

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	70.795	0.045	1.0
6	2437	245.471	0.154	1.0
11	2462	36.308	0.023	1.0

Antenna 5

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	70.795	0.028	1.0
6	2437	245.471	0.097	1.0
11	2462	36.308	0.014	1.0

**For 5GHz**

Operated in 5250MHz ~ 5350MHz band: (15.407)

Antenna 1

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	5260	146.555	0.058	1.0
4	5320	98.628	0.039	1.0

Antenna 2

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	5260	146.555	0.184	1.0
4	5320	98.628	0.124	1.0

Antenna 3

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	5260	146.555	0.073	1.0
4	5320	98.628	0.049	1.0



Operated in 5725 ~ 5850MHz band: (15.247)

Antenna 1

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	5745	251.189	0.100	1.0
3	5785	218.776	0.087	1.0
5	5825	213.796	0.085	1.0

Antenna 2

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	5745	251.189	0.315	1.0
3	5785	218.776	0.275	1.0
5	5825	213.796	0.268	1.0

Antenna 3

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	5745	251.189	0.158	1.0
3	5785	218.776	0.138	1.0
5	5825	213.796	0.135	1.0