

Frequency [MHz]	Cable loss [dB]	AF [1/m]	Corrected measures [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
			P	AV	P	AV	P	AV
lowest								
4824	3.22	34.5	61.4	37.6	74	54	-12.6	-16.4
7246.527284	4.32	37.3	57.9	36	74	54	-16.1	-18
9660.786034	4.69	39.8	48.4	30	74	54	-25.6	-24
12072.12728	7.18	41	62.8	44.6	74	54	-11.2	-9.4
14485.44353	7.62	41.1	45	31.7	74	54	-29	-22.3
middle								
4866.385	3.31	34.5	60.8	43.3	74	54	-13.2	-10.7
7298.05	4.45	37.3	57.9	43.2	74	54	-16.1	-10.8
9729.12	4.82	39.8	44.2	29.5	74	54	-29.8	-24.5
12159.4225	7.32	41	62.7	47.4	74	54	-11.3	-6.6
14592.47125	7.75	41.1	49.4	34	74	54	-24.6	-20
highest								
4936	3.39	34.5	59.6	48.9	74	54	-14.4	-5.1
7402.928469	4.52	37.3	59.1	44	74	54	-14.9	-10
9869.320969	4.95	39.8	49.5	33.9	74	54	-24.5	-20.1
12341.77722	7.48	41	62.8	44.6	74	54	-11.2	-9.4
14809.15597	7.84	41.1	48.7	35.2	74	54	-25.3	-18.8

P=Peak Detection
AV=Average Detection