MEASUREMENT REPORT

FCC PART 15 Subpart C WLAN 802.11b/g/n

FCC ID:	TK4WSD377
APPLICANT:	Compex Systems Pte Ltd
Application Type:	Certification
Product:	2.4GHz/5GHz WiFi + Bluetooth Combination Module
Model No.:	WSD377
Serial No.	WSD377-I ,WSD377-EVK
Brand Name:	COMPEX
FCC Classification:	Digital Transmission System (DTS)
FCC Rule Part(s):	Part15 Subpart C (Section 15.247)
Test Procedure(s):	ANSI C63.10-2013, KDB 558074 D01v05
Test Date:	December 13 ~ 29, 2018

Reviewed By: Jame Yuan

(Jame Yuan)

Approved By: Robin Wu

(Robin Wu)

ACCREDITED
TESTING LABORATORY
CERTIFICATE #3628.01

The test results relate only to the samples tested.
This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013. Test results reported herein relate only to the item(s) tested.
The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
1812RSU007-U2	Rev. 01	Initial report	12-29-2018	Valid

CONTENTS

Description Page

§2.1033 General Information 5

1. INTRODUCTION 6

1.1. Scope 6
1.2. MRT Test Location 6

2. PRODUCT INFORMATION 7

2.1. Feature of Equipment under Test 7
2.2. Product Specification Subjective to this Report 7
2.3. Description of Available Antennas 7
2.4. Working Frequencies for this report 8
2.5. Test Mode 8
2.6. Description of Test Software 8
2.7. Device Capabilities 9
2.8. Test Configuration 10
2.9. EMI Suppression Device(s)/Modifications 10
2.10. Labeling Requirements 10

3. DESCRIPTION of TEST 11

3.1. Evaluation Procedure 11
3.2. AC Line Conducted Emissions 11
3.3. Radiated Emissions 12

4. ANTENNA REQUIREMENTS 13

5. TEST EQUIPMENT CALIBRATION DATE 14

6. MEASUREMENT UNCERTAINTY 15

7. TEST RESULT 16

7.1. Summary 16
7.2. 6dB Bandwidth Measurement 17
7.2.1. Test Limit 17
7.2.2. Test Procedure used 17
7.2.3. Test Setting 17
7.2.4. Test Setup 17
7.2.5. Test Result 18
7.3. Output Power Measurement 23
7.3.1. Test Limit 23
7.3.2. Test Procedure Used 23

7.3.3. Test Setting 23
7.3.4. Test Setup 23
7.3.5. Test Result 24
7.4. Power Spectral Density Measurement 26
7.4.1. Test Limit 26
7.4.2. Test Procedure Used 26
7.4.3. Test Setting 26
7.4.4. Test Setup 27
7.4.5. Test Result 28
7.5. Conducted Band Edge and Out-of-Band Emissions 33
7.5.1. Test Limit 33
7.5.2. Test Procedure Used 33
7.5.3. Test Settitng 33
7.5.4. Test Setup 34
7.5.5. Test Result 35
7.6. Radiated Spurious Emission Measurement 44
7.6.1. Test Limit 44
7.6.2. Test Procedure Used 44
7.6.3. Test Setting 44
7.6.4. Test Setup 46
7.6.5. Test Result 48
7.7. Radiated Restricted Band Edge Measurement 62
7.7.1. Test Limit 62
7.7.2. Test Procedure Used 63
7.7.3. Test Setting 63
7.7.4. Test Setup 64
7.7.5. Test Result 65
7.8. AC Conducted Emissions Measurement 97
7.8.1. Test Limit 97
7.8.2. Test Setup 97
7.8.3. Test Result 98

8. CONCLUSION 100

Appendix A - Test Setup Photograph 101

Appendix B - EUT Photograph 102

§2.1033 General Information

Applicant:	Compex Systems Pte Ltd
Applicant Address:	No:9 Harrison Road, Harrison Industrial Building, #05-01, Singapore 369651
Manufacturer:	Compex Systems Pte Ltd
Manufacturer Address:	No:9 Harrison Road, Harrison Industrial Building, #05-01, Singapore 369651
Test Site:	MRT Technology (Suzhou) Co., Ltd
Test Site Address:	D8 Building, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China
FCC Registration No.:	893164
Test Device Serial No.:	N/A ☐ Production ☒ Pre-Production ☐ Engineering

Test Facility / Accreditations

Measurements were performed at MRT Laboratory located in Tian'edang Rd., Suzhou, China.

- **MRT facility is a FCC registered (MRT Reg. No. 893164) test facility with the site description report on file and has met all the requirements specified in ANSI C63.4-2014.**
- **MRT facility is an IC registered (MRT Reg. No. 11384A-1) test laboratory with the site description on file at Industry Canada.**
- **MRT facility is a VCCI registered (R-20025, G-20034, C-20020, T-20020) test laboratory with the site description on file at VCCI Council.**
- **MRT Lab is accredited to ISO 17025 by the American Association for Laboratory Accreditation (A2LA) under the American Association for Laboratory Accreditation Program (A2LA Cert. No. 3628.01) in EMC, Telecommunications, Radio and SAR testing.**

Accredited Laboratory

A2LA has accredited

MRT TECHNOLOGY (SUZHOU) CO., LTD.

Suzhou, Jiangsu, People's Republic of China

for technical competence in the field of

Electrical Testing

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated April 2017).

Presented this 24th day of July 2018.

President and CEO
For the Accreditation Council
Certificate Number 3628.01
Valid to August 31, 2020

For the tests to which this accreditation applies, please refer to the laboratory's Electrical Scope of Accreditation.

1. INTRODUCTION

1.1. Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

1.2. MRT Test Location

The map below shows the location of the MRT LABORATORY, its proximity to the Taihu Lake. These measurement tests were conducted at the MRT Technology (Suzhou) Co., Ltd. Facility located at D8 Building, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China. The measurement facility compliant with the test site requirements specified in ANSI C63.4-2014.



2. PRODUCT INFORMATION

2.1. Feature of Equipment under Test

Product Name:	2.4GHz/5GHz WiFi + Bluetooth Combination Module
Model No.:	WSD377
Serial No.:	WSD377-I ,WSD377-EVK
Brand Name:	COMPEX
Wi-Fi Specification:	802.11a/b/g/n/ac
Bluetooth Specification:	v4.2 single mode

Note: The difference between these models is only for different market.

2.2. Product Specification Subjective to this Report

Frequency Range:	802.11b/g/n-HT20: 2412 ~ 2462MHz 802.11n-HT40: 2422 ~ 2452MHz
Channel Number:	802.11b/g/n-HT20: 11 802.11n-HT40: 7
Type of Modulation:	802.11b: DSSS 802.11g/n: OFDM
Data Rate:	802.11b: 1/2/5.5/11Mbps 802.11g: 6/9/12/18/24/36/48/54Mbps 802.11n: up to 150Mbps

Note: For other features of this EUT, test report will be issued separately.

2.3. Description of Available Antennas

Antenna Type	Frequency Band (MHz)	TX Paths	Antenna Gain (dBi)
Dipole Antenna	2400 ~ 2483.5	1*1	5.0
	5150 ~ 5850	1*1	7.0

2.4. Working Frequencies for this report

802.11b/g/n-HT20

Channel	Frequency	Channel	Frequency	Channel	Frequency
01	2412 MHz	02	2417 MHz	03	2422 MHz
04	2427 MHz	05	2432 MHz	06	2437 MHz
07	2442 MHz	08	2447 MHz	09	2452 MHz
10	2457 MHz	11	2462 MHz	--	--

802.11n-HT40

Channel	Frequency	Channel	Frequency	Channel	Frequency
03	2422 MHz	04	2427 MHz	05	2432 MHz
06	2437 MHz	07	2442 MHz	08	2447 MHz
09	2452 MHz	--	--	--	--

2.5. Test Mode

Test Mode	Mode 1: Transmit by 802.11b (1Mbps)
	Mode 2: Transmit by 802.11g (6Mbps)
	Mode 3: Transmit by 802.11n-HT20 (MCS0)
	Mode 4: Transmit by 802.11n-HT40 (MCS0)

2.6. Description of Test Software

The test utility software used during testing was “QRCT3”, and the version was “v3.0-00268”.

Power setting was refered to operation description.

2.7. Device Capabilities

This device contains the following capabilities:

2.4GHz WLAN (DTS), 5GHz WLAN (UNII), Bluetooth (v2.1 + EDR)

Note: 2.4GHz WLAN (DTS) operation is possible in 20MHzand 40MHzchannel bandwidths. The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

Model No.	Test Mode	Duty Cycle
WSD377	802.11b	98.41%
	802.11g	92.15%
	802.11n-HT20	90.10%
	802.11n-HT40	82.07%

802.11b (T = 12.40ms)



802.11g (T = 2.055ms)



802.11n-HT20 (T = 1.730ms)



802.11n-HT40 (T = 846.1us)



2.8. Test Configuration

The **2.4GHz/5GHz WiFi + Bluetooth Combination Module** was tested per the guidance of ANSI C63.10-2013. ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing.

2.9. EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

2.10. Labeling Requirements

Per 2.1074 & 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase. However, when the device is so small wherein placement of the label with specified statement is not practical, only the FCC ID must be displayed on the device per Section 15.19(a)(5). Please see attachment for FCC ID label and label location.

3. DESCRIPTION of TEST

3.1. Evaluation Procedure

The measurement procedures described in the American National Standard for Testing Unlicensed Wireless Devices (ANSI C63.10-2013), and the guidance provided in ANSI C63.10 was used in the measurement of the **2.4GHz/5GHz WiFi + Bluetooth Combination Module.**

Deviation from measurement procedure…….....None

3.2. AC Line Conducted Emissions

The line-conducted facility is located inside an 8'x4'x4' shielded enclosure. A 1m x 2m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50uH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference ground-plane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the receiver and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The receiver was scanned from 150kHz to 30MHz. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 9kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Each emission was also maximized by varying: power lines, the mode of operation or data exchange speed, or support equipment whichever determined the worst-case emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions are used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

An extension cord was used to connect to a single LISN which powered by EUT. The extension cord was calibrated with LISN, the impedance and insertion loss are compliance with the requirements as stated in ANSI C63.10-2013.

3.3. Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. A MF Model 210SS turntable is used for radiated measurement. It is a continuously rotatable, remote controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm high PVC support structure is placed on top of the turntable.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHzup to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up for frequencies below 1GHz was placed on top of the 0.8 meter high, 1 x 1.5 meter table; and test set-up for frequencies 1-40GHz was placed on top of the 1.5 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions. According to 3dB Beam-Width of horn antenna, the horn antenna should be always directed to the EUT when rising height.

4. ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

- The antenna of the EUT uses a unique (IPEX) connector.

Conclusion:

The **2.4GHz/5GHz WiFi + Bluetooth Combination Module** unit complies with the requirement of §15.203.

5. TEST EQUIPMENT CALIBRATION DATE

Conducted Emissions - SR2

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
EMI Test Receiver	R&S	ESR3	MRTSUE06185	1 year	2019/04/20
Two-Line V-Network	R&S	ENV216	MRTSUE06002	1 year	2019/06/15
Two-Line V-Network	R&S	ENV216	MRTSUE06003	1 year	2019/06/15
Temperature/Humidity Meter	Testo	608-H1	MRTSUE06404	1 year	2019/08/15
Shielding Anechoic Chamber	Mikebang	Chamber-SR2	MRTSUE06215	N/A	N/A

Radiated Emissions - AC1

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
PXA Signal Analyzer	Keysight	9030B	MRTSUE06395	1 year	2019/09/05
EMI Test Receiver	R&S	ESR7	MRTSUE06001	1 year	2019/08/14
EXA Signal Analyzer	Agilent	N9020A	MRTSUE06106	1 year	2019/04/20
Loop Antenna	Schwarzbeck	FMZB 1519	MRTSUE06025	1 year	2019/11/09
Bilog Period Antenna	Schwarzbeck	VULB 9168	MRTSUE06172	1 year	2019/04/12
Broad Band Horn Antenna	Schwarzbeck	BBHA9120D	MRTSUE06023	1 year	2019/10/20
Broad Band Horn Antenna	Schwarzbeck	BBHA 9170	MRTSUE06024	1 year	2019/12/13
Microwave System Amplifier	Agilent	83017A	MRTSUE06076	1 year	2019/11/16
Amplifier	Schwarzbeck	BBV 9721	MRTSUE06121	1 year	2019/06/12
Temperature/Humidity Meter	Testo	608-H1	MRTSUE06403	1 year	2019/08/15
Anechoic Chamber	TDK	Chamber-AC1	MRTSUE06212	1 year	2019/05/02

Conducted Test Equipment - TR3

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
EXA Signal Analyzer	KEYSIGHT	N9010B	MRTSUE06452	1 year	2019/07/20
USB wideband power sensor	KEYSIGHT	U2021XA	MRTSUE06446	1 year	2019/07/20
Attenuator	MVE	MVE2211-10	MRTSUE06800	1 year	2019/07/10
Temperature & Humidity Chamber	BAOYT	BYH-150CL	MRTSUE06051	1 year	2019/11/06
Thermohygrometer	testo	608-H1	MRTSUE06401	1 year	2019/08/15

Software	**Version**	**Function**
e3	V 8.3.5	EMI Test Software

6. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k = 2.

AC Conducted Emission Measurement - SR2
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): 150kHz~30MHz: 3.46dB
Radiated Emission Measurement - AC1
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): 9kHz ~ 1GHz: 4.18dB 1GHz ~ 25GHz: 4.76dB
Spurious Emissions, Conducted - TR3
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): 0.78dB
Output Power - TR3
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): 1.13dB
Power Spectrum Density - TR3
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): 1.15dB
Occupied Bandwidth - TR3
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): 0.28%

7. TEST RESULT

7.1. Summary

Product Name: **2.4GHz/5GHz WiFi + Bluetooth Combination Module**

FCC ID: **TK4WSD377**

FCC Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.247(a)(2)	6dB Bandwidth	≥ 500kHz	Conducted	Pass	Section 7.2
15.247(b)(3)	Output Power	≤ 30dBm		Pass	Section 7.3
15.247(e)	Power Spectral Density	≤ 8dBm/3kHz		Pass	Section 7.4
15.247(d)	Band Edge / Out-of-Band Emissions	30dBc(Average)		Pass	Section 7.5
15.205 15.209	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209	Radiated	Pass	Section 7.6 & 7.7
15.207	AC Conducted Emissions 150kHz - 30MHz	< FCC 15.207 limits	Line Conducted	Pass	Section 7.8

Notes:

1) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.

2) All modes of operation and data rates were investigated. For radiated emission test, every axis (X, Y, Z) was also verified. The test results shown in the following sections represent the worst case emissions.

7.2. 6dB Bandwidth Measurement

7.2.1.Test Limit

The minimum 6dB bandwidth shall be at least 500 kHz.

7.2.2.Test Procedure used

ANSI C63.10-2013 Section 11.8

7.2.3.Test Setting

1. The Spectrum's automatic bandwidth measurement capability was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to X = 6. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. Set RBW = 100 kHz
3. VBW ≥ 3 × RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. Allow the trace was allowed to stabilize

7.2.4.Test Setup



7.2.5.Test Result

Product	2.4GHz/5GHz WiFi + Bluetooth Combination Module	Temperature	25°C
Test Engineer	Flag Yang	Relative Humidity	54%
Test Site	TR3	Test Date	2018/12/18
Test Item	6dB Bandwidth		

Test Mode	Data Rate / MCS	Channel No.	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)	Result
802.11b	1Mbps	01	2412	8.10	≥ 0.5	Pass
802.11b	1Mbps	06	2437	8.10	≥ 0.5	Pass
802.11b	1Mbps	11	2462	8.10	≥ 0.5	Pass
802.11g	6Mbps	01	2412	15.17	≥ 0.5	Pass
802.11g	6Mbps	06	2437	15.16	≥ 0.5	Pass
802.11g	6Mbps	11	2462	15.17	≥ 0.5	Pass
802.11n-HT20	MCS0	01	2412	15.18	≥ 0.5	Pass
802.11n-HT20	MCS0	06	2437	15.17	≥ 0.5	Pass
802.11n-HT20	MCS0	11	2462	15.18	≥ 0.5	Pass
802.11n-HT40	MCS0	03	2422	35.16	≥ 0.5	Pass
802.11n-HT40	MCS0	06	2437	35.17	≥ 0.5	Pass
802.11n-HT40	MCS0	09	2452	35.18	≥ 0.5	Pass

802.11b 6dB Bandwidth	
Channel 01 (2412MHz)	Channel 06 (2437MHz)
	
Channel 11 (2462MHz)	
	

802.11g 6dB Bandwidth

Channel 01 (2412MHz)



Channel 06 (2437MHz)



Channel 11 (2462MHz)



802.11n-HT20 6dB Bandwidth	
Channel 01 (2412MHz)	Channel 06 (2437MHz)
	
Channel 11 (2462MHz)	
	

802.11n-HT40 6dB Bandwidth	
Channel 03 (2422MHz)	Channel 06 (2437MHz)
	
Channel 09 (2452MHz)	
	

7.3. Output Power Measurement

7.3.1.Test Limit

The maximum output power shall be less 1 Watt (30dBm).

The conducted output power limit specified in paragraph FCC Part 15.247(b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs FCC Part 15.247(b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

7.3.2.Test Procedure Used

ANSI C63.10 Section 11.9.2.3.2

7.3.3.Test Setting

Average Power Measurement

Average power measurements were perform only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter.

7.3.4.Test Setup



7.3.5.Test Result

Power output test was verified over all data rates of each mode shown as below table, and then choose the maximum power output (gray marker) for final test of each channel.

Test Mode	Bandwidth (MHz)	Channel No.	Frequency (MHz)	Data Rate/ MCS	Average Power (dBm)
802.11b	20	6	2437	1Mbps	16.58
				2Mbps	16.42
				5.5Mbps	16.38
				11Mbps	16.03
802.11g	20	6	2437	6Mbps	16.81
				9Mbps	16.73
				12Mbps	16.64
				24Mbps	16.51
				36Mbps	16.44
				48Mbps	16.28
				54Mbps	16.19
802.11n	20	6	2437	MCS0	15.62
				MCS1	15.55
				MCS2	15.42
				MCS3	15.34
				MCS4	15.27
				MCS5	15.16
				MCS6	15.10
				MCS7	15.05
802.11n	40	6	2437	MCS0	15.62
				MCS1	15.54
				MCS2	15.42
				MCS3	15.28
				MCS4	15.19
				MCS5	15.11
				MCS6	15.06
				MCS7	15.01

Product	2.4GHz/5GHz WiFi + Bluetooth Combination Module	Temperature	25°C
Test Engineer	Flag Yang	Relative Humidity	54%
Test Site	TR3	Test Date	2018/12/15
Test Item	Output Power		

Test Mode	Data Rate/ MCS	Channel No.	Freq. (MHz)	Average Power (dBm)	Limit (dBm)	Result
802.11b	1Mbps	01	2412	16.32	≤ 30.00	Pass
802.11b	1Mbps	06	2437	16.58	≤ 30.00	Pass
802.11b	1Mbps	11	2462	17.87	≤ 30.00	Pass
802.11g	6Mbps	01	2412	16.75	≤ 30.00	Pass
802.11g	6Mbps	06	2437	16.81	≤ 30.00	Pass
802.11g	6Mbps	11	2462	16.73	≤ 30.00	Pass
802.11n-HT20	MCS0	01	2412	15.97	≤ 30.00	Pass
802.11n-HT20	MCS0	06	2437	15.62	≤ 30.00	Pass
802.11n-HT20	MCS0	11	2462	15.53	≤ 30.00	Pass
802.11n-HT40	MCS0	03	2422	15.66	≤ 30.00	Pass
802.11n-HT40	MCS0	06	2437	15.75	≤ 30.00	Pass
802.11n-HT40	MCS0	09	2452	14.27	≤ 30.00	Pass

7.4. Power Spectral Density Measurement

7.4.1.Test Limit

The maximum permissible power spectral density is 8dBm in any 3 kHz band.

The same method of determining the conducted output power shall be used to determine the power spectral density.

7.4.2.Test Procedure Used

ANSI C63.10 Section 11.10.5

7.4.3.Test Setting

1. Measure the duty cycle (x) of the transmitter output signal.
2. Set instrument center frequency to DTS channel center frequency.
3. Set span to at least 1.5 times the OBW.
4. RBW = 10 kHz.
5. VBW = 30 kHz.
6. Detector = RMS.
7. Ensure that the number of measurement points in the sweep ≥ 2 x span/RBW.
8. Sweep time = auto couple.
9. Don’t use sweep triggering. Allow sweep to “free run”.
10. Employ trace averaging (RMS) mode over a minimum of 100 traces.
11. Use the peak marker function to determine the maximum amplitude level.
12. Add 10 log (1/x), where x is the duty cycle measured in step (a, to the measured PSD to compute the average PSD during the actual transmission time.

7.4.4.Test Setup



7.4.5.Test Result

Product	2.4GHz/5GHz WiFi + Bluetooth Combination Module	Temperature	25°C
Test Engineer	Flag Yang	Relative Humidity	54%
Test Site	TR3	Test Date	2018/12/19
Test Item	Power Spectral Density		

Test Mode	Data Rate / MCS	Channel No.	Freq. (MHz)	AVGPSD (dBm/ 10kHz)	Duty Cycle (%)	Final AVGPSD (dBm/3kHz)	Limit (dBm/ 3kHz)	Result
11b	1Mbps	01	2412	-8.22	98.41	-8.22	≤ 8.0	Pass
11b	1Mbps	06	2437	-7.81	98.41	-7.81	≤ 8.0	Pass
11b	1Mbps	11	2462	-8.26	98.41	-8.26	≤ 8.0	Pass
11g	6Mbps	01	2412	-12.97	92.15	-12.61	≤ 8.0	Pass
11g	6Mbps	06	2437	-11.57	92.15	-11.21	≤ 8.0	Pass
11g	6Mbps	11	2462	-12.19	92.15	-11.84	≤ 8.0	Pass
11n-HT20	MCS0	01	2412	-12.61	90.10	-12.16	≤ 8.0	Pass
11n-HT20	MCS0	06	2437	-12.88	90.10	-12.43	≤ 8.0	Pass
11n-HT20	MCS0	11	2462	-12.51	90.10	-12.06	≤ 8.0	Pass
11n-HT40	MCS0	03	2422	-17.26	82.07	-16.40	≤ 8.0	Pass
11n-HT40	MCS0	06	2437	-15.70	82.07	-14.85	≤ 8.0	Pass
11n-HT40	MCS0	09	2452	-18.81	82.07	-12.72	≤ 8.0	Pass

Note 1: When EUT duty cycle ≥ 98%, Final AVGPSD (dBm/3kHz) = AVGPSD (dBm/10kHz).

Note 2: When EUT duty cycle < 98%, Final AVGPSD (dBm/3kHz) = AVGPSD (dBm/10kHz) + 10*log (1/Duty cycle).

Product	2.4GHz/5GHz WiFi + Bluetooth Combination Module	Temperature	25°C
Test Engineer	Flag Yang	Relative Humidity	54%

802.11b AVGPSD

Channel 01 (2412MHz)

Channel 06 (2437MHz)

Channel 11 (2462MHz)

802.11g AVGPSD	
Channel 01 (2412MHz)	Channel 06 (2437MHz)
	
Channel 11 (2462MHz)	
	

802.11n-HT20 AVGPSD	
Channel 01 (2412MHz)	Channel 06 (2437MHz)
	
Channel 11 (2462MHz)	
	

802.11n-HT40 AVGPSD	
Channel 03 (2422MHz)	Channel 06 (2437MHz)
	
Channel 09 (2452MHz)	
	

7.5. Conducted Band Edge and Out-of-Band Emissions

7.5.1.Test Limit

The limit for out-of-band spurious emissions at the band edge is 30dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100 kHz bandwidth per the PSD procedure.

7.5.2.Test Procedure Used

ANSI C63.10 Section 11.11

7.5.3.Test Settitng

Reference level measurement

1. Set instrument center frequency to DTS channel center frequency
2. Set the span to ≥ 1.5 times the DTS bandwidth
3. Set the RBW = 100 kHz
4. Set the VBW ≥ 3 x RBW
5. Detector = peak
6. Sweep time = auto couple
7. Trace mode = max hold
8. Allow trace to fully stabilize

Emission level measurement

1. Set the center frequency and span to encompass frequency range to be measured
2. RBW = 1.3MHz
3. VBW = 4MHz
4. Detector = Peak
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

Test Notes

1. RBW was set to 1.3MHzrather than 100 kHz in order to increase the measurement speed.
2. The display line shown in the following plots denotes the limit at 30dB below the fundamental emission level measured in a 100 kHz bandwidth. However, since the traces in the following plots are measured with a 1.3MHz RBW, the display line may not necessarily appear to be 30dB below the level of the fundamental in a 1.3MHzbandwidth.
3. For plots showing conducted spurious emissions near the limit, the frequencies were investigated with a reduced RBW to ensure that no emissions were present.

7.5.4.Test Setup



7.5.5.Test Result

Product	2.4GHz/5GHz WiFi + Bluetooth Combination Module	Temperature	25°C
Test Engineer	Flag Yang	Relative Humidity	54%
Test Site	TR3	Test Date	2018/12/19
Test Item	Conducted Band Edge and Out-of-Band Emissions		

Test Mode	Data Rate / MCS	Channel No.	Frequency (MHz)	Limit (dBc)	Result
802.11b	1Mbps	01	2412	30	Pass
802.11b	1Mbps	06	2437	30	Pass
802.11b	1Mbps	11	2462	30	Pass
802.11g	6Mbps	01	2412	30	Pass
802.11g	6Mbps	06	2437	30	Pass
802.11g	6Mbps	11	2462	30	Pass
802.11n-HT20	MCS0	01	2412	30	Pass
802.11n-HT20	MCS0	06	2437	30	Pass
802.11n-HT20	MCS0	11	2462	30	Pass
802.11n-HT40	MCS0	03	2422	30	Pass
802.11n-HT40	MCS0	06	2437	30	Pass
802.11n-HT40	MCS0	09	2452	30	Pass

802.11b Out-of-Band Emissions

Channel 01 (2412MHz)

100kHz PSD reference Level



Low Band Edge

Spurious Emission

Channel 06 (2437MHz)

100kHz PSD reference Level

Spurious Emission

802.11b Out-of-Band Emissions	
Channel 11 (2462MHz)	
100kHz PSD reference Level	High Band Edge
	
Spurious Emission	

802.11g Out-of-Band Emissions

Channel 01 (2412MHz)

100kHz PSD reference Level



Low Band Edge

Spurious Emission

Channel 06 (2437MHz)

100kHz PSD reference Level

Spurious Emission



802.11g Out-of-Band Emissions	
Channel 11 (2462MHz)	
100kHz PSD reference Level	High Band Edge
	
Spurious Emission	