verify No.342462780739

위변조방지/진위확인
www.docuqr.com

# TEST REPORT

**KCTL Inc.**
65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr



KCTL

**1. Client**

- Name : Suprema Inc.
- Address : 16F Parkview Office Tower, Jeongja-dong, Bundang-gu, Seongnam, Gyeonggi, 463-863, Korea
- Date of Receipt : 2018-06-01

**2. Use of Report** : -

**3. Name of Product and Model** : XPass D2 / XPD2-GKDBS

**4. Manufacturer and Country of Origin** : Suprema Inc. / Korea

**5. FCC ID** : TKWXPD2-GKDBS

**6. Date of Test** : 2018-06-12 to 2018-06-14

**7. Test Standards** : FCC Part 15 Subpart C 15.225

**8. Test Results** : Refer to the test result in the test report

| | | |
|---|---|---|
| Affirmation | Tested by<br>Name : Dokyun Lee (Signature) | Technical Manager<br>Name : Jongha Choi (Signature) |

2018-06-22

## KCTL Inc.

As a test result of the sample which was submitted from the client, this report does not guarantee the whole product quality. This test report should not be used and copied without a written agreement by KCTL Inc.

REPORT REVISION HISTORY

| Date | Revision | Page No |
|---|---|---|
| 2018-06-22 | Originally issued | - |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |

*This report shall not be reproduced except in full, without the written approval of KCTL Inc. This document may be altered or revised by KCTL Inc. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KCTL Inc. will constitute fraud and shall nullify the document.*

# [ Contents ]

**1. Client information ..... 4**
**2. Laboratory information ..... 5**
**3. Description of E.U.T. ..... 6**
3.1 Basic description ..... 6
3.2 General description ..... 6
3.3 Test frequency ..... 6
**4. Summary of test results ..... 7**
4.1 Standards & results ..... 7
4.2 Uncertainty ..... 7
**5. Test results ..... 8**
5.1 Antenna Requirement ..... 8
5.2 In-band Fundamental Emission ..... 9
5.3 In-band Spurious Emission ..... 11
5.4 Out-of-band Spurious Emission ..... 12
5.5 Frequency tolerance ..... 14
5.6 Conducted Emission ..... 15
5.7 Occupied Bandwidth ..... 17
**6. Test equipment used for test ..... 20**

This test report shall not be reproduced, except in full, without the written approval

# 1. Client information

| | |
|---|---|
| **Applicant:** | Suprema Inc. |
| **Address:** | 16F Parkview Office Tower, Jeongja-dong, Bundang-gu, Seongnam-si, Gyeonggi-do,South Korea, 463-863 |
| **Telephone number:** | +82 31 710 5669 |
| **Facsimile number:** | +82 31 783 4516 |
| **Contact person:** | Moungcheol Lee / mclee@suprema.co.kr |

| | |
|---|---|
| **Manufacturer:** | Suprema Inc. |
| **Address:** | 16F Parkview Office Tower, Jeongja-dong, Bundang-gu, Seongnam-si, Gyeonggi-do,South Korea, 463-863 |

KCTL

# 2. Laboratory information

**Address**

**KCTL Inc.**

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea

Telephone Number: 82 31 285 0894

Facsimile Number: 82 505 299 8311

FCC Site Designation No: KR0040, FCC Site Registration No: 687132

VCCI Registration No. : R-3327, G-198, C-3706, T-1849

Industry Canada Registration No. : 8035A

KOLAS NO.: KT231

SITE MAP



# 3. Description of E.U.T.

## 3.1 Basic description

| | |
|---|---|
| Applicant | Suprema Inc. |
| Address of Applicant | 16F Parkview Office Tower, Jeongja-dong, Bundang-gu, Seongnam, Gyeonggi, 463-863, Korea |
| Manufacturer | Suprema Inc. |
| Address of Manufacturer | 16F Parkview Office Tower, Jeongja-dong, Bundang-gu, Seongnam, Gyeonggi, 463-863, Korea |
| Type of equipment | XPass D2 |
| Basic Model | XPD2-GKDBS |
| Variant Model[1)] | XPD2-GDBS, XPD2-GKDB, XPD2-GDB |
| Serial number | N/A |

[1)]: Addition or absence of SAM PCB and IC related keypad and related circuit materials

## 3.2 General description

| | |
|---|---|
| Frequency Range | 2 402 ㎒ ~ 2 480 ㎒ (Bluetooth Low Energy),<br>13.56 ㎒ (NFC), 125 ㎑ (EM/HID Proxy) |
| Type of Modulation | GFSK ㎒ (Bluetooth Low Energy),<br>ASK (NFC), ASK (EM/HID Proxy) |
| The number of channels | 40 ch (Bluetooth Low Energy),<br>1 ch (NFC), 1 ch (EM/HID Proxy) |
| Type of Antenna | Chip Antenna (Bluetooth Low Energy),<br>Loop Antenna (NFC), Loop Coil Antenna (EM/HID Proxy) |
| Power supply | DC 12 V |
| Product SW/HW version | 1.0.0 / V01 |
| Radio SW/HW version | 1.0.0 / V01 |
| Test SW Version | Tera Term Version 4.87 |
| RF power setting in TEST SW | default |

Note : The above EUT information was declared by the manufacturer.

## 3.3 Test frequency

| | |
|---|---|
| Frequency | 13.56 ㎒ |

# 4. Summary of test results

## 4.1 Standards & results

| Rule Reference | Parameter | Status |
|---|---|---|
| 15.203 | Antenna Requirement | C |
| 15.225 (a) | In-band Fundamental Emission | C |
| 15.225 (b) | In-band Spurious Emission | C |
| 15.225 (c) | In-band Spurious Emission | C |
| 15.225 (d)<br>15.209 | Out-of–band Spurious Emission | C |
| 15.225 (e) | Frequency Stability Tolerance | C |
| 15.207 | Conducted Emissions | C |
| Note1) : C = Complies, NC = Not Complies, NT = Not Tested, NA = Not Applicable | | |

## 4.2 Uncertainty

| Measurement Item | Expanded Uncertainty U = *k*Uc (*k* = 2) | |
|---|---|---|
| Radiated Spurious Emissions | 30 ㎒ ~ 300 ㎒: | +4.94 ㏈, -5.06 ㏈ |
| | | +4.93 ㏈, -5.05 ㏈ |
| | 300 ㎒ ~ 1 000 ㎒: | +4.97 ㏈, -5.08 ㏈ |
| | | +4.84 ㏈, -4.96 ㏈ |
| Conducted Emissions | 9 ㎑ ~ 150 ㎑: | 3.75 ㏈ |
| | 150 ㎑ ~ 30 ㎒: | 3.36 ㏈ |

This test report shall not be reproduced, except in full, without the written approval

# 5. Test results

## 5.1 Antenna Requirement

### 5.1.1 Regulation

According to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

### 5.1.2 Result

-Complied

The Loop antenna is permanantely attached on board.

## 5.2 In-band Fundamental Emission

### 5.2.1 Regulation

15.225 (a) The field strength of any emission within the band 13.553-13.567 ㎒ shall not exceed 15, 848 microvolts/meter at 30 meters.

### 5.2.2 Measurement Procedure

Test Procedure The Radiated Electric Field Strength intensity has been measured on semi anechoic chamber with a ground plane and at a distance of 3m.

Frequency : From 9 ㎑ to 30 ㎒ at distance 3m The EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity.

Frequency : From 30 ㎒ to 1 ㎓ at distance 3m The measuring antenna height varied between 1 and 4m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity.
The measurements were performed for both vertical and horizontal antenna polarization.

Measurements were performed with a QP, PK, and AV detector. The radiated emission measurements were made with the following detector function of the test receiver (below 1 ㎓).

| Frequency | 9 - 90 ㎑ | 90 - 110 ㎑ | 110 - 490 ㎑ | 490 ㎑ - 30 ㎒ | 30 ㎒ -1 ㎓ |
|---|---|---|---|---|---|
| Detecter type | PK/AV | QP | PK/AV | QP | QP |
| IF bandwidth | 200 ㎐ | 200 ㎐ | 9 ㎑ | 9 ㎑ | 120 ㎑ |

- Part 15 Section 15.31 (f)(2) (9 ㎑ - 30 ㎒)
[Limit at 3m]=[Limit at 300m]-40 x log(3[m]/300[m])
[Limit at 3m]=[Limit at 30m]-40 x log (3[m]/30[m])

Note : Axis among X, Y and Z plans (Please refer to the “Test setup photos” to check X, Y, Z configuration).

### 5.2.3 Test Result

- Complied

| Voltage [v] | Frequency [㎒] | Reading [dBμV] | Cable Loss [dB] | Amp Gain [dB] | Antenna Factor [dB] | Factor [dB] | Result [dBμV/m at 3 m] | Limit [dBμV/m at 3 m] | Margin [dB] |
|---|---|---|---|---|---|---|---|---|---|
| **QP DATA.** | | | | | | | | | |
| 12.0 | 13.56 | 87.30 | 1.43 | -32.67 | 18.64 | -12.60 | 74.70 | 124.00 | 49.30 |

**[Result = Reading + Amp Gain + AF + CL]**
1. H = Horizontal, V = Vertical Polarization
2. AF/CL = Antenna Factor and Cable Loss
3. Factor = CL+AF+AG

This test report shall not be reproduced, except in full, without the written approval

## 5.3 In-band Spurious Emission

## 5.3.1 Regulation

15.225 (b) With in the bands 13.410-13.553 ㎒ and 13.567-13.710 ㎒, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.

15.225 (c) With in the bands 13.110-13.410 ㎒ and 13.710-14.010 ㎒, the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.

## 5.3.2 Test Result

## - Complied

Measurement Distance: 3 m

| Frequency [㎒] | Receiver Bandwidth [㎑] | Reading [dB(㎶)] | Pol. [V/H] | Cable Loss [dB] | Amp Gain [dB] | Antenna Factor [dB] | Factor [dB] | Result [dB(㎶/m)] | Limit [dB(㎶/m)] | Margin [dB] |
|---|---|---|---|---|---|---|---|---|---|---|
| **PEAK DATA.** | | | | | | | | | | |
| 13.24 | 9 | 39.90 | V | 1.43 | -32.67 | 18.64 | -12.60 | 27.30 | 80.50 | 53.20 |
| 13.55 | 9 | 75.20 | H | 1.43 | -32.67 | 18.64 | -12.60 | 62.60 | 90.50 | 27.90 |
| 13.57 | 9 | 81.10 | H | 1.43 | -32.67 | 18.64 | -12.60 | 68.50 | 90.50 | 22.00 |
| 13.84 | 9 | 38.60 | H | 1.43 | -32.67 | 18.64 | -12.60 | 26.00 | 90.50 | 64.50 |

Note : This test was performed by using peak

**[Result = Reading + Amp Gain + AF + CL]**
1. H = Horizontal, V = Vertical Polarization
2. AF/CL = Antenna Factor and Cable Loss
3. Factor = CL+AF+AG

## 5.4 Out-of-band Spurious Emission

### 5.4.1 Regulation

15.225 (d) The Field Strength of any emissions appearing outside of the 13.110-14.010 ㎒ band shall not exceed the general radiated emission limits in 15.209

| Frequency (㎒) | Field Strength (㎶/m) | Measurement distance (meters) |
|---|---|---|
| 0.009-0.490 | 2400/F(㎑) | 300 |
| 0.490-1.705 | 24000/F(㎑) | 30 |
| 1.705-30.0 | 30(29.54 ㏈㎶/m) | 30 |
| 30.0-88.0 | 100(40 ㏈㎶/m) | 3 |
| 88-216 | 150(43.5 ㏈㎶/m) | 3 |
| 216-960 | 200 (46 ㏈㎶/m) | 3 |
| Above 960 | 500 (53.98 ㏈㎶/m) | 3 |

### 5.4.2 Measurement Procedure

The spurious emissions from the EUT will be measured on an 10 m Anechoic chamber in the frequency range of 9 ㎑ to 30 ㎒ using a tuned receiver and a shielded loop antenna.
The antenna was positioned 3, 10 or 30 meters horizontally from the EUT.
Measurements haver been made in all three orthogonal axes and the shielded loop antenna was rotated to locate the maximum of the emissions.
In the case where larger measuring distances are required the results will extrapolated based on the values measuring on the closer distances according to Section 15.31 (f) (2) [2].

The final measurement will be performed with an EMI Riceiver set to Quasi Peak detector except for the frequency bands 9 ㎑ to 90 ㎑ and 110 to 490 ㎑ where an average detector will be used according to Section 15.209 (d) [2].

The final lever, expressed in ㏈㎶/m, is arrived at by taking the reading from the EMI receiver (Level ㏈㎶) and adding the antenna correction factor and cable loss fator (Factor ㏈) to it. This result then has to be compared with the relevant FCC limit. The resolution bandwith during the measurement is as follows:
9 ㎑ – 150 ㎑: ResBW: 200 ㎐
150 ㎑ – 30 ㎒: ResBW: 9 ㎑

The preliminary radiated measurements were performed to determine the frequency producing the maximum emissions in an anechoic chamber at a distance of 3 meters.
The EUT was placed on the top of the 0.8 meter height, 1 x 1.5 meter non-metallic table. To find the maximum emission levels, the height of a measuring antenna was changed and the turntable was rotated 360°.
The antenna polarization was also changed from vertical to horizontal. The spectrum was canned from 30 to 1 000 ㎒ using the BILOG antenna. To obain the final measurement data, the EUT was arranged on a turntable situated on a 10 m chamber. The EUT was tested at a distance 3 meters.
Each frequency found during preliminary measurements was re-examined and investigated. The test-receiver system was set up to average, peak, and quasi-peak detector function with specified bandwidth.

## 5.4.3 Test Result

## - Complied

Measurement Distance: 3 m

-Below 30 ㎒

| Frequency [㎒] | Receiver Bandwidth [㎑] | Reading [dB(㎶)] | Pol. [V/H] | Cable Loss [dB] | Amp Gain [dB] | Antenna Factor [dB] | Factor [dB] | Result [dB(㎶/m)] | Limit [dB(㎶/m)] | Margin [dB] |
|---|---|---|---|---|---|---|---|---|---|---|
| **PEAK DATA.** | | | | | | | | | | |
| 0.21 | 9 | 42.80 | V | 0.51 | -32.74 | 19.83 | -12.40 | 30.60 | 69.50 | 38.90 |
| 15.55 | 9 | 43.30 | V | 1.38 | -32.67 | 18.59 | -12.70 | 30.60 | 69.50 | 38.90 |

-Above 30 ㎒

| Frequency [㎒] | Receiver Bandwidth [㎑] | Reading [dB(㎶)] | Pol. [V/H] | Cable Loss [dB] | Amp Gain [dB] | Antenna Factor [dB] | Factor [dB] | Result [dB(㎶/m)] | Limit [dB(㎶/m)] | Margin [dB] |
|---|---|---|---|---|---|---|---|---|---|---|
| **QUASI PEAK DATA.** | | | | | | | | | | |
| 40.55 | 120 | 38.40 | V | 1.29 | -29.63 | 13.04 | -15.30 | 23.10 | 40.00 | 16.90 |
| 65.04 | 120 | 38.10 | V | 1.68 | -29.42 | 12.44 | -15.30 | 22.80 | 40.00 | 17.20 |
| 140.10 | 120 | 37.70 | V | 2.57 | -29.37 | 12.70 | -14.10 | 23.60 | 43.50 | 19.90 |
| 215.03 | 120 | 43.80 | V | 3.24 | -29.61 | 10.47 | -15.90 | 27.90 | 43.50 | 15.60 |
| 224.97 | 120 | 42.10 | V | 3.31 | -29.66 | 10.85 | -15.50 | 26.60 | 46.00 | 19.40 |
| 515.24 | 120 | 38.70 | V | 5.22 | -28.74 | 18.22 | -5.30 | 33.40 | 46.00 | 12.60 |

Note : This test was performed by using peak detedctor mode. If peak result meets the limit, QP measurement is skipped.

**[Result = Reading + Amp Gain + AF + CL]**
1. H = Horizontal, V = Vertical Polarization
2. AF/CL = Antenna Factor and Cable Loss
3. Factor = CL+AF+AG

## 5.5 Frequency tolerance

### 5.5.1 Regulation

15.225 (e) The frequency tolerance of the carrier signal shall be maintained within ±0.01 % of the operating frequency over a temperature variation of −20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85 % to 115 % of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

### 5.5.2 Test Result

- Complied

| VOLTAGE [%] | POWER [V] | TEMP [℃] | FREQ [㎐] | FREQ.DEV [㎐] | Deviation [%] |
|---|---|---|---|---|---|
| 100 | 12.0 | -20 | 13 559 874 | -126.00 | -0.000 93 |
| | | -10 | 13 559 860 | -140.00 | -0.001 03 |
| | | 0 | 13 559 832 | -168.00 | -0.001 24 |
| | | 10 | 13 559 908 | -92.00 | -0.000 68 |
| | | 20 | 13 559 863 | -137.00 | -0.001 01 |
| | | 25 | 13 559 839 | -161.00 | -0.001 19 |
| | | 30 | 13 559 849 | -151.00 | -0.001 11 |
| | | 40 | 13 559 827 | -173.00 | -0.001 28 |
| | | 50 | 13 559 847 | -153.00 | -0.001 13 |
| 85 | 10.2 | 20 | 13 559 829 | -171.00 | -0.001 26 |
| 115 | 13.8 | 20 | 13 559 831 | -169.00 | -0.001 25 |

# 5.6 Conducted Emission

## 5.6.1 Regulation

According to §15.207(a), for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 ㎑ to 30 ㎒, shall not exceed the limits in the following table, as measured using a 50 µH/50 Ω line impedance stabilization network (LISN).
Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

| Frequency of emission (㎒) | Conducted limit (㏈㎶) | |
|---|---|---|
| | Qausi-peak | Average |
| 0.15 – 0.5 | 66 to 56 * | 56 to 46 * |
| 0.5 – 5 | 56 | 46 |
| 5 – 30 | 60 | 50 |

* Decreases with the logarithm of the frequency.

According to §15.107(a), for unintentional device, except for Class A digital devices, line conducted emission limits are the same as the above table.

## 5.6.2 Measurement Procedure

1) The EUT was placed on a wooden table of size, 1 m by 1.5 m, raised 80 ㎝ in which is located 40 ㎝ away from the vertical wall and 1.5m away from the side wall of the shielded room.

2) Each current-carrying conductor of the EUT power cord was individually connected through a 50Ω/50µH LISN, which is an input transducer to a Spectrum Analyzer or an EMI/Field Intensity Meter, to the input power source.

3) Exploratory measurements were made to identify the frequency of the emission that had the highest amplitude relative to the limit by operating the EUT in a range of typical modes of operation, cable position, and with a typical system equipment configuration and arrangement. Based on the exploratory tests of the EUT, the one EUT cable configuration and arrangement and mode of operation that had produced the emission with the highest amplitude relative to the limit was selected for the final measurement.

4) The final test on all current-carrying conductors of all of the power cords to the equipment that comprises the EUT (but not the cords associated with other non-EUT equipment is the system) was then performed over the frequency range of 0.15 ㎒ to 30 ㎒.

5) The measurements were made with the detector set to PEAK amplitude within a bandwidth of 10 ㎑ or to QUASI-PEAK and AVERAGE within a bandwidth of 9 ㎑. The EUT was in transmitting mode during the measurements.

## 5.6.3 Test Result

## - Complied

Figure 4. The plot of Conducted Emission




Final Result

--- N Phase ---

| No. | Frequency [MHz] | Reading QP [dB(uV)] | Reading CAV [dB(uV)] | c.f [dB] | Result QP [dB(uV)] | Result CAV [dB(uV)] | Limit QP [dB(uV)] | Limit AV [dB(uV)] | Margin QP [dB] | Margin CAV [dB] |
|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 0.15122 | 7.8 | -2.3 | 9.7 | 17.5 | 7.4 | 65.9 | 55.9 | 48.4 | 48.5 |
| 2 | 0.40959 | -1.5 | -4.3 | 9.8 | 8.3 | 5.5 | 57.7 | 47.7 | 49.4 | 42.2 |
| 3 | 0.51093 | -1.6 | -4.5 | 9.9 | 8.3 | 5.4 | 56.0 | 46.0 | 47.7 | 40.6 |
| 4 | 3.58532 | -0.8 | -5.3 | 9.7 | 8.9 | 4.4 | 56.0 | 46.0 | 47.1 | 41.6 |
| 5 | 12.00064 | 15.2 | 14.8 | 10.0 | 25.2 | 24.8 | 60.0 | 50.0 | 34.8 | 25.2 |
| 6 | 24.02894 | 5.9 | 0.5 | 10.2 | 16.1 | 10.7 | 60.0 | 50.0 | 43.9 | 39.3 |

--- L1 Phase ---

| No. | Frequency [MHz] | Reading QP [dB(uV)] | Reading CAV [dB(uV)] | c.f [dB] | Result QP [dB(uV)] | Result CAV [dB(uV)] | Limit QP [dB(uV)] | Limit AV [dB(uV)] | Margin QP [dB] | Margin CAV [dB] |
|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 0.16882 | 2.9 | -2.6 | 10.0 | 12.9 | 7.4 | 65.0 | 55.0 | 52.1 | 47.6 |
| 2 | 0.56403 | -1.6 | -4.5 | 9.9 | 8.3 | 5.4 | 56.0 | 46.0 | 47.7 | 40.6 |
| 3 | 1.35177 | -1.7 | -4.5 | 9.7 | 8.0 | 5.2 | 56.0 | 46.0 | 48.0 | 40.8 |
| 4 | 5.17454 | -0.7 | -5.3 | 9.8 | 9.1 | 4.5 | 60.0 | 50.0 | 50.9 | 45.5 |
| 5 | 8.8313 | -0.7 | -5.3 | 9.9 | 9.2 | 4.6 | 60.0 | 50.0 | 50.8 | 45.4 |
| 6 | 22.51999 | 16.6 | 11.0 | 10.1 | 26.7 | 21.1 | 60.0 | 50.0 | 33.3 | 28.9 |

# 5.7 Occupied Bandwidth

## 5.7.1 Regulation

The emission bandwidth (x dB) is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated x dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth in the range of 1% to 5% of the anticipated emission bandwidth, and a video bandwidth at least 3x the resolution bandwidth.
When the occupied bandwidth limit is not stated in the applicable RSS or reference measurement method, the transmitted signal bandwidth shall be reported as the 99% emission bandwidth, as calculated or measured.

## 5.7.2 Measurement procedure

- The transmitter shall be operated at its maximum carrier power measured under normal test conditions.
- The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts.
- The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the occupied bandwidth (OBW) and video bandwidth (VBW) shall be approximately 3x RBW.

A peak, or peak hold, may be used in place of the sampling detector as this may produce a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold may be necessary to determine the occupied bandwidth if the device is not transmitting continuously.

The trace data points are recovered and are directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded.

The difference between the two recorded frequencies is the 99% occupied bandwidth.

5.7.3 Test Result

- Complied

| Voltage [V] | Frequency [㎒] | Occupied Bandwidth (99 % BW) [㎑] |
|---|---|---|
| DC 12 | 13.56 | 0.22 |

NOTE: We took the insertion loss of the cable loss into consideration within the measuring instrument.

This test report shall not be reproduced, except in full, without the written approval

### 5.7.4 Test Plot

Figure 2. Plot of the Occupied Bandwidth (Conducted)

**- Occupied Bandwidth**



## 6. Test equipment used for test

| | Equipment Name | Manufacturer | Model No. | Serial No. | Next Cal. Date |
|---|---|---|---|---|---|
| ■ | SPECTRUM ANALYZER | R&S | FSV40 | 100988 | 19.01.05 |
| ■ | DC Power Supply | AGILENT | E3632A | KR75304571 | 19.05.14 |
| ■ | Temp & Humid Chamber | Myeongseong R&P | CTHC-50P-DT | 20150824-1 | 18.08.01 |
| ■ | Signal Generator | R & S | SMR40 | 100007 | 19.05.15 |
| ■ | Vector Signal Generator | R&S | SMBV100A | 257566 | 19.01.05 |
| ■ | Loop Antenna | R&S | HFH2-Z2 | 892665/035 | 19.01.25 |
| ■ | Bilog Antenna | SCHWARZBECK | VULB9163 | 440 | 19.10.23 |
| ■ | Attenuator | HP | 8491A | MY52461848 | 19.10.23 |
| ■ | Amplifier | SONOMA | 310N | 284608 | 18.08.24 |
| ■ | EMI Test Receiver | R&S | ESCI7 | 100732 | 18.08.24 |
| ■ | EMI Test Receiver | R&S | ESCI7 | 100710 | 18.08.24 |
| ■ | Turn Table | Innco Systems | DT2000 | 79 | - |
| ■ | Antenna Mast | Innco Systems | MA4640-XP-ET | - | - |
| ■ | Turn Table | Innco Systems | DT2000 | 79 | - |
| ■ | TWO-LINE V-NETWORK | R&S | ENV216 | 101352 | 19.03.24 |
| ■ | Cable Assembly | Radiall | 2301762000PJ | 1724.66 | - |
| ■ | Cable Assembly | Gigalane | RF-400 | - | - |

This test report shall not be reproduced, except in full, without the written approval