

Operational Description

This device is a IEEE 802.11 b/g/n WLAN Microcontroller Module. The transmitter of the EUT is powered from 3.3Vdc from host equipment.

The antennas provided to the EUT, please refer to the following table:

Antenna No	Brand	Model	Gain (dBi) (Including cable loss)	Antenna Type	Connector Type	Frequency range (GHz to GHz)	Cable Length (mm)
1(Internal)	AzureWave	AW-CU300 ANT	5.12	PCB	NA	2.4~2.4835	NA
2(External)	TAOGLAS	FXP73.07.0100A	3	Monopole	I-PEX	2.4~2.4835	100
3(External)	TAOGLAS	PC11.07.0100A	3	Dipole	I-PEX	2.4~2.4835	100
4(External)	TAOGLAS	FXP74.07.0100A	4	PIFA	I-PEX	2.4~2.4835	100
5(External)	TAOGLAS	GW.17.07.0250E	2.7	Dipole	I-PEX	2.4~2.4835	250
6(External)	TAOGLAS	PC17.07.0070A	0.9	PIFA	I-PEX	2.4~2.4835	70
7(External)	LAIRD	NanoBlue-IP04_MAF94045	2	Monopole	I-PEX	2.4~2.4835	100
8(External)	MAG.LAYERS	EDA_1313_2G4C1-A16	2.39	Dipole	I-PEX	2.4~2.4835	150

The other instruction, please have a look at the users manual.