

EMC TEST REPORT

Report No.: 180400038TWN-001

Model No.: HURESAC-3XE-C

Issued Date: Apr. 11, 2018


Applicant: Johnson Health Tech. Co., Ltd.
No. 999, Sec. 2, Dongda Rd., Daya Dist., Taichung City 428,
Taiwan

Test Method/ Standard: 47 CFR FCC Part 15.247 & ANSI C63.10 2013
DA 00-705

Registration No.: 960839

Test By: Intertek Testing Services Taiwan Ltd.
Hsinchu Laboratory
No. 11, Lane 275, Ko-Nan 1 Street, Chia-Tung Li,
Shiang-Shan District, Hsinchu City, Taiwan

It may be duplicated completely for legal use with the allowance of the applicant. It shall not be reproduced except in full, without the written approval of Intertek Laboratory. The test result(s) in this report only applies to the tested sample(s).



The test report was prepared by:

Candy Liu

Candy Liu / Assistant

These measurements were taken by:

Wayne Chen

Wayne Chen/ Engineer

The test report was reviewed by:

Rico Deng

Name Rico Deng
Title Supervisor

Revision History

Report No.	Issue Date	Revision Summary
180400038TWN-001	Apr. 11, 2018	Add NFC module only. After engineer judgment, the difference does not affect original the RF characteristic, PCB layout and antenna location. Then the all test data and test items in this report based on report of 160300217TWN-001.

Table of Contents

Summary of Tests	5
1. General Information	6
1.1 Identification of the EUT	6
1.2 Description of EUT	7
1.3 Antenna description	7
1.4 Peripherals equipment	7
2. Test Specifications	8
2.1 Test Standard	8
2.2 Operation Mode	8
2.3 Applied test modes and channels	9
3. 20dB Bandwidth Test	10
3.1 Operating Environment	10
3.2 Test Setup & Procedure	10
3.3 Measured Data of Modulated Bandwidth Test Results	10
4. Carrier Frequency Separation Test	16
4.1 Operating Environment	16
4.2 Test Setup & Procedure	16
4.3 Measured Data of Carrier Frequency Separation Test Results	16
5. Number of Hopping Frequencies Test	22
5.1 Operating Environment	22
5.2 Test Setup & Procedure	22
5.3 Measured Data of Number of Hopping Frequencies Test Results	22
6. Time of Occupancy (Dwell Time)	25
6.1 Operating Environment	25
6.2 Test Setup & Procedure	25
6.3 Measured Data of Maximum Output Power Test Results	25
7. Maximum Output Power Test	35
7.1 Operating Environment	35
7.2 Test Setup & Procedure	35
7.3 Measured Data of Maximum Output Power Test Results	35
8. RF Antenna Conducted Spurious Test	36
8.1 Operating Environment	36
8.2 Test Setup & Procedure	36
8.3 Measured Data of the Highest RF Antenna Conducted Spurious Test Results	37
9. Radiated Emission Test	46
9.1 Operating Environment	46
9.2 Test Setup & Procedure	46

9.3 Emission Limits	48
9.4 Radiated Spurious Emission Test Data.....	49
9.4.1 Measurement results: frequency range from 9kHz to 30MHz.....	49
9.4.2 Measurement Results: Frequencies Equal to or Less than 1 GHz	49
9.4.3 Measurement Results: Frequency above 1GHz	50
10. Emission on the Band Edge §FCC 15.247(d).....	53
10.1 Operating Environment	53
10.2 Test Setup & Procedure	53
10.3 Test Results	53
11. Power Line Conducted Emission Test §FCC 15.207	59
11.1 Operating Environment	59
11.2 Test Setup & Procedure	59
11.3 Emission Limit.....	59
11.4 Power Line Conducted Emission Test Data.....	60
Appendix A: Test equipment list.....	62
Appendix B: Measurement Uncertainty.....	64

Summary of Tests

Test Item	Reference	Results
20dB Bandwidth Test	15.247(a)(1)	Pass
Carrier Frequency Separation Test	15.247(a)(1)	Pass
Number of Hopping Frequencies Test	15.247(a)(1)	Pass
Time of Occupancy (Dwell Time) Test	15.247(a)(1)(iii)	Pass
Maximum Output Power Test	15.247(b)	Pass
RF Antenna Conducted Spurious Test	15.247(d)	Pass
Radiated Spurious Emission Test	15.205, 15.209	Pass
Emission on the Band Edge Test	15.247(d)	Pass
AC Power Line Conducted Emission Test	15.207	Pass
Antenna Requirement	15.203	Pass

1. General Information

1.1 Identification of the EUT

Product:	Console for Exercise Machine
Model No.:	HURESAC-3XE-C
Radio Module:	WLT2564M
Brand Name:	Matrix Fitness
Frequency Range:	2402MHz~2480MHz
Total Hopping Channel No:	79 channels
Frequency of Each Channel:	2402+1k MHz, k=0~78
Type of Modulation:	GFSK, $\pi/4$ DQSP, 8DPSK
Rated Power:	DC 12 from adapter
Power Cord:	N/A
Data Cable:	N/A
Sample Received:	Mar. 09, 2016
Sample condition:	Workable
Test Date(s):	Apr. 12, 2016 ~ Jun. 13, 2016

Note 1: The test report only allows to be revised within three years from its original issued date unless further standard or the requirement was noticed.

Note 2: When determining the test conclusion, the Measurement Uncertainty of test has been considered.

Note 3: Except where explicitly agreed in writing, all work and services performed by Intertek is subject to our standard Terms and Conditions which can be obtained at our website: <http://www.intertek-twn.com/terms/>. Intertek's responsibility and liability are limited to the terms and conditions of the agreement.

This report is made solely on the basis of your instructions and / or information and materials supplied by you and provide no warranty on the tested sample(s) be truly representative of the sample source. The report is not intended to be a recommendation for any particular course of action, you are responsible for acting as you see fit on the basis of the report results. Intertek is under no obligation to refer to or report upon any facts or circumstances which are outside the specific instructions received and accepts no responsibility to any parties whatsoever, following the issue of the report, for any matters arising outside the agreed scope of the works. This report does not discharge or release you from your legal obligations and duties to any other person. You are the only one authorized to permit copying or distribution of this report (and then only in its entirety). Any such third parties to whom this report may be circulated rely on the content of the report solely at their own risk.

1.2 Description of EUT

Modulation mode	Transmit path
	Chain 0 / Main
GFSK	V
$\pi/4$ DQPSK	V
8DPSK	V

Product SW version : UI 0.1.7.2, OS 2.0.19, IO 10
Product HW version : v1.1
Radio SW version : WLT2564M AVRCP 1.6
Radio HW version : 4.00&4_0_1_7
Test SW Version : V2.0

1.3 Antenna description

The EUT uses a permanently connected antenna.

Antenna Gain : 2.5 dBi
Antenna Type : Chip Antenna
Connector Type : Fixed

1.4 Peripherals equipment

Peripherals	Brand	Model No.	Serial No.	Data cable
Notebook PC	HP	HP Compaq nc2400	CNF6413CGN	RS232 0.5 meter × 1
Adapter	N/A	LSE0107A1240	N/A	N/A

2. Test Specifications

2.1 Test Standard

The EUT was performed according to the procedures in FCC Part 15 Subpart C Section §15.205, §15.207, §15.209, §15.247, DA 00-705 and ANSI C63.10:2013.

The test of radiated measurements according to FCC Part15 Section 15.33(a) had been conducted and the field strength of this frequency band was all meet limit requirement, thus we evaluate the EUT pass the specified test.

2.2 Operation Mode

The EUT was supplied with DC 12V from adapter

TX mode based on “HCITester” to execute, and select different frequency and modulation.

2.3 Applied test modes and channels

Test items	Mode	Channel	Antenna
20 dB Bandwidth	GFSK	Low , Middle , High	Chain0
	$\pi/4$ DQPSK	Low , Middle , High	Chain0
	8DPSK	Low , Middle , High	Chain0
Maximum peak conducted output power	GFSK	Low , Middle , High	Chain0
	$\pi/4$ DQPSK	Low , Middle , High	Chain0
	8DPSK	Low , Middle , High	Chain0
Carrier Frequency Separation	GFSK	Low , Middle , High	Chain0
	$\pi/4$ DQPSK	Low , Middle , High	Chain0
	8DPSK	Low , Middle , High	Chain0
Number of Hopping Frequencies	GFSK	Normal Operation	Chain0
	$\pi/4$ DQPSK	Normal Operation	Chain0
	8DPSK	Normal Operation	Chain0
Dwell Time	GFSK	Low , Middle , High	Chain0
	$\pi/4$ DQPSK	Low , Middle , High	Chain0
	8DPSK	Low , Middle , High	Chain0
Conducted Spurious	GFSK	Low , Middle , High	Chain0
	$\pi/4$ DQPSK	Low , Middle , High	Chain0
	8DPSK	Low , Middle , High	Chain0
Radiated spurious Emission 30MHz~1GHz	GFSK	Low , Middle , High	Chain0
	$\pi/4$ DQPSK	Low , Middle , High	Chain0
	8DPSK	Low , Middle , High	Chain0
Radiated Spurious Emission 1GHz~10th Harmonic	GFSK	Low , Middle , High	Chain0
	$\pi/4$ DQPSK	Low , Middle , High	Chain0
	8DPSK	Low , Middle , High	Chain0
Emission on the Band Edge	GFSK	Low , Middle , High	Chain0
	$\pi/4$ DQPSK	Low , Middle , High	Chain0
	8DPSK	Low , Middle , High	Chain0
AC Power Line Conducted Emission	GFSK	Low , Middle , High	Chain0
	$\pi/4$ DQPSK	Low , Middle , High	Chain0
	8DPSK	Low , Middle , High	Chain0

3. 20dB Bandwidth Test

3.1 Operating Environment

Temperature:	21	°C
Relative Humidity:	55	%
Atmospheric Pressure:	1008	hPa
Test Date:	Apr. 13, 2016	

3.2 Test Setup & Procedure

The test procedure was according to FCC measurement guidelines DA 00-705.

The 20dB bandwidth per FCC §15.247(a)(1) was measured using a 50 ohm spectrum analyzer with the resolutions bandwidth set $\geq 1\%$ of 20dB Bandwidth, the video bandwidth $\geq$ RBW, and the SPAN may equal to approximately 2 to 3 times the 20dB bandwidth. The test was performed at 3 channels (lowest, middle and highest channel). The maximum 20dB modulation bandwidth is in the following Table.

3.3 Measured Data of Modulated Bandwidth Test Results

Mode	Channel	Frequency (MHz)	20dB Bandwidth (MHz)
GFSK	Low	2402	1.0913
	Middle	2441	1.0944
	High	2480	1.1075
$\pi/4$ DQPSK	Low	2402	1.4461
	Middle	2441	1.4498
	High	2480	1.447
8DPSK	Low	2402	1.4423
	Middle	2441	1.4513
	High	2480	1.4351

Please see the plot below.

Agilent Spectrum Analyzer - 20dB Occupied Bandwidth_160300217TWN-001 (GFSK_Chain0_Ch low_2402)

02:28:12 PM Apr 13, 2016

Ref Value 17.50 dBm

PNO: Wide IFGain: Low

Trig: Free Run #Atten: 20 dB

#Avg Type: RMS Avg/Hold: > 100/100

TRACE 1 2 3 4 5 6

TYPE M

DET P

Ref Offset 7.5 dB

Ref 17.50 dBm

ΔMkr3 1.0913 MHz

-0.066 dB

10 dB/div

Log

7.50

-2.50

-12.5

-22.5

-32.5

-42.5

-52.5

-62.5

-72.5

1

2

3Δ2

-10.03 dBm

Center 2.402000 GHz

#Res BW 100 kHz

#VBW 300 kHz

Span 2.000 MHz

Sweep 1.00 ms (5001 pts)

MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	2.402 099 6 GHz	9.975 dBm			
2	N	1	f	2.401 507 1 GHz	-9.992 dBm			
3	Δ2	1	f (Δ)	1.091 3 MHz (Δ)	-0.066 dB			
4								
5								
6								
7								
8								
9								
10								
11								
12								

MSG

STATUS

[illegible]

Agilent Spectrum Analyzer - 20dB Occupied Bandwidth_160300217TWN-01 (GFSK_Chain0_ch_high_2480)

L RF SQ Z DC SENSE:INT ALIGN OFF 02:30:49 PM Apr 13, 2016

Ref Value 17.50 dBm

PNO: Wide IFGain:Low Trig: Free Run #Atten: 20 dB #Avg Type: RMS Avg|Hold:> 100/100

TRACE 1 2 3 4 5 6 TYPE M N P DET P N N N N N

Ref Offset 7.5 dB
Ref 17.50 dBm

**ΔMkr3 1.107 5 MHz
-0.003 dB**

The plot shows a spectrum from approximately 2.45 GHz to 2.51 GHz. The y-axis is logarithmic power density from -72.5 dBm/div to 10 dB/div. A green horizontal line marks the reference level at 17.50 dBm. An orange trace shows the signal spectrum. Three measurement points are marked: point 1 at the main carrier peak (9.682 dBm), point 2 at a lower level (-10.330 dBm), and point 3 at a frequency offset of 1.1075 MHz (-0.003 dB). A green diamond marker indicates the offset measurement.

MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	2.480 054 4 GHz	9.682 dBm			
2	N	1	f	2.479 499 6 GHz	-10.330 dBm			
3	Δ2	1	f (Δ)	1.107 5 MHz (Δ)	-0.003 dB			
4								
5								
6								
7								
8								
9								
10								
11								
12								

Center 2.480000 GHz Span 2.000 MHz
#Res BW 100 kHz #VBW 300 kHz Sweep 1.00 ms (5001 pts)

MSG STATUS

Agilent Spectrum Analyzer - 20dB Occupied Bandwidth_160300217TWN-001 (Other_Chain0_Ch_low_2402)

L RF 50 Ω DC SENSE:INT ALIGN OFF 02:32:44 PM Apr 13, 2016

Ref Value 17.50 dBm

PNO: Wide IFGain:Low Trig: Free Run #Atten: 20 dB #Avg Type: RMS AvgHold:>100/100

TRACE 1 2 3 4 5 6
TYPE M W V U I P N N N N N
DET P N N N N N


Ref Offset 7.5 dB
Ref 17.50 dBm

**ΔMkr3 1.446 1 MHz
-0.096 dB**


Center 2.402000 GHz Span 2.000 MHz
#Res BW 100 kHz #VBW 300 kHz Sweep 1.00 ms (5001 pts)

MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	f		2.402 084 0 GHz	6.522 dBm			
2	N	f		2.401 328 8 GHz	-13.373 dBm			
3	Δ2	f	(Δ)	1.446 1 MHz (Δ)	-0.096 dB			

Chain0 : 20dB Occupied Bandwidth @ 2DH1 Ch Middle



Chain0 : 20dB Occupied Bandwidth @ 2DH1 Ch High



Agilent Spectrum Analyzer - 20dB Occupied Bandwidth_160300217TWN-001 (8DPSK_Chain0_Ch_low_2402)

02:33:28 PM Apr 13, 2016

Ref Value 17.50 dBm

PNO: Wide IFGain:Low

Trig: Free Run #Atten: 20 dB

#Avg Type: RMS AvgHold:> 100/100

TRACE 1 2 3 4 5 6

TYPE M N N N N N

DET P N N N N N

Ref Offset 7.5 dB

Ref 17.50 dBm

Δ Mkr3 1.442 3 MHz

-0.013 dB

10 dB/div

Log

7.50

-2.50

-12.5

-22.5

-32.5

-42.5

-52.5

-62.5

-72.5

1

2

3

2

-13.40 dBm

Center 2.402000 GHz

#Res BW 100 kHz

#VBW 300 kHz

Span 2.000 MHz

Sweep 1.00 ms (5001 pts)

MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	2.402 146 0 GHz	6.604 dBm			
2	N	1	f	2.401 328 3 GHz	-13.361 dBm			
3	Δ 2	1	f	(Δ) 1.442 3 MHz (Δ)	-0.013 dB			
4								
5								
6								
7								
8								
9								
10								
11								
12								

MSG

STATUS

[illegible]

Agilent Spectrum Analyzer - 20dB Occupied Bandwidth_160300217TWN-001 (8DPSK_Chain0_ch_high_2480)

02:34:13 PM Apr 13, 2016

Ref Value 17.50 dBm

PNO: Wide IFGain: Low Trig: Free Run #Atten: 20 dB

#Avg Type: RMS Avg/Hold: >100/100

TRACE 1 2 3 4 5 6
TYPE M N N N N N
DET P N N N N N

Ref Offset 7.5 dB
Ref 17.50 dBm

ΔMkr3 1.435 1 MHz
0.418 dB

Center 2.480000 GHz
#Res BW 100 kHz
Span 2.000 MHz
#VBW 300 kHz
Sweep 1.00 ms (5001 pts)

MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	f	f	2.480 151 2 GHz	6.641 dBm			
2	N	f	f	2.479 334 1 GHz	-13.381 dBm			
3	Δ2	f	(Δ)	1.435 1 MHz (Δ)	0.418 dB			

4. Carrier Frequency Separation Test

4.1 Operating Environment

Temperature:	21	°C
Relative Humidity:	55	%
Atmospheric Pressure:	1008	hPa
Test Date:	Apr. 13, 2016	

4.2 Test Setup & Procedure

The test procedure was according to FCC measurement guidelines DA 00-705.

The carrier frequency separation per FCC §15.247(a)(1) was measured using a 50 ohm spectrum analyzer with the resolutions bandwidth set at $\geq 1\%$ of the span, the video bandwidth $\geq$ RBW, and the SPAN was wide enough to capture the peaks of two adjacent channels. The carrier frequency separation result is in the following Table.

4.3 Measured Data of Carrier Frequency Separation Test Results

Mode	Channel	Frequency (MHz)	Adjacent channel separation (MHz)	Limit
GFSK	0	2402	0.999	0.7275
	39	2441	0.984	0.7296
	78	2480	1.002	0.7383
$\pi/4$ DQPSK	0	2402	0.99	0.9641
	39	2441	0.99	0.9665
	78	2480	1.002	0.9647
8DPSK	0	2402	0.999	0.9615
	39	2441	1.017	0.9675
	78	2480	1.017	0.9567

Please see the spectrum plots of worst value below.


Chain0 : Carrier Frequency Separation @ DH1 Ch Low




Chain0 : Carrier Frequency Separation @ DH1 Ch Middle




Chain0 : Carrier Frequency Separation @ DH1 Ch High




Chain0 : Carrier Frequency Separation @ 2DH1 Ch Low




Chain0 : Carrier Frequency Separation @ 2DH1 Ch Middle




Chain0 : Carrier Frequency Separation @ 2DH1 Ch High




Chain0 : Carrier Frequency Separation @ 3DH1 Ch Low



Chain0 : Carrier Frequency Separation @ 3DH1 Ch Middle



Chain0 : Carrier Frequency Separation @ 3DH1 Ch High



5. Number of Hopping Frequencies Test

5.1 Operating Environment

Temperature:	24	°C
Relative Humidity:	55	%
Atmospheric Pressure:	1008	hPa
Test Date:	Apr. 13, 2016	

5.2 Test Setup & Procedure


The test procedure was according to FCC measurement guidelines DA 00-705.

The number of hopping frequencies per FCC §15.247(a)(1) was measured using a 50 ohm spectrum analyzer with the resolutions bandwidth set at $\geq 1\%$ of the span, the video bandwidth $\geq$ RBW, and the SPAN was the frequency band of operation. The carrier frequency separation result is in the following Table.


5.3 Measured Data of Number of Hopping Frequencies Test Results

Frequency Range (MHz)	Hopping Channels
2402~2480	79


Chain0 : Number of Hopping Frequencies @ DH1 Ch Middle



Chain0 : Number of Hopping Frequencies @ 2DH1 Ch Middle



Chain0 : Number of Hopping Frequencies @ 3DH1 Ch Middle



6. Time of Occupancy (Dwell Time)

6.1 Operating Environment

Temperature:	21	°C
Relative Humidity:	55	%
Atmospheric Pressure:	1008	hPa
Test Date:	Apr. 13, 2016	

6.2 Test Setup & Procedure

The test procedure was according to FCC measurement guidelines DA 00-705.

The time of occupancy (dwell time) per FCC §15.247(a)(1) was measured using a 50 ohm spectrum analyzer with the resolutions bandwidth set at 1MHz, the video bandwidth $\geq$ RBW, and the zero span function of spectrum analyzer was enable. The EUT has its hopping function enable.

6.3 Measured Data of Maximum Output Power Test Results


The total sweep time is 0.4×79 Channels = 31.6 seconds

Due to the number of hops in the 31.6s sweep, we determined to reduce the sweep time to 5s, count the number of hops and multiply by 6.32. The total number of hops will be multiplied by the measured time of one pulse.


Mode	Packet type	Pulse duration (ms)	Number of Pulse	measure time (s)	Dwell time (s)	Limit (s)	Pass/Fail
GFSK	DH1	0.3903	32	3.16	0.1249	0.4	Pass
	DH3	1.648	18	3.16	0.2966	0.4	Pass
	DH5	2.896	13	3.16	0.3765	0.4	Pass
$\pi/4$ -DPSK	DH1	0.4273	32	3.16	0.1367	0.4	Pass
	DH3	1.679	18	3.16	0.3022	0.4	Pass
	DH5	2.928	13	3.16	0.3806	0.4	Pass
8-DPSK	DH1	0.4271	32	3.16	0.1367	0.4	Pass
	DH3	1.678	18	3.16	0.3020	0.4	Pass
	DH5	2.93	13	3.16	0.3809	0.4	Pass

Please see the plots below.


Chain0 : Dwell Time @ DH1 Ch low




Chain0 : Dwell Time @ DH3 Ch low





Chain0 : Dwell Time @ DH5 Ch low





Chain0 : Dwell Time @ 2DH1 Ch low




Chain0 : Dwell Time @ 2DH3 Ch low




Chain0 : Dwell Time @ 2DH5 Ch high





Chain0 : Dwell Time @ 3DH1 Ch low



Chain0 : Dwell Time @ 3DH3 Ch low



Chain0 : Dwell Time @ 3DH5 Ch low



7. Maximum Output Power Test

7.1 Operating Environment

Temperature:	21	°C
Relative Humidity:	55	%
Atmospheric Pressure:	1008	hPa
Test Date:	Apr. 13, 2016	

7.2 Test Setup & Procedure

The test procedure was according to FCC measurement guidelines DA 00-705.

The power output per FCC §15.247(b) was measured on the EUT using a 50 ohm SMA cable connected to peak power meter via power sensor. Power was read directly and cable loss correction (2 dB) was added to the reading to obtain power at the EUT antenna terminals. The test was performed at 3 channels (lowest, middle and highest channel).

7.3 Measured Data of Maximum Output Power Test Results

Mode	Channel	Frequency (MHz)	Maximum power (PK) (dBm)	Maximum power (PK) (mW)	Limit (dBm)	Margin (dB)
GFSK	Low	2402	6.35	4.32	20.96	-14.61
	Middle	2441	5.91	3.90	20.96	-15.05
	High	2480	5.76	3.77	20.96	-15.20
$\pi/4$ DQPSK	Low	2402	6.5	4.47	20.96	-14.46
	Middle	2441	6.16	4.13	20.96	-14.80
	High	2480	6.09	4.06	20.96	-14.87
8DPSK	Low	2402	6.81	4.80	20.96	-14.15
	Middle	2441	6.44	4.41	20.96	-14.52
	High	2480	6.25	4.22	20.96	-14.71

8. RF Antenna Conducted Spurious Test

8.1 Operating Environment

Temperature:	21	°C
Relative Humidity:	55	%
Atmospheric Pressure:	1008	hPa
Test Date:	Apr. 13, 2016	

8.2 Test Setup & Procedure



The test procedure was according to FCC measurement guidelines DA 00-705.

The measurements were performed from 30MHz to 25GHz RF antenna conducted per FCC 15.247 (c) was measured from the EUT antenna port using a 50ohm spectrum analyzer with the resolution bandwidth set at 100 kHz, and the video bandwidth set at 100 kHz.



Harmonics and spurious noise must be at least 20dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.

8.3 Measured Data of the Highest RF Antenna Conducted Spurious Test Results

Chain0 : Conducted Spurious @ DH1 Ch Low



Chain0 : Conducted Spurious @ DH1 Ch Middle



Agilent Spectrum Analyzer - Conducted Spurious_160300217TWN-001 (GFSK_Chain0_ch high_2480)

02:46:21 PM Apr 13, 2016

Ref Value 17.50 dBm

PNO: Wide IFGain:Low Trig: Free Run #Atten: 20 dB

#Avg Type: RMS Avg|Hold: 10/10

TRACE 1 2 3 4 5 6
TYPE M
DET P N N N N N

Ref Offset 7.5 dB
Ref 17.50 dBm

Mkr1 2.480 054 313 GHz
5.606 dBm

10 dB/div
Log


7.50
-2.50
-12.5
-22.5
-32.5
-42.5
-52.5
-62.5
-72.5

-14.38 dBm

Center 2.480000 GHz
#Res BW 100 kHz
#VBW 300 kHz

Span 706.5 kHz
Sweep 2.67 ms (40001 pts)

MSG STATUS



Agilent Spectrum Analyzer - Conducted Spurious_160300217TWN-001 (Other_Chain0_Ch low_2402)

02:48:23 PM Apr 13, 2016

Ref Value 17.50 dBm

PNO: Wide IFGain: Low Trig: Free Run #Atten: 20 dB

#Avg Type: RMS Avg|Hold: 10/10

TRACE 1 2 3 4 5 6
TYPE M
DET P N N N N N

Ref Offset 7.5 dB
Ref 17.50 dBm


Mkr1 2.402 090 44 GHz
2.305 dBm

10 dB/div
Log

Center 2.402000 GHz
#Res BW 100 kHz
#VBW 300 kHz

Span 1.625 MHz
Sweep 2.67 ms (40001 pts)

The screenshot displays a spectrum analyzer interface. The main plot area shows a noisy signal in orange, centered at 2.402 GHz. A green horizontal line is drawn at -22.5 dBm. A green diamond marker labeled '1' is placed on the signal at approximately 2.305 dBm. The y-axis is labeled '10 dB/div Log' and ranges from -72.5 to 7.5 dBm. The x-axis represents frequency. The top status bar shows various settings: 'L', 'RF', '50 Ω', 'DC', 'SENSE:INT', 'ALIGN OFF', and the date/time '02:48:23 PM Apr 13, 2016'. The top left shows 'Ref Value 17.50 dBm'. The top right shows 'PNO: Wide IFGain: Low Trig: Free Run #Atten: 20 dB', '#Avg Type: RMS Avg|Hold: 10/10', and trace settings. The bottom status bar shows 'Center 2.402000 GHz', '#Res BW 100 kHz', '#VBW 300 kHz', 'Span 1.625 MHz', and 'Sweep 2.67 ms (40001 pts)'.



Agilent Spectrum Analyzer - Conducted Spurious_160300217TWN-001 (Other_Chain0_ch middle_2441)

02:49:48 PM Apr 13, 2016

Ref Value 17.50 dBm

PNO: Wide IFGain: Low Trig: Free Run #Atten: 20 dB

#Avg Type: RMS Avg|Hold: 10/10

TRACE 1 2 3 4 5 6
TYPE M
DET P

Ref Offset 7.5 dB
Ref 17.50 dBm

Mkr1 2.441 078 72 GHz
2.611 dBm


10 dB/div
Log

7.50
-2.50
-12.5
-22.5
-32.5
-42.5
-52.5
-62.5
-72.5

Center 2.441000 GHz
#Res BW 100 kHz
#VBW 300 kHz

Span 1.632 MHz
Sweep 2.67 ms (40001 pts)

MSG STATUS




Agilent Spectrum Analyzer - Conducted Spurious_160300217TWN-001 (Other_Chain0_ch_high_2480)

L RF 50 Ω DC SENSE:INT ALIGN OFF 02:51:40 PM Apr 13, 2016
 Ref Value 17.50 dBm PNO: Wide Trig: Free Run #Avg Type: RMS
 IFGain:Low #Atten: 20 dB AvgHold: 10/10
 TRACE 1 2 3 4 5 6
 TYPE M
 DET P N N N N N

Ref Offset 7.5 dB
 Ref 17.50 dBm
 10 dB/div
 Log
 Mkr1 2.480 074 37 GHz
 2.465 dBm

Center 2.480000 GHz Span 1.600 MHz
 #Res BW 100 kHz #VBW 300 kHz Sweep 2.67 ms (40001 pts)

MSG STATUS



Agilent Spectrum Analyzer - Conducted Spurious_160300217TWN-001 (8DPSK_Chain0_Ch_low_2402)

02:56:23 PM Apr 13, 2016

Ref Value 17.50 dBm

PNO: Wide IFGain: Low Trig: Free Run #Atten: 20 dB

#Avg Type: RMS Avg|Hold: 10/10

TRACE 1 2 3 4 5 6
TYPE M
DET P N N N N N

Ref Offset 7.5 dB
Ref 17.50 dBm

Mkr1 2.402 013 08 GHz
2.154 dBm


10 dB/div
Log

Center 2.402000 GHz
#Res BW 100 kHz
#VBW 300 kHz

Span 1.624 MHz
Sweep 2.67 ms (40001 pts)

MSG STATUS

The screenshot displays a spectrum analyzer interface. The main plot area shows a noisy signal trace in orange. A green horizontal line is drawn across the plot at approximately -17.5 dBm. A green diamond marker is placed on the signal trace at a frequency of 2.402 GHz and a power level of 2.154 dBm. The y-axis is labeled '10 dB/div Log' and ranges from -72.5 to 7.5 dBm. The x-axis represents frequency, with a center frequency of 2.402 GHz and a span of 1.624 MHz. The resolution bandwidth (Res BW) is 100 kHz and the video bandwidth (VBW) is 300 kHz. The sweep time is 2.67 ms. The top of the screen shows the instrument name and date/time. The bottom of the screen shows a status bar with 'MSG' and 'STATUS' indicators.



Agilent Spectrum Analyzer - Conducted Spurious_160300217TWN-001 (8DPSK_Chain0_ch middle_2441)

02:55:07 PM Apr 13, 2016

Ref Value 17.50 dBm

PNO: Wide IFGain:Low Trig: Free Run #Atten: 20 dB

#Avg Type: RMS Avg|Hold: 10/10

TRACE 1 2 3 4 5 6
TYPE M
DET P N N N N N


Ref Offset 7.5 dB
Ref 17.50 dBm

Mkr1 2.441 024 08 GHz
2.318 dBm

10 dB/div
Log

Center 2.4410000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Span 1.616 MHz
Sweep 2.67 ms (40001 pts)

MSG STATUS



Agilent Spectrum Analyzer - Conducted Spurious_160300217TWN-001 (8DPSK_Chain0_ch_high_2480)

02:53:24 PM Apr 13, 2016

Ref Value 17.50 dBm

PNO: Wide IFGain: Low Trig: Free Run #Atten: 20 dB

#Avg Type: RMS Avg|Hold: 10/10

TRACE 1 2 3 4 5 6
TYPE M
DET P


Ref Offset 7.5 dB
Ref 17.50 dBm

Mkr1 2.480 158 52 GHz
2.347 dBm

10 dB/div
Log

Center 2.480000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Span 1.621 MHz
Sweep 2.67 ms (40001 pts)

MSG STATUS



9. Radiated Emission Test

9.1 Operating Environment


Temperature:	21	°C
Relative Humidity:	50	%
Atmospheric Pressure:	1008	hPa
Test Date:	Apr. 14, 2016	

9.2 Test Setup & Procedure


The test procedure was according to FCC measurement guidelines DA 00-705 and ANSI C63.10:2013.

The Diagram below shows the test setup, which is utilized to make these measurements.


Radiated emission from 9kHz to 30MHz uses Loop Antenna:



Radiated emission from 30MHz to 1GHz uses Bi-log Antenna:



Radiated emission above 1 GHz uses Horn Antenna:



According to §15.33(a), the spectrum shall be investigated from the lowest radio frequency signal generated in the device, to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower. Spectrum Analyzer Resolution Bandwidth is 100kHz or greater for frequencies 30MHz to 1GHz, 1MHz – for frequencies above 1GHz.

Configure the EUT according to ANSI C63.10: 2013 The EUT was placed on the top of the turntable 1.5 meter above ground for above 1GHz and placed on the top of the turntable 0.8 meter above ground for below 1GHz. The center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable, the peripherals will be connected to EUT and the whole system. During the test, all cables were arranged to produce worst-case emissions. The signal is maximized through rotation. The height of antenna and polarization is changing constantly for exploring for maximum signal level. The height of antenna can be up to 4 meters and down to 1 meter.

The measurement for radiated emission will be done at the distance of three meters unless the signal level is too low to measure at that distance. In the case of the reading under noise floor, a pre-amplifier is used and/or the test is conducted at a closer distance. And then all readings are extrapolated back to the equivalent 3 meter reading using inverse scaling with distance.

9.3 Emission Limits

The spurious Emission shall test through the 10th harmonic. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

Frequency (MHz)	Field Strength (microvolts/meter)
0.009~0.490	2400/F(kHz)
0.490~1.705	2400/F(kHz)
1.705~30	30
30-88	100
88-216	150
216-960	200
Above 960	500

Remark:

1. In the above table, the tighter limit applies at the band edges.
2. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system

9.4 Radiated Spurious Emission Test Data

9.4.1 Measurement results: frequency range from 9kHz to 30MHz

Frequency (MHz)	Detection value	Factor (dB/m)	Reading (dBμV)	Value (dBμV/m)	Limit @ 3m (dBμV/m)	Tolerance (dB)
0.02	QP	20.92	14.00	34.92	200.00	-165.09
0.03	QP	20.86	18.89	39.75	160.00	-120.25
0.05	QP	20.83	9.43	30.26	128.00	-97.74
0.07	QP	20.81	18.33	39.14	114.29	-75.15
0.13	QP	20.77	7.42	28.19	98.46	-70.27
0.27	QP	20.76	23.66	44.42	88.89	-44.47

9.4.2 Measurement Results: Frequencies Equal to or Less than 1 GHz

The test was performed on EUT under GFSK, $\pi/4$ DQPSK, 8DPSK mode. The worst case occurred at GFSK mode at Low channel

EUT : HURESAC-3XE-C
Worst Case : GFSK mode at Low channel

Antenna Polarized (V/H)	Freq. (MHz)	Receiver Detector	Corr. Factor (dB/m)	Reading (dBuV)	Corrected Level (dBuV/m)	Limit @ 3 m (dBuV/m)	Margin (dB)
Vertical	47.46	QP	16.97	25.06	35.71	40.00	-4.29
Vertical	72.68	QP	13.82	19.23	31.16	40.00	-8.84
Vertical	95.96	QP	11.05	15.67	38.93	43.50	-4.57
Vertical	142.52	QP	16.16	21.70	34.17	43.50	-9.33
Vertical	288.02	QP	17.06	16.75	39.13	46.00	-6.87
Vertical	528.58	QP	22.60	11.30	31.69	46.00	-14.31
Horizontal	47.46	QP	13.48	14.91	26.26	40.00	-13.74
Horizontal	95.96	QP	14.33	15.83	35.95	43.50	-7.55
Horizontal	142.52	QP	15.15	17.59	28.51	43.50	-14.99
Horizontal	239.52	QP	16.85	18.56	39.86	46.00	-6.14
Horizontal	288.02	QP	17.70	11.82	42.75	46.00	-3.25
Horizontal	336.52	QP	18.55	10.96	32.17	46.00	-13.83

Remark:1. Corr. Factor = Antenna Factor + Cable Loss
2. Corrected Level = Reading + Corr. Factor

9.4.3 Measurement Results: Frequency above 1GHz

EUT : HURESAC-3XE-C

Mode	Frequency (MHz)	Spectrum Analyzer Detector	Ant. Pol. (H/V)	Preamp. Gain (dB)	Correction Factor (dB/m)	Reading (dBμV)	Corrected Reading (dBμV/m)	Limit @ 3 m (dBμV/m)	Margin (dB)
GFSK Ch Low	3180	PK	V	39.87	-3.75	47.78	44.03	74.00	-29.97
	3960	PK	V	40.36	-1.72	44.76	43.04	74.00	-30.96
	4804	PK	V	40.13	-0.10	43.60	43.50	74.00	-30.50
	5040	PK	V	39.64	0.80	42.60	43.40	74.00	-30.60
	3150	PK	H	39.85	-3.73	45.17	41.44	74.00	-32.56
	3690	PK	H	40.17	-3.06	45.76	42.70	74.00	-31.30
	4804	PK	H	40.13	-0.10	42.02	41.92	74.00	-32.08
GFSK Ch Middle	3180	PK	V	39.87	-3.75	48.63	44.88	74.00	-29.12
	3990	PK	V	40.38	-1.57	44.11	42.54	74.00	-31.46
	4882	PK	V	39.99	0.16	43.58	43.74	74.00	-30.26
	3690	PK	H	40.17	-3.06	46.51	43.45	74.00	-30.55
	4740	PK	H	40.25	-0.31	43.51	43.20	74.00	-30.80
	4882	PK	H	39.99	0.16	43.38	43.54	74.00	-30.46
GFSK Ch High	3180	PK	V	39.87	-3.75	50.36	46.61	74.00	-27.39
	3360	PK	V	39.96	-3.89	45.62	41.73	74.00	-32.27
	3990	PK	V	40.38	-1.57	43.25	41.68	74.00	-32.32
	4350	PK	V	40.61	-1.23	44.40	43.17	74.00	-30.83
	4960	PK	V	39.84	0.41	45.40	45.81	74.00	-28.19
	4960	PK	H	39.84	0.41	42.91	43.32	74.00	-30.68
	7440	PK	H	37.91	8.82	33.80	42.62	74.00	-31.38

Remark:

1. Correction Factor = Antenna Factor + Cable Loss– Preamp. Gain
2. The frequency measured ranges from 1GHz to 25GHz.The data value listed above which is higher than the noise floor, the others please refer to noise floor level.

EUT : HURESAC-3XE-C

Mode	Frequency (MHz)	Spectrum Analyzer Detector	Ant. Pol. (H/V)	Preamp. Gain (dB)	Correction Factor (dB/m)	Reading (dBμV)	Corrected Reading (dBμV/m)	Limit @ 3 m (dBμV/m)	Margin (dB)
π/4DQPSK Ch Low	3180	PK	V	39.87	-3.75	47.67	43.92	74.00	-30.08
	3360	PK	V	39.96	-3.89	45.16	41.27	74.00	-32.73
	3990	PK	V	40.38	-1.57	44.62	43.05	74.00	-30.95
	4804	PK	V	40.13	-0.10	43.68	43.58	74.00	-30.42
	3150	PK	H	39.85	-3.73	46.37	42.64	74.00	-31.36
	3690	PK	H	40.17	-3.06	43.72	40.66	74.00	-33.34
	3960	PK	H	40.36	-1.72	44.01	42.29	74.00	-31.71
	4740	PK	H	40.25	-0.31	43.23	42.92	74.00	-31.08
	4804	PK	H	40.13	-0.10	42.65	42.55	74.00	-31.45
π/4DQPSK Ch Middle	3180	PK	V	39.87	-3.75	49.80	46.05	74.00	-27.95
	4882	PK	V	39.99	0.16	45.27	45.43	74.00	-28.57
	3690	PK	H	40.17	-3.06	46.91	43.85	74.00	-30.15
	4740	PK	H	40.25	-0.31	43.53	43.22	74.00	-30.78
	4882	PK	H	39.99	0.16	40.48	40.64	74.00	-33.36
	5730	PK	H	38.21	3.81	40.35	44.16	74.00	-29.84
	6810	PK	H	38.29	7.05	40.06	47.11	74.00	-26.89
π/4DQPSK Ch High	3180	PK	V	39.87	-3.75	51.27	47.52	74.00	-26.48
	3360	PK	V	39.96	-3.89	45.72	41.83	74.00	-32.17
	4740	PK	V	40.25	-0.31	44.35	44.04	74.00	-29.96
	4960	PK	V	39.84	0.41	43.18	43.59	74.00	-30.41
	3150	PK	H	39.85	-3.73	44.68	40.95	74.00	-33.05
	3690	PK	H	40.17	-3.06	45.54	42.48	74.00	-31.52
	4740	PK	H	40.25	-0.31	45.43	45.12	74.00	-28.88
	4960	PK	H	39.84	0.41	41.56	41.97	74.00	-32.03
	8190	PK	H	37.31	11.00	40.74	51.74	74.00	-22.26

Remark:

1. Correction Factor = Antenna Factor + Cable Loss– Preamp. Gain
2. The frequency measured ranges from 1GHz to 25GHz.The data value listed above which is higher than the noise floor, the others please refer to noise floor level.

EUT : HURESAC-3XE-C

Mode	Frequency (MHz)	Spectrum Analyzer Detector	Ant. Pol. (H/V)	Preamp. Gain (dB)	Correction Factor (dB/m)	Reading (dBμV)	Corrected Reading (dBμV/m)	Limit @ 3 m (dBμV/m)	Margin (dB)
8DPSK Ch Low	3180	PK	V	39.87	-3.75	51.05	47.30	74.00	-26.70
	3330	PK	V	39.95	-3.87	46.09	42.22	74.00	-31.78
	4804	PK	V	40.13	-0.10	42.81	42.71	74.00	-31.29
	3690	PK	H	40.17	-3.06	44.59	41.53	74.00	-32.47
	4740	PK	H	40.25	-0.31	43.37	43.06	74.00	-30.94
	4804	PK	H	40.13	-0.10	41.68	41.58	74.00	-32.42
8DPSK Ch Middle	3180	PK	V	39.87	-3.75	49.82	46.07	74.00	-27.93
	3330	PK	V	39.95	-3.87	47.36	43.49	74.00	-30.51
	3990	PK	V	40.38	-1.57	44.63	43.06	74.00	-30.94
	4882	PK	V	39.99	0.16	44.93	45.09	74.00	-28.91
	3150	PK	H	39.85	-3.73	45.85	42.12	74.00	-31.88
	3690	PK	H	40.17	-3.06	45.00	41.94	74.00	-32.06
	4740	PK	H	40.25	-0.31	44.04	43.73	74.00	-30.27
	4882	PK	H	39.99	0.16	42.31	42.47	74.00	-31.53
8DPSK Ch High	3150	PK	V	39.85	-3.73	46.45	42.72	74.00	-31.28
	3690	PK	V	40.17	-3.06	44.95	41.89	74.00	-32.11
	4740	PK	V	40.25	-0.31	45.09	44.78	74.00	-29.22
	4960	PK	V	39.84	0.41	41.82	42.23	74.00	-31.77
	3180	PK	H	39.87	-3.75	46.11	42.36	74.00	-31.64
	3360	PK	H	39.96	-3.89	45.88	41.99	74.00	-32.01
	4960	PK	H	39.84	0.41	44.45	44.86	74.00	-29.14

Remark:

1. Correction Factor = Antenna Factor + Cable Loss– Preamp. Gain
2. The frequency measured ranges from 1GHz to 25GHz.The data value listed above which is higher than the noise floor, the others please refer to noise floor level.

10. Emission on the Band Edge §FCC 15.247(d)

Radiated emissions were investigated the frequency over 1 GHz using a spectrum analyzer RBW of 1 MHz and 10 Hz VBW record Average reading. (15.209 paragraph), the Peak reading (1MHz / 3MHz; RBW / VBW) recorded also on the report. For the 20dB occupied bandwidth, the RBW is 100kHz, the VBW is 300kHz.

10.1 Operating Environment

Temperature:	25	°C
Relative Humidity:	50	%
Atmospheric Pressure:	1008	hPa
Test Date:	Apr. 13, 2016	


10.2 Test Setup & Procedure

Please refer to the section 9.2 of this report.


10.3 Test Results

Mode	Frequency (MHz)	Spectrum Analyzer Detector	Ant. Pol. (H/V)	Correction Factor (dB/m)	Reading (dBμV)	Corrected Reading (dBμV/m)	Limit @ 3 m (dBμV/m)	Margin (dB)	Restricted band (MHz)
GFSK	2358.84	PK	V	33.70	21.30	55.00	74	-19.00	2310~2390
	2376.71	AV	V	33.79	8.00	41.79	54	-12.21	
	2531.89	PK	V	34.42	21.50	55.92	74	-18.08	2483.5~2500
	2531.89	AV	V	34.42	9.71	44.13	54	-9.87	
π/4-DPSK	2377.56	PK	V	33.79	20.08	53.87	74	-20.13	2310~2390
	2372.38	AV	V	33.77	7.88	41.65	54	-12.35	
	2483.50	PK	V	34.30	29.60	63.90	74	-10.10	2483.5~2500
	2483.50	AV	V	34.30	11.72	46.02	54	-7.98	
8-DPSK	2352.02	PK	V	33.67	21.00	54.67	74	-19.33	2310~2390
	2352.22	AV	V	33.67	8.41	42.08	54	-11.92	
	2483.50	PK	V	34.30	31.05	65.35	74	-8.65	2483.5~2500
	2483.50	AV	V	34.30	12.28	46.58	54	-7.42	


Chain0 : 20dB Occupied Bandwidth @ DH1 Ch Low




Chain0 : 20dB Occupied Bandwidth @ DH1 Ch Middle



Chain0 : 20dB Occupied Bandwidth @ DH1 Ch High



Chain0 : 20dB Occupied Bandwidth @ 2DH1 Ch Low



Agilent Spectrum Analyzer - 20dB Occupied Bandwidth_160300217TWN-001 (Other_Chain0_ch middle_2441)

02:32:10 PM Apr 13, 2016

Ref Value 17.50 dBm

PNO: Wide IFGain: Low

Trig: Free Run #Atten: 20 dB

#Avg Type: RMS AvgHold: > 100/100

TRACE 1 2 3 4 5 6

TYPE M N N N N N

DET P N N N N N

Ref Offset 7.5 dB

Ref 17.50 dBm

Δ Mkr3 1.449 8 MHz

0.076 dB

10 dB/div

Log

7.50

-2.50

-12.5

-22.5

-32.5

-42.5

-52.5

-62.5

-72.5

1

2

3 Δ 2

-13.49 dBm

Center 2.441000 GHz

#Res BW 100 kHz

#VBW 300 kHz

Span 2.000 MHz

Sweep 1.00 ms (5001 pts)

MkF	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	2.441 093 6 GHz	6.513 dBm			
2	N	1	f	2.440 324 4 GHz	-13.479 dBm			
3	Δ 2	1	f (Δ)	1.449 8 MHz (Δ)	0.076 dB			
4								
5								
6								
7								
8								
9								
10								
11								
12								

MSG

STATUS

Agilent Spectrum Analyzer - 20dB Occupied Bandwidth_160300217TWN-001 (Other_Chain0_ch_high_2480)

02:31:43 PM Apr 13, 2016

Ref Value 17.50 dBm

PNO: Wide IFGain:Low

Trig: Free Run #Atten: 20 dB

#Avg Type: RMS Avg|Hold: > 100/100

TRACE 1 2 3 4 5 6

TYPE M M M M M M

DET P N N N N N

Ref Offset 7.5 dB

Ref 17.50 dBm

Δ Mkr3 1.447 0 MHz

-0.085 dB

10 dB/div

Log

7.50

-2.50

-12.5

-22.5

-32.5

-42.5

-52.5

-62.5

-72.5

Center 2.480000 GHz

#Res BW 100 kHz

#VBW 300 kHz

Span 2.000 MHz


Sweep 1.00 ms (5001 pts)

MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	2.480 073 6 GHz	6.340 dBm			
2	N	1	f	2.479 334 2 GHz	-13.574 dBm			
3	Δ 2	1	f (Δ)	1.447 0 MHz (Δ)	-0.085 dB			
4								
5								
6								
7								
8								
9								
10								
11								
12								


MSG

STATUS


Chain0 : 20dB Occupied Bandwidth @ 3DH1 Ch Low



Chain0 : 20dB Occupied Bandwidth @ 3DH1 Ch Middle



Chain0 : 20dB Occupied Bandwidth @ 3DH1 Ch High




11. Power Line Conducted Emission Test §FCC 15.207

11.1 Operating Environment

Temperature:	26	°C
Relative Humidity:	54	%
Atmospheric Pressure	1008	hPa
Test Date:	Apr. 29, 2016	

11.2 Test Setup & Procedure



The test procedure was according to ANSI C63.10:2013.

The EUT are connected to the main power through a line impedance stabilization network (LISN). This provides a 50 ohm/50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50 ohm/50uH coupling impedance with 50 ohm termination.

Both sides (Line and Neutral) of AC line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement.

The bandwidth of the field strength meter (R & S Test Receiver ESCS 30) is set at 9 kHz.

The EUT configuration refers to the “Conducted set-up photo.pdf”.

11.3 Emission Limit

Freq. (MHz)	Conducted Limit (dBuV)	
	Q.P.	Ave.
0.15~0.50	66 – 56*	56 – 46*
0.50~5.00	56	46
5.00~30.0	60	50

*Decreases with the logarithm of the frequency.


11.4 Power Line Conducted Emission Test Data

Phase : Line
EUT : HURESAC-3XE-C
Test Condition : TX mode

Frequency (MHz)	Corr. Factor (dB)	Level Qp (dBuV)	Limit Qp (dBuV)	Level Av (dBuV)	Limit Av (dBuV)	Margin (dB) Qp	Av
0.152	9.74	51.59	65.91	35.28	55.91	-14.32	-20.63
0.201	9.74	44.60	63.58	30.46	53.58	-18.98	-23.12
0.248	9.74	35.73	61.82	19.11	51.82	-26.09	-32.71
0.305	9.73	30.63	60.10	15.89	50.10	-29.47	-34.21
0.529	9.74	36.29	56.00	33.33	46.00	-19.71	-12.67
3.759	9.86	25.97	56.00	18.48	46.00	-30.03	-27.52

Remark:

1. Corr. Factor (dB) = LISN Factor (dB) + Cable Loss (dB)
2. Margin (dB) = Level (dBuV) – Limit (dBuV)




Phase : Neutral
EUT : HURESAC-3XE-C
Test Condition : TX mode

Frequency (MHz)	Corr. Factor (dB)	Level Qp (dBuV)	Limit Qp (dBuV)	Level Av (dBuV)	Limit Av (dBuV)	Margin (dB) Qp	Av
0.152	9.74	51.42	65.87	33.82	55.87	-14.45	-22.04
0.204	9.74	44.60	63.45	30.60	53.45	-18.84	-22.85
0.258	9.74	37.30	61.51	26.47	51.51	-24.22	-25.04
0.307	9.73	32.13	60.06	16.59	50.06	-27.93	-33.47
0.529	9.74	35.74	56.00	30.30	46.00	-20.26	-15.70
3.922	9.86	25.88	56.00	19.23	46.00	-30.12	-26.77

Remark:

1. Corr. Factor (dB) = LISN Factor (dB) + Cable Loss (dB)
2. Margin (dB) = Level (dBuV) – Limit (dBuV)



Appendix A: Test equipment list

Equipment	Brand	Model No.	Serial No.	Calibration Date	Next Calibration Date
ESCI EMI Test Receiver	Rohde & Schwarz	ESCI	100018	2015/12/02	2016/11/30
Spectrum Analyzer	Rohde & Schwarz	FSP30	100137	2015/08/18	2016/08/16
Horn Antenna (1-18G)	SHWARZBECK	BBHA 9120 D	9120D-456	2014/08/29	2017/08/27
Horn Antenna (14-42G)	SHWARZBECK	BBHA 9170	BBHA9170159	2014/09/16	2017/09/14
Broadband Antenna	SHWARZBECK	VULB 9168	9168-172	2013/08/08	2016/08/06
Pre-Amplifier	EMC Co.	EMC12635SE	980205	2015/10/7	2016/10/05
Pre-Amplifier	MITEQ	JS4-26004000--27-8A	828825	2015/09/15	2016/09/13
Power Meter	Anritsu	ML2495A	0844001	2015/11/11	2016/11/09
Power Sensor	Anritsu	MA2411B	0738452	2015/11/11	2016/11/09
Two-Line V-Network	Rohde & Schwarz	ENV216	101159	2015/06/08	2016/06/06
Artificial Mains Network (LISN)	Schaffner	MN2050D	1586	2015/05/27	2016/05/25
CON-1 Cable	SUHNER	BNC / RG-58	1521946	2015/05/09	2016/05/07
Test software	Audix	e3	4.2004-1-12k	NCR	NCR
Signal Analyzer	Agilent	N9030A	MY51380492	2014/09/19	2015/09/18
966-2(A) Cable 9kHz~26.5GHz	SUHNER	SMA / EX 100	N/A	2015/05/06	2016/05/05
966-2(B) Cable 9kHz~26.5GHz	SUHNER	SMA / SUCOFLEX 104P	CB0005	2015/05/06	2016/05/04

Equipment	Brand	Model No.	Serial No.	Calibration Date	Next Calibration Date
RF Cable 9kHz~26.5GHz	SUHNER	SUCOFLEX 102	CB0006	2015/05/06	2016/05/05
966-2_3m Semi-Anechoic Chamber	966_2	CEM-966_2	N/A	2015/02/24	2016/02/23
Active Loop Antenna	SCHWARZBECK MESS-ELEKTRONIC	FMZB1519	1519-067	2016/03/03	2017/03/02
EMI Test Receiver	Rohde & Schwarz	ESR-7	101232	2015/12/02	2016/11/30
High Pass Filter	Wainwright	WHKX3.0/ 18G-12SS	N/A	2015/06/06	2016/06/04
Test software	ADT	Radiated test system	7.5.14	NCR	NCR

Note: No Calibration Required (NCR).

Appendix B: Measurement Uncertainty

This uncertainty represents an expanded uncertainty expressed at approximately the 95 % confidence level using a coverage factor of $k=2$.

Item	Uncertainty
Vertically polarized radiated disturbances from 30MHz~1GHz in a semi-anechoic chamber at a distance of 3m	5.14 dB
Horizontally polarized radiated disturbances from 30MHz~1GHz in a semi-anechoic chamber at a distance of 3m	5.22 dB
Vertically polarized Radiated disturbances from 1GHz~18GHz in a semi-anechoic chamber at a distance of 3m	3.64 dB
Horizontally polarized Radiated disturbances from 1GHz~18GHz in a semi-anechoic chamber at a distance of 3m	3.64 dB
Vertically polarized Radiated disturbances from 18GHz~40GHz in a semi-anechoic chamber at a distance of 3m	2.7 dB
Horizontally polarized Radiated disturbances from 18GHz~40GHz in a semi-anechoic chamber at a distance of 3m	2.7 dB
Radiated disturbances from 9kHz~30MHz in a semi-anechoic chamber at a distance of 3m	3.53 dB
Emission on the Band Edge Test	3.64 dB
Minimum 6 dB Bandwidth	0.85 dB
Maximum Peak Conducted Output Power	0.42 dB
Power Spectral Density	0.85 dB
Emissions In Non-Restricted Frequency Bands	0.85 dB
AC Power Line Conducted Emission	2.47 dB