

FCC PART 15.247

EMI MEASUREMENT AND TEST REPORT

For

LAYON International Electronic & Telecom Co., Ltd

No.32, BaoHeRoad, NanZhou Street, GuangZhou, China

FCC ID: TNBUNI02

September 27, 2005

This Report Concerns: ☒ Original Report	Equipment Type: Bluetooth Headset
Test Engineer: Jandy Su 	
Report No.: RSZ05091203	
Receive EUT Date/ Test Date: September 15, 2005/September 19-23, 2005	
Reviewed By: Chris Zeng 	
Prepared By: Bay Area Compliance Lab Corp. (ShenZhen) 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone, ShenZhen, Guangdong 518038, P.R.China Tel: +86-755-33320018 Fax: +86-755-33320008	

Note: The test report is specially limited to the above company and this particular sample only. It may not be duplicated without prior written consent of Bay Area Compliance Lab Corp. (ShenZhen). This report **must not** be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST or any agency of the US Government.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
TEST FACILITY	4
SYSTEM TEST CONFIGURATION.....	5
DESCRIPTION OF TEST CONFIGURATION	5
EQUIPMENT MODIFICATIONS	5
CONFIGURATION OF TEST SETUP	6
BLOCK DIAGRAM OF TEST SETUP	6
SUMMARY OF TEST RESULTS	7
§15.203 - ANTENNA APPLICATION	8
APPLICABLE STANDARD	8
§15.205, §15.209, §15.247 - RADIATED EMISSION	9
APPLICABLE STANDARD	9
MEASUREMENT UNCERTAINTY	9
EUT SETUP.....	9
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	10
TEST EQUIPMENT LIST AND DETAILS.....	10
TEST PROCEDURE	10
CORRECTED AMPLITUDE & MARGIN CALCULATION	10
TEST RESULTS SUMMARY	11
TEST DATA	11
§15.247(a)(1)-CHANNEL SEPARATION TEST	13
APPLICABLE STANDARD	13
TEST EQUIPMENT LIST AND DETAILS.....	13
TEST PROCEDURE	13
TEST DATA	13
§15.247(a)(1) 20dB BANDWIDTH TESTING	17
APPLICABLE STANDARD	17
TEST EQUIPMENT LIST AND DETAILS.....	17
TEST PROCEDURE	17
TEST DATA	17
§15.247(a)(1)(iii)-QUANTITY OF HOPPING CHANNEL TEST	21
APPLICABLE STANDARD	21
TEST EQUIPMENT LIST AND DETAILS.....	21
TEST PROCEDURE	21
TEST DATA	21
§15.247(a)(1)(iii) -TIME OF OCCUPANCY (DWELL TIME).....	23
APPLICABLE STANDARD	23
TEST EQUIPMENT LIST AND DETAILS.....	23
TEST PROCEDURE	23
TEST DATA	23
§15.247(b)(1) - PEAK OUTPUT POWER MEASUREMENT	30
APPLICABLE STANDARD	30
TEST EQUIPMENT LIST AND DETAILS.....	30
TEST PROCEDURE	30
TEST DATA	30
§15.247(d)- BAND EDGES TESTING.....	34

APPLICABLE STANDARD	34
TEST EQUIPMENT LIST AND DETAILS.....	34
TEST PROCEDURE	34
TEST DATA	34

GENERAL INFORMATION

Product Description for Equipment Under Test (EUT)

The LAYON International Electronic & Telecom Co., Ltd's product, model number: U&I-02 or the "EUT" as referred to in this report is a Bluetooth Headset. The EUT is measured approximately 7.0 cm L x 5.0 cm W x 2.0 cm H, rated input voltage: DC 1.5V battery.

** The test data gathered are from production sample, serial number: 57123B002A19, provided by the manufacturer.*

Objective

The following test report is prepared on behalf of LAYON International Electronic & Telecom Co., Ltd in accordance with Part 2, Subpart J, and Part 15, Subparts A, B and C of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209, and 15.247 rules.

Related Submittal(s)/Grant(s)

No related submittal(s).

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Lab Corp. (ShenZhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility

The Test site used by Bay Area Compliance Lab Corp. (ShenZhen) to collect test data is located in the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone, ShenZhen, Guangdong 518038, P.R.China.

Test site at Bay Area Compliance Lab Corp. (ShenZhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on November 04, 2004. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2003.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Lab Corp. (ShenZhen) is a National Institute of Standards and Technology (NIST) accredited laboratory, under the National Voluntary Laboratory Accredited Program (Lab Code 200707-0). The current scope of accreditations can be found at <http://ts.nist.gov/ts/htdocs/210/214/scopes/2007070.htm>

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in a typical fashion (as normally used by a typical user).

Equipment Modifications


Bay Area Compliance Lab Corp. (ShenZhen) has not done any modification on the EUT.

Configuration of Test Setup



EUT

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.203	Antenna Requirement	Compliant
§15.205&§15.209	Radiated Emission	Compliant *
§15.247(a)(1)	Channel Separation Test	Compliant
§15.247(a)(1)(iii)	Time of occupancy (Dwell Time)	Compliant
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliant
§15.247(b)(1)	Peak Output Power Measurement	Compliant
§15.247(d)	Band edges testing	Compliant
§15.247(b)(4) § 2.1093	RF Safety Requirements	Compliant
§ 2.1051	Spurious Emission at Antenna Port	Compliant

* Within measurement uncertainty

§15.203 - ANTENNA APPLICATION

Applicable Standard

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

This product has a permanent antenna, fulfill the requirement of this section.

Test Result: Pass

§15.205, §15.209, §15.247 - RADIATED EMISSION

Applicable Standard


According to FCC §15.247 (d)

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at Bay Area Compliance Lab Corp. (ShenZhen) is ± 4.4 dB.

EUT Setup



The radiated emission tests were performed in the 3-meter Chamber, using the setup accordance with the ANSI C63.4-2003. The specification used was the FCC 15.209 and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

<i>Frequency Range</i>	<i>RBW</i>	<i>Video B/W</i>
30MHz – 1000 MHz	100 kHz	300 kHz
1000 MHz – 25 GHz	1 MHz	3 MHz

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
A.H. System	Horn Antenna	SAS-200/571	135	2005-4-28	2006-4-28
HP	Amplifier	HP8447D	2944A09795	2005-8-17	2006-8-17
HP	Preamplifier	8449B	3008A00277	2005-8-17	2006-8-17
Rohde & Schwarz	Spectrum Analyzer	FSEM30	849720/019	2004-11-10	2005-11-10
Rohde&Schwarz	EMI Test Receiver	ESCI	100035	2005-8-17	2006-8-17
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2005-4-28	2006-4-28

* **Statement of Traceability:** Bay Area Compliance Lab Corp. (ShenZhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All data was recorded in the PK&AV detection mode.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Meter reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Meter Reading} + \text{Antenna Loss} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Standard Limit}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.207, and 15.247, with the worst margin reading of:

-10.59 dB at 1800.7 MHz in the **Vertical** polarization, Low Channel

-10.61 dB at 1800.5 MHz in the **Vertical** polarization, Middle Channel

-2.55 dB at 1800.5 MHz in the **Vertical** polarization, High Channel

Test Data

Environmental Conditions

Temperature:	27 °C
Relative Humidity:	50 %
ATM Pressure:	1009 mbar

The testing was performed by Jandy Su on 2005-9-24

Test mode: Transmitting

INDICATED			TABLE	ANTENNA		CORRECTION FACTOR			CORRECTED AMPLITUDE	FCC 15.209 & FCC 15.247	
Frequency	Meter Reading	Comments	Angle	Height	Polar	Antenna Loss	Cable Loss	Amp. Gain	Corr. Ampl.	Limit	Margin
MHz	dBμV		Degree	Meter	H/ V	dB	dB	dB	dBμV/m	dBμV/m	dB
Low Channel, 1GHz-25GHz											
2402.0	89.32	PK	45	1.0	V	29.0	3.70	35.16	86.86		
2402.0	91.30	PK	180	1.2	H	29.0	3.70	35.16	88.84		
2402.0	89.10	AV	45	1.2	V	29.0	3.70	35.16	86.64		
2402.0	91.20	AV	45	1.0	H	29.0	3.7	35.16	88.74		
1800.7	41.46	AV	180	1.0	V	23.8	3.36	25.21	43.41	54	-10.59
4804.0	32.20	AV	60	1.0	H	33.9	5.20	33.00	38.30	54	-15.70
4804.0	31.10	AV	90	1.2	V	33.9	5.20	33.00	37.20	54	-16.80
1800.7	51.54	PK	45	1.2	V	23.8	3.36	25.21	53.49	74	-20.51
1601.0	31.33	AV	45	1.0	H	23.8	3.36	25.21	33.28	54	-20.72
7206.0	22.16	AV	270	1.0	H	36.3	6.00	33.50	30.96	54	-23.04
4804.0	43.90	PK	45	1.0	H	33.9	5.20	33.00	50.00	74	-24.00
7206.0	20.15	AV	180	1.2	V	36.3	6.00	33.50	28.95	54	-25.05
4804.0	42.80	PK	45	1.0	V	33.9	5.20	33.00	48.90	74	-25.10
1601.0	43.16	PK	270	1.0	H	23.8	3.36	25.21	45.11	74	-28.89
7206.0	32.70	PK	60	1.0	V	36.3	6.00	33.50	41.50	74	-32.50
7206.0	31.44	PK	60	1.2	H	36.3	6.00	33.50	40.24	74	-33.76

INDICATED			TABLE	ANTENNA		CORRECTION FACTOR			CORRECTED AMPLITUDE	FCC 15.209 & FCC 15.247	
Frequency MHz	Meter Reading dBμV	Comments	Angle Degree	Height Meter	Polar H/ V	Antenna Loss dB	Cable Loss dB	Amp. Gain dB	Corr. Ampl. dBμV/m	Limit dBμV/m	Margin dB
Middle Channel, 1GHz-25GHz											
2441.0	91.84	PK	45	1.0	V	29.0	3.7	35.16	89.38		
2441.0	93.24	PK	180	1.2	H	29.0	3.7	35.16	90.78		
2441.0	90.50	AV	45	1.2	V	29.0	3.7	35.16	88.04		
2441.0	92.10	AV	45	1.0	H	29.0	3.7	35.16	89.64		
1800.5	41.44	AV	180	1.0	V	23.8	3.36	25.21	43.39	54	-10.61
4882.0	33.60	AV	60	1.0	H	33.9	5.2	33	39.70	54	-14.30
1800.5	37.50	AV	45	1.0	H	23.8	3.36	25.21	39.45	54	-14.55
4882.0	32.70	AV	90	1.2	V	33.9	5.2	33	38.80	54	-15.20
1800.5	50.42	PK	45	1.2	V	23.8	3.36	25.21	52.37	74	-21.63
4882.0	45.06	PK	45	1.0	H	33.9	5.2	33	51.16	74	-22.84
7323.0	22.03	AV	270	1.0	H	36.3	6	33.5	30.83	54	-23.17
7323.0	21.10	AV	180	1.2	V	36.3	6	33.5	29.90	54	-24.10
4882.0	43.69	PK	45	1.0	V	33.9	5.2	33	49.79	74	-24.21
1800.5	41.80	PK	270	1.0	H	23.8	3.36	25.21	43.75	74	-30.25
7323.0	33.02	PK	60	1.0	V	36.3	6	33.5	41.82	74	-32.18
7323.0	32.79	PK	60	1.2	H	36.3	6	33.5	41.59	74	-32.41
High Channel, 1GHz-25GHz											
2480.0	86.12	PK	45	1.0	H	29.0	3.7	35.16	83.66		
2480.0	85.23	PK	180	1.2	V	29.0	3.7	35.16	82.77		
2480.0	86.10	AV	45	1.2	H	29.0	3.7	35.16	83.64		
2480.0	85.20	AV	45	1.0	V	29.0	3.7	35.16	82.74		
1800.5	49.50	AV	45	1.0	V	23.8	3.4	25.21	51.45	54	-2.55
1800.5	38.00	AV	180	1.0	H	23.8	3.4	25.21	39.95	54	-14.05
4960.0	30.30	AV	60	1.0	V	33.9	5.2	33.00	36.40	54	-17.60
4960.0	29.70	AV	90	1.2	H	33.9	5.2	33.00	35.80	54	-18.20
1800.5	51.35	PK	270	1.0	V	23.8	3.4	25.21	53.30	74	-20.70
7440.0	21.50	AV	180	1.2	H	36.3	6.0	33.50	30.30	54	-23.70
7440.0	20.50	AV	270	1.0	V	36.3	6.0	33.50	29.30	54	-24.70
4960.0	42.70	PK	45	1.0	V	33.9	5.2	33.00	48.80	74	-25.20
4960.0	42.32	PK	45	1.0	H	33.9	5.2	33.00	48.42	74	-25.58
1800.5	40.52	PK	45	1.2	H	23.8	3.4	25.21	42.47	74	-31.53
7440.0	31.49	PK	60	1.2	V	36.3	6.0	33.50	40.29	74	-33.71
7440.0	30.75	PK	60	1.0	H	36.3	6.0	33.50	39.55	74	-34.45

§15.247(a)(1)-CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20dB Bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2005-8-17	2006-8-17

* **Statement of Traceability:** Bay Area Compliance Lab Corp. (ShenZhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

1. Set the EUT in transmitting mode, spectrum Bandwidth was set at 100 kHz, maxhold the channel.
2. Set the adjacent channel of the EUT maxhold another truce.
3. Measure the channel separation.

Test Data

Environmental Conditions


Temperature:	27 °C
Relative Humidity:	50 %
ATM Pressure:	1009 mbar

The testing was performed by Jandy Su on 2005-9-22

Test Result: Pass


Test mode: Transmitting

CHANNEL	CHANNEL FREQUENCY (MHz)	SEPARATION READ VALUE (kHz)	Limit (KHz) 2/3*(20dB BW)
Low Channel	2402	1000	182.67
Adjacency Channel	2403		
Middle Channel	2441	996	188.00
Adjacency Channel	2442		
High Channel	2480	1000	188.00
Adjacency Channel	2479		




Channel separation LOW CH LAYON M/N:U&I-02

Date: 22.SEP.2005 16:26:08



Channel separation MID CH LAYON M/N:U&I-02

Date: 22.SEP.2005 16:22:54



Channel separation HIGH CH LAYON M/N:U&I-02

Date: 22.SEP.2005 16:20:09

§15.247(a)(1) 20dB BANDWIDTH TESTING

Applicable Standard

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20dB Bandwidth of the hopping channel, whichever is greater.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2005-8-17	2006-8-17

* **Statement of Traceability:** Bay Area Compliance Lab Corp. (ShenZhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

1. Check the calibration of the measuring instrument using a known signal from an external generator.
2. Position the EUT without connection to the tunable table. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Data

Environmental Conditions

Temperature:	25 ° C
Relative Humidity:	50%
ATM Pressure:	1032mbar


The testing was performed by Jandy Su on 2005-9-19

Test Result: Pass

Test mode: Transmitting


The result has been complied with the §15.247(a)(1), see the following plot:

Channel	Channel frequency (MHz)	20dB Bandwidth (KHz)
Low channel	2402	274
Middle channel	2441	270
High channel	2480	270




Layon Bluetooth Headset U&I-02 Low Channel 20dB Bandwidth

Date: 19.SEP.2005 16:56:13



Layon Bluetooth Headset U&I-02 Mid Channel 20dB Bandwidth

Date: 19.SEP.2005 16:58:34



Layon Bluetooth Headset U&I-02 High Channel 20dB Bandwidth

Date: 19.SEP.2005 17:00:10

§15.247(a)(1)(iii)-QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2005-8-17	2006-8-17

* **Statement of Traceability:** Bay Area Compliance Lab Corp. (ShenZhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in transmitting mode from first channel to last.
3. By using the Max-Hold function record the Quantity of the channel.

Limit

FCC Part 15, Subpart C Section 15.247

FREQUENCY RANGE (MHz)	Limit (Quantity of Hopping Channel)			
	20 dB bandwidth <250 kHz	20 dB bandwidth >250 kHz	20 dB bandwidth <1 MHz	20 dB bandwidth >1 MHz
902-928	50	25	N/A	N/A
2400-2483.5	N/A	N/A	15	15
5725-5850	N/A	N/A	75	N/A

Test Data

Environmental Conditions

Temperature:	27 °C
Relative Humidity:	50 %
ATM Pressure:	1009 mbar


The testing was performed by Jandy Su on 2005-9-22

Test Result: Pass

Test mode: Transmitting

The frequency hopping systems operating in 2.4~2.4835 GHz band employ 79 nonoverlapping channels.

Hopping Channel Frequency Range (MHz)	Quantity OF hopping Channel Read Value (Channel)	Quantity Of Hopping channel limit (Channel)
2402 ~ 2480	79	>15



Quantity of hopping channel LAYON M/N:U&I-02

Date: 22.SEP.2005 16:35:35

§15.247(a)(1)(iii) -TIME OF OCCUPANCY (DWELL TIME)**Applicable Standard**

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2005-8-17	2006-8-17

* **Statement of Traceability:** Bay Area Compliance Lab Corp. (ShenZhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

The EUT was worked in channel hopping; Spectrum SPAN was set as 0 Hz, Sweep was set as 0.4 X channel no.(s), The quantity of False was get from single sweep. In addition, the time of single Pluses was tested.

Limit

FCC Part 15, Subpart C Section 15.247.

FREQUENCY RANGE (MHz)	LIMIT (ms)		
	20dB bandwidth <250kHz (50 Channel)	20dB bandwidth >250kHz (50 Channel)	20dB bandwidth <1 MHz (79 Channel)
902-928	400(20s)	400(10s)	N/A
2400-2483.5	N/A	N/A	400(31.6s)
5725-5850	N/A	N/A	400(30s)

Test Data**Environmental Conditions**


Temperature:	27 °C
Relative Humidity:	50 %
ATM Pressure:	1009 mbar

The testing was performed by Jandy Su on 2005-9-23

Test Result: Pass

Test mode: Transmitting


Channel	Pulse wide (msec)	Number of hopping Pluses in 0.4*channel number	Dwell time (sec)	Limit (sec)
Low Channel	14	8	0.112	0.4
Mid Channel	14	8	0.112	0.4
High Channel	13	8	0.104	0.4



NO. of hopping pluses LOW CH LANYON Bluetooth Headset M/N:U&


I-02

Date: 23.SEP.2005 17:02:23



Pluse Width LOW CH LANYON Bluetooth Headset M/N:U&I-02


Date: 23.SEP.2005 17:20:50



NO. of hopping pluses MID CH LANYON Bluetooth Headset M/N:U


&I-02

Date: 23.SEP.2005 16:47:34



Pluse Width MID CH LANYON Bluetooth Headset M/N:U&I-02


Date: 23.SEP.2005 16:55:21



NO. of hopping pluses HIGH CH LANYON Bluetooth Headset M/N:U

&I-02

Date: 23.SEP.2005 17:24:41



Pluse Width HIGH CH LANYON Bluetooth Headset M/N:U&I-02

Date: 23.SEP.2005 17:27:12

§15.247(b)(1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

(b) The maximum peak conducted output power of the intentional radiator shall not exceed the following:

(1) For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.


Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde&Schwarz	EMI Test Receiver	ESCI	100035	2005-8-17	2006-8-17

* **Statement of Traceability:** Bay Area Compliance Lab Corp. (ShenZhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the UFL port of EUT to a Peak Power Meter.



Test Data

Environmental Conditions


Temperature:	27 °C
Relative Humidity:	50 %
ATM Pressure:	1009 mbar

The testing was performed by Jandy Su on 2005-9-22

Test Result: Pass


Test mode: Transmitting

Channel	Channel Frequency (MHz)	Reading Power (dBm)	Cable Loss (dB)	Power Output (mw)	Limit (mw)
Low Channel	2402	-9.68	0.6	0.12	125
Middle Channel	2441	-6.77	0.6	0.24	125
High Channel	2480	-9.40	0.6	0.13	125




Peak output power LOW CH LAYON M/N:U&I-02

Date: 22.SEP.2005 16:12:02



Peak output power MID CH LAYON M/N:U&I-02

Date: 22.SEP.2005 16:06:14



Peak output power HIGH CH LAYON M/N:U&I-02

Date: 22.SEP.2005 16:13:37

§15.247(d)- BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2005-8-17	2006-8-17

* **Statement of Traceability:** Bay Area Compliance Lab Corp. (ShenZhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

1. Check the calibration of the measuring instrument using a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Start 2.4 G Hz, stop 2.4835 GHz, and make sure the instrument is operated in its linear range.
3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge.
4. Measure the frequency edge point amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the edge frequency.

Test Data

Environmental Conditions


Temperature:	27 °C
Relative Humidity:	50 %
ATM Pressure:	1009 mbar

The testing was performed by Jandy Su on 2005-9-8

Test Result: Pass


Test mode: Transmitting

Frequency (MHz)	Emission (dBuV/m)	Limit (dBuV/m)
2400.0	49.87	54
2438.5	48.77	54



Layon Bluetooth Headset U&I-02 Low Channel Bandedge

Date: 19.SEP.2005 17:13:53



Layon Bluetooth Headset U&I-02 High Channel Bandedge

Date: 19.SEP.2005 17:08:26