

Radio Exposure Evaluation Report

FCC ID : TOR-O435
Equipment : Wireless Access Point
Brand Name : ARISTA
Model Name : O-435 / O-435E
Applicant : Arista Networks, Inc.
5453 Great America Parkway, Santa Clara, CA 95054 USA
Manufacturer : Arista Networks, Inc.
5453 Great America Parkway, Santa Clara, CA 95054 USA
Standard : 47 CFR FCC Part 2 Subpart J, section 2.1091

The product was received on Oct. 28, 2024, and testing was started from Nov. 15, 2024 and completed on Jan. 09, 2025. We, SPORTON INTERNATIONAL INC. Hsinhua Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR FCC Part 2 Subpart J, section 2.1091 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Hsinhua Laboratory, the test report shall not be reproduced except in full.


Approved by: Jackson Tsai

SPORTON INTERNATIONAL INC. Hsinhua Laboratory
No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)



Table of Contents

HISTORY OF THIS TEST REPORT	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Information.....	5
1.2 Applicable Standards	8
1.3 Testing Location	8
2 MAXIMUM PERMISSIBLE EXPOSURE	9
2.1 Limit of Maximum Permissible Exposure	9
2.2 RF Exposure Exempt Measurement	10
2.3 Multiple RF Sources Exposure.....	11
2.4 MPE Calculation Method	12
2.5 Calculated Result and Limit.....	13
Photographs of EUT V01	



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
2	-	Exposure evaluation	PASS	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

None

Reviewed by: Ryan Hsiao

Report Producer: Michelle Tsai

1 General Description

1.1 Information

1.1.1 EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
2.4GHz WLAN	2400-2483.5	2412-2462	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) VHT: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM) 802.11be: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM, 4096QAM)
5GHz WLAN	5150-5250 5250-5350 5470-5725 5725-5850	5180-5240 5260-5320 5500-5720 5745-5825	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM) 802.11be: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM, 4096QAM)
6GHz WLAN	5925-6425 6525-6875	5955-6415 6535-6855	802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM) 802.11be: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM, 4096QAM)
Bluetooth	2400-2483.5	2402-2480	LE: DSSS (GFSK)

1.1.2 Antenna Information

O-435

Ant.	Brand	Model Name	Antenna Type	Connector	Support	Radio
1	WHAYU	C393-510240-A	PIFA	I-Pex	6G	Radio 2
2	WHAYU	C393-510240-A	PIFA	I-Pex	6G	Radio 2
3	WHAYU	C393-510240-A	PIFA	I-Pex	2.4G+5G+6G	Radio 0
4	WHAYU	C393-510240-A	PIFA	I-Pex	2.4G+5G+6G	Radio 0
5	WHAYU	C393-510240-A	PIFA	I-Pex	2.4G+5G	Radio 1+Radio 2
6	WHAYU	C393-510240-A	PIFA	I-Pex	2.4G+5G	Radio 1+Radio 2
7	WHAYU	C393-510240-A	PIFA	I-Pex	BT	-
8	WHAYU	C393-510240-A	PIFA	I-Pex	GPS	-



Ant.	Port	Gain (dBi)										
		2.4G	UNII-1	UNII-2A	UNII-2C	UNII-3	UNII-5	UNII-6	UNII-7	UNII-8	BT	GPS
1	1	-	-	-	-	-	5.72	5.17	3.67	4.67	-	-
2	2	-	-	-	-	-	5.85	5.09	4.29	3.84	-	-
3	1	3.1	5.33	5.97	4.41	3.32	5	4.13	4.87	3.99	-	-
4	2	3.26	4.32	4.56	5.26	4.37	4.41	5.15	4.7	3.73	-	-
5	1	2.85	3.69	3.89	4.64	4.83	-	-	-	-	-	-
6	2	2.54	3.35	4.34	5.05	3.83	-	-	-	-	-	-
7	1	-	-	-	-	-	-	-	-	-	6.3	-
8	1	-	-	-	-	-	-	-	-	-	-	2.7

Composite Gain (dBi)											
Ant.		2.4G	UNII-1	UNII-2A	UNII-2C	UNII-3	UNII-5	UNII-6	UNII-7	UNII-8	
1~2	DG [1SS]	-	-	-	-	-	6.2	6.74	5.04	5.54	
	DG [2SS]	-	-	-	-	-	5.85	5.17	4.29	4.67	
3~4	DG [1SS]	5.22	6.59	6.67	6.55	5.22	6.23	6.48	6.18	5.51	
	DG [2SS]	3.26	5.33	5.97	5.26	4.37	5	5.15	4.87	3.99	
5~6	DG [1SS]	4.24	5.3	4.88	5.54	4.84	-	-	-	-	
	DG [2SS]	2.85	3.69	4.34	5.05	4.83	-	-	-	-	

Note 1: The composite gain is derived as KDB 662911 D03 v01 which was used as directional gain. For more detail information, please refer to the Antenna Pattern Report AP4O0402.

O-435E

Ant.	Brand	Model Name	Antenna Type	Connector	Support	Radio
1	WHAYU	C393-510293-A	Panel	N-type	6G	Radio 2
2	WHAYU	C393-510293-A	Panel	N-type	6G	Radio 2
3	WHAYU	C393-510293-A	Panel	N-type	2.4G+5G+6G	Radio 0
4	WHAYU	C393-510293-A	Panel	N-type	2.4G+5G+6G	Radio 0
5	WHAYU	C393-510293-A	Panel	N-type	2.4G+5G	Radio 1+Radio 2
6	WHAYU	C393-510293-A	Panel	N-type	2.4G+5G	Radio 1+Radio 2
7	WHAYU	C393-510240-A	PIFA	I-Pex	BT	-
8	WHAYU	C393-510240-A	PIFA	I-Pex	GPS	-

Ant.	Port	Gain (dBi)										
		2.4G	UNII-1	UNII-2A	UNII-2C	UNII-3	UNII-5	UNII-6	UNII-7	UNII-8	BT	GPS
1	1	-	-	-	-	-	5.39	3.98	4.51	-	-	-
2	2	-	-	-	-	-	5.98	4.5	5.14	-	-	-
3	1	6.81	5.79	4.86	5.61	5.53	5.95	3.51	4.58	-	-	-
4	2	7.22	4.63	4.62	5.1	4.48	4.99	3.7	4.09	-	-	-
5	1	6.39	4.74	4.75	5.31	4.52	-	-	-	-	-	-
6	2	6.66	4.79	4.45	5.32	5.16	-	-	-	-	-	-
7	1	-	-	-	-	-	-	-	-	-	6.5	-
8	1	-	-	-	-	-	-	-	-	-	-	3.6

Note 2: Directional gain information

	Maximum Output Power	Power Spectral Density
Non-BF	Directional gain = Max.gain + array gain. For power measurements on IEEE 802.11 devices Array Gain = 0 dB (i.e., no array gain) for N ANT ≤ 4	$DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{BI}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$
BF	$DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{BI}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$	$DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{BI}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$

Note 3: The EUT has eight antennas.

For 2.4GHz function:

For IEEE 802.11 b/g/n/VHT/ax/be mode (2TX/2RX) < **Radio 0** >

Ant. 3 (port 1) and Ant. 4 (port 2) could receive simultaneously.

For IEEE 802.11 b/g/n/VHT/ax/be mode (2TX/2RX) < **Radio 1** >

Ant. 5 (port 1) and Ant. 6 (port 2) could receive simultaneously.

For 5GHz function:

For IEEE 802.11 a/n/ac/ax/be mode(2TX/2RX) < **Radio 0** >

Ant. 3 (port 1) and Ant. 4 (port 2) could receive simultaneously.

For IEEE 802.11 a/n/ac/ax/be mode(2TX/2RX) < **Radio 2** >

Ant. 5 (port 1) and Ant. 6 (port 2) could receive simultaneously

For 6GHz function:

For IEEE 802.11 ax/be mode(2TX/2RX) < **Radio 0** >

Ant. 3 (port 1) and Ant. 4 (port 2) could receive simultaneously.

For IEEE 802.11 ax/be mode(2TX/2RX) < **Radio 2** >

Ant. 1 (port 1) and Ant. 2 (port 2) could receive simultaneously

For BT function:

For IEEE 802.15.1 Bluetooth mode (1TX/1RX)

Ant. 7 (port 1) could transmit/receive.

1.2 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR FCC Part 2 Subpart J, section 2.1091
- ♦ KDB 447498 D04 Interim General RF Exposure Guidance v01

The following reference test guidance is not within the scope of accreditation of TAF.

- ♦ 47 CFR Part 1.1307
- ♦ 47 CFR Part 1.1310

1.3 Testing Location

Test Lab. : Sporton International Inc. Hsinhua Laboratory			
☒	Hsinhua (TAF: 3785)	ADD: No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)	
		TEL: 886-3-327-3456	FAX: 886-3-327-0973
Test site Designation No. TW3785 with FCC.			
☐	Wen 33rd.St. (TAF: 3785)	ADD: No.14-1, Ln. 19, Wen 33rd St., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)	
		TEL: 886-3-318-0787	FAX: 886-3-318-0287
Test site Designation No. TW0008 with FCC.			

2 Maximum Permissible Exposure

2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f ²)*	6
30-300	61.4	0.163	1.0	6
300-1500	-	-	F/300	6
1500-100,000	-	-	5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	F/1500	30
1500-100,000	-	-	1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

Multiple Transmitters Condition

Co-location as simultaneously transmitting (co-transmitting) and the evaluation shall be consider that simultaneous transmissions from co-located devices the individual transmitters are evaluated separately. After sum of the individual value (basic restriction / reference level) are measured/calculated also have to under basic restriction / reference level.

Co-transmitting mode:

1. Radio 1 (2.4G) + Radio 2 (5G) + Radio 0 (2.4G) + Bluetooth
2. Radio 1 (2.4G) + Radio 2 (5G) + Radio 0 (5G) + Bluetooth
3. Radio 1 (2.4G) + Radio 2 (5G) + Radio 0 (6E) + Bluetooth
4. Radio 1 (2.4G) + Radio 2 (6E) + Radio 0 (2.4G) + Bluetooth
5. Radio 1 (2.4G) + Radio 2 (6E) + Radio 0 (5G) + Bluetooth
6. Radio 1 (2.4G) + Radio 2 (6E) + Radio 0 (6E) + Bluetooth

2.2 RF Exposure Exempt Measurement

Option	Refer Std.	Exemption Exposure Thresholds (TL)
A	§1.1307(b)(3)(i)(A)	Available maximum time-averaged power is no more than 1 mW
B	§1.1307(b)(3)(i)(B)	$P_{th}(mW) = \begin{cases} ERP_{20cm} (d / 20cm)^x \rightarrow d \leq 20cm \\ ERP_{20cm} \rightarrow 20cm < d \leq 40cm \end{cases}$ $x = -\log_{10} \left(\frac{60}{ERP_{20cm} \sqrt{f}} \right) \text{ and } f \text{ is in GHz}$ $\begin{cases} ERP_{20cm} : 0.3GHz \leq f < 1.5GHz \rightarrow 2040f(mW) \\ ERP_{20cm} : 1.5GHz \leq f \leq 6GHz \rightarrow 3060(mW) \end{cases}$
C	§1.1307(b)(3)(i)(C)	$\begin{cases} 0.3 \sim 1.34MHz \rightarrow ERP(W) = 1920R^2 \\ 1.34 \sim 30MHz \rightarrow ERP(W) = 3450R^2 / f^2 \\ 30 \sim 300MHz \rightarrow ERP(W) = 3.83R^2 \\ 300 \sim 1500MHz \rightarrow ERP(W) = 0.0128R^2 f \\ 1500 \sim 100000MHz \rightarrow ERP(W) = 19.2R^2 \end{cases}$ f is in MHz; R is in m; $R > \lambda / 2\pi$

2.3 Multiple RF Sources Exposure

Refer Std.	Exemption Exposure Thresholds (TL)
§1.1307(b)(3)(ii)(A)	The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required)
§1.1307(b)(3)(ii)(B)	$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{ExposureLimit_k} \leq 1$ a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph §1.1307(b)(3)(i)(B) of this section for P , including existing exempt transmitters and those being added. b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph §1.1307(b)(3)(i)(C) of this section for Threshold ERP, including existing exempt transmitters and those being added. c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters. P_i = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive). P_{th,i} = the exemption threshold power (P_{th}) according to paragraph §1.1307(b)(3)(i)(B) of this section for fixed, mobile, or portable RF source i. ERP_j = the ERP of fixed, mobile, or portable RF source j. ERP_{th,j} = exemption threshold ERP for fixed, mobile, or portable RF source j, at a distance of at least λ/2π according to the applicable formula of paragraph §1.1307(b)(3)(i)(C) of this section. Evaluated_k = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure. Evaluated Limit_k = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k, as applicable from § 1.1310 of this chapter.



2.4 MPE Calculation Method

The MPE was calculated at 20 cm to show compliance with the power density limit.
The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

2.5 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

Non-Beamforming

2.4GHz WLAN_Radio 0_O-435

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
2.4G;G1D	3.26	19.47	22.73	0.50	128.27	20.00	0.04185	1.00000	B	3060	0.0419
2.4G;D1D	3.26	18.79	22.05	0.50	109.68	20.00	0.03579	1.00000	B	3060	0.0358

2.4GHz WLAN_Radio 1_O-435

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
2.4G;G1D	2.85	20.85	23.70	0.50	160.37	20.00	0.05233	1.00000	B	3060	0.0524
2.4G;D1D	2.85	20.92	23.77	0.50	162.97	20.00	0.05318	1.00000	B	3060	0.0533

5GHz WLAN_Radio 0_Full RU_O-435

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
5.2G;D1D	5.33	20.37	25.70	0.50	254.16	20.00	0.08293	1.00000	B	3060	0.0831
5.3G;D1D	5.97	20.30	26.27	0.50	289.81	20.00	0.09456	1.00000	B	3060	0.0947
5.6G;D1D	5.26	20.38	25.64	0.50	250.67	20.00	0.08180	1.00000	B	3060	0.0819
5.8G;D1D	4.37	20.18	24.55	0.50	195.03	20.00	0.06364	1.00000	B	3060	0.0637

5GHz WLAN_Radio 2_Full RU_O-435

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
5.2G;D1D	3.69	21.10	24.79	0.50	206.12	20.00	0.06726	1.00000	B	3060	0.0674
5.3G;D1D	4.34	20.71	25.05	0.50	218.83	20.00	0.07141	1.00000	B	3060	0.0715
5.6G;D1D	5.05	20.91	25.96	0.50	269.84	20.00	0.08805	1.00000	B	3060	0.0882
5.8G;D1D	4.83	20.80	25.63	0.50	250.10	20.00	0.08161	1.00000	B	3060	0.0817

5GHz WLAN_Radio 2_Multi-RU_O-435

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
5.2G;D1D	3.69	18.32	22.01	0.50	108.67	20.00	0.03546	1.00000	B	3060	0.0355
5.3G;D1D	4.34	17.44	21.78	0.50	103.06	20.00	0.03363	1.00000	B	3060	0.0337
5.6G;D1D	5.05	18.42	23.47	0.50	152.09	20.00	0.04963	1.00000	B	3060	0.0497
5.8G;D1D	4.83	17.67	22.50	0.50	121.65	20.00	0.03969	1.00000	B	3060	0.0398

**Non-Beamforming****5GHz WLAN_Radio 2_Channel Puncturing_O-435**

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
5.2G;D1D	3.69	19.24	22.93	0.50	134.31	20.00	0.04383	1.00000	B	3060	0.0439
5.3G;D1D	4.34	18.79	23.13	0.50	140.64	20.00	0.04589	1.00000	B	3060	0.0460
5.6G;D1D	5.05	19.96	25.01	0.50	216.83	20.00	0.07075	1.00000	B	3060	0.0709
5.8G;D1D	4.83	18.95	23.78	0.50	163.35	20.00	0.05330	1.00000	B	3060	0.0534

6GHz WLAN_Radio 0_Full RU_O-435

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
6.2G;D1D	5.00	18.03	23.03	0.50	137.44	20.00	0.04485	1.00000	C	768	0.1790
6.7G;D1D	4.87	18.66	23.53	0.50	154.21	20.00	0.05032	1.00000	C	768	0.2008

6GHz WLAN_Radio 2_Full RU_O-435

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
6.2G;D1D	5.85	20.47	26.32	0.50	293.16	20.00	0.09566	1.00000	C	768	0.3817
6.7G;D1D	4.29	19.74	24.03	0.50	173.03	20.00	0.05646	1.00000	C	768	0.2253

6GHz WLAN_Radio 2_Multi-RU_O-435

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
6.2G;D1D	5.85	17.89	23.74	0.50	161.85	20.00	0.05281	1.00000	C	768	0.2107
6.7G;D1D	4.29	17.37	21.66	0.50	100.26	20.00	0.03271	1.00000	C	768	0.1305

6GHz WLAN_Radio 2_Channel Puncturing_O-435

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
6.2G;D1D	5.85	19.56	25.41	0.50	237.74	20.00	0.07758	1.00000	C	768	0.3096
6.7G;D1D	4.29	19.01	23.30	0.50	146.25	20.00	0.04772	1.00000	C	768	0.1904

Bluetooth

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
2.4G;BT-LE	6.30	9.99	16.29	0.50	29.11	20.00	0.00950	1.00000	B	3060	0.0095

**Non-Beamforming****2.4GHz WLAN_Radio 0_O-435E**

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
2.4G;G1D	7.22	19.35	26.57	0.50	310.53	20.00	0.10133	1.00000	B	3060	0.1015
2.4G;D1D	7.22	18.69	25.91	0.50	266.75	20.00	0.08704	1.00000	B	3060	0.0872

2.4GHz WLAN_Radio 1_O-435E

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
2.4G;G1D	6.66	20.67	27.33	0.50	369.92	20.00	0.12071	1.00000	B	3060	0.1209
2.4G;D1D	6.66	20.70	27.36	0.50	372.49	20.00	0.12154	1.00000	B	3060	0.1217

5GHz WLAN_Radio 0_Full RU_O-435E

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
5.2G;D1D	5.79	20.50	26.29	0.50	291.15	20.00	0.09500	1.00000	B	3060	0.0951
5.3G;D1D	4.86	20.54	25.40	0.50	237.20	20.00	0.07740	1.00000	B	3060	0.0775
5.6G;D1D	5.61	20.78	26.39	0.50	297.93	20.00	0.09721	1.00000	B	3060	0.0974
5.8G;D1D	5.53	20.66	26.19	0.50	284.52	20.00	0.09284	1.00000	B	3060	0.0930

5GHz WLAN_Radio 2_Full RU_O-435E

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
5.2G;D1D	4.79	20.96	25.75	0.50	257.10	20.00	0.08389	1.00000	B	3060	0.0840
5.3G;D1D	4.75	20.14	24.89	0.50	210.92	20.00	0.06882	1.00000	B	3060	0.0689
5.6G;D1D	5.32	20.58	25.90	0.50	266.14	20.00	0.08684	1.00000	B	3060	0.0870
5.8G;D1D	5.16	20.35	25.51	0.50	243.28	20.00	0.07938	1.00000	B	3060	0.0795

5GHz WLAN_Radio 2_Multi-RU_O-435E

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
5.2G;D1D	4.79	18.54	23.33	0.50	147.27	20.00	0.04805	1.00000	B	3060	0.0481
5.3G;D1D	4.75	17.82	22.57	0.50	123.63	20.00	0.04034	1.00000	B	3060	0.0404
5.6G;D1D	5.32	18.30	23.62	0.50	157.44	20.00	0.05137	1.00000	B	3060	0.0515
5.8G;D1D	5.16	17.89	23.05	0.50	138.07	20.00	0.04505	1.00000	B	3060	0.0451

**Non-Beamforming****5GHz WLAN_Radio 2_Channel Puncturing_O-435E**

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
5.2G;D1D	4.79	18.32	23.11	0.50	139.99	20.00	0.04568	1.00000	B	3060	0.0457
5.3G;D1D	4.75	18.37	23.12	0.50	140.32	20.00	0.04579	1.00000	B	3060	0.0459
5.6G;D1D	5.32	18.94	24.26	0.50	182.44	20.00	0.05953	1.00000	B	3060	0.0596
5.8G;D1D	5.16	18.11	23.27	0.50	145.25	20.00	0.04739	1.00000	B	3060	0.0475

6GHz WLAN_Radio 0_Full RU_O-435E

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
6.2G;D1D	5.95	16.53	22.48	0.50	121.09	20.00	0.03951	1.00000	C	768	0.1577
6.7G;D1D	4.58	16.93	21.51	0.50	96.85	20.00	0.03160	1.00000	C	768	0.1261

6GHz WLAN_Radio 2_Full RU_O-435E

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
6.2G;D1D	5.98	19.36	25.34	0.50	233.94	20.00	0.07634	1.00000	C	768	0.3046
6.7G;D1D	5.14	18.77	23.91	0.50	168.31	20.00	0.05492	1.00000	C	768	0.2192

6GHz WLAN_Radio 2_Multi-RU_O-435E

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
6.2G;D1D	5.98	17.11	23.09	0.50	139.35	20.00	0.04547	1.00000	C	768	0.1814
6.7G;D1D	5.14	16.19	21.33	0.50	92.92	20.00	0.03032	1.00000	C	768	0.1210

6GHz WLAN_Radio 2_Channel Puncturing_O-435E

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
6.2G;D1D	5.98	19.00	24.98	0.50	215.33	20.00	0.07026	1.00000	C	768	0.2804
6.7G;D1D	5.14	17.86	23.00	0.50	136.49	20.00	0.04454	1.00000	C	768	0.1777

Bluetooth

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
2.4G;BT-LE	6.50	10.00	16.50	0.50	30.56	20.00	0.00997	1.00000	B	3060	0.0100

**Beamforming
2.4GHz WLAN_Radio 0_O-435**

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
2.4G;D1D	5.22	18.79	24.01	0.50	172.23	20.00	0.05620	1.00000	B	3060	0.0563

2.4GHz WLAN_Radio 1_O-435

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
2.4G;D1D	4.24	20.92	25.16	0.50	224.45	20.00	0.07324	1.00000	B	3060	0.0733

5GHz WLAN_Radio 0_Full RU_O-435

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
5.2G;D1D	6.59	19.11	25.70	0.50	254.16	20.00	0.08293	1.00000	B	3060	0.0831
5.3G;D1D	6.67	20.13	26.80	0.50	327.42	20.00	0.10684	1.00000	B	3060	0.1070
5.6G;D1D	6.55	20.26	26.81	0.50	328.18	20.00	0.10709	1.00000	B	3060	0.1072
5.8G;D1D	5.22	20.18	25.40	0.50	237.20	20.00	0.07740	1.00000	B	3060	0.0775

5GHz WLAN_Radio 2_Full RU_O-435

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
5.2G;D1D	5.30	19.49	24.79	0.50	206.12	20.00	0.06726	1.00000	B	3060	0.0674
5.3G;D1D	4.88	20.71	25.59	0.50	247.80	20.00	0.08086	1.00000	B	3060	0.0810
5.6G;D1D	5.54	20.91	26.45	0.50	302.07	20.00	0.09857	1.00000	B	3060	0.0987
5.8G;D1D	4.84	20.80	25.64	0.50	250.67	20.00	0.08180	1.00000	B	3060	0.0819

6GHz WLAN_Radio 0_Full RU_O-435

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
6.2G;D1D	6.23	16.80	23.03	0.50	137.44	20.00	0.04485	1.00000	C	768	0.1790
6.7G;D1D	6.18	17.35	23.53	0.50	154.21	20.00	0.05032	1.00000	C	768	0.2008

6GHz WLAN_Radio 2_Full RU_O-435

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
6.2G;D1D	6.20	20.12	26.32	0.50	293.16	20.00	0.09566	1.00000	C	768	0.3817
6.7G;D1D	5.04	18.99	24.03	0.50	173.03	20.00	0.05646	1.00000	C	768	0.2253

**Beamforming
2.4GHz WLAN_Radio 0_O-435E**

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
2.4G;D1D	10.03	18.69	28.72	0.50	509.46	20.00	0.16624	1.00000	B	3060	0.1665

2.4GHz WLAN_Radio 1_O-435E

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
2.4G;D1D	9.54	20.70	30.24	0.50	722.95	20.00	0.23590	1.00000	B	3060	0.2363

5GHz WLAN_Radio 0_Full RU_O-435E

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
5.2G;D1D	8.24	18.02	26.26	0.50	289.14	20.00	0.09435	1.00000	B	3060	0.0945
5.3G;D1D	7.75	20.54	28.29	0.50	461.43	20.00	0.15057	1.00000	B	3060	0.1508
5.6G;D1D	8.37	20.66	29.03	0.50	547.15	20.00	0.17854	1.00000	B	3060	0.1788
5.8G;D1D	8.03	20.64	28.67	0.50	503.63	20.00	0.16434	1.00000	B	3060	0.1646

5GHz WLAN_Radio 2_Full RU_O-435E

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
5.2G;D1D	7.78	17.97	25.75	0.50	257.10	20.00	0.08389	1.00000	B	3060	0.0840
5.3G;D1D	7.61	20.14	27.75	0.50	407.48	20.00	0.13296	1.00000	B	3060	0.1332
5.6G;D1D	8.33	20.58	28.91	0.50	532.24	20.00	0.17367	1.00000	B	3060	0.1739
5.8G;D1D	7.86	20.35	28.21	0.50	453.01	20.00	0.14782	1.00000	B	3060	0.1480

6GHz WLAN_Radio 0_Full RU_O-435E

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
6.2G;D1D	8.49	13.99	22.48	0.50	121.09	20.00	0.03951	1.00000	C	768	0.1577
6.7G;D1D	7.35	14.16	21.51	0.50	96.85	20.00	0.03160	1.00000	C	768	0.1261

6GHz WLAN_Radio 2_Full RU_O-435E

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
6.2G;D1D	8.70	16.64	25.34	0.50	233.94	20.00	0.07634	1.00000	C	768	0.3046
6.7G;D1D	7.84	16.07	23.91	0.50	168.31	20.00	0.05492	1.00000	C	768	0.2192

Note 1: Option A, B and C refer as clause 2.2

Note 2: For option B, Pth(mW) convert to TL ERP(mW); For option C, ERP(W) convert to TL ERP(mW)

Note 3: TL Ratio=Tune-up ERP(mW)/TL ERP(mW)

**Simultaneous Transmission Analysis Mode:****Radio 1 (2.4G) + Radio 2 (5G) + Radio 0 (2.4G) + Bluetooth (O-435)**

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
2.4G;D1D	4.24	20.92	25.16	0.50	224.45	20.00	0.07324	1.00000	B	3060	0.0733
5.6G;D1D	5.54	20.91	26.45	0.50	302.07	20.00	0.09857	1.00000	B	3060	0.0987
2.4G;BT-LE	6.30	9.99	16.29	0.50	29.11	20.00	0.00950	1.00000	B	3060	0.0095
2.4G;D1D	5.22	18.79	24.01	0.50	172.23	20.00	0.05620	1.00000	B	3060	0.0563
										Sum Ratio	0.2378
										Ratio Limit	1

Radio 1 (2.4G) + Radio 2 (5G) + Radio 0 (5G) + Bluetooth (O-435)

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
2.4G;D1D	4.24	20.92	25.16	0.50	224.45	20.00	0.07324	1.00000	B	3060	0.0733
5.6G;D1D	5.54	20.91	26.45	0.50	302.07	20.00	0.09857	1.00000	B	3060	0.0987
2.4G;BT-LE	6.30	9.99	16.29	0.50	29.11	20.00	0.00950	1.00000	B	3060	0.0095
5.6G;D1D	6.55	20.26	26.81	0.50	328.18	20.00	0.10709	1.00000	B	3060	0.1072
										Sum Ratio	0.2887
										Ratio Limit	1

Radio 1 (2.4G) + Radio 2 (5G) + Radio 0 (6E) + Bluetooth (O-435)

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
2.4G;D1D	4.24	20.92	25.16	0.50	224.45	20.00	0.07324	1.00000	B	3060	0.0733
5.6G;D1D	5.54	20.91	26.45	0.50	302.07	20.00	0.09857	1.00000	B	3060	0.0987
2.4G;BT-LE	6.30	9.99	16.29	0.50	29.11	20.00	0.00950	1.00000	B	3060	0.0095
6.7G;D1D	4.87	18.66	23.53	0.50	154.21	20.00	0.05032	1.00000	C	768	0.2008
										Sum Ratio	0.3823
										Ratio Limit	1

Radio 1 (2.4G) + Radio 2 (6E) + Radio 0 (2.4G) + Bluetooth (O-435)

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
2.4G;D1D	4.24	20.92	25.16	0.50	224.45	20.00	0.07324	1.00000	B	3060	0.0733
6.2G;D1D	5.85	20.47	26.32	0.50	293.16	20.00	0.09566	1.00000	C	768	0.3817
2.4G;BT-LE	6.30	9.99	16.29	0.50	29.11	20.00	0.00950	1.00000	B	3060	0.0095
2.4G;D1D	5.22	18.79	24.01	0.50	172.23	20.00	0.05620	1.00000	B	3060	0.0563
										Sum Ratio	0.5208
										Ratio Limit	1

**Radio 1 (2.4G) + Radio 2 (6E) + Radio 0 (5G) + Bluetooth (O-435)**

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
2.4G;D1D	4.24	20.92	25.16	0.50	224.45	20.00	0.07324	1.00000	B	3060	0.0733
6.2G;D1D	5.85	20.47	26.32	0.50	293.16	20.00	0.09566	1.00000	C	768	0.3817
2.4G;BT-LE	6.30	9.99	16.29	0.50	29.11	20.00	0.00950	1.00000	B	3060	0.0095
5.6G;D1D	6.55	20.26	26.81	0.50	328.18	20.00	0.10709	1.00000	B	3060	0.1072
										Sum Ratio	0.5717
										Ratio Limit	1

Radio 1 (2.4G) + Radio 2 (6E) + Radio 0 (6E) + Bluetooth (O-435)

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
2.4G;D1D	4.24	20.92	25.16	0.50	224.45	20.00	0.07324	1.00000	B	3060	0.0733
6.2G;D1D	5.85	20.47	26.32	0.50	293.16	20.00	0.09566	1.00000	C	768	0.3817
2.4G;BT-LE	6.30	9.99	16.29	0.50	29.11	20.00	0.00950	1.00000	B	3060	0.0095
6.7G;D1D	4.87	18.66	23.53	0.50	154.21	20.00	0.05032	1.00000	C	768	0.2008
										Sum Ratio	0.6653
										Ratio Limit	1

Radio 1 (2.4G) + Radio 2 (5G) + Radio 0 (2.4G) + Bluetooth (O-435E)

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
2.4G;D1D	9.54	20.70	30.24	0.50	722.95	20.00	0.23590	1.00000	B	3060	0.2363
5.6G;D1D	8.33	20.58	28.91	0.50	532.24	20.00	0.17367	1.00000	B	3060	0.1739
2.4G;BT-LE	6.50	10.00	16.50	0.50	30.56	20.00	0.00997	1.00000	B	3060	0.0100
2.4G;D1D	10.03	18.69	28.72	0.50	509.46	20.00	0.16624	1.00000	B	3060	0.1665
										Sum Ratio	0.5867
										Ratio Limit	1

Radio 1 (2.4G) + Radio 2 (5G) + Radio 0 (5G) + Bluetooth (O-435E)

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
2.4G;D1D	9.54	20.70	30.24	0.50	722.95	20.00	0.23590	1.00000	B	3060	0.2363
5.6G;D1D	8.33	20.58	28.91	0.50	532.24	20.00	0.17367	1.00000	B	3060	0.1739
2.4G;BT-LE	6.50	10.00	16.50	0.50	30.56	20.00	0.00997	1.00000	B	3060	0.0100
5.6G;D1D	8.37	20.66	29.03	0.50	547.15	20.00	0.17854	1.00000	B	3060	0.1788
										Sum Ratio	0.5990
										Ratio Limit	1

**Radio 1 (2.4G) + Radio 2 (5G) + Radio 0 (6E) + Bluetooth (O-435E)**

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
2.4G;D1D	9.54	20.70	30.24	0.50	722.95	20.00	0.23590	1.00000	B	3060	0.2363
5.6G;D1D	8.33	20.58	28.91	0.50	532.24	20.00	0.17367	1.00000	B	3060	0.1739
2.4G;BT-LE	6.50	10.00	16.50	0.50	30.56	20.00	0.00997	1.00000	B	3060	0.0100
6.2G;D1D	5.95	16.53	22.48	0.50	121.09	20.00	0.03951	1.00000	C	768	0.1577
										Sum Ratio	0.5779
										Ratio Limit	1

Radio 1 (2.4G) + Radio 2 (6E) + Radio 0 (2.4G) + Bluetooth (O-435E)

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
2.4G;D1D	9.54	20.70	30.24	0.50	722.95	20.00	0.23590	1.00000	B	3060	0.2363
6.2G;D1D	5.98	19.36	25.34	0.50	233.94	20.00	0.07634	1.00000	C	768	0.3046
2.4G;BT-LE	6.50	10.00	16.50	0.50	30.56	20.00	0.00997	1.00000	B	3060	0.0100
2.4G;D1D	10.03	18.69	28.72	0.50	509.46	20.00	0.16624	1.00000	B	3060	0.1665
										Sum Ratio	0.7174
										Ratio Limit	1

Radio 1 (2.4G) + Radio 2 (6E) + Radio 0 (5G) + Bluetooth (O-435E)

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
2.4G;D1D	9.54	20.70	30.24	0.50	722.95	20.00	0.23590	1.00000	B	3060	0.2363
6.2G;D1D	5.98	19.36	25.34	0.50	233.94	20.00	0.07634	1.00000	C	768	0.3046
2.4G;BT-LE	6.50	10.00	16.50	0.50	30.56	20.00	0.00997	1.00000	B	3060	0.0100
5.6G;D1D	8.37	20.66	29.03	0.50	547.15	20.00	0.17854	1.00000	B	3060	0.1788
										Sum Ratio	0.7297
										Ratio Limit	1

Radio 1 (2.4G) + Radio 2 (6E) + Radio 0 (6E) + Bluetooth (O-435E)

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
2.4G;D1D	9.54	20.70	30.24	0.50	722.95	20.00	0.23590	1.00000	B	3060	0.2363
6.2G;D1D	5.98	19.36	25.34	0.50	233.94	20.00	0.07634	1.00000	C	768	0.3046
2.4G;BT-LE	6.50	10.00	16.50	0.50	30.56	20.00	0.00997	1.00000	B	3060	0.0100
6.2G;D1D	5.95	16.53	22.48	0.50	121.09	20.00	0.03951	1.00000	C	768	0.1577
										Sum Ratio	0.7086
										Ratio Limit	1



Note 1: Option A, B and C refer as clause 2.2

Note 2: For option B, Pth(mW) convert to TL ERP(mW); For option C, ERP(W) convert to TL ERP(mW)

Note 3: TL Ratio=Tune-up ERP(mW)/TL ERP(mW)

Note 4: Refer as clause 2.3 Multiple RF Sources Exposure. Please follow below option and sum TL ration table.

Option	Sum TL Ratio_B	Option	Sum TL Ratio_C	Option	Sum TL Ratio_E
B	$\sum_{i=1}^a \frac{P_i}{P_{th,i}}$	C	$\sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}}$	E	$\sum_{k=1}^c \frac{Evaluated_k}{ExposureLimit_k}$

Note: The above antenna gain was declared by manufacturer.

————THE END————