FCC TEST REPORT

REPORT NO.: RF940930L06
MODEL NO.: VIEZ300
OEM MODEL NO.: IT-G1
RECEIVED: Sep. 30, 2005
TESTED: Sep. 30 ~ Oct. 24, 2005
ISSUED: Oct. 25, 2005

APPLICANT: Richcom Enterprise Co., LTD.

ADDRESS: 2F., No.51, Sec. 2, Chongyang Rd., Sanchong City, Taipei County 241, Taiwan (R.O.C.)

ISSUED BY: Advance Data Technology Corporation

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang 244, Taipei Hsien, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd., Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This test report consists of 68 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, A2LA or any government agencies. The test results in the report only apply to the tested sample.

NO. 2177-01

0528
ILAC MRA

TABLE OF CONTENTS

1. CERTIFICATION 4
2. SUMMARY OF TEST RESULTS 5
2.1 MEASUREMENT UNCERTAINTY 6
3. GENERAL INFORMATION 7
3.1 GENERAL DESCRIPTION OF EUT 7
3.2 DESCRIPTION OF TEST MODES 8
3.2.1 CONFIGURATION OF SYSTEM UNDER TEST 9
3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL 10
3.3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS 12
3.3.4 DESCRIPTION OF SUPPORT UNITS 12
4. TEST TYPES AND RESULTS 13
4.1 CONDUCTED EMISSION MEASUREMENT 13
4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT 13
4.1.2 TEST INSTRUMENTS 13
4.1.3 TEST PROCEDURES 14
4.1.4 DEVIATION FROM TEST STANDARD 14
4.1.5 TEST SETUP 15
4.1.6 EUT OPERATING CONDITIONS 16
4.1.7 TEST RESULTS 17
4.2 RADIATED EMISSION MEASUREMENT 29
4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT 29
4.2.2 TEST INSTRUMENTS 30
4.2.3 TEST PROCEDURES 31
4.2.4 DEVIATION FROM TEST STANDARD 31
4.2.5 TEST SETUP 32
4.2.6 EUT OPERATING CONDITIONS 32
4.2.7 TEST RESULTS 33
4.3 NUMBER OF HOPPING FREQUENCY USED 38
4.3.1 LIMIT OF HOPPING FREQUENCY USED 38
4.3.2 TEST INSTRUMENTS 38
4.3.3 TEST PROCEDURES 38
4.3.4 DEVIATION FROM TEST STANDARD 39
4.3.5 TEST SETUP 39
4.3.6 TEST RESULTS 39
4.4 DWELL TIME ON EACH CHANNEL 41
4.4.1 LIMIT OF DWELL TIME USED 41
4.4.2 TEST INSTRUMENTS 41
4.4.3 TEST PROCEDURES 41

4.4.4 DEVIATION FROM TEST STANDARD 41
4.4.5 TEST SETUP 42
4.4.6 TEST RESULTS 42
4.5 CHANNEL BANDWIDTH 46
4.5.1 LIMITS OF CHANNEL BANDWIDTH 46
4.5.2 TEST INSTRUMENTS 46
4.5.3 TEST PROCEDURE 46
4.5.4 DEVIATION FROM TEST STANDARD 47
4.5.5 TEST SETUP 47
4.5.6 EUT OPERATING CONDITION 47
4.5.7 TEST RESULTS 47
4.6 HOPPING CHANNEL SEPARATION 50
4.6.1 LIMIT OF HOPPING CHANNEL SEPARATION 50
4.6.2 TEST INSTRUMENTS 50
4.6.3 TEST PROCEDURES 50
4.6.4 DEVIATION FROM TEST STANDARD 51
4.6.5 TEST SETUP 51
4.6.6 TEST RESULTS 51
4.7 MAXIMUM PEAK OUTPUT POWER 54
4.7.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT 54
4.7.2 TEST INSTRUMENTS 54
4.7.3 TEST PROCEDURES 54
4.7.4 DEVIATION FROM TEST STANDARD 54
4.7.5 TEST SETUP 55
4.7.6 EUT OPERATING CONDITION 55
4.7.7 TEST RESULTS 55
4.8 BAND EDGES MEASUREMENT 58
4.8.1 LIMITS OF BAND EDGES MEASUREMENT 58
4.8.2 TEST INSTRUMENTS 58
4.8.3 TEST PROCEDURE 58
4.8.4 DEVIATION FROM TEST STANDARD 58
4.8.5 EUT OPERATING CONDITION 58
4.8.6 TEST RESULTS 59
4.9 ANTENNA REQUIREMENT 62
4.9.1 STANDARD APPLICABLE 62
4.9.2 ANTENNA CONNECTED CONSTRUCTION 62
5. PHOTOGRAPHS OF THE TEST CONFIGURATION 63
6. INFORMATION ON THE TESTING LABORATORIES 67
APPENDIX-A A-1

1. CERTIFICATION

PRODUCT:	VoIP-Easy Pocket Gateway
OEM PRODUCT:	Bluetooth VoIP Gateway
MODEL NO.:	VIEZ300
OEM MODEL NO.:	IT-G1
BRAND NAME:	Richcom
OEM BRAND NAME:	Yamakawa
APPLICANT:	Richcom Enterprise Co., LTD.
TESTED:	Sep. 30 ~ Oct. 24, 2005
TEST SAMPLE:	ENGINEERING SAMPLE
STANDARDS:	FCC Part 15, Subpart C (Section 15.247), ANSI C63.4-2003

The above equipment (Model: VIEZ300) have been tested by **Advance Data Technology Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

prepared BY : Rennie Wang , DATE: Oct. 25, 2005
Rennie Wang

TECHNICAL ACCEPTANCE : Gary Chang , **DATE:** Oct. 25, 2005
Responsible for RF
Gary Chang

APPROVED BY : Cody Chang , **DATE:** Oct. 25, 2005
Cody Chang / Deputy Manager

2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
STANDARD SECTION	**TEST TYPE AND LIMIT**	**RESULT**	**REMARK**
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is –16.14dB at 0.158MHz.
15.247(a)(1)(iii)	Number of Hopping Frequency Used Spec.: At least 15 channels	PASS	Meet the requirement of limit.
15.247(a)(1)(iii)	Dwell Time on Each Channel Spec. : Max. 0.4 second within 31.6 second	PASS	Meet the requirement of limit.
15.247(a)(1)	1. Hopping Channel Separation Spec. : Min. 25 kHz or 20 dB bandwidth, whichever is greater (see Note) 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power Spec.: max. 30dBm (see Note)	PASS	Meet the requirement of limit.
15.247(d)	Transmitter Radiated Emissions Spec.: Table 15.209	PASS	Meet the requirement of limit. Minimum passing margin is –3.82 dB at 2483.50MHz.
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit.

NOTE: If The Frequency Hopping System operating in 2400-2483.5MHz band and the output power less than 125mW. The hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of hopping channel whichever is greater.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz ~ 30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	3.73 dB
	200MHz ~1000MHz	3.74 dB
	1GHz ~ 18GHz	2.20 dB
	18GHz ~ 40GHz	1.88 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	VoIP-Easy Pocket Gateway
OEM PRODUCT	Bluetooth VoIP Gateway
MODEL NO.	VIEZ300
OEM MODEL NO.	IT-G1
POWER SUPPLY	5Vdc from host equipment
MODULATION TYPE	GFSK
RADIO TECHNOLOGY	FHSS
TRANSFER RATE	723kbps
FREQUENCY RANGE	2402 ~ 2480MHz
NUMBER OF CHANNEL	79
OUTPUT POWER	18.621 mW
ANTENNA TYPE	Chip antenna with 0dBi gain
DATA CABLE	0.05m shielded USB extension cable without core 0.1m shielded USB cable without core
I/O PORTS	USB
ASSOCIATED DEVICES	NA

NOTE:

1. Bluetooth technology is used in this EUT.
2. The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 DESCRIPTION OF TEST MODES

79 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2431	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

3.2.1 CONFIGURATION OF SYSTEM UNDER TEST

MODE A: WITH EXTENDED USB CABLE



MODE B: WITHOUT EXTENDED USB CABLE



3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE MODE	Applicable to				Description
	PLC	RE<1G	RE≥1G	APCM	
A	√	√	√	√	With extended USB cable
B	√	√	-	-	without extended USB cable

Where **PLC:** Power Line Conducted Emission **RE<1G:** Radiated Emission below 1GHz

RE≥1G: Radiated Emission above 1GHz **APCM:** Antenna Port Conducted Measurement

Note 1: "-" means no effect.

POWER LINE CONDUCTED EMISSION TEST:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types.

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
A	0 to 78	0, 39, 78	FHSS	GFSK	DH5
B	0 to 78	0, 39, 78	FHSS	GFSK	DH5

RADIATED EMISSION TEST (BELOW 1 GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, packet types and XYZ axis.

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE	Axis
A	0 to 78	78	FHSS	GFSK	DH5	Z
B	0 to 78	78	FHSS	GFSK	DH5	z

RADIATED EMISSION TEST (ABOVE 1 GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, packet types and XYZ axis.

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE	Axis
A	0 to 78	0, 39, 78	FHSS	GFSK	DH5	Z

BANDEDGE MEASUREMENT:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types.

☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	0, 78	FHSS	GFSK	DH5

ANTENNA PORT CONDUCTED MEASUREMENT:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types.

☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	0, 39, 78	FHSS	GFSK	DH5

3.3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C. (15.247)

ANSI C63.4- 2003

All test items have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

3.3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK COMPUTER	DELL	PP05L	16484462992	E2K24CLNS
2	MODEM	ACEEX	1414V/3	0401008269	IFAXDM1414
3	PRINTER	EPSON	LQ-300+	DCGY054147	FCC DoC Approved

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	1.2 m shielded cable without core
3	1.2 m shielded cable without core

NOTE: All power cords of the above support units are non shielded (1.8m).

4. TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

NOTE: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESCS30	100291	Nov. 16, 2005
RF signal cable Woken	5D-FB	Cable-HYC01-01	Jan. 09, 2006
LISN SCHWARZBECK	NNBL 8226-2	8226-142	May. 02, 2006
LISN ROHDE & SCHWARZ	ESH2-Z5	100104	Feb. 15, 2006
Software ADT	ADT_Cond_V3	NA	NA

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in HwaYa Shielded Room 1.

3. The VCCI Site Registration No. is C-2040.

4.1.3 TEST PROCEDURES

a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.

b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.

c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.1.6 EUT OPERATING CONDITIONS

a. Connected the EUT to a notebook system and placed on a testing table.

b. The notebook system ran a test program (provided by manufacturer) to enable EUT under transmission/receiving condition continuously at specific channel frequency.

c. The notebook system sent "H" messages to its screen.

d. The notebook system sent “H” messages to modem.

e. The notebook system sent "H" messages to printer, and the printer printed them on paper.

f. Steps c ~ e were repeated.

4.1.7 TEST RESULTS

MODE A: WITH EXTENDED USB CABLE

EUT	VoIP-Easy Pocket Gateway	MEASUREMENT DETAIL	
MODEL	VIEZ300	PHASE	Line 1
CHANNEL	Channel 0	6dB BANDWIDTH	9 kHz
MODULATION TYPE	GFSK	ENVIRONMENTAL CONDITIONS	25deg. C, 70%RH, 991hPa
TEST MODE	A	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Kalvin Hsieh		

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.166	0.11	47.89	-	48.00	-	65.18	55.18	-17.18	-
2	0.224	0.11	44.56	-	44.67	-	62.69	52.69	-18.02	-
3	0.701	0.18	31.18	-	31.36	-	56.00	46.00	-24.64	-
4	1.930	0.26	29.11	-	29.37	-	56.00	46.00	-26.63	-
5	3.926	0.39	25.71	-	26.10	-	56.00	46.00	-29.90	-
6	10.273	0.54	32.98	-	33.52	-	60.00	50.00	-26.48	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT	VoIP-Easy Pocket Gateway	MEASUREMENT DETAIL	
MODEL	VIEZ300	PHASE	Line 2
CHANNEL	Channel 0	6dB BANDWIDTH	9 kHz
MODULATION TYPE	GFSK	ENVIRONMENTAL CONDITIONS	25deg. C, 70%RH, 991hPa
TEST MODE	A	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Kalvin Hsieh		

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.159	0.11	45.99	-	46.10	-	65.50	55.50	-19.40	-
2	0.181	0.11	43.12	-	43.23	-	64.43	54.43	-21.20	-
3	0.588	0.15	27.95	-	28.10	-	56.00	46.00	-27.90	-
4	2.102	0.27	27.87	-	28.14	-	56.00	46.00	-27.86	-
5	9.234	0.43	31.92	-	32.35	-	60.00	50.00	-27.65	-
6	10.652	0.44	33.46	-	33.90	-	60.00	50.00	-26.10	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT	VoIP-Easy Pocket Gateway	MEASUREMENT DETAIL	
MODEL	VIEZ300	PHASE	Line 1
CHANNEL	Channel 39	6dB BANDWIDTH	9 kHz
MODULATION TYPE	GFSK	ENVIRONMENTAL CONDITIONS	25deg. C, 70%RH, 991hPa
TEST MODE	A	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Kalvin Hsieh		

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.166	0.11	44.86	-	44.97	-	65.18	55.18	-20.21	-
2	0.231	0.11	42.79	-	42.90	-	62.40	52.40	-19.50	-
3	0.349	0.11	35.05	-	35.16	-	58.98	48.98	-23.82	-
4	0.700	0.17	32.91	-	33.08	-	56.00	46.00	-22.92	-
5	2.234	0.28	30.34	-	30.62	-	56.00	46.00	-25.38	-
6	10.539	0.54	34.02	-	34.56	-	60.00	50.00	-25.44	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT	VoIP-Easy Pocket Gateway	**MEASUREMENT DETAIL**	
MODEL	VIEZ300	**PHASE**	Line 2
CHANNEL	Channel 39	**6dB BANDWIDTH**	9 kHz
MODULATION TYPE	GFSK	**ENVIRONMENTAL CONDITIONS**	25deg. C, 70%RH, 991hPa
TEST MODE	A	**INPUT POWER (SYSTEM)**	120Vac, 60 Hz
TESTED BY	Kalvin Hsieh		

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.162	0.11	46.54	-	46.65	-	65.38	55.38	-18.73	-
2	0.230	0.11	43.51	-	43.62	-	62.46	52.46	-18.84	-
3	0.701	0.18	33.98	-	34.16	-	56.00	46.00	-21.84	-
4	0.931	0.23	31.32	-	31.55	-	56.00	46.00	-24.45	-
5	2.426	0.29	28.53	-	28.82	-	56.00	46.00	-27.18	-
6	10.148	0.44	34.35	-	34.79	-	60.00	50.00	-25.21	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT	VoIP-Easy Pocket Gateway	MEASUREMENT DETAIL	
MODEL	VIEZ300	PHASE	Line 1
CHANNEL	Channel 78	6dB BANDWIDTH	9 kHz
MODULATION TYPE	GFSK	ENVIRONMENTAL CONDITIONS	25deg. C, 70%RH, 991hPa
TEST MODE	A	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Kalvin Hsieh		

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.170	0.11	44.58	-	44.69	-	64.95	54.95	-20.26	-
2	0.229	0.11	41.75	-	41.86	-	62.50	52.50	-20.64	-
3	0.233	0.11	42.49	-	42.60	-	62.33	52.33	-19.73	-
4	0.702	0.18	32.55	-	32.73	-	56.00	46.00	-23.27	-
5	1.980	0.26	30.32	-	30.58	-	56.00	46.00	-25.42	-
6	9.918	0.54	33.92	-	34.46	-	60.00	50.00	-25.54	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT	VoIP-Easy Pocket Gateway	MEASUREMENT DETAIL	
MODEL	VIEZ300	PHASE	Line 2
CHANNEL	Channel 78	6dB BANDWIDTH	9 kHz
MODULATION TYPE	GFSK	ENVIRONMENTAL CONDITIONS	25deg. C, 70%RH, 991hPa
TEST MODE	A	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Kalvin Hsieh		

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.166	0.11	42.66	-	42.77	-	65.18	55.18	-22.41	-
2	0.229	0.11	42.84	-	42.95	-	62.48	52.48	-19.53	-
3	0.464	0.12	34.30	-	34.42	-	56.61	46.61	-22.19	-
4	0.698	0.17	34.04	-	34.21	-	56.00	46.00	-21.79	-
5	2.215	0.27	29.72	-	29.99	-	56.00	46.00	-26.01	-
6	10.785	0.44	34.28	-	34.72	-	60.00	50.00	-25.28	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



MODE B: WITHOUT EXTENDED USB CABLE

EUT	VoIP-Easy Pocket Gateway	MEASUREMENT DETAIL	
MODEL	VIEZ300	PHASE	Line 1
CHANNEL	Channel 0	6dB BANDWIDTH	9 kHz
MODULATION TYPE	GFSK	ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH, 991hPa
TEST MODE	B	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Jay Hsu		

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.181	0.11	37.40	-	37.51	-	64.43	54.43	-26.92	-
2	0.220	0.11	40.15	-	40.26	-	62.81	52.81	-22.55	-
3	0.373	0.11	25.06	-	25.17	-	58.44	48.44	-33.27	-
4	1.648	0.25	25.40	-	25.65	-	56.00	46.00	-30.35	-
5	3.813	0.38	19.57	-	19.95	-	56.00	46.00	-36.05	-
6	14.008	0.55	27.42	-	27.97	-	60.00	50.00	-32.03	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT	VoIP-Easy Pocket Gateway	MEASUREMENT DETAIL	
MODEL	VIEZ300	PHASE	Line 2
CHANNEL	Channel 0	6dB BANDWIDTH	9 kHz
MODULATION TYPE	GFSK	ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH, 991hPa
TEST MODE	B	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Jay Hsu		

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.162	0.11	48.58	-	48.69	-	65.38	55.38	-16.69	-
2	0.220	0.11	38.03	-	38.14	-	62.81	52.81	-24.67	-
3	0.705	0.18	24.85	-	25.03	-	56.00	46.00	-30.97	-
4	1.609	0.25	22.83	-	23.08	-	56.00	46.00	-32.92	-
5	5.422	0.40	20.55	-	20.95	-	60.00	50.00	-39.05	-
6	13.949	0.45	28.39	-	28.84	-	60.00	50.00	-31.16	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT	VoIP-Easy Pocket Gateway	MEASUREMENT DETAIL	
MODEL	VIEZ300	PHASE	Line 1
CHANNEL	Channel 39	6dB BANDWIDTH	9 kHz
MODULATION TYPE	GFSK	ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH, 991hPa
TEST MODE	B	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Jay Hsu		

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.162	0.11	48.36	-	48.47	-	65.38	55.38	-16.91	-
2	0.224	0.11	36.43	-	36.54	-	62.66	52.66	-26.12	-
3	0.345	0.11	34.94	-	35.05	-	59.07	49.07	-24.02	-
4	2.145	0.27	28.00	-	28.27	-	56.00	46.00	-27.73	-
5	5.594	0.43	21.74	-	22.17	-	60.00	50.00	-37.83	-
6	9.648	0.53	27.22	-	27.75	-	60.00	50.00	-32.25	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT	VoIP-Easy Pocket Gateway	MEASUREMENT DETAIL	
MODEL	VIEZ300	PHASE	Line 2
CHANNEL	Channel 39	6dB BANDWIDTH	9 kHz
MODULATION TYPE	GFSK	ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH, 991hPa
TEST MODE	B	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Jay Hsu		

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.173	0.11	44.10	-	44.21	-	64.79	54.79	-20.59	-
2	0.240	0.11	38.81	-	38.92	-	62.10	52.10	-23.18	-
3	0.322	0.11	29.24	-	29.35	-	59.66	49.66	-30.31	-
4	1.879	0.26	28.21	-	28.47	-	56.00	46.00	-27.53	-
5	3.809	0.38	21.23	-	21.61	-	56.00	46.00	-34.39	-
6	14.316	0.45	27.85	-	28.30	-	60.00	50.00	-31.70	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT	VoIP-Easy Pocket Gateway	MEASUREMENT DETAIL	
MODEL	VIEZ300	PHASE	Line 1
CHANNEL	Channel 78	6dB BANDWIDTH	9 kHz
MODULATION TYPE	GFSK	ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH, 991hPa
TEST MODE	B	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Jay Hsu		

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	**0.158**	**0.11**	**49.33**	**-**	**49.44**	**-**	**65.58**	**55.58**	**-16.14**	**-**
2	0.232	0.11	38.30	-	38.41	-	62.38	52.38	-23.97	-
3	0.345	0.11	35.22	-	35.33	-	59.07	49.07	-23.74	-
4	1.855	0.26	22.63	-	22.89	-	56.00	46.00	-33.11	-
5	6.367	0.45	21.23	-	21.68	-	60.00	50.00	-38.32	-
6	9.363	0.52	26.81	-	27.33	-	60.00	50.00	-32.67	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT	VoIP-Easy Pocket Gateway	MEASUREMENT DETAIL	
MODEL	VIEZ300	PHASE	Line 2
CHANNEL	Channel 78	6dB BANDWIDTH	9 kHz
MODULATION TYPE	GFSK	ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH, 991hPa
TEST MODE	B	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Jay Hsu		

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.158	0.11	47.11	-	47.22	-	65.58	55.58	-18.36	-
2	0.248	0.11	39.69	-	39.80	-	61.84	51.84	-22.04	-
3	0.310	0.11	21.87	-	21.98	-	59.97	49.97	-37.99	-
4	0.697	0.17	25.70	-	25.87	-	56.00	46.00	-30.13	-
5	2.125	0.27	28.14	-	28.41	-	56.00	46.00	-27.59	-
6	10.270	0.44	28.03	-	28.47	-	60.00	50.00	-31.53	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESIB7	100188	Dec. 19, 2005
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100039	Nov. 21, 2005
BILOG Antenna SCHWARZBECK	VULB9168	9168-157	Jan. 22, 2006
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-407	Jan. 16, 2006
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA 9170241	Feb. 23, 2006
Preamplifier Agilent	8449B	3008A01961	Nov. 09, 2005
Preamplifier Agilent	8447D	2944A10629	Nov. 09, 2005
RF signal cable HUBER+SUHNER	SUCOFLEX 104	218182/4	Feb. 17, 2006
RF signal cable HUBER+SUHNER	SUCOFLEX 104	218194/4	Feb. 17, 2006
Software ADT.	ADT_Radiated_V5.14	NA	NA
Antenna Tower ADT.	AT100	AT93021702	NA
Turn Table ADT.	TT100.	TT93021702	NA
Controller ADT.	SC100.	SC93021702	NA

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in HwaYa Chamber 1.

3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.

4. The IC Site Registration No. is IC4924-2.

4.2.3 TEST PROCEDURES

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection (PK) at frequency above 1GHz.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation

4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6

4.2.7 TEST RESULTS

MODE A: WITH EXTENDED USB CABLE

EUT	VoIP-Easy Pocket Gateway	**MEASUREMENT DETAIL**	
MODEL	VIEZ300	**FREQUENCY RANGE**	Below 1000MHz
CHANNEL	Channel 78	**DETECTOR FUNCTION**	Quasi-Peak
MODULATION TYPE	GFSK	**ENVIRONMENTAL CONDITIONS**	26deg. C, 65%RH, 991hPa
TEST MODE	A	**INPUT POWER (SYSTEM)**	120Vac, 60 Hz
TESTED BY	Match Tsui		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	78.60	33.83 QP	40.00	-6.17	1.50 H	277	23.72	10.11
2	117.47	30.35 QP	43.50	-13.15	1.25 H	289	17.81	12.54
3	160.24	38.34 QP	43.50	-5.16	1.50 H	286	23.71	14.63
4	348.80	33.28 QP	46.00	-12.72	1.00 H	226	17.84	15.43
5	399.34	34.05 QP	46.00	-11.95	1.25 H	37	17.42	16.62
6	700.64	30.51 QP	46.00	-15.49	1.00 H	259	8.25	22.26

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	39.72	24.43 QP	40.00	-15.57	1.25 V	151	9.51	14.92
2	70.82	31.75 QP	40.00	-8.25	1.00 V	259	19.62	12.12
3	162.18	27.97 QP	43.50	-15.53	2.00 V	13	13.52	14.45
4	300.20	28.72 QP	46.00	-17.28	1.75 V	130	14.38	14.33
5	391.56	28.86 QP	46.00	-17.14	1.00 V	220	12.42	16.44
6	597.62	28.39 QP	46.00	-17.61	1.00 V	208	7.56	20.83

REMARKS:
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

MODE B: WITHOUT EXTENDED USB CABLE

EUT	VoIP-Easy Pocket Gateway	**MEASUREMENT DETAIL**	
MODEL	VIEZ300	**FREQUENCY RANGE**	Below 1000MHz
CHANNEL	Channel 78	**DETECTOR FUNCTION**	Quasi-Peak
MODULATION TYPE	GFSK	**ENVIRONMENTAL CONDITIONS**	26deg. C, 65%RH, 991hPa
TEST MODE	B	**INPUT POWER (SYSTEM)**	120Vac, 60 Hz
TESTED BY	Match Tsui		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	76.65	33.56 QP	40.00	-6.44	1.75 H	271	22.94	10.62
2	121.36	29.62 QP	43.50	-13.88	1.25 H	100	16.73	12.90
3	162.18	37.09 QP	43.50	-6.41	1.75 H	115	22.64	14.45
4	197.17	27.11 QP	43.50	-16.39	1.50 H	55	15.76	11.35
5	401.28	29.32 QP	46.00	-16.68	1.00 H	232	12.65	16.67
6	731.74	30.36 QP	46.00	-15.64	1.00 H	250	7.37	22.99

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	35.83	23.56 QP	40.00	-16.44	1.00 V	46	9.25	14.32
2	70.82	32.36 QP	40.00	-7.64	1.00 V	232	20.23	12.12
3	158.30	27.68 QP	43.50	-15.82	1.75 V	37	13.06	14.62
4	362.40	28.15 QP	46.00	-17.85	1.00 V	232	12.39	15.75
5	393.51	30.39 QP	46.00	-15.61	1.00 V	118	13.91	16.48
6	906.69	30.76 QP	46.00	-15.24	1.50 V	358	5.59	25.17

REMARKS:
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

EUT	VoIP-Easy Pocket Gateway	MEASUREMENT DETAIL	
MODEL	VIEZ300	FREQUENCY RANGE	1 ~ 25GHz
CHANNEL	Channel 0	DETECTOR FUNCTION	Peak (PK) Average (AV)
MODULATION TYPE	GFSK	INPUT POWER (SYSTEM)	120Vac, 60 Hz
ENVIRONMENTAL CONDITIONS	26deg. C, 65%RH, 991hPa	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	57.03 PK	74.00	-16.97	1.04 H	326	24.99	32.04
1	2390.00	47.03 AV	54.00	-6.97	1.04 H	326	14.99	32.04
2	*2402.00	107.93 PK			1.04 H	326	75.84	32.09
2	*2402.00	77.93 AV			1.04 H	326	45.84	32.09
3	4804.00	51.57 PK	74.00	-22.43	1.20 H	352	13.42	38.15
3	4804.00	21.57 AV	54.00	-32.43	1.20 H	352	-16.58	38.15

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	52.30 PK	74.00	-21.70	1.16 V	178	20.26	32.04
1	2390.00	42.30 AV	54.00	-11.70	1.16 V	178	10.26	32.04
2	*2402.00	103.20 PK			1.16 V	178	71.11	32.09
2	*2402.00	73.20 AV			1.16 V	178	41.11	32.09
3	4804.00	52.15 PK	74.00	-21.85	1.24 V	242	14.00	38.15
3	4804.00	22.15 AV	54.00	-31.85	1.24 V	242	-16.00	38.15

REMARKS:
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle be equal to: 20log(3.125/100)= -30 dB.
6. Average value = peak reading –20log(duty cycle).

EUT	VoIP-Easy Pocket Gateway	**MEASUREMENT DETAIL**	
MODEL	VIEZ300	**FREQUENCY RANGE**	1 ~ 25GHz
CHANNEL	Channel 39	**DETECTOR FUNCTION**	Peak (PK) Average (AV)
MODULATION TYPE	GFSK	**INPUT POWER (SYSTEM)**	120Vac, 60 Hz
ENVIRONMENTAL CONDITIONS	26deg. C, 65%RH, 991hPa	**TESTED BY**	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2441.00	107.87 PK			1.35 H	6	75.61	32.26
1	*2441.00	77.87 AV			1.35 H	6	45.61	32.26
2	4882.00	52.12 PK	74.00	-21.88	1.18 H	360	13.78	38.34
2	4882.00	22.12 AV	54.00	-31.88	1.18 H	360	-16.22	38.34

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2441.00	103.38 PK			1.18 V	184	71.12	32.26
1	*2441.00	73.38 AV			1.18 V	184	41.12	32.26
2	4882.00	51.68 PK	74.00	-22.32	1.24 V	214	13.34	38.34
2	4882.00	21.68 AV	54.00	-32.32	1.24 V	214	-16.66	38.34

REMARKS:
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle be equal to: 20log(3.125/100)= -30 dB.
6. Average value = peak reading –20log(duty cycle).

EUT	VoIP-Easy Pocket Gateway	**MEASUREMENT DETAIL**	
MODEL	VIEZ300	**FREQUENCY RANGE**	1 ~ 25GHz
CHANNEL	Channel 78	**DETECTOR FUNCTION**	Peak (PK) Average (AV)
MODULATION TYPE	GFSK	**INPUT POWER (SYSTEM)**	120Vac, 60 Hz
ENVIRONMENTAL CONDITIONS	26deg. C, 65%RH, 991hPa	**TESTED BY**	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	108.04 PK			1.31 H	332	75.60	32.44
1	*2480.00	78.04 AV			1.31 H	332	45.60	32.44
2	2483.50	60.18 PK	74.00	-13.82	1.18 H	184	27.72	32.46
2	**2483.50**	**50.18 AV**	**54.00**	**-3.82**	**1.18 H**	**184**	**17.72**	**32.46**
3	4960.00	52.14 PK	74.00	-21.86	1.20 H	360	13.57	38.57
3	4960.00	22.14 AV	54.00	-31.86	1.20 H	360	-16.43	38.57

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	103.57 PK			1.17 V	181	71.13	32.44
1	*2480.00	73.57 AV			1.17 V	181	41.13	32.44
2	2483.50	55.71 PK	74.00	-18.29	1.17 V	181	23.25	32.46
2	2483.50	45.71 AV	54.00	-8.29	1.17 V	181	13.25	32.46
3	4960.00	52.47 PK	74.00	-21.53	1.21 V	300	13.90	38.57
3	4960.00	22.54 AV	54.00	-31.46	1.21 V	300	-16.03	38.57

REMARKS:
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle be equal to: 20log(3.125/100)= -30 dB.
6. Average value = peak reading –20log(duty cycle).

4.3 NUMBER OF HOPPING FREQUENCY USED

4.3.1 LIMIT OF HOPPING FREQUENCY USED

At least 15 channels frequencies, and should be equally spaced.

4.3.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSEK30	100049	Aug. 14, 2006

NOTE: The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.

4.3.3 TEST PROCEDURES

a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.

c. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.

d. Set the SA on View mode and then plot the result on SA screen.

e. Repeat above procedures until all frequencies measured were complete.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation.

4.3.5 TEST SETUP



4.3.6 TEST RESULTS

There are 79 hopping frequencies in the hopping mode. Please refer to next two pages for the test result. On the plots, it shows that the hopping frequencies are equally spaced.


*RBW 100 kHz
*VBW 300 kHz
SWT 5 ms
Marker 1 [T1]
11.48 dBm
2.402000000 GHz
Ref 20 dBm
*Att 30 dB
Marker 2 [T1]
11.60 dBm
1 PK
VIEW
EXT
Center 2.42133 GHz
4.2 MHz/
Span 42 MHz


*RBW 100 kHz
*VBW 300 kHz
SWT 5 ms
Marker 1 [T1]
10.86 dBm
2.443000000 GHz
Ref 20 dBm
*Att 30 dB
Marker 2 [T1]
10.54 dBm
1 PK
VIEW
EXT
Center 2.4634 GHz
4.2 MHz/
Span 42 MHz

4.4 DWELL TIME ON EACH CHANNEL

4.4.1 LIMIT OF DWELL TIME USED

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

4.4.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSEK30	100049	Aug. 14, 2006

NOTES: The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.

4.4.3 TEST PROCEDURES

a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.

c. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.

d. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.

e. Repeat above procedures until all different time-slot modes have been completed.

4.4.4 DEVIATION FROM TEST STANDARD

No deviation.

4.4.5 TEST SETUP

4.4.6 TEST RESULTS

MODE	NUMBER OF TRANSMISSION IN A 31.6 (79HOPPING * 0.4)	LENGTH OF TRANSMISSION TIME (msec)	RESULT (msec)	LIMIT (msec)
DH1	50 (times / 5 sec) * 6.32 = 316.00 times	0.438	138.41	400
DH3	28 (times / 5 sec) * 6.32 = 176.96 times	1.710	302.60	400
DH5	19 (times / 5 sec) * 6.32 = 120.08 times	2.970	356.64	400

NOTE: Test plots of the transmitting time slot are shown on next 3 pages.

DH1


RBW 100 kHz
*VBW 100 kHz
SWT 5 s
Ref 20 dBm
*Att 30 dB
1 PK *
CLRWR
A
SGL
20
10
0
-10
-20
-30
-40
-50
-60
-70
-80
Center 2.402 GHz
500 ms/


RBW 100 kHz
*VBW 100 kHz
SWT 3 ms
Delta 2 [T1]
5.06 dB
438.000000 µs
Ref 20 dBm
*Att 30 dB
Marker 1 [T1]
-62.51 dBm
990.000000 µs
1 AP
VIEW
A
20
10
0
-10
-20
-30
-40
-50
-60
-70
-80
Center 2.402 GHz
300 µs/

DH3


RBW 100 kHz
*VBW 100 kHz
SWT 5 s
Ref 20 dBm
*Att 30 dB
1 PK
CLRWR
A
SGL
20
10
0
-10
-20
-30
-40
-50
-60
-70
-80
Center 2.402 GHz
500 ms/


RBW 100 kHz
*VBW 100 kHz
SWT 3 ms
Delta 2 [T1]
-2.85 dB
1.710000 ms
Ref 20 dBm
*Att 30 dB
Marker 1 [T1]
-58.75 dBm
1 PK
VIEW
A
20
10
0
-10
-20
-30
-40
-50
-60
-70
-80
Center 2.402 GHz
300 µs/

DH5


RBW 100 kHz
*VBW 100 kHz
SWT 5 s
Ref 20 dBm
*Att 30 dB
1 PK *
CLRWR
A
SGL
20
10
0
-10
-20
-30
-40
-50
-60
-70
-80
Center 2.402 GHz
500 ms/


RBW 100 kHz
*VBW 100 kHz
SWT 5 ms
Delta 2 [T1]
-1.13 dB
2.970000 ms
Ref 20 dBm
*Att 30 dB
Marker 1 [T1]
-58.12 dBm
980.000000 µs
1 PK *
VIEW
A
20
10
0
-10
-20
-30
-40
-50
-60
-70
-80
Center 2.402 GHz
500 µs/

4.5 CHANNEL BANDWIDTH

4.5.1 LIMITS OF CHANNEL BANDWIDTH

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dBbandwidth of hopping channel shell be a minimum limit for the hopping channel separation.

4.5.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSEK30	100049	Aug. 14, 2006

NOTE: The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.

4.5.3 TEST PROCEDURE

a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.

c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.

d. Repeat above procedures until all frequencies measured were complete.

4.5.4 DEVIATION FROM TEST STANDARD

No deviation.

4.5.5 TEST SETUP

4.5.6 EUT OPERATING CONDITION

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.5.7 TEST RESULTS

EUT	VoIP-Easy Pocket Gateway	**MODEL**	VIEZ300
MODULATION TYPE	GFSK	**ENVIRONMENTAL CONDITIONS**	27deg. C, 65%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**TESTED BY**	Long Chen

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	1.065
39	2441	1.050
78	2480	1.050

CH 0


*RBW 30 kHz
*VBW 300 kHz
SWT 2.5 ms
Marker 1 [T1]
9.14 dBm
2.402036000 GHz
Ref 20 dBm
*Att 30 dB
ndB [T1] 20.00 dB
BW 1.065000000 MHz
Temp 1 [T1 ndB]
-10.64 dBm
2.401439000 GHz
Temp 2 [T1 ndB]
-10.95 dBm
2.402504000 GHz
1 PK
VIEW
A
EXT
Center 2.402 GHz
150 kHz/
Span 1.5 MHz

CH 39


*RBW 30 kHz
*VBW 300 kHz
SWT 2.5 ms
Marker 1 [T1]
8.14 dBm
2.440973000 GHz
Ref 20 dBm
*Att 30 dB
ndB [T1] 20.00 dB
BW 1.050000000 MHz
Temp 1 [T1 ndB]
-11.90 dBm
2.440439000 GHz
Temp 2 [T1 ndB]
-11.80 dBm
2.441489000 GHz
1 PK
VIEW
A
EXT
Center 2.441 GHz
150 kHz/
Span 1.5 MHz

CH 78


*RBW 30 kHz
*VBW 300 kHz
SWT 2.5 ms
Marker 1 [T1]
9.49 dBm
2.480042000 GHz
Ref 20 dBm
*Att 30 dB
ndB [T1] 20.00 dB
BW 1.050000000 MHz
Temp 1 [T1 ndB]
-10.65 dBm
2.479442000 GHz
Temp 2 [T1 ndB]
-10.49 dBm
2.480492000 GHz
1 PK
VIEW
A
EXT
T1
T2
Center 2.48 GHz
150 kHz/
Span 1.5 MHz

4.6 HOPPING CHANNEL SEPARATION

4.6.1 LIMIT OF HOPPING CHANNEL SEPARATION

At least 25kHz or two-third of 20dB hopping channel bandwidth (whichever is greater).

4.6.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSEK30	100049	Aug. 14, 2006

NOTES: The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.

4.6.3 TEST PROCEDURES

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
3. By using the MaxHold function record the separation of two adjacent channels.
4. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.

4.6.4 DEVIATION FROM TEST STANDARD

No deviation.

4.6.5 TEST SETUP

4.6.6 TEST RESULTS

EUT	VoIP-Easy Pocket Gateway	**MODEL**	VIEZ300
MODULATION TYPE	GFSK	**ENVIRONMENTAL CONDITIONS**	27deg. C, 65%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**TESTED BY**	Long Chen

CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)	20dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	1.000	1.065	0.710	PASS
39	2441	1.015	1.050	0.700	PASS
78	2480	1.005	1.050	0.700	PASS

NOTE: The minimum limit is two-third 20dB bandwidth. Test results please refer to next two pages.

CH 0


*RBW 100 kHz
*VBW 100 kHz
SWT 2.5 ms
Delta 2 [T1]
-0.07 dB
1.000000000 MHz
Ref 20 dBm
*Att 30 dB
Marker 1 [T1]
12.02 dBm
2.401810000 GHz
1 PK
VIEW
EXT
Center 2.40255 GHz
250 kHz/
Span 2.5 MHz

CH 39


*RBW 100 kHz
*VBW 100 kHz
SWT 2.5 ms
Delta 2 [T1]
0.00 dB
1.015000000 MHz
Ref 20 dBm
*Att 30 dB
Marker 1 [T1]
10.56 dBm
2.440805000 GHz
1 PK
VIEW
EXT
Center 2.441425 GHz
250 kHz/
Span 2.5 MHz

CH 78


*RBW 100 kHz
*VBW 100 kHz
SWT 2.5 ms
Delta 2 [T1]
-0.03 dB
1.005000000 MHz
Ref 20 dBm
*Att 30 dB
Marker 1 [T1]
9.85 dBm
2.478815000 GHz
1 PK
VIEW
A
EXT
20
10
0
-10
-20
-30
-40
-50
-60
-70
-80
Center 2.479425 GHz
250 kHz/
Span 2.5 MHz

4.7 MAXIMUM PEAK OUTPUT POWER

4.7.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 125mW.

4.7.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
SPECTRUM ANALYEER	FSEK30	100049	Aug. 14, 2006

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.7.3 TEST PROCEDURES

a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.

c. The center frequency of the spectrum analyzer is set to the fundamental frequency and using 3 MHz RBW and 3 MHz VBW.

d. Measure the captured power within the band and recording the plot.

e. Repeat above procedures until all frequencies required were complete.

4.7.4 DEVIATION FROM TEST STANDARD

No deviation

4.7.5 TEST SETUP

For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.

4.7.6 EUT OPERATING CONDITION

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.7.7 TEST RESULTS

EUT	VoIP-Easy Pocket Gateway	**MODEL**	VIEZ300
MODULATION TYPE	GFSK	**ENVIRONMENTAL CONDITIONS**	27deg. C, 65%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**TESTED BY**	Long Chen

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (mW)	PASS/FAIL
0	2402	18.621	12.70	125	PASS
39	2441	13.366	11.26	125	PASS
78	2480	18.281	12.62	125	PASS

CH 0


*RBW 3 MHz
*VBW 3 MHz
SWT 2.5 ms
Marker 1 [T1]
12.70 dBm
2.401920000 GHz
Ref 20 dBm
*Att 30 dB
1 PK
MAXH
A
EXT
20
10
0
-10
-20
-30
-40
-50
-60
-70
-80
Center 2.402 GHz
4 MHz/
Span 40 MHz

CH 39


*RBW 3 MHz
*VBW 3 MHz
SWT 2.5 ms
Marker 1 [T1]
11.26 dBm
2.441160000 GHz
Ref 20 dBm
*Att 30 dB
1 PK
VIEW
A
EXT
20
10
0
-10
-20
-30
-40
-50
-60
-70
-80
Center 2.441 GHz
4 MHz/
Span 40 MHz

CH 78


*RBW 3 MHz
*VBW 3 MHz
SWT 2.5 ms
Marker 1 [T1]
12.62 dBm
2.479840000 GHz
Ref 20 dBm
*Att 30 dB
1 PK
VIEW
EXT
Center 2.48 GHz
4 MHz/
Span 40 MHz

4.8 BAND EDGES MEASUREMENT

4.8.1 LIMITS OF BAND EDGES MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100KHz RBW).

4.8.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSEK30	100049	Aug. 14, 2006

NOTES: The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.

4.8.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100 kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

4.8.4 DEVIATION FROM TEST STANDARD

No deviation.

4.8.5 EUT OPERATING CONDITION

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.8.6 TEST RESULTS

The spectrum plots are attached on the following 4 images. D1 line indicates the highest level, D2 line indicates the 20dB offset below D1. It shows compliance with the requirement in part 15.247(d).

NOTE 1:

The band edge emission plot on page 60 shows 55.05dBc between carrier maximum power and local maximum emission in restrict band (2.3782GHz). The emission of carrier strength list in the test result of channel 0 at the item 4.2.7 is 107.93dBuV/m (Peak), so the maximum field strength in restrict band is 107.93 – 55.05 = 52.88dBuV/m, which is under 74 dBuV/m limit.

The band edge emission plot on page 60 shows 55.05dBc between carrier maximum power and local maximum emission in restrict band (2.3782GHz). The emission of carrier strength list in the test result of channel 0 at the item 4.2.7 is 77.93dBuV/m (Average), so the maximum field strength in restrict band is 77.93 – 55.05 = 22.88dBuV/m, which is under 54 dBuV/m limit.

NOTE 2:

The band edge emission plot on page 61 shows 52.99dBc between carrier maximum power and local maximum emission in restrict band (2.4841GHz). The emission of carrier strength list in the test result of channel 78 at the item 4.2.7 is 108.04dBuV/m (Peak), so the maximum field strength in restrict band is 108.04 – 52.99 = 55.05dBuV/m, which is under 74 dBuV/m limit.

The band edge emission plot on page 61 shows 52.99dBc between carrier maximum power and local maximum emission in restrict band (2.4841GHz). The emission of carrier strength list in the test result of channel 78 at the item 4.2.7 is 78.04dBuV/m (Average), so the maximum field strength in restrict band is 78.04 – 52.99 = 25.05dBuV/m, which is under 54 dBuV/m limit.


*RBW 100 kHz
*VBW 100 kHz
SWT 10 ms
Marker 1 [T1]
12.38 dBm
2.402200000 GHz
Ref 20 dBm
*Att 30 dB
Marker 2 [T1]
-38.42 dBm
2.399000000 GHz
Marker 3 [T1]
-50.18 dBm
2.390000000 GHz
Marker 4 [T1]
-42.67 dBm
2.378200000 GHz
D1 12.38 dBm
D2 -7.62 dBm
1 PK
VIEW
EXT
F1
F2
Center 2.3546 GHz
10 MHz/
Span 100 MHz


*RBW 100 kHz
*VBW 100 kHz
SWT 2.5 s
Marker 1 [T1]
9.35 dBm
2.377180000 GHz
Ref 20 dBm
*Att 30 dB
Marker 2 [T1]
-43.75 dBm
22.053540000 GHz
D1 12.38 dBm
D2 -7.62 dBm
1 PK
VIEW
EXT
Start 30 MHz
2.497 GHz/
Stop 25 GHz


*RBW 100 kHz
*VBW 100 kHz
SWT 10 ms
Marker 1 [T1]
11.67 dBm
2.479840000 GHz
Ref 20 dBm
*Att 30 dB
Marker 2 [T1]
-43.23 dBm
2.483500000 GHz
Marker 3 [T1]
-41.32 dBm
2.484100000 GHz
Marker 4 [T1]
-47.91 dBm
2.500000000 GHz
D1 11.67 dBm
D2 -9.33 dBm
1 PK
VIEW
EXT
F1
F2
Center 2.5278 GHz
10 MHz/
Span 100 MHz


*RBW 100 kHz
*VBW 100 kHz
SWT 2.5 s
Marker 1 [T1]
10.84 dBm
2.477060000 GHz
Ref 20 dBm
*Att 30 dB
Marker 2 [T1]
-43.20 dBm
22.153420000 GHz
D1 11.67 dBm
D2 -9.33 dBm
1 PK
VIEW
EXT
Start 30 MHz
2.497 GHz/
Stop 25 GHz

4.9 ANTENNA REQUIREMENT

4.9.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

4.9.2 ANTENNA CONNECTED CONSTRUCTION

The antenna used in this product is Chip antenna without antenna connector. The maximum gain of this antenna is 0dBi.

5. PHOTOGRAPHS OF THE TEST CONFIGURATION

CONDUCTED EMISSION TEST

TEST MODE A



TEST MODE B

RADIATED EMISSION TEST

TEST MODE A





TEST MODE B





6. INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

USA	FCC, NVLAP, UL, A2LA
Germany	TUV Rheinland
Japan	VCCI
Norway	NEMKO
Canada	INDUSTRY CANADA , CSA
R.O.C.	CNLA, BSMI, DGT
Netherlands	Telefication
Singapore	PSB , GOST-ASIA(MOU)
Russia	CERTIS(MOU)

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site: www.adt.com.tw/index.5/phtml. If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:
Tel: 886-2-26052180
Fax: 886-2-26052943

Hsin Chu EMC/RF Lab:
Tel: 886-3-5935343
Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety Telecom Lab:
Tel: 886-3-3183232
Fax: 886-3-3185050

Linko RF Lab.
Tel: 886-3-3270910
Fax: 886-3-3270892

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.

APPENDIX-A

MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.