MPE TEST REPORT

of

FCC CFR 47 part 1, 1.1307(b), 1.1310

FCC ID : TQ8-AC115TAGG

Equipment Under Test	:	DIGITAL CAR AUDIO SYSTEM
Model Name	:	AC115TAGG
Alternative Model Name	:	AC105TAGE, AC115TAGE, AC105TAGG, AC105TAGN, AC115TAGN, AC105TAGL, AC115TAGL
Applicant	:	Hyundai MOBIS Co., Ltd.
Manufacturer	:	Hyundai MOBIS Co., Ltd.
Date of Test(s)	:	2014.08.01 ~ 2014.08.05
Date of Issue	:	2014.08.06

In the configuration tested, the EUT complied with the standards specified above.

Tested By: **Wonjun Sim** **Date:** **2014.08.06**

Approved By: **Hyunchae You** **Date:** **2014.08.06**

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

INDEX

Table of Contents Page

1. General Information ---------- 3

2. RF Exposure Evaluation ---------- 4

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

1. General Information

1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)
-Wireless Div. 2FL, 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 435-837
All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.
Telephone : +82 31 688 0901
FAX : +82 31 688 0921

1.2. Details of Applicant

Applicant : Hyundai MOBIS Co., Ltd.
Address : 203, Teheran-ro, Gangnam-gu, Seoul, 135-977, Korea
Contact Person : Choi, Seung-Hun
Phone No. : +82 31 260 0098

1.3. Description of EUT

Kind of Product	DIGITAL CAR AUDIO SYSTEM
Model Name	AC115TAGG
Alternative Model Name	AC105TAGE,AC115TAGE,AC105TAGG,AC105TAGN,AC115TAGN, AC105TAGL,AC115TAGL
Power Supply	DC 14.4 V (Vehicle Battery)
Frequency Range	2 402 ㎒ ~ 2 480 ㎒
Modulation Technique	GFSK, π/4DQPSK, 8DPSK
Number of Channels	79 channel
Antenna Type	Internal type
Antenna Gain	3.5 ㏈i

1.4. Test report revision

Revision	Report number	Date of Issue	Description
0	F690501/RF-RTL007889	2014.08.06	Initial

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

2. RF Exposure Evaluation

2.1. Environmental evaluation and exposure limit according to FCC CFR 47 part 1, 1.1307(b), 1.1310

According to FCC 1.1310 : The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in §1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (㎒)	Electric Field Strength(V/m)	Magnetic Field Strength (A/m)	Power Density (㎽/㎠)	Average Time
(A) Limits for Occupational /Control Exposures				
300 – 1 500	--	--	F/300	6
1 500 – 100 000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300 – 1 500	--	--	F/1500	30
1 500 – 100 000	**--**	**--**	**1**	**30**

2.1.1. Friis transmission formula: Pd = (Pout*G)/(4*pi*R^2)

Where Pd = power density in ㎽/㎠

Pout = output power to antenna in ㎽

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in ㎝

Pd the limit of MPE, 1 ㎽/㎠. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

2.1.2. Test Result of RF Exposure Evaluation

Test Item : RF Exposure Evaluation Data
Test Mode : Normal Operation

2.1.3. Output Power into Antenna & RF Exposure Evaluation Distance

GFSK

Channel	Output Average Power to Antenna (dBm)	Antenna Gain (dBi)	Power Density at 20 ㎝ (㎽/㎠)	LIMITS (㎽/㎠)
Maximum tune up tolerance	4.00	3.5	0.001 119	1

Note :
1. The power density Pd (5th column) at a distance of 20 ㎝ calculated from the friis transmission formula is far below the limit of 1 ㎽/㎠.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.