



# TEST REPORT

## KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR17-SRF0069

Page (1) of (72)

# KCTL

### 1. Client

- Name : HYUNDAI MOBIS CO., LTD.
- Address : 203, Teheran-ro, Gangnam-gu, Seoul, South Korea, 135-977
- Date of Receipt : 2017-05-18

### 2. Use of Report : -

### 3. Name of Product and Model : DISPLAY CAR SYSTEM / ADCB0J3AN

### 4. Manufacturer and Country of Origin : Hyundai MOBIS Co., Ltd. / Korea

### 5. FCC ID : TQ8-ADCB0J3AN

### 6. Date of Test : 2017-06-26 to 2017-06-30

### 7. Test Standards : FCC Part 15 Subpart C 15.247

### 8. Test Results : Refer to the test result in the test report

|             |                                                                                                                        |                                                                                                                         |
|-------------|------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| Affirmation | Tested by                                                                                                              | Technical Manager                                                                                                       |
|             | <br>Name : Jaehyong Lee (Signature) | <br>Name : Changmin Kim (Signature) |

2017-07-07

## KCTL Inc.

As a test result of the sample which was submitted from the client, this report does not guarantee the whole product quality. This test report should not be used and copied without a written agreement by KCTL Inc.

## REPORT REVISION HISTORY

| Date       | Revision          | Page No |
|------------|-------------------|---------|
| 2017-07-07 | Originally issued | -       |
|            |                   |         |
|            |                   |         |
|            |                   |         |
|            |                   |         |
|            |                   |         |
|            |                   |         |
|            |                   |         |
|            |                   |         |
|            |                   |         |
|            |                   |         |

*This report shall not be reproduced except in full, without the written approval of KCTL Inc. This document may be altered or revised by KCTL Inc. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KCTL Inc. will constitute fraud and shall nullify the document.*

**KCTL**

## [ Contents ]

|                                                             |           |
|-------------------------------------------------------------|-----------|
| <b>1. Client information .....</b>                          | <b>4</b>  |
| <b>2. Laboratory information .....</b>                      | <b>5</b>  |
| <b>3. Description of E.U.T.....</b>                         | <b>6</b>  |
| 3.1 Basic description .....                                 | 6         |
| 3.2 General description .....                               | 6         |
| 3.3 Test frequency .....                                    | 7         |
| 3.4 Test Voltage .....                                      | 7         |
| <b>4. Summary of test results.....</b>                      | <b>8</b>  |
| 4.1 Standards & results .....                               | 8         |
| 4.2 Uncertainty .....                                       | 8         |
| <b>5. Test results .....</b>                                | <b>9</b>  |
| 5.1 Antenna Requirement .....                               | 9         |
| 5.2 Maximum Peak Output Power .....                         | 10        |
| 5.3 Carrier Frequency Separation .....                      | 13        |
| 5.4 20 dB Channel Bandwidth.....                            | 20        |
| 5.5 Number of Hopping Channels .....                        | 33        |
| 5.6 Time of Occupancy(Dwell Time) .....                     | 38        |
| 5.7 Spurious Emission, Band edge and Restricted bands ..... | 50        |
| <b>6. Test equipment used for test.....</b>                 | <b>72</b> |

|                                                                                                                                                                                           |                                                  |                                                                                     |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------|-------------------------------------------------------------------------------------|
| <b>KCTL Inc.</b><br>65, Sinwon-ro, Yeongtong-gu,<br>Suwon-si, Gyeonggi-do, 16677, Korea<br>TEL: 82-31-285-0894 FAX: 82-505-299-8311<br><a href="http://www.kctl.co.kr">www.kctl.co.kr</a> | Report No.:<br>KR17- SRF0069<br>Page (4) of (72) |  |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------|-------------------------------------------------------------------------------------|

## 1. Client information

**Applicant:** HYUNDAI MOBIS CO., LTD.  
**Address:** 203, Teheran-ro, Gangnam-gu, Seoul, South Korea, 135-977  
**Telephone number:** 82 31 260 0098  
**Facsimile number:** 82 31 899 1788  
**Contact person:** Seunghoon Choi / csh@mobis.co.kr

**Manufacturer:** Hyundai Mobis Co., Ltd.  
**Address:** 95, Sayang 2-Gil, Munbaek-Myeon, Jincheon-Gun,  
 Chungcheongbuk-Do 365-862 Korea



## KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR17- SRF0069

Page (5) of (72)

# KCTL

## 2. Laboratory information

### Address

#### **KCTL Inc.**

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea

Telephone Number: 82 31 285 0894

Facsimile Number: 82 505 299 8311

FCC Site Designation No: KR0040, FCC Site Registration No: 687132

VCCI Registration No. : R-3327, G-198, C-3706, T-1849

Industry Canada Registration No. : 8035A

KOLAS NO.: KT231

### **SITE MAP**



This test report shall not be reproduced, except in full, without the written approval

KCTL-TIR001-003/2

### 3. Description of E.U.T.

#### 3.1 Basic description

|                         |                                                                                |
|-------------------------|--------------------------------------------------------------------------------|
| Applicant               | HYUNDAI MOBIS CO., LTD.                                                        |
| Address of Applicant    | 203, Teheran-ro, Gangnam-gu, Seoul, South Korea, 135-977                       |
| Manufacturer            | Hyundai MOBIS Co., Ltd.                                                        |
| Address of Manufacturer | 95, Sayang 2-Gil, Munbaek-Myeon, Jincheon-Gun, Chungcheongbuk-Do 365-862 Korea |
| Type of equipment       | DISPLAY CAR SYSTEM                                                             |
| Basic Model             | ADCB0J3AN                                                                      |
| Serial number           | N/A                                                                            |

#### 3.2 General description

|                                      |                                                                                                                                                                                            |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Frequency Range                      | 2 402 MHz ~ 2 480 MHz (Bluetooth)<br>776 MHz ~ 787 MHz (LTE Band 13)<br>1 710 MHz ~ 1 755 MHz (LTE Band 4)<br>824.7 MHz ~ 848.31 MHz (CDMA 850)<br>1 851.25 MHz ~ 1 908.75 MHz (CDMA 1900) |
| Type of Modulation                   | GFSK, $\pi/4$ DQPSK, 8DPSK (Bluetooth),<br>QPSK, 16QAM (LTE Band 13, LTE Band 4)<br>1xRTT (CDMA 850, CDMA 1900)                                                                            |
| The number of channels               | 79 channel (Bluetooth)                                                                                                                                                                     |
| Type of Antenna                      | Chip Antenna (Bluetooth), External Antenna (LTE/CDMA)                                                                                                                                      |
| Antenna Gain                         | -0.1 dBi (2 400 MHz ~ 2 483.5 MHz)                                                                                                                                                         |
| Transmit Power                       | 4.45 dBm (Bluetooth)                                                                                                                                                                       |
| Conducted Output Power <sup>2)</sup> | 23.70 dBm (LTE Band 13), 23.26 dBm (LTE Band 4)<br>23.78 dBm (CDMA 850, CDMA 1900)                                                                                                         |
| Power supply                         | DC 14.40 V                                                                                                                                                                                 |
| Product SW/HW version                | JS.USA.0000.V084.170317 / JS.USA.0000.V084.170317                                                                                                                                          |
| Radio SW/HW version                  | 01 / 01                                                                                                                                                                                    |
| Test SW Version                      | Bluetooth Tester V1.6 (Bluetooth)<br>CMW50050-141780 (LTE/CDMA)                                                                                                                            |
| RF power setting in TEST SW          | Referred the measuring instrument from manufacturer                                                                                                                                        |

Note<sub>1)</sub> : The above EUT information was declared by the manufacturer.

Note<sub>2)</sub> : Test was performed by modular transmitter (Model Name: CASAN, FCC:LHJ-CASAN,  
Test Report no.3562408EMC02 Rev: 1 issued on 03, October, 2014 by SGS North America Inc.)

### 3.3 Test frequency

|                   | Frequency |
|-------------------|-----------|
| Lowest frequency  | 2 402 MHz |
| Middle frequency  | 2 441 MHz |
| Highest frequency | 2 480 MHz |

### 3.4 Test Voltage

| Mode            | Voltage    |
|-----------------|------------|
| Nominal Voltage | DC 14.40 V |

#### - 15.247 Requirements for Bluetooth transmitter

- This Bluetooth module has been tested by a Bluetooth Qualification Lab, and we confirm the following:
  - 1) This system is hopping pseudo-randomly.
  - 2) Each frequency is used equally on the average by each transmitter.
  - 3) The receiver input bandwidths that match the hopping channel bandwidths of their corresponding transmitters
  - 4) The receiver shifts frequencies in synchronization with the transmitted signals.
- 15.247(g): The system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this Section 15.247 should the transmitter be presented with a continuous data (or information) stream.
- 15.247(h): The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

## 4. Summary of test results

### 4.1 Standards & results

| FCC Rule                                                                                                                                                                                                                                                         | IC Rule                          | Parameter                                       | Report Section | Test Result                 |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------|-------------------------------------------------|----------------|-----------------------------|
| 15.203,<br>15.247(b)(4)                                                                                                                                                                                                                                          | -                                | Antenna Requirement                             | 5.1            | C                           |
| 15.247(b)(1), (4)                                                                                                                                                                                                                                                | RSS-247, 5.4 (2)                 | Maximum Peak Output Power                       | 5.2            | C                           |
| 15.247(a)(1)                                                                                                                                                                                                                                                     | RSS-247, 5.1 (2)                 | Carrier Frequency Separation                    | 5.3            | C                           |
| 15.247(a)(1)                                                                                                                                                                                                                                                     | RSS-247, 5.1 (1)                 | 20dB Channel Bandwidth                          | 5.4            | C                           |
| -                                                                                                                                                                                                                                                                | RSS-GEN, 6.6                     | Occupied Bandwidth                              | 5.4            | C                           |
| 15.247(a)(iii)<br>15.247(b)(1)                                                                                                                                                                                                                                   | RSS-247, 5.1                     | Number of Hopping Channel                       | 5.5            | C                           |
| 15.247(a)(iii)                                                                                                                                                                                                                                                   | RSS-247, 5.1 (4)                 | Time of Occupancy(Dwell Time)                   | 5.6            | C                           |
| 15.247(d),<br>15.205(a),<br>15.209(a)                                                                                                                                                                                                                            | RSS-247, 5.5<br>RSS-GEN, 8.9, 10 | Spurious Emission, BandEdge,<br>Restricted Band | 5.7            | C                           |
| 15.207(a)                                                                                                                                                                                                                                                        | RSS-GEN, 8.8                     | Conducted Emissions                             | 5.8            | N/A<br>(Note <sub>2</sub> ) |
| Note <sub>1</sub> : C = complies, NC = Not complies, NT = Not tested, NA = Not Applicable<br>Note <sub>2</sub> : This test is not applicable because the EUT falls into the automotive device and it's not to be connected to the public utility(AC) power line. |                                  |                                                 |                |                             |

- The general test methods used to test on this device are ANSI C63.10-2013

### 4.2 Uncertainty

| Measurement Item             | Expanded Uncertainty<br>$U = kU_c (k = 2)$ |                    |
|------------------------------|--------------------------------------------|--------------------|
| Conducted RF power           | 1.44 dB                                    |                    |
| Conducted Spurious Emissions | 1.52 dB                                    |                    |
| Radiated Spurious Emissions  | 30 MHz ~ 300 MHz:                          | +4.94 dB, -5.06 dB |
|                              |                                            | +4.93 dB, -5.05 dB |
|                              | 300 MHz ~ 1 000 MHz:                       | +4.97 dB, -5.08 dB |
|                              |                                            | +4.84 dB, -4.96 dB |
| Conducted Emissions          | 1 GHz ~ 25 GHz:                            | +6.03 dB, -6.05 dB |
|                              | 9 kHz ~ 150 kHz:                           | 3.75 dB            |
|                              | 150 kHz ~ 30 MHz:                          | 3.36 dB            |

## 5. Test results

### 5.1 Antenna Requirement

#### 5.1.1 Regulation

According to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

And according to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### 5.1.2 Result

##### -Complied

The transmitter has permanently attached Chip Antenna (internal antenna) on board.

## 5.2 Maximum Peak Output Power

### 5.2.1 Regulation

According to §15.247(a)(1) Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2 400-2 483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

According to §15.247(b)(1), for frequency hopping systems operating in the 2 400-2 483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5 725-5 850 MHz band: 1 watt. For all other frequency hopping systems in the 2 400-2 483.5 MHz band: 0.125 watts.

According to §15.247(b)(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### 5.2.2 Measurement Procedure

The method of measurement used to test this FHSS device is ANSI C63.10-2013.

This is an RF-conducted test to evaluate maximum peak output power. Use a direct connection between the antenna port of the unlicensed wireless device and the spectrum analyzer, through suitable attenuation.

The hopping shall be disabled for this test:

**KCTL Inc.**

65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR17- SRF0069  
Page (11) of (72)



a) Use the following spectrum analyzer settings:

- 1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
- 2) RBW > 20 dB bandwidth of the emission being measured.
- 3) VBW  $\geq$  RBW.
- 4) Sweep: Auto.
- 5) Detector function: Peak.
- 6) Trace: Max hold.

b) Allow trace to stabilize.

c) Use the marker-to-peak function to set the marker to the peak of the emission.

d) The indicated level is the peak output power, after any corrections for external attenuators and cables.

e) A plot of the test results and setup description shall be included in the test report.

**NOTE:**

A peak responding power meter may be used, where the power meter and sensor system video bandwidth is greater than the occupied bandwidth of the unlicensed wireless device, rather than a spectrum analyzer.



### 5.2.3 Test Result

- Complied

- GFSK

| Channel | Frequency [MHz] | Result [dBm] | Limit [dBm] | Margin [dB] | Avarage Power [dBm] |
|---------|-----------------|--------------|-------------|-------------|---------------------|
| Lowest  | 2 402           | 3.45         | 20.97       | 17.52       | 2.42                |
| Middle  | 2 441           | 2.95         | 20.97       | 18.02       | 2.20                |
| Highest | 2 480           | 2.45         | 20.97       | 18.52       | 1.60                |

-  $\pi/4$ DQPSK

| Channel | Frequency [MHz] | Result [dBm] | Limit [dBm] | Margin [dB] | Avarage Power [dBm] |
|---------|-----------------|--------------|-------------|-------------|---------------------|
| Lowest  | 2 402           | 3.85         | 20.97       | 17.12       | 0.87                |
| Middle  | 2 441           | 3.65         | 20.97       | 17.32       | 0.56                |
| Highest | 2 480           | 3.15         | 20.97       | 17.82       | 0.08                |

- 8DPSK

| Channel | Frequency [MHz] | Result [dBm] | Limit [dBm] | Margin [dB] | Avarage Power [dBm] |
|---------|-----------------|--------------|-------------|-------------|---------------------|
| Lowest  | 2 402           | 4.45         | 20.97       | 16.52       | 0.93                |
| Middle  | 2 441           | 4.15         | 20.97       | 16.82       | 0.58                |
| Highest | 2 480           | 3.75         | 20.97       | 17.22       | 0.01                |

NOTE:

1. We took the insertion loss of the cable loss into consideration within the measuring instrument.
2. It was measured by power sensor.

## 5.3 Carrier Frequency Separation

### 5.3.1 Regulation

According to §15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2 400-2 483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

### 5.3.2 Measurement Procedure

The method of measurement used to test this FHSS device is ANSI C63.10-2013.

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a) Span: Wide enough to capture the peaks of two adjacent channels.
- b) RBW: Start with the RBW set to approximately 30 % of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- c) Video (or average) bandwidth (VBW)  $\geq$  RBW.
- d) Sweep: Auto.
- e) Detector function: Peak.
- f) Trace: Max hold.
- g) Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

Compliance of an EUT with the appropriate regulatory limit shall be determined. A plot of the data shall be included in the test report.

### 5.3.3 Test Result

#### - Complied

#### - GFSK

| Channel | Frequency [MHz] | Carrier frequency separation [MHz] | Limit                                        |
|---------|-----------------|------------------------------------|----------------------------------------------|
| Lowest  | 2 402           | 1.001                              | ≥25 kHz or two-thirds of the 20 dB bandwidth |
| Middle  | 2 441           | 1.001                              | ≥25 kHz or two-thirds of the 20 dB bandwidth |
| Highest | 2 480           | 1.001                              | ≥25 kHz or two-thirds of the 20 dB bandwidth |

#### - $\pi/4$ DQPSK

| Channel | Frequency [MHz] | Carrier frequency separation [MHz] | Limit                                        |
|---------|-----------------|------------------------------------|----------------------------------------------|
| Lowest  | 2 402           | 1.001                              | ≥25 kHz or two-thirds of the 20 dB bandwidth |
| Middle  | 2 441           | 1.001                              | ≥25 kHz or two-thirds of the 20 dB bandwidth |
| Highest | 2 480           | 1.001                              | ≥25 kHz or two-thirds of the 20 dB bandwidth |

#### - 8DPSK

| Channel | Frequency [MHz] | Carrier frequency separation [MHz] | Limit                                        |
|---------|-----------------|------------------------------------|----------------------------------------------|
| Lowest  | 2 402           | 1.001                              | ≥25 kHz or two-thirds of the 20 dB bandwidth |
| Middle  | 2 441           | 1.001                              | ≥25 kHz or two-thirds of the 20 dB bandwidth |
| Highest | 2 480           | 1.001                              | ≥25 kHz or two-thirds of the 20 dB bandwidth |

NOTE: We took the insertion loss of the cable loss into consideration within the measuring instrument.



## KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR17- SRF0069

Page (16) of (72)

# KCTL

Highest Channel (2 480 MHz)



-  $\pi/4$ DQPSK

Lowest Channel (2 402 MHz)



This test report shall not be reproduced, except in full, without the written approval

KCTL-TIR001-003/2

## KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR17- SRF0069

Page (17) of (72)

# KCTL

### Middle Channel (2 441 MHz)



### Highest Channel (2 480 MHz)



## KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)


Report No.:  
KR17- SRF0069

Page (18) of (72)


# KCTL

### - 8DPSK

Lowest Channel (2 402 MHz)



Middle Channel (2 441 MHz)




## KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR17- SRF0069  
Page (19) of (72)

# KCTL

### Highest Channel (2 480 MHz)



# KCTL

## 5.4 20 dB Channel Bandwidth

### 5.4.1 Regulation

According to §15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2 400-2 483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

### 5.4.2 Measurement Procedure

The method of measurement used to test this FHSS device is ANSI C63.10-2013.

The occupied bandwidth is measured as the width of the spectral envelope of the modulated signal, at an amplitude level reduced from a reference value by a specified ratio (or in decibels, a specified number of dB down from the reference value). Typical ratios, expressed in dB, are -6 dB, -20 dB, and -26 dB, corresponding to 6 dB BW, 20 dB BW, and 26 dB BW, respectively. In this subclause, the ratio is designated by “-xx dB.” The reference value is either the level of the unmodulated carrier or the highest level of the spectral envelope of the modulated signal, as stated by the applicable requirement. Some requirements might specify a specific maximum or minimum value for the “-xx dB” bandwidth; other requirements might specify that the “-xx dB” bandwidth be entirely contained within the authorized or designated frequency band.

- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and Five times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1 % to 5 % of the OBW and video bandwidth (VBW) shall be approximately three times RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than  $[10 \log (OBW/RBW)]$  below the reference level. Specific guidance is given in 4.1.5.2.
- d) Steps a) through c) might require iteration to adjust within the specified tolerances.
- e) The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target “-xx dB down” requirement; that is, if the requirement calls for measuring the -20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value.
- f) Set detection mode to peak and trace mode to max hold.

- g) Determine the reference value: Set the EUT to transmit an unmodulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).
- h) Determine the “-xx dB down amplitude” using [(reference value) - xx]. Alternatively, this calculation may be made by using the marker-delta function of the instrument.
- i) If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j).
- j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-xx dB down amplitude” determined in step h). If a marker is below this “-xx dB down amplitude” value, then it shall be as close as possible to this value. The occupied bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the “-xx dB down amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.
- k) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

### 5.4.3 Test Result

- Complied

| Mode          | Channel | Frequency<br>[MHz] | 20 dB Channel<br>Bandwidth [MHz] | Occupied<br>Bandwidth<br>(99 % BW) [MHz] |
|---------------|---------|--------------------|----------------------------------|------------------------------------------|
| GFSK          | Lowest  | 2 402              | 1.040                            | 0.908                                    |
|               | Middle  | 2 441              | 1.040                            | 0.908                                    |
|               | Highest | 2 480              | 1.040                            | 0.908                                    |
| $\pi/4$ DQPSK | Lowest  | 2 402              | 1.283                            | 1.151                                    |
|               | Middle  | 2 441              | 1.283                            | 1.151                                    |
|               | Highest | 2 480              | 1.283                            | 1.151                                    |
| 8DPSK         | Lowest  | 2 402              | 1.286                            | 1.154                                    |
|               | Middle  | 2 441              | 1.286                            | 1.154                                    |
|               | Highest | 2 480              | 1.286                            | 1.154                                    |


NOTE: We took the insertion loss of the cable loss into consideration within the measuring instrument.

## 5.4.4 Test Plot


Figure 2. Plot of the 20 dB Channel Bandwidth &amp; Occupied Bandwidth (Conducted)

### - GFSK\_20 dB Channel Bandwidth

Lowest Channel (2 402 MHz)



Middle Channel (2 441 MHz)



## KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR17- SRF0069

Page (24) of (72)


# KCTL

Highest Channel (2 480 MHz)



-  $\pi/4$ QPSK\_20 dB Channel Bandwidth

Lowest Channel (2 402 MHz)



This test report shall not be reproduced, except in full, without the written approval

KCTL-TIR001-003/2


## KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)


Report No.:  
KR17- SRF0069  
Page (25) of (72)

# KCTL

### Middle Channel (2 441 MHz)



### Highest Channel (2 480 MHz)



This test report shall not be reproduced, except in full, without the written approval

## KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR17- SRF0069  
Page (26) of (72)


# KCTL

### - 8DPSK\_20 dB Channel Bandwidth

Lowest Channel (2 402 MHz)



Middle Channel (2 441 MHz)



This test report shall not be reproduced, except in full, without the written approval

KCTL-TIR001-003/2

## KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR17- SRF0069

Page (27) of (72)

# KCTL

Highest Channel (2 480 MHz)



# KCTL

## KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR17- SRF0069

Page (28) of (72)


# KCTL

### - GFSK\_Occupied Bandwidth

Lowest Channel (2 402 MHz)



Middle Channel (2 441 MHz)



This test report shall not be reproduced, except in full, without the written approval

KCTL-TIR001-003/2

## KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR17- SRF0069

Page (29) of (72)


# KCTL

Highest Channel (2 480 MHz)



-  $\pi/4$ DQPSK\_Occupied Bandwidth


Lowest Channel (2 402 MHz)



This test report shall not be reproduced, except in full, without the written approval

KCTL-TIR001-003/2

### Middle Channel (2 441 MHz)



## Highest Channel (2 480 MHz)



## KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)


Report No.:  
KR17- SRF0069

Page (31) of (72)


# KCTL

### - 8DPSK\_Occupied Bandwidth

Lowest Channel (2 402 MHz)



Middle Channel (2 441 MHz)



This test report shall not be reproduced, except in full, without the written approval


## KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR17- SRF0069  
Page (32) of (72)

# KCTL

Highest Channel (2 480 MHz)



# KCTL

## 5.5 Number of Hopping Channels

### 5.5.1 Regulation

According to §15.247(a)(1)(iii), Frequency hopping systems in the 2 400-2 483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used. According to §15.247(b)(1), For frequency hopping systems operating in the 2 400-2 483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5 725-5 850 MHz band: 1 watt. For all other frequency hopping systems in the 2 400-2 483.5 MHz band: 0.125 watts.

### 5.5.2 Measurement Procedure

The method of measurement used to test this FHSS device is ANSI C63.10-2013.

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a) Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- b) RBW: To identify clearly the individual channels, set the RBW to less than 30 % of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- c) VBW  $\geq$  RBW.
- d) Sweep: Auto.
- e) Detector function: Peak.
- f) Trace: Max hold.
- g) Allow the trace to stabilize.

It might prove necessary to break the span up into subranges to show clearly all of the hopping frequencies. Compliance of an EUT with the appropriate regulatory limit shall be determined for the number of hopping channels. A plot of the data shall be included in the test report.

### 5.5.3 Test Result

- Complied

| Mode          | Frequency [MHz] | Number of hopping channel | Limit |
|---------------|-----------------|---------------------------|-------|
| GFSK          | 2 402 – 2 480   | 79                        | ≥15   |
| $\pi/4$ DQPSK | 2 402 – 2 480   | 79                        | ≥15   |
| 8DPSK         | 2 402 – 2 480   | 79                        | ≥15   |

NOTE:


1. We took the insertion loss of the cable loss into consideration within the measuring instrument.
2. Measurement is made with EUT operating in hopping mode between 79 channels providing a worse case scenario as compared to AFH mode hopping between 20 channels.

## 5.5.4 Test Plot


Figure 3. Plot of the Number of Hopping Channels (Conducted)

### Non-AFH Mode

#### - GFSK



#### - $\pi/4$ QPSK




## KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR17- SRF0069  
Page (36) of (72)


# KCTL

### - 8DPSK



### AFH Mode

### - GFSK



## KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR17- SRF0069


Page (37) of (72)

# KCTL

### - $\pi/4$ DQPSK



### - 8DPSK



## 5.6 Time of Occupancy(Dwell Time)

### 5.6.1 Regulation

According to §15.247(a)(1)(iii), frequency hopping systems in the 2 400-2 483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

### 5.6.2 Measurement Procedure

The method of measurement used to test this FHSS device is ANSI C63.10-2013.

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a) Span: Zero span, centered on a hopping channel.
- b) RBW shall be  $\leq$  channel spacing and where possible RBW should be set  $\gg 1 / T$ , where  $T$  is the expected dwell time per channel.
- c) Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
- d) Detector function: Peak.
- e) Trace: Max hold.

Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time.

Repeat the measurement using a longer sweep time to determine the number of hops over the period specified in the requirements. The sweep time shall be equal to, or less than, the period specified in the requirements. Determine the number of hops over the sweep time and calculate the total number of hops in the period specified in the requirements, using the following equation:

$$\begin{aligned} &(\text{Number of hops in the period specified in the requirements}) = \\ &(\text{number of hops on spectrum analyzer}) \times (\text{period specified in the requirements} / \text{analyzer} \\ &\text{sweep time}) \end{aligned}$$

The average time of occupancy is calculated from the transmit time per hop multiplied by the number of hops in the period specified in the requirements. If the number of hops in a specific time varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation.

The measured transmit time and time between hops shall be consistent with the values described in the operational description for the EUT.

**KCTL Inc.**

65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR17- SRF0069

Page (40) of (72)



### 5.6.3 Test Result

#### - Complied

#### - Non-AFH

| Modulation | Frequency [MHz] | Reading [ms] | Hopping rate [hop/s] | Number of Channels | Result [s] | Limit [s] |
|------------|-----------------|--------------|----------------------|--------------------|------------|-----------|
| DH1        | 2 441           | 0.382        | 800.000              | 79                 | 0.122      | 0.400     |
| DH3        | 2 441           | 1.637        | 400.000              | 79                 | 0.262      | 0.400     |
| DH5        | 2 441           | 2.891        | 266.667              | 79                 | 0.308      | 0.400     |
| 2-DH1      | 2 441           | 0.388        | 800.000              | 79                 | 0.124      | 0.400     |
| 2-DH3      | 2 441           | 1.639        | 400.000              | 79                 | 0.262      | 0.400     |
| 2-DH5      | 2 441           | 2.891        | 266.667              | 79                 | 0.308      | 0.400     |
| 3-DH1      | 2 441           | 0.388        | 800.000              | 79                 | 0.124      | 0.400     |
| 3-DH3      | 2 441           | 1.639        | 400.000              | 79                 | 0.262      | 0.400     |
| 3-DH5      | 2 441           | 2.891        | 266.667              | 79                 | 0.308      | 0.400     |

#### - AFH

| Modulation | Frequency [MHz] | Reading [ms] | Hopping rate [hop/s] | Number of Channels | Result [s] | Limit [s] |
|------------|-----------------|--------------|----------------------|--------------------|------------|-----------|
| DH1        | 2 441           | 0.382        | 400.000              | 20                 | 0.061      | 0.400     |
| DH3        | 2 441           | 1.637        | 200.000              | 20                 | 0.131      | 0.400     |
| DH5        | 2 441           | 2.891        | 133.333              | 20                 | 0.154      | 0.400     |
| 2-DH1      | 2 441           | 0.388        | 400.000              | 20                 | 0.062      | 0.400     |
| 2-DH3      | 2 441           | 1.639        | 200.000              | 20                 | 0.131      | 0.400     |
| 2-DH5      | 2 441           | 2.891        | 133.333              | 20                 | 0.154      | 0.400     |
| 3-DH1      | 2 441           | 0.388        | 400.000              | 20                 | 0.062      | 0.400     |
| 3-DH3      | 2 441           | 1.639        | 200.000              | 20                 | 0.131      | 0.400     |
| 3-DH5      | 2 441           | 2.891        | 133.333              | 20                 | 0.154      | 0.400     |

**NOTE 1. Non AFH**

Result = Number of Transmission in 31.6s x Length of Tmasmission Test period  
= 0.4 [seconds / channel] × 79 [channel] = 31.6 [seconds]

**NOTE 2. AFH**


Result = Number of Transmission in 8s x Length of Tmasmission Test period  
= 0.4 [seconds / channel] × 20 [channel] = 8 [seconds]

## 5.6.4 Test Plot


Figure 4. Plot of the Time of Occupancy (Conducted)

### - GFSK\_Non AFH mode

DH1 (2 441 MHz)



DH3 (2 441 MHz)



## KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR17- SRF0069

Page (42) of (72)


# KCTL

DH5 (2 441 MHz)



-  $\pi/4$ DQPSK\_Non AFH mode

2-DH1 (2 441 MHz)




## KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)


Report No.:  
KR17- SRF0069  
Page (43) of (72)

# KCTL

### 2-DH3 (2 441 MHz)



### 2-DH5 (2 441 MHz)



## KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)


Report No.:  
KR17- SRF0069

Page (44) of (72)


# KCTL

### - 8DPSK\_Non AFH mode

3-DH1 (2 441 MHz)



3-DH3 (2 441 MHz)




## KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR17- SRF0069  
Page (45) of (72)


# KCTL

3-DH5 (2 441 MHz)




- GFSK\_AFH mode


DH1 (2 441 MHz)



DH3 (2 441 MHz)



DH5 (2 441 MHz)



## KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)


Report No.:  
KR17- SRF0069

Page (47) of (72)


# KCTL

### - $\pi/4$ DQPSK\_AFH mode

2-DH1 (2 441 MHz)



2-DH3 (2 441 MHz)



## KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR17- SRF0069

Page (48) of (72)

# KCTL

2-DH5 (2 441 MHz)



- 8DPSK\_AFH mode

3-DH1 (2 441 MHz)

