

* RF Exposure

1. Regulation

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this Chapter.

Limits for Maximum Permissible Exposure: RF exposure is calculated.

Frequency Range	Electric Field Strength [V/m]	Magnetic Field Strength [A/m]	Power Density [mW/cm ²]	Averaging Time [minute]
Limits for General Population / Uncontrolled Exposure				
0.3 ~ 1.34	614	1.63	*(100)	30
1.34 ~ 30	824/f	2.19/f	*(180/f ²)	30
30 ~ 300	27.5	0.073	0.2	30
300 ~ 1 500	/	/	f/1 500	30
1 500 ~ 15 000	/	/	1.0	30

f=frequency in MHz, *= plane-wave equivalent power density

MPE (Maximum Permissible Exposure) Prediction

Predication of MPE limit at a given distance: Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2 \quad (\Rightarrow R = \sqrt{PG/4\pi S})$$

S = power density [mW/cm²]

P = Power input to antenna [mW]

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna [cm]

2. RF Exposure Compliance Issue

The information should be included in the user's manual:

This appliance and its antenna must not be co-located or operation in conjunction with any other antenna or transmitter. A minimum separation distance of 20 cm must be maintained between the antenna and the person for this appliance to satisfy the RF exposure requirements.

3. Calculation Result of RF Exposure

	Target power [dBm]	Tune up tolerance [dB]	Max tune up power [dBm]	Max tune up power [mW]	Ant Gain [dBi]	Ant Gain [mW]	Power Density at 20 cm [mW/cm ²]	Limit [mW/cm ²]
Bluetooth GFSK	1.0	±2.0	3.0	2.00	2.29	1.69	0.000 67	1.000 00
Bluetooth [I]/4DQPSK	-1.0	±2.0	1.0	1.26	2.29	1.69	0.000 42	1.000 00
Bluetooth 8DPSK	-1.0	±2.0	1.0	1.26	2.29	1.69	0.000 42	1.000 00
WiFi 2.4G 802.11b	14.0	±2.0	16.0	39.81	4.11	2.58	0.020 40	1.000 00
WiFi 2.4G 802.11g	10.0	±2.0	12.0	15.85	4.11	2.58	0.008 12	1.000 00
WiFi 2.4G 802.11n_HT20	10.0	±2.0	12.0	15.85	4.11	2.58	0.008 12	1.000 00
WiFi 5G 802.11a/n20/n40 /ac20/ac40/ac80 _5 150 BW	12.0	±2.0	14.0	25.12	2.89	1.95	0.009 72	1.000 00
WiFi 5G 802.11a/n20/n40 /ac20/ac40/ac80 _5 250 BW	12.0	±2.0	14.0	25.12	2.89	1.95	0.009 72	1.000 00
WiFi 5G 802.11a/n20/n40 /ac20/ac40/ac80 _5 470 BW	9.6	±2.0	11.6	14.45	2.51	1.78	0.005 13	1.000 00
WiFi 5G 802.11a/n20/n40 /ac20/ac40/ac80 _5 750 BW	11.0	±2.0	13.0	19.95	5.78	3.78	0.011 93	1.000 00

4. Target power and tolerance, Max tuneup power

Mode	Target power [dBm]	Tolerance [dB]	Max tuneup power [dBm]	Average Power [dBm]
Bluetooth GFSK	1.0	±2.0	3.0	1.66
Bluetooth [1]4DQPSK	-1.0	±2.0	1.0	0.14
Bluetooth 8DPSK	-1.0	±2.0	1.0	0.14
WiFi 2.4G 802.11b	14.0	±2.0	16.0	15.54
WiFi 2.4G 802.11g	10.0	±2.0	12.0	11.87
WiFi 2.4G 802.11n_HT20	10.0	±2.0	12.0	11.69
WiFi 5G 802.11a/n20/n40 /ac20/ac40/ac80 _5 150 BW	12.0	±2.0	14.0	13.10
WiFi 5G 802.11a/n20/n40 /ac20/ac40/ac80 _5 250 BW	12.0	±2.0	14.0	12.89
WiFi 5G 802.11a/n20/n40 /ac20/ac40/ac80 _5 470 BW	9.6	±2.0	11.6	10.70
WiFi 5G 802.11a/n20/n40 /ac20/ac40/ac80 _5 750 BW	11.0	±2.0	13.0	11.98