RF EXPOSURE LAB, LLC

2867 Progress Place, Suite 4D • Escondido, CA 92029 • U.S.A.
TEL (760) 737-3131 • FAX (760) 737-9131
http://www.rfexposurelab.com

CERTIFICATE OF COMPLIANCE
SAR EVALUATION

Sendum Corporation	Dates of Test: November 23, 2005
4500 Beedie Street	Test Report Number: SAR.20051101
Burnaby, BC V5J 5L2, Canada	Revision C

FCC ID:	TS5-6050M-OM200
IC Certificate:	6234A-OM200
Model(s):	OM200
Test Sample:	Pre-Production Unit same as Production
Serial No.:	3A137985
Equipment Type:	Dual Band Wireless Tracking Device
Classification:	Portable Transmitter Next to Body
TX Frequency Range:	824.7 – 848.31 MHz, 1851.25 – 1908.75 MHz
Frequency Tolerance:	± 120 kHz
Maximum RF Output:	24 dBm Conducted
Signal Modulation:	CDMA
Antenna Type (Length):	Internal (PCB), P/N CCI-01
Battery:	P/N fba00005 Battery Pack
Application Type:	Certification
FCC Rule Parts:	Part 22H, Part 24E
IC Specification:	RSS-129, RSS-133

This wireless mobile and/or portable device has been shown to be compliant for localized specific absorption rate (SAR) for uncontrolled environment/general exposure limits specified in ANSI/IEEE Std. C95.1-1999 and had been tested in accordance with the measurement procedures specified in IEEE 1528-2003, OET Bulletin 65 Supp. C, RSS-102 and Safety Code 6 (See test report).

I attest to the accuracy of the data. All measurements were performed by myself or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

RF Exposure Lab, LLC certifies that no party to this application has been denied FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 853(a).

Jay M. Moulton
Vice President

ACCREDITED
Certificate # 2387.01

© 2005 RF Exposure Lab, LLC
This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

Table of Contents

1. Introduction 3
SAR Definition [5] 3
2. SAR Measurement Setup 4
Robotic System 4
System Hardware 4
System Description 4
E-Field Probe ALS-E-020 5
3. Robot Specifications 7
4. Probe and Dipole Calibration 8
5. Phantom & Simulating Tissue Specifications 9
SAM Phantom 9
Brain & Muscle Simulating Mixture Characterization 9
Device Holder 9
6. Definition of Reference Points 10
Ear Reference Point 10
Device Reference Points 10
7. Test Configuration Positions 11
Positioning for Cheek/Touch [5] 11
Positioning for Ear / 15˚ Tilt [5] 12
Body Worn Configurations 13
8. ANSI/IEEE C95.1 – 1999 RF Exposure Limits [2] 14
Uncontrolled Environment 14
Controlled Environment 14
9. Measurement Uncertainty 15
10. System Validation 16
Tissue Verification 16
Test System Verification 16
11. SAR Test Data Summary 17
Procedures Used To Establish Test Signal 17
Device Test Condition 17
SAR Data Summary – 835 MHz Body 18
SAR Data Summary – 1900 MHz Body 19
12. Test Equipment List 20
13. Conclusion 21
14. References 22
Appendix A – System Validation Plots and Data 23
Appendix B – SAR Test Data Plots 32
Appendix C – SAR Test Setup Photos 73
Appendix D – Probe Calibration Data Sheets 81
Appendix E – Dipole Calibration Data Sheets 102
Appendix F – Phantom Calibration Data Sheets 121

© 2005 RF Exposure Lab, LLC

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

1. Introduction

This measurement report shows compliance of the Sendum Corporation Model OM200 FCC ID: TS5-6050M-OM200 with FCC Part 2, 1093, ET Docket 93-62 Rules for mobile and portable devices and IC Certificate: 6234A-OM20 with RSS102 & Safety Code 6. The FCC have adopted the guidelines for evaluating the environmental effects of radio frequency radiation in ET Docket 93-62 on August 6, 1996 to protect the public and workers from the potential hazards of RF emissions due to FCC regulated portable devices. [1]

The test procedures, as described in ANSI C95.1 – 1999 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [2], ANSI C95.3 – 2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields [3], FCC OET Bulletin 65 Supp. C – 2001 [4], and IEEE Std.1528 – 2003 Recommended Practice [5] were employed.

SAR Definition [5]

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (*dW*) absorbed by (dissipated in) an incremental mass (*dm*) contained in a volume element (*dV*) of a given density (ρ).

$$SAR = \frac{d}{dt}\left(\frac{dW}{dm}\right) = \frac{d}{dt}\left(\frac{dW}{\rho dV}\right)$$

SAR is expressed in units of watts per kilogram (W/kg). *SAR* can be related to the electric field at a point by

$$SAR = \frac{\sigma \mid E \mid^2}{\rho}$$

where:

σ = conductivity of the tissue (S/m)
ρ = mass density of the tissue (kg/m^3)
E = rms electric field strength (V/m)

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

2. SAR Measurement Setup

Robotic System

The measurements are conducted utilizing the ALSAS-10-U automated dosimetric assessment system. The ALSAS-10-U is designed and manufactured by Aprel Laboratories in Nepean, Ontario, Canada. The system utilizes a Robcomm 3 robot manufactured by ThermoCRS located in Michigan USA.

System Hardware

The system consists of a six axis articulated arm, controller for precise probe positioning (0.05 mm repeatability), a power supply, a teach pendent for teaching area scans, near field probe, an IBM Pentium 4™ 2.66 GHz PC with Windows XP Pro™, and custom software developed to enable communications between the robot controller software and the host operating system.

An amplifier is located on the articulated arm, which is isolated from the custom designed end effector and robot arm. The end effector provides the mechanical touch detection functionality and probe connection interface. The amplifier is functionally validated within the manufacturer's site and calibrated at NCL Calibration Laboratories. A Data Acquisition Card (DAC) is used to collect the signal as detected by the isotropic e-field probe. The DAC manufacturer calibrates the DAC to NIST standards. A formal validation is executed using all mechanical and electronic components to prove conformity of the measurement platform as a whole.

System Description

The ALSAS-10-U has been designed to measure devices within the compliance environment to meet all recognized standards. The system also conforms to standards, which are currently being developed by the scientific and manufacturing community.

The course scan resolution is defined by the operator and reflects the requirements of the standard to which the device is being tested. Precise measurements are made within the predefined course scan area and the values are logged.

The user predefines the sample rate for which the measurements are made so as to ensure that the full duty-cycle of a pulse modulation device is covered during the sample. The following algorithm is an example of the function used by the system for linearization of the output for the probe.

$$V_i = U_i + U_i^2 \bullet \frac{cf}{dcp_i}$$

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.



The Aprel E-Field probe is evaluated to establish the diode compression point.

A complex algorithm is then used to calculate the values within the measured points down to a resolution of 1mm. The data from this process is then used to provide the co-ordinates from which the cube scan is created for the determination of the 1 g and 10 g averages.

Cube scan averaging consists of a number of complex algorithms, which are used to calculate the one, and ten gram averages. The basis for the cube scan process is centered on the location where the maximum measured SAR value was found. When a secondary peak value is found which is within 60% of the initial peak value, the system will report this back to the operator who can then assess the need for further analysis of both the peak values prior to the one and ten-gram cube scan averaging process. The algorithm consists of 3D cubic Spline, and Lagrange extrapolation to the surface, which form the matrix for calculating the measurement output for the one and ten gram average values. The resolution for the physical scan integral is user defined with a final calculated resolution down to 1mm.

In-depth analysis for the differential of the physical scanning resolution for the cube scan analysis has been carried out, to identify the optimum setting for the probe positioning steps, and this has been determined at 8mm increments on the X, & Y planes. The reduction of the physical step increment increased the time taken for analysis but did not provide a better uncertainty or return on measured values.

The final output from the system provides data for the area scan measurements, physical and splined (1mm resolution) cube scan with physical and calculated values (1mm resolution).

The overall uncertainty for the methodology and algorithms the ALSAS-10-U used during the SAR calculation was evaluated using the data from IEEE 1528 f3 algorithm:

$$f_3(x,y,z) = A\frac{a^2}{\frac{a^2}{4} + x'^2 + y'^2}\left(e^{-\frac{2z}{a}} + \frac{a^2}{2(a+2z)^2}\right)$$

The probe used during the measurement process has been assessed to provide values for diode compression. These values are calculated during the probe calibration exercise and are used in the mathematical calculations for the assessment of SAR.

E-Field Probe ALS-E-020

The E-field probe used by RF Exposure Lab, LLC, has been fully calibrated and assessed for isotropic, and boundary effect. The probe utilizes a triangular sensor arrangement as detailed in the diagram below right.

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.



Δ-BEAM



The SAR is assessed with the probe which moves at a default height of 5mm from the center of the diode, which is mounted to the sensor, to the phantom surface (Z height). The diagram above right shows how the center of the sensor is defined with the location of the diode placed at the center of the dipole. The 5mm default in the Z axis is the optimum height for assessing SAR where the boundary effect is at its least, with the probe located closest to the phantom surface (boundary).

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

3. Robot Specifications

Specifications

Positioner:	ThermoCRS, Robot Model: Robocomm 3
Repeatability:	0.05 mm
No. of axis:	6

Data Acquisition Card (DAC) System

Cell Controller

Processor:	Pentium 4™
Clock Speed:	2.66 GHz
Operating System:	Windows XP Pro™

Data Converter

Features:	Signal Amplifier, End Effector, DAC
Software:	ALSAS 10-U Software

E-Field Probe

Model:	ALS-E-020
Serial Number:	RFE-215
Construction:	Triangular Core Touch Detection System
Frequency:	10MHz to 6GHz

Phantom

Phantom:	Uniphantom, Right Phantom, Left Phantom



This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

4. Probe and Dipole Calibration

See Appendix D and E.

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

5. Phantom & Simulating Tissue Specifications

SAM Phantom

The Aprel system utilizes three separate phantoms. Each phantom for SAR assessment testing is a low loss dielectric shell, with shape and dimensions derived from the anthropomorphic data of the 90th percentile adult male head dimensions as tabulated by the US Army. The SAM phantom shell is bisected along the mid sagittai plane into right and left halves. The perimeter sidewalls of each phantom half is extended to allow filling with liquid to a depth of 15 cm that is sufficient to minimize reflections from the upper surface [5]. See photos in Appendix C.

Brain & Muscle Simulating Mixture Characterization

The brain and muscle mixtures consist of a glycol based chemical and saline solution. The mixture is calibrated to obtain proper dielectric constant (permittivity) and conductivity of the desired tissue. The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 have been incorporated in the following tables. Other head and body tissue parameters that have not been specified in P1528 are derived from the issue dielectric parameters computed from the 4-Cole-Cole equations.

Table 5.1 Typical Composition of Ingredients for Tissue

Ingredients		Simulating Tissue	
		800 MHz Muscle	1900 MHz Muscle
Mixing Percentage			
Water		52.40	69.91
DGBE		0.00	29.96
Sugar		45.00	0.00
HEC		1.00	0.00
Salt		1.40	0.13
Bactericide		0.10	0.00
Dielectric Constant	Target	56.10	54.00
Conductivity (S/m)	Target	0.95	1.45

Device Holder

In combination with the SAM phantom, the mounting device enables the rotation of the mounted transmitter in spherical coordinates whereby the rotation point is the ear opening. The devices can easily, accurately, and repeatably be positioned according to the FCC specifications. The device holder can be locked at different phantom locations (left head, right head, and uni-phantom).

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

6. Definition of Reference Points

Ear Reference Point

Figure 6.2 shows the front, back and side views of the SAM Phantom. The point "M" is the reference point for the center of the mouth, "LE" is the left ear reference point (ERP), and "RE" is the right ERP. The ERPs are 15mm posterior to the entrance to the ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 6.1. The plane passing through the two ear canals and M is defined as the Reference Plane. The line N-F (Neck-Front) is perpendicular to the reference plane and passing through the RE (or LE) is called the Reference Pivoting Line (see Figure 6.1). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines are marked on the external phantom shell to facilitate handset positioning [5].



Figure 6.1 Close-up side view of ERP's

Figure 6.2 Front, back and side view of SAM

Device Reference Points

Two imaginary lines on the device need to be established: the vertical centerline and the horizontal line. The test device is placed in a normal operating position with the "test device reference point" located along the "vertical centerline" on the front of the device aligned to the "ear reference point" (See Fig. 6.3). The "test device reference point" is than located at the same level as the center of the ear reference point. The test device is positioned so that the "vertical centerline" is bisecting the front surface of the device at it's top and bottom edges, positioning the "ear reference point" on the outer surface of both the left and right head phantoms on the ear reference point [5].



Figure 6.3 Handset Vertical Center & Horizontal Line Reference Points

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

7. Test Configuration Positions

Positioning for Cheek/Touch [5]

1. Position the device close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 7.1), such that the plane defined by the vertical center line and the horizontal line of the device is approximately parallel to the sagittal plane of the phantom.



Figure 7.1 Front, Side and Top View of Cheek/Touch Position

2. Translate the device towards the phantom along the line passing through RE and LE until the device touches the ear.

3. While maintaining the device in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to MB-NF including the line MB (called the reference plane).

4. Rotate the device around the vertical centerline until the device (horizontal line) is symmetrical with respect to the line NF.

5. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE and maintaining the device contact with the ear, rotate the device about the line NF until any point on the device is in contact with a phantom point below the ear (cheek). See Figure 7.2.



Figure 7.2 Side view w/ relevant markings

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

Positioning for Ear / 15° Tilt [5]

With the test device aligned in the Cheek/Touch Position":

1. While maintaining the orientation of the device, retracted the device parallel to the reference plane far enough to enable a rotation of the device by 15 degrees.

2. Rotate the device around the horizontal line by 15 degrees.

3. While maintaining the orientation of the device, move the device parallel to the reference plane until any part of the device touches the head. (In this position, point A is located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact is at any location other than the pinna, the angle of the device shall be reduced. The tilted position is obtained when any part of the device is in contact with the ear as well as a second part of the device is in contact with the head (see Figure 7.3).



Figure 7.3 Front, Side and Top View of Ear/15° Tilt Position

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

Body Worn Configurations

Body-worn operating configurations are tested with the accessories attached to the device and positioned against a flat phantom in a normal use configuration. A device with a headset output is tested with a headset connected to the device. Body dielectric parameters are used.

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then, when multiple accessories that contain metallic components are supplied with the device, the device is tested with each accessory that contains a unique metallic component. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration where a separation distance between the back of the device and the flat phantom is used. All test position spacings are documented.

Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessory(ies), including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

In all cases SAR measurements are performed to investigate the worst-case positioning. Worst-case positioning is then documented and used to perform Body SAR testing.

In order for users to be aware of the body-worn operating requirements for meeting RF exposure compliance, operating instructions and cautions statements are included in the user's manual.

© 2005 RF Exposure Lab, LLC

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

8. ANSI/IEEE C95.1 – 1999 RF Exposure Limits [2]

Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Table 8.1 Human Exposure Limits

	UNCONTROLLED ENVIRONMENT General Population (W/kg) or (mW/g)	CONTROLLED ENVIROMENT Professional Population (W/kg) or (mW/g)
SPATIAL PEAK SAR[1] Brain	1.60	8.00
SPATIAL AVERAGE SAR[2] Whole Body	0.08	0.40
SPATIAL PEAK SAR[3] Hands, Feet, Ankles, Wrists	4.00	20.00

[1] The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
[2] The Spatial Average value of the SAR averaged over the whole body.
[3] The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

9. Measurement Uncertainty

See Appendix B SAR Test Data Plots for Measurement Uncertainty.

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

10. System Validation

Tissue Verification

Table 10.1 Measured Tissue Parameters

Date(s)	11/232005	835 MHz Body		1900 MHz Body	
Liquid Temperature (˚C)	21.0	Target	Measured	Target	Measured
Dielectric Constant: ε		55.20	54.64	53.30	52.66
Conductivity: σ		0.970	0.96	1.52	1.56

See Appendix A for data printout.

Test System Verification

Prior to assessment, the system is verified to the ±10% of the specifications at 835 MHz and 1900 MHz by using the system kit. Power is extrapolated to 1 watt. (Graphic Plots Attached)

Table 10.2 System Dipole Validation Target & Measured

System Validation Kit: ALS-D-835-S-2 S/N: RFE-274	835 MHz Body	Targeted SAR_{1g} (W/kg) 9.5	Measure SAR_{1g} (W/kg) 9.832	Deviation (%) + 3.49
System Validation Kit: ALS-D-1900-S-2 S/N: RFE-277	1900 MHz Body	Targeted SAR_{1g} (W/kg) 39.7	Measure SAR_{1g} (W/kg) 42.06	Deviation (%) + 5.94

See Appendix A for data plots.



Figure 10.1 Dipole Validation Test Setup

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

11. SAR Test Data Summary

See Measurement Result Data Pages

See Appendix B for SAR Test Data Plots.
See Appendix C for SAR Test Setup Photos.

Procedures Used To Establish Test Signal

The device was placed into simulated transmit mode using the manufacturer's test codes. Such test signals offer a consistent means for testing SAR and are recommended for evaluating SAR. When test modes are not available or inappropriate for testing a device, the actual transmission is activated through a base station simulator or similar equipment. See data pages for actual procedure used in measurement.

Device Test Condition

The device is battery operated. Each SAR measurement was taken with a fully charged battery. In order to verify that the device was tested at full power, conducted output power measurements were performed before and after each SAR measurement to confirm the output power. If a conducted power deviation of more than 5% occurred, the test was repeated.

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

SAR Data Summary – 835 MHz Body

MEASUREMENT RESULTS								
Gap	EUT Position	Frequency		Modulation	Begin / End Power			SAR (W/kg)
		MHz	Ch.		(dBm)		Battery	
Touch	Next to Ankle	836.52	384	CDMA	24.12	23.98	Standard	0.403
	Away from Ankle	824.70	1013	CDMA	24.10	24.05	Standard	0.877
		836.52	384	CDMA	24.21	24.16	Standard	0.717
		848.31	777	CDMA	24.18	24.09	Standard	0.756
	Antenna Edge	836.52	384	CDMA	24.07	23.94	Standard	0.147
					Muscle (Ankle) 4.0 W/kg (mW/g) averaged over 10 gram			

1. Battery is fully charged for all tests.
   Power Measured ☒Conducted ☐ERP ☐EIRP

2. SAR Measurement
   Phantom Configuration ☐Left Head ☒Uniphantom ☐Right Head
   SAR Configuration ☐Head ☒Body

3. Test Signal Call Mode ☒Test Code ☐Base Station Simulator

4. Test Configuration ☐With Belt Clip ☐Without Belt Clip ☒N/A

Jay M. Moulton
Vice President

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

SAR Data Summary – 1900 MHz Body

MEASUREMENT RESULTS								
Gap	EUT Position	Frequency		Modulation	Begin / End Power			SAR (W/kg)
		MHz	Ch.		(dBm)		Battery	
Touch	Next to Ankle	1880.00	600	CDMA	24.05	23.98	Standard	0.369
	Away from Ankle	1851.25	25	CDMA	24.13	24.02	Standard	0.788
		1880.00	600	CDMA	24.08	24.01	Standard	1.175
		1908.75	1175	CDMA	24.21	24.11	Standard	0.893
	Antenna Edge	1880.00	600	CDMA	24.19	24.14	Standard	0.335
					Muscle (Ankle) 4.0 W/kg (mW/g) averaged over 10 gram			

5. Battery is fully charged for all tests.
   Power Measured ☒Conducted ☐ERP ☐EIRP

6. SAR Measurement
   Phantom Configuration ☐Left Head ☒Uniphantom ☐Right Head
   SAR Configuration ☐Head ☒Body

7. Test Signal Call Mode ☒Test Code ☐Base Station Simulator

8. Test Configuration ☐With Belt Clip ☐Without Belt Clip ☒N/A

Jay M. Moulton
Vice President

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

12. Test Equipment List

Table 12.1 Equipment Specifications

Type	Calibration Due Date	Serial Number
ThermoCRS Robot	N/A	RAF0338198
ThermoCRS Controller	N/A	RCF0338224
ThermoCRS Teach Pendant (Joystick)	N/A	STP0334405
IBM Computer, 2.66 MHz P4	N/A	8189D8U KCPR08N
Aprel E-Field Probe ALS-E020	06/10/2006	RFE-215
Aprel Dummy Probe	N/A	023
Aprel Left Phantom	N/A	RFE-267
Aprel Right Phantom	N/A	RFE-268
Aprel UniPhantom	N/A	RFE-273
Aprel Validation Dipole ALS-D-835-S-2	02/20/2006	RFE-274
Aprel Validation Dipole ALS-D-1900-S-2	02/20/2006	RFE-277
Aprel Validation Dipole ALS-D-2450-S-2	02/20/2006	RFE-278
Aprel Validation Dipole ALS-D-900-S-2	02/20/2006	RFE-275
Agilent (HP) 437B Power Meter	12/14/2005	3125U08837
Agilent (HP) 8481B Power Sensor	12/14/2005	3318A05384
Agilent (HP) 8350B Signal Generator	03/03/2006	2749A10226
Agilent (HP) 83525A RF Plug-In	03/03/2006	2647A01172
Agilent (HP) 8753C Vector Network Analyzer	02/03/2006	3135A01724
Agilent (HP) 85047A S-Parameter Test Set	02/03/2006	2904A00595
Aprel Dielectric Probe Assembly	N/A	0011
Microwave Power Devices 510-10E Amplifier	03/03/2006	6063-001
Microwave Power Devices 1020-9E Amplifier	03/03/2006	5618-1
Brain Equivalent Matter (835 MHz)	N/A	N/A
Brain Equivalent Matter (1900 MHz)	N/A	N/A
Brain Equivalent Matter (900 MHz)	N/A	N/A
Muscle Equivalent Matter (835 MHz)	N/A	N/A
Muscle Equivalent Matter (1900 MHz)	N/A	N/A
Muscle Equivalent Matter (900 MHz)	N/A	N/A
Muscle Equivalent Matter (2450 MHz)	N/A	N/A
Muscle Equivalent Matter (5200 MHz)	N/A	N/A

© 2005 RF Exposure Lab, LLC

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

13. Conclusion

The SAR measurement indicates that the EUT complies with the RF radiation exposure limits of the FCC. These measurements are taken to simulate the RF effects exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The tested device complies with the requirements in respect to all parameters subject to the test. The test results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body is a very complex phenomena that depends on the mass, shape, and size of the body; the orientation of the body with respect to the field vectors; and, the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because innumerable factors may interact to determine the specific biological outcome of an exposure to electromagnetic fields, any protection guide shall consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

14. References

[1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radio Frequency Radiation, August 1996

[2] ANSI/IEEE C95.1 – 1999, American National Standard Safety Levels with respect to Human Exposure to Radio Frequency Electromagnetic Fields, 300kHz to 100GHz, New York: IEEE, 1992.

[3] ANSI/IEEE C95.3 – 2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields – RF and Microwave, New York: IEEE, 1992.

[4] Federal Communications Commission, OET Bulletin 65 (Edition 97-01), Supplement C (Edition 01-01), Evaluating Compliance with FCC Guidelines for Human Exposure to Radio Frequency Electromagnetic Fields, July 2001.

[5] IEEE Standard 1528 – 2003, IEEE Recommended Practice for Determining the Peak-Spatial Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communication Devices: Measurement Techniques, October 2003.

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

Appendix A – System Validation Plots and Data

```
************************************************************
Test Result for UIM Dielectric Parameter
Tue 23/Nov/2005 11:07:20
Freq  Frequency(GHz)
FCC_eH      FCC Bulletin 65 Supplement C ( June 2001) Limits for Head Epsilon
FCC_sH      FCC Bulletin 65 Supplement C (June 2001) Limits for Head Sigma
FCC_eB      FCC Limits for Body Epsilon
FCC_sB      FCC Limits for Body Sigma
Test_e      Epsilon  of  UIM
Test_s      Sigma of UIM
************************************************************
```

Freq	FCC_eB	FCC_sB	Test_e	Test_s
0.7850	55.39	0.97	55.43	0.95
0.7950	55.36	0.97	55.31	0.95
0.8050	55.32	0.97	55.15	0.95
0.8150	55.28	0.97	54.96	0.95
0.8250	55.24	0.97	54.85	0.96
0.8350	55.20	0.97	54.64	0.96
0.8450	55.17	0.98	54.52	0.96
0.8550	55.14	0.99	54.30	0.97
0.8650	55.11	1.01	54.18	0.98
0.8750	55.08	1.02	54.12	0.99
0.8850	55.05	1.03	54.11	1.00

```
************************************************************
Test Result for UIM Dielectric Parameter
Wed 23/Nov/2005 14:54:01
Freq  Frequency(GHz)
FCC_eH      FCC Bulletin 65 Supplement C ( June 2001) Limits for Head Epsilon
FCC_sH      FCC Bulletin 65 Supplement C (June 2001) Limits for Head Sigma
FCC_eB      FCC Limits for Body Epsilon
FCC_sB      FCC Limits for Body Sigma
Test_e      Epsilon  of  UIM
Test_s      Sigma of UIM
************************************************************
```

Freq	FCC_eB	FCC_sB	Test_e	Test_s
1.8500	53.30	1.52	52.34	1.52
1.8600	53.30	1.52	52.48	1.52
1.8700	53.30	1.52	52.56	1.53
1.8800	53.30	1.52	52.66	1.53
1.8900	53.30	1.52	52.77	1.55
1.9000	53.30	1.52	52.66	1.56
1.9100	53.30	1.52	52.47	1.55
1.9200	53.30	1.52	52.35	1.53
1.9300	53.30	1.52	52.11	1.55
1.9400	53.30	1.52	51.95	1.54
1.9500	53.30	1.52	51.79	1.55

© 2005 RF Exposure Lab, LLC

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

SAR Test Report

Operator : Jay
Validation Date : 23-Nov-2005
Measurement Date : 23-Nov-2005
Starting Time : 23-Nov-2005 11:40:55 AM
End Time : 23-Nov-2005 11:56:18 AM
Scanning Time : 923 secs

Product Data
Device Name : Validation
Serial No. : 835
Type : Dipole
Model : ALS-D-835-S-2
Frequency : 835.00 MHz
Max. Transmit Pwr : 0.25 W
Drift Time : 0 min(s)
Length : 161 mm
Width : 3.6 mm
Depth : 89.8 mm
Antenna Type : Internal
Power Drift-Start : 2.022 W/kg
Power Drift-Finish: 2.023 W/kg
Power Drift (%) : 0.042

Phantom Data
Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : System Default
Location : Center
Description : Uni-Phantom

Tissue Data
Type : BODY
Serial No. : 835
Frequency : 835 MHz
Last Calib. Date : 23-Nov-2005
Temperature : 21 °C
Ambient Temp. : 22 °C
Humidity : 40 RH%
Epsilon : 54.64 F/m
Sigma : 0.96 S/m
Density : 1000 kg/cu. m

Probe Data
Name : Probe 215 - RFEL
Model : E020
Type : E-Field Triangle
Serial No. : 215
Last Calib. Date : 10-Jun-2005
Frequency : 835 MHz
Duty Cycle Factor: 1
Conversion Factor: 6.07
Probe Sensitivity: 1.20 1.20 1.20 $\mu V/(V/m)^2$
Compression Point: 95 mV
Offset : 1.56 mm

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

```
Measurement Data
Crest Factor      : 1
Scan Type         : Complete
Tissue Temp.      : 21°C
Ambient Temp.     : 22°C
Set-up Date       : 23-Nov-2005
Set-up Time       : 2:15:04 PM
Area Scan         : 5x6x1 : Measurement x=10mm, y=10mm, z=4mm
Zoom Scan         : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data
DUT Position      : Touch
Separation        : 0
Channel           : Mid - 835
```



```
1 gram SAR value   : 2.458 W/kg
10 gram SAR value  : 1.568 W/kg
Area Scan Peak SAR : 2.680 W/kg
Zoom Scan Peak SAR : 3.753 W/kg
```


This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

Exposure Assessment Measurement Uncertainty

Source of Uncertainty	Tolerance Value	Probability Distribution	Divisor	c_i^1 (1-g)	c_i^1 (10-g)	Standard Uncertainty (1-g) %	Standard Uncertainty (10-g) %
Measurement System							
Probe Calibration	3.5	normal	1	1	1	3.5	3.5
Axial Isotropy	3.7	rectangular	•3	$(1-cp)^{1/2}$	$(1-cp)^{1/2}$	1.5	1.5
Hemispherical Isotropy	10.9	rectangular	•3	•cp	•cp	4.4	4.4
Boundary Effect	1.0	rectangular	•3	1	1	0.6	0.6
Linearity	4.7	rectangular	•3	1	1	2.7	2.7
Detection Limit	1.0	rectangular	•3	1	1	0.6	0.6
Readout Electronics	1.0	normal	1	1	1	1.0	1.0
Response Time	0.8	rectangular	•3	1	1	0.5	0.5
Integration Time	1.7	rectangular	•3	1	1	1.0	1.0
RF Ambient Condition	3.0	rectangular	•3	1	1	1.7	1.7
Probe Positioner Mech.	0.4	rectangular	•3	1	1	0.2	0.2
Restriction							
Probe Positioning with respect to Phantom Shell	2.9	rectangular	•3	1	1	1.7	1.7
Extrapolation and Integration	3.7	rectangular	•3	1	1	2.1	2.1
Test Sample Positioning	4.0	normal	1	1	1	4.0	4.0
Device Holder Uncertainty	2.0	normal	1	1	1	2.0	2.0
Drift of Output Power	0.0	rectangular	•3	1	1	0.0	0.0
Phantom and Setup							
Phantom Uncertainty(shape & thickness tolerance)	3.4	rectangular	•3	1	1	2.0	2.0
Liquid Conductivity(target)	5.0	rectangular	•3	0.7	0.5	2.0	1.4
Liquid Conductivity(meas.)	4.3	normal	1	0.7	0.5	3.0	2.2
Liquid Permittivity(target)	5.0	rectangular	•3	0.6	0.5	1.7	1.4
Liquid Permittivity(meas.)	6.1	normal	1	0.6	0.5	3.7	3.1
Combined Uncertainty		RSS				10.4	9.8
Combined Uncertainty (coverage factor=2)		Normal(k=2)				20.8	19.7

© 2005 RF Exposure Lab, LLC

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.



This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

SAR Test Report

Operator : Jay
Validation Date : 23-Nov-2005
Measurement Date : 23-Nov-2005
Starting Time : 23-Nov-2005 03:02:14 PM
End Time : 23-Nov-2005 03:17:29 PM
Scanning Time : 915 secs

Product Data
Device Name : Validation
Serial No. : 1900
Type : Dipole
Model : ALS-D-1900-S-2
Frequency : 1900.00 MHz
Max. Transmit Pwr : 0.1 W
Drift Time : 0 min(s)
Length : 68 mm
Width : 3.6 mm
Depth : 39.5 mm
Antenna Type : Internal
Power Drift-Start : 2.712 W/kg
Power Drift-Finish: 2.823 W/kg
Power Drift (%) : 4.773

Phantom Data
Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : System Default
Location : Center
Description : Uni-Phantom

Tissue Data
Type : BODY
Serial No. : 1900
Frequency : 1900 MHz
Last Calib. Date : 23-Nov-2005
Temperature : 21 °C
Ambient Temp. : 22 °C
Humidity : 40 RH%
Epsilon : 52.66 F/m
Sigma : 1.56 S/m
Density : 1000 kg/cu. m

Probe Data
Name : Probe 215 - RFEL
Model : E020
Type : E-Field Triangle
Serial No. : 215
Last Calib. Date : 10-Jun-2005
Frequency : 1900 MHz
Duty Cycle Factor: 1
Conversion Factor: 3.8
Probe Sensitivity: 1.20 1.20 1.20 $\mu V/(V/m)^2$
Compression Point: 95 mV
Offset : 1.56 mm

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

```
Measurement Data
Crest Factor      : 1
Scan Type         : Complete
Tissue Temp.      : 21°C
Ambient Temp.     : 22°C
Set-up Date       : 23-Nov-2005
Set-up Time       : 3:01:48 PM
Area Scan         : 5x6x1 : Measurement x=10mm, y=10mm, z=4mm
Zoom Scan         : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data
DUT Position      : Touch
Separation        : 0
Channel           : Mid - 1900
```



```
1 gram SAR value   : 4.206 W/kg
10 gram SAR value  : 2.190 W/kg
Area Scan Peak SAR : 4.812 W/kg
Zoom Scan Peak SAR : 7.796 W/kg
```

© 2005 RF Exposure Lab, LLC

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

Exposure Assessment Measurement Uncertainty

Source of Uncertainty	Tolerance Value	Probability Distribution	Divisor	c_i^1 (1-g)	c_i^1 (10-g)	Standard Uncertainty (1-g) %	Standard Uncertainty (10-g) %
Measurement System							
Probe Calibration	3.5	normal	1	1	1	3.5	3.5
Axial Isotropy	3.7	rectangular	•3	$(1-cp)^{1/2}$	$(1-cp)^{1/2}$	1.5	1.5
Hemispherical Isotropy	10.9	rectangular	•3	•cp	•cp	4.4	4.4
Boundary Effect	1.0	rectangular	•3	1	1	0.6	0.6
Linearity	4.7	rectangular	•3	1	1	2.7	2.7
Detection Limit	1.0	rectangular	•3	1	1	0.6	0.6
Readout Electronics	1.0	normal	1	1	1	1.0	1.0
Response Time	0.8	rectangular	•3	1	1	0.5	0.5
Integration Time	1.7	rectangular	•3	1	1	1.0	1.0
RF Ambient Condition	3.0	rectangular	•3	1	1	1.7	1.7
Probe Positioner Mech.	0.4	rectangular	•3	1	1	0.2	0.2
Restriction							
Probe Positioning with respect to Phantom Shell	2.9	rectangular	•3	1	1	1.7	1.7
Extrapolation and Integration	3.7	rectangular	•3	1	1	2.1	2.1
Test Sample Positioning	4.0	normal	1	1	1	4.0	4.0
Device Holder Uncertainty	2.0	normal	1	1	1	2.0	2.0
Drift of Output Power	0.0	rectangular	•3	1	1	0.0	0.0
Phantom and Setup							
Phantom Uncertainty(shape & thickness tolerance)	3.4	rectangular	•3	1	1	2.0	2.0
Liquid Conductivity(target)	5.0	rectangular	•3	0.7	0.5	2.0	1.4
Liquid Conductivity(meas.)	0.2	rectangular	•3	0.7	0.5	0.1	0.1
Liquid Permittivity(target)	2.0	rectangular	•3	0.6	0.5	0.7	0.6
Liquid Permittivity(meas.)	5.1	rectangular	•3	0.6	0.5	1.8	1.5
Combined Uncertainty		RSS				9.3	9.1
Combined Uncertainty (coverage factor=2)		Normal(k=2)				18.6	18.2

© 2005 RF Exposure Lab, LLC

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.



This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

Appendix B – SAR Test Data Plots

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

SAR Test Report

Operator : Jay
Validation Date : 23-Nov-2005
Measurement Date : 23-Nov-2005
Starting Time : 23-Nov-2005 12:26:12 PM
End Time : 23-Nov-2005 12:43:55 PM
Scanning Time : 1063 secs

Product Data
Device Name : Sendum
Serial No. : 3A137985
Type : Other
Model : OM200
Frequency : 835.00 MHz
Max. Transmit Pwr : 0.25 W
Drift Time : 0 min(s)
Length : 50 mm
Width : 87 mm
Depth : 35 mm
Antenna Type : Internal
Power Drift-Start : 0.371 W/kg
Power Drift-Finish: 0.363 W/kg
Power Drift (%) : -2.608

Phantom Data
Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : System Default
Location : Center
Description : Uni-Phantom

Tissue Data
Type : BODY
Serial No. : 835
Frequency : 835 MHz
Last Calib. Date : 23-Nov-2005
Temperature : 21 °C
Ambient Temp. : 22 °C
Humidity : 40 RH%
Epsilon : 54.64 F/m
Sigma : 0.96 S/m
Density : 1000 kg/cu. m

Probe Data
Name : Probe 215 - RFEL
Model : E020
Type : E-Field Triangle
Serial No. : 215
Last Calib. Date : 10-Jun-2005
Frequency : 835 MHz
Duty Cycle Factor: 1
Conversion Factor: 6.07
Probe Sensitivity: 1.20 1.20 1.20 $\mu V/(V/m)^2$
Compression Point: 95 mV
Offset : 1.56 mm

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

```
Measurement Data
Crest Factor      : 1
Scan Type         : Complete
Tissue Temp.      : 21°C
Ambient Temp.     : 23°C
Set-up Date       : 18-Nov-2005
Set-up Time       : 10:41:47 AM
Area Scan         : 7x6x1 : Measurement x=10mm, y=10mm, z=4mm
Zoom Scan         : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data
DUT Position      : Touch
Separation        : 0
Channel           : Mid - 384
```



```
1 gram SAR value   : 0.565 W/kg
10 gram SAR value  : 0.403 W/kg
Area Scan Peak SAR : 0.605 W/kg
Zoom Scan Peak SAR : 0.770 W/kg
```


This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

Exposure Assessment Measurement Uncertainty

Source of Uncertainty	Tolerance Value	Probability Distribution	Divisor	c_i^1 (1-g)	c_i^1 (10-g)	Standard Uncertainty (1-g) %	Standard Uncertainty (10-g) %
Measurement System							
Probe Calibration	3.5	normal	1	1	1	3.5	3.5
Axial Isotropy	3.7	rectangular	•3	$(1-cp)^{1/2}$	$(1-cp)^{1/2}$	1.5	1.5
Hemispherical Isotropy	10.9	rectangular	•3	•cp	•cp	4.4	4.4
Boundary Effect	1.0	rectangular	•3	1	1	0.6	0.6
Linearity	4.7	rectangular	•3	1	1	2.7	2.7
Detection Limit	1.0	rectangular	•3	1	1	0.6	0.6
Readout Electronics	1.0	normal	1	1	1	1.0	1.0
Response Time	0.8	rectangular	•3	1	1	0.5	0.5
Integration Time	1.7	rectangular	•3	1	1	1.0	1.0
RF Ambient Condition	3.0	rectangular	•3	1	1	1.7	1.7
Probe Positioner Mech.	0.4	rectangular	•3	1	1	0.2	0.2
Restriction							
Probe Positioning with respect to Phantom Shell	2.9	rectangular	•3	1	1	1.7	1.7
Extrapolation and Integration	3.7	rectangular	•3	1	1	2.1	2.1
Test Sample Positioning	4.0	normal	1	1	1	4.0	4.0
Device Holder Uncertainty	2.0	normal	1	1	1	2.0	2.0
Drift of Output Power	7.6	rectangular	•3	1	1	4.4	4.4
Phantom and Setup							
Phantom Uncertainty(shape & thickness tolerance)	3.4	rectangular	•3	1	1	2.0	2.0
Liquid Conductivity(target)	5.0	rectangular	•3	0.7	0.5	2.0	1.4
Liquid Conductivity(meas.)	4.3	normal	1	0.7	0.5	3.0	2.2
Liquid Permittivity(target)	5.0	rectangular	•3	0.6	0.5	1.7	1.4
Liquid Permittivity(meas.)	6.1	normal	1	0.6	0.5	3.7	3.1
Combined Uncertainty		RSS				11.3	10.8
Combined Uncertainty (coverage factor=2)		Normal(k=2)				22.6	21.5

© 2005 RF Exposure Lab, LLC

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.



This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

SAR Test Report

Operator : Jay
Validation Date : 23-Nov-2005
Measurement Date : 23-Nov-2005
Starting Time : 23-Nov-2005 01:57:07 PM
End Time : 23-Nov-2005 02:14:45 PM
Scanning Time : 1058 secs

Product Data
Device Name : Sendum
Serial No. : 3A137985
Type : Other
Model : OM200
Frequency : 835.00 MHz
Max. Transmit Pwr : 0.25 W
Drift Time : 0 min(s)
Length : 50 mm
Width : 87 mm
Depth : 35 mm
Antenna Type : Internal
Power Drift-Start : 0.710 W/kg
Power Drift-Finish: 0.705 W/kg
Power Drift (%) : -0.738

Phantom Data
Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : System Default
Location : Center
Description : Uni-Phantom

Tissue Data
Type : BODY
Serial No. : 835
Frequency : 835 MHz
Last Calib. Date : 23-Nov-2005
Temperature : 21 °C
Ambient Temp. : 22 °C
Humidity : 40 RH%
Epsilon : 54.64 F/m
Sigma : 0.96 S/m
Density : 1000 kg/cu. m

Probe Data
Name : Probe 215 - RFEL
Model : E020
Type : E-Field Triangle
Serial No. : 215
Last Calib. Date : 10-Jun-2005
Frequency : 835 MHz
Duty Cycle Factor: 1
Conversion Factor: 6.07
Probe Sensitivity: 1.20 1.20 1.20 $\mu V/(V/m)^2$
Compression Point: 95 mV
Offset : 1.56 mm

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

```
Measurement Data
Crest Factor      : 1
Scan Type         : Complete
Tissue Temp.      : 21°C
Ambient Temp.     : 22°C
Set-up Date       : 23-Nov-2005
Set-up Time       : 12:26:56 PM
Area Scan         : 7x6x1 : Measurement x=10mm, y=10mm, z=4mm
Zoom Scan         : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data
DUT Position      : Touch
Separation        : 0
Channel           : Low - 1013
```



```
1 gram SAR value    : 1.369 W/kg
10 gram SAR value   : 0.877 W/kg
Area Scan Peak SAR  : 1.596 W/kg
Zoom Scan Peak SAR  : 2.061 W/kg
```


This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

Exposure Assessment Measurement Uncertainty

Source of Uncertainty	Tolerance Value	Probability Distribution	Divisor	c_i^1 (1-g)	c_i^1 (10-g)	Standard Uncertainty (1-g) %	Standard Uncertainty (10-g) %
Measurement System							
Probe Calibration	3.5	normal	1	1	1	3.5	3.5
Axial Isotropy	3.7	rectangular	•3	$(1-cp)^{1/2}$	$(1-cp)^{1/2}$	1.5	1.5
Hemispherical Isotropy	10.9	rectangular	•3	•cp	•cp	4.4	4.4
Boundary Effect	1.0	rectangular	•3	1	1	0.6	0.6
Linearity	4.7	rectangular	•3	1	1	2.7	2.7
Detection Limit	1.0	rectangular	•3	1	1	0.6	0.6
Readout Electronics	1.0	normal	1	1	1	1.0	1.0
Response Time	0.8	rectangular	•3	1	1	0.5	0.5
Integration Time	1.7	rectangular	•3	1	1	1.0	1.0
RF Ambient Condition	3.0	rectangular	•3	1	1	1.7	1.7
Probe Positioner Mech.	0.4	rectangular	•3	1	1	0.2	0.2
Restriction							
Probe Positioning with respect to Phantom Shell	2.9	rectangular	•3	1	1	1.7	1.7
Extrapolation and Integration	3.7	rectangular	•3	1	1	2.1	2.1
Test Sample Positioning	4.0	normal	1	1	1	4.0	4.0
Device Holder Uncertainty	2.0	normal	1	1	1	2.0	2.0
Drift of Output Power	14.7	rectangular	•3	1	1	8.5	8.5
Phantom and Setup							
Phantom Uncertainty(shape & thickness tolerance)	3.4	rectangular	•3	1	1	2.0	2.0
Liquid Conductivity(target)	5.0	rectangular	•3	0.7	0.5	2.0	1.4
Liquid Conductivity(meas.)	4.3	normal	1	0.7	0.5	3.0	2.2
Liquid Permittivity(target)	5.0	rectangular	•3	0.6	0.5	1.7	1.4
Liquid Permittivity(meas.)	6.1	normal	1	0.6	0.5	3.7	3.1
Combined Uncertainty		RSS				13.4	13.0
Combined Uncertainty (coverage factor=2)		Normal(k=2)				26.8	26.0

© 2005 RF Exposure Lab, LLC

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.



This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

SAR Test Report

Operator : Jay
Validation Date : 23-Nov-2005
Measurement Date : 23-Nov-2005
Starting Time : 23-Nov-2005 12:50:04 PM
End Time : 23-Nov-2005 01:07:37 PM
Scanning Time : 1053 secs

Product Data
Device Name : Sendum
Serial No. : 3A137985
Type : Other
Model : OM200
Frequency : 835.00 MHz
Max. Transmit Pwr : 0.25 W
Drift Time : 0 min(s)
Length : 50 mm
Width : 87 mm
Depth : 35 mm
Antenna Type : Internal
Power Drift-Start : 0.615 W/kg
Power Drift-Finish: 0.627 W/kg
Power Drift (%) : 1.290

Phantom Data
Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : System Default
Location : Center
Description : Uni-Phantom

Tissue Data
Type : BODY
Serial No. : 835
Frequency : 835 MHz
Last Calib. Date : 23-Nov-2005
Temperature : 21 °C
Ambient Temp. : 22 °C
Humidity : 40 RH%
Epsilon : 54.64 F/m
Sigma : 0.96 S/m
Density : 1000 kg/cu. m

Probe Data
Name : Probe 215 - RFEL
Model : E020
Type : E-Field Triangle
Serial No. : 215
Last Calib. Date : 10-Jun-2005
Frequency : 835 MHz
Duty Cycle Factor: 1
Conversion Factor: 6.07
Probe Sensitivity: 1.20 1.20 1.20 $\mu V/(V/m)^2$
Compression Point: 95 mV
Offset : 1.56 mm

© 2005 RF Exposure Lab, LLC

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

```
Measurement Data
Crest Factor      : 1
Scan Type         : Complete
Tissue Temp.      : 21°C
Ambient Temp.     : 22°C
Set-up Date       : 23-Nov-2005
Set-up Time       : 12:26:56 PM
Area Scan         : 7x6x1 : Measurement x=10mm, y=10mm, z=4mm
Zoom Scan         : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data
DUT Position      : Touch
Separation        : 0
Channel           : Mid - 384
```



```
1 gram SAR value    : 1.104 W/kg
10 gram SAR value   : 0.717 W/kg
Area Scan Peak SAR  : 1.286 W/kg
Zoom Scan Peak SAR  : 1.601 W/kg
```


This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

Exposure Assessment Measurement Uncertainty

Source of Uncertainty	Tolerance Value	Probability Distribution	Divisor	c_i^1 (1-g)	c_i^1 (10-g)	Standard Uncertainty (1-g) %	Standard Uncertainty (10-g) %
Measurement System							
Probe Calibration	3.5	normal	1	1	1	3.5	3.5
Axial Isotropy	3.7	rectangular	•3	$(1-cp)^{1/2}$	$(1-cp)^{1/2}$	1.5	1.5
Hemispherical Isotropy	10.9	rectangular	•3	•cp	•cp	4.4	4.4
Boundary Effect	1.0	rectangular	•3	1	1	0.6	0.6
Linearity	4.7	rectangular	•3	1	1	2.7	2.7
Detection Limit	1.0	rectangular	•3	1	1	0.6	0.6
Readout Electronics	1.0	normal	1	1	1	1.0	1.0
Response Time	0.8	rectangular	•3	1	1	0.5	0.5
Integration Time	1.7	rectangular	•3	1	1	1.0	1.0
RF Ambient Condition	3.0	rectangular	•3	1	1	1.7	1.7
Probe Positioner Mech.	0.4	rectangular	•3	1	1	0.2	0.2
Restriction							
Probe Positioning with respect to Phantom Shell	2.9	rectangular	•3	1	1	1.7	1.7
Extrapolation and Integration	3.7	rectangular	•3	1	1	2.1	2.1
Test Sample Positioning	4.0	normal	1	1	1	4.0	4.0
Device Holder Uncertainty	2.0	normal	1	1	1	2.0	2.0
Drift of Output Power	14.3	rectangular	•3	1	1	8.3	8.3
Phantom and Setup							
Phantom Uncertainty(shape & thickness tolerance)	3.4	rectangular	•3	1	1	2.0	2.0
Liquid Conductivity(target)	5.0	rectangular	•3	0.7	0.5	2.0	1.4
Liquid Conductivity(meas.)	4.3	normal	1	0.7	0.5	3.0	2.2
Liquid Permittivity(target)	5.0	rectangular	•3	0.6	0.5	1.7	1.4
Liquid Permittivity(meas.)	6.1	normal	1	0.6	0.5	3.7	3.1
Combined Uncertainty		RSS				13.3	12.9
Combined Uncertainty (coverage factor=2)		Normal(k=2)				26.6	25.7

© 2005 RF Exposure Lab, LLC

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.



This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

SAR Test Report

Operator : Jay
Validation Date : 23-Nov-2005
Measurement Date : 23-Nov-2005
Starting Time : 23-Nov-2005 02:17:25 PM
End Time : 23-Nov-2005 02:34:51 PM
Scanning Time : 1046 secs

Product Data
Device Name : Sendum
Serial No. : 3A137985
Type : Other
Model : OM200
Frequency : 835.00 MHz
Max. Transmit Pwr : 0.25 W
Drift Time : 0 min(s)
Length : 50 mm
Width : 87 mm
Depth : 35 mm
Antenna Type : Internal
Power Drift-Start : 0.467 W/kg
Power Drift-Finish: 0.431 W/kg
Power Drift (%) : -7.715

Phantom Data
Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : System Default
Location : Center
Description : Uni-Phantom

Tissue Data
Type : BODY
Serial No. : 835
Frequency : 835 MHz
Last Calib. Date : 23-Nov-2005
Temperature : 21 °C
Ambient Temp. : 22 °C
Humidity : 40 RH%
Epsilon : 54.64 F/m
Sigma : 0.96 S/m
Density : 1000 kg/cu. m

Probe Data
Name : Probe 215 - RFEL
Model : E020
Type : E-Field Triangle
Serial No. : 215
Last Calib. Date : 10-Jun-2005
Frequency : 835 MHz
Duty Cycle Factor: 1
Conversion Factor: 6.07
Probe Sensitivity: 1.20 1.20 1.20 $\mu V/(V/m)^2$
Compression Point: 95 mV
Offset : 1.56 mm

© 2005 RF Exposure Lab, LLC

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

```
Measurement Data
Crest Factor      : 1
Scan Type         : Complete
Tissue Temp.      : 21°C
Ambient Temp.     : 22°C
Set-up Date       : 23-Nov-2005
Set-up Time       : 12:26:56 PM
Area Scan         : 7x6x1 : Measurement x=10mm, y=10mm, z=4mm
Zoom Scan         : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data
DUT Position      : Touch
Separation        : 0
Channel           : High - 777
```



```
1 gram SAR value    : 1.177 W/kg
10 gram SAR value   : 0.756 W/kg
Area Scan Peak SAR  : 1.338 W/kg
Zoom Scan Peak SAR  : 1.711 W/kg
```


This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

Exposure Assessment Measurement Uncertainty

Source of Uncertainty	Tolerance Value	Probability Distribution	Divisor	c_i^1 (1-g)	c_i^1 (10-g)	Standard Uncertainty (1-g) %	Standard Uncertainty (10-g) %
Measurement System							
Probe Calibration	3.5	normal	1	1	1	3.5	3.5
Axial Isotropy	3.7	rectangular	•3	$(1-cp)^{1/2}$	$(1-cp)^{1/2}$	1.5	1.5
Hemispherical Isotropy	10.9	rectangular	•3	•cp	•cp	4.4	4.4
Boundary Effect	1.0	rectangular	•3	1	1	0.6	0.6
Linearity	4.7	rectangular	•3	1	1	2.7	2.7
Detection Limit	1.0	rectangular	•3	1	1	0.6	0.6
Readout Electronics	1.0	normal	1	1	1	1.0	1.0
Response Time	0.8	rectangular	•3	1	1	0.5	0.5
Integration Time	1.7	rectangular	•3	1	1	1.0	1.0
RF Ambient Condition	3.0	rectangular	•3	1	1	1.7	1.7
Probe Positioner Mech.	0.4	rectangular	•3	1	1	0.2	0.2
Restriction							
Probe Positioning with respect to Phantom Shell	2.9	rectangular	•3	1	1	1.7	1.7
Extrapolation and Integration	3.7	rectangular	•3	1	1	2.1	2.1
Test Sample Positioning	4.0	normal	1	1	1	4.0	4.0
Device Holder Uncertainty	2.0	normal	1	1	1	2.0	2.0
Drift of Output Power	7.7	rectangular	•3	1	1	4.5	4.5
Phantom and Setup							
Phantom Uncertainty(shape & thickness tolerance)	3.4	rectangular	•3	1	1	2.0	2.0
Liquid Conductivity(target)	5.0	rectangular	•3	0.7	0.5	2.0	1.4
Liquid Conductivity(meas.)	4.3	normal	1	0.7	0.5	3.0	2.2
Liquid Permittivity(target)	5.0	rectangular	•3	0.6	0.5	1.7	1.4
Liquid Permittivity(meas.)	6.1	normal	1	0.6	0.5	3.7	3.1
Combined Uncertainty		RSS				11.3	10.8
Combined Uncertainty (coverage factor=2)		Normal(k=2)				22.6	21.6

© 2005 RF Exposure Lab, LLC

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.



This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

SAR Test Report

Operator : Jay
Validation Date : 23-Nov-2005
Measurement Date : 23-Nov-2005
Starting Time : 23-Nov-2005 01:21:35 PM
End Time : 23-Nov-2005 01:36:46 PM
Scanning Time : 911 secs

Product Data
Device Name : Sendum
Serial No. : 3A137985
Type : Other
Model : OM200
Frequency : 835.00 MHz
Max. Transmit Pwr : 0.25 W
Drift Time : 0 min(s)
Length : 50 mm
Width : 35 mm
Depth : 87 mm
Antenna Type : Internal
Power Drift-Start : 0.147 W/kg
Power Drift-Finish: 0.140 W/kg
Power Drift (%) : -5.273

Phantom Data
Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : System Default
Location : Center
Description : Uni-Phantom

Tissue Data
Type : BODY
Serial No. : 835
Frequency : 835 MHz
Last Calib. Date : 23-Nov-2005
Temperature : 21 °C
Ambient Temp. : 22 °C
Humidity : 40 RH%
Epsilon : 54.64 F/m
Sigma : 0.96 S/m
Density : 1000 kg/cu. m

Probe Data
Name : Probe 215 - RFEL
Model : E020
Type : E-Field Triangle
Serial No. : 215
Last Calib. Date : 10-Jun-2005
Frequency : 835 MHz
Duty Cycle Factor: 1
Conversion Factor: 6.07
Probe Sensitivity: 1.20 1.20 1.20 $\mu V/(V/m)^2$
Compression Point: 95 mV
Offset : 1.56 mm

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

```
Measurement Data
Crest Factor      : 1
Scan Type         : Complete
Tissue Temp.      : 21°C
Ambient Temp.     : 22°C
Set-up Date       : 23-Nov-2005
Set-up Time       : 1:21:24 PM
Area Scan         : 6x5x1 : Measurement x=10mm, y=10mm, z=4mm
Zoom Scan         : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data
DUT Position      : Touch
Separation        : 0
Channel           : Mid - 384
```



```
1 gram SAR value    : 0.265 W/kg
10 gram SAR value   : 0.147 W/kg
Area Scan Peak SAR  : 0.301 W/kg
Zoom Scan Peak SAR  : 0.500 W/kg
```


This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

Exposure Assessment Measurement Uncertainty

Source of Uncertainty	Tolerance Value	Probability Distribution	Divisor	c_i^1 (1-g)	c_i^1 (10-g)	Standard Uncertainty (1-g) %	Standard Uncertainty (10-g) %
Measurement System							
Probe Calibration	3.5	normal	1	1	1	3.5	3.5
Axial Isotropy	3.7	rectangular	•3	$(1-cp)^{1/2}$	$(1-cp)^{1/2}$	1.5	1.5
Hemispherical Isotropy	10.9	rectangular	•3	•cp	•cp	4.4	4.4
Boundary Effect	1.0	rectangular	•3	1	1	0.6	0.6
Linearity	4.7	rectangular	•3	1	1	2.7	2.7
Detection Limit	1.0	rectangular	•3	1	1	0.6	0.6
Readout Electronics	1.0	normal	1	1	1	1.0	1.0
Response Time	0.8	rectangular	•3	1	1	0.5	0.5
Integration Time	1.7	rectangular	•3	1	1	1.0	1.0
RF Ambient Condition	3.0	rectangular	•3	1	1	1.7	1.7
Probe Positioner Mech.	0.4	rectangular	•3	1	1	0.2	0.2
Restriction							
Probe Positioning with respect to Phantom Shell	2.9	rectangular	•3	1	1	1.7	1.7
Extrapolation and Integration	3.7	rectangular	•3	1	1	2.1	2.1
Test Sample Positioning	4.0	normal	1	1	1	4.0	4.0
Device Holder Uncertainty	2.0	normal	1	1	1	2.0	2.0
Drift of Output Power	5.3	rectangular	•3	1	1	3.0	3.0
Phantom and Setup							
Phantom Uncertainty(shape & thickness tolerance)	3.4	rectangular	•3	1	1	2.0	2.0
Liquid Conductivity(target)	5.0	rectangular	•3	0.7	0.5	2.0	1.4
Liquid Conductivity(meas.)	4.3	normal	1	0.7	0.5	3.0	2.2
Liquid Permittivity(target)	5.0	rectangular	•3	0.6	0.5	1.7	1.4
Liquid Permittivity(meas.)	6.1	normal	1	0.6	0.5	3.7	3.1
Combined Uncertainty		RSS				10.8	10.3
Combined Uncertainty (coverage factor=2)		Normal(k=2)				21.6	20.6

© 2005 RF Exposure Lab, LLC

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.



This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

SAR Test Report

Operator : Jay
Validation Date : 23-Nov-2005
Measurement Date : 23-Nov-2005
Starting Time : 23-Nov-2005 04:03:08 PM
End Time : 23-Nov-2005 04:20:54 PM
Scanning Time : 1066 secs

Product Data
Device Name : Sendum
Serial No. : 3A137985
Type : Other
Model : OM200
Frequency : 1900.00 MHz
Max. Transmit Pwr : 0.25 W
Drift Time : 0 min(s)
Length : 50 mm
Width : 87 mm
Depth : 35 mm
Antenna Type : Internal
Power Drift-Start : 0.355 W/kg
Power Drift-Finish: 0.371 W/kg
Power Drift (%) : 4.427

Phantom Data
Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : System Default
Location : Center
Description : Uni-Phantom

Tissue Data
Type : BODY
Serial No. : 1900
Frequency : 1900 MHz
Last Calib. Date : 23-Nov-2005
Temperature : 21 °C
Ambient Temp. : 22 °C
Humidity : 40 RH%
Epsilon : 52.66 F/m
Sigma : 1.56 S/m
Density : 1000 kg/cu. m

Probe Data
Name : Probe 215 - RFEL
Model : E020
Type : E-Field Triangle
Serial No. : 215
Last Calib. Date : 10-Jun-2005
Frequency : 1900 MHz
Duty Cycle Factor: 1
Conversion Factor: 3.8
Probe Sensitivity: 1.20 1.20 1.20 $\mu V/(V/m)^2$
Compression Point: 95 mV
Offset : 1.56 mm

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

Measurement Data
Crest Factor : 1
Scan Type : Complete
Tissue Temp. : 21°C
Ambient Temp. : 22°C
Set-up Date : 23-Nov-2005
Set-up Time : 4:02:40 PM
Area Scan : 7x6x1 : Measurement x=10mm, y=10mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data
DUT Position : Touch
Separation : 0
Channel : Mid - 600



1 gram SAR value : 0.584 W/kg
10 gram SAR value : 0.369 W/kg
Area Scan Peak SAR : 0.616 W/kg
Zoom Scan Peak SAR : 0.890 W/kg

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

Exposure Assessment Measurement Uncertainty

Source of Uncertainty	Tolerance Value	Probability Distribution	Divisor	c_i^1 (1-g)	c_i^1 (10-g)	Standard Uncertainty (1-g) %	Standard Uncertainty (10-g) %
Measurement System							
Probe Calibration	3.5	normal	1	1	1	3.5	3.5
Axial Isotropy	3.7	rectangular	•3	$(1-cp)^{1/2}$	$(1-cp)^{1/2}$	1.5	1.5
Hemispherical Isotropy	10.9	rectangular	•3	•cp	•cp	4.4	4.4
Boundary Effect	1.0	rectangular	•3	1	1	0.6	0.6
Linearity	4.7	rectangular	•3	1	1	2.7	2.7
Detection Limit	1.0	rectangular	•3	1	1	0.6	0.6
Readout Electronics	1.0	normal	1	1	1	1.0	1.0
Response Time	0.8	rectangular	•3	1	1	0.5	0.5
Integration Time	1.7	rectangular	•3	1	1	1.0	1.0
RF Ambient Condition	3.0	rectangular	•3	1	1	1.7	1.7
Probe Positioner Mech.	0.4	rectangular	•3	1	1	0.2	0.2
Restriction							
Probe Positioning with respect to Phantom Shell	2.9	rectangular	•3	1	1	2.1	2.1
Extrapolation and Integration	3.7	rectangular	•3	1	1	2.1	2.1
Test Sample Positioning	4.0	normal	1	1	1	4.0	4.0
Device Holder Uncertainty	2.0	normal	1	1	1	2.0	2.0
Drift of Output Power	0.0	rectangular	•3	1	1	0.0	0.0
Phantom and Setup							
Phantom Uncertainty(shape & thickness tolerance)	3.4	rectangular	•3	1	1	2.0	2.0
Liquid Conductivity(target)	13.0	rectangular	•3	0.7	0.5	5.3	3.8
Liquid Conductivity(meas.)	0.1	rectangular	•3	0.7	0.5	0.1	0.0
Liquid Permittivity(target)	2.0	rectangular	•3	0.6	0.5	0.8	0.6
Liquid Permittivity(meas.)	3.9	rectangular	•3	0.6	0.5	1.4	1.1
Combined Uncertainty		RSS				10.3	9.5
Combined Uncertainty (coverage factor=2)		Normal(k=2)				20.6	19.1

© 2005 RF Exposure Lab, LLC

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.



This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

SAR Test Report

Operator : Jay
Validation Date : 23-Nov-2005
Measurement Date : 23-Nov-2005
Starting Time : 23-Nov-2005 05:03:51 PM
End Time : 23-Nov-2005 05:21:23 PM
Scanning Time : 1052 secs

Product Data
Device Name : Sendum
Serial No. : 3A137985
Type : Other
Model : OM200
Frequency : 1900.00 MHz
Max. Transmit Pwr : 0.25 W
Drift Time : 0 min(s)
Length : 50 mm
Width : 87 mm
Depth : 35 mm
Antenna Type : Internal
Power Drift-Start : 0.399 W/kg
Power Drift-Finish: 0.387 W/kg
Power Drift (%) : -3.856

Phantom Data
Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : System Default
Location : Center
Description : Uni-Phantom

Tissue Data
Type : BODY
Serial No. : 1900
Frequency : 1900 MHz
Last Calib. Date : 23-Nov-2005
Temperature : 21 °C
Ambient Temp. : 22 °C
Humidity : 40 RH%
Epsilon : 52.66 F/m
Sigma : 1.56 S/m
Density : 1000 kg/cu. m

Probe Data
Name : Probe 215 - RFEL
Model : E020
Type : E-Field Triangle
Serial No. : 215
Last Calib. Date : 10-Jun-2005
Frequency : 1900 MHz
Duty Cycle Factor: 1
Conversion Factor: 3.8
Probe Sensitivity: 1.20 1.20 1.20 $\mu V/(V/m)^2$
Compression Point: 95 mV
Offset : 1.56 mm

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

```
Measurement Data
Crest Factor      : 1
Scan Type         : Complete
Tissue Temp.      : 21°C
Ambient Temp.     : 22°C
Set-up Date       : 23-Nov-2005
Set-up Time       : 4:02:40 PM
Area Scan         : 7x6x1 : Measurement x=10mm, y=10mm, z=4mm
Zoom Scan         : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data
DUT Position      : Touch
Separation        : 0
Channel           : Low - 25
```



```
1 gram SAR value    : 1.298 W/kg
10 gram SAR value   : 0.788 W/kg
Area Scan Peak SAR  : 1.479 W/kg
Zoom Scan Peak SAR  : 1.951 W/kg
```


This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

Exposure Assessment Measurement Uncertainty

Source of Uncertainty	Tolerance Value	Probability Distribution	Divisor	c_i^1 (1-g)	c_i^1 (10-g)	Standard Uncertainty (1-g) %	Standard Uncertainty (10-g) %
Measurement System							
Probe Calibration	3.5	normal	1	1	1	3.5	3.5
Axial Isotropy	3.7	rectangular	•3	$(1-cp)^{1/2}$	$(1-cp)^{1/2}$	1.5	1.5
Hemispherical Isotropy	10.9	rectangular	•3	•cp	•cp	4.4	4.4
Boundary Effect	1.0	rectangular	•3	1	1	0.6	0.6
Linearity	4.7	rectangular	•3	1	1	2.7	2.7
Detection Limit	1.0	rectangular	•3	1	1	0.6	0.6
Readout Electronics	1.0	normal	1	1	1	1.0	1.0
Response Time	0.8	rectangular	•3	1	1	0.5	0.5
Integration Time	1.7	rectangular	•3	1	1	1.0	1.0
RF Ambient Condition	3.0	rectangular	•3	1	1	1.7	1.7
Probe Positioner Mech.	0.4	rectangular	•3	1	1	0.2	0.2
Restriction							
Probe Positioning with respect to Phantom Shell	2.9	rectangular	•3	1	1	2.1	2.1
Extrapolation and Integration	3.7	rectangular	•3	1	1	2.1	2.1
Test Sample Positioning	4.0	normal	1	1	1	4.0	4.0
Device Holder Uncertainty	2.0	normal	1	1	1	2.0	2.0
Drift of Output Power	0.0	rectangular	•3	1	1	0.0	0.0
Phantom and Setup							
Phantom Uncertainty(shape & thickness tolerance)	3.4	rectangular	•3	1	1	2.0	2.0
Liquid Conductivity(target)	13.0	rectangular	•3	0.7	0.5	5.3	3.8
Liquid Conductivity(meas.)	0.1	rectangular	•3	0.7	0.5	0.1	0.0
Liquid Permittivity(target)	2.0	rectangular	•3	0.6	0.5	0.8	0.6
Liquid Permittivity(meas.)	3.9	rectangular	•3	0.6	0.5	1.4	1.1
Combined Uncertainty		RSS				10.3	9.5
Combined Uncertainty (coverage factor=2)		Normal(k=2)				20.6	19.1

© 2005 RF Exposure Lab, LLC

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.



This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

SAR Test Report

Operator : Jay
Validation Date : 23-Nov-2005
Measurement Date : 23-Nov-2005
Starting Time : 23-Nov-2005 04:42:25 PM
End Time : 23-Nov-2005 05:00:12 PM
Scanning Time : 1067 secs

Product Data
Device Name : Sendum
Serial No. : 3A137985
Type : Other
Model : OM200
Frequency : 1900.00 MHz
Max. Transmit Pwr : 0.25 W
Drift Time : 0 min(s)
Length : 50 mm
Width : 87 mm
Depth : 35 mm
Antenna Type : Internal
Power Drift-Start : 0.701 W/kg
Power Drift-Finish: 0.681 W/kg
Power Drift (%) : -2.824

Phantom Data
Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : System Default
Location : Center
Description : Uni-Phantom

Tissue Data
Type : BODY
Serial No. : 1900
Frequency : 1900 MHz
Last Calib. Date : 23-Nov-2005
Temperature : 21 °C
Ambient Temp. : 22 °C
Humidity : 40 RH%
Epsilon : 52.66 F/m
Sigma : 1.56 S/m
Density : 1000 kg/cu. m

Probe Data
Name : Probe 215 - RFEL
Model : E020
Type : E-Field Triangle
Serial No. : 215
Last Calib. Date : 10-Jun-2005
Frequency : 1900 MHz
Duty Cycle Factor: 1
Conversion Factor: 3.8
Probe Sensitivity: 1.20 1.20 1.20 $\mu V/(V/m)^2$
Compression Point: 95 mV
Offset : 1.56 mm

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

```
Measurement Data
Crest Factor      : 1
Scan Type         : Complete
Tissue Temp.      : 21°C
Ambient Temp.     : 22°C
Set-up Date       : 23-Nov-2005
Set-up Time       : 4:02:40 PM
Area Scan         : 7x6x1 : Measurement x=10mm, y=10mm, z=4mm
Zoom Scan         : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data
DUT Position      : Touch
Separation        : 0
Channel           : Mid - 600
```



```
1 gram SAR value    : 1.982 W/kg
10 gram SAR value   : 1.175 W/kg
Area Scan Peak SAR  : 2.394 W/kg
Zoom Scan Peak SAR  : 3.052 W/kg
```


This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

Exposure Assessment Measurement Uncertainty

Source of Uncertainty	Tolerance Value	Probability Distribution	Divisor	c_i^1 (1-g)	c_i^1 (10-g)	Standard Uncertainty (1-g) %	Standard Uncertainty (10-g) %
Measurement System							
Probe Calibration	3.5	normal	1	1	1	3.5	3.5
Axial Isotropy	3.7	rectangular	•3	$(1-cp)^{1/2}$	$(1-cp)^{1/2}$	1.5	1.5
Hemispherical Isotropy	10.9	rectangular	•3	•cp	•cp	4.4	4.4
Boundary Effect	1.0	rectangular	•3	1	1	0.6	0.6
Linearity	4.7	rectangular	•3	1	1	2.7	2.7
Detection Limit	1.0	rectangular	•3	1	1	0.6	0.6
Readout Electronics	1.0	normal	1	1	1	1.0	1.0
Response Time	0.8	rectangular	•3	1	1	0.5	0.5
Integration Time	1.7	rectangular	•3	1	1	1.0	1.0
RF Ambient Condition	3.0	rectangular	•3	1	1	1.7	1.7
Probe Positioner Mech.	0.4	rectangular	•3	1	1	0.2	0.2
Restriction							
Probe Positioning with respect to Phantom Shell	2.9	rectangular	•3	1	1	2.1	2.1
Extrapolation and Integration	3.7	rectangular	•3	1	1	2.1	2.1
Test Sample Positioning	4.0	normal	1	1	1	4.0	4.0
Device Holder Uncertainty	2.0	normal	1	1	1	2.0	2.0
Drift of Output Power	0.0	rectangular	•3	1	1	0.0	0.0
Phantom and Setup							
Phantom Uncertainty(shape & thickness tolerance)	3.4	rectangular	•3	1	1	2.0	2.0
Liquid Conductivity(target)	13.0	rectangular	•3	0.7	0.5	5.3	3.8
Liquid Conductivity(meas.)	0.1	rectangular	•3	0.7	0.5	0.1	0.0
Liquid Permittivity(target)	2.0	rectangular	•3	0.6	0.5	0.8	0.6
Liquid Permittivity(meas.)	3.9	rectangular	•3	0.6	0.5	1.4	1.1
Combined Uncertainty		RSS				10.3	9.5
Combined Uncertainty (coverage factor=2)		Normal(k=2)				20.6	19.1

© 2005 RF Exposure Lab, LLC

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.



This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

SAR Test Report

Operator : Jay
Validation Date : 23-Nov-2005
Measurement Date : 23-Nov-2005
Starting Time : 23-Nov-2005 05:23:54 PM
End Time : 23-Nov-2005 05:41:34 PM
Scanning Time : 1060 secs

Product Data
Device Name : Sendum
Serial No. : 3A137985
Type : Other
Model : OM200
Frequency : 1900.00 MHz
Max. Transmit Pwr : 0.25 W
Drift Time : 0 min(s)
Length : 50 mm
Width : 87 mm
Depth : 35 mm
Antenna Type : Internal
Power Drift-Start : 0.453 W/kg
Power Drift-Finish: 0.439 W/kg
Power Drift (%) : -3.923

Phantom Data
Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : System Default
Location : Center
Description : Uni-Phantom

Tissue Data
Type : BODY
Serial No. : 1900
Frequency : 1900 MHz
Last Calib. Date : 23-Nov-2005
Temperature : 21 °C
Ambient Temp. : 22 °C
Humidity : 40 RH%
Epsilon : 52.66 F/m
Sigma : 1.56 S/m
Density : 1000 kg/cu. m

Probe Data
Name : Probe 215 - RFEL
Model : E020
Type : E-Field Triangle
Serial No. : 215
Last Calib. Date : 10-Jun-2005
Frequency : 1900 MHz
Duty Cycle Factor: 1
Conversion Factor: 3.8
Probe Sensitivity: 1.20 1.20 1.20 $\mu V/(V/m)^2$
Compression Point: 95 mV
Offset : 1.56 mm

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

```
Measurement Data
Crest Factor      : 1
Scan Type         : Complete
Tissue Temp.      : 21°C
Ambient Temp.     : 22°C
Set-up Date       : 23-Nov-2005
Set-up Time       : 4:02:40 PM
Area Scan         : 7x6x1 : Measurement x=10mm, y=10mm, z=4mm
Zoom Scan         : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data
DUT Position      : Touch
Separation        : 0
Channel           : High - 1175
```



```
1 gram SAR value    : 1.518 W/kg
10 gram SAR value   : 0.893 W/kg
Area Scan Peak SAR  : 1.737 W/kg
Zoom Scan Peak SAR  : 2.372 W/kg
```


This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

Exposure Assessment Measurement Uncertainty

Source of Uncertainty	Tolerance Value	Probability Distribution	Divisor	c_i^1 (1-g)	c_i^1 (10-g)	Standard Uncertainty (1-g) %	Standard Uncertainty (10-g) %
Measurement System							
Probe Calibration	3.5	normal	1	1	1	3.5	3.5
Axial Isotropy	3.7	rectangular	•3	$(1-cp)^{1/2}$	$(1-cp)^{1/2}$	1.5	1.5
Hemispherical Isotropy	10.9	rectangular	•3	•cp	•cp	4.4	4.4
Boundary Effect	1.0	rectangular	•3	1	1	0.6	0.6
Linearity	4.7	rectangular	•3	1	1	2.7	2.7
Detection Limit	1.0	rectangular	•3	1	1	0.6	0.6
Readout Electronics	1.0	normal	1	1	1	1.0	1.0
Response Time	0.8	rectangular	•3	1	1	0.5	0.5
Integration Time	1.7	rectangular	•3	1	1	1.0	1.0
RF Ambient Condition	3.0	rectangular	•3	1	1	1.7	1.7
Probe Positioner Mech.	0.4	rectangular	•3	1	1	0.2	0.2
Restriction							
Probe Positioning with respect to Phantom Shell	2.9	rectangular	•3	1	1	2.1	2.1
Extrapolation and Integration	3.7	rectangular	•3	1	1	2.1	2.1
Test Sample Positioning	4.0	normal	1	1	1	4.0	4.0
Device Holder Uncertainty	2.0	normal	1	1	1	2.0	2.0
Drift of Output Power	0.0	rectangular	•3	1	1	0.0	0.0
Phantom and Setup							
Phantom Uncertainty(shape & thickness tolerance)	3.4	rectangular	•3	1	1	2.0	2.0
Liquid Conductivity(target)	13.0	rectangular	•3	0.7	0.5	5.3	3.8
Liquid Conductivity(meas.)	0.1	rectangular	•3	0.7	0.5	0.1	0.0
Liquid Permittivity(target)	2.0	rectangular	•3	0.6	0.5	0.8	0.6
Liquid Permittivity(meas.)	3.9	rectangular	•3	0.6	0.5	1.4	1.1
Combined Uncertainty		RSS				10.3	9.5
Combined Uncertainty (coverage factor=2)		Normal(k=2)				20.6	19.1

© 2005 RF Exposure Lab, LLC

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.



This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

SAR Test Report

Operator : Jay
Validation Date : 23-Nov-2005
Measurement Date : 23-Nov-2005
Starting Time : 23-Nov-2005 03:43:06 PM
End Time : 23-Nov-2005 03:58:24 PM
Scanning Time : 918 secs

Product Data
Device Name : Sendum
Serial No. : 3A137985
Type : Other
Model : OM200
Frequency : 1900.00 MHz
Max. Transmit Pwr : 0.25 W
Drift Time : 0 min(s)
Length : 50 mm
Width : 35 mm
Depth : 87 mm
Antenna Type : Internal
Power Drift-Start : 0.500 W/kg
Power Drift-Finish: 0.515 W/kg
Power Drift (%) : 2.906

Phantom Data
Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : System Default
Location : Center
Description : Uni-Phantom

Tissue Data
Type : BODY
Serial No. : 1900
Frequency : 1900 MHz
Last Calib. Date : 23-Nov-2005
Temperature : 21 °C
Ambient Temp. : 22 °C
Humidity : 40 RH%
Epsilon : 52.66 F/m
Sigma : 1.56 S/m
Density : 1000 kg/cu. m

Probe Data
Name : Probe 215 - RFEL
Model : E020
Type : E-Field Triangle
Serial No. : 215
Last Calib. Date : 10-Jun-2005
Frequency : 1900 MHz
Duty Cycle Factor: 1
Conversion Factor: 3.8
Probe Sensitivity: 1.20 1.20 1.20 $\mu V/(V/m)^2$
Compression Point: 95 mV
Offset : 1.56 mm

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

```
Measurement Data
Crest Factor      : 1
Scan Type         : Complete
Tissue Temp.      : 21°C
Ambient Temp.     : 22°C
Set-up Date       : 23-Nov-2005
Set-up Time       : 3:20:17 PM
Area Scan         : 6x5x1 : Measurement x=10mm, y=10mm, z=4mm
Zoom Scan         : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data
DUT Position      : Touch
Separation        : 0
Channel           : Mid - 600
```



```
1 gram SAR value    : 0.628 W/kg
10 gram SAR value   : 0.335 W/kg
Area Scan Peak SAR  : 0.772 W/kg
Zoom Scan Peak SAR  : 1.111 W/kg
```


This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

Exposure Assessment Measurement Uncertainty

Source of Uncertainty	Tolerance Value	Probability Distribution	Divisor	c_i^1 (1-g)	c_i^1 (10-g)	Standard Uncertainty (1-g) %	Standard Uncertainty (10-g) %
Measurement System							
Probe Calibration	3.5	normal	1	1	1	3.5	3.5
Axial Isotropy	3.7	rectangular	•3	$(1-cp)^{1/2}$	$(1-cp)^{1/2}$	1.5	1.5
Hemispherical Isotropy	10.9	rectangular	•3	•cp	•cp	4.4	4.4
Boundary Effect	1.0	rectangular	•3	1	1	0.6	0.6
Linearity	4.7	rectangular	•3	1	1	2.7	2.7
Detection Limit	1.0	rectangular	•3	1	1	0.6	0.6
Readout Electronics	1.0	normal	1	1	1	1.0	1.0
Response Time	0.8	rectangular	•3	1	1	0.5	0.5
Integration Time	1.7	rectangular	•3	1	1	1.0	1.0
RF Ambient Condition	3.0	rectangular	•3	1	1	1.7	1.7
Probe Positioner Mech.	0.4	rectangular	•3	1	1	0.2	0.2
Restriction							
Probe Positioning with respect to Phantom Shell	2.9	rectangular	•3	1	1	2.1	2.1
Extrapolation and Integration	3.7	rectangular	•3	1	1	2.1	2.1
Test Sample Positioning	4.0	normal	1	1	1	4.0	4.0
Device Holder Uncertainty	2.0	normal	1	1	1	2.0	2.0
Drift of Output Power	0.0	rectangular	•3	1	1	0.0	0.0
Phantom and Setup							
Phantom Uncertainty(shape & thickness tolerance)	3.4	rectangular	•3	1	1	2.0	2.0
Liquid Conductivity(target)	13.0	rectangular	•3	0.7	0.5	5.3	3.8
Liquid Conductivity(meas.)	0.1	rectangular	•3	0.7	0.5	0.1	0.0
Liquid Permittivity(target)	2.0	rectangular	•3	0.6	0.5	0.8	0.6
Liquid Permittivity(meas.)	3.9	rectangular	•3	0.6	0.5	1.4	1.1
Combined Uncertainty		RSS				10.3	9.5
Combined Uncertainty (coverage factor=2)		Normal(k=2)				20.6	19.1

© 2005 RF Exposure Lab, LLC

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.



This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

Appendix C – SAR Test Setup Photos



System Body Configuration

Sugar Body Tissue Depth

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.



Glycol Body Tissue Depth



Next to Ankle Position Front

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.



Next to Ankle Position Side



Away from Ankle Position Front

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.



Away from Ankle Position Side



Antenna Edge Position Front

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.



Antenna Edge Position Side

Front of Unit

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

Front of Unit

Back of Unit

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

Front of PCB



Back of PCB

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.



Battery



Antenna

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

Appendix D – Probe Calibration Data Sheets

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

NCL CALIBRATION LABORATORIES

Calibration File No.: CP-604

Client.: RFEL

C E R T I F I C A T E O F C A L I B R A T I O N

It is certified that the equipment identified below has been calibrated in the **NCL CALIBRATION LABORATORIES** by qualified personnel following recognized procedures and using transfer standards traceable to NRC/NIST.

Equipment: Miniature Isotropic RF Probe 835 MHz

Manufacturer: APREL Laboratories
Model No.: E-020
Serial No.: 215

BODY Calibration

Calibration Procedure: SSI/DRB-TP-D01-032-E020-V2
Project No: RFEL-Probe-215-Calibration-5166

Calibrated: 10th June 2005
Released on: 10th June 2005

This Calibration Certificate is Incomplete Unless Accompanied with the Calibration Results Summary

Released By: Signature On File

NCL CALIBRATION LABORATORIES

51 SPECTRUM WAY
NEPEAN, ONTARIO
CANADA K2R 1E6

Division of APREL Lab.
TEL: (613) 820-4988
FAX: (613) 820-4161

Introduction

This Calibration Report reproduces the results of the calibration performed in line with the SSI/DRB-TP-D01-032-E020-V2 E-Field Probe Calibration Procedure. The results contained within this report are for APREL E-Field Probe E-020 215.

References

SSI/DRB-TP-D01-032-E020-V2 E-Field Probe Calibration Procedure
IEEE 1528 "Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques"
SSI-TP-011 Tissue Calibration Procedure

Conditions

Probe 215 was a new probe taken from stock prior to calibration.

Ambient Temperature of the Laboratory:	22 °C +/- 0.5°C
Temperature of the Tissue:	21 °C +/- 0.5°C

We the undersigned attest that to the best of our knowledge the calibration of this probe has been accurately conducted and that all information contained within this report has been reviewed for accuracy.

Stuart Nicol
Director Product Development

Janusz Lokaj
Member of Engineering Staff
(Calibration Engineer)

Calibration Results Summary

Probe Type:	E-Field Probe E-020
Serial Number:	215
Frequency:	835 MHz
Sensor Offset:	1.56 mm
Sensor Length:	2.5 mm
Tip Enclosure:	Ertalyte*
Tip Diameter:	**<**5 mm
Tip Length:	60 mm
Total Length:	290 mm

*Resistive to recommended tissue recipes per IEEE-1528

Sensitivity in Air

Channel X:	1.2 $\mu V/(V/m)^2$
Channel Y:	1.2 $\mu V/(V/m)^2$
Channel Z:	1.2 $\mu V/(V/m)^2$
Diode Compression Point:	95 mV

Sensitivity in Body Tissue

Frequency: 835 MHz

Epsilon: 56.1 (+/-5%) **Sigma:** 0.95 S/m (+/-10%)

ConvF

Channel X: 6.07

Channel Y: 6.07

Channel Z: 6.07

Tissue sensitivity values were calculated using the load impedance of the APREL Laboratories Daq-Paq.

Boundary Effect:

Uncertainty resulting from the boundary effect is less than 2% for the distance between the tip of the probe and the tissue boundary, when less than 2.44mm.

Spatial Resolution:

The measured probe tip diameter is 5 mm (+/- 0.01 mm) and therefore meets the requirements of SSI/DRB-TP-D01-032 for spatial resolution.

Receiving Pattern 835 MHz (Air)



Isotropy Error 835 MHz (Air)





Isotropicity in Tissue: 0.10 dB

Dynamic Range



Video Bandwidth



Video Bandwidth at 500 Hz 1 dB
Video Bandwidth at 1.02 KHz: 3 dB

Conversion Factor Uncertainty Assessment

Frequency:		835MHz	
Epsilon:	56.1 (+/-5%)	**Sigma:**	0.95 S/m (+/-10%)
ConvF			
Channel X:	6.07	7%(K=2)	
Channel Y:	6.07	7%(K=2)	
Channel Z:	6.07	7%(K=2)	

To minimize the uncertainty calculation all tissue sensitivity values were calculated using a load impedance of 5 MΩ.

Boundary Effect:

For a distance of 2.4mm the evaluated uncertainty (increase in the probe sensitivity) is less than 2%.

Test Equipment

The test equipment used during Probe Calibration, manufacturer, model number and, current calibration status are listed and located on the main APREL server R:\NCL\Calibration Equipment\Instrument List May 2005.

NCL CALIBRATION LABORATORIES

Calibration File No.: CP-605

Client.: RFEL

C E R T I F I C A T E O F C A L I B R A T I O N

It is certified that the equipment identified below has been calibrated in the **NCL CALIBRATION LABORATORIES** by qualified personnel following recognized procedures and using transfer standards traceable to NRC/NIST.

Equipment: Miniature Isotropic RF Probe 1900 MHz

Manufacturer: APREL Laboratories
Model No.: E-020
Serial No.: 215

BODY Calibration

Calibration Procedure: SSI/DRB-TP-D01-032-E020-V2
Project No: RFEL-Probe-215-Calibration-5166

Calibrated: 10th June 2005
Released on: 10th June 2005

This Calibration Certificate is Incomplete Unless Accompanied with the Calibration Results Summary

Released By: Signature On File

NCL CALIBRATION LABORATORIES

51 SPECTRUM WAY
NEPEAN, ONTARIO
CANADA K2R 1E6

Division of APREL Lab.
TEL: (613) 820-4988
FAX: (613) 820-4161

Introduction

This Calibration Report reproduces the results of the calibration performed in line with the SSI/DRB-TP-D01-032-E020-V2 E-Field Probe Calibration Procedure. The results contained within this report are for APREL E-Field Probe E-020 215.

References

SSI/DRB-TP-D01-032-E020-V2 E-Field Probe Calibration Procedure
IEEE 1528 “Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques”
SSI-TP-011 Tissue Calibration Procedure

Conditions

Probe 215 was a new probe taken from stock prior to calibration.

Ambient Temperature of the Laboratory: 22 °C +/- 0.5°C
Temperature of the Tissue: 21 °C +/- 0.5°C

We the undersigned attest that to the best of our knowledge the calibration of this probe has been accurately conducted and that all information contained within this report has been reviewed for accuracy.

Stuart Nicol
Director Product Development

Janusz Lokaj
Member of Engineering Staff
(Calibration Engineer)

Calibration Results Summary

Probe Type:	E-Field Probe E-020
Serial Number:	215
Frequency:	1900 MHz
Sensor Offset:	1.56 mm
Sensor Length:	2.5 mm
Tip Enclosure:	Ertalyte*
Tip Diameter:	**<**5 mm
Tip Length:	60 mm
Total Length:	290 mm

*Resistive to recommended tissue recipes per IEEE-1528

Sensitivity in Air

Channel X:	1.2 $\mu V/(V/m)^2$
Channel Y:	1.2 $\mu V/(V/m)^2$
Channel Z:	1.2 $\mu V/(V/m)^2$
Diode Compression Point:	95 mV

Sensitivity in Body Tissue

Frequency: 1900 MHz

Epsilon: 53.3 (+/-5%) **Sigma:** 1.52 S/m (+/-10%)

ConvF

Channel X: 3.8

Channel Y: 3.8

Channel Z: 3.8

Tissue sensitivity values were calculated using the load impedance of the APREL Laboratories Daq-Paq.

Boundary Effect:

Uncertainty resulting from the boundary effect is less than 2% for the distance between the tip of the probe and the tissue boundary, when less than 2.44mm.

Spatial Resolution:

The measured probe tip diameter is 5 mm (+/- 0.01 mm) and therefore meets the requirements of SSI/DRB-TP-D01-032 for spatial resolution.

Receiving Pattern 1900 MHz (Air)



Isotropy Error 1900 MHz (Air)





Isotropicity in Tissue: 0.10 dB

Dynamic Range



Video Bandwidth



Video Bandwidth at 500 Hz 1 dB
Video Bandwidth at 1.02 KHz: 3 dB

Conversion Factor Uncertainty Assessment

Frequency:		1900MHz	
Epsilon:	53.3 (+/-5%)	**Sigma:**	1.52 S/m (+/-10%)
ConvF			
Channel X:	3.8	7%(K=2)	
Channel Y:	3.8	7%(K=2)	
Channel Z:	3.8	7%(K=2)	

To minimize the uncertainty calculation all tissue sensitivity values were calculated using a load impedance of 5 MΩ.

Boundary Effect:

For a distance of 2.4mm the evaluated uncertainty (increase in the probe sensitivity) is less than 2%.

Test Equipment

The test equipment used during Probe Calibration, manufacturer, model number and, current calibration status are listed and located on the main APREL server R:\NCL\Calibration Equipment\Instrument List May 2005.

Appendix E – Dipole Calibration Data Sheets

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

NCL CALIBRATION LABORATORIES

Calibration File No: CD-339
Project Number: RFEB-ALSAS-10U-4087

CERTIFICATE OF CALIBRATION

It is certified that the equipment identified below has been calibrated in the **NCL CALIBRATION LABORATORIES** by qualified personnel following recognized procedures and using transfer standards traceable to NRC/NIST.

RFE Validation Dipole

Manufacturer: APREL Laboratories
Part number: ALS-D-835-S-2
Frequency: 835 MHz
Serial No: RFE-274

Customer: RFE

Calibrated: 20 February 2004
Released on: 20 February 2004

Released By: _____

NCL CALIBRATION LABORATORIES

51 SPECTRUM WAY
NEPEAN, ONTARIO
CANADA K2R 1E6

Division of APREL Lab.
TEL: (613) 820-4988
FAX: (613) 820-4162

Calibration Results Summary

The following results relate the Calibrated Dipole and should be used as a quick reference for the user.

Mechanical Dimensions

Length: 161.8 mm
Height: 91.1 mm

Electrical Specification

SWR: 1.11 U
Return Loss: -26.20 dB
Impedance: 52.40 Ω

System Validation Results

Frequency	1 Gram	10 Gram	Peak
835 MHz	9.33	6.42	15.0



Calibrated by

Approved by:

Introduction

This Calibration Report has been produced in line with the SSI Dipole Calibration Procedure SSI-TP-018-ALSAS. The results contained within this report are for Validation Dipole RFE-274. The calibration routine consisted of a three-step process. Step 1 was a mechanical verification of the dipole to ensure that it meets the IEEE/APREL mechanical specifications. Step 2 was an Electrical Calibration for the Validation Dipole, where the SWR, Impedance, and the Return loss were assessed. Step 3 involved a System Validation using the ALSAS-10U, along with RFE E-020 130 MHz to 26 GHz E-Field Probe Serial Number 213.

References

SSI-TP-018-ALSAS Dipole Calibration Procedure
SSI-TP-016 Tissue Calibration Procedure
IEEE 1528 "Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques"

Conditions

Dipole RFE-274 was new taken from stock.

Ambient Temperature of the Laboratory: 22 °C +/- 0.5°C
Temperature of the Tissue: 20 °C +/- 0.5°C

Dipole Calibration Results

Mechanical Verification

IEEE Length	IEEE Height	Measured Length	Measured Height
162.0 mm	91.0 mm	161.8 mm	91.1 mm

Tissue Validation

Head Tissue 835 MHz	Measured
Dielectric constant, ε_r	42.54
Conductivity, σ [S/m]	0.91

Electrical Calibration

Test	Result
S11 R/L	-26.2 dB
SWR	1.11 U
Impedance	52.4 Ω

The Following Graphs are the results as displayed on the Vector Network Analyzer.

S11 Parameter Return Loss



Calibrated by

Approved by:

SWR


S11 FORWARD REFLECTION
SWR
▸REF=294.938 mU
500.000 mU/DIV
CH 1 - S11
REFERENCE PLANE
5.0515 mm
▸MARKER 1
0.838000 GHz
1.108 U
MARKER TO MAX
MARKER TO MIN
1
0.748000
GHz
0.928000
MARKER READOUT
FUNCTIONS

Smith Chart Dipole Impedance



Calibrated by

Approved by:

System Validation Results Using the Electrically Calibrated Dipole

Head Tissue Frequency	1 Gram	10 Gram	Peak Above Feed Point
835 MHz	9.33	6.42	15.0



 Calibrated by Approved by:

Test Equipment

The test equipment used during Probe Calibration, manufacturer, model number and, current calibration status are listed and located on the main APREL server R:\NCL\Calibration Equipment\Instrument List May 2003

NCL CALIBRATION LABORATORIES

Calibration File No: CD-341
Project Number: RFEB-ALSAS-10U-4087

CERTIFICATE OF CALIBRATION

It is certified that the equipment identified below has been calibrated in the **NCL CALIBRATION LABORATORIES** by qualified personnel following recognized procedures and using transfer standards traceable to NRC/NIST.

RFE Validation Dipole

Manufacturer: APREL Laboratories
Part number: ALS-D-1900-S-2
Frequency: 1.9 GHz
Serial No: RFE-277

Customer: RFE

Calibrated: 20 February 2004
Released on: 20 February 2004

Released By: _____

NCL CALIBRATION LABORATORIES

51 SPECTRUM WAY
NEPEAN, ONTARIO
CANADA K2R 1E6

Division of APREL Lab.
TEL: (613) 820-4988
FAX: (613) 820-4161

Calibration Results Summary

The following results relate the Calibrated Dipole and should be used as a quick reference for the user.

Mechanical Dimensions

Length: 68.0 mm
Height: 37.5 mm

Electrical Specification

SWR: 1.08 U
Return Loss: -30.3 dB
Impedance: 48.3 Ω

System Validation Results

Frequency	1 Gram	10 Gram	Peak
1.9 GHz	36.0	20.78	67.7



Calibrated by

Approved by:

Introduction

This Calibration Report has been produced in line with the SSI Dipole Calibration Procedure SSI-TP-018-ALSAS. The results contained within this report are for Validation Dipole RFE-277. The calibration routine consisted of a three-step process. Step 1 was a mechanical verification of the dipole to ensure that it meets the IEEE/APREL mechanical specifications. Step 2 was an Electrical Calibration for the Validation Dipole, where the SWR, Impedance, and the Return loss were assessed. Step 3 involved a System Validation using the ALSAS-10U, along with Panasonic E-020 130 MHz to 26 GHz E-Field Probe Serial Number 213.

References

SSI-TP-018-ALSAS Dipole Calibration Procedure
SSI-TP-016 Tissue Calibration Procedure
IEEE 1528 "Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques"

Conditions

Dipole RFE-277 was new taken from stock.

Ambient Temperature of the Laboratory: 22 °C +/- 0.5°C
Temperature of the Tissue: 20 °C +/- 0.5°C

Dipole Calibration Results

Mechanical Verification

IEEE Length	IEEE Height	Measured Length	Measured Height
68.0 mm	39.5 mm	68.0 mm	37.5 mm

Tissue Validation

Head Tissue 1900 MHz	Measured
Dielectric constant, ε_r	39.9
Conductivity, σ [S/m]	1.42

Electrical Calibration

Test	Result
S11 R/L	-30.3 dB
SWR	1.08 U
Impedance	48.3 Ω

The Following Graphs are the results as displayed on the Vector Network Analyzer.

S11 Parameter Return Loss



Calibrated by

Approved by:

SWR



Calibrated by

Approved by:

Smith Chart Dipole Impedance



System Validation Results Using the Electrically Calibrated Dipole

Frequency	1 Gram	10 Gram	Peak Above Feed Point
1.9 GHz	36.0	20.78	67.7



Test Equipment

The test equipment used during Probe Calibration, manufacturer, model number and, current calibration status are listed and located on the main APREL server R:\NCL\Calibration Equipment\Instrument List May 2003

Appendix F – Phantom Calibration Data Sheets

This report shall not be reproduced except in full without the written approval of RF Exposure Lab, LLC.

NCL CALIBRATION LABORATORIES

Calibration File No.: RFE-273

CERTIFICATE OF CALIBRATION

It is certified that the equipment identified below has been calibrated in the **NCL CALIBRATION LABORATORIES** by qualified personnel following recognized procedures and using transfer standards traceable to National Standards.

Thickness of the UniPhantom is 2 mm ± 10%
Pinna thickness is 6 mm ± 10%

Resolution:	0.01 mm	Calibrated to:	0.0 mm
Stability:	OK	Accuracy:	< 0.1 mm

Calibrated By: Karen K. Feb 17/04.

NCL CALIBRATION LABORATORIES

51 SPECTRUM WAY
NEPEAN, ONTARIO
CANADA K2R 1E6

Division of APREL Lab.
TEL: (613) 820-4988
FAX: (613) 820-4161