

# TEST REPORT

## Part 15 Subpart C 15.247

**Equipment under test** SAMJIN Gateway

**Model name** GWTP-ST

**FCC ID** TSW-GWTP-ST

**Applicant** Samjin LND

**Manufacturer** Samjin LND

**Date of test(s)** 2018.02.12 ~ 2018.02.23, 03.14

**Date of issue** 2018.03.15

**Issued to**  
**Samjin LND**

64-17, Dongtangiheung-ro, Dongtan-myeon, Hwaseong-si,  
Gyeonggi-do, 18487, Korea  
Tel: + 82-31-379-2073 / Fax: +82-31-376-8156

**Issued by**  
**KES Co., Ltd.**

3701, 40, Simin-daero 365beon-gil, Dongan-gu, Anyang-si,  
Gyeonggi-do, 14057, Korea  
473-21, Gayeo-ro, Yeoju-si, Gyeonggi-do, Korea  
Tel: +82-31-425-6200 / Fax: +82-31-424-0450

| Test and report completed by :                                                      | Report approval by :                                                                 |
|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
|  |  |
| Young-Jin Lee<br>Test engineer                                                      | Hyeon-Su, Jang<br>Technical manager                                                  |

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

**KES Co., Ltd.**

3701, 40, Simin-daero 365beon-gil,  
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea  
Tel: +82-31-425-6200 / Fax: +82-31-424-0450  
www.kes.co.kr

Test report No.:

KES-RF-18T0033-R1

Page ( 2 ) of (34)

---

**Revision history**

| Revision | Date of issue | Test report No.   | Description                            |
|----------|---------------|-------------------|----------------------------------------|
| -        | 2018.03.11    | KES-RF-18T0033    | Initial                                |
| 1        | 2018.03.15    | KES-RF-18T0033-R1 | Retest a restricted band and emission. |

---

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



---

## TABLE OF CONTENTS

|             |                                                |    |
|-------------|------------------------------------------------|----|
| 1.          | General information .....                      | 4  |
| 1.1.        | EUT description .....                          | 4  |
| 1.2.        | Test configuration.....                        | 4  |
| 1.3.        | Device modifications.....                      | 4  |
| 1.4.        | Frequency/channel operations.....              | 5  |
| 1.5.        | Accessory information .....                    | 5  |
| 1.6.        | Measurement results explanation example.....   | 5  |
| 1.7.        | Measurement Uncertainty .....                  | 5  |
| 2.          | Summary of tests.....                          | 6  |
| 3.          | Test results.....                              | 7  |
| 3.1.        | 6 dB bandwidth.....                            | 7  |
| 3.2.        | Output power.....                              | 9  |
| 3.3.        | Power spectral density.....                    | 12 |
| 3.4.        | Radiated restricted band and emissions.....    | 14 |
| 3.5.        | Conducted spurious emissions & band edge ..... | 29 |
| 3.6.        | AC conducted emissions .....                   | 31 |
| Appendix A. | Measurement equipment .....                    | 33 |
| Appendix B. | Test setup photos .....                        | 34 |



## 1. General information

Applicant: Samjin LND  
Applicant address: 64-17, Dongtangiheung-ro, Dongtan-myeon, Hwaseong-si,  
Gyeonggi-do, 18487, Korea  
Test site: KES Co., Ltd.  
Test site address: 3701, 40, Simin-daero 365beon-gil, Dongan-gu, Anyang-si,  
Gyeonggi-do, 14057, Korea  
473-21, Gayeo-ro, Yeosu-si, Gyeonggi-do, Korea  
Test Facility FCC Accreditation Designation No.: KR0100, Registration No.: 444148  
FCC rule part(s): 15.247  
FCC ID: TSW-GWTP-ST  
Test device serial No.: ☒ Production ☐ Pre-production ☐ Engineering

### 1.1. EUT description

Equipment under test SAMJIN Gateway  
Frequency range 2 402 MHz ~ 2 480 MHz (LE)  
2 412 MHz ~ 2 462 MHz (11b/g/n\_HT20)  
Model: GWTP-ST  
Modulation technique WIFI : DSSS, OFDM  
BT : GFSK  
Number of channels 2 402 MHz ~ 2 480 MHz (LE) : 40 ch  
2 412 MHz ~ 2 462 MHz (11b/g/n\_HT20) : 11 ch  
Antenna specification 2.4 GHz Antenna type : Dipole Antenna, Peak gain : 5.25 dBi  
Power source DC 5.0 V

### 1.2. Test configuration

The **Samjin LND GWTP-ST FCC ID: TSW-GWTP-ST** was tested per the guidance of KDB 558074 D01 v04. ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing.

### 1.3. Device modifications

N/A

#### 1.4. Frequency/channel operations

| Ch. | Frequency (MHz) | Rate(Mbps) |
|-----|-----------------|------------|
| 00  | 2 402           | 1          |
| .   | .               | .          |
| 20  | 2 442           | 1          |
| .   | .               | .          |
| 39  | 2 480           | 1          |

#### 1.5. Accessory information

| Equipment | Manufacturer | Model | Serial No. | Power source |
|-----------|--------------|-------|------------|--------------|
| -         | -            | -     | -          | -            |

#### 1.6. Measurement results explanation example

For all conducted test items

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 1.10 + 10 = 11.10 \text{ (dB)}\end{aligned}$$

#### 1.7. Measurement Uncertainty

| Test Item                                                                                                                                     |              | Uncertainty |
|-----------------------------------------------------------------------------------------------------------------------------------------------|--------------|-------------|
| Uncertainty for Conduction emission test                                                                                                      |              | 2.62 dB     |
| Uncertainty for Radiation emission test<br>(include Fundamental emission)                                                                     | 9kHz - 30MHz | 4.54 dB     |
|                                                                                                                                               | 30MHz - 1GHz | 4.36 dB     |
|                                                                                                                                               | Above 1GHz   | 5.00 dB     |
| Note. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2. |              |             |



## 2. Summary of tests

| Reference     | Parameter                                 | Test results |
|---------------|-------------------------------------------|--------------|
| 15.247(a)(2)  | 6 dB bandwidth                            | Pass         |
| 15.247(b)(3)  | Output power                              | Pass         |
| 15.247(e)     | Power spectral density                    | Pass         |
| 15.205 15.209 | Radiated restricted band and emission     | Pass         |
| 15.247(d)     | Conducted spurious emission and band edge | Pass         |
| 15.207(a)     | AC conducted emissions                    | Pass         |

### 3. Test results


#### 3.1. 6 dB bandwidth

##### Test procedure

KDB 558074 D01 v04 – Section 8.1 or 8.2

Used test method is section 8.1.

##### Test setup



##### Section 8.1

1. RBW = 100 kHz.
2. VBW  $\geq 3 \times$  RBW.
3. Detector = peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

##### Section 8.2

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., RBW = 100 kHz, VBW  $\geq 3 \times$  RBW, peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be  $\geq 6$  dB.

##### Limit

According to §15.247(a)(2), systems using digital modulation techniques may operate 902 ~ 928 MHz, 2 400 ~ 2 483.5 MHz, and 5 725 ~ 5 850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.




## KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,  
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea  
Tel: +82-31-425-6200 / Fax: +82-31-424-0450  
www.kes.co.kr

Test report No.:  
KES-RF-18T0033-R1  
Page ( 8 ) of (34)

### Test results

| Frequency(MHz) | 6 dB bandwidth(MHz) | Limit(MHz) |
|----------------|---------------------|------------|
| 2 402          | 0.709               | 0.5        |
| 2 442          | 0.714               |            |
| 2 480          | 0.712               |            |



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.


### 3.2. Output power

#### Test procedure

KDB 558074 D01 v04 – section 9.1.1 or 9.1.3 and 9.2.3.2

Used test method is section 9.1.1 and 9.2.3.2

#### Test setup



#### Section 9.1.1

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

1. Set the  $RBW \geq DTS$  bandwidth.
2. Set  $VBW \geq 3 \times RBW$ .
3. Set  $span \geq 3 \times RBW$
4. Sweep time = auto couple
5. Detector = peak
6. Trace mode = max hold
7. Allow trace to fully stabilize
8. Use peak marker function to determine the peak amplitude level

#### Section 9.1.3

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

#### Section 9.2.3.2

Alternatively, measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Since this measurement is made only during the ON time of the transmitter, no duty cycle correction is required.



---

## Limit

According to §15.247(b)(3), For systems using digital modulation in the 902~928 MHz, 2 400~2 483.5 MHz, and 5 725~5 850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted out-put power. Maximum Conducted Out-put Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

According to §15.247(b)(4), The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmit-ting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.



# KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,  
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea  
Tel: +82-31-425-6200 / Fax: +82-31-424-0450  
www.kes.co.kr


Test report No.:

KES-RF-18T0033-R1

Page (11 ) of (34)

## Test results

| Frequency(MHz) | Peak output power(dBm) | Average output power(dBm) | Limit(dBm) |
|----------------|------------------------|---------------------------|------------|
| 2 402          | 5.57                   | 5.37                      | 30         |
| 2 442          | 6.47                   | 6.13                      |            |
| 2 480          | 6.24                   | 5.94                      |            |



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.


The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

### 3.3. Power spectral density

#### Test procedure

KDB 558074 D01 v04- section 10.2

#### Test setup



#### Section 10.2

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the RBW :  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
4. Set the VBW  $\geq 3 \times \text{RBW}$ .
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW(no less than 3 kHz) and repeat.


#### Limit

According to §15.247(e), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.



## Test results

| Frequency(MHz) | PSD (dBm) | Limit(dBm) |
|----------------|-----------|------------|
| 2 402          | -8.55     | 8          |
| 2 442          | -7.65     |            |
| 2 480          | -7.38     |            |




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.


### 3.4. Radiated restricted band and emissions

#### Test setup


The diagram below shows the test setup that is utilized to make the measurements for emission from 9 kHz to 30 MHz Emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 1 GHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz emissions, whichever is lower.



#### Test procedure below 30 MHz

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. Then antenna is a loop antenna is fixed at one meter above the ground to determine the maximum value of the field strength. Both parallel and perpendicular of the antenna are set to make the measurement.
3. For each suspected emission, the EUT was arranged to its worst case and then the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test-receiver system was set to average or quasi peak detect function and Specified Bandwidth with Maximum hold mode.

#### Test procedure above 30 MHz

1. Spectrum analyzer settings for  $f < 1$  GHz:
  - ① Span = wide enough to fully capture the emission being measured
  - ② RBW = 100 kHz
  - ③ VBW  $\geq$  RBW
  - ④ Detector = quasi peak
  - ⑤ Sweep time = auto
  - ⑥ Trace = max hold
2. Spectrum analyzer settings for  $f \geq 1$  GHz: Peak
  - ① Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
  - ② RBW = 1 MHz
  - ③ VBW  $\geq$  3 MHz
  - ④ Detector = peak
  - ⑤ Sweep time = auto
  - ⑥ Trace = max hold
  - ⑦ Trace was allowed to stabilize

3. Spectrum analyzer settings for  $f \geq 1$  GHz: Average

- ① Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- ② RBW = 1 MHz
- ③ VBW  $\geq 3 \times$  RBW
- ④ Detector = RMS, if span/(# of points in sweep)  $\leq$  (RBW/2). Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.
- ⑤ Averaging type = power(i.e., RMS)
  - 1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
  - 2) Some instruments require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used.
- ⑥ Sweep = auto
- ⑦ Trace = max hold
- ⑧ Perform a trace average of at least 100 traces.
- ⑨ A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:
  - 1) If power averaging (RMS) mode was used in step ⑤, then the applicable correction factor is  $10 \log(1/x)$ , where x is the duty cycle.
  - 2) If linear voltage averaging mode was used in step ⑤, then the applicable correction factor is  $20 \log(1/x)$ , where x is the duty cycle.
  - 3) If a specific emission is demonstrated to be continuous ( $\geq 98$  percent duty cycle) rather than turning on and off with the transmit cycle, then no duty cycle correction is required for that emission.

**Note.**

1.  $f < 30$  MHz, extrapolation factor of 40 dB/decade of distance.  $F_d = 40 \log(D_m/D_s)$   
 $f \geq 30$  MHz, extrapolation factor of 20 dB/decade of distance.  $F_d = 20 \log(D_m/D_s)$   
Where:  
 $F_d$  = Distance factor in dB  
 $D_m$  = Measurement distance in meters  
 $D_s$  = Specification distance in meters
3. CF(Correction factors(dB)) = Antenna factor(dB/m) + Cable loss(dB) + or Amp. gain(dB) + or  $F_d$ (dB)
4. Field strength(dB $\mu$ V/m) = Level(dB $\mu$ V) + CF (dB) + or DCF(dB)
5. Margin(dB) = Limit(dB $\mu$ V/m) - Field strength(dB $\mu$ V/m)
6. Emissions below 18 GHz were measured at a 3 meter test distance while emissions above 18 GHz were measured at a 1 meter test distance with the application of a distance correction factor.
7. The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z, it was determined that **X orientation** was worst-case orientation; therefore, all final radiated testing was performed with the EUT in **X orientation**.
8. The worst-case emissions are reported however emissions whose levels were not within 20 dB of respective limits were not reported.
9. According to exploratory test no any obvious emission were detected from 9kHz to 30MHz. Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30 m open area test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

**KES Co., Ltd.**

3701, 40, Simin-daero 365beon-gil,  
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea  
Tel: +82-31-425-6200 / Fax: +82-31-424-0450  
www.kes.co.kr

Test report No.:

KES-RF-18T0033-R1

Page (17 ) of (34)

**Limit**

According to 15.209(a), for an intentional radiator devices, the general required of field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values :

| Frequency (MHz) | Distance (Meters) | Radiated ( $\mu\text{V/m}$ ) |
|-----------------|-------------------|------------------------------|
| 0.009 ~ 0.490   | 300               | 2400/F(kHz)                  |
| 0.490 ~ 1.705   | 30                | 24000/F(kHz)                 |
| 1.705 ~ 30.0    | 30                | 30                           |
| 30 ~ 88         | 3                 | 100**                        |
| 88 ~ 216        | 3                 | 150**                        |
| 216 ~ 960       | 3                 | 200**                        |
| Above 960       | 3                 | 500                          |

\*\*Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54 ~ 72 MHz, 76 ~ 88 MHz, 174 ~ 216 MHz or 470 ~ 806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

### Duty cycle

Regarding to KDB 558074 D01\_v04, 6.0, the maximum duty cycles of all modes were investigated and set the spectrum analyzer as below.


Set RBW  $\geq$  OBW if possible; otherwise, set RBW to the largest available value. Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are  $> 50/T$  and the number of sweep points across duration T exceeds 100.

| T <sub>on</sub> time (ms) | Period (ms) | Duty cycle (Linear) | Duty cycle (%) | Minimum VBW (kHz) | Duty cycle correction factor (dB) |
|---------------------------|-------------|---------------------|----------------|-------------------|-----------------------------------|
| 0.442 0                   | 0.652 2     | 0.677 7             | 67.77          | 2.26              | 1.69                              |

Duty cycle (Linear) = T<sub>on</sub> time/Period

Minimum VBW(kHz) = 1/T<sub>on</sub>, where T is on time in second

DCF(Duty cycle correction factor (dB)) = 10log(1/duty cycle)



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.


The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



### Test results (Below 30 MHz)

Mode: BLE  
Distance of measurement: 3 meter  
Channel: 20 (Worst case)

| Frequency<br>(MHz)                                            | Level<br>(dBμV) | Ant. Pol.<br>(H/V) | CF<br>(dB) | F <sub>d</sub><br>(dB) | Field strength<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|---------------------------------------------------------------|-----------------|--------------------|------------|------------------------|----------------------------|-------------------|----------------|
| No spurious emissions were detected within 20 dB of the limit |                 |                    |            |                        |                            |                   |                |



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



# KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,  
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea  
Tel: +82-31-425-6200 / Fax: +82-31-424-0450  
www.kes.co.kr


Test report No.:

KES-RF-18T0033-R1

Page (20 ) of (34)

## Test results (Below 1 000 MHz) – Worst case

Mode: BLE  
Distance of measurement: 3 meter  
Channel: 20 (Worst case)



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



### Test results (Above 1 000 MHz)


Mode: BLE  
Distance of measurement: 3 meter  
Channel: 00

#### - Spurious

| Frequency (MHz) | Level (dBμV) | Detect mode | Ant. Pol. (H/V) | CF (dB) | DCF (dB) | Field strength (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
|-----------------|--------------|-------------|-----------------|---------|----------|-------------------------|----------------|-------------|
| 2 506.50        | 53.53        | Peak        | V               | 0.01    | -        | 53.54                   | 74.00          | 20.46       |
| 4 813.00        | 42.01        | Peak        | V               | 7.66    | -        | 49.67                   | 74.00          | 24.33       |


#### - Band edge

| Frequency (MHz) | Level (dBμV) | Detect mode | Ant. Pol. (H/V) | CF (dB) | DCF (dB) | Field strength (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
|-----------------|--------------|-------------|-----------------|---------|----------|-------------------------|----------------|-------------|
| 2 341.24        | 50.64        | Peak        | H               | -0.31   | -        | 50.33                   | 74.00          | 23.67       |
| 2 341.24        | 50.93        | Peak        | V               | -0.31   | -        | 50.62                   | 74.00          | 23.38       |



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



Note.


1. Average test would be performed if the peak result were greater than the average limit.



Mode: BLE  
Distance of measurement: 3 meter  
Channel: 20

- Spurious

| Frequency (MHz) | Level (dBμV) | Detect mode | Ant. Pol. (H/V) | CF (dB) | DCF (dB) | Field strength (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
|-----------------|--------------|-------------|-----------------|---------|----------|-------------------------|----------------|-------------|
| 2 341.50        | 50.44        | Peak        | H               | -0.31   | -        | 50.13                   | 74.00          | 23.87       |
| 2 341.50        | 50.63        | Peak        | V               | -0.31   | -        | 50.32                   | 74.00          | 23.68       |
| 4 878.00        | 44.77        | Peak        | V               | 8.17    | -        | 52.94                   | 74.00          | 21.06       |



Note.

1. Average test would be performed if the peak result were greater than the average limit.




Mode: BLE  
Distance of measurement: 3 meter  
Channel: 39


- Spurious

| Frequency (MHz) | Level (dBμV) | Detect mode | Ant. Pol. (H/V) | CF (dB) | DCF (dB) | Field strength (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
|-----------------|--------------|-------------|-----------------|---------|----------|-------------------------|----------------|-------------|
| 2 341.50        | 49.03        | Peak        | H               | -0.31   | -        | 48.72                   | 74.00          | 25.28       |
| 2 376.30        | 53.33        | Peak        | V               | -0.25   | -        | 53.08                   | 74.00          | 20.92       |
| 4 965.50        | 42.24        | Peak        | V               | 8.85    | -        | 51.09                   | 74.00          | 22.91       |

- Band edge

| Frequency (MHz) | Level (dBμV) | Detect mode | Ant. Pol. (H/V) | CF (dB) | DCF (dB) | Field strength (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
|-----------------|--------------|-------------|-----------------|---------|----------|-------------------------|----------------|-------------|
| 2 493.00        | 44.48        | Peak        | H               | -0.03   | -        | 44.45                   | 74.00          | 29.55       |
| 2 483.50        | 57.67        | Peak        | V               | -0.05   | -        | 57.62                   | 74.00          | 16.38       |
| 2 483.50        | 36.90        | Average     | V               | -0.05   | 1.69     | 38.54                   | 54.00          | 15.46       |





Note.

1. Average test would be performed if the peak result were greater than the average limit.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



---


**Test results - Simultaneous Tx Radiated Spurious Emissions Measurements(Worst case)**

Mode: 802.11g, LE  
Distance of measurement: 3 meter  
Channel: 1, 20  
- **Spurious**

| Frequency<br>(MHz) | Level<br>(dBμV) | Detect mode | Ant. Pol.<br>(H/V) | CF<br>(dB) | DCF<br>(dB) | Field strength<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|--------------------|-----------------|-------------|--------------------|------------|-------------|----------------------------|-------------------|----------------|
| 1 855.30           | 48.58           | Peak        | H                  | -2.50      | -           | 46.08                      | 74.00             | 27.92          |
| 2 121.60           | 47.58           | Peak        | H                  | -0.73      | -           | 46.85                      | 74.00             | 27.15          |
| 2 164.98           | 47.85           | Peak        | H                  | -0.64      | -           | 47.21                      | 74.00             | 26.79          |
| 1 525.30           | 53.26           | Peak        | V                  | -5.72      | -           | 47.54                      | 74.00             | 26.46          |
| 1 840.80           | 54.49           | Peak        | V                  | -2.65      | -           | 51.84                      | 74.00             | 22.16          |
| 2 052.10           | 50.82           | Peak        | V                  | -0.87      | -           | 49.95                      | 74.00             | 24.05          |
| 4 834.00           | 45.35           | Peak        | V                  | 7.82       | -           | 53.17                      | 74.00             | 20.83          |

---

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



Note.

1. No spurious emission were detected above 6 GHz.


This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



**Test results (18 GHz to 30 GHz) – Worst case**

Mode: BLE  
Distance of measurement: 3 meter  
Channel: 20 (Worst case)




Note.

1. No spurious emission were detected above 18 GHz.

### 3.5 Conducted spurious emissions & band edge

#### Test setup



#### Test procedure

##### Band edge

KDB 558074 D01 v04 – Section 11.3

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW = 100 kHz
4. VBW = 300 kHz
5. Detector = Peak
6. Trace mode = max hold
7. Sweep time = auto
8. The trace was allowed to stabilize

##### Out of band emissions

KDB 558074 D01 v04 – Section 11.3


1. Start frequency was set to 30 MHz and stop frequency was set to 25 GHz for 2.4 GHz frequencies and 40 GHz for 5 GHz frequencies
2. RBW = 100 kHz
3. VBW = 300 kHz
4. Detector = Peak
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

#### Limit

According to 15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph(b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in section 15.209(a) is not required. In addition, radiated emission which in the restricted band, as define in section 15.205(a), must also comply the radiated emission limits specified in section 15.209(a) (see section 15.205(c))




## Test results



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

### 3.6. AC conducted emissions

#### Test setup



#### Limit

According to 15.207(a), for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50uH/50 ohm line impedance stabilization network (LISN). Compliance with the provision of this paragraph shall on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower applies at the boundary between the frequencies ranges.

| Frequency of Emission (MHz) | Conducted limit (dBμV/m) |          |
|-----------------------------|--------------------------|----------|
|                             | Quasi-peak               | Average  |
| 0.15 – 0.50                 | 66 - 56*                 | 56 - 46* |
| 0.50 – 5.00                 | 56                       | 46       |
| 5.00 – 30.0                 | 60                       | 50       |


#### Note:

1. All AC line conducted spurious emission are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and the appropriate frequencies. All data rates and modes were investigated for conducted spurious emission. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section.
3. Both Cable loss and LISN factor are included in measurement level(QP Level or AV Level).



## Test results


### Hot Line



#### Final Result

| Frequency (MHz) | QuasiPeak (dBµV) | CAverage (dBµV) | Limit (dBµV) | Margin (dB) | Meas. Time (ms) | Bandwidth (kHz) | Line | Corr. (dB) |
|-----------------|------------------|-----------------|--------------|-------------|-----------------|-----------------|------|------------|
| 0.160000        | ---              | 30.21           | 55.46        | 25.25       | 1000.0          | 9.000           | L1   | 19.5       |
| 0.160000        | 46.89            | ---             | 65.46        | 18.57       | 1000.0          | 9.000           | L1   | 19.5       |
| 0.525000        | ---              | 35.58           | 46.00        | 10.42       | 1000.0          | 9.000           | L1   | 19.6       |
| 0.525000        | 37.30            | ---             | 56.00        | 18.70       | 1000.0          | 9.000           | L1   | 19.6       |
| 3.000000        | ---              | 26.15           | 46.00        | 19.85       | 1000.0          | 9.000           | L1   | 20.0       |
| 3.000000        | 28.31            | ---             | 56.00        | 27.69       | 1000.0          | 9.000           | L1   | 20.0       |
| 3.360000        | ---              | 18.64           | 46.00        | 27.36       | 1000.0          | 9.000           | L1   | 20.0       |
| 3.360000        | 28.71            | ---             | 56.00        | 27.29       | 1000.0          | 9.000           | L1   | 20.0       |
| 5.250000        | ---              | 31.25           | 50.00        | 18.75       | 1000.0          | 9.000           | L1   | 19.9       |
| 5.250000        | 33.95            | ---             | 60.00        | 26.05       | 1000.0          | 9.000           | L1   | 19.9       |

### Neutral Line



#### Final Result

| Frequency (MHz) | QuasiPeak (dBµV) | CAverage (dBµV) | Limit (dBµV) | Margin (dB) | Meas. Time (ms) | Bandwidth (kHz) | Line | Corr. (dB) |
|-----------------|------------------|-----------------|--------------|-------------|-----------------|-----------------|------|------------|
| 0.160000        | ---              | 30.38           | 55.46        | 25.08       | 1000.0          | 9.000           | N    | 19.5       |
| 0.160000        | 46.45            | ---             | 65.46        | 19.01       | 1000.0          | 9.000           | N    | 19.5       |
| 0.525000        | ---              | 35.14           | 46.00        | 10.86       | 1000.0          | 9.000           | N    | 19.6       |
| 0.525000        | 36.68            | ---             | 56.00        | 19.32       | 1000.0          | 9.000           | N    | 19.6       |
| 3.000000        | ---              | 26.17           | 46.00        | 19.83       | 1000.0          | 9.000           | N    | 20.0       |
| 3.000000        | 28.24            | ---             | 56.00        | 27.76       | 1000.0          | 9.000           | N    | 20.0       |
| 3.340000        | ---              | 18.43           | 46.00        | 27.57       | 1000.0          | 9.000           | N    | 20.0       |
| 3.340000        | 32.17            | ---             | 56.00        | 23.83       | 1000.0          | 9.000           | N    | 20.0       |
| 5.250000        | ---              | 31.24           | 50.00        | 18.76       | 1000.0          | 9.000           | N    | 19.9       |
| 5.250000        | 33.92            | ---             | 60.00        | 26.08       | 1000.0          | 9.000           | N    | 19.9       |

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



## Appendix A. Measurement equipment

| Equipment                           | Manufacturer               | Model            | Serial No.   | Calibration interval | Calibration date | Calibration due. |
|-------------------------------------|----------------------------|------------------|--------------|----------------------|------------------|------------------|
| Spectrum Analyzer                   | R&S                        | FSV30            | 101389       | 1 year               | 2018.01.19       | 2019.01.19       |
| Spectrum Analyzer                   | R&S                        | FSV40            | 101002       | 1 year               | 2017.07.04       | 2018.07.04       |
| 8360B Series Swept Signal Generator | HP                         | 83630B           | 3844A00786   | 1 year               | 2018.01.22       | 2019.01.22       |
| Power Meter                         | Anritsu                    | ML2495A          | 1438001      | 1 year               | 2018.01.25       | 2019.01.25       |
| Pulse Power Sensor                  | Anritsu                    | MA2411B          | 1339205      | 1 year               | 2018.01.25       | 2019.01.25       |
| Attenuator                          | Agilent                    | 8493C            | 51401        | 1 year               | 2017.07.04       | 2018.07.04       |
| Loop Antenna                        | Schwarzbeck                | FMZB1513         | 225          | 2 years              | 2017.05.10       | 2019.05.10       |
| Trilog-broadband antenna            | SCHWARZBECK                | VULB 9163        | 9168-714     | 2 years              | 2017.11.28       | 2018.11.28       |
| Horn Antenna                        | A.H                        | SAS-571          | 414          | 2 years              | 2017.02.15       | 2019.02.15       |
| Horn Antenna                        | SCHWARZBECK                | BBHA9170         | BBHA 9170550 | 2 years              | 2017.02.15       | 2019.02.15       |
| High Pass Filter                    | Wainwright Instrument Gmbh | WHJS3000-10TT    | 1            | 1 year               | 2017.07.03       | 2018.07.03       |
| Low Pass Filter                     | Wainwright Instrument Gmbh | WLK1.0/18 G-10TT | 1            | 1 year               | 2017.07.03       | 2018.07.03       |
| Preamplifier                        | R&S                        | SCU01            | 100603       | 1 year               | 2017.11.27       | 2018.11.27       |
| Preamplifier                        | AGILENT                    | 8449B            | 3008A01742   | 1 year               | 2018.01.11       | 2019.01.11       |
| EMI Test Receiver                   | R&S                        | ESR3             | 101781       | 1 year               | 2017.04.27       | 2018.04.27       |
| EMI Test Receiver                   | R&S                        | ESU26            | 100552       | 1 year               | 2017.04.19       | 2018.04.19       |
| Pulse Limiter                       | R&S                        | ESH3-Z2          | 101915       | 1 year               | 2017.11.27       | 2018.11.27       |
| LISN                                | R&S                        | ENV216           | 101787       | 1 year               | 2018.01.15       | 2019.01.15       |

## Peripheral devices

| Device            | Manufacturer                  | Model No.     | Serial No.      |
|-------------------|-------------------------------|---------------|-----------------|
| Notebook computer | Samsung Electronics Co., Ltd. | NT-R540-PS35S | ZSME93AZ700280W |

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.