

# EXALT COMMUNICATIONS, INC.

## 5 GHz Radio Module Model: EX-5i

27 July 2009

Report No.: SL09061401-EXT-004

(This report supersedes: None)



Modifications made to the product : None

This Test Report is Issued Under the Authority of:

|                                                                                     |                                                                                      |
|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
|  |  |
| Choon Sian Ooi<br>Test Engineer                                                     | Leslie Bai<br>Engineering Reviewer                                                   |

This test report may be reproduced in full only.  
Test result presented in this test report is applicable to the representative sample only.

# EMC Test Report

To: FCC Part 15.247 & RSS210 Issue7: 2007

SIEMIC, INC.  
Accessing global markets



## Laboratory Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to [testing](#) and [certification](#), SIEMIC provides initial design reviews and [compliance management](#) through out a project. Our extensive experience with [China](#), [Asia Pacific](#), [North America](#), [European](#), and [international](#) compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the [global markets](#).

### Accreditations for Conformity Assessment

| Country/Region | Accreditation Body     | Scope                              |
|----------------|------------------------|------------------------------------|
| USA            | FCC, A2LA              | EMC , RF/Wireless , Telecom        |
| Canada         | IC, A2LA, NIST         | EMC, RF/Wireless , Telecom         |
| Taiwan         | BSMI , NCC , NIST      | EMC, RF, Telecom , Safety          |
| Hong Kong      | OFTA , NIST            | RF/Wireless ,Telecom               |
| Australia      | NATA, NIST             | EMC, RF, Telecom , Safety          |
| Korea          | KCC/RRA, NIST          | EMI, EMS, RF , Telecom, Safety     |
| Japan          | VCCI, JATE, TELEC, RFT | EMI, RF/Wireless, Telecom          |
| Mexico         | NOM, COFETEL, Caniety  | Safety, EMC , RF/Wireless, Telecom |
| Europe         | A2LA, NIST             | EMC, RF, Telecom , Safety          |

### Accreditations for Product Certifications

| Country   | Accreditation Body | Scope              |
|-----------|--------------------|--------------------|
| USA       | FCC TCB, NIST      | EMC , RF , Telecom |
| Canada    | IC FCB , NIST      | EMC , RF , Telecom |
| Singapore | iDA, NIST          | EMC , RF , Telecom |

This page has been left blank intentionally.

**CONTENTS**

1 EXECUTIVE SUMMARY & EUT INFORMATION..... 6

2 TECHNICAL DETAILS..... 7

3 MODIFICATION ..... 8

4 TEST SUMMARY ..... 9

5 MEASUREMENTS, EXAMINATION AND DERIVED RESULTS ..... 10

ANNEX A. TEST INSTRUMENT & METHOD ..... 23

ANNEX B EUT AND TEST SETUP PHOTOGRAPHS..... 23

ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT ..... 23

ANNEX D USER MANUAL, BLOCK & CIRCUIT DIAGRAM ..... 23

ANNEX E SIEMIC ACCREDITATION ..... 23



## 1 Executive Summary & EUT information

The purpose of this test programme was to demonstrate compliance of the Exalt Communications, Inc., 5 GHz Radio Module, and Model: EX-5i against the current Stipulated Standards. The 5 GHz Radio Module have demonstrated compliance with the FCC 15.247 2009.

### EUT Information

|                                                    |   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|----------------------------------------------------|---|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>EUT Description</b>                             | : | The unlicensed products are fixed point-to-point radio operating in the 5725-5850 MHz bands. Two units, combined with external antennas and transmission lines, make up a complete point-to-point link. Users connect Ethernet and/or time division multiplexed (TDM) signals (T1, E1 or DS3) to carry bi-directional traffic across the link in place of traditional copper wires or fiber. The system utilizes time division duplex (TDD) radio transmission, and provides the administrator selection between one of three modulation modes, and one of four occupied bandwidths. The administrator may also select the specific operating center frequency across a frequency range that is defined by the limits of the selected occupied bandwidth. The output power may be adjusted by the installer in accordance to the connected transmission system and the specific regulations or link design. The radio is connected to a flat panel or parabolic dish antenna with coaxial transmission line, or in some cases, elliptical waveguide. The transmission system is grounded, along with any lightning arrestors that may be placed at any cable egress points. The radio is typically mounted in a grounded equipment rack, or on a table top or wall-mounted, and is connected to DC power, via either direct DC source or AC/DC converter, with power grounding, as required. The user's services (T1, E1, DS3, Ethernet) are directly connected, along with any diagnostic equipment. The radio chassis has a separate grounding connector, if required for separate chassis grounding. |
| <b>Model No</b>                                    | : | EX-5i                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Input Power</b>                                 | : | 120 Vac                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>Classification Per Stipulated Test Standard</b> | : | Spread Spectrum System / Device                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |

## 2 TECHNICAL DETAILS

|                                        |                                                                                     |
|----------------------------------------|-------------------------------------------------------------------------------------|
| <b>Purpose</b>                         | Compliance testing of 5 GHz Radio Module with stipulated standard                   |
| <b>Applicant / Client</b>              | Exalt Communications, Inc.                                                          |
| <b>Manufacturer</b>                    | Exalt Communications, Inc.<br>580 Division Street<br>Campbell, California 95008 USA |
| <b>Laboratory performing the tests</b> | SIEMIC Laboratories                                                                 |
| <b>Test report reference number</b>    | SL09061401-EXT-004                                                                  |
| <b>Date EUT received</b>               | 09 July 2009                                                                        |
| <b>Standard applied</b>                | 47 CFR §15.247 (2009)                                                               |
| <b>Dates of test (from – to)</b>       | July 10-21 2009                                                                     |
| <b>No of Units:</b>                    | 1                                                                                   |
| <b>Equipment Category:</b>             | DTS                                                                                 |
| <b>Trade Name:</b>                     | Exalt Communications, Inc.                                                          |
| <b>Model :</b>                         | EX-5i                                                                               |
| <b>RF Operating Frequency (ies)</b>    | 5745 to 5825 MHz                                                                    |
| <b>Channel Bandwidth:</b>              | 8MHz Channel Bandwidth, 16MHz Channel Bandwidth, 32MHz Channel Bandwidth            |
| <b>Modulation :</b>                    | Mode 1:QPSK, Mode 2:16QAM, Mode 3:64QAM                                             |
| <b>FCC ID :</b>                        | TTM-105P25N                                                                         |
| <b>IC ID :</b>                         | 6254A-105P25N                                                                       |

### 3 MODIFICATION

NONE

## 4 TEST SUMMARY

The product was tested in accordance with the following specifications. All Testing has been performed according to below product classification:

Spread Spectrum System / Device

### Test Results Summary

| Test Standard                                                                                     |                       | Description                      | Pass / Fail |
|---------------------------------------------------------------------------------------------------|-----------------------|----------------------------------|-------------|
| CFR 47 Part 15.247: 2009                                                                          | RSS 210 Issue 7: 2007 |                                  |             |
| 15.203                                                                                            |                       | Antenna Requirement              | Pass        |
| 15.205                                                                                            | RSS210(A8.5)          | Restricted Band of Operation     | Pass        |
| 15.207(a)                                                                                         | RSSGen(7.2.2)         | Conducted Emissions Voltage      | Pass        |
| 15.247(a)(1)                                                                                      | RSS210(A8.1)          | Channel Separation               | N/A         |
| 15.247(a)(1)                                                                                      | RSS210(A8.1)          | Occupied Bandwidth               | Pass        |
| 15.247(a)(2)                                                                                      | RSS210 (A8.2)         | Bandwidth                        | Pass        |
| 15.247(a)(1)                                                                                      | RSS210(A8.1)          | Number of Hopping Channels       | N/A         |
| 15.247(a)(1)                                                                                      | RSS210(A8.1)          | Time of Occupancy                | N/A         |
| 15.247(b)                                                                                         | RSS210(A8.4)          | Output Power                     | Pass        |
| 15.247(c)                                                                                         | RSS210(A8.4)          | Antenna Gain > 6 dBi             | Pass        |
| 15.247(d)                                                                                         | RSS210(A8.5)          | Conducted Spurious Emissions     | Pass        |
| 15.209; 15.247(d)                                                                                 | RSS210(A8.5)          | Radiated Spurious Emissions      | Pass        |
| 15.247(e)                                                                                         | RSS210(A8.3)          | Power Spectral Density           | Pass        |
| 15.247(f)                                                                                         | RSS210(A8.3)          | Hybrid System Requirement        | N/A         |
| 15.247(g)                                                                                         | RSS210(A8.1)          | Hopping Capability               | N/A         |
| 15.247(h)                                                                                         | RSS210(A8.1)          | Hopping Coordination Requirement | N/A         |
| 15.247(i)                                                                                         | RSSGen(5.5)           | RF Exposure requirement          | Pass        |
|                                                                                                   | RSSGen(4.8)           | Receiver Spurious Emissions      | Pass        |
| ANSI C63.4: 2003/ RSS-Gen Issue 2: 2007                                                           |                       |                                  |             |
| PS: All measurement uncertainties are not taken into consideration for all presented test result. |                       |                                  |             |

## **5 MEASUREMENTS, EXAMINATION AND DERIVED RESULTS**

### **5.1 Antenna Requirement**

**Requirement(s):** 47 CFR §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Antenna requirement must meet at least one of the following:

- a) Antenna must be permanently attached to the device.
- b) Antenna must use a unique type of connector to attach to the device.
- c) Device must be professionally installed. Installer shall be responsible for ensuring that the correct antenna is employed with the device.

The device must be professionally installed. Installer shall be responsible for ensuring that the correct antenna is employed with the device.

Antenna Model: SP6-5GHz

## 5.2 Conducted Emissions Voltage

Requirement :

| Frequency of emission (MHz) | Conducted limit (dBμV) |           |
|-----------------------------|------------------------|-----------|
|                             | Quasi-peak             | Average   |
| 0.15–0.5                    | 66 to 56*              | 56 to 46* |
| 0.5–5                       | 56                     | 46        |
| 5–30                        | 60                     | 50        |

\*Decreases with the logarithm of the frequency.

### Procedures:

1. All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR and Average detectors, are reported. All other emissions were relatively insignificant.
  2. A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
  3. Conducted Emissions Measurement Uncertainty  
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 9kHz – 30MHz (Average & Quasi-peak) is  $\pm 3.5$ dB.
  4. Environmental Conditions
 

|                      |          |
|----------------------|----------|
| Temperature          | 23°C     |
| Relative Humidity    | 50%      |
| Atmospheric Pressure | 1019mbar |
- Test Date : July 10-21 2009  
Tested By :Choon Sian Ooi


### Results:

## Results:

### Note: 2


Average Limit

Quasi-Peak Limit



Phase Line Plot at 120Vac, 60Hz

| Line Under Test | Frequency (MHz) | Corrected Amplitude (dBuV) QP | Limit (dBuV) QP | Margin (dB) QP | Corrected Amplitude (dBuV) AVG | Limit (dBuV) AVG | Margin (dB) AVG |
|-----------------|-----------------|-------------------------------|-----------------|----------------|--------------------------------|------------------|-----------------|
| Phase           | 3.09            | 50.80                         | 56.00           | -5.20          | 45.88                          | 46.00            | -0.12           |
| Phase           | 3.37            | 47.03                         | 56.00           | -8.97          | 43.09                          | 46.00            | -2.91           |
| Phase           | 2.80            | 42.09                         | 56.00           | -13.91         | 36.44                          | 46.00            | -9.56           |
| Phase           | 0.16            | 42.22                         | 65.54           | -23.32         | 27.83                          | 55.54            | -27.71          |
| Phase           | 4.89            | 23.89                         | 56.00           | -32.11         | 19.58                          | 46.00            | -26.42          |
| Phase           | 4.81            | 24.96                         | 56.00           | -31.04         | 20.18                          | 46.00            | -25.82          |



**Neutral Line Plot at 120Vac, 60Hz**

| Line Under Test | Frequency (MHz) | Corrected Amplitude (dBuV) QP | Limit (dBuV) QP | Margin (dB) QP | Corrected Amplitude (dBuV) AVG | Limit (dBuV) AVG | Margin (dB) AVG |
|-----------------|-----------------|-------------------------------|-----------------|----------------|--------------------------------|------------------|-----------------|
| Neutral         | 3.09            | 50.74                         | 56.00           | -5.26          | 45.88                          | 46.00            | -0.12           |
| Neutral         | 3.37            | 47.39                         | 56.00           | -8.61          | 42.70                          | 46.00            | -3.30           |
| Neutral         | 2.81            | 43.19                         | 56.00           | -12.81         | 39.99                          | 46.00            | -6.01           |
| Neutral         | 4.86            | 24.26                         | 56.00           | -31.74         | 19.58                          | 46.00            | -26.42          |
| Neutral         | 0.22            | 44.25                         | 62.87           | -18.62         | 35.22                          | 52.87            | -17.65          |
| Neutral         | 4.79            | 23.10                         | 56.00           | -32.90         | 18.94                          | 46.00            | -27.06          |

## 5.3 6dB & 99% Occupied Bandwidth

- Conducted Measurement  
EUT was set for low , mid, high channel with modulated mode and highest RF output power.  
The spectrum analyzer was connected to the antenna terminal.
- Environmental Conditions
 

|                      |          |
|----------------------|----------|
| Temperature          | 23°C     |
| Relative Humidity    | 50%      |
| Atmospheric Pressure | 1019mbar |
- Conducted Emissions Measurement Uncertainty  
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 40GHz is  $\pm 1.5$ dB.
- Test Date : July 10-21 2009  
Tested By :Choon Sian Ooi

**Requirement(s):** 47 CFR §15.247(a)(1) ; RSS210(A8.1)

**Procedures:** The 6dB bandwidths were measured conducted using a spectrum analyzer at low, mid, and hi channels. 6 dB Bandwidth Limit: > 500 kHz.


**Mode: 1 = QPSK      Mode: 2 = 16QAM      Mode: 3 = 64QAM**

| Channel      | Channel Bandwidth | Chain | 6 dB Channel Bandwidth (MHz) | 99% Channel Bandwidth (MHz) | 6 dB Occupied Bandwidth Limit (KHz) |
|--------------|-------------------|-------|------------------------------|-----------------------------|-------------------------------------|
| Low Channel  | 8MHz              | 1     | 7.25                         | 7.833                       | 500                                 |
|              | 8MHz              | 2     | 7.33                         | 8.00                        | 500                                 |
|              | 8MHz              | 3     | 7.29                         | 7.92                        | 500                                 |
| Mid Channel  | 8MHz              | 1     | 7.13                         | 7.75                        | 500                                 |
|              | 8MHz              | 2     | 7.38                         | 8.00                        | 500                                 |
|              | 8MHz              | 3     | 7.33                         | 8.00                        | 500                                 |
| High Channel | 8MHz              | 1     | 7.13                         | 7.79                        | 500                                 |
|              | 8MHz              | 2     | 7.29                         | 7.92                        | 500                                 |
|              | 8MHz              | 3     | 7.25                         | 7.96                        | 500                                 |


| Channel      | Channel Bandwidth | Mode | 6 dB Channel Bandwidth (MHz) | 99% Channel Bandwidth (MHz) | 6 dB Occupied Bandwidth Limit (KHz) |
|--------------|-------------------|------|------------------------------|-----------------------------|-------------------------------------|
| Low Channel  | 16MHz             | 1    | 14.08                        | 15.58                       | 500                                 |
|              | 16MHz             | 2    | 14.58                        | 14.58                       | 500                                 |
|              | 16MHz             | 3    | 14.50                        | 15.83                       | 500                                 |
| Mid Channel  | 16MHz             | 1    | 14.08                        | 15.58                       | 500                                 |
|              | 16MHz             | 2    | 14.58                        | 16.00                       | 500                                 |
|              | 16MHz             | 3    | 14.58                        | 16.00                       | 500                                 |
| High Channel | 16MHz             | 1    | 14.17                        | 15.58                       | 500                                 |
|              | 16MHz             | 2    | 14.50                        | 15.42                       | 500                                 |
|              | 16MHz             | 3    | 14.67                        | 15.58                       | 500                                 |

| Channel      | Channel Bandwidth | Mode | 6 dB Channel Bandwidth (MHz) | 99% Channel Bandwidth (MHz) | 6 dB Occupied Bandwidth Limit (KHz) |
|--------------|-------------------|------|------------------------------|-----------------------------|-------------------------------------|
| Low Channel  | 32MHz             | 1    | 29.5                         | 31.5                        | 500                                 |
|              | 32MHz             | 2    | 29.5                         | 31.3                        | 500                                 |
|              | 32MHz             | 3    | 29.2                         | 31.7                        | 500                                 |
| Mid Channel  | 32MHz             | 1    | 29.5                         | 31.3                        | 500                                 |
|              | 32MHz             | 2    | 29.2                         | 31.5                        | 500                                 |
|              | 32MHz             | 3    | 29.8                         | 31.5                        | 500                                 |
| High Channel | 32MHz             | 1    | 28.7                         | 31.2                        | 500                                 |
|              | 32MHz             | 2    | 29.5                         | 31.2                        | 500                                 |
|              | 32MHz             | 3    | 29.2                         | 31.2                        | 500                                 |


Refer to the attached plots.




6 dB Bandwidth - Low Channel (8MHz Mode 1)




6 dB Bandwidth - Low Channel (8MHz Mode 2)




6 dB Bandwidth – Low Channel (8MHz Mode 3)




6 dB Bandwidth – Mid Channel (8MHz Mode 1)




6 dB Bandwidth – Mid Channel (8MHz Mode 2)




6 dB Bandwidth – Mid Channel (8MHz Mode 3)




6 dB Bandwidth – High Channel (8MHz Mode 1)




6 dB Bandwidth – High Channel (8MHz Mode 2)




6 dB Bandwidth – High Channel (8MHz Mode 3)




6 dB Bandwidth – Low Channel (16MHz Mode 1)




6 dB Bandwidth – Low Channel (16MHz Mode 2)




6 dB Bandwidth – Low Channel (16MHz Mode 3)




6 dB Bandwidth – Mid Channel (16MHz Mode 1)




6 dB Bandwidth – Mid Channel (16MHz Mode 2)




6 dB Bandwidth – Mid Channel (16MHz Mode 3)




6 dB Bandwidth – High Channel (16MHz Mode 1)




6 dB Bandwidth – High Channel (16MHz Mode 2)




6 dB Bandwidth – High Channel (16MHz Mode 3)




6 dB Bandwidth – Low Channel (32MHz Mode 1)




6 dB Bandwidth – Low Channel (32MHz Mode 2)




6 dB Bandwidth – Low Channel (32MHz Mode 3)




6 dB Bandwidth – Mid Channel (32MHz Mode 1)




6 dB Bandwidth – Mid Channel (32MHz Mode 2)




6 dB Bandwidth – Mid Channel (32MHz Mode 3)




6 dB Bandwidth – High Channel (32MHz Mode 1)




6 dB Bandwidth – High Channel (32MHz Mode 2)




6 dB Bandwidth – High Channel (32MHz Mode 3)




99% Bandwidth - Low Channel (8MHz Mode 1)




99% Bandwidth - Low Channel (8MHz Mode 2)




99% Bandwidth – Low Channel (8MHz Mode 3)




99% Bandwidth – Mid Channel (8MHz Mode 1)




99% Bandwidth – Mid Channel (8MHz Mode 2)




99% Bandwidth – Mid Channel (8MHz Mode 3)




99% Bandwidth – High Channel (8MHz Mode 1)




99% Bandwidth – High Channel (8MHz Mode 2)




99% Bandwidth – High Channel (8MHz Mode 3)




99% Bandwidth – Low Channel (16MHz Mode 1)




99% Bandwidth – Low Channel (16MHz Mode 2)




99% Bandwidth – Low Channel (16MHz Mode 3)




99% Bandwidth – Mid Channel (16MHz Mode 1)




99% Bandwidth – Mid Channel (16MHz Mode 2)




99% Bandwidth – Mid Channel (16MHz Mode 3)




99% Bandwidth – High Channel (16MHz Mode 1)




99% Bandwidth – High Channel (16MHz Mode 2)




99% Bandwidth – High Channel (16MHz Mode 3)




99% Bandwidth – Low Channel (32MHz Mode 1)




99% Bandwidth – Low Channel (32MHz Mode 2)




99% Bandwidth – Low Channel (32MHz Mode 3)




99% Bandwidth – Mid Channel (32MHz Mode 1)




99% Bandwidth – Mid Channel (32MHz Mode 2)




99% Bandwidth – Mid Channel (32MHz Mode 3)



99% Bandwidth – High Channel (32MHz Mode 1)



99% Bandwidth – High Channel (32MHz Mode 2)



99% Bandwidth – High Channel (32MHz Mode 3)

## 5.4 Peak Spectral Density

1. Conducted Measurement  
EUT was set for low , mid, high channel with modulated mode and highest RF output power.  
The spectrum analyzer was connected to the antenna terminal.
2. Conducted Emissions Measurement Uncertainty  
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 40GHz is  $\pm 1.5\text{dB}$ .
3. Environmental Conditions

|                      |          |
|----------------------|----------|
| Temperature          | 23°C     |
| Relative Humidity    | 50%      |
| Atmospheric Pressure | 1019mbar |
4. Test Date : July 10-21 2009  
Tested By :Choon Sian Ooi

**Standard Requirement :** 47 CFR §15.247(e); RSS210(A8.3)


For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission

**Procedures:** The Peak Spectral density measurement was taken conducted using a spectrum analyzer.


RBW=3KHz, VBW > RBW , Sweep time to SPAN/RBW (sec)

**Test Result :**


Refer to the attached plots.




Low Channel (8MHz Mode 1)




Low Channel (8MHz Mode 2)




Low Channel (8MHz Mode 3)




Mid Channel (8MHz Mode 1)




Mid Channel (8MHz Mode 2)




Mid Channel (8MHz Mode 3)




High Channel (8MHz Mode 1)




High Channel (8MHz Mode 2)




### High Channel (8MHz Mode 3)







Low Channel (16MHz Mode 2)




Low Channel (16MHz Mode 3)




Mid Channel (16MHz Mode 1)




Mid Channel (16MHz Mode 2)




Mid Channel (16MHz Mode 3)




High Channel (16MHz Mode 1)




High Channel (16MHz Mode 2)




High Channel (16MHz Mode 3)




Low Channel (32MHz Mode 1)




Low Channel (32MHz Mode 2)




Low Channel (32MHz Mode 3)




Mid Channel (32MHz Mode 1)




Mid Channel (32MHz Mode 2)




Mid Channel (32MHz Mode 3)



High Channel (32MHz Mode 1)



High Channel (32MHz Mode 2)



High Channel (32MHz Mode 3)

## 5.10 Peak Output Power

1. Conducted Measurement  
EUT was set for low , mid, high channel with modulated mode and highest RF output power.  
The spectrum analyzer was connected to the antenna terminal.
2. Conducted Emissions Measurement Uncertainty  
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 40GHz is  $\pm 1.5\text{dB}$ .
3. Environmental Conditions
 

|                      |          |
|----------------------|----------|
| Temperature          | 23°C     |
| Relative Humidity    | 50%      |
| Atmospheric Pressure | 1019mbar |
4. Test Date : July 10-21 2009  
Tested By :Choon Sian Ooi

Standard Requirement: 47 CFR §15.247(b); RSS210 (A8.4)

**Procedures:** The peak output power was measured conducted using a spectrum analyzer at low, mid, and hi channels. Sample detector was set to measure the power output.

**Note:** Systems operating in the 5725–5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter peak output power


### Test Result:

| Channel      | Channel Bandwidth | Mode | Power (dBm) | Limit (dBm) |
|--------------|-------------------|------|-------------|-------------|
| Low Channel  | 8MHz              | 1    | 24.1        | 30dbm       |
|              | 8MHz              | 2    | 24.3        |             |
|              | 8MHz              | 3    | 24.4        |             |
| Mid Channel  | 8MHz              | 1    | 24.2        |             |
|              | 8MHz              | 2    | 23.8        |             |
|              | 8MHz              | 3    | 23.6        |             |
| High Channel | 8MHz              | 1    | 23.1        |             |
|              | 8MHz              | 2    | 23.8        |             |
|              | 8MHz              | 3    | 22.2        |             |


| Channel      | Channel Bandwidth | Mode | Power (dBm) | Limit (dBm) |
|--------------|-------------------|------|-------------|-------------|
| Low Channel  | 16MHz             | 1    | 24.9        | 30dBm       |
|              | 16MHz             | 2    | 24.3        |             |
|              | 16MHz             | 3    | 24.1        |             |
| Mid Channel  | 16MHz             | 1    | 24.8        |             |
|              | 16MHz             | 2    | 23.8        |             |
|              | 16MHz             | 3    | 23.1        |             |
| High Channel | 16MHz             | 1    | 23.1        |             |
|              | 16MHz             | 2    | 21.6        |             |
|              | 16MHz             | 3    | 22.5        |             |

| Channel      | Channel Bandwidth | Mode | Power (dBm) | Limit (dBm) |
|--------------|-------------------|------|-------------|-------------|
| Low Channel  | 32MHz             | 1    | 24.9        | 30dBm       |
|              | 32MHz             | 2    | 23.1        |             |
|              | 32MHz             | 3    | 24.2        |             |
| Mid Channel  | 32MHz             | 1    | 23.0        |             |
|              | 32MHz             | 2    | 23.2        |             |
|              | 32MHz             | 3    | 22.5        |             |
| High Channel | 32MHz             | 1    | 23.2        |             |
|              | 32MHz             | 2    | 22.4        |             |
|              | 32MHz             | 3    | 21.9        |             |


Refer to the attached plots.




Low Channel (8MHz Mode 1)




Low Channel (8MHz Mode 2)




Low Channel (8MHz Mode 3)




Mid Channel (8MHz Mode 1)




Mid Channel (8MHz Mode 2)




Mid Channel (8MHz Mode 3)




High Channel (8MHz Mode 1)




High Channel (8MHz Mode 2)




High Channel (8MHz Mode 3)




Low Channel (16MHz Mode 1)




Low Channel (16MHz Mode 2)




Low Channel (16MHz Mode 3)




Mid Channel (16MHz Mode 1)




Mid Channel (16MHz Mode 2)




Mid Channel (16MHz Mode 3)




High Channel (16MHz Mode 1)




High Channel (16MHz Mode 2)




High Channel (16MHz Mode 3)




Low Channel (32MHz Mode 1)




Low Channel (32MHz Mode 2)




Low Channel (32MHz Mode 3)




Mid Channel (32MHz Mode 1)




Mid Channel (32MHz Mode 2)




Mid Channel (32MHz Mode 3)



High Channel (32MHz Mode 1)



High Channel (32MHz Mode 2)



High Channel (32MHz Mode 3)

## 5.10 Antenna Port Emission

1. Conducted Measurement  
EUT was set for low , mid, high channel with modulated mode and highest RF output power.  
The spectrum analyzer was connected to the antenna terminal.
2. Conducted Emissions Measurement Uncertainty  
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 40GHz is  $\pm 1.5\text{dB}$ .
3. Environmental Conditions


|                      |          |
|----------------------|----------|
| Temperature          | 23°C     |
| Relative Humidity    | 50%      |
| Atmospheric Pressure | 1019mbar |
4. Test Date : July 10-21 2009  
Tested By :Choon Sian Ooi

**Standard Requirement :** 47 CFR §15.247(d); RSS210(A8.5)


**Procedures:** The conducted spurious emissions were measured conducted using a spectrum analyzer at low, mid, and hi channels. The limit was determined by attenuating 20 dB of the RF peak power output

**Test Result:**


Low Channel (8MHz Mode 1)




Low Channel (8MHz Mode 2)




Low Channel (8MHz Mode 3)




Mid Channel (8MHz Mode 1)




Mid Channel (8MHz Mode 2)




Mid Channel (8MHz Mode 3)




High Channel (8MHz Mode 1)




High Channel (8MHz Mode 2)




### High Channel (8MHz Mode 3)




### Low Channel (16MHz Mode 1)




Low Channel (16MHz Mode 2)




Low Channel (16MHz Mode 3)




Mid Channel (16MHz Mode 1)




Mid Channel (16MHz Mode 2)




Mid Channel (16MHz Mode 3)




High Channel (16MHz Mode 1)




High Channel (16MHz Mode 2)




High Channel (16MHz Mode 3)




Low Channel (32MHz Mode 1)




Low Channel (32MHz Mode 2)




Low Channel (32MHz Mode 3)




Mid Channel (32MHz Mode 1)




Mid Channel (32MHz Mode 2)




Mid Channel (32MHz Mode 3)




### High Channel (32MHz Mode 1)



### High Channel (32MHz Mode 2)



High Channel (32MHz Mode 3)



## 5.10 Radiated Spurious Emission < 1GHz

1. All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR detectors, are reported. All other emissions were relatively insignificant.
2. A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
3. Radiated Emissions Measurement Uncertainty  
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 1GHz (QP only @ 3m & 10m) is +5.6dB/-4.5dB (for EUTs < 0.5m X 0.5m X 0.5m).
4. Environmental Conditions
 

|                      |          |
|----------------------|----------|
| Temperature          | 23°C     |
| Relative Humidity    | 50%      |
| Atmospheric Pressure | 1019mbar |

Test Date : January 12-23 2009  
 Tested By : Choon Sian Ooi

**Standard Requirement :** 47 CFR §15.247(d); RSS210(A8.5)


**Procedures:** Radiated emissions were measured according to ANSI C63.4. The EUT was set to transmit at the highest output power. The EUT was set to transmit at mid channel. Note that setting the channel other than mid, the spurious emissions are the same.

The limit is converted from microvolts/meter to decibel microvolts/meter.

Sample Calculation: Corrected Amplitude = Raw Amplitude(dBμV/m) + ACF(dB) + Cable Loss(dB)

**Test Result:**


### Radiated Emission Plot (Transmit Mode)



### Test Data

| Frequency (MHz) | Quasi-Peak (dBμV/m) | Antenna height (cm) | Polarity | Turntable position (deg) | Limit (dBμV/m) | Margin (dB) |
|-----------------|---------------------|---------------------|----------|--------------------------|----------------|-------------|
| 959.98          | 44.84               | 108.00              | V        | 236.00                   | 46.00          | -1.16       |
| 39.35           | 34.91               | 104.00              | H        | 359.00                   | 40.00          | -5.09       |
| 39.66           | 34.19               | 101.00              | V        | 37.00                    | 40.00          | -5.81       |
| 599.99          | 38.69               | 104.00              | V        | 162.00                   | 46.00          | -7.31       |
| 359.99          | 38.82               | 100.00              | V        | 134.00                   | 46.00          | -7.18       |
| 720.00          | 34.65               | 207.00              | H        | 271.00                   | 46.00          | -11.35      |

## Radiated Emission Plot (Receive Mode)



## Test Data

| Frequency (MHz) | Quasi-Peak (dBμV/m) | Antenna height (cm) | Polarity | Turntable position (deg) | Limit (dBμV/m) | Margin (dB) |
|-----------------|---------------------|---------------------|----------|--------------------------|----------------|-------------|
| 959.98          | 44.97               | 108.00              | V        | 222.00                   | 46.00          | -1.03       |
| 359.99          | 40.44               | 200.00              | V        | 153.00                   | 46.00          | -5.56       |
| 600.01          | 40.21               | 100.00              | V        | 146.00                   | 46.00          | -5.79       |
| 39.77           | 31.34               | 110.00              | V        | 80.00                    | 40.00          | -8.66       |
| 39.57           | 31.65               | 103.00              | H        | 41.00                    | 40.00          | -8.35       |
| 720.00          | 37.49               | 103.00              | V        | 142.00                   | 46.00          | -8.51       |

## 5.10 Radiated Spurious Emissions > 1GHz & Band Edge

- All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR detectors, are reported. All other emissions were relatively insignificant.
- A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
- Radiated Emissions Measurement Uncertainty  
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 1GHz – 40GH is +5.6dB/-4.5dB (for EUTs < 0.5m X 0.5m X 0.5m).
- |                          |                      |          |
|--------------------------|----------------------|----------|
| Environmental Conditions | Temperature          | 23°C     |
|                          | Relative Humidity    | 50%      |
|                          | Atmospheric Pressure | 1019mbar |

Test Date : January 12-23 2009  
Tested By :Choon Sian Ooi

Standard Requirement: 47 CFR §15.247(d); RSS210(A8.5)

**Procedures:** Equipment was setup in a semi-anechoic chamber. For measurements above 1 GHz an average measurement was taken with a 10Hz video bandwidth. The EUT was tested at low, mid and high with the highest output power. Investigated up to 10<sup>th</sup> harmonic of the operating frequency.

Sample Calculation:

EUT Field Strength = Raw Amplitude(dBμ V/m) – Amplifier Gain(dB) + Antenna Factor(dB) + Cable Loss(dB) + Filter Attenuation(dB, if used)

**Test Result:**

### Low Channel (8MHz Mode 1)

| Frequency | Reading  | Direction | Height | Polar | Antenna Loss | Cable loss | Amplifier | Corrected Reading | 15.247/15.209  | 15.247/15.209 |          |
|-----------|----------|-----------|--------|-------|--------------|------------|-----------|-------------------|----------------|---------------|----------|
| GHz       | (dBuV/m) | Degree    | Meter  | H / V | (dB)         | (dB)       | (dB)      | (dBuV/m)          | Limit (dBuV/m) | Margin        | Comments |
| 11.46     | 52.78    | 0.00      | 1.50   | v     | 42.20        | 7.17       | 32.70     | 69.45             | 74.00          | -4.55         | Peak     |
| 11.46     | 49.67    | 0.00      | 1.50   | h     | 42.20        | 7.17       | 32.70     | 66.34             | 74.00          | -7.66         | Peak     |
| 11.46     | 36.94    | 0.00      | 1.50   | v     | 42.20        | 7.17       | 32.70     | 53.61             | 54.00          | -0.39         | Ave      |
| 11.46     | 36.77    | 0.00      | 1.50   | h     | 42.20        | 7.17       | 32.70     | 53.44             | 54.00          | -0.56         | Ave      |

### Low Channel (8MHz Mode 2)

| Frequency | Reading  | Direction | Height | Polar | Antenna Loss | Cable loss | Amplifier | Corrected Reading | 15.247/15.209  | 15.247/15.209 |          |
|-----------|----------|-----------|--------|-------|--------------|------------|-----------|-------------------|----------------|---------------|----------|
| GHz       | (dBuV/m) | Degree    | Meter  | H / V | (dB)         | (dB)       | (dB)      | (dBuV/m)          | Limit (dBuV/m) | Margin        | Comments |
| 11.462    | 52.23    | 0         | 1.5    | v     | 42.2         | 7.17       | 32.7      | 68.9              | 74             | -5.10         | Peak     |
| 11.462    | 50.57    | 0         | 1.5    | h     | 42.2         | 7.17       | 32.7      | 67.24             | 74             | -6.76         | Peak     |
| 11.462    | 36.85    | 0         | 1.5    | v     | 42.2         | 7.17       | 32.7      | 53.52             | 54             | -0.48         | Ave      |
| 11.462    | 36.69    | 0         | 1.5    | h     | 42.2         | 7.17       | 32.7      | 53.36             | 54             | -0.64         | Ave      |

### Low Channel (8MHz Mode 3)

| Frequency | Reading  | Direction | Height | Polar | Antenna Loss | Cable loss | Amplifier | Corrected Reading | 15.247/15.209  | 15.247/15.209 |          |
|-----------|----------|-----------|--------|-------|--------------|------------|-----------|-------------------|----------------|---------------|----------|
| GHz       | (dBuV/m) | Degree    | Meter  | H / V | (dB)         | (dB)       | (dB)      | (dBuV/m)          | Limit (dBuV/m) | Margin        | Comments |
| 11.46     | 53.67    | 0.00      | 1.50   | v     | 42.20        | 7.17       | 32.70     | 70.34             | 74.00          | -3.66         | Peak     |
| 11.46     | 56.23    | 0.00      | 1.50   | h     | 42.20        | 7.17       | 32.70     | 72.90             | 74.00          | -1.10         | Peak     |
| 11.46     | 36.34    | 0.00      | 1.50   | v     | 42.20        | 7.17       | 32.70     | 53.01             | 54.00          | -0.99         | Ave      |
| 11.46     | 36.65    | 0.00      | 1.50   | h     | 42.20        | 7.17       | 32.70     | 53.32             | 54.00          | -0.68         | Ave      |

### Mid Channel (8MHz Mode 1)

| Frequency | Reading  | Direction | Height | Polar | Antenna Loss | Cable loss | Amplifier | Corrected Reading | 15.247/15.209  | 15.247/15.209 |          |
|-----------|----------|-----------|--------|-------|--------------|------------|-----------|-------------------|----------------|---------------|----------|
| GHz       | (dBuV/m) | Degree    | Meter  | H / V | (dB)         | (dB)       | (dB)      | (dBuV/m)          | Limit (dBuV/m) | Margin        | Comments |
| 11.57     | 54.96    | 0.00      | 1.50   | v     | 43.20        | 7.42       | 32.51     | 73.07             | 74.00          | -0.94         | Peak     |
| 11.57     | 54.14    | 0.00      | 1.50   | h     | 43.20        | 7.42       | 32.51     | 72.25             | 74.00          | -1.76         | Peak     |
| 11.57     | 35.67    | 0.00      | 1.50   | v     | 43.20        | 7.42       | 32.51     | 53.78             | 54.00          | -0.22         | Ave      |
| 11.57     | 35.74    | 0.00      | 1.50   | h     | 43.20        | 7.42       | 32.51     | 53.85             | 54.00          | -0.15         | Ave      |

### Mid Channel (8MHz Mode 2)

| Frequency | Reading  | Direction | Height | Polar | Antenna Loss | Cable loss | Amplifier | Corrected Reading | 15.247/15.209  | 15.247/15.209 |          |
|-----------|----------|-----------|--------|-------|--------------|------------|-----------|-------------------|----------------|---------------|----------|
| GHz       | (dBuV/m) | Degree    | Meter  | H / V | (dB)         | (dB)       | (dB)      | (dBuV/m)          | Limit (dBuV/m) | Margin        | Comments |
| 11.57     | 54.94    | 0.00      | 1.50   | v     | 43.20        | 7.42       | 32.51     | 73.05             | 74.00          | -0.95         | Peak     |
| 11.57     | 54.73    | 0.00      | 1.50   | h     | 43.20        | 7.42       | 32.51     | 72.84             | 74.00          | -1.16         | Peak     |
| 11.57     | 35.37    | 0.00      | 1.50   | v     | 43.20        | 7.42       | 32.51     | 53.48             | 54.00          | -0.52         | Ave      |
| 11.57     | 35.17    | 0.00      | 1.50   | h     | 43.20        | 7.42       | 32.51     | 53.28             | 54.00          | -0.72         | Ave      |

Mid Channel (8MHz Mode 3)

| Frequency | Reading  | Direction | Height | Polar | Antenna Loss | Cable loss | Amplifier | Corrected Reading | 15.247/15.209  | 15.247/15.209 |          |
|-----------|----------|-----------|--------|-------|--------------|------------|-----------|-------------------|----------------|---------------|----------|
| GHz       | (dBuV/m) | Degree    | Meter  | H / V | (dB)         | (dB)       | (dB)      | (dBuV/m)          | Limit (dBuV/m) | Margin        | Comments |
| 11.57     | 54.54    | 0.00      | 1.50   | v     | 43.20        | 7.42       | 32.51     | 72.65             | 74.00          | -1.35         | Peak     |
| 11.57     | 54.23    | 0.00      | 1.50   | h     | 43.20        | 7.42       | 32.51     | 72.34             | 74.00          | -1.66         | Peak     |
| 11.57     | 35.75    | 0.00      | 1.50   | v     | 43.20        | 7.42       | 32.51     | 53.86             | 54.00          | -0.14         | Ave      |
| 11.57     | 35.64    | 0.00      | 1.50   | h     | 43.20        | 7.42       | 32.51     | 53.75             | 54.00          | -0.25         | Ave      |

High Channel (8MHz Mode 1)

| Frequency | Reading  | Direction | Height | Polar | Antenna Loss | Cable loss | Amplifier | Corrected Reading | 15.247/15.209  | 15.247/15.209 |          |
|-----------|----------|-----------|--------|-------|--------------|------------|-----------|-------------------|----------------|---------------|----------|
| GHz       | (dBuV/m) | Degree    | Meter  | H / V | (dB)         | (dB)       | (dB)      | (dBuV/m)          | Limit (dBuV/m) | Margin        | Comments |
| 11.57     | 54.54    | 0.00      | 1.50   | v     | 43.20        | 7.42       | 32.51     | 72.65             | 74.00          | -1.35         | Peak     |
| 11.57     | 54.23    | 0.00      | 1.50   | h     | 43.20        | 7.42       | 32.51     | 72.34             | 74.00          | -1.66         | Peak     |
| 11.57     | 35.75    | 0.00      | 1.50   | v     | 43.20        | 7.42       | 32.51     | 53.86             | 54.00          | -0.14         | Ave      |
| 11.57     | 35.64    | 0.00      | 1.50   | h     | 43.20        | 7.42       | 32.51     | 53.75             | 54.00          | -0.25         | Ave      |

High Channel (8MHz Mode 2)

| Frequency | Reading  | Direction | Height | Polar | Antenna Loss | Cable loss | Amplifier | Corrected Reading | 15.247/15.209  | 15.247/15.209 |          |
|-----------|----------|-----------|--------|-------|--------------|------------|-----------|-------------------|----------------|---------------|----------|
| GHz       | (dBuV/m) | Degree    | Meter  | H / V | (dB)         | (dB)       | (dB)      | (dBuV/m)          | Limit (dBuV/m) | Margin        | Comments |
| 11.57     | 54.54    | 0.00      | 1.50   | v     | 43.20        | 7.42       | 32.51     | 72.65             | 74.00          | -1.35         | Peak     |
| 11.57     | 54.23    | 0.00      | 1.50   | h     | 43.20        | 7.42       | 32.51     | 72.34             | 74.00          | -1.66         | Peak     |
| 11.57     | 35.75    | 0.00      | 1.50   | v     | 43.20        | 7.42       | 32.51     | 53.86             | 54.00          | -0.14         | Ave      |
| 11.57     | 35.64    | 0.00      | 1.50   | h     | 43.20        | 7.42       | 32.51     | 53.75             | 54.00          | -0.25         | Ave      |

High Channel (8MHz Mode 3)

| Frequency | Reading  | Direction | Height | Polar | Antenna Loss | Cable loss | Amplifier | Corrected Reading | 15.247/15.209  | 15.247/15.209 |          |
|-----------|----------|-----------|--------|-------|--------------|------------|-----------|-------------------|----------------|---------------|----------|
| GHz       | (dBuV/m) | Degree    | Meter  | H / V | (dB)         | (dB)       | (dB)      | (dBuV/m)          | Limit (dBuV/m) | Margin        | Comments |
| 11.69     | 55.52    | 0.00      | 1.50   | v     | 43.20        | 7.42       | 32.51     | 73.63             | 74.00          | -0.38         | Peak     |
| 11.69     | 55.22    | 0.00      | 1.50   | h     | 43.20        | 7.42       | 32.51     | 73.33             | 74.00          | -0.67         | Peak     |
| 11.69     | 35.83    | 0.00      | 1.50   | v     | 43.20        | 7.42       | 32.51     | 53.94             | 54.00          | -0.06         | Ave      |
| 11.69     | 35.62    | 0.00      | 1.50   | h     | 43.20        | 7.42       | 32.51     | 53.73             | 54.00          | -0.27         | Ave      |

Low Channel (16MHz Mode 1)

| Frequency | Reading  | Direction | Height | Polar | Antenna Loss | Cable loss | Amplifier | Corrected Reading | 15.247/15.209  | 15.247/15.209 |          |
|-----------|----------|-----------|--------|-------|--------------|------------|-----------|-------------------|----------------|---------------|----------|
| GHz       | (dBuV/m) | Degree    | Meter  | H / V | (dB)         | (dB)       | (dB)      | (dBuV/m)          | Limit (dBuV/m) | Margin        | Comments |
| 11.47     | 56.52    | 0.00      | 1.50   | v     | 42.20        | 7.17       | 32.70     | 73.19             | 74.00          | -0.81         | Peak     |
| 11.47     | 56.28    | 0.00      | 1.50   | h     | 42.20        | 7.17       | 32.70     | 72.95             | 74.00          | -1.05         | Peak     |
| 11.47     | 35.77    | 0.00      | 1.50   | v     | 42.20        | 7.17       | 32.70     | 52.44             | 54.00          | -1.56         | Ave      |
| 11.47     | 35.62    | 0.00      | 1.50   | h     | 42.20        | 7.17       | 32.70     | 52.29             | 54.00          | -1.71         | Ave      |

Low Channel (16MHz Mode 2)

| Frequency | Reading  | Direction | Height | Polar | Antenna Loss | Cable loss | Amplifier | Corrected Reading | 15.247/15.209  | 15.247/15.209 |          |
|-----------|----------|-----------|--------|-------|--------------|------------|-----------|-------------------|----------------|---------------|----------|
| GHz       | (dBuV/m) | Degree    | Meter  | H / V | (dB)         | (dB)       | (dB)      | (dBuV/m)          | Limit (dBuV/m) | Margin        | Comments |
| 11.47     | 56.82    | 0.00      | 1.50   | v     | 42.20        | 7.17       | 32.70     | 73.49             | 74.00          | -0.51         | Peak     |
| 11.47     | 56.29    | 0.00      | 1.50   | h     | 42.20        | 7.17       | 32.70     | 72.96             | 74.00          | -1.04         | Peak     |
| 11.47     | 37.15    | 0.00      | 1.50   | v     | 42.20        | 7.17       | 32.70     | 53.82             | 54.00          | -0.18         | Ave      |
| 11.47     | 36.96    | 0.00      | 1.50   | h     | 42.20        | 7.17       | 32.70     | 53.63             | 54.00          | -0.37         | Ave      |

Low Channel (16MHz Mode 3)

| Frequency | Reading  | Direction | Height | Polar | Antenna Loss | Cable loss | Amplifier | Corrected Reading | 15.247/15.209  | 15.247/15.209 |          |
|-----------|----------|-----------|--------|-------|--------------|------------|-----------|-------------------|----------------|---------------|----------|
| GHz       | (dBuV/m) | Degree    | Meter  | H / V | (dB)         | (dB)       | (dB)      | (dBuV/m)          | Limit (dBuV/m) | Margin        | Comments |
| 11.47     | 56.47    | v160      | 1.00   | v     | 42.20        | 7.17       | 32.70     | 73.14             | 74.00          | -0.86         | Peak     |
| 11.47     | 56.27    | 178.00    | 1.30   | h     | 42.20        | 7.17       | 32.70     | 72.94             | 74.00          | -1.06         | Peak     |
| 11.47     | 37.32    | 160.00    | 1.00   | v     | 42.20        | 7.17       | 32.70     | 53.99             | 54.00          | -0.01         | Ave      |
| 11.47     | 36.21    | 178.00    | 1.30   | h     | 42.20        | 7.17       | 32.70     | 52.88             | 54.00          | -1.12         | Ave      |

Mid Channel (16MHz Mode 1)

| Frequency | Reading  | Direction | Height | Polar | Antenna Loss | Cable loss | Amplifier | Corrected Reading | 15.247/15.209  | 15.247/15.209 |          |
|-----------|----------|-----------|--------|-------|--------------|------------|-----------|-------------------|----------------|---------------|----------|
| GHz       | (dBuV/m) | Degree    | Meter  | H / V | (dB)         | (dB)       | (dB)      | (dBuV/m)          | Limit (dBuV/m) | Margin        | Comments |
| 11.58     | 55.86    | 0.00      | 1.50   | v     | 43.20        | 7.42       | 32.51     | 73.97             | 74.00          | -0.03         | Peak     |
| 11.58     | 55.69    | 0.00      | 1.50   | h     | 43.20        | 7.42       | 32.51     | 73.80             | 74.00          | -0.20         | Peak     |
| 11.58     | 35.74    | 0.00      | 1.50   | v     | 43.20        | 7.42       | 32.51     | 53.85             | 54.00          | -0.15         | Ave      |
| 11.58     | 35.36    | 0.00      | 1.50   | h     | 43.20        | 7.42       | 32.51     | 53.47             | 54.00          | -0.53         | Ave      |

Mid Channel (16MHz Mode 2)

| Frequency | Reading  | Direction | Height | Polar | Antenna Loss | Cable loss | Amplifier | Corrected Reading | 15.247/15.209  | 15.247/15.209 |          |
|-----------|----------|-----------|--------|-------|--------------|------------|-----------|-------------------|----------------|---------------|----------|
| GHz       | (dBuV/m) | Degree    | Meter  | H / V | (dB)         | (dB)       | (dB)      | (dBuV/m)          | Limit (dBuV/m) | Margin        | Comments |
| 11.58     | 55.54    | 0.00      | 1.50   | v     | 43.20        | 7.42       | 32.51     | 73.65             | 74.00          | -0.35         | Peak     |
| 11.58     | 55.51    | 0.00      | 1.50   | h     | 43.20        | 7.42       | 32.51     | 73.62             | 74.00          | -0.38         | Peak     |
| 11.58     | 35.86    | 0.00      | 1.50   | v     | 43.20        | 7.42       | 32.51     | 53.97             | 54.00          | -0.03         | Ave      |
| 11.58     | 35.77    | 0.00      | 1.50   | h     | 43.20        | 7.42       | 32.51     | 53.88             | 54.00          | -0.12         | Ave      |

Mid Channel (16MHz Mode 3)

| Frequency | Reading  | Direction | Height | Polar | Antenna Loss | Cable loss | Amplifier | Corrected Reading | 15.247/15.209  | 15.247/15.209 |          |
|-----------|----------|-----------|--------|-------|--------------|------------|-----------|-------------------|----------------|---------------|----------|
| GHz       | (dBuV/m) | Degree    | Meter  | H / V | (dB)         | (dB)       | (dB)      | (dBuV/m)          | Limit (dBuV/m) | Margin        | Comments |
| 11.58     | 55.68    | 0.00      | 1.50   | v     | 43.20        | 7.42       | 32.51     | 73.79             | 74.00          | -0.22         | Peak     |
| 11.58     | 55.62    | 0.00      | 1.50   | h     | 43.20        | 7.42       | 32.51     | 73.73             | 74.00          | -0.28         | Peak     |
| 11.58     | 35.64    | 0.00      | 1.50   | v     | 43.20        | 7.42       | 32.51     | 53.75             | 54.00          | -0.25         | Ave      |
| 11.58     | 35.56    | 0.00      | 1.50   | h     | 43.20        | 7.42       | 32.51     | 53.67             | 54.00          | -0.33         | Ave      |

High Channel (16MHz Mode 1)

| Frequency | Reading  | Direction | Height | Polar | Antenna Loss | Cable loss | Amplifier | Corrected Reading | 15.247/15.209  | 15.247/15.209 |          |
|-----------|----------|-----------|--------|-------|--------------|------------|-----------|-------------------|----------------|---------------|----------|
| GHz       | (dBuV/m) | Degree    | Meter  | H / V | (dB)         | (dB)       | (dB)      | (dBuV/m)          | Limit (dBuV/m) | Margin        | Comments |
| 11.68     | 54.95    | 0.00      | 1.50   | v     | 43.20        | 7.42       | 32.51     | 73.06             | 74.00          | -0.94         | Peak     |
| 11.68     | 54.75    | 0.00      | 1.50   | h     | 43.20        | 7.42       | 32.51     | 72.86             | 74.00          | -1.14         | Peak     |
| 11.68     | 35.36    | 0.00      | 1.50   | v     | 43.20        | 7.42       | 32.51     | 53.47             | 54.00          | -0.53         | Ave      |
| 11.68     | 35.17    | 0.00      | 1.50   | h     | 43.20        | 7.42       | 32.51     | 53.28             | 54.00          | -0.72         | Ave      |

High Channel (16MHz Mode 2)

| Frequency | Reading  | Direction | Height | Polar | Antenna Loss | Cable loss | Amplifier | Corrected Reading | 15.247/15.209  | 15.247/15.209 |          |
|-----------|----------|-----------|--------|-------|--------------|------------|-----------|-------------------|----------------|---------------|----------|
| GHz       | (dBuV/m) | Degree    | Meter  | H / V | (dB)         | (dB)       | (dB)      | (dBuV/m)          | Limit (dBuV/m) | Margin        | Comments |
| 11.68     | 55.58    | 0.00      | 1.50   | v     | 43.20        | 7.42       | 32.51     | 73.69             | 74.00          | -0.31         | Peak     |
| 11.68     | 55.36    | 0.00      | 1.50   | h     | 43.20        | 7.42       | 32.51     | 73.47             | 74.00          | -0.53         | Peak     |
| 11.68     | 35.41    | 0.00      | 1.50   | v     | 43.20        | 7.42       | 32.51     | 53.52             | 54.00          | -0.48         | Ave      |
| 11.68     | 35.27    | 0.00      | 1.50   | h     | 43.20        | 7.42       | 32.51     | 53.38             | 54.00          | -0.62         | Ave      |

High Channel (16MHz Mode 3)

| Frequency | Reading  | Direction | Height | Polar | Antenna Loss | Cable loss | Amplifier | Corrected Reading | 15.247/15.209  | 15.247/15.209 |          |
|-----------|----------|-----------|--------|-------|--------------|------------|-----------|-------------------|----------------|---------------|----------|
| GHz       | (dBuV/m) | Degree    | Meter  | H / V | (dB)         | (dB)       | (dB)      | (dBuV/m)          | Limit (dBuV/m) | Margin        | Comments |
| 11.68     | 55.24    | 0.00      | 1.50   | v     | 43.20        | 7.42       | 32.51     | 73.35             | 74.00          | -0.66         | Peak     |
| 11.68     | 55.19    | 0.00      | 1.50   | h     | 43.20        | 7.42       | 32.51     | 73.30             | 74.00          | -0.70         | Peak     |
| 11.68     | 35.17    | 0.00      | 1.50   | v     | 43.20        | 7.42       | 32.51     | 53.28             | 54.00          | -0.72         | Ave      |
| 11.68     | 35.04    | 0.00      | 1.50   | h     | 43.20        | 7.42       | 32.51     | 53.15             | 54.00          | -0.85         | Ave      |

Low Channel (32MHz Mode 1)

| Frequency | Reading  | Direction | Height | Polar | Antenna Loss | Cable loss | Amplifier | Corrected Reading | 15.247/15.209  | 15.247/15.209 |          |
|-----------|----------|-----------|--------|-------|--------------|------------|-----------|-------------------|----------------|---------------|----------|
| GHz       | (dBuV/m) | Degree    | Meter  | H / V | (dB)         | (dB)       | (dB)      | (dBuV/m)          | Limit (dBuV/m) | Margin        | Comments |
| 11.49     | 57.16    | 0.00      | 1.50   | v     | 42.20        | 7.17       | 32.70     | 73.83             | 74.00          | -0.17         | Peak     |
| 11.49     | 56.74    | 0.00      | 1.50   | h     | 42.20        | 7.17       | 32.70     | 73.41             | 74.00          | -0.59         | Peak     |
| 11.49     | 37.17    | 0.00      | 1.50   | v     | 42.20        | 7.17       | 32.70     | 53.84             | 54.00          | -0.16         | Ave      |
| 11.49     | 36.95    | 0.00      | 1.50   | h     | 42.20        | 7.17       | 32.70     | 53.62             | 54.00          | -0.38         | Ave      |

Low Channel (32MHz Mode 2)

| Frequency | Reading  | Direction | Height | Polar | Antenna Loss | Cable loss | Amplifier | Corrected Reading | 15.247/15.209  | 15.247/15.209 |          |
|-----------|----------|-----------|--------|-------|--------------|------------|-----------|-------------------|----------------|---------------|----------|
| GHz       | (dBuV/m) | Degree    | Meter  | H / V | (dB)         | (dB)       | (dB)      | (dBuV/m)          | Limit (dBuV/m) | Margin        | Comments |
| 11.49     | 56.94    | 0.00      | 1.50   | v     | 42.20        | 7.17       | 32.70     | 73.61             | 74.00          | -0.39         | Peak     |
| 11.49     | 56.59    | 0.00      | 1.50   | h     | 42.20        | 7.17       | 32.70     | 73.26             | 74.00          | -0.74         | Peak     |
| 11.49     | 36.64    | 0.00      | 1.50   | v     | 42.20        | 7.17       | 32.70     | 53.31             | 54.00          | -0.69         | Ave      |
| 11.49     | 36.34    | 0.00      | 1.50   | h     | 42.20        | 7.17       | 32.70     | 53.01             | 54.00          | -0.99         | Ave      |

Low Channel (32MHz Mode 3)

| Frequency | Reading  | Direction | Height | Polar | Antenna Loss | Cable loss | Amplifier | Corrected Reading | 15.247/15.209  | 15.247/15.209 |          |
|-----------|----------|-----------|--------|-------|--------------|------------|-----------|-------------------|----------------|---------------|----------|
| GHz       | (dBuV/m) | Degree    | Meter  | H / V | (dB)         | (dB)       | (dB)      | (dBuV/m)          | Limit (dBuV/m) | Margin        | Comments |
| 11.49     | 57.44    | 0.00      | 1.50   | v     | 42.20        | 7.17       | 32.70     | 74.11             | 74.00          | 0.11          | Peak     |
| 11.49     | 57.13    | 0.00      | 1.50   | h     | 42.20        | 7.17       | 32.70     | 73.80             | 74.00          | -0.20         | Peak     |
| 11.49     | 36.74    | 0.00      | 1.50   | v     | 42.20        | 7.17       | 32.70     | 53.41             | 54.00          | -0.59         | Ave      |
| 11.49     | 36.57    | 0.00      | 1.50   | h     | 42.20        | 7.17       | 32.70     | 53.24             | 54.00          | -0.76         | Ave      |

Mid Channel (32MHz Mode 1)

| Frequency | Reading  | Direction | Height | Polar | Antenna Loss | Cable loss | Amplifier | Corrected Reading | 15.247/15.209  | 15.247/15.209 |          |
|-----------|----------|-----------|--------|-------|--------------|------------|-----------|-------------------|----------------|---------------|----------|
| GHz       | (dBuV/m) | Degree    | Meter  | H / V | (dB)         | (dB)       | (dB)      | (dBuV/m)          | Limit (dBuV/m) | Margin        | Comments |
| 11.58     | 55.36    | 0.00      | 1.50   | v     | 43.20        | 7.42       | 32.51     | 73.47             | 74.00          | -0.53         | Peak     |
| 11.58     | 55.13    | 0.00      | 1.50   | h     | 43.20        | 7.42       | 32.51     | 73.24             | 74.00          | -0.76         | Peak     |
| 11.58     | 35.34    | 0.00      | 1.50   | v     | 43.20        | 7.42       | 32.51     | 53.45             | 54.00          | -0.55         | Ave      |
| 11.58     | 35.25    | 0.00      | 1.50   | h     | 43.20        | 7.42       | 32.51     | 53.36             | 54.00          | -0.64         | Ave      |

Mid Channel (32MHz Mode 2)

| Frequency | Reading  | Direction | Height | Polar | Antenna Loss | Cable loss | Amplifier | Corrected Reading | 15.247/15.209  | 15.247/15.209 |          |
|-----------|----------|-----------|--------|-------|--------------|------------|-----------|-------------------|----------------|---------------|----------|
| GHz       | (dBuV/m) | Degree    | Meter  | H / V | (dB)         | (dB)       | (dB)      | (dBuV/m)          | Limit (dBuV/m) | Margin        | Comments |
| 11.58     | 55.16    | 0.00      | 1.50   | v     | 43.20        | 7.42       | 32.51     | 73.27             | 74.00          | -0.73         | Peak     |
| 11.58     | 55.02    | 0.00      | 1.50   | h     | 43.20        | 7.42       | 32.51     | 73.13             | 74.00          | -0.88         | Peak     |
| 11.58     | 35.42    | 0.00      | 1.50   | v     | 43.20        | 7.42       | 32.51     | 53.53             | 54.00          | -0.47         | Ave      |
| 11.58     | 35.39    | 0.00      | 1.50   | h     | 43.20        | 7.42       | 32.51     | 53.50             | 54.00          | -0.50         | Ave      |

Mid Channel (32MHz Mode 3)

| Frequency | Reading  | Direction | Height | Polar | Antenna Loss | Cable loss | Amplifier | Corrected Reading | 15.247/15.209  | 15.247/15.209 |          |
|-----------|----------|-----------|--------|-------|--------------|------------|-----------|-------------------|----------------|---------------|----------|
| GHz       | (dBuV/m) | Degree    | Meter  | H / V | (dB)         | (dB)       | (dB)      | (dBuV/m)          | Limit (dBuV/m) | Margin        | Comments |
| 11.58     | 55.46    | 0.00      | 1.50   | v     | 43.20        | 7.42       | 32.51     | 73.57             | 74.00          | -0.44         | Peak     |
| 11.58     | 55.24    | 0.00      | 1.50   | h     | 43.20        | 7.42       | 32.51     | 73.35             | 74.00          | -0.66         | Peak     |
| 11.58     | 35.12    | 0.00      | 1.50   | v     | 43.20        | 7.42       | 32.51     | 53.23             | 54.00          | -0.77         | Ave      |
| 11.58     | 35.29    | 0.00      | 1.50   | h     | 43.20        | 7.42       | 32.51     | 53.40             | 54.00          | -0.60         | Ave      |

High Channel (32MHz Mode 1)

| Frequency | Reading  | Direction | Height | Polar | Antenna Loss | Cable loss | Amplifier | Corrected Reading | 15.247/15.209  | 15.247/15.209 |          |
|-----------|----------|-----------|--------|-------|--------------|------------|-----------|-------------------|----------------|---------------|----------|
| GHz       | (dBuV/m) | Degree    | Meter  | H / V | (dB)         | (dB)       | (dB)      | (dBuV/m)          | Limit (dBuV/m) | Margin        | Comments |
| 11.66     | 55.36    | 0.00      | 1.50   | v     | 43.20        | 7.42       | 32.51     | 73.47             | 74.00          | -0.53         | Peak     |
| 11.66     | 55.14    | 0.00      | 1.50   | h     | 43.20        | 7.42       | 32.51     | 73.25             | 74.00          | -0.75         | Peak     |
| 11.66     | 35.32    | 0.00      | 1.50   | v     | 43.20        | 7.42       | 32.51     | 53.43             | 54.00          | -0.57         | Ave      |
| 11.66     | 35.21    | 0.00      | 1.50   | h     | 43.20        | 7.42       | 32.51     | 53.32             | 54.00          | -0.68         | Ave      |


High Channel (32MHz Mode 2)

| Frequency | Reading  | Direction | Height | Polar | Antenna Loss | Cable loss | Amplifier | Corrected Reading | 15.247/15.209  | 15.247/15.209 |          |
|-----------|----------|-----------|--------|-------|--------------|------------|-----------|-------------------|----------------|---------------|----------|
| GHz       | (dBuV/m) | Degree    | Meter  | H / V | (dB)         | (dB)       | (dB)      | (dBuV/m)          | Limit (dBuV/m) | Margin        | Comments |
| 11.66     | 55.31    | 0.00      | 1.50   | v     | 43.20        | 7.42       | 32.51     | 73.42             | 74.00          | -0.58         | Peak     |
| 11.66     | 55.29    | 0.00      | 1.50   | h     | 43.20        | 7.42       | 32.51     | 73.40             | 74.00          | -0.60         | Peak     |
| 11.66     | 35.12    | 0.00      | 1.50   | v     | 43.20        | 7.42       | 32.51     | 53.23             | 54.00          | -0.77         | Ave      |
| 11.66     | 35.04    | 0.00      | 1.50   | h     | 43.20        | 7.42       | 32.51     | 53.15             | 54.00          | -0.85         | Ave      |


High Channel (32MHz Mode 3)

| Frequency | Reading  | Direction | Height | Polar | Antenna Loss | Cable loss | Amplifier | Corrected Reading | 15.247/15.209  | 15.247/15.209 |          |
|-----------|----------|-----------|--------|-------|--------------|------------|-----------|-------------------|----------------|---------------|----------|
| GHz       | (dBuV/m) | Degree    | Meter  | H / V | (dB)         | (dB)       | (dB)      | (dBuV/m)          | Limit (dBuV/m) | Margin        | Comments |
| 11.66     | 55.41    | 0.00      | 1.50   | v     | 43.20        | 7.42       | 32.51     | 73.52             | 74.00          | -0.48         | Peak     |
| 11.66     | 55.36    | 0.00      | 1.50   | h     | 43.20        | 7.42       | 32.51     | 73.47             | 74.00          | -0.53         | Peak     |
| 11.66     | 35.34    | 0.00      | 1.50   | v     | 43.20        | 7.42       | 32.51     | 53.45             | 54.00          | -0.55         | Ave      |
| 11.66     | 35.19    | 0.00      | 1.50   | h     | 43.20        | 7.42       | 32.51     | 53.30             | 54.00          | -0.70         | Ave      |


Vertical Polarity




Low Channel (8MHz Mode 1)




Low Channel (8MHz Mode 2)




Low Channel (8MHz Mode 3)




High Channel (8MHz Mode 1)




### High Channel (8MHz Mode 2)




### High Channel (8MHz Mode 3)




### Low Channel (16MHz Mode 1)




### Low Channel (16MHz Mode 2)




### Low Channel (16MHz Mode 3)




### High Channel (16MHz Mode 1)




### High Channel (16MHz Mode 2)




### High Channel (16MHz Mode 3)




### Low Channel (32MHz Mode 1)




### Low Channel (32MHz Mode 2)




### Low Channel (32MHz Mode 3)



### High Channel (32MHz Mode 1)




### High Channel (32MHz Mode 2)




### High Channel (32MHz Mode 3)


## Horizontal Polarity




### Low Channel (8MHz Mode 1)




### Low Channel (8MHz Mode 2)




Low Channel (8MHz Mode 3)




High Channel (8MHz Mode 1)




High Channel (8MHz Mode 2)




High Channel (8MHz Mode 3)




### Low Channel (16MHz Mode 1)




### Low Channel (16MHz Mode 2)




### Low Channel (16MHz Mode 3)







### High Channel (16MHz Mode 2)




### High Channel (16MHz Mode 3)




Low Channel (32MHz Mode 1)




Low Channel (32MHz Mode 2)




### Low Channel (32MHz Mode 3)



### High Channel (32MHz Mode 1)



High Channel (32MHz Mode 2)



High Channel (32MHz Mode 3)

## Annex A. TEST INSTRUMENT & METHOD

### Annex A.i. TEST INSTRUMENTATION & GENERAL PROCEDURES

| Instrument                      | Manufacturer    | Model   | CAL Due Date |
|---------------------------------|-----------------|---------|--------------|
| Spectrum Analyzer               | HP              | 8564E   | 04/26/2010   |
| EMI Receiver                    | Rohde & Schwarz | ESIB 40 | 4/25/2010    |
| R&S LISN                        | R&S             | ESH2-Z5 | 04/24/2010   |
| CHASE LISN                      | Chase           | MN2050B | 04/24/2010   |
| Antenna(1 ~18GHz)               | Emco            | 3115    | 01/04/2010   |
| Antenna<br>(30MHz~2GHz)         | Sunol Sciences  | JB1     | 01/04/2010   |
| Chamber                         | Lingren         | 3m      | 04/18/2010   |
| Pre-Amplifier(1 ~<br>26GHz)     | HP              | 8449    | 04/24/2010   |
| Horn Antenna<br>(18~40GHz)      | Com Power       | AH-840  | 03/19/2010   |
| Microwave Pre-Amp<br>(18~40GHz) | Com Power       | PA-840  | 03/19/2010   |

Note: No calibration required.

## Annex A.ii. CONDUCTED EMISSIONS TEST DESCRIPTION

### Test Set-up

1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table, as shown in [Annex B](#).
2. The power supply for the EUT was fed through a 50 $\Omega$ /50 $\mu$ H EUT LISN, connected to filtered mains.
3. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss coaxial cable.
4. All other supporting equipments were powered separately from another main supply.

### Test Method

1. The EUT was switched on and allowed to warm up to its normal operating condition.
2. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver.
3. High peaks, relative to the limit line, were then selected.
4. The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 KHz. For FCC tests, only Quasi-peak measurements were made; while for CISPR/EN tests, both Quasi-peak and Average measurements were made.
5. Steps 2 to 4 were then repeated for the LIVE line (for AC mains) or DC line (for DC power).

### Sample Calculation Example

At 20 MHz

limit = 250  $\mu$ V = 47.96 dB $\mu$ V

Transducer factor of LISN, pulse limiter & cable loss at 20 MHz = 11.20 dB

Q-P reading obtained directly from EMI Receiver = 40.00 dB $\mu$ V

(Calibrated for system losses)

Therefore, Q-P margin = 47.96 – 40.00 = 7.96

i.e. **7.96 dB below limit**

## Annex A. iii RADIATED EMISSIONS TEST DESCRIPTION


### EUT Characterisation

EUT characterisation, over the frequency range from 30MHz to 10<sup>th</sup> Harmonic , was done in order to minimise radiated emissions testing time while still maintaining high confidence in the test results.

The EUT was placed in the chamber, at a height of about 0.8m on a turntable. Its radiated emissions frequency profile was observed, using a spectrum analyzer /receiver with the appropriate broadband antenna placed 3m away from the EUT. Radiated emissions from the EUT were maximised by rotating the turntable manually, changing the antenna polarisation and manipulating the EUT cables while observing the frequency profile on the spectrum analyzer / receiver. Frequency points at which maximum emissions occurred, clock frequencies and operating frequencies were then noted for the formal radiated emissions test at the Open Area Test Site (OATS).

### Test Set-up

1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m X 1.0m X 0.8m high, non-metallic table.
2. The filtered power supply for the EUT and supporting equipment were tapped from the appropriate power sockets located on the turntable.
3. The relevant broadband antenna was set at the required test distance away from the EUT and supporting equipment boundary.



---

## **Test Method**

The following procedure was performed to determine the maximum emission axis of EUT:

1. With the receiving antenna is H polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
2. With the receiving antenna is V polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
3. Compare the results derived from above two steps. So, the axis of maximum emission from EUT was determined and the configuration was used to perform the final measurement.

### **Final Radiated Emission Measurement**

1. Setup the configuration according to figure 1. Turn on EUT and make sure that it is in normal function.
2. For emission frequencies measured below 1 GHz, a pre-scan is performed in a shielded chamber to determine the accurate frequencies of higher emissions will be checked on a open test site. As the same purpose, for emission frequencies measured above 1 GHz, a pre-scan also be performed with a 1 meter measuring distance before final test.
3. For emission frequencies measured below and above 1 GHz, set the spectrum analyzer on a 100 kHz and 1 MHz resolution bandwidth respectively for each frequency measured in step 2.
4. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from 0

## Annex B EUT AND TEST SETUP PHOTOGRAPHS

Please see the attachment

## Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

### EUT TEST CONDITIONS


#### Annex C. i. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.


| Equipment Description<br>(Including Brand Name) | Model & Serial Number | Cable Description<br>(List Length, Type & Purpose) |
|-------------------------------------------------|-----------------------|----------------------------------------------------|
| N/A                                             | N/A                   | N/A                                                |

Remarks: The device does not have any supporting equipment, but it is controlled by itself when performing the compliance evaluations.

## Block Configuration Diagram for Radiated Emission



## Block Configuration Diagram for Conducted Emission



## **Annex C.ii. EUT OPERATING CONDITIONS**

The following is the description of how the EUT is exercised during testing.

| Test              | Description Of Operation                                       |
|-------------------|----------------------------------------------------------------|
| Emissions Testing | The EUT was controlled by itself Using manufacturer's program. |
| Others Testing    | TX mode is normal mode with full power.                        |

## **Annex D USER MANUAL, BLOCK & CIRCUIT DIAGRAM**

**Please see attachment**

## Annex E SIEMIC ACCREDITATION

### SIEMIC ACREDITATION DETAILS: A2LA 17025 & ISO Guide 65 : 2742.01 , 2742.2



THE AMERICAN ASSOCIATION FOR  
LABORATORY ACCREDITATION

### ACCREDITED LABORATORY

A2LA has accredited

**SIEMIC LABORATORIES**


**San Jose, CA**

for technical competence in the field of

#### Electrical Testing

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 *General Requirements for the Competence of Testing and Calibration Laboratories*. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated 18 June 2005).

Presented this 11th day of July 2008.



President  
For the Accreditation Council  
Certificate Number 2742.01  
Valid to September 30, 2010



For the tests or types of tests to which this accreditation applies,  
please refer to the laboratory's Electrical Scope of Accreditation.



THE AMERICAN ASSOCIATION FOR  
LABORATORY ACCREDITATION

### ACCREDITED PRODUCT CERTIFICATION BODY

A2LA has accredited

**SIEMIC INC.**


**San Jose, CA**

for technical competence as a

#### Product Certification Body

This product certification body is accredited in accordance with the recognized International Standard ISO/IEC Guide 65:1996 *General requirements for bodies operating product certification systems*. This accreditation demonstrates technical competence for a defined scope and the operation of a quality management system for a Telecommunications Certification Body (TCB) meeting FCC (U.S.), IDA (Singapore) and IC (Canada) requirements.

Presented this 9<sup>th</sup> day of January 2009.



President  
For the Accreditation Council  
Certificate Number: 2742.02  
Valid to: September 30, 2010



For the product certification schemes to which this accreditation applies,  
please refer to the certification body's Scope of Accreditation.

SCOPE OF ACCREDITATION TO ISO/IEC GUIDE 65:1996

SIEMIC INC.  
2206 Ringwood Ave.  
San Jose, CA 95131  
Mr. Snell Leong (Authorized Representative) Phone: 408 526 1188  
[www.siemic.com](http://www.siemic.com)

**PRODUCT CERTIFICATION CONFORMITY ASSESSMENT BODY (CAB)**

Valid to: September 30, 2010

Certificate Number: 2742.02

In recognition of the successful completion of the A2LA Certification Body Accreditation Program evaluation, including the US Federal Communications Commission (FCC), Industry Canada (IC) and Singapore (IDA) requirements for the indicated types of product certifications, accreditation is granted to this organization to perform the following product certification schemes:

Economy

Scope

**Federal Communication Commission - (FCC)**

|                                    |                |
|------------------------------------|----------------|
| Unlicensed Radio Frequency Devices | A1, A2, A3, A4 |
| Licensed Radio Frequency Devices   | B1, B2, B3, B4 |
| Telephone Terminal Equipment       | C              |

*\*Please refer to FCC TCB Program Roles and Responsibilities, v04, released February 14, 2008 detailing scopes, roles and responsibilities. <http://www.fcc.gov/oet/ea/FCC-Overview-TCB-Program.pdf>*

**Industry Canada - (IC)**

|       |                                                                                          |
|-------|------------------------------------------------------------------------------------------|
| Radio | All Radio Standards Specifications (RSS) in Category I<br>Equipment Standards List Radio |
|-------|------------------------------------------------------------------------------------------|

*\*Please refer to Industry Canada (IC) website at: [http://www.ic.gc.ca/epic/site/smt-gst.nsf/en/h\\_sf01342e.html](http://www.ic.gc.ca/epic/site/smt-gst.nsf/en/h_sf01342e.html)*

**IDA - Singapore**

|                               |                                                                                                                             |
|-------------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Line Terminal Equipment       | All Technical Specifications for Line Terminal<br>Equipment – Table 1 of IDA MRA Recognition<br>Scheme: 2008, Annex 2       |
| Radio-Communication Equipment | All Technical Specifications for Radio-Communication<br>Equipment – Table 2 of IDA MRA Recognition<br>Scheme: 2008, Annex 2 |

*\*Please refer to Info-Communication Development Authority (IDA) Singapore website at:  
[http://www.ida.gov.sg/doc/Policies%20and%20Regulation/Policies\\_and\\_Regulation\\_Level2/20060609145118/MRARecScheme.pdf](http://www.ida.gov.sg/doc/Policies%20and%20Regulation/Policies_and_Regulation_Level2/20060609145118/MRARecScheme.pdf)*



**SIEMIC, Inc.**  
Accessing global markets

Title: RF Test Report Exalt Communications, Inc., model : EX-5i  
To: FCC 15.247 2009, RSS 210 Issue 7: 2007

Serial# SL09061401-EXT-004  
Issue Date 27 July 2009  
Page 128 of 140  
www.sieminc.com

**SIEMIC ACREDITATION DETAILS: FCC Test Site Registration No. 783147**

## **FEDERAL COMMUNICATIONS COMMISSION**

**Laboratory Division  
7435 Oakland Mills Road  
Columbia, MD 21046**

December 20, 2007

Registration Number: 783147

SIEMIC Laboratories  
2206 Ringwood Avenue,  
San Jose, CA 95131

Attention: Leslie Bai

Re: Measurement facility located at San Jose  
3 & 10 meter site  
Date of Renewal: December 20, 2007

Dear Sir or Madam:

Your request for renewal of the registration of the subject measurement facility has been received. The information submitted has been placed in your file and the registration has been renewed. The name of your organization will remain on the list of facilities whose measurement data will be accepted in conjunction with applications for Certification under Parts 15 or 18 of the Commission's Rules. Please note that the file must be updated for any changes made to the facility and the registration must be renewed at least every three years.

Measurement facilities that have indicated that they are available to the public to perform measurement services on a fee basis may be found on the FCC website [www.fcc.gov](http://www.fcc.gov) under E-Filing, OET Equipment Authorization Electronic Filing, Test Firms.

Sincerely,

Phyllis Parrish  
Industry Analyst

**SIEMIC ACREDITATION DETAILS: Industry of Canada CAB ID : US0160**



**UNITED STATES DEPARTMENT OF COMMERCE**  
**National Institute of Standards and Technology**  
Gaithersburg, Maryland 20899

March 4, 2009

Mr. Leslie Bai  
SIEMIC, Inc.  
2206 Ringwood Avenue  
San Jose, CA 95131

Dear Mr. Bai:


NIST is pleased to inform you that your laboratory has been recognized by Industry Canada (IC), under the Asia Pacific Economic Cooperation for Telecommunications Equipment Mutual Recognition Arrangement (APEC Tel MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I** Procedures, of the APEC Tel MRA. The pertinent information about your laboratory's designation is as follows:

CAB Name: SIEMIC, Inc.  
Physical Location: 2206 Ringwood Avenue, San Jose, CA 95131 USA  
Identification No.: US0160  
Recognized Scope: CS-03 Part I, II, V, VI, VII and VIII

You may submit test data to IC to verify that the equipment to be imported into Canada satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements.

Recognized CABs are listed on the NIST website at <http://ts.nist.gov/mra>. Please contact Ms. Ramona Saar at (301) 975-5521 or [ramona.saar@nist.gov](mailto:ramona.saar@nist.gov) if you have any questions.

Sincerely,



David F. Alderman  
Group Leader, Standards Coordination and Conformity Group  
Standards Services Division

Enclosure

cc: CAB Program Manager

## SIEMIC ACREDITATION DETAILS: Industry of Canada Test Site Registration No. 4842-1



May 23rd, 2008

OUR FILE: 46405-4842

Submission No: 126429

Siemic Inc.  
2206 Ringwood Ave.  
San Jose CA 95131  
USA

**Attention:** Leslie Bai

Dear Sir/Madame:

The Bureau has received your application for the registration / renewal of a 3/10m OATS. Be advised that the information received was satisfactory to Industry Canada. The following number(s) is now associated to the site(s) for which registration / renewal was sought (**4842A-1**). Please reference the appropriate site number in the body of test reports containing measurements performed on the site. In addition, please be informed that the Bureau is now utilizing a **new site numbering scheme** in order to simplify the electronic filing process. Our goal is to reduce the number of secondary codes associated to one particular company. The following changes have been made to your record.

- Your primary code is: **4842**
- The company number associated to the site(s) located at the above address is: **4842A**
- The table below is a summary of the changes made to the unique site registration number(s):

| New Site Number | Obsolete Site Number | Description of Site | Expiry Date (YYYY-MM-DD) |
|-----------------|----------------------|---------------------|--------------------------|
| 4842A-1         | 4842-1               | 3m Chamber          | 2010-05-23               |

Furthermore, to obtain or renew a unique site number, the applicant shall demonstrate that the site has been accredited to ANSI C63.4-2003 or later. A scope of accreditation indicating the accreditation by a recognized accreditation body to ANSI C63.4-2003 shall be accepted. Please indicate in a letter the previous assigned site number if applicable and the type of site (example: 3 meter OATS or 3 meter chamber). If the test facility is not accredited to ANSI C63.4-2003 or later, the test facility shall submit test data demonstrating full compliance with the ANSI standard. The Bureau will evaluate the filing to determine if recognition shall be granted.

The frequency for re-validation of the test site and the information that is required to be filed or retained by the testing party shall comply with the requirements established by the accrediting organization. However, in all cases, test site re-validation shall occur on an interval not to exceed two years. There is no fee or form associated with an OATS filing. OATS submissions are encouraged to be submitted electronically to the Bureau using the following URL;  
[http://strategis.ic.gc.ca/epic/internet/inceb-bhst.nsf/en/h\\_t00052e.html](http://strategis.ic.gc.ca/epic/internet/inceb-bhst.nsf/en/h_t00052e.html).

If you have any questions, you may contact the Bureau by e-mail at [certification\\_bureau@ic.gc.ca](mailto:certification_bureau@ic.gc.ca)  
Please reference our file and submission number above for all correspondence.

Yours sincerely,



S. Proulx  
Test & Measurement Specialist  
Certification and Engineering Bureau  
3701 Carling Ave., Building 94  
Ottawa, Ontario K2H 8S2



## **FEDERAL COMMUNICATIONS COMMISSION**

**Laboratory Division  
7435 Oakland Mills Road  
Columbia, MD 21046**

**August 28, 2008**

**Siemic Laboratories  
2206 Ringwood Ave.,  
San Jose, CA 95131**

**Attention: Leslie Bai**

**Re: Accreditation of Siemic Laboratories  
Designation Number: US1109  
Test Firm Registration #: 540430**

**Dear Sir or Madam:**

We have been notified by American Association for Laboratory Accreditation that Siemic Laboratories has been accredited as a Conformity Assessment Body (CAB).

At this time Siemic Laboratories is hereby designated to perform compliance testing on equipment subject to Declaration Of Conformity (DOC) and Certification under Parts 15 and 18 of the Commission's Rules.

This designation will expire upon expiration of the accreditation or notification of withdrawal of designation.

Sincerely,

**George Tannahill  
Electronics Engineer**

**SIEMIC ACREDITATION DETAILS: Australia CAB ID : US0160**



**UNITED STATES DEPARTMENT OF COMMERCE**  
**National Institute of Standards and Technology**  
Gaithersburg, Maryland 20899

November 20, 2008

Mr. Leslie Bai  
SIEMIC, Inc.  
2206 Ringwood Avenue  
San Jose, CA 95131


Dear Mr. Bai:

NIST is pleased to inform you that your laboratory has been recognized by the Australian Communications and Media Authority (ACMA) under the Asia Pacific Economic Cooperation for Telecommunications Equipment Mutual Recognition Arrangement (APEC Tel MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I** Procedures, of the APEC Tel MRA. The pertinent information about your laboratory's designation is as follows:

CAB Name: Siemic, Inc.  
Physical Location: 2206 Ringwood Avenue, San Jose, CA 95131  
Identification No.: US0160  
Recognized Scope: EMC: AS/NZS 4251.1 (until 5/31/2009), AS/NZS 4251.2 (until 5/31/2009), AS/NZS CISPR 11, AS/NZS CISPR 14.1, AS/NZS CISPR 22, AS/NZS 61000.6.3, AS/NZS 61000.6.4  
Radiocommunications: AS/NZS 4281, AS/NZS 4268, AS/NZS 4280.1, AS/NZS 4280.2, AS/NZS 4295, AS/NZS 4582, AS/NZS 4583, AS/NZS 4769.1, AS/NZS 4769.2, AS/NZS 4770, AS/NZS 4771  
Telecommunications: AS/ACIF S002:05, AS/ACIF S003:06, AS/ACIF S004:06, AS/ACIF S006:01, AS/ACIF S016:01, AS/ACIF S031:01, AS/ACIF S038:01, AS/ACIF S040:01, AS/ACIF S041:05, AS/ACIF S043.2:06, AS/NZS 60950.1

You may submit test data to ACMA to verify that the equipment to be imported into Australia satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements. Recognized CABs are listed on the NIST website at <http://ts.nist.gov/mra>. Please contact Ms. Ramona Saar, at (301) 975-5521 or [ramona.saar@nist.gov](mailto:ramona.saar@nist.gov) if you have questions.

Sincerely,



David F. Alderman  
Group Leader, Standards Coordination and Conformity Group  
Standards Services Division

Enclosure

cc: Snell Leong, Siemic, Inc.; Ramona Saar, NIST

**NIST**

**SIEMIC ACREDITATION DETAILS: Korea CAB ID: US0160**



**UNITED STATES DEPARTMENT OF COMMERCE**  
**National Institute of Standards and Technology**  
Gaithersburg, Maryland 20899.

October 1, 2008

Mr. Leslie Bai  
SIEMIC, Inc.  
2206 Ringwood Avenue  
San Jose, CA 95131

Dear Mr. Bai:

NIST is pleased to inform you that your laboratory has been recognized by the Radio Research Agency (RRA) Korea Communications Commission (KCC) under the Asia Pacific Economic Cooperation for Telecommunications Equipment Mutual Recognition Arrangement (APEC Tel MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I** Procedures, of the APEC Tel MRA. The pertinent information about your laboratory's designation is as follows:

CAB Name: SIEMIC, Inc.  
Physical Location: 2206 Ringwood Avenue, San Jose, CA 95131  
Identification No.: US0160  
Recognized Scope: **EMI:** KCC Notice 2008-39, RRL Notice 2008-3: CA Procedures for EMI  
KN22: Test Method for EMI  
**EMS:** KCC Notice 2008-38, RRL Notice 2008-4: CA Procedures for EMS  
KN24, KN-61000-4-2, -4-3, -4-4, -4-5, -4-6, -4-8, -4-11: Test Method for EMS  
**Wireless:** RRL Notice 2008-26, RRL Notice 2008-2, RRL Notice 2008-10,  
RRL Notice 2007-49, RRL Notice 2007-20, RRL Notice 2007-21,  
RRL Notice 2007-80, RRL Notice 2004-68  
**Wired:** President Notice 20664, RRL Notice 2007-30,  
RRL Notice 2008-7 with attachments 1, 3, 5, 6  
President Notice 20664, RRL Notice 2008-7 with attachment 4

You may submit test data to RRA/KCC to verify that the equipment to be imported into Korea satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements.

Recognized CABs are listed on the NIST website at <http://ts.nist.gov/mra>. If you have any questions please contact Ramona Saar at (301) 975-5521 or [ramona.saar@nist.gov](mailto:ramona.saar@nist.gov).

Sincerely,

David F. Alderman  
Group Leader, Standards Coordination and Conformity Group  
Standards Services Division

Enclosure

cc: Ramona Saar

**NIST**

**SIEMIC ACREDITATION DETAILS: Taiwan BSMI Accreditation No. SL2-IN-E-1130R**



UNITED STATES DEPARTMENT OF COMMERCE  
National Institute of Standards and Technology  
Gaithersburg, Maryland 20899

May 3, 2006

Mr. Leslie Bai  
SIEMIC Laboratories  
2206 Ringwood Avenue  
San Jose, CA 95131

Dear Mr. Bai:

I am pleased to inform you that your laboratory has been recognized by the Chinese Taipei's Bureau of Standards, Metrology, and Inspection (BSMI) under the Asia Pacific Economic Cooperation (APEC) Mutual Recognition Arrangement (MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I** Procedures, of the APEC Tel MRA. You may submit test data to BSMI to verify that the equipment to be imported into Chinese Taipei satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements. The pertinent designation information is as follows:

- BSMI number: **SL2-IN-E-1130R** (Must be applied to the test reports)
- U.S. Identification No: **US0160**
- Scope of Designation: **CNS 13438**
- Authorized signatory: **Mr. Leslie Bai**

The names of all recognized CABs will be posted on the NIST website at <http://ts.nist.gov/mra>. If you have any questions, please contact Mr. Dhillon at 301-975-5521. We appreciate your continued interest in our international conformity assessment activities.

Sincerely,

David F. Alderman  
Group Leader, Standards Coordination and Conformity Group

cc: Jogindar Dhillon

**NIST**

**SIEMIC ACREDITATION DETAILS: Taiwan NCC CAB ID: US0160**



UNITED STATES DEPARTMENT OF COMMERCE  
National Institute of Standards and Technology  
Gaithersburg, Maryland 20899

November 25, 2008

Mr. Leslie Bai  
SIEMIC, Inc.  
2206 Ringwood Avenue  
San Jose, CA 95131

Dear Mr. Bai:


NIST is pleased to inform you that your laboratory has been recognized by the National Communications Commission (NCC) for the requested scope expansion under the Asia Pacific Economic Cooperation for Telecommunications Equipment Mutual Recognition Arrangement (APEC Tel MRA). Your laboratory is designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I** Procedures, of the APEC Tel MRA. The pertinent information about your laboratory's designation is as follows:

CAB Name: SIEMIC, Inc.  
Physical Location: 2206 Ringwood Avenue, San Jose, CA 95131  
Identification No.: US0160  
Current Scope: LP0002  
Additional Scope: PSTN01, ADSL01, ID0002, IS6100 and CNS 14336

You may submit test data to NCC to verify that the equipment to be imported into China satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements.

Recognized CABs are listed on the NIST website at <http://ts.nist.gov/mra>. If you have any questions please contact Ramona Saar at (301) 975-5521 or [ramona.saar@nist.gov](mailto:ramona.saar@nist.gov).

Sincerely,



David F. Alderman  
Group Leader, Standards Coordination and Conformity Group  
Standards Services Division

Enclosure

cc: Ramona Saar

**NIST**



**SIEMIC ACREDITATION DETAILS: Mexico NOM Recognition**



**Laboratorio Valentin V. Rivero**

México D.F. a 18 de octubre de 2009.

**LESLIE BAI  
DIRECTOR OF CERTIFICATION  
SIEMIC LABORATORIES, INC.  
ACCESSING GLOBAL MARKETS  
P R E S E N T E**

En contestación a su escrito de fecha 5 de septiembre del año en curso, le comento que estamos muy interesados en su intención de firmar un Acuerdo de Reconocimiento Mutuo, para lo cual adjunto a este escrito encontrara el Acuerdo en idioma inglés y español preferido de los cuales le pido sea revisado y en su caso corregido, para que si este de acuerdo poder firmarlo para mandarlo con las autoridades Mexicanas para su visto bueno y así poder ejercer dicho acuerdo.

Aprovecho este escrito para mencionarle que nuestro intermediario gestor será la empresa Isabel de México, S. A. de C. V., empresa que ha colaborado durante mucho tiempo con nosotros en lo relacionado a la evaluación de la conformidad y que cuenta con amplia experiencia en la gestión de la certificación de cumplimiento con Normas Oficiales Mexicanas de producto en México.

Me despido de usted enviándole un cordial saludo y esperando sus comentarios al Acuerdo que nos ocupa.

Atentamente:

  
**Ing. Faustino Sánchez González  
Gerente Técnico del Laboratorio de  
CANIETI**

**SIEMIC ACREDITATION DETAILS: Hong Kong OFTA CAB ID : US0160**



**UNITED STATES DEPARTMENT OF COMMERCE**  
**National Institute of Standards and Technology**  
Gaithersburg, Maryland 20899-

December 8, 2008

Mr. Leslie Bai  
SIEMIC, Inc.  
2206 Ringwood Avenue  
San Jose, CA 95131

Dear Mr. Bai:

NIST is pleased to inform you that your laboratory has been recognized by the Office of the Telecommunications Authority (OFTA) under the Asia Pacific Economic Cooperation for Telecommunications Equipment Mutual Recognition Arrangement (APEC Tel MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I** Procedures, of the APEC Tel MRA. The pertinent information about your laboratory's designation is as follows:

CAB Name: SIEMIC, Inc.  
Physical Location: 2206 Ringwood Avenue, San Jose, California 95131 USA  
Identification No.: US0160  
Recognized Scope: **Radio:** HKTA 1002, 1007, 1008, 1010, 1015, 1016, 1020, 1022, 1026, 1027, 1029, 1030, 1031, 1032, 1033, 1034, 1035, 1036, 1037, 1039, 1041, 1042, 1043, 1044, 1046, 1047, 1048, 1049, 1051  
**Telecom:** HKTA 2011, 2012, 2013, 2014, 2017, 2018, 2022, 2024, 2026, 2027, 2028, 2029, 2030, 2031, 2032, 2033

You may submit test data to OFTA to verify that the equipment to be imported into Hong Kong satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements.

Recognized CABs are listed on the NIST website at <http://ts.nist.gov/mra>. If you have any questions please contact Ramona Saar at (301) 975-5521 or [ramona.saar@nist.gov](mailto:ramona.saar@nist.gov).

Sincerely,



David F. Alderman  
Group Leader, Standards Coordination and Conformity Group  
Standards Services Division

Enclosure

cc: Ramona Saar

**NIST**



VCCI Council

# CERTIFICATE

Company: SIEMIC Inc.

<Member No. 3081 >

Facility: SIEMIC Inc.

(Radiation 3 meter site)

Location of Facility:

2206 Ringwood Avenue, San Jose, CA 95131 USA

*This is to certify that the following measuring facility  
has been registered in accordance with the Rules  
for Voluntary Control Measures*

Registration No.: R-3083

Date of Registration: June 12 , 2009

This Certificate is valid until September 30 , 2010

VCCI Council





VCCI Council

# CERTIFICATE

Company: SIEMIC Inc.

<Member No. 3081 >

Facility: SIEMIC Inc.

(Main Ports Conducted Interference Measurement)

Location of Facility:

2206 Ringwood Avenue, San Jose, CA 95131 USA

*This is to certify that the following measuring facility  
has been registered in accordance with the Rules  
for Voluntary Control Measures*

Registration No.: C-3421

Date of Registration: June 12 , 2009

This Certificate is valid until September 30 , 2010

VCCI Council





VCCI Council

# CERTIFICATE

Company: SIEMIC Inc.

<Member No. 3081 >

Facility: SIEMIC Inc.

(Telecommunication Ports Conducted Interference Measurement)

Location of Facility:

2206 Ringwood Avenue, San Jose, CA 95131 USA

*This is to certify that the following measuring facility  
has been registered in accordance with the Rules  
for Voluntary Control Measures*

Registration No.: T-1597

Date of Registration: June 12 , 2009

This Certificate is valid until September 30 , 2010

VCCI Council

