




FCC RADIO EXPOSURE TEST REPORT

FCC ID : TV7CB5A60
Equipment : CubeG-5ac60ad
Brand Name : MikroTik
Model Name : CubeG-5ac60ad-US
Applicant : Mikrotikls SIA
Brivibas gatve 214i, Riga, LV-1039 Latvia
Manufacturer : MIKROTIKLS SIA
Brivibas gatve 214i, Riga, LV-1039 Latvia
Standard : 47 CFR Part 2.1091

The product was received on Dec. 03, 2019, and testing was started from Jan. 06, 2020 and completed on Mar. 03, 2020. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR Part 2.1091, and shown compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.


Approved by: Sam Chen

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 EUT General Information	5
2 Maximum Permissible Exposure	6
2.1 Limit of Maximum Permissible Exposure	6
2.2 MPE Calculation Method.....	6
2.3 Calculated Result and Limit.....	7

Photographs of EUT v01



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
2	-	Exposure evaluation	PASS	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Sam Chen

Report Producer: Viola Huang



1 General Description

1.1 EUT General Information

RF General Information			
Evaluation Mode	Frequency Range	Operating Frequency	Modulation Type
5GHz WLAN	5150-5250 MHz 5725-5850 MHz	5180-5240 MHz 5745-5825 MHz	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)
60G	57-71GHz	58.32 GHz 60.48 GHz 62.64 GHz	$\pi/2$ -BPSK, $\pi/2$ -QPSK, $\pi/2$ -16QAM

Testing LocationTesting Location		
☐	HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-327-0973
☒	JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

2 Maximum Permissible Exposure

2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Method

The MPE was calculated at 21 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$



2.3 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

For WLAN 5GHz

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)
5.2G;D1D	11.00	14.25	25.25	0.50	25.75	0.37584	21	0.06782	1.00000
5.8G;D1D	11.00	14.26	25.26	0.50	25.76	0.37670	21	0.06797	1.00000

For 60GHz

Worst-case Integrated Band Power of Unwanted Emission (30MHz ~ 40GHz)						
Start (MHz)	Stop (MHz)	Limit (dBuV/m at 3m)	Limit (mW EIRP)	RBW (MHz)	Num Intervals	Integrated Band Power (mW)
30	88	40	3.01995E-06	0.1	580	0.002
88	216	43.5	6.76083E-06	0.1	1280	0.009
216	960	46	1.20226E-05	0.1	7440	0.089
960	1000	54	7.58578E-05	0.1	400	0.030
1000	40000	54	7.58578E-05	1	39000	2.958
Total						3.089

Total Integrated Band Power of All Emission (30MHz ~ 200GHz)				
Test Frequency (GHz)	30MHz ~ 40GHz Integrated Band Power (mW)	40 ~ 200GHz EIRP (dBm)	40 ~ 200GHz EIRP (mW)	30MHz ~200GHz Total Integrated Band Power (mW)
58.32	3.089	36.49	4459.36	4462.449
60.48		36.43	4394.01	4397.099
62.64		34.61	2892.95	2896.039

Maximum Permissible Exposure of Fundamental Emissions							
Separation Distance (cm)	21						
Maximum EIPR Power of Test Frequency (GHz)	Ant. Gain (dBi)	Average EIRP Power (dBm)	Tolerance (dB)	Tune-up Average EIRP Power (dBm)	Tune-up Average EIRP Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)
58.32	30	36.49	0.50	36.99	5000.35	0.90228	1.00

**Simultaneous Transmission Analysis Mode: WLAN 5GHz + 60GHz**

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Ratio (S/Limit)
5G	11.00	14.26	25.26	0.50	25.76	0.37670	21	0.06797	1	0.06797
60G	30.00	6.49	36.49	0.50	36.99	5.00695	21	0.90347	1	0.90347
									Sum Ratio	0.97144
									Ratio Limit	1

Note: The above antenna gain was declared by manufacturer.

————THE END————