

RF Exposure Report

Report No.: SA161004C24H

FCC ID: TVE-140701

Test Model: FAP-221E, FAP-223E

Series Model: FortiAP 221Exxxxx, FAP-221Exxxxx, FORTIAP-221Exxxxx, FortiAP 223Exxxxx, FAP-223Exxxxx, FORTIAP-223Exxxxx (where "x" can be used as "A-Z", or "0-9", or "-", or blank for marketing purposes only)

Received Date: Jun. 04, 2018

Test Date: Oct. 08, 2016 ~ Jan. 19, 2017 (For 5180 ~ 5240MHz band 802.11ac (VHT80) mode and 5745 ~ 5825MHz band)
Sep. 27 ~ Oct. 17, 2017 (For 5260 ~ 5320MHz, 5500 ~ 5720MHz band)
Jun. 06 ~ Jun. 08, 2018 (For 5180 ~ 5240MHz band 802.11a, 802.11n (HT20) and 802.11n (HT40) mode)

Issued Date: Jun. 12, 2018

Applicant: Fortinet Inc.

Address: 899 Kifer Road Sunnyvale, CA 94086 USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan (R.O.C.)

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, TAIWAN (R.O.C.)

FCC Registration / Designation Number: 788550 / TW0003



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
3 Calculation Result of Maximum Conducted Power	6

Release Control Record

Issue No.	Description	Date Issued
SA161004C24H	Original release	Jun. 12, 2018

1 Certificate of Conformity

Product: Secured Wireless Access Point

Brand: Fortinet Inc.

Test Model: FAP-221E, FAP-223E

Series Model: FortiAP 221Exxxxx, FAP-221Exxxxx, FORTIAP-221Exxxxx, FortiAP 223Exxxxx, FAP-223Exxxxx, FORTIAP-223Exxxxx (where "x" can be used as "A-Z", or "0-9", or "-", or blank for marketing purposes only)

Sample Status: Engineering sample

Applicant: Fortinet Inc.

Test Date: Oct. 08, 2016 ~ Jan. 19, 2017 (For 5180 ~ 5240MHz band 802.11ac (VHT80) mode and 5745 ~ 5825MHz band)

Sep. 27 ~ Oct. 17, 2017 (For 5260 ~ 5320MHz, 5500 ~ 5720MHz band)

Jun. 06 ~ Jun. 08, 2018 (For 5180 ~ 5240MHz band 802.11a, 802.11n (HT20) and 802.11n (HT40) mode)

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1-1992

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : Celine Chou , Date: Jun. 12, 2018
Celine Chou / Specialist

Approved by : Bruce Chen , Date: Jun. 12, 2018
Bruce Chen / Project Engineer

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

2.2 MPE Calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

3 Calculation Result of Maximum Conducted Power

Frequency Band (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
CDD Mode					
2412-2462	24.82	7.59	20	0.347	1
5180-5240	17.18	8.61	20	0.075	1
5260-5320	23.80	8.61	20	0.347	1
5500-5720	23.72	8.61	20	0.340	1
5745-5825	25.79	8.61	20	0.548	1
Beamforming Mode					
2412-2462	21.46	7.59	20	0.160	1
5180-5240	14.17	8.61	20	0.038	1
5260-5320	20.79	8.61	20	0.173	1
5500-5720	20.71	8.61	20	0.170	1
5745-5825	22.78	8.61	20	0.274	1

Note:

2.4GHz: Directional gain = 4.58dBi + 10log(2) = 7.59dBi

5GHz: Directional gain = 5.60dBi + 10log(2) = 8.61dBi

Conclusion:

Both of the WLAN 2.4G & WLAN 5G can transmit simultaneously, the formula of calculated the MPE is:

CPD1 / LPD1 + CPD2 / LPD2 +etc. < 1

CPD = Calculation power density

LPD = Limit of power density

2.4G + 5G = 0.347 + 0.548 = 0.895

Therefore the maximum calculations of above situations are less than the "1" limit.

---END---