

RF Exposure Report

Report No.: MFBDIS-WTW-P23110748 R1

FCC ID: TVE-240607

Test Model: FBS-10F-WiFi

Series Model: FortiBranchSASE-10F-WiFixxxxxxxxxxx, FBS-10F-WiFixxxxxxxxxxx,
FORTIBRANCHSASE-10F-WiFixxxxxxxxxxx (where "x" can be used as "A-
Z", or "0-9", or "-", or blank for software changes or marketing purposes
only)

Received Date: 2024/2/29

Test Date: 2024/2/29 ~ 2024/4/6

Issued Date: 2024/8/20

Applicant: Fortinet, Inc.

Address: 909 Kifer Road Sunnyvale, Ca. 94086

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, Taiwan

FCC Registration / 788550 / TW0003
Designation Number:



This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE)	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
3 Calculation Result of Maximum Conducted Power	6

Release Control Record

Issue No.	Description	Date Issued
MFBDYS-WTW-P23110748	Original Release	2024/7/11
MFBDYS-WTW-P23110748 R1	1. Revise applicant' address, brand and series model name 2. Remove WLAN 5G Band 2, 3	2024/8/20

1 Certificate of Conformity

Product: Secured Wireless Access Point

Brand: FORTINET

Test Model: FBS-10F-WiFi

Series Model: FortiBranchSASE-10F-WiFixxxxxxxxxxx, FBS-10F-WiFixxxxxxxxxxx,
FORTIBRANCHSASE-10F-WiFixxxxxxxxxxx (where "x" can be used as "A-Z", or
"0-9", or "-", or blank for software changes or marketing purposes only)

Sample Status: Engineering Sample

Applicant: Fortinet, Inc.

Test Date: 2024/2/29 ~ 2024/4/6

FCC Rule Part: FCC Part 2 (Section 2.1091)

Standards: KDB 447498 D01 General RF Exposure Guidance v06

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : Lena Wang, **Date:** 2024/8/20
Lena Wang / Specialist

Approved by : Jeremy Lin, **Date:** 2024/8/20
Jeremy Lin / Project Engineer

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

2.2 MPE Calculation Formula

$$P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 21cm away from the body of the user. So, this device is classified as **Mobile Device**.

3 Calculation Result of Maximum Conducted Power

Frequency Band (MHz)	Max Average Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WLAN					
CDD Mode					
2412-2462	26.01	7.38	21	0.394	1
5180-5240	25.55	8.36	21	0.444	1
5745-5825	24.41	8.36	21	0.341	1
Beamforming Mode					
2412-2462	25.04	7.38	21	0.315	1
5180-5240	25.55	8.36	21	0.444	1
5745-5825	24.41	8.36	21	0.341	1
BT LE					
2402-2480	5.43	3.6	21	0.001	1

Note:

1. Directional gain:

2.4GHz Band: Directional gain = $10 \log[(10^{\text{Chain0/20}} + 10^{\text{Chain1/20}})^2 / 2] = 7.38\text{dBi}$

5GHz: Directional gain = $10 \log[(10^{\text{Chain0/20}} + 10^{\text{Chain1/20}})^2 / 2] = 8.36\text{dBi}$

2. Detail antenna specification please refer to antenna datasheet and/or antenna measurement report.

3. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

Conclusion:

The formula of calculated the MPE is:

$\text{CPD1} / \text{LPD1} + \text{CPD2} / \text{LPD2} + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

The simultaneous operation mode was determined by client.

No	Mode
1	WLAN 2.4G+ WLAN 5GHz =0.394/1+0.444/1=0.838
2	WLAN 5GHz + BLE =0.444/1+0.001/1=0.445

*WLAN 2.4G and BT technologies cannot transmit at same time.

Therefore the maximum calculations of above situations are less than the "1" limit.

---END---