FCC Test Report

Report No.: RF160613C30-1

FCC ID: TVE-281BB022

Test Model: FAP-U421EV

Series Model: FortiAP-U421EVxxxxxx, FAP-U421EVxxxxxx, FORTIAP-U421EVxxxxxx, FortiAP-U423EVxxxxxx, FAP-U423EVxxxxxx, FORTIAP-U423EVxxxxxx (where “x” can be used as “A-Z” or “0-9” or “-“ or blank for software changes or marketing purposes only) (refer to item 3.1 for more details)

Received Date: Jun. 13, 2016

Test Date: Jun. 28 ~ Jul. 05, 2016

Issued Date: Jul. 05, 2016

Applicant: Fortinet Inc.

Address: 899 Kifer Road Sunnyvale, CA 94086 USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan, R.O.C.

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, TAIWAN (R.O.C.)

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.
The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record **4**

1 Certificate of Conformity **5**

2 Summary of Test Results **6**

2.1 Measurement Uncertainty 6
2.2 Modification Record 6

3 General Information **7**

3.1 General Description of EUT 7
3.2 Description of Test Modes 9
3.2.1 Test Mode Applicability and Tested Channel Detail 10
3.3 Description of Support Units 11
3.3.1 Configuration of System under Test 12
3.4 General Description of Applied Standards 12

4 Test Types and Results **14**

4.1 Radiated Emission and Bandedge Measurement 14
4.1.1 Limits of Radiated Emission and Bandedge Measurement 14
4.1.2 Test Instruments 15
4.1.3 Test Procedures 16
4.1.4 Deviation from Test Standard 16
4.1.5 Test Setup 17
4.1.6 EUT Operating Conditions 17
4.1.7 Test Results 18
4.2 Conducted Emission Measurement 26
4.2.1 Limits of Conducted Emission Measurement 26
4.2.2 Test Instruments 26
4.2.3 Test Procedures 27
4.2.4 Deviation from Test Standard 27
4.2.5 Test Setup 27
4.2.6 EUT Operating Conditions 27
4.2.7 Test Results 28
4.3 Number of Hopping Frequency Used 32
4.3.1 Limits of Hopping Frequency Used Measurement 32
4.3.2 Test Setup 32
4.3.3 Test Instruments 32
4.3.4 Test Procedure 32
4.3.5 Deviation fromTest Standard 32
4.3.6 Test Results 32
4.4 Dwell Time on Each Channel 34
4.4.1 Limits of Dwell Time on Each Channel Measurement 34
4.4.2 Test Setup 34
4.4.3 Test Instruments 34
4.4.4 Test Procedures 34
4.4.5 Deviation from Test Standard 34
4.4.6 Test Results 35
4.5 Channel Bandwidth 37
4.5.1 Limits of Channel Bandwidth Measurement 37
4.5.2 Test Setup 37
4.5.3 Test Instruments 37
4.5.4 Test Procedure 37
4.5.5 Deviation from Test Standard 37
4.5.6 EUT Operating Condition 37
4.5.7 Test Results 38
4.6 Hopping Channel Separation 39
4.6.1 Limits of Hopping Channel Separation Measurement 39

4.6.2 Test Setup 39
4.6.3 Test Instruments 39
4.6.4 Test Procedure 39
4.6.5 Deviation from Test Standard 39
4.6.6 Test Results 40
4.7 Maximum Output Power 41
4.7.1 Limits of Maximum Output Power Measurement 41
4.7.2 Test Setup 41
4.7.3 Test Instruments 41
4.7.4 Test Procedure 41
4.7.5 Deviation fromTest Standard 41
4.7.6 EUT Operating Condition 41
4.7.7 Test Results 42
4.8 Conducted Out of Band Emission Measurement 43
4.8.1 Limits Of Conducted Out Of Band Emission Measurement 43
4.8.2 Test Instruments 43
4.8.3 Test Procedure 43
4.8.4 Deviation from Test Standard 43
4.8.5 EUT Operating Condition 43
4.8.6 Test Results 43

5 Pictures of Test Arrangements 46

Appendix – Information on the Testing Laboratories 47

Release Control Record

Issue No.	Description	Date Issued
RF160613C30-1	Original release.	Jul. 05, 2016

1 Certificate of Conformity

Product: Secured Wireless Access Point

Brand: Fortinet Inc.

Test Model: FAP-U421EV

Series Model: FortiAP-U421EVxxxxxx, FAP-U421EVxxxxxx, FORTIAP-U421EVxxxxxx, FortiAP-U423EVxxxxxx, FAP-U423EVxxxxxx, FORTIAP-U423EVxxxxxx (where "x" can be used as "A-Z" or "0-9" or "-" or blank for software changes or marketing purposes only) (refer to item 3.1 for more details)

Sample Status: Engineering sample

Applicant: Fortinet Inc.

Test Date: Jun. 28 ~ Jul. 05, 2016

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)
ANSI C63.10:2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : _____ , **Date:** Jul. 05, 2016
Suntee Liu / Specialist

Approved by : _____ , **Date:** Jul. 05, 2016
Ken Liu / Senior Manager

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)			
FCC Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	Pass	Meet the requirement of limit. Minimum passing margin is -5.52dB at 0.52544MHz.
15.247(a)(1)(iii)	Number of Hopping Frequency Used	Pass	Meet the requirement of limit.
15.247(a)(1)(iii)	Dwell Time on Each Channel	Pass	Meet the requirement of limit.
15.247(a)(1)	1. Hopping Channel Separation 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	Pass	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power	Pass	Meet the requirement of limit.
15.205 / 15.209 / 15.247(d)	Radiated Emissions and Band Edge Measurement	Pass	Meet the requirement of limit. Minimum passing margin is -3.2dB at 37.68MHz.
15.247(d)	Antenna Port Emission	Pass	Meet the requirement of limit.
15.203	Antenna Requirement	Pass	Antenna connector is IPEX not a standard connector.

Note: If The Frequency Hopping System operating in 2400-2483.5MHz band and the output power less than 125mW. The hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of hopping channel whichever is greater.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (

3 General Information

3.1 General Description of EUT

Product	Secured Wireless Access Point
Brand	Fortinet Inc.
Test Model	FAP-U421EV
Series Model	FortiAP-U421EVxxxxxx, FAP-U421EVxxxxxx, FORTIAP-U421EVxxxxxx, FortiAP-U423EVxxxxxx, FAP-U423EVxxxxxx, FORTIAP-U423EVxxxxxx (where “x” can be used as “A-Z” or “0-9” or “-“ or blank for software changes or marketing purposes only) (refer to Note for more details)
Model Difference	Refer to Note
Sample Status	Engineering sample
Power Supply Rating	12Vdc (adapter) 54Vdc (POE)
Modulation Type	GFSK,

Note:

1. The EUT uses following antennas.

Antenna Type	Printed	Antenna Connector	IPEX
Gain (dBi)	Frequency (MHz)		
	2400~2500	5150~5850	
WLAN Internal Ant. 1	3.81	-	
WLAN Internal Ant. 2	3.98	-	
WLAN Internal Ant. 3	3.47	-	
WLAN Internal Ant. 4	3.75	-	
WLAN Internal Ant. 5	-	5.65	
WLAN Internal Ant. 6	-	5.50	
WLAN Internal Ant. 7	-	5.84	
WLAN Internal Ant. 8	-	5.84	
Gain (dBi)	Frequency (MHz)		
	2400	2450	2500
BT Internal Ant. 9	2.56	2.91	2.62





Antenna Type	Dipole	Antenna Connector	RPSMA
Gain (dBi)	Frequency (MHz)		
	2400~2500	5150~5850	
WLAN External Ant.	4.42	3	

2. All models are listed as below (where “x” can be used as “A-Z” or “0-9” or “-“ or blank for software changes or marketing purposes only). Model FAP-U421EV is the representative for final test.

Brand	Model	Difference
Fortinet Inc.	FortiAP-U421EVxxxxxx	Internal antenna
	FAP-U421EVxxxxxx	
	FORTIAP-U421EVxxxxxx	
	FortiAP-U423EVxxxxxx	External antenna
	FAP-U423EVxxxxxx	
	FORTIAP-U423EVxxxxx	

3. WLAN 2.4GHz and WLAN 5GHz and BT technologies can transmit at same time.
4. Spurious emission of the simultaneous operation (WLAN 2.4GHz and WLAN 5GHz and BT) has been evaluated and no non-compliance was found.

3.2 Description of Test Modes

79 channels are provided to this EUT:

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

3.2.1 Test Mode Applicability and Tested Channel Detail

EUT Configure Mode	Applicable to				Description
	RE≥1G	RE<1G	PLC	APCM	
A	√	√	√	√	Power from adapter
B	-	√	√	-	Power from POE

Where RE≥1G: Radiated Emission above 1GHz & Bandedge Measurement RE<1G: Radiated Emission below 1GHz
PLC: Power Line Conducted Emission APCM: Antenna Port Conducted Measurement

Note:
1. The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on Y-plane.
2. "-" means no effect.

Radiated Emission Test (Above 1GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Pakcet Type
A	0 to 78	0, 39, 78	FHSS	GFSK	DH5
A	0 to 78	0, 39, 78	FHSS	8DPSK	DH5

Radiated Emission Test (Below 1GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Pakcet Type
A, B	0 to 78	0	FHSS	GFSK	DH5

Power Line Conducted Emission Test:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Pakcet Type
A, B	0 to 78	0	FHSS	GFSK	DH5

Antenna Port Conducted Measurement:

☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Pakcet Type
A	0 to 78	0, 39, 78	FHSS	GFSK	DH5
A	0 to 78	0, 39, 78	FHSS	8DPSK	DH5

Test Condition:

Applicable to	Environmental Conditions	Input Power	Tested by
RE≥1G	19 deg. C, 70% RH	120Vac, 60Hz	Jones Chang
RE<1G	18 deg. C, 70% RH	120Vac, 60Hz	Nick Hsu
PLC	18 deg. C, 70% RH	120Vac, 60Hz	Nick Hsu
APCM	25 deg. C, 60% RH	120Vac, 60Hz	Leo Tsai

3.3 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	Notebook	DELL	E5410	1HC2XM1	FCC DoC Approved	-
B.	Load	NA	NA	NA	NA	-
C.	Flash	Transcend	8GB	NA	NA	-
D.	Adapter	Asian Power Devices Inc.	WA-36A12R	NA	NA	Option of EUT I/P: 100-240Vac, 50-60Hz, 0.9A Max. O/P: 12Vdc, 3A 1.8m DC cable with 1 core
E.	POE	EnGenius	EPA5006GAT	NA	NA	Option of EUT I/P: 100-240Vac, 50-60Hz, 0.8A O/P: 54Vdc, 0.6A 0.5m power cable w/o core

Note:

1. All power cords of the above support units are non-shielded (1.8m).
2. Item A acted as a communication partner to transfer data.

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	RJ45	1	5	N	0	-
2.	RJ45	2	1	N	0	-
3.	RJ45	1	1.8	N	0	-

3.3.1 Configuration of System under Test

Mode A



Mode B



3.4 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247)
FCC Public Notice DA 00-705
ANSI C63.10:2013

All test items have been performed and recorded as per the above standards.

Note: The EUT has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.1.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
Test Receiver ROHDE & SCHWARZ	ESIB7	100187	Apr. 18, 2016	Apr. 17, 2017
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100041	Sep. 02, 2015	Sep. 01, 2016
BILOG Antenna SCHWARZBECK	VULB9168	9168-171	Jan. 07, 2016	Jan. 06, 2017
HORN Antenna SCHWARZBECK	9120D	209	Jan. 20, 2016	Jan. 19, 2017
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA9170241	Jan. 18, 2016	Jan. 17, 2017
Preamplifier Agilent	8447D	2944A10738	Oct.18, 2015	Oct. 17, 2016
Preamplifier Agilent	8449B	3008A01964	Aug. 22, 2015	Aug. 21, 2016
RF signal cable HUBER+SUHNER	SUCOFLEX 104	Cable-CH3-03 (214378)	Aug. 22, 2015	Aug. 21, 2016
RF signal cable HUBER+SUHNER	SUCOFLEX 106	Cable-CH3-03 (309224+12738)	Aug. 22, 2015	Aug. 21, 2016
Software BV ADT	ADT_Radiated_ V7.6.15.9.4	NA	NA	NA
Antenna Tower inn-co GmbH	MA 4000	013303	NA	NA
Antenna Tower Controller BV ADT	AT100	AT93021702	NA	NA
Turn Table BV ADT	TT100	TT93021702	NA	NA
Turn Table Controller BV ADT	SC100	SC93021702	NA	NA
High Speed Peak Power Meter	ML2495A	0824011	Jul. 09, 2015	Jul. 08, 2016
Power Sensor	MA2411B	0738171	Jul. 09, 2015	Jul. 08, 2016

Note:
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Chamber 3.
3. The horn antenna and preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
4. The FCC Site Registration No. is 988962.
5. The IC Site Registration No. is IC 7450F-3.

4.1.3 Test Procedures

a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.

f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. For Average measurement, due to the DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: 20log(3.125 / 100)= -30.1 dB, therefore Average value = peak reading + 20log(duty cycle).
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 Deviation from Test Standard

No deviation.

4.1.5 Test Setup

<Frequency Range 30MHz~1GHz>



<Frequency Range above 1GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

a. Placed the EUT on the testing table.
b. Prepared a notebook to act as a communication partner and placed it outside of testing area.
c. The communication partner connected with EUT via a RJ45 cable and ran a test program (provided by manufacturer) to enable EUT under transmission condition continuously at specific channel frequency.
d. The communication partner sent data to EUT by command "PING".

4.1.7 Test Results

Above 1GHz Data:

GFSK

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	51.8 PK	74.0	-22.2	2.31 H	37	53.1	-1.3
2	2390.00	43.1 AV	54.0	-10.9	2.31 H	37	44.4	-1.3
3	#2400.00	46.8 PK	74.0	-27.2	1.66 H	31	48.1	-1.3
4	#2400.00	16.7 AV	54.0	-37.3	1.66 H	31	18.0	-1.3
5	*2402.00	105.0 PK			1.66 H	31	72.2	32.8
6	*2402.00	74.9 AV			1.66 H	31	42.1	32.8
7	4804.00	47.8 PK	74.0	-26.2	1.73 H	100	41.9	5.9
8	4804.00	17.6 AV	54.0	-36.4	1.73 H	100	11.7	5.9
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	50.7 PK	74.0	-23.3	2.21 V	297	52.0	-1.3
2	2390.00	39.5 AV	54.0	-14.5	2.21 V	297	40.8	-1.3
3	#2400.00	42.2 PK	74.0	-31.8	2.20 V	306	43.5	-1.3
4	#2400.00	12.1 AV	54.0	-41.9	2.20 V	306	13.4	-1.3
5	*2402.00	99.5 PK			2.20 V	306	66.7	32.8
6	*2402.00	69.4 AV			2.20 V	306	36.6	32.8
7	4804.00	48.1 PK	74.0	-25.9	1.71 V	189	42.2	5.9
8	4804.00	18.0 AV	54.0	-36.0	1.71 V	189	12.1	5.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.
7. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: 20log(3.125 / 100)= -30.1 dB
8. Average value = peak reading + 20log(duty cycle).

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	105.1 PK			1.56 H	35	72.1	33.0
2	*2441.00	75.0 AV			1.56 H	35	42.0	33.0
3	4882.00	48.6 PK	74.0	-25.4	1.55 H	195	42.7	5.9
4	4882.00	18.5 AV	54.0	-35.5	1.55 H	195	12.6	5.9
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	99.7 PK			1.95 V	303	66.7	33.0
2	*2441.00	69.6 AV			1.95 V	303	36.6	33.0
3	4882.00	47.9 PK	74.0	-26.1	1.52 V	176	42.0	5.9
4	4882.00	17.8 AV	54.0	-36.2	1.52 V	176	11.9	5.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: 20log(3.125 / 100)= -30.1 dB
7. Average value = peak reading + 20log(duty cycle).

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	105.8 PK			1.11 H	38	72.8	33.0
2	*2480.00	75.7 AV			1.11 H	38	42.7	33.0
3	2483.50	45.2 PK	74.0	-28.8	1.11 H	38	46.3	-1.1
4	2483.50	15.1 AV	54.0	-38.9	1.11 H	38	16.2	-1.1
5	4960.00	47.6 PK	74.0	-26.4	1.85 H	183	41.5	6.1
6	4960.00	17.5 AV	54.0	-36.5	1.85 H	183	11.4	6.1
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	96.8 PK			1.57 V	323	63.8	33.0
2	*2480.00	66.7 AV			1.57 V	323	33.7	33.0
3	2483.50	43.6 PK	74.0	-30.4	1.57 V	323	44.7	-1.1
4	2483.50	13.6 AV	54.0	-40.4	1.57 V	323	14.7	-1.1
5	4960.00	48.5 PK	74.0	-25.5	1.28 V	129	42.4	6.1
6	4960.00	18.4 AV	54.0	-35.6	1.28 V	129	12.3	6.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: 20log(3.125 / 100)= -30.1 dB
7. Average value = peak reading + 20log(duty cycle).

8DPSK

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	50.7 PK	74.0	-23.3	2.09 H	38	52.0	-1.3
2	2390.00	39.6 AV	54.0	-14.4	2.09 H	38	40.9	-1.3
3	#2400.00	48.6 PK	74.0	-25.4	1.61 H	30	49.9	-1.3
4	#2400.00	18.5 AV	54.0	-35.5	1.61 H	30	19.8	-1.3
5	*2402.00	104.7 PK			1.61 H	30	71.9	32.8
6	*2402.00	74.6 AV			1.61 H	30	41.8	32.8
7	4804.00	47.8 PK	74.0	-26.2	1.76 H	114	41.9	5.9
8	4804.00	17.7 AV	54.0	-36.3	1.76 H	114	11.8	5.9
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	50.5 PK	74.0	-23.5	1.87 V	303	51.8	-1.3
2	2390.00	38.3 AV	54.0	-15.7	1.87 V	303	39.6	-1.3
3	#2400.00	46.7 PK	74.0	-27.3	2.24 V	304	48.0	-1.3
4	#2400.00	16.6 AV	54.0	-37.4	2.24 V	304	17.9	-1.3
5	*2402.00	98.3 PK			2.24 V	304	65.5	32.8
6	*2402.00	68.2 AV			2.24 V	304	35.4	32.8
7	4804.00	47.7 PK	74.0	-26.3	1.66 V	194	41.8	5.9
8	4804.00	17.6 AV	54.0	-36.4	1.66 V	194	11.7	5.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.
7. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: 20log(3.125 / 100)= -30.1 dB
8. Average value = peak reading + 20log(duty cycle).

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	103.9 PK			1.45 H	35	70.9	33.0
2	*2441.00	73.8 AV			1.45 H	35	40.8	33.0
3	4882.00	48.2 PK	74.0	-25.8	1.72 H	156	42.3	5.9
4	4882.00	18.1 AV	54.0	-35.9	1.72 H	156	12.2	5.9
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	97.9 PK			2.91 V	14	64.9	33.0
2	*2441.00	67.8 AV			2.91 V	14	34.8	33.0
3	4882.00	48.4 PK	74.0	-25.6	2.11 V	173	42.5	5.9
4	4882.00	18.3 AV	54.0	-35.7	2.11 V	173	12.4	5.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: 20log(3.125 / 100)= -30.1 dB
7. Average value = peak reading + 20log(duty cycle).

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	103.0 PK			1.39 H	35	70.0	33.0
2	*2480.00	72.9 AV			1.39 H	35	39.9	33.0
3	2483.50	45.7 PK	74.0	-28.3	1.39 H	35	46.8	-1.1
4	2483.50	15.6 AV	54.0	-38.4	1.39 H	35	16.7	-1.1
5	4960.00	48.4 PK	74.0	-25.6	2.00 H	128	42.3	6.1
6	4960.00	18.3 AV	54.0	-35.7	2.00 H	128	12.2	6.1
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	99.9 PK			2.59 V	27	66.9	33.0
2	*2480.00	69.8 AV			2.59 V	27	36.8	33.0
3	2483.50	45.0 PK	74.0	-29.0	2.59 V	27	46.1	-1.1
4	2483.50	14.9 AV	54.0	-39.1	2.59 V	27	16.0	-1.1
5	4960.00	48.2 PK	74.0	-25.8	1.56 V	135	42.1	6.1
6	4960.00	18.1 AV	54.0	-35.9	1.56 V	135	12.0	6.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: 20log(3.125 / 100)= -30.1 dB
7. Average value = peak reading + 20log(duty cycle).

Below 1GHz worst-case data: GFSK

Mode A

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	57.12	30.9 QP	40.0	-9.1	2.00 H	156	45.5	-14.6
2	142.67	30.6 QP	43.5	-12.9	2.00 H	261	44.9	-14.3
3	166.00	29.2 QP	43.5	-14.3	2.00 H	132	43.2	-14.0
4	222.38	29.7 QP	46.0	-16.3	1.50 H	327	45.6	-15.9
5	296.27	26.6 QP	46.0	-19.4	1.00 H	119	38.9	-12.3
6	335.15	31.1 QP	46.0	-14.9	1.00 H	116	42.5	-11.4
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	49.34	34.7 QP	40.0	-5.3	1.00 V	277	49.1	-14.4
2	127.11	25.0 QP	43.5	-18.5	1.00 V	16	40.9	-15.9
3	158.22	28.1 QP	43.5	-15.4	1.00 V	127	41.8	-13.7
4	220.44	24.8 QP	46.0	-21.2	1.50 V	247	40.7	-15.9
5	294.32	23.5 QP	46.0	-22.5	1.50 V	180	35.9	-12.4
6	335.15	26.8 QP	46.0	-19.2	1.50 V	161	38.2	-11.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

Mode B

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	57.12	30.9 QP	40.0	-9.1	2.00 H	16	45.5	-14.6
2	90.17	28.5 QP	43.5	-15.0	2.00 H	285	48.2	-19.7
3	107.67	27.4 QP	43.5	-16.1	2.00 H	285	45.0	-17.6
4	144.61	29.1 QP	43.5	-14.4	2.00 H	278	43.3	-14.2
5	232.11	30.7 QP	46.0	-15.3	1.00 H	152	46.4	-15.7
6	333.21	29.9 QP	46.0	-16.1	1.00 H	128	41.3	-11.4
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	**37.68**	**36.8 QP**	**40.0**	**-3.2**	**1.00 V**	**280**	**52.2**	**-15.4**
2	57.12	28.5 QP	40.0	-11.5	1.00 V	198	43.1	-14.6
3	82.40	24.1 QP	40.0	-15.9	1.50 V	16	43.2	-19.1
4	140.72	29.9 QP	43.5	-13.6	1.00 V	257	44.4	-14.5
5	169.89	30.6 QP	43.5	-12.9	1.00 V	83	44.8	-14.2
6	232.11	24.6 QP	46.0	-21.4	2.00 V	211	40.3	-15.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
Test Receiver ROHDE & SCHWARZ	ESCI	100613	Nov. 16, 2015	Nov. 15, 2016
RF signal cable (with 10dB PAD) Woken	5D-FB	Cable-cond1-01	Dec. 26, 2015	Dec. 25, 2016
LISN ROHDE & SCHWARZ (EUT)	ESH3-Z5	835239/001	Feb. 26, 2016	Feb. 25, 2017
LISN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100311	Jul. 24, 2015	Jul. 23, 2016
Software ADT	BV ADT_Cond_ V7.3.7.3	NA	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Shielded Room 1.
3. The VCCI Site Registration No. is C-2040.

4.2.3 Test Procedures

a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.

b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.

c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) were not recorded.

NOTE: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

4.2.4 Deviation from Test Standard

No deviation.

4.2.5 Test Setup

4.2.7 Test Results

Worst-Case Data: GFSK

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
Test Mode	A		

No	Freq.	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16569	10.08	35.55	23.55	45.63	33.63	65.17	55.17	-19.54	-21.54
2	0.20865	10.08	27.43	14.68	37.51	24.76	63.26	53.26	-25.75	-28.50
3	0.27903	10.12	22.00	13.56	32.12	23.68	60.84	50.84	-28.72	-27.16
4	0.47453	10.18	24.45	21.12	34.63	31.30	56.43	46.43	-21.80	-15.13
5	3.63772	10.45	16.73	8.76	27.18	19.21	56.00	46.00	-28.82	-26.79
6	22.47219	11.58	9.48	3.86	21.06	15.44	60.00	50.00	-38.94	-34.56

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.



Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
Test Mode	A		

No	Freq.	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15719	10.08	38.12	24.50	48.20	34.58	65.61	55.61	-17.41	-21.03
2	0.18519	10.08	32.62	17.23	42.70	27.31	64.25	54.25	-21.55	-26.94
3	0.21256	10.09	27.71	14.06	37.80	24.15	63.10	53.10	-25.30	-28.95
4	0.25557	10.12	20.54	9.96	30.66	20.08	61.57	51.57	-30.91	-31.49
5	0.32595	10.18	17.10	7.56	27.28	17.74	59.55	49.55	-32.27	-31.81
6	3.70028	10.56	12.41	5.61	22.97	16.17	56.00	46.00	-33.03	-29.83

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.



Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
Test Mode	B		

No	Freq.	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15391	10.08	44.56	28.75	54.64	38.83	65.79	55.79	-11.15	-16.96
2	0.16955	10.08	40.22	24.62	50.30	34.70	64.98	54.98	-14.68	-20.28
3	0.18519	10.08	37.20	22.39	47.28	32.47	64.25	54.25	-16.97	-21.78
4	0.21647	10.09	32.84	19.51	42.93	29.60	62.95	52.95	-20.02	-23.35
5	**0.52544**	**10.20**	**35.56**	**30.28**	**45.76**	**40.48**	**56.00**	**46.00**	**-10.24**	**-5.52**
6	10.88686	10.82	28.31	23.25	39.13	34.07	60.00	50.00	-20.87	-15.93

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.



Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
Test Mode	B		

No	Freq.	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15391	10.08	45.02	28.09	55.10	38.17	65.79	55.79	-10.69	-17.62
2	0.16569	10.08	42.12	27.42	52.20	37.50	65.17	55.17	-12.97	-17.67
3	0.18128	10.08	39.14	24.72	49.22	34.80	64.43	54.43	-15.21	-19.63
4	0.20893	10.09	33.39	19.98	43.48	30.07	63.25	53.25	-19.77	-23.18
5	0.52927	10.25	35.07	29.29	45.32	39.54	56.00	46.00	-10.68	-6.46
6	10.99634	10.92	27.10	21.84	38.02	32.76	60.00	50.00	-21.98	-17.24

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.



4.3 Number of Hopping Frequency Used

4.3.1 Limits of Hopping Frequency Used Measurement

At least 15 channels frequencies, and should be equally spaced.

4.3.2 Test Setup

4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.3.4 Test Procedure

a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
c. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
d. Set the SA on View mode and then plot the result on SA screen.
e. Repeat above procedures until all frequencies measured were complete.

4.3.5 Deviation fromTest Standard

No deviation.

4.3.6 Test Results

There are 79 hopping frequencies in the hopping mode. Please refer to next page for the test result. On the plots, it shows that the hopping frequencies are equally spaced.

GFSK


RBW 100 kHz
VBW 300 kHz
SWT 5 ms
[T1] MP VIEW
[T2] MP VIEW
Ref 29 dBm
Att 20 dB
Offset 19 dB
Marker 1 [T1]
6.38 dBm
2.40200 GHz
Marker 2 [T1]
6.33 dBm
2.44200 GHz
Center 2.42142 GHz
4.2 MHz/
Span 42 MHz


RBW 100 kHz
VBW 300 kHz
SWT 5 ms
[T1] MP VIEW
[T2] MP VIEW
Ref 29 dBm
Att 20 dB
Offset 19 dB
Marker 1 [T1]
3.96 dBm
2.44300 GHz
Marker 2 [T1]
4.79 dBm
2.48000 GHz
Center 2.4634 GHz
4.2 MHz/
Span 42 MHz

8DPSK


RBW 100 kHz
VBW 300 kHz
SWT 5 ms
[T1] MP VIEW
[T2] MP VIEW
Ref 29 dBm
Att 20 dB
Offset 19 dB
Marker 1 [T1]
1.89 dBm
2.40200 GHz
Marker 2 [T1]
2.56 dBm
2.44200 GHz
Center 2.42142 GHz
4.2 MHz/
Span 42 MHz


RBW 100 kHz
VBW 300 kHz
SWT 5 ms
[T1] MP VIEW
[T2] MP VIEW
Ref 29 dBm
Att 20 dB
Offset 19 dB
Marker 1 [T1]
0.13 dBm
2.44300 GHz
Marker 2 [T1]
-1.62 dBm
2.48000 GHz
Center 2.4634 GHz
4.2 MHz/
Span 42 MHz

4.4 Dwell Time on Each Channel

4.4.1 Limits of Dwell Time on Each Channel Measurement

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

4.4.2 Test Setup

4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.4.4 Test Procedures

a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
c. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
d. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
e. Repeat above procedures until all different time-slot modes have been completed.

4.4.5 Deviation from Test Standard

No deviation.

4.4.6 Test Results

GFSK

Mode	Number of transmission in a 31.6 (79Hopping*0.4)	Length of transmission time (msec)	Result (msec)	Limit (msec)
DH1	51 (times / 5 sec) * 6.32 = 322.32 times	0.462	148.91	400
DH3	25 (times / 5 sec) * 6.32 = 158 times	1.72	271.76	400
DH5	16 (times / 5 sec) * 6.32 = 101.12 times	2.96	299.32	400

Note: Test plots of the transmitting time slot are shown as below.

DH1



DH3



DH5



8DPSK

Mode	Number of transmission in a 31.6 (79Hopping*0.4)	Length of transmission time (msec)	Result (msec)	Limit (msec)
DH1	51 (times / 5 sec) * 6.32 = 322.32 times	0.468	150.85	400
DH3	25 (times / 5 sec) * 6.32 = 158 times	1.76	278.08	400
DH5	16 (times / 5 sec) * 6.32 = 101.12 times	2.96	299.32	400

Note: Test plots of the transmitting time slot are shown as below.

DH1



DH3



DH5



4.5 Channel Bandwidth

4.5.1 Limits of Channel Bandwidth Measurement

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dBbandwidth of hopping channel shell be a minimum limit for the hopping channel separation.

4.5.2 Test Setup

4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.5.4 Test Procedure

a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
d. Repeat above procedures until all frequencies measured were complete.

4.5.5 Deviation from Test Standard

No deviation.

4.5.6 EUT Operating Condition

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.5.7 Test Results

Channel	Frequency (MHz)	20dB Bandwidth (MHz)	
		GFSK	8DPSK
0	2402	0.88	1.33
39	2441	0.99	1.30
78	2480	0.97	1.30

Spectrum Plot of Worst Value	
GFSK	8DPSK
	

4.6 Hopping Channel Separation

4.6.1 Limits of Hopping Channel Separation Measurement

At least 25kHz or two-third of 20dB hopping channel bandwidth (whichever is greater).

4.6.2 Test Setup

4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.6.4 Test Procedure

Measurement Procedure REF

a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
c. By using the MaxHold function record the separation of two adjacent channels.
d. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
e. Repeat above procedures until all frequencies measured were complete.

4.6.5 Deviation from Test Standard

No deviation.

4.6.6 Test Results

Channel	Frequency (MHz)	Adjacent Channel Separation (MHz)		20dB Bandwidth (MHz)		Minimum Limit (MHz)		Pass / Fail
		GFSK	8DPSK	GFSK	8DPSK	GFSK	8DPSK	
0	2402	1.00	1.00	0.88	1.33	0.59	0.89	Pass
39	2441	1.00	1.00	0.99	1.30	0.66	0.87	Pass
78	2480	1.00	1.00	0.97	1.30	0.65	0.87	Pass

Note: The minimum limit is two-third 20dB bandwidth.

Spectrum Plot of Worst Value	
GFSK	8DPSK
	

4.7 Maximum Output Power

4.7.1 Limits of Maximum Output Power Measurement

The Maximum Output Power Measurement is 125mW.

4.7.2 Test Setup

4.7.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.7.4 Test Procedure

a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
c. The center frequency of the spectrum analyzer is set to the fundamental frequency and using 3MHz RBW and 10 MHz VBW.
d. Measure the captured power within the band and recording the plot.
e. Repeat above procedures until all frequencies required were complete.

4.7.5 Deviation fromTest Standard

No deviation.

4.7.6 EUT Operating Condition

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.7.7 Test Results

Channel	Frequency (MHz)	Output Power (mW)		Output Power (dBm)		Power Limit (mW)	Pass / Fail
		GFSK	8DPSK	GFSK	8DPSK		
0	2402	**6.442**	5.675	8.09	7.54	125	Pass
39	2441	5.105	4.498	7.08	6.53	125	Pass
78	2480	3.698	3.327	5.68	5.22	125	Pass

Spectrum Plot of Worst Value	
GFSK	8DPSK





4.8 Conducted Out of Band Emission Measurement

4.8.1 Limits Of Conducted Out Of Band Emission Measurement

Below –20dB of the highest emission level of operating band (in 100kHz RBW).

4.8.2 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.8.3 Test Procedure

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100 kHz and 300 kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

4.8.4 Deviation from Test Standard

No deviation.

4.8.5 EUT Operating Condition

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.8.6 Test Results

The spectrum plots are attached on the following images. D1 line indicates the highest level, D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.

GFSK

Hopping disabled_ Low Channel



Hopping disabled_ High Channel



Hopping enabled_ Low Channel



Hopping enabled_ High Channel



8DPSK

Hopping disabled_ Low Channel



Hopping disabled_ High Channel



Hopping enabled_ Low Channel



Hopping enabled_ High Channel



5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab
Tel: 886-2-26052180
Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab
Tel: 886-3-6668565
Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab
Tel: 886-3-3183232
Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com
Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---