FCC Test Report

Report No.: RF170720C12

FCC ID: TVE-291BB033

Test Model: FortiAP U422EV

Series Model: FortiAP U422EVxxxxxx, FAP-U422EVxxxxxx, FORTIAP-U422EVxxxxxx (where “x” can be used as “A-Z”, or “0-9”, or “-“, or blank for marketing purposes only) (refer to item 3.1 for more details)

Received Date: Jul. 20, 2017

Test Date: Sep. 13 ~ Oct. 03, 2017

Issued Date: Oct. 13, 2017

Applicant: Fortinet Inc.

Address: 899 Kifer Road Sunnyvale, CA 94086 USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan (R.O.C.)

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, TAIWAN (R.O.C.)

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.
This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record **4**

1 Certificate of Conformity **5**

2 Summary of Test Results **6**

2.1 Measurement Uncertainty 6
2.2 Modification Record 6

3 General Information **7**

3.1 General Description of EUT 7
3.2 Description of Test Modes 8
3.2.1 Test Mode Applicability and Tested Channel Detail 9
3.3 Duty Cycle of Test Signal 11
3.4 Description of Support Units 12
3.4.1 Configuration of System under Test 12
3.5 General Description of Applied Standards 12

4 Test Types and Results **13**

4.1 Radiated Emission and Bandedge Measurement 13
4.1.1 Limits of Radiated Emission and Bandedge Measurement 13
4.1.2 Test Instruments 14
4.1.3 Test Procedures 15
4.1.4 Deviation from Test Standard 15
4.1.5 Test Setup 16
4.1.6 EUT Operating Conditions 17
4.1.7 Test Results 18
4.2 Conducted Emission Measurement 31
4.2.1 Limits of Conducted Emission Measurement 31
4.2.2 Test Instruments 31
4.2.3 Test Procedures 32
4.2.4 Deviation from Test Standard 32
4.2.5 Test Setup 32
4.2.6 EUT Operating Conditions 32
4.2.7 Test Results 33
4.3 6dB Bandwidth Measurement 35
4.3.1 Limits of 6dB Bandwidth Measurement 35
4.3.2 Test Setup 35
4.3.3 Test Instruments 35
4.3.4 Test Procedure 35
4.3.5 Deviation fromTest Standard 35
4.3.6 EUT Operating Conditions 35
4.3.7 Test Result 36
4.4 Conducted Output Power Measurement 38
4.4.1 Limits of Conducted Output Power Measurement 38
4.4.2 Test Setup 38
4.4.3 Test Instruments 38
4.4.4 Test Procedures 38
4.4.5 Deviation from Test Standard 38
4.4.6 EUT Operating Conditions 38
4.4.7 Test Results 39
4.5 Power Spectral Density Measurement 41
4.5.1 Limits of Power Spectral Density Measurement 41
4.5.2 Test Setup 41
4.5.3 Test Instruments 41
4.5.4 Test Procedure 41
4.5.5 Deviation from Test Standard 42
4.5.6 EUT Operating Condition 42

4.5.7 Test Results 43
4.6 Conducted Out of Band Emission Measurement 48
4.6.1 Limits of Conducted Out of Band Emission Measurement 48
4.6.2 Test Setup 48
4.6.3 Test Instruments 48
4.6.4 Test Procedure 48
4.6.5 Deviation from Test Standard 48
4.6.6 EUT Operating Condition 48
4.6.7 Test Results 48

5 Pictures of Test Arrangements 65

Appendix – Information on the Testing Laboratories 66

Release Control Record

Issue No.	Description	Date Issued
RF170720C12	Original release.	Oct. 13, 2017

1 Certificate of Conformity

Product:	Secured Wireless Access Point
Brand:	Fortinet Inc.
Test Model:	FortiAP U422EV
Series Model:	FortiAP U422EVxxxxxx, FAP-U422EVxxxxxx, FORTIAP-U422EVxxxxxx (where "x" can be used as "A-Z", or "0-9", or "-", or blank for marketing purposes only) (refer to item 3.1 for more details)
Sample Status:	Engineering sample
Applicant:	Fortinet Inc.
Test Date:	Sep. 13 ~ Oct. 03, 2017
Standards:	47 CFR FCC Part 15, Subpart C (Section 15.247) ANSI C63.10:2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : Celine Chou , **Date:** Oct. 13, 2017

Celine Chou / Specialist

Approved by : Ken Liu , **Date:** Oct. 13, 2017

Ken Liu / Senior Manager

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)			
FCC Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	Pass	Meet the requirement of limit. Minimum passing margin is -8.99dB at 0.45097MHz.
15.205 / 15.209 / 15.247(d)	Radiated Emissions and Band Edge Measurement	Pass	Meet the requirement of limit. Minimum passing margin is -1.0dB at 2390.00MHz.
15.247(d)	Antenna Port Emission	Pass	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	Pass	Meet the requirement of limit.
15.247(b)	Conducted power	Pass	Meet the requirement of limit.
15.247(e)	Power Spectral Density	Pass	Meet the requirement of limit.
15.203	Antenna Requirement	Pass	Antenna connector is N-Type plug not a standard connector.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150kHz ~ 30MHz	2.94 dB
Radiated Emissions up to 1 GHz	30MHz ~ 200MHz	3.63 dB
	200MHz ~1000MHz	3.64 dB
Radiated Emissions above 1 GHz	1GHz ~ 18GHz	2.29 dB
	18GHz ~ 40GHz	2.29 dB

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT

Product	Secured Wireless Access Point
Brand	Fortinet Inc.
Test Model	FortiAP U422EV
Series Model	FortiAP U422EVxxxxxx, FAP-U422EVxxxxxx, FORTIAP-U422EVxxxxxx (where “x” can be used as “A-Z”, or “0-9”, or “-“, or blank for marketing purposes only)
Model Difference	Refer to note
Sample Status	Engineering sample
Power Supply Rating	54Vdc from POE
Modulation Type	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
Modulation Technology	DSSS, OFDM
Transfer Rate	802.11b:11/5.5/2/1Mbps 802.11g: 54/48/36/24/18/12/9/6Mbps 802.11n: up to 600Mbps
Operating Frequency	2412 ~ 2462MHz
Number of Channel	802.11b, 802.11g, 802.11n (HT20): 11 802.11n (HT40): 7
Output Power	CDD Mode: 761.835mW Beamforming Mode: 120.504mW
Antenna Type	Refer to note
Antenna Connector	Refer to note
Accessory Device	POE, Wall mount
Cable Supplied	1.75m non-shielded Grounding cable without core connected EUT

Note:

1. The EUT incorporates a MIMO function. Physically, the EUT provides 4 completed transmitters and 4 receivers.

Modulation Mode	Beamforming Mode	TX Function
802.11b	Not Support	4TX
802.11g	Not Support	4TX
802.11n (HT20)	Support	4TX
802.11n (HT40)	Support	4TX

* For 802.11n, CDD mode and Beamforming mode are presented in power output test item. For other test items, CDD mode is the worst case for final tests after pretesting.

2. The following models are provided to this EUT.

Brand	Model	Description
Fortinet Inc.	FortiAP U422EVxxxxxx	where “x” can be used as “A-Z”, or “0-9”, or“-“, or blank for marketing purposes only
	FAP-U422EVxxxxxx	
	FORTIAP-U422EVxxxxxx	

* The model FortiAP U422EV was chosen for final test.

3. The EUT consumes power from the following POE.

Brand	SENAO
Model	PIN060-54PR
Input Power	100-240Vac, 50/60Hz, 1.5A
Output Power	54Vdc / 1.11A PIN 3,4,5,6: 54Vdc PIN 1,2,7,8 RETURN
Power Line	0.5m non-shielded without core

4. The following antennas were provided to the EUT.

Antenna Type	Dipole					Antenna Connector			N-Type plug			
Gain (dBi)	Frequency (MHz)											
	2400	2450	2500	4900	5150	5250	5350	5500	5600	5725	5850	5925
WLAN Ant.	4.4	4.6	5.0	6.5	6.8	7.0	6.2	5.9	6.1	6.3	5.8	5.8

Antenna Type	Printed	Antenna Connector	MMCX
Gain (dBi)	Frequency (MHz)		
	2400	2450	2500
BT Ant.	5.77	5.52	5.57

5. 2.4GHz, 5GHz & BT or 2.4GHz, 5GHz & BT LE technology can transmit at same time. BT and BT LE cannot transmit simultaneously.
6. Spurious emission of the simultaneous operation (2.4GHz, 5GHz & BT or 2.4GHz, 5GHz & BT LE) has been evaluated and no non-compliance was found.

3.2 Description of Test Modes

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20):

Channel	Frequency	Channel	Frequency
1	2412MHz	7	2442MHz
2	2417MHz	8	2447MHz
3	2422MHz	9	2452MHz
4	2427MHz	10	2457MHz
5	2432MHz	11	2462MHz
6	2437MHz		

7 channels are provided for 802.11n (HT40):

Channel	Frequency	Channel	Frequency
3	2422MHz	7	2442MHz
4	2427MHz	8	2447MHz
5	2432MHz	9	2452MHz
6	2437MHz		

3.2.1 Test Mode Applicability and Tested Channel Detail

EUT Configure Mode	Applicable to				Description
	RE≥1G	RE<1G	PLC	APCM	
-	√	√	√	√	-

Where RE≥1G: Radiated Emission above 1GHz & Bandedge Measurement RE<1G: Radiated Emission below 1GHz
PLC: Power Line Conducted Emission APCM: Antenna Port Conducted Measurement

Note: The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **Z-plane**.

Radiated Emission Test (Above 1GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
-	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
-	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
-	802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	6.5
-	802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	13.5

Radiated Emission Test (Below 1GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
-	802.11b	1 to 11	1	DSSS	DBPSK	1.0

Power Line Conducted Emission Test:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
-	802.11b	1 to 11	1	DSSS	DBPSK	1.0

6dB Bandwidth, Power Spectral Density and Conducted Out of Band Emission Measurement:

☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
-	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
-	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
-	802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	6.5
-	802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	13.5

Conducted Output Power Measurement:

☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
CDD Mode						
-	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
-	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
-	802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	6.5
-	802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	13.5
Beamforming Mode						
-	802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	6.5
-	802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	13.5

Test Condition:

Applicable to	Environmental Conditions	Input Power	Tested by
RE≥1G	25 deg. C, 70% RH	120Vac, 60Hz	Matthew Yang
RE<1G	25 deg. C, 70% RH	120Vac, 60Hz	Matthew Yang
PLC	25 deg. C, 75% RH	120Vac, 60Hz	Matthew Yang
APCM	25 deg. C, 60% RH	120Vac, 60Hz	Credic Wu

3.3 Duty Cycle of Test Signal

802.11b, 802.11g, 802.11n (HT20): Duty cycle of test signal is > 98%, duty factor is not required.
802.11n (HT40): Duty cycle of test signal is < 98%, duty factor is required.

802.11g: Duty cycle = 12.444/12.480 = 0.997
802.11g: Duty cycle = 2.062/2.092 = 0.986
802.11n (HT20): Duty cycle = 1.920/1.950 = 0.985
802.11n (HT40): Duty cycle = 0.937/0.980 = 0.956, Duty factor = 10 * log(1/0.956) = 0.19

802.11b



802.11g



802.11n (HT20)



802.11n (HT40)



3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	Notebook	DELL	E5410	6RP2YM1	FCC DoC Approved	-
B.	Load	NA	NA	NA	NA	-

Note:

1. All power cords of the above support units are non-shielded (1.8m).
2. Item A acted as a communication partner to transfer data.

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	RJ45, Cat5e	1	3	N	0	-
2.	RJ45, Cat5e	2	1.8	N	0	-
3.	RJ45, Cat5e	1	1.8	N	0	-

3.4.1 Configuration of System under Test



3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247)
KDB 558074 D01 DTS Meas Guidance v04
KDB 662911 D01 Multiple Transmitter Output v02r01
ANSI C63.10:2013

All test items have been performed and recorded as per the above standards.

Note: The EUT has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 30dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Note:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 30dB under any condition of modulation.

4.1.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
Test Receiver ROHDE & SCHWARZ	ESCI	100424	Oct. 24, 2016	Oct. 23, 2017
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100040	Aug. 18, 2017	Aug. 17, 2018
BILOG Antenna SCHWARZBECK	VULB9168	9168-155	Dec. 28, 2016	Dec. 27, 2017
HORN Antenna SCHWARZBECK	BBHA 9120D	9120D-1170	Dec. 15, 2016	Dec. 14, 2017
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA9170241	Dec. 14, 2016	Dec. 13, 2017
Loop Antenna EMCI	EM-6879	269	Aug. 11, 2017	Aug. 10, 2018
Preamplifier Agilent	8449B	3008A01960	Aug. 08, 2017	Aug. 07, 2018
Preamplifier Agilent	8447D	2944A10631	Aug. 08, 2017	Aug. 07, 2018
RF signal cable HUBER+SUHNER	SUCOFLEX 104	MY 13380+295012/04	Aug. 08, 2017	Aug. 07, 2018
RF signal cable HUBER+SUHNER	SUCOFLEX 104	Cable-CH4-03 (250724)	Aug. 08, 2017	Aug. 07, 2018
Software BV ADT	ADT_Radiated_ V7.6.15.9.4	NA	NA	NA
Antenna Tower inn-co GmbH	MA 4000	010303	NA	NA
Antenna Tower Controller BV ADT	AT100	AT93021703	NA	NA
Turn Table BV ADT	TT100	TT93021703	NA	NA
Turn Table Controller BV ADT	SC100	SC93021703	NA	NA
High Speed Peak Power Meter	ML2495A	0824012	Aug. 18, 2017	Aug. 17, 2018
Power Sensor	MA2411B	0738171	Aug. 18, 2017	Aug. 17, 2018

Note:
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Chamber 4.
3. The horn antenna and preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
4. The FCC Designation Number is TW0003. The number will be varied with the Lab location and scope as attached.
5. The IC Site Registration No. is IC7450F-4.

4.1.3 Test Procedures

For Radiated emission below 30MHz

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. Both X and Y axes of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz

a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.

f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.

2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.

3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is ≥ 1/T (Duty cycle < 98%) or 10 Hz (Duty cycle ≥ 98%) for Peak detection at frequency above 1GHz.

4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 Deviation from Test Standard

No deviation.

4.1.5 Test Setup

For Radiated emission below 30MHz



For Radiated emission 30MHz to 1GHz



For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

a. Placed the EUT on the testing table.
b. Prepared a notebook to act as a communication partner and placed it outside of testing area.
c. The communication partner connected with EUT via a RJ45 cable and ran a test program (provided by manufacturer) to enable EUT under transmission condition continuously at specific channel frequency.
d. The communication partner sent data to EUT by command "PING".

4.1.7 Test Results

Above 1GHz Data:

802.11b

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	57.9 PK	74.0	-16.1	3.44 H	83	24.4	33.5
2	2390.00	46.0 AV	54.0	-8.0	3.44 H	83	12.5	33.5
3	*2412.00	101.7 PK			3.50 H	38	68.2	33.5
4	*2412.00	97.9 AV			3.50 H	38	64.4	33.5
5	4824.00	49.2 PK	74.0	-24.8	3.02 H	256	41.2	8.0
6	4824.00	36.8 AV	54.0	-17.2	3.02 H	256	28.8	8.0
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	65.1 PK	74.0	-8.9	2.10 V	185	31.8	33.3
2	2390.00	52.9 AV	54.0	-1.1	2.10 V	185	19.6	33.3
3	*2412.00	118.2 PK			2.00 V	161	84.9	33.3
4	*2412.00	114.4 AV			2.00 V	161	81.1	33.3
5	4824.00	52.8 PK	74.0	-21.2	1.95 V	173	45.0	7.8
6	4824.00	45.0 AV	54.0	-9.0	1.95 V	173	37.2	7.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	107.8 PK			3.44 H	41	74.2	33.6
2	*2437.00	103.9 AV			3.44 H	41	70.3	33.6
3	4874.00	50.8 PK	74.0	-23.2	3.14 H	208	42.7	8.1
4	4874.00	37.9 AV	54.0	-16.1	3.14 H	208	29.8	8.1
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	123.7 PK			2.01 V	19	90.3	33.4
2	*2437.00	120.0 AV			2.01 V	19	86.6	33.4
3	4874.00	56.8 PK	74.0	-17.2	2.01 V	202	48.9	7.9
4	4874.00	51.7 AV	54.0	-2.3	2.01 V	202	43.8	7.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	101.3 PK			3.64 H	35	67.5	33.8
2	*2462.00	97.3 AV			3.64 H	35	63.5	33.8
3	2483.50	58.5 PK	74.0	-15.5	3.49 H	77	24.6	33.9
4	2483.50	46.2 AV	54.0	-7.8	3.49 H	77	12.3	33.9
5	4924.00	49.7 PK	74.0	-24.3	2.98 H	210	41.4	8.3
6	4924.00	36.9 AV	54.0	-17.1	2.98 H	210	28.6	8.3
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	116.9 PK			2.10 V	164	83.3	33.6
2	*2462.00	113.2 AV			2.10 V	164	79.6	33.6
3	2483.50	65.1 PK	74.0	-8.9	2.04 V	174	31.5	33.6
4	2483.50	52.9 AV	54.0	-1.1	2.04 V	174	19.3	33.6
5	4924.00	50.8 PK	74.0	-23.2	1.61 V	213	42.8	8.0
6	4924.00	40.1 AV	54.0	-13.9	1.61 V	213	32.1	8.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

802.11g

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	57.2 PK	74.0	-16.8	3.42 H	101	23.7	33.5
2	2390.00	45.8 AV	54.0	-8.2	3.42 H	101	12.3	33.5
3	*2412.00	97.8 PK			3.53 H	38	64.3	33.5
4	*2412.00	87.9 AV			3.53 H	38	54.4	33.5
5	4824.00	49.4 PK	74.0	-24.6	2.88 H	214	41.4	8.0
6	4824.00	36.5 AV	54.0	-17.5	2.88 H	214	28.5	8.0
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	68.6 PK	74.0	-5.4	1.93 V	356	35.3	33.3
2	2390.00	52.9 AV	54.0	-1.1	1.93 V	356	19.6	33.3
3	*2412.00	116.7 PK			2.02 V	4	83.4	33.3
4	*2412.00	106.5 AV			2.02 V	4	73.2	33.3
5	4824.00	50.1 PK	74.0	-23.9	2.46 V	118	42.3	7.8
6	4824.00	36.9 AV	54.0	-17.1	2.46 V	118	29.1	7.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	57.6 PK	74.0	-16.4	3.58 H	96	24.1	33.5
2	2390.00	46.0 AV	54.0	-8.0	3.58 H	96	12.5	33.5
3	*2437.00	105.8 PK			3.77 H	37	72.2	33.6
4	*2437.00	96.1 AV			3.77 H	37	62.5	33.6
5	4874.00	49.7 PK	74.0	-24.3	2.93 H	207	41.6	8.1
6	4874.00	36.8 AV	54.0	-17.2	2.93 H	207	28.7	8.1
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	69.0 PK	74.0	-5.0	2.01 V	239	35.7	33.3
2	2390.00	52.9 AV	54.0	-1.1	2.01 V	239	19.6	33.3
3	*2437.00	124.3 PK			2.05 V	343	90.9	33.4
4	*2437.00	113.9 AV			2.05 V	343	80.5	33.4
5	4874.00	54.1 PK	74.0	-19.9	2.05 V	196	46.2	7.9
6	4874.00	39.7 AV	54.0	-14.3	2.05 V	196	31.8	7.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	100.4 PK			3.57 H	32	66.6	33.8
2	*2462.00	90.9 AV			3.57 H	32	57.1	33.8
3	2483.50	57.7 PK	74.0	-16.3	3.40 H	91	23.8	33.9
4	2483.50	46.1 AV	54.0	-7.9	3.40 H	91	12.2	33.9
5	4924.00	49.9 PK	74.0	-24.1	2.79 H	208	41.6	8.3
6	4924.00	36.9 AV	54.0	-17.1	2.79 H	208	28.6	8.3
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	117.7 PK			2.02 V	200	84.1	33.6
2	*2462.00	107.6 AV			2.02 V	200	74.0	33.6
3	2483.50	72.4 PK	74.0	-1.6	2.04 V	170	38.8	33.6
4	2483.50	52.8 AV	54.0	-1.2	2.04 V	170	19.2	33.6
5	4924.00	50.3 PK	74.0	-23.7	1.69 V	227	42.3	8.0
6	4924.00	37.3 AV	54.0	-16.7	1.69 V	227	29.3	8.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

802.11n (HT20)

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	57.0 PK	74.0	-17.0	3.51 H	89	23.5	33.5
2	2390.00	45.9 AV	54.0	-8.1	3.51 H	89	12.4	33.5
3	*2412.00	96.9 PK			3.58 H	34	63.4	33.5
4	*2412.00	87.0 AV			3.58 H	34	53.5	33.5
5	4824.00	49.2 PK	74.0	-24.8	2.76 H	281	41.2	8.0
6	4824.00	36.2 AV	54.0	-17.8	2.76 H	281	28.2	8.0
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	68.8 PK	74.0	-5.2	1.86 V	1	35.3	33.5
2	2390.00	52.8 AV	54.0	-1.2	1.86 V	1	19.3	33.5
3	*2412.00	115.7 PK			1.75 V	8	82.2	33.5
4	*2412.00	105.6 AV			1.75 V	8	72.1	33.5
5	4824.00	49.6 PK	74.0	-24.4	2.33 V	135	41.6	8.0
6	4824.00	36.3 AV	54.0	-17.7	2.33 V	135	28.3	8.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	57.3 PK	74.0	-16.7	3.66 H	87	23.8	33.5
2	2390.00	45.8 AV	54.0	-8.2	3.66 H	87	12.3	33.5
3	*2437.00	105.8 PK			3.78 H	40	72.2	33.6
4	*2437.00	96.1 AV			3.78 H	40	62.5	33.6
5	4874.00	49.6 PK	74.0	-24.4	2.70 H	288	41.5	8.1
6	4874.00	36.5 AV	54.0	-17.5	2.70 H	288	28.4	8.1
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	69.6 PK	74.0	-4.4	2.16 V	345	36.1	33.5
2	2390.00	52.5 AV	54.0	-1.5	2.16 V	345	19.0	33.5
3	*2437.00	122.7 PK			1.79 V	11	89.1	33.6
4	*2437.00	112.6 AV			1.79 V	11	79.0	33.6
5	4874.00	52.0 PK	74.0	-22.0	2.18 V	185	43.9	8.1
6	4874.00	39.3 AV	54.0	-14.7	2.18 V	185	31.2	8.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	97.9 PK			3.91 H	39	64.1	33.8
2	*2462.00	88.7 AV			3.91 H	39	54.9	33.8
3	2483.50	57.3 PK	74.0	-16.7	3.47 H	80	23.4	33.9
4	2483.50	45.9 AV	54.0	-8.1	3.47 H	80	12.0	33.9
5	4924.00	49.7 PK	74.0	-24.3	2.91 H	295	41.4	8.3
6	4924.00	36.6 AV	54.0	-17.4	2.91 H	295	28.3	8.3
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	116.8 PK			1.83 V	3	83.0	33.8
2	*2462.00	106.7 AV			1.83 V	3	72.9	33.8
3	2483.50	68.4 PK	74.0	-5.6	1.99 V	16	34.5	33.9
4	2483.50	52.5 AV	54.0	-1.5	1.99 V	16	18.6	33.9
5	4924.00	50.1 PK	74.0	-23.9	2.05 V	168	41.8	8.3
6	4924.00	37.0 AV	54.0	-17.0	2.05 V	168	28.7	8.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

802.11n (HT40)

CHANNEL	TX Channel 3	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	57.2 PK	74.0	-16.8	3.55 H	123	23.7	33.5
2	2390.00	45.8 AV	54.0	-8.2	3.55 H	123	12.3	33.5
3	*2422.00	93.0 PK			3.43 H	38	59.4	33.6
4	*2422.00	83.1 AV			3.43 H	38	49.5	33.6
5	4844.00	49.4 PK	74.0	-24.6	2.68 H	320	41.4	8.0
6	4844.00	36.5 AV	54.0	-17.5	2.68 H	320	28.5	8.0
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	64.8 PK	74.0	-9.2	1.98 V	3	31.3	33.5
2	2390.00	52.7 AV	54.0	-1.3	1.98 V	3	19.2	33.5
3	*2422.00	111.0 PK			1.71 V	7	77.4	33.6
4	*2422.00	101.2 AV			1.71 V	7	67.6	33.6
5	4844.00	50.1 PK	74.0	-23.9	2.35 V	55	42.1	8.0
6	4844.00	36.7 AV	54.0	-17.3	2.35 V	55	28.7	8.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	57.6 PK	74.0	-16.4	3.34 H	114	24.1	33.5
2	2390.00	45.8 AV	54.0	-8.2	3.34 H	114	12.3	33.5
3	*2437.00	96.7 PK			3.45 H	39	63.1	33.6
4	*2437.00	87.0 AV			3.45 H	39	53.4	33.6
5	4874.00	49.7 PK	74.0	-24.3	2.75 H	332	41.6	8.1
6	4874.00	36.7 AV	54.0	-17.3	2.75 H	332	28.6	8.1
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	67.5 PK	74.0	-6.5	2.05 V	1	34.0	33.5
2	**2390.00**	**53.0 AV**	**54.0**	**-1.0**	**2.05 V**	**1**	**19.5**	**33.5**
3	*2437.00	114.2 PK			1.74 V	4	80.6	33.6
4	*2437.00	104.3 AV			1.74 V	4	70.7	33.6
5	4874.00	50.4 PK	74.0	-23.6	2.37 V	51	42.3	8.1
6	4874.00	37.0 AV	54.0	-17.0	2.37 V	51	28.9	8.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 9	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	97.0 PK			3.45 H	38	63.2	33.8
2	*2452.00	87.2 AV			3.45 H	38	53.4	33.8
3	2483.50	58.3 PK	74.0	-15.7	3.28 H	71	24.4	33.9
4	2483.50	46.0 AV	54.0	-8.0	3.28 H	71	12.1	33.9
5	4904.00	49.9 PK	74.0	-24.1	2.73 H	333	41.7	8.2
6	4904.00	36.6 AV	54.0	-17.4	2.73 H	333	28.4	8.2
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	113.8 PK			1.84 V	5	80.0	33.8
2	*2452.00	104.0 AV			1.84 V	5	70.2	33.8
3	2483.50	72.5 PK	74.0	-1.5	2.01 V	4	38.6	33.9
4	2483.50	51.4 AV	54.0	-2.6	2.01 V	4	17.5	33.9
5	4904.00	50.4 PK	74.0	-23.6	2.56 V	70	42.2	8.2
6	4904.00	37.1 AV	54.0	-16.9	2.56 V	70	28.9	8.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

Below 1GHz worst-case data: 802.11b

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	45.42	31.3 QP	40.0	-8.7	1.00 H	73	46.0	-14.7
2	97.81	35.4 QP	43.5	-8.1	2.00 H	79	54.1	-18.7
3	241.40	29.6 QP	46.0	-16.4	1.00 H	32	44.1	-14.5
4	499.48	25.2 QP	46.0	-20.8	1.24 H	12	33.5	-8.3
5	730.38	40.6 QP	46.0	-5.4	1.24 H	94	44.0	-3.4
6	938.01	39.5 QP	46.0	-6.5	1.24 H	13	39.0	0.5
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	30.00	34.6 QP	40.0	-5.4	1.24 V	209	50.6	-16.0
2	97.81	31.6 QP	43.5	-11.9	1.24 V	92	50.3	-18.7
3	167.67	28.4 QP	43.5	-15.1	1.00 V	175	42.2	-13.8
4	400.52	27.6 QP	46.0	-18.4	1.00 V	25	38.0	-10.4
5	716.80	37.5 QP	46.0	-8.5	1.49 V	38	41.3	-3.8
6	949.65	35.4 QP	46.0	-10.6	2.00 V	12	34.7	0.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1.The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
Test Receiver ROHDE & SCHWARZ	ESCI	100613	Nov. 21, 2016	Nov. 20, 2017
RF signal cable (with 10dB PAD) Woken	5D-FB	Cable-cond1-01	Dec. 22, 2016	Dec. 21, 2017
LISN ROHDE & SCHWARZ (EUT)	ESH3-Z5	835239/001	Mar. 10, 2017	Mar. 09, 2018
LISN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100311	Aug. 15, 2017	Aug. 14, 2018
Software ADT	BV ADT_Cond_ V7.3.7.3	NA	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Shielded Room 1.
3. The VCCI Site Registration No. is C-2040.

4.2.3 Test Procedures

a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.

b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.

c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

4.2.4 Deviation from Test Standard

No deviation.

4.2.5 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT Operating Conditions

Same as 4.1.6.

4.2.7 Test Results

Worst-case data: 802.11b

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)

No	Freq.	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16569	10.45	37.85	22.38	48.30	32.83	65.17	55.17	-16.87	-22.34
2	0.22038	10.46	25.24	13.55	35.70	24.01	62.80	52.80	-27.10	-28.79
3	0.44325	10.51	34.21	26.31	44.72	36.82	57.00	47.00	-12.28	-10.18
4	1.25687	10.49	28.24	23.59	38.73	34.08	56.00	46.00	-17.27	-11.92
5	2.32787	10.54	31.85	25.25	42.39	35.79	56.00	46.00	-13.61	-10.21
6	20.70878	11.45	26.26	19.74	37.71	31.19	60.00	50.00	-22.29	-18.81

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.



Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)

No	Freq.	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16569	10.21	31.24	17.35	41.45	27.56	65.17	55.17	-23.72	-27.61
2	0.36114	10.23	23.14	15.30	33.37	25.53	58.70	48.70	-25.33	-23.17
3	**0.45097**	**10.24**	**34.26**	**27.63**	**44.50**	**37.87**	**56.86**	**46.86**	**-12.36**	**-8.99**
4	1.85142	10.31	30.23	23.84	40.54	34.15	56.00	46.00	-15.46	-11.85
5	2.12455	10.32	31.45	24.23	41.77	34.55	56.00	46.00	-14.23	-11.45
6	20.21612	11.06	23.13	16.72	34.19	27.78	60.00	50.00	-25.81	-22.22

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.



4.3 6dB Bandwidth Measurement

4.3.1 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 Test Setup



4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.3.4 Test Procedure

a. Set resolution bandwidth (RBW) = 100kHz.

b. Set the video bandwidth (VBW) ≥ 3 x RBW, Detector = average.

c. Trace mode = max hold.

d. Sweep = auto couple.

e. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

4.3.5 Deviation fromTest Standard

No deviation.

4.3.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 Test Result

802.11b

Channel	Frequency (MHz)	6dB Bandwidth (MHz)				Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3		
1	2412	9.09	9.07	8.59	9.03	0.5	Pass
6	2437	9.07	9.08	9.07	9.11	0.5	Pass
11	2462	8.59	8.11	8.58	8.60	0.5	Pass

802.11g

Channel	Frequency (MHz)	6dB Bandwidth (MHz)				Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3		
1	2412	16.43	16.43	16.40	16.41	0.5	Pass
6	2437	16.40	16.40	16.38	16.37	0.5	Pass
11	2462	16.42	16.41	16.41	16.40	0.5	Pass

802.11n (HT20)

Channel	Frequency (MHz)	6dB Bandwidth (MHz)				Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3		
1	2412	17.69	17.69	17.67	17.69	0.5	Pass
6	2437	17.62	17.63	17.65	17.63	0.5	Pass
11	2462	17.65	17.69	17.65	17.65	0.5	Pass

802.11n (HT40)

Channel	Frequency (MHz)	6dB Bandwidth (MHz)				Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3		
3	2422	36.46	36.48	36.46	36.44	0.5	Pass
6	2437	36.37	36.39	36.37	36.10	0.5	Pass
9	2452	36.08	35.86	35.85	35.85	0.5	Pass

Spectrum Plot of Worst Value

802.11b



802.11g



802.11n (HT20)



802.11n (HT40)



4.4 Conducted Output Power Measurement

4.4.1 Limits of Conducted Output Power Measurement

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

Per KDB 662911 D01 Multiple Transmitter Output Method of conducted output power measurement on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$;
Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any N_{ANT};
Array Gain = 5 log(N_{ANT}/N_{SS}) dB or 3 dB, whichever is less for 20-MHz channel widths with $N_{ANT} \geq 5$.

For power measurements on all other devices: Array Gain = 10 log(N_{ANT}/N_{SS}) dB.

4.4.2 Test Setup



4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.4.4 Test Procedures

An average power sensor was used on the output port of the EUT. A power meter was used to read the response of the average power sensor. Record the power level.

4.4.5 Deviation from Test Standard

No deviation.

4.4.6 EUT Operating Conditions

Same as item 4.3.6.

4.4.7 Test Results

CDD Mode

802.11b

Channel	Frequency (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
1	2412	16.62	16.90	16.84	17.22	195.927	22.92	30.00	Pass
6	2437	22.58	22.68	22.59	23.30	**761.835**	28.82	30.00	Pass
11	2462	15.92	16.40	16.16	16.27	166.405	22.21	30.00	Pass

802.11g

Channel	Frequency (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
1	2412	12.44	12.91	12.64	12.68	73.982	18.69	30.00	Pass
6	2437	20.92	21.34	21.22	21.58	536.053	27.29	30.00	Pass
11	2462	14.57	15.20	14.98	15.06	125.295	20.98	30.00	Pass

802.11n (HT20)

Channel	Frequency (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
1	2412	12.79	13.45	13.22	13.09	82.501	19.16	30.00	Pass
6	2437	20.50	20.79	20.78	21.14	481.843	26.83	30.00	Pass
11	2462	13.46	14.10	13.88	13.89	96.811	19.86	30.00	Pass

802.11n (HT40)

Channel	Frequency (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
3	2422	10.89	12.05	11.85	11.30	57.107	17.57	30.00	Pass
6	2437	13.23	14.17	14.25	13.67	97.048	19.87	30.00	Pass
9	2452	14.33	15.27	15.18	14.70	123.226	20.91	30.00	Pass

Beamforming Mode

802.11n (HT20)

Channel	Frequency (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
1	2412	6.77	7.43	7.20	7.07	20.606	13.14	24.98	Pass
6	2437	14.48	14.77	14.76	15.12	**120.504**	20.81	24.98	Pass
11	2462	7.44	8.08	7.86	7.87	24.210	13.84	24.98	Pass

Note: Directional gain = 5dBi + 10log(4) = 11.02dBi > 6dBi, so the power limit shall be reduced to 30-(11.02-6) = 24.98dBm.

802.11n (HT40)

Channel	Frequency (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
3	2422	4.87	6.03	5.83	5.28	14.289	11.55	24.98	Pass
6	2437	7.21	8.15	8.23	7.65	24.266	13.85	24.98	Pass
9	2452	8.31	9.25	9.16	8.68	30.832	14.89	24.98	Pass

Note: Directional gain = 5dBi + 10log(4) = 11.02dBi > 6dBi, so the power limit shall be reduced to 30-(11.02-6) = 24.98dBm.

4.5 Power Spectral Density Measurement

4.5.1 Limits of Power Spectral Density Measurement

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 Test Setup



4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.5.4 Test Procedure

For Average Power (Duty cycle ≥ 98%)

a. Set instrument center frequency to DTS channel center frequency.

b. Set span to at least 1.5 times the OBW.

c. Set RBW to: 3 kHz ≤ RBW ≤ 100 kHz.

d. Set VBW ≥3 x RBW.

e. Detector = power averaging (RMS) or sample detector (when RMS not available).

f. Ensure that the number of measurement points in the sweep ≥ 2 x span/RBW.

g. Sweep time = auto couple.

h. Employ trace averaging (RMS) mode over a minimum of 100 traces.

i. Use the peak marker function to determine the maximum amplitude level.

For Average Power (Duty cycle < 98%)

a. Measure the duty cycle (x).

b. Set instrument center frequency to DTS channel center frequency.

c. Set span to at least 1.5 times the OBW.

d. Set RBW to: 3 kHz ≤ RBW ≤ 100 kHz.

e. Set VBW ≥3 x RBW.

f. Detector = power averaging (RMS) or sample detector (when RMS not available).

g. Ensure that the number of measurement points in the sweep ≥ 2 x span/RBW.

h. Sweep time = auto couple.

i. Do not use sweep triggering. Allow sweep to “free run”.

j. Employ trace averaging (RMS) mode over a minimum of 100 traces.

k. Use the peak marker function to determine the maximum amplitude level.

l. Add 10 log (1/x), where x is the duty cycle measured in step (a, to the measured PSD to compute the average PSD during the actual transmission time.

4.5.5 Deviation from Test Standard

No deviation.

4.5.6 EUT Operating Condition

Same as item 4.3.6

4.5.7 Test Results

802.11b

TX chain	Channel	Frequency (MHz)	PSD (dBm/10kHz)	10 log (N=4) dB	Total PSD (dBm/10kHz)	Limit (dBm/3kHz)	Pass / Fail
0	1	2412	-12.09	6.02	-6.07	2.98	Pass
	6	2437	-6.07	6.02	-0.05	2.98	Pass
	11	2462	-12.94	6.02	-6.92	2.98	Pass
1	1	2412	-10.95	6.02	-4.93	2.98	Pass
	6	2437	-5.36	6.02	0.66	2.98	Pass
	11	2462	-12.09	6.02	-6.07	2.98	Pass
2	1	2412	-10.96	6.02	-4.94	2.98	Pass
	6	2437	-5.32	6.02	0.70	2.98	Pass
	11	2462	-11.21	6.02	-5.19	2.98	Pass
3	1	2412	-11.29	6.02	-5.27	2.98	Pass
	6	2437	-5.26	6.02	0.76	2.98	Pass
	11	2462	-12.23	6.02	-6.21	2.98	Pass

Note:

1. Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
2. Directional gain = 5dBi + 10log(4) = 11.02dBi > 6dBi, so the power density limit shall be reduced to 8-(11.02-6) = 2.98dBm.

802.11g

TX chain	Channel	Frequency (MHz)	PSD (dBm/10kHz)	10 log (N=4) dB	Total PSD (dBm/10kHz)	Limit (dBm/3kHz)	Pass / Fail
0	1	2412	-18.95	6.02	-12.93	2.98	Pass
	6	2437	-10.28	6.02	-4.26	2.98	Pass
	11	2462	-16.57	6.02	-10.55	2.98	Pass
1	1	2412	-17.02	6.02	-11.00	2.98	Pass
	6	2437	-9.07	6.02	-3.05	2.98	Pass
	11	2462	-15.00	6.02	-8.98	2.98	Pass
2	1	2412	-18.03	6.02	-12.01	2.98	Pass
	6	2437	-9.13	6.02	-3.11	2.98	Pass
	11	2462	-14.58	6.02	-8.56	2.98	Pass
3	1	2412	-18.01	6.02	-11.99	2.98	Pass
	6	2437	-8.88	6.02	-2.86	2.98	Pass
	11	2462	-15.26	6.02	-9.24	2.98	Pass

Note:

1. Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
2. Directional gain = 5dBi + 10log(4) = 11.02dBi > 6dBi, so the power density limit shall be reduced to 8-(11.02-6) = 2.98dBm.

802.11n (HT20)

TX chain	Channel	Frequency (MHz)	PSD (dBm/10kHz)	10 log (N=4) dB	Total PSD (dBm/10kHz)	Limit (dBm/3kHz)	Pass / Fail
0	1	2412	-16.82	6.02	-10.80	2.98	Pass
	6	2437	-11.11	6.02	-5.09	2.98	Pass
	11	2462	-17.08	6.02	-11.06	2.98	Pass
1	1	2412	-17.81	6.02	-11.79	2.98	Pass
	6	2437	-10.28	6.02	-4.26	2.98	Pass
	11	2462	-16.93	6.02	-10.91	2.98	Pass
2	1	2412	-18.24	6.02	-12.22	2.98	Pass
	6	2437	-10.46	6.02	-4.44	2.98	Pass
	11	2462	-17.17	6.02	-11.15	2.98	Pass
3	1	2412	-18.05	6.02	-12.03	2.98	Pass
	6	2437	-10.25	6.02	-4.23	2.98	Pass
	11	2462	-15.30	6.02	-9.28	2.98	Pass

Note:

1. Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
2. Directional gain = 5dBi + 10log(4) = 11.02dBi > 6dBi, so the power density limit shall be reduced to 8-(11.02-6) = 2.98dBm.

802.11n (HT40)

TX chain	Channel	Frequency (MHz)	PSD w/o Duty Factor (dBm/10kHz)	10 log (N=4) dB	Duty Factor (dB)	Total PSD With Duty Factor (dBm/10kHz)	Limit (dBm/3kHz)	Pass / Fail
0	3	2422	-24.65	6.02	0.19	-18.44	2.98	Pass
	6	2437	-21.99	6.02	0.19	-15.78	2.98	Pass
	9	2452	-20.75	6.02	0.19	-14.54	2.98	Pass
1	3	2422	-23.80	6.02	0.19	-17.59	2.98	Pass
	6	2437	-20.22	6.02	0.19	-14.01	2.98	Pass
	9	2452	-19.16	6.02	0.19	-12.95	2.98	Pass
2	3	2422	-22.92	6.02	0.19	-16.71	2.98	Pass
	6	2437	-20.85	6.02	0.19	-14.64	2.98	Pass
	9	2452	-19.32	6.02	0.19	-13.11	2.98	Pass
3	3	2422	-23.73	6.02	0.19	-17.52	2.98	Pass
	6	2437	-20.95	6.02	0.19	-14.74	2.98	Pass
	9	2452	-19.86	6.02	0.19	-13.65	2.98	Pass

Note:

1. Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
2. Directional gain = 5dBi + 10log(4) = 11.02dBi > 6dBi, so the power density limit shall be reduced to 8-(11.02-6) = 2.98dBm.
3. Refer to section 3.3 for duty cycle spectrum plot.

Spectrum Plot of Worst Value

802.11b



802.11g



802.11n (HT20)



802.11n (HT40)



4.6 Conducted Out of Band Emission Measurement

4.6.1 Limits of Conducted Out of Band Emission Measurement

Below 30dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 Test Setup



4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.6.4 Test Procedure

MEASUREMENT PROCEDURE REF

a. Set the RBW = 100 kHz.
b. Set the VBW ≥ 300 kHz.
c. Detector = average.
d. Sweep time = auto couple.
e. Trace mode = max hold.
f. Allow trace to fully stabilize.
g. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOBE

a. Set RBW = 100 kHz.
b. Set VBW ≥ 300 kHz.
c. Detector = average.
d. Sweep = auto couple.
e. Trace Mode = max hold.
f. Allow trace to fully stabilize.
g. Use the peak marker function to determine the maximum amplitude level.

4.6.5 Deviation from Test Standard

No deviation.

4.6.6 EUT Operating Condition

Same as item 4.3.6

4.6.7 Test Results

The conducted emission test is performed on each TX port of operating mode without summing or adding 10log (N) since the limit is relative emission limit.
The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 30dB offset below D1. It shows compliance with the requirement.

802.11b_Chain 0

CH 1





CH 6





CH 11





CH 1 Band edge



CH 11 Band edge



802.11b_Chain 1

CH 1





CH 6





CH 11





CH 1 Band edge



CH 11 Band edge



802.11b_Chain 2

CH 1





CH 6





CH 11





CH 1 Band edge



CH 11 Band edge



802.11b_Chain 3

CH 1





CH 6





CH 11





CH 1 Band edge



CH 11 Band edge



802.11g_Chain 0

CH 1





CH 6





CH 11





CH 1 Band edge



CH 11 Band edge



802.11g_Chain 1

CH 1





CH 6





CH 11





CH 1 Band edge



CH 11 Band edge



802.11g_Chain 2

CH 1





CH 6





CH 11





CH 1 Band edge



CH 11 Band edge



802.11g_Chain 3

CH 1





CH 6





CH 11





CH 1 Band edge



CH 11 Band edge



802.11n (HT20)_Chain 0

CH 1





CH 6





CH 11





CH 1 Band edge



CH 11 Band edge



802.11n (HT20)_Chain 1

CH 1





CH 6





CH 11





CH 1 Band edge



CH 11 Band edge



802.11n (HT20)_Chain 2

CH 1





CH 6





CH 11





CH 1 Band edge



CH 11 Band edge



802.11n (HT20)_Chain 3

CH 1





CH 6





CH 11





CH 1 Band edge



CH 11 Band edge



802.11n (HT40)_Chain 0

CH 3





CH 6





CH 9





CH 3 Band edge



CH 9 Band edge



802.11n (HT40)_Chain 1

CH 3





CH 6





CH 9





CH 3 Band edge



CH 9 Band edge



802.11n (HT40)_Chain 2

CH 3





CH 6





CH 9





CH 3 Band edge



CH 9 Band edge



802.11n (HT40)_Chain 3

CH 3





CH 6





CH 9





CH 3 Band edge



CH 9 Band edge



5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab
Tel: 886-2-26052180
Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab
Tel: 886-3-6668565
Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab
Tel: 886-3-3183232
Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com
Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---