

## FCC Test Report

**Report No.:** RFBDYS-WTW-P20110362A

**FCC ID:** TVE-3617T01066

**Test Model:** FAP-234F

**Series Model:** FortiAP 234Fxxxxxx, FAP-234Fxxxxxx, FORTIAP-234Fxxxxxx (Where "x" can be used as "A-Z", or "0-9", or "-", or blank for software changes or marketing purposes only)

**Received Date:** Nov. 11, 2020

**Test Date:** Dec. 31, 2020 ~ Mar. 08, 2021

**Issued Date:** Mar. 22, 2021

**Applicant:** Fortinet Inc.

**Address:** 899 Kifer Road Sunnyvale, CA 94086 USA

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch  
Lin Kou Laboratories

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

**Test Location:** No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City  
33383, TAIWAN

**FCC Registration /** 788550 / TW0003  
**Designation Number:**



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

## Table of Contents

|                                                             |           |
|-------------------------------------------------------------|-----------|
| <b>Release Control Record</b>                               | <b>4</b>  |
| <b>1 Certificate of Conformity</b>                          | <b>5</b>  |
| <b>2 Summary of Test Results</b>                            | <b>6</b>  |
| 2.1 Measurement Uncertainty                                 | 6         |
| 2.2 Modification Record                                     | 6         |
| <b>3 General Information</b>                                | <b>7</b>  |
| 3.1 General Description of EUT                              | 7         |
| 3.2 Description of Test Modes                               | 11        |
| 3.2.1 Test Mode Applicability and Tested Channel Detail     | 12        |
| 3.3 Duty Cycle of Test Signal                               | 16        |
| 3.4 Description of Support Units                            | 18        |
| 3.4.1 Configuration of System under Test                    | 18        |
| 3.5 General Description of Applied Standards and References | 19        |
| <b>4 Test Types and Results</b>                             | <b>20</b> |
| 4.1 Radiated Emission and Bandedge Measurement              | 20        |
| 4.1.1 Limits of Radiated Emission and Bandedge Measurement  | 20        |
| 4.1.2 Test Instruments                                      | 21        |
| 4.1.3 Test Procedures                                       | 22        |
| 4.1.4 Deviation from Test Standard                          | 23        |
| 4.1.5 Test Setup                                            | 23        |
| 4.1.6 EUT Operating Conditions                              | 24        |
| 4.1.7 Test Results                                          | 25        |
| 4.2 Conducted Emission Measurement                          | 77        |
| 4.2.1 Limits of Conducted Emission Measurement              | 77        |
| 4.2.2 Test Instruments                                      | 77        |
| 4.2.3 Test Procedures                                       | 78        |
| 4.2.4 Deviation from Test Standard                          | 78        |
| 4.2.5 Test Setup                                            | 78        |
| 4.2.6 EUT Operating Conditions                              | 78        |
| 4.2.7 Test Results                                          | 79        |
| 4.3 Transmit Power Measurement                              | 83        |
| 4.3.1 Limits of Transmit Power Measurement                  | 83        |
| 4.3.2 Test Setup                                            | 83        |
| 4.3.3 Test Instruments                                      | 83        |
| 4.3.4 Test Procedure                                        | 84        |
| 4.3.5 Deviation from Test Standard                          | 84        |
| 4.3.6 EUT Operating Conditions                              | 84        |
| 4.3.7 Test Result                                           | 85        |
| 4.4 Occupied Bandwidth Measurement                          | 120       |
| 4.4.1 Test Setup                                            | 120       |
| 4.4.2 Test Instruments                                      | 120       |
| 4.4.3 Test Procedure                                        | 120       |
| 4.4.4 Test Result                                           | 121       |
| 4.5 Peak Power Spectral Density Measurement                 | 127       |
| 4.5.1 Limits of Peak Power Spectral Density Measurement     | 127       |
| 4.5.2 Test Setup                                            | 127       |
| 4.5.3 Test Instruments                                      | 127       |
| 4.5.4 Test Procedures                                       | 127       |
| 4.5.5 Deviation from Test Standard                          | 128       |
| 4.5.6 EUT Operating Conditions                              | 128       |
| 4.5.7 Test Results                                          | 129       |
| 4.6 Frequency Stability                                     | 138       |
| 4.6.1 Limits of Frequency Stability Measurement             | 138       |

|                                                                 |            |
|-----------------------------------------------------------------|------------|
| 4.6.2 Test Setup .....                                          | 138        |
| 4.6.3 Test Instruments .....                                    | 138        |
| 4.6.4 Test Procedure .....                                      | 138        |
| 4.6.5 Deviation from Test Standard .....                        | 139        |
| 4.6.6 EUT Operating Condition .....                             | 139        |
| 4.6.7 Test Results .....                                        | 139        |
| 4.7 6dB Bandwidth Measurement .....                             | 141        |
| 4.7.1 Limits of 6dB Bandwidth Measurement .....                 | 141        |
| 4.7.2 Test Setup .....                                          | 141        |
| 4.7.3 Test Instruments .....                                    | 141        |
| 4.7.4 Test Procedure .....                                      | 141        |
| 4.7.5 Deviation from Test Standard .....                        | 141        |
| 4.7.6 EUT Operating Condition .....                             | 141        |
| 4.7.7 Test Results .....                                        | 142        |
| <b>5 Pictures of Test Arrangements .....</b>                    | <b>146</b> |
| <b>Annex A - Band Edge Measurement .....</b>                    | <b>147</b> |
| <b>Appendix – Information of the Testing Laboratories .....</b> | <b>166</b> |

### Release Control Record

| Issue No.             | Description      | Date Issued   |
|-----------------------|------------------|---------------|
| RFBDYS-WTW-P20110362A | Original release | Mar. 22, 2021 |

## 1 Certificate of Conformity

**Product:** Secured Wireless Access Point

**Brand:** Fortinet

**Test Model:** FAP-234F

**Series Model:** FortiAP 234Fxxxxxx, FAP-234Fxxxxxx, FORTIAP-234Fxxxxxx (Where "x" can be used as "A-Z", or "0-9", or "-", or blank for software changes or marketing purposes only)

**Sample Status:** Engineering sample

**Applicant:** Fortinet Inc.

**Test Date:** Dec. 31, 2020 ~ Mar. 08, 2021

**Standards:** 47 CFR FCC Part 15, Subpart E (Section 15.407)  
ANSI C63.10:2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

**Prepared by :** Celine Chou , **Date:** Mar. 22, 2021  
Celine Chou / Senior Specialist

**Approved by :** Bruce Chen , **Date:** Mar. 22, 2021  
Bruce Chen / Senior Project Engineer

## 2 Summary of Test Results

| 47 CFR FCC Part 15, Subpart E (Section 15.407) |                                            |        |                                                                                              |
|------------------------------------------------|--------------------------------------------|--------|----------------------------------------------------------------------------------------------|
| FCC Clause                                     | Test Item                                  | Result | Remarks                                                                                      |
| 15.407(b)(8)                                   | AC Power Conducted Emissions               | Pass   | Meet the requirement of limit.<br>Minimum passing margin is -4.21dB at 0.47400MHz.           |
| 15.407(b)<br>(1/2/3/4(i/ii)/8)                 | Radiated Emissions & Band Edge Measurement | Pass   | Meet the requirement of limit.<br>Minimum passing margin is -0.4dB at 60.93MHz and 59.92MHz. |
| 15.407(a)(1/2/3)                               | Max Average Transmit Power                 | Pass   | Meet the requirement of limit.                                                               |
| ---                                            | Occupied Bandwidth Measurement             | -      | Reference only.                                                                              |
| 15.407(a)(1/2/3)                               | Peak Power Spectral Density                | Pass   | Meet the requirement of limit.                                                               |
| 15.407(e)                                      | 6dB bandwidth                              | Pass   | Meet the requirement of limit.<br>(U-NII-3 Band only)                                        |
| 15.407(g)                                      | Frequency Stability                        | Pass   | Meet the requirement of limit.                                                               |
| 15.203                                         | Antenna Requirement                        | Pass   | Antenna connector is IPEX not a standard connector.                                          |

Note:

- For U-NII-2A, U-NII-2C band compliance with rule 15.407(b) of the band-edge items, the test plots were recorded in Annex A. Test Procedures refer to report 4.1.3.
- Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

### 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

| Measurement                        | Frequency        | Expanded Uncertainty (k=2) (±) |
|------------------------------------|------------------|--------------------------------|
| Conducted Emissions at mains ports | 150kHz ~ 30MHz   | 2.79 dB                        |
| Radiated Emissions up to 1 GHz     | 9kHz ~ 30MHz     | 3.04 dB                        |
|                                    | 30MHz ~ 200MHz   | 3.86 dB                        |
|                                    | 200MHz ~ 1000MHz | 3.87 dB                        |
| Radiated Emissions above 1 GHz     | 1GHz ~ 18GHz     | 2.29 dB                        |
|                                    | 18GHz ~ 40GHz    | 2.29 dB                        |

### 2.2 Modification Record

There were no modifications required for compliance.

### 3 General Information

#### 3.1 General Description of EUT

|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product               | Secured Wireless Access Point                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Brand                 | Fortinet                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Test Model            | FAP-234F                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Series Model          | FortiAP 234Fxxxxxx, FAP-234Fxxxxxx, FORTIAP-234Fxxxxxx (Where "x" can be used as "A-Z", or "0-9", or "-", or blank for software changes or marketing purposes only)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Model Difference      | Refer to note                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Sample Status         | Engineering sample                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Power Supply Rating   | 54Vdc from POE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Modulation Type       | 256QAM, 64QAM, 16QAM, QPSK, BPSK for OFDM<br>1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK for OFDMA                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Modulation Technology | OFDM, OFDMA                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Transfer Rate         | 802.11a: 54/48/36/24/18/12/9/6Mbps<br>802.11n (HT20/40): up to MCS7<br>802.11ac (VHT20/40): up to MCS9<br>802.11ax: up to MCS11                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Operating Frequency   | 5260 ~ 5320MHz, 5500 ~ 5720MHz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Number of Channel     | <b>5G traffic radio (Radio 2):</b><br>5260 ~ 5320MHz:<br>802.11a, 802.11n (HT20), 802.11ac (VHT20), 802.11ax (HE20): 4<br>802.11n (HT40), 802.11ac (VHT40), 802.11ax (HE40): 2<br>802.11ac (VHT80), 802.11ax (HE80): 1<br>5500 ~ 5720MHz:<br>802.11a, 802.11n (HT20), 802.11ac (VHT20), 802.11ax (HE20): 12<br>802.11n (HT40), 802.11ac (VHT40), 802.11ax (HE40): 6<br>802.11ac (VHT80), 802.11ax (HE80): 3<br><b>Scanning radio (Radio 3):</b><br>802.11a, 802.11n (HT20), 802.11ac (VHT20): 4<br>802.11n (HT40), 802.11ac (VHT40): 2<br>802.11ac (VHT80): 1<br>5500 ~ 5720MHz:<br>802.11a, 802.11n (HT20), 802.11ac (VHT20): 12<br>802.11n (HT40), 802.11ac (VHT40): 6<br>802.11ac (VHT80): 3 |

|                   |                                                                                                                                                                                                                                                                                                 |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Output Power      | <b>5G traffic radio (Radio 2):</b><br>CDD Mode:<br>5260 ~ 5320MHz: 95.177mW<br>5500 ~ 5720MHz: 94.147mW<br>Beamforming Mode:<br>5260 ~ 5320MHz: 47.592mW<br>5500 ~ 5720MHz: 47.077mW<br><b>Scanning radio (Radio 3):</b><br>CDD Mode:<br>5260 ~ 5320MHz: 138.995mW<br>5500 ~ 5720MHz: 112.980mW |
| Antenna Type      | Refer to note                                                                                                                                                                                                                                                                                   |
| Antenna Connector | Refer to note                                                                                                                                                                                                                                                                                   |
| Accessory Device  | POE                                                                                                                                                                                                                                                                                             |
| Cable Supplied    | NA                                                                                                                                                                                                                                                                                              |

**Note:**

1. This report is prepared for FCC class II permissive change. The difference compared with the original report (BV CPS report no.: RFBDYS-WTW-P20110362-1) is adding 5.26GHz to 5.32GHz and 5.50GHz to 5.72GHz by software.
2. The following models are provided to this EUT. The model FAP-234F was chosen for final test.

| Brand    | Model                                                                                                                                                               | Description                        |
|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------|
| Fortinet | FAP-234F                                                                                                                                                            | Series model for marketing purpose |
|          | FortiAP 234Fxxxxxx, FAP-234Fxxxxxx, FORTIAP-234Fxxxxxx (Where "x" can be used as "A-Z", or "0-9", or "-", or blank for software changes or marketing purposes only) |                                    |

3. The EUT incorporates a MIMO function. Physically, the EUT provides 2 completed transmitters and 2 receivers.

| Radio                         | Modulation Mode  | Beamforming Mode | TX Function |
|-------------------------------|------------------|------------------|-------------|
| 5G traffic radio<br>(Radio 2) | 802.11a          | Not Support      | 2TX         |
|                               | 802.11n (HT20)   | Not Support      | 2TX         |
|                               | 802.11n (HT40)   | Not Support      | 2TX         |
|                               | 802.11ac (VHT20) | Support          | 2TX         |
|                               | 802.11ac (VHT40) | Support          | 2TX         |
|                               | 802.11ac (VHT80) | Support          | 2TX         |
|                               | 802.11ax (HE20)  | Support          | 2TX         |
|                               | 802.11ax (HE40)  | Support          | 2TX         |
|                               | 802.11ax (HE80)  | Support          | 2TX         |
| Scanning radio<br>(Radio 3)   | 802.11a          | Not Support      | 1TX         |
|                               | 802.11n (HT20)   | Not Support      | 1TX         |
|                               | 802.11n (HT40)   | Not Support      | 1TX         |
|                               | 802.11ac (VHT20) | Not Support      | 1TX         |
|                               | 802.11ac (VHT40) | Not Support      | 1TX         |
|                               | 802.11ac (VHT80) | Not Support      | 1TX         |

\* The bandwidth and modulation are similar for HT20/HT40 on 802.11n mode and VHT20/VHT40/VHT80 on 802.11ac mode and HE20/HE40/HE80 on 802.11ax mode. Therefore the investigated worst case is the representative mode in test report. (Final test mode refer section 3.2.1)

\* For 802.11n, CDD mode and Beamforming mode are presented in power output test item. For other test items, CDD mode is the worst case for final tests after pretesting.

4. The EUT consumes power from the following POEs.

| POE 1        |                           |
|--------------|---------------------------|
| Brand        | SENAO                     |
| Model        | EPA5006GPR                |
| Input Power  | 100-240Vac, 50-60Hz, 0.8A |
| Output Power | 54Vdc, 0.6A               |

| POE 2 (Optional) |                           |
|------------------|---------------------------|
| Brand            | SENAO                     |
| Model            | EPA5006GP                 |
| Input Power      | 100-240Vac, 50-60Hz, 0.8A |
| Output Power     | 54Vdc, 0.6A               |

5. The following antennas were provided to the EUT.

| No. | Type        | Connector | Gain (dBi) |         |         |         |         |         | Remark                     |
|-----|-------------|-----------|------------|---------|---------|---------|---------|---------|----------------------------|
|     |             |           | 2400MHz    | 2450MHz | 2500MHz | 5150MHz | 5500MHz | 5850MHz |                            |
| 1   | Patch Array | IPEX      | 9.47       | 10.20   | 10.16   | -       | -       | -       | 2G traffic radio (Radio 1) |
| 2   | Patch Array | IPEX      | 9.24       | 10.25   | 9.73    | -       | -       | -       |                            |
| 3   | Patch Array | IPEX      | -          | -       | -       | 9.75    | 9.94    | 10.02   | 5G traffic radio (Radio 2) |
| 4   | Patch Array | IPEX      | -          | -       | -       | 9.81    | 10.17   | 10.02   |                            |
| 5   | Dipole      | IPEX      | 4.25       | 4.99    | 4.15    | -       | -       | -       | BT LE / Zigbee             |
| 6   | Dipole      | IPEX      | 3.38       | 3.38    | 3.84    | 4.92    | 4.54    | 4.80    | Scanning radio (Radio 3)   |

\* The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

6. The simultaneous operation mode was determined by client.

| No | Mode                                                                                             |
|----|--------------------------------------------------------------------------------------------------|
| 1  | 2G traffic radio (Radio 1) + 5GHz traffic radio (Radio 2) + 5G Scanning radio (Radio 3) + BLE    |
| 2  | 2G traffic radio (Radio 1) + 5GHz traffic radio (Radio 2) + 5G Scanning radio (Radio 3) + Zigbee |
| 3  | 5GHz traffic radio (Radio 2) + 2G Scanning radio (Radio 3) + BLE                                 |
| 4  | 5GHz traffic radio (Radio 2) + 2G Scanning radio (Radio 3) + Zigbee                              |

\* 5GHz traffic radio (Radio 2) and 5G Scanning radio (Radio 3) cannot transmit in the same band at same time. 2G traffic radio (Radio 1) and 2G Scanning radio (Radio 3) cannot transmit at same time.

\* Zigbee and BT technologies cannot transmit at same time.

\* Spurious emission of the simultaneous operation has been evaluated and no non-compliance was found.

### 3.2 Description of Test Modes

For 5260 ~ 5320MHz:

4 channels are provided for 802.11a, 802.11n (HT20), 802.11ac (VHT20), 802.11ax (HE20):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 52      | 5260 MHz  | 60      | 5300 MHz  |
| 56      | 5280 MHz  | 64      | 5320 MHz  |

2 channels are provided for 802.11n (HT40), 802.11ac (VHT40), 802.11ax (HE40):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 54      | 5270 MHz  | 62      | 5310 MHz  |

1 channel is provided for 802.11ac (VHT80), 802.11ax (HE80):

| Channel | Frequency |
|---------|-----------|
| 58      | 5290MHz   |

For 5500 ~ 5720MHz:

12 channels are provided for 802.11a, 802.11n (HT20), 802.11ac (VHT20), 802.11ax (HE20):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 100     | 5500 MHz  | 124     | 5620 MHz  |
| 104     | 5520 MHz  | 128     | 5640 MHz  |
| 108     | 5540 MHz  | 132     | 5660 MHz  |
| 112     | 5560 MHz  | 136     | 5680 MHz  |
| 116     | 5580 MHz  | 140     | 5700 MHz  |
| 120     | 5600 MHz  | 144     | 5720 MHz  |

6 channels are provided for 802.11n (HT40), 802.11ac (VHT40), 802.11ax (HE40):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 102     | 5510 MHz  | 126     | 5630 MHz  |
| 110     | 5550 MHz  | 134     | 5670 MHz  |
| 118     | 5590 MHz  | 142     | 5710 MHz  |

3 channels are provided for 802.11ac (VHT80), 802.11ax (HE80):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 106     | 5530 MHz  | 122     | 5610 MHz  |
| 138     | 5690 MHz  |         |           |

### 3.2.1 Test Mode Applicability and Tested Channel Detail

| EUT Configure Mode | Applicable to |       |     |      | Description |
|--------------------|---------------|-------|-----|------|-------------|
|                    | RE $\geq$ 1G  | RE<1G | PLC | APCM |             |
| -                  | √             | √     | √   | √    | -           |

Where RE $\geq$ 1G: Radiated Emission above 1GHz & Bandedge Measurement

RE<1G: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

Note:

1. The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **Z-plane**.
2. Radiated emission test (below 1GHz) and power line conducted emission test items chosen the worst maximum power.

#### **Radiated Emission Test (Above 1GHz):**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT Configure Mode | Mode             | Frequency Band (MHz) | Available Channel | Tested Channel     | Modulation Technology | Data Rate (Mbps) | Remark  |
|--------------------|------------------|----------------------|-------------------|--------------------|-----------------------|------------------|---------|
| -                  | 802.11a          | 5260-5320            | 52 to 64          | 52, 60, 64         | OFDM                  | 6.0              | Radio 2 |
|                    | 802.11ax (HE20)  |                      | 52 to 64          | 52, 60, 64         | OFDMA                 | MCS0             |         |
|                    | 802.11ax (HE40)  |                      | 54 to 62          | 54, 62             | OFDMA                 | MCS0             |         |
|                    | 802.11ax (HE80)  |                      | 58                | 58                 | OFDMA                 | MCS0             |         |
| -                  | 802.11a          | 5500-5720            | 100 to 144        | 100, 116, 140, 144 | OFDM                  | 6.0              |         |
|                    | 802.11ax (HE20)  |                      | 100 to 144        | 100, 116, 140, 144 | OFDMA                 | MCS0             |         |
|                    | 802.11ax (HE40)  |                      | 102 to 142        | 102, 110, 134, 142 | OFDMA                 | MCS0             |         |
|                    | 802.11ax (HE80)  |                      | 106 to 138        | 106, 122, 138      | OFDMA                 | MCS0             |         |
| -                  | 802.11a          | 5260-5320            | 52 to 64          | 52, 60, 64         | OFDM                  | 6.0              | Radio 3 |
|                    | 802.11ac (VHT20) |                      | 52 to 64          | 52, 60, 64         | OFDM                  | 6.5              |         |
|                    | 802.11ac (VHT40) |                      | 54 to 62          | 54, 62             | OFDM                  | 13.5             |         |
|                    | 802.11ac (VHT80) |                      | 58                | 58                 | OFDM                  | 29.3             |         |
| -                  | 802.11a          | 5500-5720            | 100 to 144        | 100, 116, 140, 144 | OFDM                  | 6.0              |         |
|                    | 802.11ac (VHT20) |                      | 100 to 144        | 100, 116, 140, 144 | OFDM                  | 6.5              |         |
|                    | 802.11ac (VHT40) |                      | 102 to 142        | 102, 110, 134, 142 | OFDM                  | 13.5             |         |
|                    | 802.11ac (VHT80) |                      | 106 to 138        | 106, 122, 138      | OFDM                  | 29.3             |         |

### **Radiated Emission Test (Below 1GHz):**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT Configure Mode | Mode             | Frequency Band (MHz) | Available Channel | Tested Channel | Modulation Technology | Data Rate (Mbps) | Remark  |
|--------------------|------------------|----------------------|-------------------|----------------|-----------------------|------------------|---------|
| -                  | 802.11ax (HE20)  | 5260-5320            | 52 to 64          | 60             | OFDMA                 | MCS0             | Radio 2 |
| -                  | 802.11ax (HE20)  | 5500-5720            | 100 to 144        |                | OFDMA                 | MCS0             |         |
| -                  | 802.11ac (VHT20) | 5260-5320            | 52 to 64          | 60             | OFDM                  | 6.5              | Radio 3 |
| -                  | 802.11ac (VHT20) | 5500-5720            | 100 to 144        |                | OFDM                  | 6.5              |         |

### **Power Line Conducted Emission Test:**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT Configure Mode | Mode             | Frequency Band (MHz) | Available Channel | Tested Channel | Modulation Technology | Data Rate (Mbps) | Remark  |
|--------------------|------------------|----------------------|-------------------|----------------|-----------------------|------------------|---------|
| -                  | 802.11ax (HE20)  | 5260-5320            | 52 to 64          | 60             | OFDMA                 | MCS0             | Radio 2 |
| -                  | 802.11ax (HE20)  | 5500-5720            | 100 to 144        |                | OFDMA                 | MCS0             |         |
| -                  | 802.11ac (VHT20) | 5260-5320            | 52 to 64          | 60             | OFDM                  | 6.5              | Radio 3 |
| -                  | 802.11ac (VHT20) | 5500-5720            | 100 to 144        |                | OFDM                  | 6.5              |         |

### Antenna Port Conducted Measurement:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT Configure Mode | Mode             | Frequency Band (MHz) | Available Channel | Tested Channel     | Modulation Technology | Data Rate (Mbps) | Remark  |
|--------------------|------------------|----------------------|-------------------|--------------------|-----------------------|------------------|---------|
| -                  | 802.11a          | 5260-5320            | 52 to 64          | 52, 60, 64         | OFDM                  | 6.0              | Radio 2 |
|                    | 802.11n (HT20)   |                      | 52 to 64          | 52, 60, 64         | OFDM                  | 6.5              |         |
|                    | 802.11n (HT40)   |                      | 54 to 62          | 54, 62             | OFDM                  | 13.5             |         |
|                    | 802.11ac (VHT20) |                      | 52 to 64          | 52, 60, 64         | OFDM                  | 6.5              |         |
|                    | 802.11ac (VHT40) |                      | 54 to 62          | 54, 62             | OFDM                  | 13.5             |         |
|                    | 802.11ac (VHT80) |                      | 58                | 58                 | OFDM                  | 29.3             |         |
|                    | 802.11ax (HE20)  |                      | 52 to 64          | 52, 60, 64         | OFDMA                 | MCS0             |         |
|                    | 802.11ax (HE40)  |                      | 54 to 62          | 54, 62             | OFDMA                 | MCS0             |         |
|                    | 802.11ax (HE80)  |                      | 58                | 58                 | OFDMA                 | MCS0             |         |
| -                  | 802.11a          | 5500-5720            | 100 to 144        | 100, 116, 140, 144 | OFDM                  | 6.0              | Radio 2 |
|                    | 802.11n (HT20)   |                      | 100 to 144        | 100, 116, 140, 144 | OFDM                  | 6.5              |         |
|                    | 802.11n (HT40)   |                      | 102 to 142        | 102, 110, 134, 142 | OFDM                  | 13.5             |         |
|                    | 802.11ac (VHT20) |                      | 100 to 144        | 100, 116, 140, 144 | OFDM                  | 6.5              |         |
|                    | 802.11ac (VHT40) |                      | 102 to 142        | 102, 110, 134, 142 | OFDM                  | 13.5             |         |
|                    | 802.11ac (VHT80) |                      | 106 to 138        | 106, 122, 138      | OFDM                  | 29.3             |         |
|                    | 802.11ax (HE20)  |                      | 100 to 144        | 100, 116, 140, 144 | OFDMA                 | MCS0             |         |
|                    | 802.11ax (HE40)  |                      | 102 to 142        | 102, 110, 134, 142 | OFDMA                 | MCS0             |         |
|                    | 802.11ax (HE80)  |                      | 106 to 138        | 106, 122, 138      | OFDMA                 | MCS0             |         |
| -                  | 802.11a          | 5260-5320            | 52 to 64          | 52, 60, 64         | OFDM                  | 6.0              | Radio 3 |
|                    | 802.11n (HT20)   |                      | 52 to 64          | 52, 60, 64         | OFDM                  | 6.5              |         |
|                    | 802.11n (HT40)   |                      | 54 to 62          | 54, 62             | OFDM                  | 13.5             |         |
|                    | 802.11ac (VHT20) |                      | 52 to 64          | 52, 60, 64         | OFDM                  | 6.5              |         |
|                    | 802.11ac (VHT40) |                      | 54 to 62          | 54, 62             | OFDM                  | 13.5             |         |
|                    | 802.11ac (VHT80) |                      | 58                | 58                 | OFDM                  | 29.3             |         |
| -                  | 802.11a          | 5500-5720            | 100 to 144        | 100, 116, 140, 144 | OFDM                  | 6.0              | Radio 3 |
|                    | 802.11n (HT20)   |                      | 100 to 144        | 100, 116, 140, 144 | OFDM                  | 6.5              |         |
|                    | 802.11n (HT40)   |                      | 102 to 142        | 102, 110, 134, 142 | OFDM                  | 13.5             |         |
|                    | 802.11ac (VHT20) |                      | 100 to 144        | 100, 116, 140, 144 | OFDM                  | 6.5              |         |
|                    | 802.11ac (VHT40) |                      | 102 to 142        | 102, 110, 134, 142 | OFDM                  | 13.5             |         |
|                    | 802.11ac (VHT80) |                      | 106 to 138        | 106, 122, 138      | OFDM                  | 29.3             |         |

**Test Condition:**

| Applicable to | Environmental Conditions | Input Power | Tested by               |
|---------------|--------------------------|-------------|-------------------------|
| RE $\geq$ 1G  | 23 deg. C, 67% RH        | 54Vdc       | Edison Lee<br>Titan Hsu |
| RE<1G         | 23 deg. C, 66% RH        | 54Vdc       | Titan Hsu               |
| PLC           | 25 deg. C, 75% RH        | 54Vdc       | Rex Wang                |
| APCM          | 25 deg. C, 60% RH        | 54Vdc       | Jisyong Wang            |

### 3.3 Duty Cycle of Test Signal

#### 5G traffic radio (Radio 2)

Duty cycle of test signal is < 98%, duty factor is required.

802.11a: Duty cycle =  $1.430/1.560 = 0.917$ , Duty factor =  $10 * \log(1/0.917) = 0.38$

802.11ax (HE20): Duty cycle =  $5.425/5.885 = 0.922$ , Duty factor =  $10 * \log(1/0.922) = 0.35$

802.11ax (HE40): Duty cycle =  $5.435/6.515 = 0.834$ , Duty factor =  $10 * \log(1/0.834) = 0.79$

802.11ax (HE80): Duty cycle =  $5.420/5.860 = 0.925$ , Duty factor =  $10 * \log(1/0.925) = 0.34$



## Scanning radio (Radio 3)


Duty cycle of test signal is < 98%, duty factor is required.

802.11a: Duty cycle =  $2.020/2.137 = 0.945$ , Duty factor =  $10 * \log(1/0.945) = 0.24$

802.11ac (VHT20): Duty cycle =  $1.877/1.995 = 0.941$ , Duty factor =  $10 * \log(1/0.941) = 0.26$

802.11ac (VHT40): Duty cycle =  $0.921/1.048 = 0.879$ , Duty factor =  $10 * \log(1/0.879) = 0.56$

802.11ac (VHT80): Duty cycle =  $0.456/0.495 = 0.921$ , Duty factor =  $10 * \log(1/0.921) = 0.36$



### 3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.


| ID | Product  | Brand | Model No. | Serial No. | FCC ID           | Remarks |
|----|----------|-------|-----------|------------|------------------|---------|
| A. | Notebook | DELL  | E5410     | 1HC2XM1    | FCC DoC Approved | -       |
| B. | Load     | NA    | NA        | NA         | NA               | -       |

Note:

1. All power cords of the above support units are non-shielded (1.8m).
2. Item A acted as a communication partner to transfer data.

| ID | Descriptions | Qty. | Length (m) | Shielding (Yes/No) | Cores (Qty.) | Remarks     |
|----|--------------|------|------------|--------------------|--------------|-------------|
| 1. | LAN          | 1    | 1.5        | N                  | 0            | RJ45, Cat5e |
| 2. | LAN          | 1    | 1.5        | N                  | 0            | RJ45, Cat5e |
| 3. | LAN          | 1    | 7          | N                  | 0            | RJ45, Cat5e |
| 4. | LAN          | 1    | 1.5        | N                  | 0            | RJ45, Cat5e |

#### 3.4.1 Configuration of System under Test



### 3.5 General Description of Applied Standards and References

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards and references:

**Test standard:**

**FCC Part 15, Subpart E (15.407)**

ANSI C63.10:2013

All test items have been performed and recorded as per the above standards.

**References Test Guidance:**

**KDB 789033 D02 General UNII Test Procedure New Rules v02r01**

**KDB 662911 D01 Multiple Transmitter Output v02r01**

All test items have been performed as a reference to the above KDB test guidance.

## 4 Test Types and Results

### 4.1 Radiated Emission and Bandedge Measurement

#### 4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table.

| Frequencies (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009 ~ 0.490     | 2400/F(kHz)                       | 300                           |
| 0.490 ~ 1.705     | 24000/F(kHz)                      | 30                            |
| 1.705 ~ 30.0      | 30                                | 30                            |
| 30 ~ 88           | 100                               | 3                             |
| 88 ~ 216          | 150                               | 3                             |
| 216 ~ 960         | 200                               | 3                             |
| Above 960         | 500                               | 3                             |

Note:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

Limits of unwanted emission out of the restricted bands

| Applicable To                                                                                    |                                     |                  | Limit                                                                                                                                   |                                                                                                                                           |
|--------------------------------------------------------------------------------------------------|-------------------------------------|------------------|-----------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| 789033 D02 General UNII Test Procedure<br>New Rules v02r01                                       |                                     |                  | Field Strength at 3m                                                                                                                    |                                                                                                                                           |
|                                                                                                  |                                     |                  | PK: 74 (dBµV/m)                                                                                                                         | AV: 54 (dBµV/m)                                                                                                                           |
| Frequency Band                                                                                   | Applicable To                       |                  | EIRP Limit                                                                                                                              | Equivalent Field Strength at 3m                                                                                                           |
| 5150~5250 MHz                                                                                    | 15.407(b)(1)                        |                  | PK: -27 (dBm/MHz)                                                                                                                       | PK: 68.2(dBµV/m)                                                                                                                          |
| 5250~5350 MHz                                                                                    | 15.407(b)(2)                        |                  |                                                                                                                                         |                                                                                                                                           |
| 5470~5725 MHz                                                                                    | 15.407(b)(3)                        |                  |                                                                                                                                         |                                                                                                                                           |
| 5725~5850 MHz                                                                                    | <input checked="" type="checkbox"/> | 15.407(b)(4)(i)  | PK: -27 (dBm/MHz) <sup>*1</sup><br>PK: 10 (dBm/MHz) <sup>*2</sup><br>PK: 15.6 (dBm/MHz) <sup>*3</sup><br>PK: 27 (dBm/MHz) <sup>*4</sup> | PK: 68.2(dBµV/m) <sup>*1</sup><br>PK: 105.2 (dBµV/m) <sup>*2</sup><br>PK: 110.8(dBµV/m) <sup>*3</sup><br>PK: 122.2 (dBµV/m) <sup>*4</sup> |
|                                                                                                  | <input type="checkbox"/>            | 15.407(b)(4)(ii) | Emission limits in section 15.247(d)                                                                                                    |                                                                                                                                           |
| <sup>*1</sup> beyond 75 MHz or more above of the band edge.                                      |                                     |                  | <sup>*2</sup> below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above.                                                    |                                                                                                                                           |
| <sup>*3</sup> below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above. |                                     |                  | <sup>*4</sup> from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.                    |                                                                                                                                           |

Note: The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000 \sqrt{30P}}{3} \text{ } \mu\text{V/m, where P is the eirp (Watts).}$$

#### 4.1.2 Test Instruments

| Description & Manufacturer                | Model No.                             | Serial No.                                          | Cal. Date     | Cal. Due      |
|-------------------------------------------|---------------------------------------|-----------------------------------------------------|---------------|---------------|
| Test Receiver<br>ROHDE & SCHWARZ          | ESR3                                  | 102579                                              | Jul. 07, 2020 | Jul. 06, 2021 |
| Spectrum Analyzer<br>ROHDE & SCHWARZ      | FSP40                                 | 100269                                              | Jun. 09, 2020 | Jun. 08, 2021 |
| BILOG Antenna<br>SCHWARZBECK              | VULB9168                              | 9168-171                                            | Nov. 04, 2020 | Nov. 03, 2021 |
| HORN Antenna<br>SCHWARZBECK               | 9120D                                 | 209                                                 | Nov. 22, 2020 | Nov. 21, 2021 |
| HORN Antenna<br>SCHWARZBECK               | BBHA 9170                             | BBHA9170241                                         | Nov. 22, 2020 | Nov. 21, 2021 |
| Loop Antenna<br>TESEQ                     | HLA 6121                              | 45745                                               | Jul. 06, 2020 | Jul. 05, 2021 |
| Preamplifier<br>Agilent<br>(Below 1GHz)   | 8447D                                 | 2944A10738                                          | Aug. 16, 2020 | Aug. 15, 2021 |
| Preamplifier<br>Agilent<br>(Above 1GHz)   | 8449B                                 | 3008A02465                                          | Mar. 23, 2020 | Mar. 22, 2021 |
| RF Coaxial Cable<br>WOKEN<br>With 5dB PAD | 8D-FB                                 | Cable-CH3-01                                        | Aug. 16, 2020 | Aug. 15, 2021 |
| RF signal cable<br>HUBER+SUHNER           | SUCOFLEX 104                          | Cable-CH3-03<br>(223653/4)                          | Aug. 16, 2020 | Aug. 15, 2021 |
| RF signal cable<br>HUBER+SUHNER&<br>EMCI  | SUCOFLEX<br>104&EMC104-SM-S<br>M-8000 | Cable-CH3-03<br>(309224+170907)                     | Aug. 16, 2020 | Aug. 15, 2021 |
| Software<br>BV ADT                        | ADT_Radiated_<br>V7.6.15.9.5          | NA                                                  | NA            | NA            |
| Antenna Tower<br>inn-co GmbH              | MA 4000                               | 013303                                              | NA            | NA            |
| Antenna Tower Controller<br>BV ADT        | AT100                                 | AT93021702                                          | NA            | NA            |
| Turn Table<br>BV ADT                      | TT100                                 | TT93021702                                          | NA            | NA            |
| Turn Table Controller<br>BV ADT           | SC100                                 | SC93021702                                          | NA            | NA            |
| Boresight Antenna Fixture                 | FBA-01                                | FBA-SIP01                                           | NA            | NA            |
| Pre-amplifier (18GHz-40GHz)<br>EMC        | EMC184045B                            | 980175                                              | Sep. 04, 2020 | Sep. 03, 2021 |
| USB Wideband Power Sensor<br>KEYSIGHT     | U2021XA                               | MY55050005/MY5519<br>0004/MY55190007/MY<br>55210005 | Jul. 13, 2020 | Jul. 12, 2021 |

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.  
2. The test was performed in HwaYa Chamber 3.

#### 4.1.3 Test Procedures

##### For Radiated emission below 30MHz

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note:

- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

##### For Radiated emission above 30MHz

- The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
- The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
- The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is  $\geq 1/T$  (Duty cycle < 98%) or 10Hz (Duty cycle  $\geq 98\%$ ) for Average detection (AV) at frequency above 1GHz.  
**5G traffic radio (Radio 2)**  
 (802.11a: RBW = 1MHz, VBW = 1kHz; 802.11ax (HE20): RBW = 1MHz, VBW = 1kHz; 802.11ax (HE40): RBW = 1MHz, VBW = 1kHz; 802.11ax (HE80): RBW = 1MHz, VBW = 1kHz)  
**Scanning radio (Radio 3)**  
 (802.11a: RBW = 1MHz, VBW = 1kHz; 802.11ac (VHT20): RBW = 1MHz, VBW = 1kHz; 802.11ac (VHT40): RBW = 1MHz, VBW = 3kHz; 802.11ac (VHT80): RBW = 1MHz, VBW = 3kHz)
- All modes of operation were investigated and the worst-case emissions are reported.

#### 4.1.4 Deviation from Test Standard


No deviation.

#### 4.1.5 Test Setup


For Radiated emission below 30MHz



For Radiated emission 30MHz to 1GHz



#### For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.1.6 EUT Operating Conditions

- Placed the EUT on the testing table.
- Prepared a notebook to act as a communication partner and placed it outside of testing area.
- The communication partner connected with EUT via a RJ45 cable and ran a test program (provided by manufacturer) to enable EUT under transmission condition continuously at specific channel frequency.
- The communication partner sent data to EUT by command "PING".

#### 4.1.7 Test Results

Above 1GHz data:

5G traffic radio (Radio 2)

|                 |              |                   |                           |
|-----------------|--------------|-------------------|---------------------------|
| RF Mode         | TX 802.11a   | Channel           | CH 52 : 5260 MHz          |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 5150.00         | 59.0 PK                 | 74.0           | -15.0       | 1.79 H             | 352                  | 52.4             | 6.6                      |
| 2                                                    | 5150.00         | 46.2 AV                 | 54.0           | -7.8        | 1.79 H             | 352                  | 39.6             | 6.6                      |
| 3                                                    | *5260.00        | 120.0 PK                |                |             | 1.72 H             | 344                  | 78.1             | 41.9                     |
| 4                                                    | *5260.00        | 109.6 AV                |                |             | 1.72 H             | 344                  | 67.7             | 41.9                     |
| 5                                                    | #10520.00       | 60.2 PK                 | 68.2           | -8.0        | 1.88 H             | 261                  | 42.6             | 17.6                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 5150.00         | 58.3 PK                 | 74.0           | -15.7       | 1.65 V             | 351                  | 51.7             | 6.6                      |
| 2                                                    | 5150.00         | 45.6 AV                 | 54.0           | -8.4        | 1.65 V             | 351                  | 39.0             | 6.6                      |
| 3                                                    | *5260.00        | 116.7 PK                |                |             | 1.82 V             | 345                  | 74.8             | 41.9                     |
| 4                                                    | *5260.00        | 106.8 AV                |                |             | 1.82 V             | 345                  | 64.9             | 41.9                     |
| 5                                                    | #10520.00       | 59.9 PK                 | 68.2           | -8.3        | 1.55 V             | 19                   | 42.3             | 17.6                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |              |                   |                           |
|-----------------|--------------|-------------------|---------------------------|
| RF Mode         | TX 802.11a   | Channel           | CH 60 : 5300 MHz          |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *5300.00        | 120.4 PK                |                |             | 1.83 H             | 342                  | 78.5             | 41.9                     |
| 2                                                    | *5300.00        | 110.1 AV                |                |             | 1.83 H             | 342                  | 68.2             | 41.9                     |
| 3                                                    | 10600.00        | 59.7 PK                 | 74.0           | -14.3       | 1.83 H             | 3                    | 42.5             | 17.2                     |
| 4                                                    | 10600.00        | 47.7 AV                 | 54.0           | -6.3        | 1.83 H             | 3                    | 30.5             | 17.2                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *5300.00        | 117.5 PK                |                |             | 1.67 V             | 346                  | 75.6             | 41.9                     |
| 2                                                    | *5300.00        | 107.5 AV                |                |             | 1.67 V             | 346                  | 65.6             | 41.9                     |
| 3                                                    | 10600.00        | 59.7 PK                 | 74.0           | -14.3       | 1.59 V             | 18                   | 42.5             | 17.2                     |
| 4                                                    | 10600.00        | 47.7 AV                 | 54.0           | -6.3        | 1.59 V             | 18                   | 30.5             | 17.2                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency.

|                 |              |                   |                           |
|-----------------|--------------|-------------------|---------------------------|
| RF Mode         | TX 802.11a   | Channel           | CH 64 : 5320 MHz          |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *5320.00        | 119.0 PK                |                |             | 1.65 H             | 344                  | 77.0             | 42.0                     |
| 2                                                    | *5320.00        | 108.1 AV                |                |             | 1.65 H             | 344                  | 66.1             | 42.0                     |
| 3                                                    | 5350.00         | 59.7 PK                 | 74.0           | -14.3       | 1.57 H             | 345                  | 53.3             | 6.4                      |
| 4                                                    | 5350.00         | 47.9 AV                 | 54.0           | -6.1        | 1.57 H             | 345                  | 41.5             | 6.4                      |
| 5                                                    | 10640.00        | 60.4 PK                 | 74.0           | -13.6       | 1.61 H             | 19                   | 43.0             | 17.4                     |
| 6                                                    | 10640.00        | 46.3 AV                 | 54.0           | -7.7        | 1.61 H             | 19                   | 28.9             | 17.4                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *5320.00        | 116.5 PK                |                |             | 1.61 V             | 345                  | 74.5             | 42.0                     |
| 2                                                    | *5320.00        | 106.4 AV                |                |             | 1.61 V             | 345                  | 64.4             | 42.0                     |
| 3                                                    | 5350.00         | 58.2 PK                 | 74.0           | -15.8       | 1.56 V             | 337                  | 51.8             | 6.4                      |
| 4                                                    | 5350.00         | 45.5 AV                 | 54.0           | -8.5        | 1.56 V             | 337                  | 39.1             | 6.4                      |
| 5                                                    | 10640.00        | 59.6 PK                 | 74.0           | -14.4       | 1.60 V             | 19                   | 42.2             | 17.4                     |
| 6                                                    | 10640.00        | 48.1 AV                 | 54.0           | -5.9        | 1.60 V             | 19                   | 30.7             | 17.4                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency.

|                 |              |                   |                           |
|-----------------|--------------|-------------------|---------------------------|
| RF Mode         | TX 802.11a   | Channel           | CH 100 : 5500 MHz         |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 5460.00         | 58.3 PK                 | 74.0           | -15.7       | 1.69 H             | 346                  | 52.0             | 6.3                      |
| 2                                                    | 5460.00         | 46.9 AV                 | 54.0           | -7.1        | 1.69 H             | 346                  | 40.6             | 6.3                      |
| 3                                                    | #5470.00        | 58.1 PK                 | 68.2           | -10.1       | 1.63 H             | 349                  | 51.8             | 6.3                      |
| 4                                                    | *5500.00        | 119.6 PK                |                |             | 1.67 H             | 345                  | 77.5             | 42.1                     |
| 5                                                    | *5500.00        | 109.2 AV                |                |             | 1.67 H             | 345                  | 67.1             | 42.1                     |
| 6                                                    | 11000.00        | 60.8 PK                 | 74.0           | -13.2       | 1.49 H             | 324                  | 42.2             | 18.6                     |
| 7                                                    | 11000.00        | 52.6 AV                 | 54.0           | -1.4        | 1.49 H             | 324                  | 34.0             | 18.6                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 5460.00         | 57.5 PK                 | 74.0           | -16.5       | 1.45 V             | 358                  | 51.2             | 6.3                      |
| 2                                                    | 5460.00         | 44.8 AV                 | 54.0           | -9.2        | 1.45 V             | 358                  | 38.5             | 6.3                      |
| 3                                                    | #5470.00        | 57.9 PK                 | 68.2           | -10.3       | 1.43 V             | 355                  | 51.6             | 6.3                      |
| 4                                                    | *5500.00        | 117.2 PK                |                |             | 1.54 V             | 348                  | 75.1             | 42.1                     |
| 5                                                    | *5500.00        | 107.3 AV                |                |             | 1.54 V             | 348                  | 65.2             | 42.1                     |
| 6                                                    | 11000.00        | 60.9 PK                 | 74.0           | -13.1       | 1.38 V             | 15                   | 42.3             | 18.6                     |
| 7                                                    | 11000.00        | 52.5 AV                 | 54.0           | -1.5        | 1.38 V             | 15                   | 33.9             | 18.6                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

|                 |              |                   |                           |
|-----------------|--------------|-------------------|---------------------------|
| RF Mode         | TX 802.11a   | Channel           | CH 116 : 5580 MHz         |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *5580.00        | 119.8 PK                |                |             | 1.71 H             | 342                  | 77.7             | 42.1                     |
| 2                                                    | *5580.00        | 109.4 AV                |                |             | 1.71 H             | 342                  | 67.3             | 42.1                     |
| 3                                                    | 11160.00        | 61.0 PK                 | 74.0           | -13.0       | 1.86 H             | 27                   | 42.5             | 18.5                     |
| 4                                                    | 11160.00        | 46.5 AV                 | 54.0           | -7.5        | 1.86 H             | 27                   | 28.0             | 18.5                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *5580.00        | 117.9 PK                |                |             | 1.63 V             | 348                  | 75.8             | 42.1                     |
| 2                                                    | *5580.00        | 107.3 AV                |                |             | 1.63 V             | 348                  | 65.2             | 42.1                     |
| 3                                                    | 11160.00        | 60.9 PK                 | 74.0           | -13.1       | 2.67 V             | 325                  | 42.4             | 18.5                     |
| 4                                                    | 11160.00        | 49.2 AV                 | 54.0           | -4.8        | 2.67 V             | 325                  | 30.7             | 18.5                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.

|                 |              |                   |                           |
|-----------------|--------------|-------------------|---------------------------|
| RF Mode         | TX 802.11a   | Channel           | CH 140 : 5700 MHz         |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *5700.00        | 119.7 PK                |                |             | 1.62 H             | 345                  | 77.4             | 42.3                     |
| 2                                                    | *5700.00        | 109.3 AV                |                |             | 1.62 H             | 345                  | 67.0             | 42.3                     |
| 3                                                    | #5725.00        | 59.9 PK                 | 68.2           | -8.3        | 1.69 H             | 341                  | 53.4             | 6.5                      |
| 4                                                    | 11400.00        | 60.2 PK                 | 74.0           | -13.8       | 1.97 H             | 18                   | 42.3             | 17.9                     |
| 5                                                    | 11400.00        | 46.6 AV                 | 54.0           | -7.4        | 1.97 H             | 18                   | 28.7             | 17.9                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *5700.00        | 117.7 PK                |                |             | 1.52 V             | 351                  | 75.4             | 42.3                     |
| 2                                                    | *5700.00        | 107.5 AV                |                |             | 1.52 V             | 351                  | 65.2             | 42.3                     |
| 3                                                    | #5725.00        | 48.7 PK                 | 68.2           | -19.5       | 1.65 V             | 347                  | 42.2             | 6.5                      |
| 4                                                    | 11400.00        | 59.7 PK                 | 74.0           | -14.3       | 3.12 V             | 299                  | 41.8             | 17.9                     |
| 5                                                    | 11400.00        | 46.8 AV                 | 54.0           | -7.2        | 3.12 V             | 299                  | 28.9             | 17.9                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |              |                   |                           |
|-----------------|--------------|-------------------|---------------------------|
| RF Mode         | TX 802.11a   | Channel           | CH 144 : 5720 MHz         |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | #5470.00        | 57.8 PK                 | 68.2           | -10.4       | 1.55 H             | 352                  | 51.5             | 6.3                      |
| 2                                                    | *5720.00        | 119.9 PK                |                |             | 1.51 H             | 359                  | 77.7             | 42.2                     |
| 3                                                    | *5720.00        | 109.5 AV                |                |             | 1.51 H             | 359                  | 67.3             | 42.2                     |
| 4                                                    | #5850.00        | 58.1 PK                 | 68.2           | -10.1       | 1.57 H             | 355                  | 51.3             | 6.8                      |
| 5                                                    | 11440.00        | 59.5 PK                 | 74.0           | -14.5       | 1.46 H             | 334                  | 41.5             | 18.0                     |
| 6                                                    | 11440.00        | 47.4 AV                 | 54.0           | -6.6        | 1.46 H             | 334                  | 29.4             | 18.0                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | #5470.00        | 58.0 PK                 | 68.2           | -10.2       | 1.55 V             | 342                  | 51.7             | 6.3                      |
| 2                                                    | *5720.00        | 118.5 PK                |                |             | 1.58 V             | 347                  | 76.3             | 42.2                     |
| 3                                                    | *5720.00        | 107.5 AV                |                |             | 1.58 V             | 347                  | 65.3             | 42.2                     |
| 4                                                    | #5850.00        | 58.3 PK                 | 68.2           | -9.9        | 1.52 V             | 345                  | 51.5             | 6.8                      |
| 5                                                    | 11440.00        | 59.7 PK                 | 74.0           | -14.3       | 1.42 V             | 18                   | 41.7             | 18.0                     |
| 6                                                    | 11440.00        | 46.8 AV                 | 54.0           | -7.2        | 1.42 V             | 18                   | 28.8             | 18.0                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

|                 |                    |                   |                           |
|-----------------|--------------------|-------------------|---------------------------|
| RF Mode         | TX 802.11ax (HE20) | Channel           | CH 52 : 5260 MHz          |
| Frequency Range | 1GHz ~ 40GHz       | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 5150.00         | 59.1 PK                 | 74.0           | -14.9       | 1.79 H             | 355                  | 52.5             | 6.6                      |
| 2                                                    | 5150.00         | 46.2 AV                 | 54.0           | -7.8        | 1.79 H             | 355                  | 39.6             | 6.6                      |
| 3                                                    | *5260.00        | 122.7 PK                |                |             | 1.70 H             | 346                  | 80.8             | 41.9                     |
| 4                                                    | *5260.00        | 108.9 AV                |                |             | 1.70 H             | 346                  | 67.0             | 41.9                     |
| 5                                                    | #10520.00       | 59.6 PK                 | 68.2           | -8.6        | 1.39 H             | 12                   | 42.0             | 17.6                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 5150.00         | 58.4 PK                 | 74.0           | -15.6       | 1.55 V             | 338                  | 51.8             | 6.6                      |
| 2                                                    | 5150.00         | 45.6 AV                 | 54.0           | -8.4        | 1.55 V             | 338                  | 39.0             | 6.6                      |
| 3                                                    | *5260.00        | 120.0 PK                |                |             | 1.63 V             | 347                  | 78.1             | 41.9                     |
| 4                                                    | *5260.00        | 106.0 AV                |                |             | 1.63 V             | 347                  | 64.1             | 41.9                     |
| 5                                                    | #10520.00       | 59.9 PK                 | 68.2           | -8.3        | 1.52 V             | 17                   | 42.3             | 17.6                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |                    |                   |                           |
|-----------------|--------------------|-------------------|---------------------------|
| RF Mode         | TX 802.11ax (HE20) | Channel           | CH 60 : 5300 MHz          |
| Frequency Range | 1GHz ~ 40GHz       | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *5300.00        | 122.9 PK                |                |             | 1.72 H             | 342                  | 81.0             | 41.9                     |
| 2                                                    | *5300.00        | 109.5 AV                |                |             | 1.72 H             | 342                  | 67.6             | 41.9                     |
| 3                                                    | 10600.00        | 59.4 PK                 | 74.0           | -14.6       | 1.79 H             | 4                    | 42.2             | 17.2                     |
| 4                                                    | 10600.00        | 47.9 AV                 | 54.0           | -6.1        | 1.79 H             | 4                    | 30.7             | 17.2                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *5300.00        | 120.5 PK                |                |             | 1.55 V             | 344                  | 78.6             | 41.9                     |
| 2                                                    | *5300.00        | 106.6 AV                |                |             | 1.55 V             | 344                  | 64.7             | 41.9                     |
| 3                                                    | 10600.00        | 59.4 PK                 | 74.0           | -14.6       | 1.65 V             | 22                   | 42.2             | 17.2                     |
| 4                                                    | 10600.00        | 46.1 AV                 | 54.0           | -7.9        | 1.65 V             | 22                   | 28.9             | 17.2                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency.

|                 |                    |                   |                           |
|-----------------|--------------------|-------------------|---------------------------|
| RF Mode         | TX 802.11ax (HE20) | Channel           | CH 64 : 5320 MHz          |
| Frequency Range | 1GHz ~ 40GHz       | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *5320.00        | 121.4 PK                |                |             | 1.80 H             | 343                  | 79.4             | 42.0                     |
| 2                                                    | *5320.00        | 107.3 AV                |                |             | 1.80 H             | 343                  | 65.3             | 42.0                     |
| 3                                                    | 5350.00         | 60.2 PK                 | 74.0           | -13.8       | 1.89 H             | 349                  | 53.8             | 6.4                      |
| 4                                                    | 5350.00         | 47.7 AV                 | 54.0           | -6.3        | 1.89 H             | 349                  | 41.3             | 6.4                      |
| 5                                                    | 10640.00        | 59.9 PK                 | 74.0           | -14.1       | 1.80 H             | 4                    | 42.5             | 17.4                     |
| 6                                                    | 10640.00        | 48.2 AV                 | 54.0           | -5.8        | 1.80 H             | 4                    | 30.8             | 17.4                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *5320.00        | 119.6 PK                |                |             | 1.73 V             | 345                  | 77.6             | 42.0                     |
| 2                                                    | *5320.00        | 106.0 AV                |                |             | 1.73 V             | 345                  | 64.0             | 42.0                     |
| 3                                                    | 5350.00         | 58.7 PK                 | 74.0           | -15.3       | 1.66 V             | 351                  | 52.3             | 6.4                      |
| 4                                                    | 5350.00         | 45.5 AV                 | 54.0           | -8.5        | 1.66 V             | 351                  | 39.1             | 6.4                      |
| 5                                                    | 10640.00        | 59.4 PK                 | 74.0           | -14.6       | 1.59 V             | 18                   | 42.0             | 17.4                     |
| 6                                                    | 10640.00        | 46.4 AV                 | 54.0           | -7.6        | 1.59 V             | 18                   | 29.0             | 17.4                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.

|                 |                    |                   |                           |
|-----------------|--------------------|-------------------|---------------------------|
| RF Mode         | TX 802.11ax (HE20) | Channel           | CH 100 : 5500 MHz         |
| Frequency Range | 1GHz ~ 40GHz       | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 5460.00         | 58.0 PK                 | 74.0           | -16.0       | 1.66 H             | 337                  | 51.7             | 6.3                      |
| 2                                                    | 5460.00         | 47.0 AV                 | 54.0           | -7.0        | 1.66 H             | 337                  | 40.7             | 6.3                      |
| 3                                                    | #5470.00        | 58.8 PK                 | 68.2           | -9.4        | 1.65 H             | 346                  | 52.5             | 6.3                      |
| 4                                                    | *5500.00        | 122.1 PK                |                |             | 1.72 H             | 342                  | 80.0             | 42.1                     |
| 5                                                    | *5500.00        | 108.6 AV                |                |             | 1.72 H             | 342                  | 66.5             | 42.1                     |
| 6                                                    | 11000.00        | 60.5 PK                 | 74.0           | -13.5       | 1.48 H             | 326                  | 41.9             | 18.6                     |
| 7                                                    | 11000.00        | 50.9 AV                 | 54.0           | -3.1        | 1.48 H             | 326                  | 32.3             | 18.6                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 5460.00         | 57.6 PK                 | 74.0           | -16.4       | 1.53 V             | 342                  | 51.3             | 6.3                      |
| 2                                                    | 5460.00         | 44.9 AV                 | 54.0           | -9.1        | 1.53 V             | 342                  | 38.6             | 6.3                      |
| 3                                                    | #5470.00        | 58.0 PK                 | 68.2           | -10.2       | 1.58 V             | 344                  | 51.7             | 6.3                      |
| 4                                                    | *5500.00        | 119.0 PK                |                |             | 1.60 V             | 347                  | 76.9             | 42.1                     |
| 5                                                    | *5500.00        | 106.3 AV                |                |             | 1.60 V             | 347                  | 64.2             | 42.1                     |
| 6                                                    | 11000.00        | 60.2 PK                 | 74.0           | -13.8       | 1.55 V             | 356                  | 41.6             | 18.6                     |
| 7                                                    | 11000.00        | 50.7 AV                 | 54.0           | -3.3        | 1.55 V             | 356                  | 32.1             | 18.6                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

|                 |                    |                   |                           |
|-----------------|--------------------|-------------------|---------------------------|
| RF Mode         | TX 802.11ax (HE20) | Channel           | CH 116 : 5580 MHz         |
| Frequency Range | 1GHz ~ 40GHz       | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *5580.00        | 122.8 PK                |                |             | 1.65 H             | 344                  | 80.7             | 42.1                     |
| 2                                                    | *5580.00        | 108.7 AV                |                |             | 1.65 H             | 344                  | 66.6             | 42.1                     |
| 3                                                    | 11160.00        | 60.6 PK                 | 74.0           | -13.4       | 1.93 H             | 15                   | 42.1             | 18.5                     |
| 4                                                    | 11160.00        | 47.1 AV                 | 54.0           | -6.9        | 1.93 H             | 15                   | 28.6             | 18.5                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *5580.00        | 119.7 PK                |                |             | 1.58 V             | 345                  | 77.6             | 42.1                     |
| 2                                                    | *5580.00        | 106.4 AV                |                |             | 1.58 V             | 345                  | 64.3             | 42.1                     |
| 3                                                    | 11160.00        | 60.0 PK                 | 74.0           | -14.0       | 2.06 V             | 359                  | 41.5             | 18.5                     |
| 4                                                    | 11160.00        | 46.8 AV                 | 54.0           | -7.2        | 2.06 V             | 359                  | 28.3             | 18.5                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.

|                 |                    |                   |                           |
|-----------------|--------------------|-------------------|---------------------------|
| RF Mode         | TX 802.11ax (HE20) | Channel           | CH 140 : 5700 MHz         |
| Frequency Range | 1GHz ~ 40GHz       | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *5700.00        | 122.7 PK                |                |             | 1.66 H             | 355                  | 80.4             | 42.3                     |
| 2                                                    | *5700.00        | 109.4 AV                |                |             | 1.66 H             | 355                  | 67.1             | 42.3                     |
| 3                                                    | #5725.00        | 62.5 PK                 | 68.2           | -5.7        | 1.69 H             | 354                  | 56.0             | 6.5                      |
| 4                                                    | 11400.00        | 60.2 PK                 | 74.0           | -13.8       | 1.74 H             | 17                   | 42.3             | 17.9                     |
| 5                                                    | 11400.00        | 46.5 AV                 | 54.0           | -7.5        | 1.74 H             | 17                   | 28.6             | 17.9                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *5700.00        | 120.3 PK                |                |             | 1.58 V             | 346                  | 78.0             | 42.3                     |
| 2                                                    | *5700.00        | 106.7 AV                |                |             | 1.58 V             | 346                  | 64.4             | 42.3                     |
| 3                                                    | #5725.00        | 60.4 PK                 | 68.2           | -7.8        | 1.61 V             | 350                  | 53.9             | 6.5                      |
| 4                                                    | 11400.00        | 59.9 PK                 | 74.0           | -14.1       | 1.38 V             | 21                   | 42.0             | 17.9                     |
| 5                                                    | 11400.00        | 46.7 AV                 | 54.0           | -7.3        | 1.38 V             | 21                   | 28.8             | 17.9                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |                    |                   |                           |
|-----------------|--------------------|-------------------|---------------------------|
| RF Mode         | TX 802.11ax (HE20) | Channel           | CH 144 : 5720 MHz         |
| Frequency Range | 1GHz ~ 40GHz       | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | #5470.00        | 57.9 PK                 | 68.2           | -10.3       | 1.59 H             | 355                  | 51.6             | 6.3                      |
| 2                                                    | *5720.00        | 121.6 PK                |                |             | 1.62 H             | 358                  | 79.4             | 42.2                     |
| 3                                                    | *5720.00        | 108.9 AV                |                |             | 1.62 H             | 358                  | 66.7             | 42.2                     |
| 4                                                    | #5850.00        | 58.3 PK                 | 68.2           | -9.9        | 1.55 H             | 354                  | 51.5             | 6.8                      |
| 5                                                    | 11440.00        | 59.5 PK                 | 74.0           | -14.5       | 1.47 H             | 334                  | 41.5             | 18.0                     |
| 6                                                    | 11440.00        | 47.0 AV                 | 54.0           | -7.0        | 1.47 H             | 334                  | 29.0             | 18.0                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | #5470.00        | 58.0 PK                 | 68.2           | -10.2       | 1.52 V             | 348                  | 51.7             | 6.3                      |
| 2                                                    | *5720.00        | 119.5 PK                |                |             | 1.50 V             | 346                  | 77.3             | 42.2                     |
| 3                                                    | *5720.00        | 106.8 AV                |                |             | 1.50 V             | 346                  | 64.6             | 42.2                     |
| 4                                                    | #5850.00        | 58.4 PK                 | 68.2           | -9.8        | 1.55 V             | 347                  | 51.6             | 6.8                      |
| 5                                                    | 11440.00        | 59.8 PK                 | 74.0           | -14.2       | 1.44 V             | 15                   | 41.8             | 18.0                     |
| 6                                                    | 11440.00        | 46.5 AV                 | 54.0           | -7.5        | 1.44 V             | 15                   | 28.5             | 18.0                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

|                 |                    |                   |                           |
|-----------------|--------------------|-------------------|---------------------------|
| RF Mode         | TX 802.11ax (HE40) | Channel           | CH 54 : 5270 MHz          |
| Frequency Range | 1GHz ~ 40GHz       | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 5150.00         | 59.0 PK                 | 74.0           | -15.0       | 1.85 H             | 346                  | 52.4             | 6.6                      |
| 2                                                    | 5150.00         | 45.9 AV                 | 54.0           | -8.1        | 1.85 H             | 346                  | 39.3             | 6.6                      |
| 3                                                    | *5270.00        | 119.7 PK                |                |             | 1.78 H             | 342                  | 77.8             | 41.9                     |
| 4                                                    | *5270.00        | 106.6 AV                |                |             | 1.78 H             | 342                  | 64.7             | 41.9                     |
| 5                                                    | #10540.00       | 59.5 PK                 | 68.2           | -8.7        | 1.32 H             | 16                   | 41.9             | 17.6                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 5150.00         | 58.8 PK                 | 74.0           | -15.2       | 1.65 V             | 349                  | 52.2             | 6.6                      |
| 2                                                    | 5150.00         | 45.6 AV                 | 54.0           | -8.4        | 1.65 V             | 349                  | 39.0             | 6.6                      |
| 3                                                    | *5270.00        | 117.1 PK                |                |             | 1.58 V             | 346                  | 75.2             | 41.9                     |
| 4                                                    | *5270.00        | 104.2 AV                |                |             | 1.58 V             | 346                  | 62.3             | 41.9                     |
| 5                                                    | #10540.00       | 60.3 PK                 | 68.2           | -7.9        | 1.64 V             | 15                   | 42.7             | 17.6                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |                    |                   |                           |
|-----------------|--------------------|-------------------|---------------------------|
| RF Mode         | TX 802.11ax (HE40) | Channel           | CH 62 : 5310 MHz          |
| Frequency Range | 1GHz ~ 40GHz       | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *5310.00        | 118.9 PK                |                |             | 1.71 H             | 342                  | 76.9             | 42.0                     |
| 2                                                    | *5310.00        | 106.1 AV                |                |             | 1.71 H             | 342                  | 64.1             | 42.0                     |
| 3                                                    | 5350.00         | 63.6 PK                 | 74.0           | -10.4       | 1.75 H             | 342                  | 57.2             | 6.4                      |
| 4                                                    | 5350.00         | 50.7 AV                 | 54.0           | -3.3        | 1.75 H             | 342                  | 44.3             | 6.4                      |
| 5                                                    | 10620.00        | 59.4 PK                 | 74.0           | -14.6       | 1.82 H             | 3                    | 42.0             | 17.4                     |
| 6                                                    | 10620.00        | 48.1 AV                 | 54.0           | -5.9        | 1.82 H             | 3                    | 30.7             | 17.4                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *5310.00        | 116.7 PK                |                |             | 1.79 V             | 345                  | 74.7             | 42.0                     |
| 2                                                    | *5310.00        | 104.3 AV                |                |             | 1.79 V             | 345                  | 62.3             | 42.0                     |
| 3                                                    | 5350.00         | 61.9 PK                 | 74.0           | -12.1       | 1.71 V             | 346                  | 55.5             | 6.4                      |
| 4                                                    | 5350.00         | 49.0 AV                 | 54.0           | -5.0        | 1.71 V             | 346                  | 42.6             | 6.4                      |
| 5                                                    | 10620.00        | 59.0 PK                 | 74.0           | -15.0       | 1.55 V             | 20                   | 41.6             | 17.4                     |
| 6                                                    | 10620.00        | 47.9 AV                 | 54.0           | -6.1        | 1.55 V             | 20                   | 30.5             | 17.4                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency.

|                 |                    |                   |                           |
|-----------------|--------------------|-------------------|---------------------------|
| RF Mode         | TX 802.11ax (HE40) | Channel           | CH 102 : 5510 MHz         |
| Frequency Range | 1GHz ~ 40GHz       | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 5460.00         | 59.9 PK                 | 74.0           | -14.1       | 1.61 H             | 343                  | 53.6             | 6.3                      |
| 2                                                    | 5460.00         | 47.2 AV                 | 54.0           | -6.8        | 1.61 H             | 343                  | 40.9             | 6.3                      |
| 3                                                    | #5470.00        | 62.6 PK                 | 68.2           | -5.6        | 1.64 H             | 345                  | 56.3             | 6.3                      |
| 4                                                    | *5510.00        | 119.2 PK                |                |             | 1.62 H             | 345                  | 77.1             | 42.1                     |
| 5                                                    | *5510.00        | 105.5 AV                |                |             | 1.62 H             | 345                  | 63.4             | 42.1                     |
| 6                                                    | 11020.00        | 60.9 PK                 | 74.0           | -13.1       | 1.69 H             | 19                   | 42.3             | 18.6                     |
| 7                                                    | 11020.00        | 50.4 AV                 | 54.0           | -3.6        | 1.69 H             | 19                   | 31.8             | 18.6                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 5460.00         | 59.1 PK                 | 74.0           | -14.9       | 1.58 V             | 355                  | 52.8             | 6.3                      |
| 2                                                    | 5460.00         | 47.2 AV                 | 54.0           | -6.8        | 1.58 V             | 355                  | 40.9             | 6.3                      |
| 3                                                    | #5470.00        | 59.5 PK                 | 68.2           | -8.7        | 1.63 V             | 342                  | 53.2             | 6.3                      |
| 4                                                    | *5510.00        | 116.6 PK                |                |             | 1.61 V             | 345                  | 74.5             | 42.1                     |
| 5                                                    | *5510.00        | 103.2 AV                |                |             | 1.61 V             | 345                  | 61.1             | 42.1                     |
| 6                                                    | 11020.00        | 62.2 PK                 | 74.0           | -11.8       | 1.33 V             | 353                  | 43.6             | 18.6                     |
| 7                                                    | 11020.00        | 51.4 AV                 | 54.0           | -2.6        | 1.33 V             | 353                  | 32.8             | 18.6                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

|                 |                    |                   |                           |
|-----------------|--------------------|-------------------|---------------------------|
| RF Mode         | TX 802.11ax (HE40) | Channel           | CH 110 : 5550 MHz         |
| Frequency Range | 1GHz ~ 40GHz       | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *5550.00        | 119.6 PK                |                |             | 1.60 H             | 346                  | 77.5             | 42.1                     |
| 2                                                    | *5550.00        | 105.8 AV                |                |             | 1.60 H             | 346                  | 63.7             | 42.1                     |
| 3                                                    | 11100.00        | 60.6 PK                 | 74.0           | -13.4       | 1.68 H             | 19                   | 42.3             | 18.3                     |
| 4                                                    | 11100.00        | 46.7 AV                 | 54.0           | -7.3        | 1.68 H             | 19                   | 28.4             | 18.3                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *5550.00        | 116.1 PK                |                |             | 1.47 V             | 346                  | 74.0             | 42.1                     |
| 2                                                    | *5550.00        | 103.4 AV                |                |             | 1.47 V             | 346                  | 61.3             | 42.1                     |
| 3                                                    | 11100.00        | 60.8 PK                 | 74.0           | -13.2       | 1.47 V             | 12                   | 42.5             | 18.3                     |
| 4                                                    | 11100.00        | 48.5 AV                 | 54.0           | -5.5        | 1.47 V             | 12                   | 30.2             | 18.3                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.

|                 |                    |                   |                           |
|-----------------|--------------------|-------------------|---------------------------|
| RF Mode         | TX 802.11ax (HE40) | Channel           | CH 134 : 5670 MHz         |
| Frequency Range | 1GHz ~ 40GHz       | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *5670.00        | 119.6 PK                |                |             | 1.56 H             | 354                  | 77.4             | 42.2                     |
| 2                                                    | *5670.00        | 105.8 AV                |                |             | 1.56 H             | 354                  | 63.6             | 42.2                     |
| 3                                                    | #5725.00        | 62.3 PK                 | 68.2           | -5.9        | 1.62 H             | 347                  | 55.8             | 6.5                      |
| 4                                                    | 11340.00        | 60.3 PK                 | 74.0           | -13.7       | 1.72 H             | 13                   | 42.2             | 18.1                     |
| 5                                                    | 11340.00        | 46.5 AV                 | 54.0           | -7.5        | 1.72 H             | 13                   | 28.4             | 18.1                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *5670.00        | 116.7 PK                |                |             | 1.49 V             | 349                  | 74.5             | 42.2                     |
| 2                                                    | *5670.00        | 103.5 AV                |                |             | 1.49 V             | 349                  | 61.3             | 42.2                     |
| 3                                                    | #5725.00        | 59.0 PK                 | 68.2           | -9.2        | 1.56 V             | 347                  | 52.5             | 6.5                      |
| 4                                                    | 11340.00        | 60.3 PK                 | 74.0           | -13.7       | 1.38 V             | 26                   | 42.2             | 18.1                     |
| 5                                                    | 11340.00        | 46.7 AV                 | 54.0           | -7.3        | 1.38 V             | 26                   | 28.6             | 18.1                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |                    |                   |                           |
|-----------------|--------------------|-------------------|---------------------------|
| RF Mode         | TX 802.11ax (HE40) | Channel           | CH 142 : 5710 MHz         |
| Frequency Range | 1GHz ~ 40GHz       | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | #5470.00        | 57.8 PK                 | 68.2           | -10.4       | 1.55 H             | 355                  | 51.5             | 6.3                      |
| 2                                                    | *5710.00        | 119.3 PK                |                |             | 1.53 H             | 358                  | 77.0             | 42.3                     |
| 3                                                    | *5710.00        | 106.4 AV                |                |             | 1.53 H             | 358                  | 64.1             | 42.3                     |
| 4                                                    | #5850.00        | 58.4 PK                 | 68.2           | -9.8        | 1.53 H             | 342                  | 51.6             | 6.8                      |
| 5                                                    | 11420.00        | 59.4 PK                 | 74.0           | -14.6       | 1.58 H             | 346                  | 41.5             | 17.9                     |
| 6                                                    | 11420.00        | 46.4 AV                 | 54.0           | -7.6        | 1.58 H             | 346                  | 28.5             | 17.9                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | #5470.00        | 58.1 PK                 | 68.2           | -10.1       | 1.58 V             | 345                  | 51.8             | 6.3                      |
| 2                                                    | *5710.00        | 117.3 PK                |                |             | 1.60 V             | 348                  | 75.0             | 42.3                     |
| 3                                                    | *5710.00        | 104.6 AV                |                |             | 1.60 V             | 348                  | 62.3             | 42.3                     |
| 4                                                    | #5850.00        | 58.4 PK                 | 68.2           | -9.8        | 1.55 V             | 344                  | 51.6             | 6.8                      |
| 5                                                    | 11420.00        | 59.6 PK                 | 74.0           | -14.4       | 1.35 V             | 18                   | 41.7             | 17.9                     |
| 6                                                    | 11420.00        | 46.5 AV                 | 54.0           | -7.5        | 1.35 V             | 18                   | 28.6             | 17.9                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

|                 |                    |                   |                           |
|-----------------|--------------------|-------------------|---------------------------|
| RF Mode         | TX 802.11ax (HE80) | Channel           | CH 58 : 5290 MHz          |
| Frequency Range | 1GHz ~ 40GHz       | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 5150.00         | 59.1 PK                 | 74.0           | -14.9       | 1.69 H             | 355                  | 52.5             | 6.6                      |
| 2                                                    | 5150.00         | 46.2 AV                 | 54.0           | -7.8        | 1.69 H             | 355                  | 39.6             | 6.6                      |
| 3                                                    | *5290.00        | 116.6 PK                |                |             | 1.88 H             | 342                  | 74.7             | 41.9                     |
| 4                                                    | *5290.00        | 104.2 AV                |                |             | 1.88 H             | 342                  | 62.3             | 41.9                     |
| 5                                                    | 5350.00         | 66.7 PK                 | 74.0           | -7.3        | 1.76 H             | 340                  | 60.3             | 6.4                      |
| 6                                                    | 5350.00         | 52.9 AV                 | 54.0           | -1.1        | 1.76 H             | 340                  | 46.5             | 6.4                      |
| 7                                                    | #10580.00       | 59.4 PK                 | 68.2           | -8.8        | 1.64 H             | 11                   | 42.0             | 17.4                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 5150.00         | 59.2 PK                 | 74.0           | -14.8       | 1.53 V             | 329                  | 52.6             | 6.6                      |
| 2                                                    | 5150.00         | 45.8 AV                 | 54.0           | -8.2        | 1.53 V             | 329                  | 39.2             | 6.6                      |
| 3                                                    | *5290.00        | 115.5 PK                |                |             | 1.58 V             | 346                  | 73.6             | 41.9                     |
| 4                                                    | *5290.00        | 101.9 AV                |                |             | 1.58 V             | 346                  | 60.0             | 41.9                     |
| 5                                                    | 5350.00         | 65.6 PK                 | 74.0           | -8.4        | 1.50 V             | 344                  | 59.2             | 6.4                      |
| 6                                                    | 5350.00         | 52.1 AV                 | 54.0           | -1.9        | 1.50 V             | 344                  | 45.7             | 6.4                      |
| 7                                                    | #10580.00       | 59.2 PK                 | 68.2           | -9.0        | 1.52 V             | 21                   | 41.8             | 17.4                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

|                 |                    |                   |                           |
|-----------------|--------------------|-------------------|---------------------------|
| RF Mode         | TX 802.11ax (HE80) | Channel           | CH 106 : 5530 MHz         |
| Frequency Range | 1GHz ~ 40GHz       | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 5460.00         | 66.6 PK                 | 74.0           | -7.4        | 1.70 H             | 350                  | 60.3             | 6.3                      |
| 2                                                    | 5460.00         | 52.3 AV                 | 54.0           | -1.7        | 1.70 H             | 350                  | 46.0             | 6.3                      |
| 3                                                    | #5470.00        | 67.2 PK                 | 68.2           | -1.0        | 1.74 H             | 344                  | 60.9             | 6.3                      |
| 4                                                    | *5530.00        | 116.3 PK                |                |             | 1.71 H             | 343                  | 74.2             | 42.1                     |
| 5                                                    | *5530.00        | 102.5 AV                |                |             | 1.71 H             | 343                  | 60.4             | 42.1                     |
| 6                                                    | #5725.00        | 58.6 PK                 | 68.2           | -9.6        | 1.67 H             | 326                  | 52.1             | 6.5                      |
| 7                                                    | 11060.00        | 60.5 PK                 | 74.0           | -13.5       | 1.82 H             | 16                   | 42.1             | 18.4                     |
| 8                                                    | 11060.00        | 46.7 AV                 | 54.0           | -7.3        | 1.82 H             | 16                   | 28.3             | 18.4                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 5460.00         | 64.7 PK                 | 74.0           | -9.3        | 1.54 V             | 339                  | 58.4             | 6.3                      |
| 2                                                    | 5460.00         | 51.3 AV                 | 54.0           | -2.7        | 1.54 V             | 339                  | 45.0             | 6.3                      |
| 3                                                    | #5470.00        | 65.8 PK                 | 68.2           | -2.4        | 1.59 V             | 344                  | 59.5             | 6.3                      |
| 4                                                    | *5530.00        | 113.1 PK                |                |             | 1.67 V             | 345                  | 71.0             | 42.1                     |
| 5                                                    | *5530.00        | 100.1 AV                |                |             | 1.67 V             | 345                  | 58.0             | 42.1                     |
| 6                                                    | #5725.00        | 57.8 PK                 | 68.2           | -10.4       | 1.65 V             | 334                  | 51.3             | 6.5                      |
| 7                                                    | 11060.00        | 60.7 PK                 | 74.0           | -13.3       | 1.37 V             | 19                   | 42.3             | 18.4                     |
| 8                                                    | 11060.00        | 46.8 AV                 | 54.0           | -7.2        | 1.37 V             | 19                   | 28.4             | 18.4                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |                    |                   |                           |
|-----------------|--------------------|-------------------|---------------------------|
| RF Mode         | TX 802.11ax (HE80) | Channel           | CH 122 : 5610 MHz         |
| Frequency Range | 1GHz ~ 40GHz       | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 5460.00         | 59.2 PK                 | 74.0           | -14.8       | 1.49 H             | 344                  | 52.9             | 6.3                      |
| 2                                                    | 5460.00         | 46.5 AV                 | 54.0           | -7.5        | 1.49 H             | 344                  | 40.2             | 6.3                      |
| 3                                                    | #5470.00        | 59.6 PK                 | 68.2           | -8.6        | 1.52 H             | 345                  | 53.3             | 6.3                      |
| 4                                                    | *5610.00        | 116.7 PK                |                |             | 1.57 H             | 343                  | 74.6             | 42.1                     |
| 5                                                    | *5610.00        | 103.5 AV                |                |             | 1.57 H             | 343                  | 61.4             | 42.1                     |
| 6                                                    | #5725.00        | 65.4 PK                 | 68.2           | -2.8        | 1.61 H             | 352                  | 58.9             | 6.5                      |
| 7                                                    | 11220.00        | 60.3 PK                 | 74.0           | -13.7       | 1.51 H             | 338                  | 41.8             | 18.5                     |
| 8                                                    | 11220.00        | 47.1 AV                 | 54.0           | -6.9        | 1.51 H             | 338                  | 28.6             | 18.5                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 5460.00         | 58.1 PK                 | 74.0           | -15.9       | 1.44 V             | 350                  | 51.8             | 6.3                      |
| 2                                                    | 5460.00         | 45.2 AV                 | 54.0           | -8.8        | 1.44 V             | 350                  | 38.9             | 6.3                      |
| 3                                                    | #5470.00        | 59.3 PK                 | 68.2           | -8.9        | 1.42 V             | 349                  | 53.0             | 6.3                      |
| 4                                                    | *5610.00        | 113.7 PK                |                |             | 1.46 V             | 346                  | 71.6             | 42.1                     |
| 5                                                    | *5610.00        | 100.6 AV                |                |             | 1.46 V             | 346                  | 58.5             | 42.1                     |
| 6                                                    | #5725.00        | 64.5 PK                 | 68.2           | -3.7        | 1.46 V             | 351                  | 58.0             | 6.5                      |
| 7                                                    | 11220.00        | 60.2 PK                 | 74.0           | -13.8       | 1.42 V             | 13                   | 41.7             | 18.5                     |
| 8                                                    | 11220.00        | 47.0 AV                 | 54.0           | -7.0        | 1.42 V             | 13                   | 28.5             | 18.5                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |                    |                   |                           |
|-----------------|--------------------|-------------------|---------------------------|
| RF Mode         | TX 802.11ax (HE80) | Channel           | CH 138 : 5690 MHz         |
| Frequency Range | 1GHz ~ 40GHz       | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | #5470.00        | 58.1 PK                 | 68.2           | -10.1       | 1.58 H             | 342                  | 51.8             | 6.3                      |
| 2                                                    | *5690.00        | 116.9 PK                |                |             | 1.62 H             | 345                  | 74.6             | 42.3                     |
| 3                                                    | *5690.00        | 103.9 AV                |                |             | 1.62 H             | 345                  | 61.6             | 42.3                     |
| 4                                                    | #5850.00        | 59.2 PK                 | 68.2           | -9.0        | 1.55 H             | 348                  | 52.4             | 6.8                      |
| 5                                                    | 11380.00        | 59.5 PK                 | 74.0           | -14.5       | 1.52 H             | 349                  | 41.7             | 17.8                     |
| 6                                                    | 11380.00        | 46.4 AV                 | 54.0           | -7.6        | 1.52 H             | 349                  | 28.6             | 17.8                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | #5470.00        | 57.9 PK                 | 68.2           | -10.3       | 1.45 V             | 342                  | 51.6             | 6.3                      |
| 2                                                    | *5690.00        | 114.3 PK                |                |             | 1.50 V             | 344                  | 72.0             | 42.3                     |
| 3                                                    | *5690.00        | 101.6 AV                |                |             | 1.50 V             | 344                  | 59.3             | 42.3                     |
| 4                                                    | #5850.00        | 58.6 PK                 | 68.2           | -9.6        | 1.47 V             | 346                  | 51.8             | 6.8                      |
| 5                                                    | 11380.00        | 59.4 PK                 | 74.0           | -14.6       | 1.35 V             | 22                   | 41.6             | 17.8                     |
| 6                                                    | 11380.00        | 46.3 AV                 | 54.0           | -7.7        | 1.35 V             | 22                   | 28.5             | 17.8                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

### Scanning radio (Radio 3)

|                 |              |                   |                           |
|-----------------|--------------|-------------------|---------------------------|
| RF Mode         | TX 802.11a   | Channel           | CH 52 : 5260 MHz          |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *5260.00        | 108.4 PK                |                |             | 1.59 H             | 284                  | 66.5             | 41.9                     |
| 2                                                    | *5260.00        | 98.2 AV                 |                |             | 1.59 H             | 284                  | 56.3             | 41.9                     |
| 3                                                    | 5350.00         | 57.8 PK                 | 74.0           | -16.2       | 1.62 H             | 286                  | 51.4             | 6.4                      |
| 4                                                    | 5350.00         | 44.7 AV                 | 54.0           | -9.3        | 1.62 H             | 286                  | 38.3             | 6.4                      |
| 5                                                    | #10520.00       | 60.2 PK                 | 68.2           | -8.0        | 1.85 H             | 338                  | 42.6             | 17.6                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *5260.00        | 119.1 PK                |                |             | 1.76 V             | 1                    | 77.2             | 41.9                     |
| 2                                                    | *5260.00        | 109.1 AV                |                |             | 1.76 V             | 1                    | 67.2             | 41.9                     |
| 3                                                    | 5350.00         | 65.7 PK                 | 74.0           | -8.3        | 1.78 V             | 3                    | 59.3             | 6.4                      |
| 4                                                    | 5350.00         | 52.9 AV                 | 54.0           | -1.1        | 1.78 V             | 3                    | 46.5             | 6.4                      |
| 5                                                    | #10520.00       | 58.2 PK                 | 68.2           | -10.0       | 2.74 V             | 78                   | 40.6             | 17.6                     |

#### Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiation frequency is out of the restricted band.

|                 |              |                   |                           |
|-----------------|--------------|-------------------|---------------------------|
| RF Mode         | TX 802.11a   | Channel           | CH 60 : 5300 MHz          |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *5300.00        | 109.0 PK                |                |             | 1.44 H             | 288                  | 67.1             | 41.9                     |
| 2                                                    | *5300.00        | 99.3 AV                 |                |             | 1.44 H             | 288                  | 57.4             | 41.9                     |
| 3                                                    | 10600.00        | 58.7 PK                 | 74.0           | -15.3       | 2.88 H             | 83                   | 41.5             | 17.2                     |
| 4                                                    | 10600.00        | 45.7 AV                 | 54.0           | -8.3        | 2.88 H             | 83                   | 28.5             | 17.2                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *5300.00        | 119.0 PK                |                |             | 1.57 V             | 5                    | 77.1             | 41.9                     |
| 2                                                    | *5300.00        | 109.0 AV                |                |             | 1.57 V             | 5                    | 67.1             | 41.9                     |
| 3                                                    | 10600.00        | 58.2 PK                 | 74.0           | -15.8       | 2.78 V             | 81                   | 41.0             | 17.2                     |
| 4                                                    | 10600.00        | 45.4 AV                 | 54.0           | -8.6        | 2.78 V             | 81                   | 28.2             | 17.2                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency.

|                 |              |                   |                           |
|-----------------|--------------|-------------------|---------------------------|
| RF Mode         | TX 802.11a   | Channel           | CH 64 : 5320 MHz          |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *5320.00        | 106.6 PK                |                |             | 1.38 H             | 290                  | 64.6             | 42.0                     |
| 2                                                    | *5320.00        | 96.4 AV                 |                |             | 1.38 H             | 290                  | 54.4             | 42.0                     |
| 3                                                    | 5350.00         | 58.6 PK                 | 74.0           | -15.4       | 1.40 H             | 292                  | 52.2             | 6.4                      |
| 4                                                    | 5350.00         | 44.9 AV                 | 54.0           | -9.1        | 1.40 H             | 292                  | 38.5             | 6.4                      |
| 5                                                    | 10640.00        | 59.5 PK                 | 74.0           | -14.5       | 1.88 H             | 339                  | 42.1             | 17.4                     |
| 6                                                    | 10640.00        | 46.2 AV                 | 54.0           | -7.8        | 1.88 H             | 339                  | 28.8             | 17.4                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *5320.00        | 116.2 PK                |                |             | 1.52 V             | 5                    | 74.2             | 42.0                     |
| 2                                                    | *5320.00        | 106.0 AV                |                |             | 1.52 V             | 5                    | 64.0             | 42.0                     |
| 3                                                    | 5350.00         | 66.7 PK                 | 74.0           | -7.3        | 1.51 V             | 5                    | 60.3             | 6.4                      |
| 4                                                    | 5350.00         | 52.4 AV                 | 54.0           | -1.6        | 1.51 V             | 5                    | 46.0             | 6.4                      |
| 5                                                    | 10640.00        | 58.5 PK                 | 74.0           | -15.5       | 2.77 V             | 82                   | 41.1             | 17.4                     |
| 6                                                    | 10640.00        | 45.8 AV                 | 54.0           | -8.2        | 2.77 V             | 82                   | 28.4             | 17.4                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency.

|                 |              |                   |                           |
|-----------------|--------------|-------------------|---------------------------|
| RF Mode         | TX 802.11a   | Channel           | CH 100 : 5500 MHz         |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 5460.00         | 57.5 PK                 | 74.0           | -16.5       | 1.20 H             | 277                  | 51.2             | 6.3                      |
| 2                                                    | 5460.00         | 44.5 AV                 | 54.0           | -9.5        | 1.20 H             | 277                  | 38.2             | 6.3                      |
| 3                                                    | #5470.00        | 58.2 PK                 | 68.2           | -10.0       | 1.22 H             | 180                  | 51.9             | 6.3                      |
| 4                                                    | *5500.00        | 108.1 PK                |                |             | 1.14 H             | 281                  | 66.0             | 42.1                     |
| 5                                                    | *5500.00        | 98.1 AV                 |                |             | 1.14 H             | 281                  | 56.0             | 42.1                     |
| 6                                                    | 11000.00        | 60.8 PK                 | 74.0           | -13.2       | 1.92 H             | 319                  | 42.2             | 18.6                     |
| 7                                                    | 11000.00        | 47.0 AV                 | 54.0           | -7.0        | 1.92 H             | 319                  | 28.4             | 18.6                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 5460.00         | 60.5 PK                 | 74.0           | -13.5       | 1.83 V             | 3                    | 54.2             | 6.3                      |
| 2                                                    | 5460.00         | 47.0 AV                 | 54.0           | -7.0        | 1.83 V             | 3                    | 40.7             | 6.3                      |
| 3                                                    | #5470.00        | 66.6 PK                 | 68.2           | -1.6        | 1.90 V             | 3                    | 60.3             | 6.3                      |
| 4                                                    | *5500.00        | 117.2 PK                |                |             | 1.82 V             | 5                    | 75.1             | 42.1                     |
| 5                                                    | *5500.00        | 106.7 AV                |                |             | 1.82 V             | 5                    | 64.6             | 42.1                     |
| 6                                                    | 11000.00        | 59.2 PK                 | 74.0           | -14.8       | 2.07 V             | 139                  | 40.6             | 18.6                     |
| 7                                                    | 11000.00        | 46.6 AV                 | 54.0           | -7.4        | 2.07 V             | 139                  | 28.0             | 18.6                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

|                 |              |                   |                           |
|-----------------|--------------|-------------------|---------------------------|
| RF Mode         | TX 802.11a   | Channel           | CH 116 : 5580 MHz         |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 5460.00         | 58.0 PK                 | 74.0           | -16.0       | 1.41 H             | 278                  | 51.7             | 6.3                      |
| 2                                                    | 5460.00         | 44.5 AV                 | 54.0           | -9.5        | 1.41 H             | 278                  | 38.2             | 6.3                      |
| 3                                                    | #5470.00        | 58.6 PK                 | 68.2           | -9.6        | 1.40 H             | 278                  | 52.3             | 6.3                      |
| 4                                                    | *5580.00        | 109.6 PK                |                |             | 1.36 H             | 277                  | 67.5             | 42.1                     |
| 5                                                    | *5580.00        | 99.4 AV                 |                |             | 1.36 H             | 277                  | 57.3             | 42.1                     |
| 6                                                    | 11160.00        | 60.6 PK                 | 74.0           | -13.4       | 1.77 H             | 312                  | 42.1             | 18.5                     |
| 7                                                    | 11160.00        | 47.1 AV                 | 54.0           | -6.9        | 1.77 H             | 312                  | 28.6             | 18.5                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 5460.00         | 60.0 PK                 | 74.0           | -14.0       | 1.76 V             | 2                    | 53.7             | 6.3                      |
| 2                                                    | 5460.00         | 48.2 AV                 | 54.0           | -5.8        | 1.76 V             | 2                    | 41.9             | 6.3                      |
| 3                                                    | #5470.00        | 61.0 PK                 | 68.2           | -7.2        | 1.74 V             | 5                    | 54.7             | 6.3                      |
| 4                                                    | *5580.00        | 117.4 PK                |                |             | 1.70 V             | 6                    | 75.3             | 42.1                     |
| 5                                                    | *5580.00        | 107.7 AV                |                |             | 1.70 V             | 6                    | 65.6             | 42.1                     |
| 6                                                    | 11160.00        | 59.3 PK                 | 74.0           | -14.7       | 2.31 V             | 93                   | 40.8             | 18.5                     |
| 7                                                    | 11160.00        | 45.8 AV                 | 54.0           | -8.2        | 2.31 V             | 93                   | 27.3             | 18.5                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

|                 |              |                   |                           |
|-----------------|--------------|-------------------|---------------------------|
| RF Mode         | TX 802.11a   | Channel           | CH 140 : 5700 MHz         |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *5700.00        | 105.8 PK                |                |             | 1.41 H             | 281                  | 63.5             | 42.3                     |
| 2                                                    | *5700.00        | 95.3 AV                 |                |             | 1.41 H             | 281                  | 53.0             | 42.3                     |
| 3                                                    | #5725.00        | 60.6 PK                 | 68.2           | -7.6        | 1.44 H             | 275                  | 54.1             | 6.5                      |
| 4                                                    | 11400.00        | 59.8 PK                 | 74.0           | -14.2       | 1.88 H             | 323                  | 41.9             | 17.9                     |
| 5                                                    | 11400.00        | 46.5 AV                 | 54.0           | -7.5        | 1.88 H             | 323                  | 28.6             | 17.9                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *5700.00        | 115.0 PK                |                |             | 1.96 V             | 5                    | 72.7             | 42.3                     |
| 2                                                    | *5700.00        | 105.7 AV                |                |             | 1.96 V             | 5                    | 63.4             | 42.3                     |
| 3                                                    | #5725.00        | 66.5 PK                 | 68.2           | -1.7        | 1.94 V             | 4                    | 60.0             | 6.5                      |
| 4                                                    | 11400.00        | 59.0 PK                 | 74.0           | -15.0       | 2.12 V             | 102                  | 41.1             | 17.9                     |
| 5                                                    | 11400.00        | 45.5 AV                 | 54.0           | -8.5        | 2.12 V             | 102                  | 27.6             | 17.9                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |              |                   |                           |
|-----------------|--------------|-------------------|---------------------------|
| RF Mode         | TX 802.11a   | Channel           | CH 144 : 5720 MHz         |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | #5470.00        | 58.2 PK                 | 68.2           | -10.0       | 1.36 H             | 278                  | 51.9             | 6.3                      |
| 2                                                    | *5720.00        | 106.5 PK                |                |             | 1.39 H             | 277                  | 64.3             | 42.2                     |
| 3                                                    | *5720.00        | 96.6 AV                 |                |             | 1.39 H             | 277                  | 54.4             | 42.2                     |
| 4                                                    | #5850.00        | 58.0 PK                 | 68.2           | -10.2       | 1.41 H             | 279                  | 51.2             | 6.8                      |
| 5                                                    | 11440.00        | 59.2 PK                 | 74.0           | -14.8       | 1.89 H             | 318                  | 41.2             | 18.0                     |
| 6                                                    | 11440.00        | 46.3 AV                 | 54.0           | -7.7        | 1.89 H             | 318                  | 28.3             | 18.0                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | #5470.00        | 58.8 PK                 | 68.2           | -9.4        | 1.88 V             | 1                    | 52.5             | 6.3                      |
| 2                                                    | *5720.00        | 115.6 PK                |                |             | 1.97 V             | 6                    | 73.4             | 42.2                     |
| 3                                                    | *5720.00        | 105.5 AV                |                |             | 1.97 V             | 6                    | 63.3             | 42.2                     |
| 4                                                    | #5850.00        | 59.2 PK                 | 68.2           | -9.0        | 1.78 V             | 7                    | 52.4             | 6.8                      |
| 5                                                    | 11440.00        | 59.2 PK                 | 74.0           | -14.8       | 2.35 V             | 117                  | 41.2             | 18.0                     |
| 6                                                    | 11440.00        | 46.1 AV                 | 54.0           | -7.9        | 2.35 V             | 117                  | 28.1             | 18.0                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

|                 |                     |                   |                           |
|-----------------|---------------------|-------------------|---------------------------|
| RF Mode         | TX 802.11ac (VHT20) | Channel           | CH 52 : 5260 MHz          |
| Frequency Range | 1GHz ~ 40GHz        | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *5260.00        | 108.7 PK                |                |             | 1.48 H             | 284                  | 66.8             | 41.9                     |
| 2                                                    | *5260.00        | 98.5 AV                 |                |             | 1.48 H             | 284                  | 56.6             | 41.9                     |
| 3                                                    | 5350.00         | 57.6 PK                 | 74.0           | -16.4       | 1.52 H             | 286                  | 51.2             | 6.4                      |
| 4                                                    | 5350.00         | 44.7 AV                 | 54.0           | -9.3        | 1.52 H             | 286                  | 38.3             | 6.4                      |
| 5                                                    | #10520.00       | 59.7 PK                 | 68.2           | -8.5        | 1.91 H             | 335                  | 42.1             | 17.6                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *5260.00        | 119.2 PK                |                |             | 1.65 V             | 3                    | 77.3             | 41.9                     |
| 2                                                    | *5260.00        | 108.9 AV                |                |             | 1.65 V             | 3                    | 67.0             | 41.9                     |
| 3                                                    | 5350.00         | 63.5 PK                 | 74.0           | -10.5       | 1.74 V             | 5                    | 57.1             | 6.4                      |
| 4                                                    | 5350.00         | 52.2 AV                 | 54.0           | -1.8        | 1.74 V             | 5                    | 45.8             | 6.4                      |
| 5                                                    | #10520.00       | 58.4 PK                 | 68.2           | -9.8        | 2.77 V             | 81                   | 40.8             | 17.6                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |                     |                   |                           |
|-----------------|---------------------|-------------------|---------------------------|
| RF Mode         | TX 802.11ac (VHT20) | Channel           | CH 60 : 5300 MHz          |
| Frequency Range | 1GHz ~ 40GHz        | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *5300.00        | 108.6 PK                |                |             | 1.29 H             | 293                  | 66.7             | 41.9                     |
| 2                                                    | *5300.00        | 98.6 AV                 |                |             | 1.29 H             | 293                  | 56.7             | 41.9                     |
| 3                                                    | 10600.00        | 59.0 PK                 | 74.0           | -15.0       | 1.91 H             | 341                  | 41.8             | 17.2                     |
| 4                                                    | 10600.00        | 45.9 AV                 | 54.0           | -8.1        | 1.91 H             | 341                  | 28.7             | 17.2                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *5300.00        | 119.4 PK                |                |             | 1.73 V             | 3                    | 77.5             | 41.9                     |
| 2                                                    | *5300.00        | 109.3 AV                |                |             | 1.73 V             | 3                    | 67.4             | 41.9                     |
| 3                                                    | 10600.00        | 58.0 PK                 | 74.0           | -16.0       | 2.78 V             | 82                   | 40.8             | 17.2                     |
| 4                                                    | 10600.00        | 45.5 AV                 | 54.0           | -8.5        | 2.78 V             | 82                   | 28.3             | 17.2                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.

|                 |                     |                   |                           |
|-----------------|---------------------|-------------------|---------------------------|
| RF Mode         | TX 802.11ac (VHT20) | Channel           | CH 64 : 5320 MHz          |
| Frequency Range | 1GHz ~ 40GHz        | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *5320.00        | 105.9 PK                |                |             | 1.38 H             | 288                  | 63.9             | 42.0                     |
| 2                                                    | *5320.00        | 95.8 AV                 |                |             | 1.38 H             | 288                  | 53.8             | 42.0                     |
| 3                                                    | 5350.00         | 57.9 PK                 | 74.0           | -16.1       | 1.42 H             | 291                  | 51.5             | 6.4                      |
| 4                                                    | 5350.00         | 44.9 AV                 | 54.0           | -9.1        | 1.42 H             | 291                  | 38.5             | 6.4                      |
| 5                                                    | 10640.00        | 58.9 PK                 | 74.0           | -15.1       | 1.92 H             | 341                  | 41.5             | 17.4                     |
| 6                                                    | 10640.00        | 45.9 AV                 | 54.0           | -8.1        | 1.92 H             | 341                  | 28.5             | 17.4                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *5320.00        | 115.6 PK                |                |             | 1.67 V             | 4                    | 73.6             | 42.0                     |
| 2                                                    | *5320.00        | 105.7 AV                |                |             | 1.67 V             | 4                    | 63.7             | 42.0                     |
| 3                                                    | 5350.00         | 66.6 PK                 | 74.0           | -7.4        | 1.61 V             | 2                    | 60.2             | 6.4                      |
| 4                                                    | 5350.00         | 52.2 AV                 | 54.0           | -1.8        | 1.61 V             | 2                    | 45.8             | 6.4                      |
| 5                                                    | 10640.00        | 58.3 PK                 | 74.0           | -15.7       | 2.78 V             | 82                   | 40.9             | 17.4                     |
| 6                                                    | 10640.00        | 45.8 AV                 | 54.0           | -8.2        | 2.78 V             | 82                   | 28.4             | 17.4                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency.

|                 |                     |                   |                           |
|-----------------|---------------------|-------------------|---------------------------|
| RF Mode         | TX 802.11ac (VHT20) | Channel           | CH 100 : 5500 MHz         |
| Frequency Range | 1GHz ~ 40GHz        | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 5460.00         | 58.0 PK                 | 74.0           | -16.0       | 1.40 H             | 279                  | 51.7             | 6.3                      |
| 2                                                    | 5460.00         | 44.3 AV                 | 54.0           | -9.7        | 1.40 H             | 279                  | 38.0             | 6.3                      |
| 3                                                    | #5470.00        | 58.8 PK                 | 68.2           | -9.4        | 1.38 H             | 280                  | 52.5             | 6.3                      |
| 4                                                    | *5500.00        | 107.4 PK                |                |             | 1.38 H             | 281                  | 65.3             | 42.1                     |
| 5                                                    | *5500.00        | 97.3 AV                 |                |             | 1.38 H             | 281                  | 55.2             | 42.1                     |
| 6                                                    | 11000.00        | 60.3 PK                 | 74.0           | -13.7       | 1.73 H             | 310                  | 41.7             | 18.6                     |
| 7                                                    | 11000.00        | 47.0 AV                 | 54.0           | -7.0        | 1.73 H             | 310                  | 28.4             | 18.6                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 5460.00         | 60.6 PK                 | 74.0           | -13.4       | 1.86 V             | 3                    | 54.3             | 6.3                      |
| 2                                                    | 5460.00         | 47.3 AV                 | 54.0           | -6.7        | 1.86 V             | 3                    | 41.0             | 6.3                      |
| 3                                                    | #5470.00        | 67.2 PK                 | 68.2           | -1.0        | 1.90 V             | 1                    | 60.9             | 6.3                      |
| 4                                                    | *5500.00        | 117.0 PK                |                |             | 1.80 V             | 6                    | 74.9             | 42.1                     |
| 5                                                    | *5500.00        | 106.9 AV                |                |             | 1.80 V             | 6                    | 64.8             | 42.1                     |
| 6                                                    | 11000.00        | 60.6 PK                 | 74.0           | -13.4       | 2.33 V             | 97                   | 42.0             | 18.6                     |
| 7                                                    | 11000.00        | 46.1 AV                 | 54.0           | -7.9        | 2.33 V             | 97                   | 27.5             | 18.6                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

|                 |                     |                   |                           |
|-----------------|---------------------|-------------------|---------------------------|
| RF Mode         | TX 802.11ac (VHT20) | Channel           | CH 116 : 5580 MHz         |
| Frequency Range | 1GHz ~ 40GHz        | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 5460.00         | 57.6 PK                 | 74.0           | -16.4       | 1.40 H             | 279                  | 51.3             | 6.3                      |
| 2                                                    | 5460.00         | 44.3 AV                 | 54.0           | -9.7        | 1.40 H             | 279                  | 38.0             | 6.3                      |
| 3                                                    | #5470.00        | 58.2 PK                 | 68.2           | -10.0       | 1.35 H             | 271                  | 51.9             | 6.3                      |
| 4                                                    | *5580.00        | 109.1 PK                |                |             | 1.37 H             | 277                  | 67.0             | 42.1                     |
| 5                                                    | *5580.00        | 99.3 AV                 |                |             | 1.37 H             | 277                  | 57.2             | 42.1                     |
| 6                                                    | 11160.00        | 60.6 PK                 | 74.0           | -13.4       | 1.83 H             | 336                  | 42.1             | 18.5                     |
| 7                                                    | 11160.00        | 47.0 AV                 | 54.0           | -7.0        | 1.83 H             | 336                  | 28.5             | 18.5                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 5460.00         | 60.3 PK                 | 74.0           | -13.7       | 1.80 V             | 6                    | 54.0             | 6.3                      |
| 2                                                    | 5460.00         | 47.5 AV                 | 54.0           | -6.5        | 1.80 V             | 6                    | 41.2             | 6.3                      |
| 3                                                    | #5470.00        | 59.5 PK                 | 68.2           | -8.7        | 1.78 V             | 3                    | 53.2             | 6.3                      |
| 4                                                    | *5580.00        | 117.8 PK                |                |             | 1.77 V             | 2                    | 75.7             | 42.1                     |
| 5                                                    | *5580.00        | 107.6 AV                |                |             | 1.77 V             | 2                    | 65.5             | 42.1                     |
| 6                                                    | 11160.00        | 59.5 PK                 | 74.0           | -14.5       | 2.23 V             | 95                   | 41.0             | 18.5                     |
| 7                                                    | 11160.00        | 46.0 AV                 | 54.0           | -8.0        | 2.23 V             | 95                   | 27.5             | 18.5                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

|                 |                     |                   |                           |
|-----------------|---------------------|-------------------|---------------------------|
| RF Mode         | TX 802.11ac (VHT20) | Channel           | CH 140 : 5700 MHz         |
| Frequency Range | 1GHz ~ 40GHz        | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *5700.00        | 106.0 PK                |                |             | 1.41 H             | 277                  | 63.7             | 42.3                     |
| 2                                                    | *5700.00        | 95.1 AV                 |                |             | 1.41 H             | 277                  | 52.8             | 42.3                     |
| 3                                                    | #5725.00        | 58.4 PK                 | 68.2           | -9.8        | 1.44 H             | 280                  | 51.9             | 6.5                      |
| 4                                                    | 11400.00        | 59.1 PK                 | 74.0           | -14.9       | 1.79 H             | 335                  | 41.2             | 17.9                     |
| 5                                                    | 11400.00        | 45.9 AV                 | 54.0           | -8.1        | 1.79 H             | 335                  | 28.0             | 17.9                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *5700.00        | 114.9 PK                |                |             | 1.91 V             | 4                    | 72.6             | 42.3                     |
| 2                                                    | *5700.00        | 104.9 AV                |                |             | 1.91 V             | 4                    | 62.6             | 42.3                     |
| 3                                                    | #5725.00        | 66.6 PK                 | 68.2           | -1.6        | 1.99 V             | 7                    | 60.1             | 6.5                      |
| 4                                                    | 11400.00        | 59.1 PK                 | 74.0           | -14.9       | 2.40 V             | 99                   | 41.2             | 17.9                     |
| 5                                                    | 11400.00        | 45.2 AV                 | 54.0           | -8.8        | 2.40 V             | 99                   | 27.3             | 17.9                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |                     |                   |                           |
|-----------------|---------------------|-------------------|---------------------------|
| RF Mode         | TX 802.11ac (VHT20) | Channel           | CH 144 : 5720 MHz         |
| Frequency Range | 1GHz ~ 40GHz        | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | #5470.00        | 58.1 PK                 | 68.2           | -10.1       | 1.41 H             | 272                  | 51.8             | 6.3                      |
| 2                                                    | *5720.00        | 105.3 PK                |                |             | 1.45 H             | 269                  | 63.1             | 42.2                     |
| 3                                                    | *5720.00        | 95.1 AV                 |                |             | 1.45 H             | 269                  | 52.9             | 42.2                     |
| 4                                                    | #5850.00        | 58.6 PK                 | 68.2           | -9.6        | 1.49 H             | 272                  | 51.8             | 6.8                      |
| 5                                                    | 11440.00        | 60.0 PK                 | 74.0           | -14.0       | 1.72 H             | 321                  | 42.0             | 18.0                     |
| 6                                                    | 11440.00        | 46.1 AV                 | 54.0           | -7.9        | 1.72 H             | 321                  | 28.1             | 18.0                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | #5470.00        | 63.2 PK                 | 68.2           | -5.0        | 1.75 V             | 2                    | 56.9             | 6.3                      |
| 2                                                    | *5720.00        | 116.6 PK                |                |             | 1.98 V             | 6                    | 74.4             | 42.2                     |
| 3                                                    | *5720.00        | 106.4 AV                |                |             | 1.98 V             | 6                    | 64.2             | 42.2                     |
| 4                                                    | #5850.00        | 60.3 PK                 | 68.2           | -7.9        | 1.80 V             | 10                   | 53.5             | 6.8                      |
| 5                                                    | 11440.00        | 59.6 PK                 | 74.0           | -14.4       | 2.16 V             | 112                  | 41.6             | 18.0                     |
| 6                                                    | 11440.00        | 45.2 AV                 | 54.0           | -8.8        | 2.16 V             | 112                  | 27.2             | 18.0                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

|                 |                     |                   |                           |
|-----------------|---------------------|-------------------|---------------------------|
| RF Mode         | TX 802.11ac (VHT40) | Channel           | CH 54 : 5270 MHz          |
| Frequency Range | 1GHz ~ 40GHz        | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 5150.00         | 58.0 PK                 | 74.0           | -16.0       | 1.35 H             | 279                  | 51.4             | 6.6                      |
| 2                                                    | 5150.00         | 44.8 AV                 | 54.0           | -9.2        | 1.35 H             | 279                  | 38.2             | 6.6                      |
| 3                                                    | *5270.00        | 105.5 PK                |                |             | 1.21 H             | 295                  | 63.6             | 41.9                     |
| 4                                                    | *5270.00        | 95.5 AV                 |                |             | 1.21 H             | 295                  | 53.6             | 41.9                     |
| 5                                                    | 5350.00         | 57.7 PK                 | 74.0           | -16.3       | 1.45 H             | 285                  | 51.3             | 6.4                      |
| 6                                                    | 5350.00         | 45.0 AV                 | 54.0           | -9.0        | 1.45 H             | 285                  | 38.6             | 6.4                      |
| 7                                                    | #10540.00       | 59.4 PK                 | 68.2           | -8.8        | 2.00 H             | 350                  | 41.8             | 17.6                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 5150.00         | 60.8 PK                 | 74.0           | -13.2       | 1.65 V             | 5                    | 54.2             | 6.6                      |
| 2                                                    | 5150.00         | 47.8 AV                 | 54.0           | -6.2        | 1.65 V             | 5                    | 41.2             | 6.6                      |
| 3                                                    | *5270.00        | 117.1 PK                |                |             | 1.73 V             | 3                    | 75.2             | 41.9                     |
| 4                                                    | *5270.00        | 106.7 AV                |                |             | 1.73 V             | 3                    | 64.8             | 41.9                     |
| 5                                                    | 5350.00         | 65.2 PK                 | 74.0           | -8.8        | 1.94 V             | 1                    | 58.8             | 6.4                      |
| 6                                                    | 5350.00         | 52.4 AV                 | 54.0           | -1.6        | 1.94 V             | 1                    | 46.0             | 6.4                      |
| 7                                                    | #10540.00       | 58.6 PK                 | 68.2           | -9.6        | 2.67 V             | 85                   | 41.0             | 17.6                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

|                 |                     |                   |                           |
|-----------------|---------------------|-------------------|---------------------------|
| RF Mode         | TX 802.11ac (VHT40) | Channel           | CH 62 : 5310 MHz          |
| Frequency Range | 1GHz ~ 40GHz        | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *5310.00        | 103.4 PK                |                |             | 1.40 H             | 292                  | 61.4             | 42.0                     |
| 2                                                    | *5310.00        | 92.9 AV                 |                |             | 1.40 H             | 292                  | 50.9             | 42.0                     |
| 3                                                    | 5350.00         | 58.2 PK                 | 74.0           | -15.8       | 1.26 H             | 285                  | 51.8             | 6.4                      |
| 4                                                    | 5350.00         | 45.5 AV                 | 54.0           | -8.5        | 1.26 H             | 285                  | 39.1             | 6.4                      |
| 5                                                    | 10620.00        | 58.6 PK                 | 74.0           | -15.4       | 1.90 H             | 329                  | 41.2             | 17.4                     |
| 6                                                    | 10620.00        | 45.7 AV                 | 54.0           | -8.3        | 1.90 H             | 329                  | 28.3             | 17.4                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *5310.00        | 113.7 PK                |                |             | 1.71 V             | 2                    | 71.7             | 42.0                     |
| 2                                                    | *5310.00        | 103.0 AV                |                |             | 1.71 V             | 2                    | 61.0             | 42.0                     |
| 3                                                    | 5350.00         | 67.1 PK                 | 74.0           | -6.9        | 1.59 V             | 3                    | 60.7             | 6.4                      |
| 4                                                    | 5350.00         | 52.7 AV                 | 54.0           | -1.3        | 1.59 V             | 3                    | 46.3             | 6.4                      |
| 5                                                    | 10620.00        | 59.6 PK                 | 74.0           | -14.4       | 2.59 V             | 87                   | 42.2             | 17.4                     |
| 6                                                    | 10620.00        | 45.6 AV                 | 54.0           | -8.4        | 2.59 V             | 87                   | 28.2             | 17.4                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency.

|                 |                     |                   |                           |
|-----------------|---------------------|-------------------|---------------------------|
| RF Mode         | TX 802.11ac (VHT40) | Channel           | CH 102 : 5510 MHz         |
| Frequency Range | 1GHz ~ 40GHz        | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 5460.00         | 57.8 PK                 | 74.0           | -16.2       | 1.41 H             | 280                  | 51.5             | 6.3                      |
| 2                                                    | 5460.00         | 44.7 AV                 | 54.0           | -9.3        | 1.41 H             | 280                  | 38.4             | 6.3                      |
| 3                                                    | #5470.00        | 57.9 PK                 | 68.2           | -10.3       | 1.39 H             | 281                  | 51.6             | 6.3                      |
| 4                                                    | *5510.00        | 103.0 PK                |                |             | 1.33 H             | 277                  | 60.9             | 42.1                     |
| 5                                                    | *5510.00        | 92.8 AV                 |                |             | 1.33 H             | 277                  | 50.7             | 42.1                     |
| 6                                                    | 11020.00        | 60.3 PK                 | 74.0           | -13.7       | 1.93 H             | 345                  | 41.7             | 18.6                     |
| 7                                                    | 11020.00        | 46.9 AV                 | 54.0           | -7.1        | 1.93 H             | 345                  | 28.3             | 18.6                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 5460.00         | 60.3 PK                 | 74.0           | -13.7       | 1.90 V             | 4                    | 54.0             | 6.3                      |
| 2                                                    | 5460.00         | 47.8 AV                 | 54.0           | -6.2        | 1.90 V             | 4                    | 41.5             | 6.3                      |
| 3                                                    | #5470.00        | 66.6 PK                 | 68.2           | -1.6        | 1.78 V             | 3                    | 60.3             | 6.3                      |
| 4                                                    | *5510.00        | 113.2 PK                |                |             | 1.81 V             | 3                    | 71.1             | 42.1                     |
| 5                                                    | *5510.00        | 102.4 AV                |                |             | 1.81 V             | 3                    | 60.3             | 42.1                     |
| 6                                                    | 11020.00        | 60.6 PK                 | 74.0           | -13.4       | 2.35 V             | 100                  | 42.0             | 18.6                     |
| 7                                                    | 11020.00        | 45.9 AV                 | 54.0           | -8.1        | 2.35 V             | 100                  | 27.3             | 18.6                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

|                 |                     |                   |                           |
|-----------------|---------------------|-------------------|---------------------------|
| RF Mode         | TX 802.11ac (VHT40) | Channel           | CH 110 : 5550 MHz         |
| Frequency Range | 1GHz ~ 40GHz        | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 5460.00         | 57.4 PK                 | 74.0           | -16.6       | 1.37 H             | 282                  | 51.1             | 6.3                      |
| 2                                                    | 5460.00         | 44.5 AV                 | 54.0           | -9.5        | 1.37 H             | 282                  | 38.2             | 6.3                      |
| 3                                                    | #5470.00        | 58.0 PK                 | 68.2           | -10.2       | 1.40 H             | 279                  | 51.7             | 6.3                      |
| 4                                                    | *5550.00        | 105.5 PK                |                |             | 1.35 H             | 282                  | 63.4             | 42.1                     |
| 5                                                    | *5550.00        | 95.3 AV                 |                |             | 1.35 H             | 282                  | 53.2             | 42.1                     |
| 6                                                    | 11100.00        | 60.0 PK                 | 74.0           | -14.0       | 1.89 H             | 340                  | 41.7             | 18.3                     |
| 7                                                    | 11100.00        | 46.6 AV                 | 54.0           | -7.4        | 1.89 H             | 340                  | 28.3             | 18.3                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 5460.00         | 60.1 PK                 | 74.0           | -13.9       | 1.75 V             | 5                    | 53.8             | 6.3                      |
| 2                                                    | 5460.00         | 47.2 AV                 | 54.0           | -6.8        | 1.75 V             | 5                    | 40.9             | 6.3                      |
| 3                                                    | #5470.00        | 64.6 PK                 | 68.2           | -3.6        | 1.77 V             | 3                    | 58.3             | 6.3                      |
| 4                                                    | *5550.00        | 115.1 PK                |                |             | 1.87 V             | 3                    | 73.0             | 42.1                     |
| 5                                                    | *5550.00        | 104.5 AV                |                |             | 1.87 V             | 3                    | 62.4             | 42.1                     |
| 6                                                    | 11100.00        | 59.6 PK                 | 74.0           | -14.4       | 2.33 V             | 92                   | 41.3             | 18.3                     |
| 7                                                    | 11100.00        | 46.3 AV                 | 54.0           | -7.7        | 2.33 V             | 92                   | 28.0             | 18.3                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

|                 |                     |                   |                           |
|-----------------|---------------------|-------------------|---------------------------|
| RF Mode         | TX 802.11ac (VHT40) | Channel           | CH 134 : 5670 MHz         |
| Frequency Range | 1GHz ~ 40GHz        | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *5670.00        | 103.1 PK                |                |             | 1.36 H             | 276                  | 60.9             | 42.2                     |
| 2                                                    | *5670.00        | 93.0 AV                 |                |             | 1.36 H             | 276                  | 50.8             | 42.2                     |
| 3                                                    | #5725.00        | 59.5 PK                 | 68.2           | -8.7        | 1.32 H             | 270                  | 53.0             | 6.5                      |
| 4                                                    | 11340.00        | 59.1 PK                 | 74.0           | -14.9       | 1.92 H             | 333                  | 41.0             | 18.1                     |
| 5                                                    | 11340.00        | 46.3 AV                 | 54.0           | -7.7        | 1.92 H             | 333                  | 28.2             | 18.1                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *5670.00        | 112.3 PK                |                |             | 1.93 V             | 4                    | 70.1             | 42.2                     |
| 2                                                    | *5670.00        | 101.7 AV                |                |             | 1.93 V             | 4                    | 59.5             | 42.2                     |
| 3                                                    | #5725.00        | 66.5 PK                 | 68.2           | -1.7        | 1.82 V             | 9                    | 60.0             | 6.5                      |
| 4                                                    | 11340.00        | 58.6 PK                 | 74.0           | -15.4       | 2.13 V             | 99                   | 40.5             | 18.1                     |
| 5                                                    | 11340.00        | 45.0 AV                 | 54.0           | -9.0        | 2.13 V             | 99                   | 26.9             | 18.1                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |                     |                   |                           |
|-----------------|---------------------|-------------------|---------------------------|
| RF Mode         | TX 802.11ac (VHT40) | Channel           | CH 142 : 5710 MHz         |
| Frequency Range | 1GHz ~ 40GHz        | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | #5470.00        | 58.0 PK                 | 68.2           | -10.2       | 1.40 H             | 278                  | 51.7             | 6.3                      |
| 2                                                    | *5710.00        | 104.0 PK                |                |             | 1.41 H             | 276                  | 61.7             | 42.3                     |
| 3                                                    | *5710.00        | 93.2 AV                 |                |             | 1.41 H             | 276                  | 50.9             | 42.3                     |
| 4                                                    | #5850.00        | 58.3 PK                 | 68.2           | -9.9        | 1.44 H             | 280                  | 51.5             | 6.8                      |
| 5                                                    | 11420.00        | 59.8 PK                 | 74.0           | -14.2       | 1.96 H             | 342                  | 41.9             | 17.9                     |
| 6                                                    | 11420.00        | 46.5 AV                 | 54.0           | -7.5        | 1.96 H             | 342                  | 28.6             | 17.9                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | #5470.00        | 63.1 PK                 | 68.2           | -5.1        | 1.97 V             | 2                    | 56.8             | 6.3                      |
| 2                                                    | *5710.00        | 114.2 PK                |                |             | 1.99 V             | 6                    | 71.9             | 42.3                     |
| 3                                                    | *5710.00        | 102.9 AV                |                |             | 1.99 V             | 6                    | 60.6             | 42.3                     |
| 4                                                    | #5850.00        | 60.3 PK                 | 68.2           | -7.9        | 1.68 V             | 10                   | 53.5             | 6.8                      |
| 5                                                    | 11420.00        | 58.4 PK                 | 74.0           | -15.6       | 2.20 V             | 106                  | 40.5             | 17.9                     |
| 6                                                    | 11420.00        | 44.8 AV                 | 54.0           | -9.2        | 2.20 V             | 106                  | 26.9             | 17.9                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

|                 |                     |                   |                           |
|-----------------|---------------------|-------------------|---------------------------|
| RF Mode         | TX 802.11ac (VHT80) | Channel           | CH 58 : 5290 MHz          |
| Frequency Range | 1GHz ~ 40GHz        | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 5150.00         | 57.7 PK                 | 74.0           | -16.3       | 1.37 H             | 296                  | 51.1             | 6.6                      |
| 2                                                    | 5150.00         | 45.3 AV                 | 54.0           | -8.7        | 1.37 H             | 296                  | 38.7             | 6.6                      |
| 3                                                    | *5290.00        | 89.0 PK                 |                |             | 1.29 H             | 289                  | 47.1             | 41.9                     |
| 4                                                    | *5290.00        | 78.2 AV                 |                |             | 1.29 H             | 289                  | 36.3             | 41.9                     |
| 5                                                    | 5350.00         | 57.2 PK                 | 74.0           | -16.8       | 2.91 H             | 139                  | 50.8             | 6.4                      |
| 6                                                    | 5350.00         | 45.7 AV                 | 54.0           | -8.3        | 2.91 H             | 139                  | 39.3             | 6.4                      |
| 7                                                    | #10580.00       | 59.0 PK                 | 68.2           | -9.2        | 1.93 H             | 333                  | 41.6             | 17.4                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 5150.00         | 57.6 PK                 | 74.0           | -16.4       | 1.77 V             | 360                  | 51.0             | 6.6                      |
| 2                                                    | 5150.00         | 45.7 AV                 | 54.0           | -8.3        | 1.77 V             | 360                  | 39.1             | 6.6                      |
| 3                                                    | *5290.00        | 98.7 PK                 |                |             | 1.69 V             | 4                    | 56.8             | 41.9                     |
| 4                                                    | *5290.00        | 87.8 AV                 |                |             | 1.69 V             | 4                    | 45.9             | 41.9                     |
| 5                                                    | 5350.00         | 66.8 PK                 | 74.0           | -7.2        | 1.81 V             | 3                    | 60.4             | 6.4                      |
| 6                                                    | 5350.00         | 52.8 AV                 | 54.0           | -1.2        | 1.81 V             | 3                    | 46.4             | 6.4                      |
| 7                                                    | #10580.00       | 59.4 PK                 | 68.2           | -8.8        | 2.61 V             | 88                   | 42.0             | 17.4                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

|                 |                     |                   |                           |
|-----------------|---------------------|-------------------|---------------------------|
| RF Mode         | TX 802.11ac (VHT80) | Channel           | CH 106 : 5530 MHz         |
| Frequency Range | 1GHz ~ 40GHz        | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 5460.00         | 57.5 PK                 | 74.0           | -16.5       | 1.39 H             | 283                  | 51.2             | 6.3                      |
| 2                                                    | 5460.00         | 45.3 AV                 | 54.0           | -8.7        | 1.39 H             | 283                  | 39.0             | 6.3                      |
| 3                                                    | #5470.00        | 58.8 PK                 | 68.2           | -9.4        | 1.41 H             | 277                  | 52.5             | 6.3                      |
| 4                                                    | *5530.00        | 93.1 PK                 |                |             | 1.37 H             | 276                  | 51.0             | 42.1                     |
| 5                                                    | *5530.00        | 83.2 AV                 |                |             | 1.37 H             | 276                  | 41.1             | 42.1                     |
| 6                                                    | #5725.00        | 58.8 PK                 | 68.2           | -9.4        | 1.40 H             | 281                  | 52.3             | 6.5                      |
| 7                                                    | 11060.00        | 59.7 PK                 | 74.0           | -14.3       | 1.82 H             | 316                  | 41.3             | 18.4                     |
| 8                                                    | 11060.00        | 46.6 AV                 | 54.0           | -7.4        | 1.82 H             | 316                  | 28.2             | 18.4                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 5460.00         | 62.7 PK                 | 74.0           | -11.3       | 1.79 V             | 3                    | 56.4             | 6.3                      |
| 2                                                    | 5460.00         | 47.0 AV                 | 54.0           | -7.0        | 1.79 V             | 3                    | 40.7             | 6.3                      |
| 3                                                    | #5470.00        | 66.5 PK                 | 68.2           | -1.7        | 1.63 V             | 4                    | 60.2             | 6.3                      |
| 4                                                    | *5530.00        | 102.8 PK                |                |             | 1.80 V             | 3                    | 60.7             | 42.1                     |
| 5                                                    | *5530.00        | 92.5 AV                 |                |             | 1.80 V             | 3                    | 50.4             | 42.1                     |
| 6                                                    | #5725.00        | 59.3 PK                 | 68.2           | -8.9        | 1.83 V             | 5                    | 52.8             | 6.5                      |
| 7                                                    | 11060.00        | 60.1 PK                 | 74.0           | -13.9       | 2.33 V             | 90                   | 41.7             | 18.4                     |
| 8                                                    | 11060.00        | 46.4 AV                 | 54.0           | -7.6        | 2.33 V             | 90                   | 28.0             | 18.4                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |                     |                   |                           |
|-----------------|---------------------|-------------------|---------------------------|
| RF Mode         | TX 802.11ac (VHT80) | Channel           | CH 122 : 5610 MHz         |
| Frequency Range | 1GHz ~ 40GHz        | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 5460.00         | 58.0 PK                 | 74.0           | -16.0       | 1.37 H             | 283                  | 51.7             | 6.3                      |
| 2                                                    | 5460.00         | 45.3 AV                 | 54.0           | -8.7        | 1.37 H             | 283                  | 39.0             | 6.3                      |
| 3                                                    | #5470.00        | 58.7 PK                 | 68.2           | -9.5        | 1.41 H             | 279                  | 52.4             | 6.3                      |
| 4                                                    | *5610.00        | 100.8 PK                |                |             | 1.34 H             | 278                  | 58.7             | 42.1                     |
| 5                                                    | *5610.00        | 90.9 AV                 |                |             | 1.34 H             | 278                  | 48.8             | 42.1                     |
| 6                                                    | #5725.00        | 57.8 PK                 | 68.2           | -10.4       | 1.38 H             | 280                  | 51.3             | 6.5                      |
| 7                                                    | 11220.00        | 58.6 PK                 | 74.0           | -15.4       | 1.85 H             | 320                  | 40.1             | 18.5                     |
| 8                                                    | 11220.00        | 45.7 AV                 | 54.0           | -8.3        | 1.85 H             | 320                  | 27.2             | 18.5                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 5460.00         | 60.3 PK                 | 74.0           | -13.7       | 1.70 V             | 3                    | 54.0             | 6.3                      |
| 2                                                    | 5460.00         | 48.6 AV                 | 54.0           | -5.4        | 1.70 V             | 3                    | 42.3             | 6.3                      |
| 3                                                    | #5470.00        | 62.3 PK                 | 68.2           | -5.9        | 1.79 V             | 6                    | 56.0             | 6.3                      |
| 4                                                    | *5610.00        | 109.8 PK                |                |             | 1.63 V             | 4                    | 67.7             | 42.1                     |
| 5                                                    | *5610.00        | 99.3 AV                 |                |             | 1.63 V             | 4                    | 57.2             | 42.1                     |
| 6                                                    | #5725.00        | 66.5 PK                 | 68.2           | -1.7        | 1.85 V             | 4                    | 60.0             | 6.5                      |
| 7                                                    | 11220.00        | 60.4 PK                 | 74.0           | -13.6       | 2.03 V             | 102                  | 41.9             | 18.5                     |
| 8                                                    | 11220.00        | 45.8 AV                 | 54.0           | -8.2        | 2.03 V             | 102                  | 27.3             | 18.5                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |                     |                   |                           |
|-----------------|---------------------|-------------------|---------------------------|
| RF Mode         | TX 802.11ac (VHT80) | Channel           | CH 138 : 5690 MHz         |
| Frequency Range | 1GHz ~ 40GHz        | Detector Function | Peak (PK)<br>Average (AV) |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | #5470.00        | 58.1 PK                 | 68.2           | -10.1       | 1.34 H             | 289                  | 51.8             | 6.3                      |
| 2                                                    | *5690.00        | 101.7 PK                |                |             | 1.37 H             | 279                  | 59.4             | 42.3                     |
| 3                                                    | *5690.00        | 91.8 AV                 |                |             | 1.37 H             | 279                  | 49.5             | 42.3                     |
| 4                                                    | #5850.00        | 58.4 PK                 | 68.2           | -9.8        | 1.33 H             | 291                  | 51.6             | 6.8                      |
| 5                                                    | 11380.00        | 57.0 PK                 | 74.0           | -17.0       | 3.02 H             | 87                   | 39.2             | 17.8                     |
| 6                                                    | 11380.00        | 45.1 AV                 | 54.0           | -8.9        | 3.02 H             | 87                   | 27.3             | 17.8                     |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | #5470.00        | 62.5 PK                 | 68.2           | -5.7        | 1.81 V             | 4                    | 56.2             | 6.3                      |
| 2                                                    | *5690.00        | 111.0 PK                |                |             | 1.74 V             | 4                    | 68.7             | 42.3                     |
| 3                                                    | *5690.00        | 100.3 AV                |                |             | 1.74 V             | 4                    | 58.0             | 42.3                     |
| 4                                                    | #5850.00        | 63.1 PK                 | 68.2           | -5.1        | 2.16 V             | 7                    | 56.3             | 6.8                      |
| 5                                                    | 11380.00        | 59.4 PK                 | 74.0           | -14.6       | 1.93 V             | 121                  | 41.6             | 17.8                     |
| 6                                                    | 11380.00        | 45.0 AV                 | 54.0           | -9.0        | 1.93 V             | 121                  | 27.2             | 17.8                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

# Below 1GHz Worst-Case Data:


## 5G traffic radio (Radio 2)

|                 |                    |                   |                  |
|-----------------|--------------------|-------------------|------------------|
| RF Mode         | TX 802.11ax (HE20) | Channel           | CH 60 : 5300 MHz |
| Frequency Range | 30MHz ~ 1GHz       | Detector Function | Quasi-Peak (QP)  |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|-----------------------------------------------------|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 45.46       | 29.4 QP                 | 40.0           | -10.6       | 1.50 H             | 117                  | 38.5             | -9.1                     |
| 2                                                   | 80.61       | 30.9 QP                 | 40.0           | -9.1        | 2.00 H             | 132                  | 44.4             | -13.5                    |
| 3                                                   | 135.43      | 37.6 QP                 | 43.5           | -5.9        | 2.00 H             | 56                   | 47.0             | -9.4                     |
| 4                                                   | 208.54      | 27.8 QP                 | 43.5           | -15.7       | 1.50 H             | 71                   | 38.8             | -11.0                    |
| 5                                                   | 374.42      | 28.1 QP                 | 46.0           | -17.9       | 1.00 H             | 222                  | 33.2             | -5.1                     |
| 6                                                   | 555.77      | 30.3 QP                 | 46.0           | -15.7       | 1.50 H             | 153                  | 31.4             | -1.1                     |

### Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. The other emission levels were very low against the limit of frequency range 30MHz ~ 1000MHz.
4. Margin value = Emission Level – Limit value.
5. The emission levels were very low against the limit of frequency range 9kHz ~ 30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




|                 |                    |                   |                  |
|-----------------|--------------------|-------------------|------------------|
| RF Mode         | TX 802.11ax (HE20) | Channel           | CH 60 : 5300 MHz |
| Frequency Range | 30MHz ~ 1GHz       | Detector Function | Quasi-Peak (QP)  |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|---------------------------------------------------|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.                                               | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                 | 60.93       | 39.6 QP                 | 40.0           | -0.4        | 1.00 V             | 301                  | 49.4             | -9.8                     |
| 2                                                 | 80.61       | 33.2 QP                 | 40.0           | -6.8        | 1.50 V             | 5                    | 46.7             | -13.5                    |
| 3                                                 | 186.04      | 28.8 QP                 | 43.5           | -14.7       | 1.00 V             | 160                  | 39.3             | -10.5                    |
| 4                                                 | 278.83      | 24.9 QP                 | 46.0           | -21.1       | 1.50 V             | 176                  | 31.9             | -7.0                     |
| 5                                                 | 356.14      | 30.3 QP                 | 46.0           | -15.7       | 1.50 V             | 5                    | 35.8             | -5.5                     |
| 6                                                 | 506.57      | 34.5 QP                 | 46.0           | -11.5       | 1.00 V             | 324                  | 36.7             | -2.2                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. The other emission levels were very low against the limit of frequency range 30MHz ~ 1000MHz.
4. Margin value = Emission Level – Limit value.
5. The emission levels were very low against the limit of frequency range 9kHz ~ 30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




### Scanning radio (Radio 3)

|                 |                     |                   |                  |
|-----------------|---------------------|-------------------|------------------|
| RF Mode         | TX 802.11ac (VHT20) | Channel           | CH 60 : 5300 MHz |
| Frequency Range | 30MHz ~ 1GHz        | Detector Function | Quasi-Peak (QP)  |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|-----------------------------------------------------|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 48.28       | 29.2 QP                 | 40.0           | -10.8       | 1.50 H             | 96                   | 38.3             | -9.1                     |
| 2                                                   | 77.80       | 29.4 QP                 | 40.0           | -10.6       | 1.50 H             | 249                  | 42.2             | -12.8                    |
| 3                                                   | 157.93      | 34.8 QP                 | 43.5           | -8.7        | 1.50 H             | 210                  | 43.2             | -8.4                     |
| 4                                                   | 280.23      | 25.8 QP                 | 46.0           | -20.2       | 1.00 H             | 124                  | 32.7             | -6.9                     |
| 5                                                   | 374.42      | 26.8 QP                 | 46.0           | -19.2       | 1.00 H             | 226                  | 31.9             | -5.1                     |
| 6                                                   | 593.72      | 30.7 QP                 | 46.0           | -15.3       | 1.50 H             | 211                  | 30.5             | 0.2                      |

#### Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. The other emission levels were very low against the limit of frequency range 30MHz ~ 1000MHz.
4. Margin value = Emission Level – Limit value.
5. The emission levels were very low against the limit of frequency range 9kHz ~ 30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




|                 |                     |                   |                  |
|-----------------|---------------------|-------------------|------------------|
| RF Mode         | TX 802.11ac (VHT20) | Channel           | CH 60 : 5300 MHz |
| Frequency Range | 30MHz ~ 1GHz        | Detector Function | Quasi-Peak (QP)  |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|---------------------------------------------------|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.                                               | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                 | 59.92       | 39.6 QP                 | 40.0           | -0.4        | 1.00 V             | 13                   | 49.0             | -9.4                     |
| 2                                                 | 105.91      | 30.1 QP                 | 43.5           | -13.4       | 1.00 V             | 57                   | 42.5             | -12.4                    |
| 3                                                 | 187.45      | 28.3 QP                 | 43.5           | -15.2       | 1.00 V             | 165                  | 39.0             | -10.7                    |
| 4                                                 | 356.14      | 30.0 QP                 | 46.0           | -16.0       | 1.50 V             | 288                  | 35.5             | -5.5                     |
| 5                                                 | 493.91      | 33.4 QP                 | 46.0           | -12.6       | 1.00 V             | 14                   | 35.9             | -2.5                     |
| 6                                                 | 555.77      | 31.9 QP                 | 46.0           | -14.1       | 1.00 V             | 245                  | 33.0             | -1.1                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. The other emission levels were very low against the limit of frequency range 30MHz ~ 1000MHz.
4. Margin value = Emission Level – Limit value.
5. The emission levels were very low against the limit of frequency range 9kHz ~ 30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.



## 4.2 Conducted Emission Measurement

### 4.2.1 Limits of Conducted Emission Measurement

| Frequency (MHz) | Conducted Limit (dBuV) |         |
|-----------------|------------------------|---------|
|                 | Quasi-peak             | Average |
| 0.15 - 0.5      | 66 - 56                | 56 - 46 |
| 0.50 - 5.0      | 56                     | 46      |
| 5.0 - 30.0      | 60                     | 50      |

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 4.2.2 Test Instruments

| Description & Manufacturer              | Model No.                | Serial No.     | Cal. Date     | Cal. Due      |
|-----------------------------------------|--------------------------|----------------|---------------|---------------|
| Test Receiver<br>ROHDE & SCHWARZ        | ESCI                     | 100613         | Dec. 04, 2020 | Dec. 03, 2021 |
| RF signal cable<br>Woken                | 5D-FB                    | Cable-cond1-01 | Sep. 04, 2020 | Sep. 03, 2021 |
| LISN<br>ROHDE & SCHWARZ<br>(EUT)        | ENV216                   | 101826         | Feb. 20, 2020 | Feb. 19, 2021 |
|                                         |                          |                | Feb. 25, 2021 | Feb. 24, 2022 |
| LISN<br>ROHDE & SCHWARZ<br>(Peripheral) | ESH3-Z5                  | 100311         | Aug. 28, 2020 | Aug. 27, 2021 |
| Software<br>ADT                         | BV ADT_Conc_<br>V7.3.7.4 | NA             | NA            | NA            |

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in HwaYa Shielded Room 1 (Conduction 1).

3. The VCCI Site Registration No. is C-12040.

### 4.2.3 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

### 4.2.4 Deviation from Test Standard

No deviation.

### 4.2.5 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

### 4.2.6 EUT Operating Conditions

Same as 4.1.6.

#### 4.2.7 Test Results

Worst-case data:

5G traffic radio (Radio 2)


802.11ax (HE20)

| Phase | Line (L) | Detector Function | Quasi-Peak (QP) / Average (AV) |
|-------|----------|-------------------|--------------------------------|
|-------|----------|-------------------|--------------------------------|

| No | Freq.<br>[MHz] | Corr.<br>Factor<br>(dB) | Reading Value<br>[dB (uV)] |       | Emission Level<br>[dB (uV)] |       | Limit<br>[dB (uV)] |       | Margin<br>(dB) |        |
|----|----------------|-------------------------|----------------------------|-------|-----------------------------|-------|--------------------|-------|----------------|--------|
|    |                |                         |                            |       |                             |       |                    |       |                |        |
|    |                |                         | Q.P.                       | AV.   | Q.P.                        | AV.   | Q.P.               | AV.   | Q.P.           | AV.    |
| 1  | 0.15400        | 10.09                   | 33.42                      | 26.94 | 43.51                       | 37.03 | 65.78              | 55.78 | -22.27         | -18.75 |
| 2  | 0.16535        | 10.10                   | 35.68                      | 24.11 | 45.78                       | 34.21 | 65.19              | 55.19 | -19.41         | -20.98 |
| 3  | 0.48063        | 10.20                   | 35.24                      | 29.49 | 45.44                       | 39.69 | 56.33              | 46.33 | -10.89         | -6.64  |
| 4  | 1.89800        | 10.36                   | 24.78                      | 20.33 | 35.14                       | 30.69 | 56.00              | 46.00 | -20.86         | -15.31 |
| 5  | 12.25800       | 10.93                   | 22.84                      | 17.80 | 33.77                       | 28.73 | 60.00              | 50.00 | -26.23         | -21.27 |
| 6  | 19.36600       | 11.29                   | 22.46                      | 19.74 | 33.75                       | 31.03 | 60.00              | 50.00 | -26.25         | -18.97 |

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




|       |             |                   |                                |
|-------|-------------|-------------------|--------------------------------|
| Phase | Neutral (N) | Detector Function | Quasi-Peak (QP) / Average (AV) |
|-------|-------------|-------------------|--------------------------------|

| No       | Freq.<br>[MHz] | Corr.<br>Factor<br>(dB) | Reading Value<br>[dB (uV)] |              | Emission Level<br>[dB (uV)] |              | Limit<br>[dB (uV)] |              | Margin<br>(dB) |              |
|----------|----------------|-------------------------|----------------------------|--------------|-----------------------------|--------------|--------------------|--------------|----------------|--------------|
|          |                |                         |                            |              |                             |              |                    |              |                |              |
|          |                |                         | Q.P.                       | AV.          | Q.P.                        | AV.          | Q.P.               | AV.          | Q.P.           | AV.          |
| 1        | 0.15687        | 10.08                   | 42.22                      | 27.93        | 52.30                       | 38.01        | 65.63              | 55.63        | -13.33         | -17.62       |
| 2        | 0.18200        | 10.09                   | 34.24                      | 21.86        | 44.33                       | 31.95        | 64.39              | 54.39        | -20.06         | -22.44       |
| <b>3</b> | <b>0.47400</b> | <b>10.20</b>            | <b>33.47</b>               | <b>32.03</b> | <b>43.67</b>                | <b>42.23</b> | <b>56.44</b>       | <b>46.44</b> | <b>-12.77</b>  | <b>-4.21</b> |
| 4        | 1.29426        | 10.31                   | 22.12                      | 18.69        | 32.43                       | 29.00        | 56.00              | 46.00        | -23.57         | -17.00       |
| 5        | 11.80600       | 10.77                   | 20.45                      | 15.24        | 31.22                       | 26.01        | 60.00              | 50.00        | -28.78         | -23.99       |
| 6        | 19.61000       | 11.08                   | 22.26                      | 20.26        | 33.34                       | 31.34        | 60.00              | 50.00        | -26.66         | -18.66       |

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.



# Scanning radio (Radio 3)


802.11ac (VHT20)

| Phase | Line (L) | Detector Function | Quasi-Peak (QP) / Average (AV) |
|-------|----------|-------------------|--------------------------------|
|-------|----------|-------------------|--------------------------------|

| No | Freq.<br>[MHz] | Corr.<br>Factor<br>(dB) | Reading Value |       | Emission Level |       | Limit     |       | Margin |        |
|----|----------------|-------------------------|---------------|-------|----------------|-------|-----------|-------|--------|--------|
|    |                |                         | [dB (uV)]     |       | [dB (uV)]      |       | [dB (uV)] |       | (dB)   |        |
|    |                |                         | Q.P.          | AV.   | Q.P.           | AV.   | Q.P.      | AV.   | Q.P.   | AV.    |
| 1  | 0.15000        | 10.09                   | 35.65         | 25.07 | 45.74          | 35.16 | 66.00     | 56.00 | -20.26 | -20.84 |
| 2  | 0.16535        | 10.10                   | 39.36         | 23.49 | 49.46          | 33.59 | 65.19     | 55.19 | -15.73 | -21.60 |
| 3  | 0.47400        | 10.20                   | 35.84         | 31.90 | 46.04          | 42.10 | 56.44     | 46.44 | -10.40 | -4.34  |
| 4  | 2.04600        | 10.37                   | 25.51         | 21.14 | 35.88          | 31.51 | 56.00     | 46.00 | -20.12 | -14.49 |
| 5  | 12.26200       | 10.93                   | 22.32         | 17.39 | 33.25          | 28.32 | 60.00     | 50.00 | -26.75 | -21.68 |
| 6  | 19.61000       | 11.30                   | 22.87         | 21.61 | 34.17          | 32.91 | 60.00     | 50.00 | -25.83 | -17.09 |

## Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




|       |             |                   |                                |
|-------|-------------|-------------------|--------------------------------|
| Phase | Neutral (N) | Detector Function | Quasi-Peak (QP) / Average (AV) |
|-------|-------------|-------------------|--------------------------------|

| No | Freq.<br>[MHz] | Corr.<br>Factor<br>(dB) | Reading Value<br>[dB (uV)] |       | Emission Level<br>[dB (uV)] |       | Limit<br>[dB (uV)] |       | Margin<br>(dB) |        |
|----|----------------|-------------------------|----------------------------|-------|-----------------------------|-------|--------------------|-------|----------------|--------|
|    |                |                         |                            |       |                             |       |                    |       |                |        |
|    |                |                         | Q.P.                       | AV.   | Q.P.                        | AV.   | Q.P.               | AV.   | Q.P.           | AV.    |
| 1  | 0.16600        | 10.09                   | 36.58                      | 23.34 | 46.67                       | 33.43 | 65.16              | 55.16 | -18.49         | -21.73 |
| 2  | 0.19000        | 10.10                   | 30.44                      | 18.51 | 40.54                       | 28.61 | 64.04              | 54.04 | -23.50         | -25.43 |
| 3  | 0.34200        | 10.16                   | 24.35                      | 17.96 | 34.51                       | 28.12 | 59.15              | 49.15 | -24.64         | -21.03 |
| 4  | 0.47434        | 10.20                   | 35.90                      | 31.97 | 46.10                       | 42.17 | 56.44              | 46.44 | -10.34         | -4.27  |
| 5  | 13.23800       | 10.82                   | 20.89                      | 15.89 | 31.71                       | 26.71 | 60.00              | 50.00 | -28.29         | -23.29 |
| 6  | 19.85400       | 11.09                   | 21.83                      | 19.58 | 32.92                       | 30.67 | 60.00              | 50.00 | -27.08         | -19.33 |

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.



### 4.3 Transmit Power Measurement

#### 4.3.1 Limits of Transmit Power Measurement

| Operation Band | EUT Category   |                                   | Limit                                                                                                                       |
|----------------|----------------|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| U-NII-1        |                | Outdoor Access Point              | 1 Watt (30 dBm)<br>(Max. e.i.r.p $\leq$ 125mW(21 dBm) at any elevation angle above 30 degrees as measured from the horizon) |
|                |                | Fixed point-to-point Access Point | 1 Watt (30 dBm)                                                                                                             |
|                |                | Indoor Access Point               | 1 Watt (30 dBm)                                                                                                             |
|                |                | Mobile and Portable client device | 250mW (24 dBm)                                                                                                              |
| U-NII-2A       | $\sqrt{\quad}$ |                                   | 250mW (24 dBm) or 11 dBm+10 log B*                                                                                          |
| U-NII-2C       | $\sqrt{\quad}$ |                                   | 250mW (24 dBm) or 11 dBm+10 log B*                                                                                          |
| U-NII-3        | $\sqrt{\quad}$ |                                   | 1 Watt (30 dBm)                                                                                                             |

\*B is the 26 dB emission bandwidth in megahertz

Per KDB 662911 Method of conducted output power measurement on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for  $N_{ANT} \leq 4$ ;


Array Gain = 0 dB (i.e., no array gain) for channel widths  $\geq 40$  MHz for any  $N_{ANT}$ ;

Array Gain =  $5 \log(N_{ANT}/N_{SS})$  dB or 3 dB, whichever is less for 20-MHz channel widths with  $N_{ANT} \geq 5$ .


For power measurements on all other devices: Array Gain =  $10 \log(N_{ANT}/N_{SS})$  dB.

#### 4.3.2 Test Setup

For Power Output



For 26dB Bandwidth and power output of transmission above 5.725 GHz where the EBW crosses 5.725 GHz



#### 4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

#### 4.3.4 Test Procedure

##### For Average Power Measurement

Method PM is used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst and set the detector to average. Duty factor is not added to measured value.

For transmission above 5.725 GHz where the EBW crosses 5.725 GHz

For channel aggregation (channel 138, 142, 144) measurement refer to KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Section II E 2 b) method SA-1.

##### For 26dB Bandwidth

- a. Set RBW = approximately 1% of the emission bandwidth.
- b. Set the VBW > RBW.
- c. Detector = Peak.
- d. Trace mode = max hold.
- e. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

#### 4.3.5 Deviation from Test Standard

No deviation.

#### 4.3.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

#### 4.3.7 Test Result

5G traffic radio (Radio 2)

Power Output:

CDD Mode

802.11a

| Chan. | Freq.<br>(MHz)         | Average Power (dBm) |         | Total<br>Power<br>(mW) | Total<br>Power<br>(dBm) | Power<br>Limit<br>(dBm) | Pass /<br>Fail |
|-------|------------------------|---------------------|---------|------------------------|-------------------------|-------------------------|----------------|
|       |                        | Chain 0             | Chain 1 |                        |                         |                         |                |
| 52    | 5260                   | 15.69               | 15.79   | 75.000                 | 18.75                   | 19.83                   | Pass           |
| 60    | 5300                   | 15.65               | 15.91   | 75.722                 | 18.79                   | 19.83                   | Pass           |
| 64    | 5320                   | 15.62               | 15.96   | 75.921                 | 18.80                   | 19.83                   | Pass           |
| 100   | 5500                   | 14.76               | 15.21   | 63.112                 | 18.00                   | 19.83                   | Pass           |
| 116   | 5580                   | 15.06               | 15.58   | 68.204                 | 18.34                   | 19.83                   | Pass           |
| 140   | 5700                   | 15.19               | 15.23   | 66.380                 | 18.22                   | 19.83                   | Pass           |
| 144   | 5720<br>(For U-NII-2C) | 15.10               | 15.50   | 67.841                 | 18.31                   | 18.70                   | Pass           |
| 144   | 5720<br>(For U-NII-3)  | 10.86               | 9.06    | 20.244                 | 13.06                   | 25.83                   | Pass           |

Note:

- 5260-5320MHz: Antenna gain = 10.17dBi > 6dBi, so the power limit shall be reduced to 24 - (10.17 - 6) = 19.83dBm.
- 5500-5700MHz: Antenna gain = 10.17dBi > 6dBi, so the power limit shall be reduced to 24 - (10.17 - 6) = 19.83dBm.
- 5720MHz: Antenna gain = 10.17dBi > 6dBi, so the power limit shall be reduced to 22.87 - (10.17 - 6) = 18.70dBm.
- 5745-5825MHz: Antenna gain = 10.17dBi > 6dBi, so the power limit shall be reduced to 30 - (10.17 - 6) = 25.83dBm.

Chain 0

- 11dBm + 10log (20.67) = 24.15 > 24dBm
- 11dBm + 10log (20.66) = 24.15 > 24dBm
- 11dBm + 10log (20.68) = 24.15 > 24dBm
- 11dBm + 10log (20.31) = 24.07 > 24dBm
- 11dBm + 10log (20.75) = 24.17 > 24dBm
- 11dBm + 10log (20.54) = 24.12 > 24dBm
- 11dBm + 10log (5725.00 - 5709.57) = 22.88 < 24dBm

Chain 1

- 11dBm + 10log (20.53) = 24.12 > 24dBm
- 11dBm + 10log (20.66) = 24.15 > 24dBm
- 11dBm + 10log (20.70) = 24.15 > 24dBm
- 11dBm + 10log (20.76) = 24.17 > 24dBm
- 11dBm + 10log (20.77) = 24.17 > 24dBm
- 11dBm + 10log (20.75) = 24.17 > 24dBm
- 11dBm + 10log (5725.00 - 5709.59) = 22.87 < 24dBm

## 802.11n (HT20)

| Chan. | Freq.<br>(MHz)         | Average Power (dBm) |         | Total<br>Power<br>(mW) | Total<br>Power<br>(dBm) | Power<br>Limit<br>(dBm) | Pass /<br>Fail |
|-------|------------------------|---------------------|---------|------------------------|-------------------------|-------------------------|----------------|
|       |                        | Chain 0             | Chain 1 |                        |                         |                         |                |
| 52    | 5260                   | 16.58               | 16.78   | 93.142                 | 19.69                   | 19.83                   | Pass           |
| 60    | 5300                   | 16.41               | 17.00   | 93.871                 | 19.73                   | 19.83                   | Pass           |
| 64    | 5320                   | 16.40               | 16.90   | 92.629                 | 19.67                   | 19.83                   | Pass           |
| 100   | 5500                   | 15.05               | 15.68   | 68.972                 | 18.39                   | 19.83                   | Pass           |
| 116   | 5580                   | 15.31               | 15.78   | 71.807                 | 18.56                   | 19.83                   | Pass           |
| 140   | 5700                   | 15.34               | 15.56   | 70.173                 | 18.46                   | 19.83                   | Pass           |
| 144   | 5720<br>(For U-NII-2C) | 15.40               | 15.38   | 69.188                 | 18.40                   | 18.86                   | Pass           |
| 144   | 5720<br>(For U-NII-3)  | 10.83               | 7.75    | 18.063                 | 12.57                   | 25.83                   | Pass           |

### Note:

- 5260-5320MHz: Antenna gain = 10.17dBi > 6dBi, so the power limit shall be reduced to  $24 - (10.17 - 6) = 19.83\text{dBm}$ .
- 5500-5700MHz: Antenna gain = 10.17dBi > 6dBi, so the power limit shall be reduced to  $24 - (10.17 - 6) = 19.83\text{dBm}$ .
- 5720MHz: Antenna gain = 10.17dBi > 6dBi, so the power limit shall be reduced to  $23.03 - (10.17 - 6) = 18.86\text{dBm}$ .
- 5745-5825MHz: Antenna gain = 10.17dBi > 6dBi, so the power limit shall be reduced to  $30 - (10.17 - 6) = 25.83\text{dBm}$ .

### Chain 0

- $11\text{dBm} + 10\log(21.51) = 24.32 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.87) = 24.39 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.89) = 24.40 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.08) = 24.23 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.43) = 24.31 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.86) = 24.39 > 24\text{dBm}$
- $11\text{dBm} + 10\log(5725.00 - 5709.02) = 23.03 < 24\text{dBm}$

### Chain 1

- $11\text{dBm} + 10\log(21.55) = 24.33 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.93) = 24.41 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.35) = 24.29 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.90) = 24.40 > 24\text{dBm}$
- $11\text{dBm} + 10\log(22.37) = 24.49 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.95) = 24.41 > 24\text{dBm}$
- $11\text{dBm} + 10\log(5725.00 - 5708.94) = 23.05 < 24\text{dBm}$

## 802.11n (HT40)

| Chan. | Freq.<br>(MHz)         | Average Power (dBm) |         | Total<br>Power<br>(mW) | Total<br>Power<br>(dBm) | Power<br>Limit<br>(dBm) | Pass /<br>Fail |
|-------|------------------------|---------------------|---------|------------------------|-------------------------|-------------------------|----------------|
|       |                        | Chain 0             | Chain 1 |                        |                         |                         |                |
| 54    | 5270                   | 16.56               | 16.33   | 88.243                 | 19.46                   | 19.83                   | Pass           |
| 62    | 5310                   | 16.41               | 16.76   | 91.176                 | 19.60                   | 19.83                   | Pass           |
| 102   | 5510                   | 16.05               | 16.62   | 86.192                 | 19.35                   | 19.83                   | Pass           |
| 110   | 5550                   | 16.23               | 16.67   | 88.427                 | 19.47                   | 19.83                   | Pass           |
| 134   | 5670                   | 16.43               | 16.60   | 89.663                 | 19.53                   | 19.83                   | Pass           |
| 142   | 5710<br>(For U-NII-2C) | 15.96               | 16.00   | 79.256                 | 18.99                   | 19.83                   | Pass           |
| 142   | 5710<br>(For U-NII-3)  | 5.72                | 7.18    | 8.956                  | 9.52                    | 25.83                   | Pass           |

Note:

- 5260-5320MHz: Antenna gain = 10.17dBi > 6dBi, so the power limit shall be reduced to  $24 - (10.17 - 6) = 19.83\text{dBm}$ .
- 5500-5720MHz: Antenna gain = 10.17dBi > 6dBi, so the power limit shall be reduced to  $24 - (10.17 - 6) = 19.83\text{dBm}$ .
- 5745-5825MHz: Antenna gain = 10.17dBi > 6dBi, so the power limit shall be reduced to  $30 - (10.17 - 6) = 25.83\text{dBm}$ .

Chain 0

- $11\text{dBm} + 10\log(42.27) = 27.26 > 24\text{dBm}$
- $11\text{dBm} + 10\log(42.23) = 27.25 > 24\text{dBm}$
- $11\text{dBm} + 10\log(42.40) = 27.27 > 24\text{dBm}$
- $11\text{dBm} + 10\log(42.18) = 27.25 > 24\text{dBm}$
- $11\text{dBm} + 10\log(42.16) = 27.24 > 24\text{dBm}$
- $11\text{dBm} + 10\log(5725.00 - 5688.85) = 26.58 > 24\text{dBm}$

Chain 1

- $11\text{dBm} + 10\log(42.42) = 27.27 > 24\text{dBm}$
- $11\text{dBm} + 10\log(42.43) = 27.27 > 24\text{dBm}$
- $11\text{dBm} + 10\log(42.47) = 27.28 > 24\text{dBm}$
- $11\text{dBm} + 10\log(42.29) = 27.26 > 24\text{dBm}$
- $11\text{dBm} + 10\log(42.07) = 27.23 > 24\text{dBm}$
- $11\text{dBm} + 10\log(5725.00 - 5688.63) = 26.60 > 24\text{dBm}$

# 802.11ac (VHT20)

| Chan. | Freq.<br>(MHz)         | Average Power (dBm) |         | Total<br>Power<br>(mW) | Total<br>Power<br>(dBm) | Power<br>Limit<br>(dBm) | Pass /<br>Fail |
|-------|------------------------|---------------------|---------|------------------------|-------------------------|-------------------------|----------------|
|       |                        | Chain 0             | Chain 1 |                        |                         |                         |                |
| 52    | 5260                   | 16.60               | 16.81   | 93.682                 | 19.72                   | 19.83                   | Pass           |
| 60    | 5300                   | 16.43               | 17.02   | 94.304                 | 19.75                   | 19.83                   | Pass           |
| 64    | 5320                   | 16.42               | 16.92   | 93.057                 | 19.69                   | 19.83                   | Pass           |
| 100   | 5500                   | 15.10               | 15.71   | 69.599                 | 18.43                   | 19.83                   | Pass           |
| 116   | 5580                   | 15.35               | 15.80   | 72.296                 | 18.59                   | 19.83                   | Pass           |
| 140   | 5700                   | 15.36               | 15.58   | 70.497                 | 18.48                   | 19.83                   | Pass           |
| 144   | 5720<br>(For U-NII-2C) | 15.43               | 15.42   | 69.748                 | 18.44                   | 18.86                   | Pass           |
| 144   | 5720<br>(For U-NII-3)  | 10.85               | 7.80    | 18.187                 | 12.60                   | 25.83                   | Pass           |

## Note:

- 5260-5320MHz: Antenna gain = 10.17dBi > 6dBi, so the power limit shall be reduced to  $24 - (10.17 - 6) = 19.83\text{dBm}$ .
- 5500-5700MHz: Antenna gain = 10.17dBi > 6dBi, so the power limit shall be reduced to  $24 - (10.17 - 6) = 19.83\text{dBm}$ .
- 5720MHz: Antenna gain = 10.17dBi > 6dBi, so the power limit shall be reduced to  $23.03 - (10.17 - 6) = 18.86\text{dBm}$ .
- 5745-5825MHz: Antenna gain = 10.17dBi > 6dBi, so the power limit shall be reduced to  $30 - (10.17 - 6) = 25.83\text{dBm}$ .

## Chain 0

- $11\text{dBm} + 10\log(21.51) = 24.32 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.87) = 24.39 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.89) = 24.40 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.08) = 24.23 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.43) = 24.31 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.86) = 24.39 > 24\text{dBm}$
- $11\text{dBm} + 10\log(5725.00 - 5709.02) = 23.03 < 24\text{dBm}$

## Chain 1

- $11\text{dBm} + 10\log(21.55) = 24.33 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.93) = 24.41 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.35) = 24.29 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.90) = 24.40 > 24\text{dBm}$
- $11\text{dBm} + 10\log(22.37) = 24.49 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.95) = 24.41 > 24\text{dBm}$
- $11\text{dBm} + 10\log(5725.00 - 5708.94) = 23.05 < 24\text{dBm}$

### 802.11ac (VHT40)

| Chan. | Freq.<br>(MHz)         | Average Power (dBm) |         | Total<br>Power<br>(mW) | Total<br>Power<br>(dBm) | Power<br>Limit<br>(dBm) | Pass /<br>Fail |
|-------|------------------------|---------------------|---------|------------------------|-------------------------|-------------------------|----------------|
|       |                        | Chain 0             | Chain 1 |                        |                         |                         |                |
| 54    | 5270                   | 16.55               | 16.60   | 90.894                 | 19.59                   | 19.83                   | Pass           |
| 62    | 5310                   | 16.43               | 16.78   | 91.597                 | 19.62                   | 19.83                   | Pass           |
| 102   | 5510                   | 16.10               | 16.65   | 86.976                 | 19.39                   | 19.83                   | Pass           |
| 110   | 5550                   | 16.26               | 16.71   | 89.148                 | 19.50                   | 19.83                   | Pass           |
| 134   | 5670                   | 16.45               | 16.62   | 90.077                 | 19.55                   | 19.83                   | Pass           |
| 142   | 5710<br>(For U-NII-2C) | 15.98               | 16.01   | 79.530                 | 19.01                   | 19.83                   | Pass           |
| 142   | 5710<br>(For U-NII-3)  | 5.75                | 7.20    | 9.006                  | 9.55                    | 25.83                   | Pass           |

Note:

- 5260-5320MHz: Antenna gain = 10.17dBi > 6dBi, so the power limit shall be reduced to  $24 - (10.17 - 6) = 19.83\text{dBm}$ .
- 5500-5720MHz: Antenna gain = 10.17dBi > 6dBi, so the power limit shall be reduced to  $24 - (10.17 - 6) = 19.83\text{dBm}$ .
- 5745-5825MHz: Antenna gain = 10.17dBi > 6dBi, so the power limit shall be reduced to  $30 - (10.17 - 6) = 25.83\text{dBm}$ .

#### Chain 0

- $11\text{dBm} + 10\log(42.27) = 27.26 > 24\text{dBm}$
- $11\text{dBm} + 10\log(42.23) = 27.25 > 24\text{dBm}$
- $11\text{dBm} + 10\log(42.40) = 27.27 > 24\text{dBm}$
- $11\text{dBm} + 10\log(42.18) = 27.25 > 24\text{dBm}$
- $11\text{dBm} + 10\log(42.16) = 27.24 > 24\text{dBm}$
- $11\text{dBm} + 10\log(5725.00 - 5688.85) = 26.58 > 24\text{dBm}$

#### Chain 1

- $11\text{dBm} + 10\log(42.42) = 27.27 > 24\text{dBm}$
- $11\text{dBm} + 10\log(42.43) = 27.27 > 24\text{dBm}$
- $11\text{dBm} + 10\log(42.47) = 27.28 > 24\text{dBm}$
- $11\text{dBm} + 10\log(42.29) = 27.26 > 24\text{dBm}$
- $11\text{dBm} + 10\log(42.07) = 27.23 > 24\text{dBm}$
- $11\text{dBm} + 10\log(5725.00 - 5688.63) = 26.60 > 24\text{dBm}$

802.11ac (VHT80)

| Chan. | Freq.<br>(MHz)         | Average Power (dBm) |         | Total<br>Power<br>(mW) | Total<br>Power<br>(dBm) | Power<br>Limit<br>(dBm) | Pass /<br>Fail |
|-------|------------------------|---------------------|---------|------------------------|-------------------------|-------------------------|----------------|
|       |                        | Chain 0             | Chain 1 |                        |                         |                         |                |
| 58    | 5290                   | 16.21               | 16.62   | 87.703                 | 19.43                   | 19.83                   | Pass           |
| 106   | 5530                   | 16.43               | 16.95   | 93.499                 | 19.71                   | 19.83                   | Pass           |
| 122   | 5610                   | 16.49               | 16.83   | 92.760                 | 19.67                   | 19.83                   | Pass           |
| 138   | 5690<br>(For U-NII-2C) | 16.28               | 16.58   | 87.961                 | 19.44                   | 19.83                   | Pass           |
| 138   | 5690<br>(For U-NII-3)  | 3.30                | 3.32    | 4.286                  | 6.32                    | 25.83                   | Pass           |

Note:

- 5260-5320MHz: Antenna gain = 10.17dBi > 6dBi, so the power limit shall be reduced to  $24 - (10.17 - 6) = 19.83\text{dBm}$ .
- 5500-5720MHz: Antenna gain = 10.17dBi > 6dBi, so the power limit shall be reduced to  $24 - (10.17 - 6) = 19.83\text{dBm}$ .
- 5745-5825MHz: Antenna gain = 10.17dBi > 6dBi, so the power limit shall be reduced to  $30 - (10.17 - 6) = 25.83\text{dBm}$ .

Chain 0

- $11\text{dBm} + 10\log(82.60) = 30.16 > 24\text{dBm}$
- $11\text{dBm} + 10\log(83.03) = 30.19 > 24\text{dBm}$
- $11\text{dBm} + 10\log(83.60) = 30.22 > 24\text{dBm}$
- $11\text{dBm} + 10\log(5725.00 - 5648.47) = 29.84 > 24\text{dBm}$

Chain 1

- $11\text{dBm} + 10\log(82.50) = 30.16 > 24\text{dBm}$
- $11\text{dBm} + 10\log(82.75) = 30.17 > 24\text{dBm}$
- $11\text{dBm} + 10\log(82.12) = 30.14 > 24\text{dBm}$
- $11\text{dBm} + 10\log(5725.00 - 5648.66) = 29.83 > 24\text{dBm}$

### 802.11ax (HE20)

| Chan. | Freq.<br>(MHz)         | Average Power (dBm) |         | Total<br>Power<br>(mW) | Total<br>Power<br>(dBm) | Power<br>Limit<br>(dBm) | Pass /<br>Fail |
|-------|------------------------|---------------------|---------|------------------------|-------------------------|-------------------------|----------------|
|       |                        | Chain 0             | Chain 1 |                        |                         |                         |                |
| 52    | 5260                   | 16.63               | 16.84   | 94.332                 | 19.75                   | 19.83                   | Pass           |
| 60    | 5300                   | 16.47               | 17.06   | <b>95.177</b>          | 19.79                   | 19.83                   | Pass           |
| 64    | 5320                   | 16.45               | 16.99   | 94.160                 | 19.74                   | 19.83                   | Pass           |
| 100   | 5500                   | 15.13               | 15.73   | 69.995                 | 18.45                   | 19.83                   | Pass           |
| 116   | 5580                   | 15.38               | 15.83   | 72.797                 | 18.62                   | 19.83                   | Pass           |
| 140   | 5700                   | 15.39               | 15.61   | 70.985                 | 18.51                   | 19.83                   | Pass           |
| 144   | 5720<br>(For U-NII-2C) | 15.47               | 15.45   | 70.312                 | 18.47                   | 18.86                   | Pass           |
| 144   | 5720<br>(For U-NII-3)  | 10.89               | 7.82    | 18.328                 | 12.63                   | 25.83                   | Pass           |

#### Note:

- 5260-5320MHz: Antenna gain = 10.17dBi > 6dBi, so the power limit shall be reduced to  $24 - (10.17 - 6) = 19.83\text{dBm}$ .
- 5500-5700MHz: Antenna gain = 10.17dBi > 6dBi, so the power limit shall be reduced to  $24 - (10.17 - 6) = 19.83\text{dBm}$ .
- 5720MHz: Antenna gain = 10.17dBi > 6dBi, so the power limit shall be reduced to  $23.03 - (10.17 - 6) = 18.86\text{dBm}$ .
- 5745-5825MHz: Antenna gain = 10.17dBi > 6dBi, so the power limit shall be reduced to  $30 - (10.17 - 6) = 25.83\text{dBm}$ .

#### Chain 0

- $11\text{dBm} + 10\log(21.51) = 24.32 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.87) = 24.39 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.89) = 24.40 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.08) = 24.23 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.43) = 24.31 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.86) = 24.39 > 24\text{dBm}$
- $11\text{dBm} + 10\log(5725.00 - 5709.02) = 23.03 < 24\text{dBm}$

#### Chain 1

- $11\text{dBm} + 10\log(21.55) = 24.33 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.93) = 24.41 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.35) = 24.29 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.90) = 24.40 > 24\text{dBm}$
- $11\text{dBm} + 10\log(22.37) = 24.49 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.95) = 24.41 > 24\text{dBm}$
- $11\text{dBm} + 10\log(5725.00 - 5708.94) = 23.05 < 24\text{dBm}$

### 802.11ax (HE40)

| Chan. | Freq.<br>(MHz)         | Average Power (dBm) |         | Total<br>Power<br>(mW) | Total<br>Power<br>(dBm) | Power<br>Limit<br>(dBm) | Pass /<br>Fail |
|-------|------------------------|---------------------|---------|------------------------|-------------------------|-------------------------|----------------|
|       |                        | Chain 0             | Chain 1 |                        |                         |                         |                |
| 54    | 5270                   | 16.57               | 16.62   | 91.314                 | 19.61                   | 19.83                   | Pass           |
| 62    | 5310                   | 16.45               | 16.81   | 92.130                 | 19.64                   | 19.83                   | Pass           |
| 102   | 5510                   | 16.12               | 16.68   | 87.485                 | 19.42                   | 19.83                   | Pass           |
| 110   | 5550                   | 16.28               | 16.73   | 89.560                 | 19.52                   | 19.83                   | Pass           |
| 134   | 5670                   | 16.49               | 16.64   | 90.697                 | 19.58                   | 19.83                   | Pass           |
| 142   | 5710<br>(For U-NII-2C) | 16.00               | 16.03   | 79.897                 | 19.03                   | 19.83                   | Pass           |
| 142   | 5710<br>(For U-NII-3)  | 5.80                | 7.24    | 9.099                  | 9.59                    | 25.83                   | Pass           |

Note:

- 5260-5320MHz: Antenna gain = 10.17dBi > 6dBi, so the power limit shall be reduced to  $24 - (10.17 - 6) = 19.83\text{dBm}$ .
- 5500-5720MHz: Antenna gain = 10.17dBi > 6dBi, so the power limit shall be reduced to  $24 - (10.17 - 6) = 19.83\text{dBm}$ .
- 5745-5825MHz: Antenna gain = 10.17dBi > 6dBi, so the power limit shall be reduced to  $30 - (10.17 - 6) = 25.83\text{dBm}$ .

#### Chain 0

- $11\text{dBm} + 10\log(42.27) = 27.26 > 24\text{dBm}$
- $11\text{dBm} + 10\log(42.23) = 27.25 > 24\text{dBm}$
- $11\text{dBm} + 10\log(42.40) = 27.27 > 24\text{dBm}$
- $11\text{dBm} + 10\log(42.18) = 27.25 > 24\text{dBm}$
- $11\text{dBm} + 10\log(42.16) = 27.24 > 24\text{dBm}$
- $11\text{dBm} + 10\log(5725.00 - 5688.85) = 26.58 > 24\text{dBm}$

#### Chain 1

- $11\text{dBm} + 10\log(42.42) = 27.27 > 24\text{dBm}$
- $11\text{dBm} + 10\log(42.43) = 27.27 > 24\text{dBm}$
- $11\text{dBm} + 10\log(42.47) = 27.28 > 24\text{dBm}$
- $11\text{dBm} + 10\log(42.29) = 27.26 > 24\text{dBm}$
- $11\text{dBm} + 10\log(42.07) = 27.23 > 24\text{dBm}$
- $11\text{dBm} + 10\log(5725.00 - 5688.63) = 26.60 > 24\text{dBm}$

### 802.11ax (HE80)

| Chan. | Freq.<br>(MHz)         | Average Power (dBm) |         | Total<br>Power<br>(mW) | Total<br>Power<br>(dBm) | Power<br>Limit<br>(dBm) | Pass /<br>Fail |
|-------|------------------------|---------------------|---------|------------------------|-------------------------|-------------------------|----------------|
|       |                        | Chain 0             | Chain 1 |                        |                         |                         |                |
| 58    | 5290                   | 16.27               | 16.65   | 88.602                 | 19.47                   | 19.83                   | Pass           |
| 106   | 5530                   | 16.46               | 16.98   | <b>94.147</b>          | 19.74                   | 19.83                   | Pass           |
| 122   | 5610                   | 16.51               | 16.88   | 93.524                 | 19.71                   | 19.83                   | Pass           |
| 138   | 5690<br>(For U-NII-2C) | 16.30               | 16.60   | 88.367                 | 19.46                   | 19.83                   | Pass           |
| 138   | 5690<br>(For U-NII-3)  | 3.35                | 3.39    | 4.345                  | 6.38                    | 25.83                   | Pass           |

#### Note:

- 5260-5320MHz: Antenna gain = 10.17dBi > 6dBi, so the power limit shall be reduced to  $24 - (10.17 - 6) = 19.83\text{dBm}$ .
- 5500-5720MHz: Antenna gain = 10.17dBi > 6dBi, so the power limit shall be reduced to  $24 - (10.17 - 6) = 19.83\text{dBm}$ .
- 5745-5825MHz: Antenna gain = 10.17dBi > 6dBi, so the power limit shall be reduced to  $30 - (10.17 - 6) = 25.83\text{dBm}$ .

#### Chain 0

- $11\text{dBm} + 10\log(82.60) = 30.16 > 24\text{dBm}$
- $11\text{dBm} + 10\log(83.03) = 30.19 > 24\text{dBm}$
- $11\text{dBm} + 10\log(83.60) = 30.22 > 24\text{dBm}$
- $11\text{dBm} + 10\log(5725.00 - 5648.47) = 29.84 > 24\text{dBm}$

#### Chain 1

- $11\text{dBm} + 10\log(82.50) = 30.16 > 24\text{dBm}$
- $11\text{dBm} + 10\log(82.75) = 30.17 > 24\text{dBm}$
- $11\text{dBm} + 10\log(82.12) = 30.14 > 24\text{dBm}$
- $11\text{dBm} + 10\log(5725.00 - 5648.66) = 29.83 > 24\text{dBm}$

## Beamforming Mode

### 802.11ac (VHT20)

| Chan. | Freq.<br>(MHz)         | Average Power (dBm) |         | Total<br>Power<br>(mW) | Total<br>Power<br>(dBm) | Power<br>Limit<br>(dBm) | Pass /<br>Fail |
|-------|------------------------|---------------------|---------|------------------------|-------------------------|-------------------------|----------------|
|       |                        | Chain 0             | Chain 1 |                        |                         |                         |                |
| 52    | 5260                   | 13.59               | 13.80   | 46.844                 | 16.71                   | 16.89                   | Pass           |
| 60    | 5300                   | 13.42               | 14.01   | 47.155                 | 16.74                   | 16.89                   | Pass           |
| 64    | 5320                   | 13.41               | 13.91   | 46.532                 | 16.68                   | 16.89                   | Pass           |
| 100   | 5500                   | 12.09               | 12.70   | 34.802                 | 15.42                   | 16.89                   | Pass           |
| 116   | 5580                   | 12.34               | 12.79   | 36.150                 | 15.58                   | 16.89                   | Pass           |
| 140   | 5700                   | 12.35               | 12.57   | 35.251                 | 15.47                   | 16.89                   | Pass           |
| 144   | 5720<br>(For U-NII-2C) | 12.42               | 12.39   | 34.796                 | 15.42                   | 15.92                   | Pass           |
| 144   | 5720<br>(For U-NII-3)  | 7.84                | 4.79    | 9.094                  | 9.59                    | 22.89                   | Pass           |

Note:

- 5260-5320MHz: Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 13.11\text{dBi} > 6\text{dBi}$ , so the power limit shall be reduced to  $24 - (13.11 - 6) = 16.89\text{dBm}$ .
- 5500-5700MHz: Directional gain = Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 13.11\text{dBi} > 6\text{dBi}$ , so the power limit shall be reduced to  $24 - (13.11 - 6) = 16.89\text{dBm}$ .
- 5720MHz: Directional gain = Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 13.11\text{dBi} > 6\text{dBi}$ , so the power limit shall be reduced to  $23.03 - (13.11 - 6) = 15.92\text{dBm}$ .
- 5745-5825MHz: Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 13.11\text{dBi} > 6\text{dBi}$ , so the power limit shall be reduced to  $30 - (13.11 - 6) = 22.89\text{dBm}$ .

#### Chain 0

- $11\text{dBm} + 10\log(21.51) = 24.32 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.87) = 24.39 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.89) = 24.40 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.08) = 24.23 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.43) = 24.31 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.86) = 24.39 > 24\text{dBm}$
- $11\text{dBm} + 10\log(5725.00 - 5709.02) = 23.03 < 24\text{dBm}$

#### Chain 1

- $11\text{dBm} + 10\log(21.55) = 24.33 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.93) = 24.41 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.35) = 24.29 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.90) = 24.40 > 24\text{dBm}$
- $11\text{dBm} + 10\log(22.37) = 24.49 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.95) = 24.41 > 24\text{dBm}$
- $11\text{dBm} + 10\log(5725.00 - 5708.94) = 23.05 < 24\text{dBm}$

### 802.11ac (VHT40)

| Chan. | Freq.<br>(MHz)         | Average Power (dBm) |         | Total<br>Power<br>(mW) | Total<br>Power<br>(dBm) | Power<br>Limit<br>(dBm) | Pass /<br>Fail |
|-------|------------------------|---------------------|---------|------------------------|-------------------------|-------------------------|----------------|
|       |                        | Chain 0             | Chain 1 |                        |                         |                         |                |
| 54    | 5270                   | 13.54               | 13.59   | 45.450                 | 16.58                   | 16.89                   | Pass           |
| 62    | 5310                   | 13.42               | 13.77   | 45.802                 | 16.61                   | 16.89                   | Pass           |
| 102   | 5510                   | 13.09               | 13.64   | 43.491                 | 16.38                   | 16.89                   | Pass           |
| 110   | 5550                   | 13.25               | 13.70   | 44.577                 | 16.49                   | 16.89                   | Pass           |
| 134   | 5670                   | 13.44               | 13.61   | 45.042                 | 16.54                   | 16.89                   | Pass           |
| 142   | 5710<br>(For U-NII-2C) | 12.97               | 13.00   | 39.768                 | 16.00                   | 16.89                   | Pass           |
| 142   | 5710<br>(For U-NII-3)  | 2.74                | 4.19    | 4.504                  | 6.54                    | 22.89                   | Pass           |

Note:

- 5260-5320MHz: Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 13.11\text{dBi} > 6\text{dBi}$ , so the power limit shall be reduced to  $24 - (13.11 - 6) = 16.89\text{dBm}$ .
- 5500-5720MHz: Directional gain = Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 13.11\text{dBi} > 6\text{dBi}$ , so the power limit shall be reduced to  $24 - (13.11 - 6) = 16.89\text{dBm}$ .
- 5745-5825MHz: Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 13.11\text{dBi} > 6\text{dBi}$ , so the power limit shall be reduced to  $30 - (13.11 - 6) = 22.89\text{dBm}$ .

#### Chain 0

- $11\text{dBm} + 10\log(42.27) = 27.26 > 24\text{dBm}$
- $11\text{dBm} + 10\log(42.23) = 27.25 > 24\text{dBm}$
- $11\text{dBm} + 10\log(42.40) = 27.27 > 24\text{dBm}$
- $11\text{dBm} + 10\log(42.18) = 27.25 > 24\text{dBm}$
- $11\text{dBm} + 10\log(42.16) = 27.24 > 24\text{dBm}$
- $11\text{dBm} + 10\log(5725.00 - 5688.85) = 26.58 > 24\text{dBm}$

#### Chain 1

- $11\text{dBm} + 10\log(42.42) = 27.27 > 24\text{dBm}$
- $11\text{dBm} + 10\log(42.43) = 27.27 > 24\text{dBm}$
- $11\text{dBm} + 10\log(42.47) = 27.28 > 24\text{dBm}$
- $11\text{dBm} + 10\log(42.29) = 27.26 > 24\text{dBm}$
- $11\text{dBm} + 10\log(42.07) = 27.23 > 24\text{dBm}$
- $11\text{dBm} + 10\log(5725.00 - 5688.63) = 26.60 > 24\text{dBm}$

## 802.11ac (VHT80)

| Chan. | Freq.<br>(MHz)         | Average Power (dBm) |         | Total<br>Power<br>(mW) | Total<br>Power<br>(dBm) | Power<br>Limit<br>(dBm) | Pass /<br>Fail |
|-------|------------------------|---------------------|---------|------------------------|-------------------------|-------------------------|----------------|
|       |                        | Chain 0             | Chain 1 |                        |                         |                         |                |
| 58    | 5290                   | 13.20               | 13.61   | 43.854                 | 16.42                   | 16.89                   | Pass           |
| 106   | 5530                   | 13.42               | 13.94   | 46.753                 | 16.70                   | 16.89                   | Pass           |
| 122   | 5610                   | 13.48               | 13.82   | 46.383                 | 16.66                   | 16.89                   | Pass           |
| 138   | 5690<br>(For U-NII-2C) | 13.27               | 13.57   | 43.983                 | 16.43                   | 16.89                   | Pass           |
| 138   | 5690<br>(For U-NII-3)  | 0.29                | 0.31    | 2.143                  | 3.31                    | 22.89                   | Pass           |

Note:

- 5260-5320MHz: Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 13.11\text{dBi} > 6\text{dBi}$ , so the power limit shall be reduced to  $24 - (13.11 - 6) = 16.89\text{dBm}$ .
- 5500-5720MHz: Directional gain = Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 13.11\text{dBi} > 6\text{dBi}$ , so the power limit shall be reduced to  $24 - (13.11 - 6) = 16.89\text{dBm}$ .
- 5745-5825MHz: Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 13.11\text{dBi} > 6\text{dBi}$ , so the power limit shall be reduced to  $30 - (13.11 - 6) = 22.89\text{dBm}$ .

Chain 0

- $11\text{dBm} + 10\log(82.60) = 30.16 > 24\text{dBm}$
- $11\text{dBm} + 10\log(83.03) = 30.19 > 24\text{dBm}$
- $11\text{dBm} + 10\log(83.60) = 30.22 > 24\text{dBm}$
- $11\text{dBm} + 10\log(5725.00 - 5648.47) = 29.84 > 24\text{dBm}$

Chain 1

- $11\text{dBm} + 10\log(82.50) = 30.16 > 24\text{dBm}$
- $11\text{dBm} + 10\log(82.75) = 30.17 > 24\text{dBm}$
- $11\text{dBm} + 10\log(82.12) = 30.14 > 24\text{dBm}$
- $11\text{dBm} + 10\log(5725.00 - 5648.66) = 29.83 > 24\text{dBm}$

### 802.11ax (HE20)

| Chan. | Freq.<br>(MHz)         | Average Power (dBm) |         | Total<br>Power<br>(mW) | Total<br>Power<br>(dBm) | Power<br>Limit<br>(dBm) | Pass /<br>Fail |
|-------|------------------------|---------------------|---------|------------------------|-------------------------|-------------------------|----------------|
|       |                        | Chain 0             | Chain 1 |                        |                         |                         |                |
| 52    | 5260                   | 13.62               | 13.83   | 47.169                 | 16.74                   | 16.89                   | Pass           |
| 60    | 5300                   | 13.46               | 14.05   | <b>47.592</b>          | 16.78                   | 16.89                   | Pass           |
| 64    | 5320                   | 13.44               | 13.98   | 47.084                 | 16.73                   | 16.89                   | Pass           |
| 100   | 5500                   | 12.12               | 12.72   | 35.000                 | 15.44                   | 16.89                   | Pass           |
| 116   | 5580                   | 12.37               | 12.82   | 36.401                 | 15.61                   | 16.89                   | Pass           |
| 140   | 5700                   | 12.38               | 12.60   | 35.495                 | 15.50                   | 16.89                   | Pass           |
| 144   | 5720<br>(For U-NII-2C) | 12.46               | 12.44   | 35.159                 | 15.46                   | 15.92                   | Pass           |
| 144   | 5720<br>(For U-NII-3)  | 7.88                | 4.81    | 9.165                  | 9.62                    | 22.89                   | Pass           |

Note:

- 5260-5320MHz: Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 13.11\text{dBi} > 6\text{dBi}$ , so the power limit shall be reduced to  $24 - (13.11 - 6) = 16.89\text{dBm}$ .
- 5500-5700MHz: Directional gain = Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 13.11\text{dBi} > 6\text{dBi}$ , so the power limit shall be reduced to  $24 - (13.11 - 6) = 16.89\text{dBm}$ .
- 5720MHz: Directional gain = Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 13.11\text{dBi} > 6\text{dBi}$ , so the power limit shall be reduced to  $23.03 - (13.11 - 6) = 15.92\text{dBm}$ .
- 5745-5825MHz: Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 13.11\text{dBi} > 6\text{dBi}$ , so the power limit shall be reduced to  $30 - (13.11 - 6) = 22.89\text{dBm}$ .

#### Chain 0

- $11\text{dBm} + 10\log(21.51) = 24.32 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.87) = 24.39 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.89) = 24.40 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.08) = 24.23 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.43) = 24.31 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.86) = 24.39 > 24\text{dBm}$
- $11\text{dBm} + 10\log(5725.00 - 5709.02) = 23.03 < 24\text{dBm}$

#### Chain 1

- $11\text{dBm} + 10\log(21.55) = 24.33 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.93) = 24.41 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.35) = 24.29 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.90) = 24.40 > 24\text{dBm}$
- $11\text{dBm} + 10\log(22.37) = 24.49 > 24\text{dBm}$
- $11\text{dBm} + 10\log(21.95) = 24.41 > 24\text{dBm}$
- $11\text{dBm} + 10\log(5725.00 - 5708.94) = 23.05 < 24\text{dBm}$

# 802.11ax (HE40)

| Chan. | Freq.<br>(MHz)         | Average Power (dBm) |         | Total<br>Power<br>(mW) | Total<br>Power<br>(dBm) | Power<br>Limit<br>(dBm) | Pass /<br>Fail |
|-------|------------------------|---------------------|---------|------------------------|-------------------------|-------------------------|----------------|
|       |                        | Chain 0             | Chain 1 |                        |                         |                         |                |
| 54    | 5270                   | 13.56               | 13.61   | 45.660                 | 16.60                   | 16.89                   | Pass           |
| 62    | 5310                   | 13.44               | 13.80   | 46.068                 | 16.63                   | 16.89                   | Pass           |
| 102   | 5510                   | 13.11               | 13.67   | 43.745                 | 16.41                   | 16.89                   | Pass           |
| 110   | 5550                   | 13.27               | 13.72   | 44.783                 | 16.51                   | 16.89                   | Pass           |
| 134   | 5670                   | 13.48               | 13.63   | 45.352                 | 16.57                   | 16.89                   | Pass           |
| 142   | 5710<br>(For U-NII-2C) | 12.99               | 13.02   | 39.951                 | 16.02                   | 16.89                   | Pass           |
| 142   | 5710<br>(For U-NII-3)  | 2.79                | 4.23    | 4.550                  | 6.58                    | 22.89                   | Pass           |

Note:

- 5260-5320MHz: Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 13.11\text{dBi} > 6\text{dBi}$ , so the power limit shall be reduced to  $24 - (13.11 - 6) = 16.89\text{dBm}$ .
- 5500-5720MHz: Directional gain = Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 13.11\text{dBi} > 6\text{dBi}$ , so the power limit shall be reduced to  $24 - (13.11 - 6) = 16.89\text{dBm}$ .
- 5745-5825MHz: Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 13.11\text{dBi} > 6\text{dBi}$ , so the power limit shall be reduced to  $30 - (13.11 - 6) = 22.89\text{dBm}$ .

Chain 0

- $11\text{dBm} + 10\log(42.27) = 27.26 > 24\text{dBm}$
- $11\text{dBm} + 10\log(42.23) = 27.25 > 24\text{dBm}$
- $11\text{dBm} + 10\log(42.40) = 27.27 > 24\text{dBm}$
- $11\text{dBm} + 10\log(42.18) = 27.25 > 24\text{dBm}$
- $11\text{dBm} + 10\log(42.16) = 27.24 > 24\text{dBm}$
- $11\text{dBm} + 10\log(5725.00 - 5688.85) = 26.58 > 24\text{dBm}$

Chain 1

- $11\text{dBm} + 10\log(42.42) = 27.27 > 24\text{dBm}$
- $11\text{dBm} + 10\log(42.43) = 27.27 > 24\text{dBm}$
- $11\text{dBm} + 10\log(42.47) = 27.28 > 24\text{dBm}$
- $11\text{dBm} + 10\log(42.29) = 27.26 > 24\text{dBm}$
- $11\text{dBm} + 10\log(42.07) = 27.23 > 24\text{dBm}$
- $11\text{dBm} + 10\log(5725.00 - 5688.63) = 26.60 > 24\text{dBm}$

### 802.11ax (HE80)

| Chan. | Freq.<br>(MHz)         | Average Power (dBm) |         | Total<br>Power<br>(mW) | Total<br>Power<br>(dBm) | Power<br>Limit<br>(dBm) | Pass /<br>Fail |
|-------|------------------------|---------------------|---------|------------------------|-------------------------|-------------------------|----------------|
|       |                        | Chain 0             | Chain 1 |                        |                         |                         |                |
| 58    | 5290                   | 13.26               | 13.64   | 44.304                 | 16.46                   | 16.89                   | Pass           |
| 106   | 5530                   | 13.45               | 13.97   | <b>47.077</b>          | 16.73                   | 16.89                   | Pass           |
| 122   | 5610                   | 13.50               | 13.87   | 46.765                 | 16.70                   | 16.89                   | Pass           |
| 138   | 5690<br>(For U-NII-2C) | 13.29               | 13.59   | 44.186                 | 16.45                   | 16.89                   | Pass           |
| 138   | 5690<br>(For U-NII-3)  | 0.34                | 0.38    | 2.173                  | 3.37                    | 22.89                   | Pass           |

#### Note:

- 5260-5320MHz: Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 13.11\text{dBi} > 6\text{dBi}$ , so the power limit shall be reduced to  $24 - (13.11 - 6) = 16.89\text{dBm}$ .
- 5500-5720MHz: Directional gain = Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 13.11\text{dBi} > 6\text{dBi}$ , so the power limit shall be reduced to  $24 - (13.11 - 6) = 16.89\text{dBm}$ .
- 5745-5825MHz: Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 13.11\text{dBi} > 6\text{dBi}$ , so the power limit shall be reduced to  $30 - (13.11 - 6) = 22.89\text{dBm}$ .

#### Chain 0

- $11\text{dBm} + 10\log(82.60) = 30.16 > 24\text{dBm}$
- $11\text{dBm} + 10\log(83.03) = 30.19 > 24\text{dBm}$
- $11\text{dBm} + 10\log(83.60) = 30.22 > 24\text{dBm}$
- $11\text{dBm} + 10\log(5725.00 - 5648.47) = 29.84 > 24\text{dBm}$


#### Chain 1

- $11\text{dBm} + 10\log(82.50) = 30.16 > 24\text{dBm}$
- $11\text{dBm} + 10\log(82.75) = 30.17 > 24\text{dBm}$
- $11\text{dBm} + 10\log(82.12) = 30.14 > 24\text{dBm}$
- $11\text{dBm} + 10\log(5725.00 - 5648.66) = 29.83 > 24\text{dBm}$


## Straddle channel power plots:

802.11a

Chain 0




Chain 1




802.11ax (HE20)

Chain 0




Chain 1




802.11ax (HE40)

Chain 0




Chain 1




802.11ax (HE80)

Chain 0



Chain 1



26dB Bandwidth:

802.11a

| Chan. | Freq.<br>(MHz)         | 26dBc Bandwidth (MHz) |         |
|-------|------------------------|-----------------------|---------|
|       |                        | Chain 0               | Chain 1 |
| 52    | 5260                   | 20.67                 | 20.53   |
| 60    | 5300                   | 20.66                 | 20.66   |
| 64    | 5320                   | 20.68                 | 20.70   |
| 100   | 5500                   | 20.31                 | 20.76   |
| 116   | 5580                   | 20.75                 | 20.77   |
| 140   | 5700                   | 20.54                 | 20.75   |
| 144   | 5720<br>(For U-NII-2C) | 15.43                 | 15.41   |
| 144   | 5720<br>(For U-NII-3)  | 5.33                  | 5.34    |

For CH144 (U-NII-2C Band): The 26dBc bandwidth below 5725MHz = 5725MHz - Marker 1

For CH144 (U-NII-3 Band): The 26dBc bandwidth above 5725MHz = Marker 1 + Delta 2 - 5725MHz

802.11ax (HE20)

| Chan. | Freq.<br>(MHz)         | 26dBc Bandwidth (MHz) |         |
|-------|------------------------|-----------------------|---------|
|       |                        | Chain 0               | Chain 1 |
| 52    | 5260                   | 21.51                 | 21.55   |
| 60    | 5300                   | 21.87                 | 21.93   |
| 64    | 5320                   | 21.89                 | 21.35   |
| 100   | 5500                   | 21.08                 | 21.90   |
| 116   | 5580                   | 21.43                 | 22.37   |
| 140   | 5700                   | 21.86                 | 21.95   |
| 144   | 5720<br>(For U-NII-2C) | 15.98                 | 16.06   |
| 144   | 5720<br>(For U-NII-3)  | 6.05                  | 5.74    |

For CH144 (U-NII-2C Band): The 26dBc bandwidth below 5725MHz = 5725MHz - Marker 1

For CH144 (U-NII-3 Band): The 26dBc bandwidth above 5725MHz = Marker 1 + Delta 2 - 5725MHz

#### 802.11ax (HE40)

| Chan. | Freq.<br>(MHz)         | 26dBc Bandwidth (MHz) |         |
|-------|------------------------|-----------------------|---------|
|       |                        | Chain 0               | Chain 1 |
| 54    | 5270                   | 42.27                 | 42.42   |
| 62    | 5310                   | 42.23                 | 42.43   |
| 102   | 5510                   | 42.40                 | 42.47   |
| 110   | 5550                   | 42.18                 | 42.29   |
| 134   | 5670                   | 42.16                 | 42.07   |
| 142   | 5710<br>(For U-NII-2C) | 36.15                 | 36.37   |
| 142   | 5710<br>(For U-NII-3)  | 5.97                  | 6.19    |

For CH142 (U-NII-2C Band): The 26dBc bandwidth below 5725MHz = 5725MHz - Marker 1

For CH142 (UNII-3 Band): The 26dBc bandwidth above 5725MHz = Marker 1 + Delta 2 - 5725MHz

#### 802.11ax (HE80)


| Chan. | Freq.<br>(MHz)         | 26dBc Bandwidth (MHz) |         |
|-------|------------------------|-----------------------|---------|
|       |                        | Chain 0               | Chain 1 |
| 58    | 5290                   | 82.60                 | 82.50   |
| 106   | 5530                   | 83.03                 | 82.75   |
| 122   | 5610                   | 83.60                 | 82.12   |
| 138   | 5690<br>(For U-NII-2C) | 76.53                 | 76.34   |
| 138   | 5690<br>(For U-NII-3)  | 6.52                  | 6.22    |

For CH138 (U-NII-2C Band): The 26dBc bandwidth below 5725MHz = 5725MHz - Marker 1


For CH138 (UNII-3 Band): The 26dBc bandwidth above 5725MHz = Marker 1 + Delta 2 - 5725MHz

## Spectrum Plot of Worst Value


### 802.11a




### 802.11ax (HE20)



### 802.11ax (HE40)



### 802.11ax (HE80)



## EUT Average Power

### CDD Mode

#### 802.11a

| Frequency Band (MHz) | Max. Power         |                   |
|----------------------|--------------------|-------------------|
|                      | Output Power (dBm) | Output Power (mW) |
| 5250~5350            | 18.80              | 75.921            |
| 5470~5725            | 18.34              | 68.204            |

#### 802.11n (HT20)

| Frequency Band (MHz) | Max. Power         |                   |
|----------------------|--------------------|-------------------|
|                      | Output Power (dBm) | Output Power (mW) |
| 5250~5350            | 19.73              | 93.871            |
| 5470~5725            | 18.56              | 71.807            |

#### 802.11n (HT40)

| Frequency Band (MHz) | Max. Power         |                   |
|----------------------|--------------------|-------------------|
|                      | Output Power (dBm) | Output Power (mW) |
| 5250~5350            | 19.60              | 91.176            |
| 5470~5725            | 19.53              | 89.663            |

#### 802.11ac (VHT20)

| Frequency Band (MHz) | Max. Power         |                   |
|----------------------|--------------------|-------------------|
|                      | Output Power (dBm) | Output Power (mW) |
| 5250~5350            | 19.75              | 94.304            |
| 5470~5725            | 18.59              | 72.296            |

#### 802.11ac (VHT40)

| Frequency Band (MHz) | Max. Power         |                   |
|----------------------|--------------------|-------------------|
|                      | Output Power (dBm) | Output Power (mW) |
| 5250~5350            | 19.62              | 91.597            |
| 5470~5725            | 19.55              | 90.077            |

#### 802.11ac (VHT80)

| Frequency Band (MHz) | Max. Power         |                   |
|----------------------|--------------------|-------------------|
|                      | Output Power (dBm) | Output Power (mW) |
| 5250~5350            | 19.43              | 87.703            |
| 5470~5725            | 19.71              | 93.499            |

#### 802.11ax (HE20)

| Frequency Band (MHz) | Max. Power         |                   |
|----------------------|--------------------|-------------------|
|                      | Output Power (dBm) | Output Power (mW) |
| 5250~5350            | 19.79              | 95.177            |
| 5470~5725            | 18.62              | 72.797            |

#### 802.11ax (HE40)

| Frequency Band (MHz) | Max. Power         |                   |
|----------------------|--------------------|-------------------|
|                      | Output Power (dBm) | Output Power (mW) |
| 5250~5350            | 19.64              | 92.130            |
| 5470~5725            | 19.58              | 90.697            |

#### 802.11ax (HE80)

| Frequency Band (MHz) | Max. Power         |                   |
|----------------------|--------------------|-------------------|
|                      | Output Power (dBm) | Output Power (mW) |
| 5250~5350            | 19.47              | 88.602            |
| 5470~5725            | 19.74              | 94.147            |

## Beamforming Mode

### 802.11ac (VHT20)

| Frequency Band (MHz) | Max. Power         |                   |
|----------------------|--------------------|-------------------|
|                      | Output Power (dBm) | Output Power (mW) |
| 5250~5350            | 16.74              | 47.155            |
| 5470~5725            | 15.58              | 36.150            |

### 802.11ac (VHT40)

| Frequency Band (MHz) | Max. Power         |                   |
|----------------------|--------------------|-------------------|
|                      | Output Power (dBm) | Output Power (mW) |
| 5250~5350            | 16.61              | 45.802            |
| 5470~5725            | 16.54              | 45.042            |

### 802.11ac (VHT80)

| Frequency Band (MHz) | Max. Power         |                   |
|----------------------|--------------------|-------------------|
|                      | Output Power (dBm) | Output Power (mW) |
| 5250~5350            | 16.42              | 43.854            |
| 5470~5725            | 16.70              | 46.753            |

### 802.11ax (HE20)

| Frequency Band (MHz) | Max. Power         |                   |
|----------------------|--------------------|-------------------|
|                      | Output Power (dBm) | Output Power (mW) |
| 5250~5350            | 16.78              | 47.592            |
| 5470~5725            | 15.61              | 36.401            |

### 802.11ax (HE40)

| Frequency Band (MHz) | Max. Power         |                   |
|----------------------|--------------------|-------------------|
|                      | Output Power (dBm) | Output Power (mW) |
| 5250~5350            | 16.63              | 46.068            |
| 5470~5725            | 16.57              | 45.352            |

### 802.11ax (HE80)

| Frequency Band (MHz) | Max. Power        |                    |
|----------------------|-------------------|--------------------|
|                      | Output Power (mW) | Output Power (dBm) |
| 5250~5350            | 16.46             | 44.304             |
| 5470~5725            | 16.73             | 47.077             |

### Scanning radio (Radio 3)

#### Power Output:

#### 802.11a

| Chan. | Freq.<br>(MHz)         | Average Power<br>(mW) | Average Power<br>(dBm) | Power Limit (dBm) | Pass / Fail |
|-------|------------------------|-----------------------|------------------------|-------------------|-------------|
| 52    | 5260                   | 130.617               | 21.16                  | 24.00             | Pass        |
| 60    | 5300                   | 136.458               | 21.35                  | 24.00             | Pass        |
| 64    | 5320                   | 84.528                | 19.27                  | 24.00             | Pass        |
| 100   | 5500                   | 76.208                | 18.82                  | 24.00             | Pass        |
| 116   | 5580                   | 110.408               | 20.43                  | 24.00             | Pass        |
| 140   | 5700                   | 67.920                | 18.32                  | 24.00             | Pass        |
| 144   | 5720<br>(For U-NII-2C) | 83.368                | 19.21                  | 24.00             | Pass        |
| 144   | 5720<br>(For U-NII-3)  | 20.324                | 13.08                  | 30.00             | Pass        |

Note:

1.  $11\text{dBm} + 10\log(28.73) = 25.58 > 24\text{dBm}$
2.  $11\text{dBm} + 10\log(28.87) = 25.60 > 24\text{dBm}$
3.  $11\text{dBm} + 10\log(25.14) = 25.00 > 24\text{dBm}$
4.  $11\text{dBm} + 10\log(25.50) = 25.06 > 24\text{dBm}$
5.  $11\text{dBm} + 10\log(39.52) = 26.96 > 24\text{dBm}$
6.  $11\text{dBm} + 10\log(26.49) = 25.23 > 24\text{dBm}$
7.  $11\text{dBm} + 10\log(5725.00 - 5703.88) = 24.24 > 24\text{dBm}$

#### 802.11n (HT20)

| Chan. | Freq.<br>(MHz)         | Average Power<br>(mW) | Average Power<br>(dBm) | Power Limit (dBm) | Pass / Fail |
|-------|------------------------|-----------------------|------------------------|-------------------|-------------|
| 52    | 5260                   | 130.017               | 21.14                  | 24.00             | Pass        |
| 60    | 5300                   | 134.896               | 21.30                  | 24.00             | Pass        |
| 64    | 5320                   | 85.507                | 19.32                  | 24.00             | Pass        |
| 100   | 5500                   | 78.524                | 18.95                  | 24.00             | Pass        |
| 116   | 5580                   | 109.648               | 20.40                  | 24.00             | Pass        |
| 140   | 5700                   | 66.681                | 18.24                  | 24.00             | Pass        |
| 144   | 5720<br>(For U-NII-2C) | 79.616                | 19.01                  | 24.00             | Pass        |
| 144   | 5720<br>(For U-NII-3)  | 21.281                | 13.28                  | 30.00             | Pass        |

Note:

1.  $11\text{dBm} + 10\log(28.51) = 25.54 > 24\text{dBm}$
2.  $11\text{dBm} + 10\log(29.43) = 25.68 > 24\text{dBm}$
3.  $11\text{dBm} + 10\log(26.40) = 25.21 > 24\text{dBm}$
4.  $11\text{dBm} + 10\log(27.50) = 25.39 > 24\text{dBm}$
5.  $11\text{dBm} + 10\log(41.07) = 27.13 > 24\text{dBm}$
6.  $11\text{dBm} + 10\log(27.57) = 25.40 > 24\text{dBm}$
7.  $11\text{dBm} + 10\log(5725.00 - 5703.98) = 24.22 > 24\text{dBm}$

#### 802.11n (HT40)

| Chan. | Freq.<br>(MHz)         | Average Power<br>(mW) | Average Power<br>(dBm) | Power Limit (dBm) | Pass / Fail |
|-------|------------------------|-----------------------|------------------------|-------------------|-------------|
| 54    | 5270                   | 106.660               | 20.28                  | 24.00             | Pass        |
| 62    | 5310                   | 64.714                | 18.11                  | 24.00             | Pass        |
| 102   | 5510                   | 57.943                | 17.63                  | 24.00             | Pass        |
| 110   | 5550                   | 101.158               | 20.05                  | 24.00             | Pass        |
| 134   | 5670                   | 69.823                | 18.44                  | 24.00             | Pass        |
| 142   | 5710<br>(For U-NII-2C) | 87.297                | 19.41                  | 24.00             | Pass        |
| 142   | 5710<br>(For U-NII-3)  | 8.356                 | 9.22                   | 30.00             | Pass        |

Note:

1.  $11\text{dBm} + 10\log(54.37) = 28.35 > 24\text{dBm}$
2.  $11\text{dBm} + 10\log(49.84) = 27.97 > 24\text{dBm}$
3.  $11\text{dBm} + 10\log(50.88) = 28.06 > 24\text{dBm}$
4.  $11\text{dBm} + 10\log(76.52) = 29.83 > 24\text{dBm}$
5.  $11\text{dBm} + 10\log(53.59) = 28.29 > 24\text{dBm}$
6.  $11\text{dBm} + 10\log(5725.00 - 5678.04) = 27.71 > 24\text{dBm}$

#### 802.11ac (VHT20)

| Chan. | Freq.<br>(MHz)         | Average Power<br>(mW) | Average Power<br>(dBm) | Power Limit (dBm) | Pass / Fail |
|-------|------------------------|-----------------------|------------------------|-------------------|-------------|
| 52    | 5260                   | 133.352               | 21.25                  | 24.00             | Pass        |
| 60    | 5300                   | <b>138.995</b>        | 21.43                  | 24.00             | Pass        |
| 64    | 5320                   | 87.498                | 19.42                  | 24.00             | Pass        |
| 100   | 5500                   | 80.353                | 19.05                  | 24.00             | Pass        |
| 116   | 5580                   | <b>112.980</b>        | 20.53                  | 24.00             | Pass        |
| 140   | 5700                   | 67.920                | 18.32                  | 24.00             | Pass        |
| 144   | 5720<br>(For U-NII-2C) | 80.724                | 19.07                  | 24.00             | Pass        |
| 144   | 5720<br>(For U-NII-3)  | 21.827                | 13.39                  | 30.00             | Pass        |

Note:

1.  $11\text{dBm} + 10\log(28.51) = 25.54 > 24\text{dBm}$
2.  $11\text{dBm} + 10\log(29.43) = 25.68 > 24\text{dBm}$
3.  $11\text{dBm} + 10\log(26.40) = 25.21 > 24\text{dBm}$
4.  $11\text{dBm} + 10\log(27.50) = 25.39 > 24\text{dBm}$
5.  $11\text{dBm} + 10\log(41.07) = 27.13 > 24\text{dBm}$
6.  $11\text{dBm} + 10\log(27.57) = 25.40 > 24\text{dBm}$
7.  $11\text{dBm} + 10\log(5725.00 - 5703.98) = 24.22 > 24\text{dBm}$

#### 802.11ac (VHT40)

| Chan. | Freq.<br>(MHz)         | Average Power<br>(mW) | Average Power<br>(dBm) | Power Limit (dBm) | Pass / Fail |
|-------|------------------------|-----------------------|------------------------|-------------------|-------------|
| 54    | 5270                   | 107.647               | 20.32                  | 24.00             | Pass        |
| 62    | 5310                   | 66.222                | 18.21                  | 24.00             | Pass        |
| 102   | 5510                   | 59.156                | 17.72                  | 24.00             | Pass        |
| 110   | 5550                   | 103.992               | 20.17                  | 24.00             | Pass        |
| 134   | 5670                   | 71.121                | 18.52                  | 24.00             | Pass        |
| 142   | 5710<br>(For U-NII-2C) | 89.536                | 19.52                  | 24.00             | Pass        |
| 142   | 5710<br>(For U-NII-3)  | 8.531                 | 9.31                   | 30.00             | Pass        |

Note:

1.  $11\text{dBm} + 10\log(54.37) = 28.35 > 24\text{dBm}$
2.  $11\text{dBm} + 10\log(49.84) = 27.97 > 24\text{dBm}$
3.  $11\text{dBm} + 10\log(50.88) = 28.06 > 24\text{dBm}$
4.  $11\text{dBm} + 10\log(76.52) = 29.83 > 24\text{dBm}$
5.  $11\text{dBm} + 10\log(53.59) = 28.29 > 24\text{dBm}$
6.  $11\text{dBm} + 10\log(5725.00 - 5678.04) = 27.71 > 24\text{dBm}$

802.11ac (VHT80)


| Chan. | Freq.<br>(MHz)         | Average Power<br>(mW) | Average Power<br>(dBm) | Power Limit (dBm) | Pass / Fail |
|-------|------------------------|-----------------------|------------------------|-------------------|-------------|
| 58    | 5290                   | 3.412                 | 5.33                   | 24.00             | Pass        |
| 106   | 5530                   | 11.561                | 10.63                  | 24.00             | Pass        |
| 122   | 5610                   | 64.863                | 18.12                  | 24.00             | Pass        |
| 138   | 5690<br>(For U-NII-2C) | 89.536                | 19.52                  | 24.00             | Pass        |
| 138   | 5690<br>(For U-NII-3)  | 8.531                 | 9.31                   | 30.00             | Pass        |

Note:


1.  $11\text{dBm} + 10\log(99.26) = 30.96 > 24\text{dBm}$
2.  $11\text{dBm} + 10\log(98.77) = 30.94 > 24\text{dBm}$
3.  $11\text{dBm} + 10\log(103.67) = 31.15 > 24\text{dBm}$
4.  $11\text{dBm} + 10\log(5725.00 - 5616.69) = 31.35 > 24\text{dBm}$

## Straddle channel power plots:


802.11a



802.11ac (VHT20)




802.11ac (VHT40)




## 802.11ac (VHT80)

CH 138 (For U-NII-2C)



CH 138 (For U-NII-3)



26dB Bandwidth:

802.11a

| Chan. | Freq. (MHz)            | 26dBc Bandwidth (MHz) |
|-------|------------------------|-----------------------|
| 52    | 5260                   | 28.73                 |
| 60    | 5300                   | 28.87                 |
| 64    | 5320                   | 25.14                 |
| 100   | 5500                   | 25.50                 |
| 116   | 5580                   | 39.52                 |
| 140   | 5700                   | 26.49                 |
| 144   | 5720<br>(For U-NII-2C) | 21.12                 |
| 144   | 5720<br>(For U-NII-3)  | 10.42                 |

For CH144 (U-NII-2C Band): The 26dBc bandwidth below 5725MHz = 5725MHz - Marker 1

For CH144 (U-NII-3 Band): The 26dBc bandwidth above 5725MHz = Marker 1 + Delta 2 - 5725MHz

802.11ac (VHT20)

| Chan. | Freq. (MHz)            | 26dBc Bandwidth (MHz) |
|-------|------------------------|-----------------------|
| 52    | 5260                   | 28.51                 |
| 60    | 5300                   | 29.43                 |
| 64    | 5320                   | 26.40                 |
| 100   | 5500                   | 27.50                 |
| 116   | 5580                   | 41.07                 |
| 140   | 5700                   | 27.57                 |
| 144   | 5720<br>(For U-NII-2C) | 21.02                 |
| 144   | 5720<br>(For U-NII-3)  | 10.97                 |

For CH144 (U-NII-2C Band): The 26dBc bandwidth below 5725MHz = 5725MHz - Marker 1

For CH144 (U-NII-3 Band): The 26dBc bandwidth above 5725MHz = Marker 1 + Delta 2 - 5725MHz

#### 802.11ac (VHT40)

| Chan. | Freq. (MHz)            | 26dBc Bandwidth (MHz) |
|-------|------------------------|-----------------------|
| 54    | 5270                   | 54.37                 |
| 62    | 5310                   | 49.84                 |
| 102   | 5510                   | 50.88                 |
| 110   | 5550                   | 76.52                 |
| 134   | 5670                   | 53.59                 |
| 142   | 5710<br>(For U-NII-2C) | 46.96                 |
| 142   | 5710<br>(For U-NII-3)  | 15.83                 |

For CH142 (U-NII-2C Band): The 26dBc bandwidth below 5725MHz = 5725MHz - Marker 1

For CH142 (U-NII-3 Band): The 26dBc bandwidth above 5725MHz = Marker 1 + Delta 2 - 5725MHz

#### 802.11ac (VHT80)


| Chan. | Freq. (MHz)            | 26dBc Bandwidth (MHz) |
|-------|------------------------|-----------------------|
| 58    | 5290                   | 99.26                 |
| 106   | 5530                   | 98.77                 |
| 122   | 5610                   | 103.67                |
| 138   | 5690<br>(For U-NII-2C) | 108.31                |
| 138   | 5690<br>(For U-NII-3)  | 33.70                 |

For CH138 (U-NII-2C Band): The 26dBc bandwidth below 5725MHz = 5725MHz - Marker 1


For CH138 (U-NII-3 Band): The 26dBc bandwidth above 5725MHz = Marker 1 + Delta 2 - 5725MHz

## Spectrum Plot of Worst Value


### 802.11a




### 802.11ac (VHT20)



### 802.11ac (VHT40)



### 802.11ac (VHT80)



## EUT Average Power

### 802.11a

| Frequency Band (MHz) | Max. Power         |                   |
|----------------------|--------------------|-------------------|
|                      | Output Power (dBm) | Output Power (mW) |
| 5250~5350            | 21.35              | 136.458           |
| 5470~5725            | 20.43              | 110.408           |

### 802.11n (HT20)

| Frequency Band (MHz) | Max. Power         |                   |
|----------------------|--------------------|-------------------|
|                      | Output Power (dBm) | Output Power (mW) |
| 5250~5350            | 21.30              | 134.896           |
| 5470~5725            | 20.40              | 109.648           |

### 802.11n (HT40)

| Frequency Band (MHz) | Max. Power         |                   |
|----------------------|--------------------|-------------------|
|                      | Output Power (dBm) | Output Power (mW) |
| 5250~5350            | 20.28              | 106.660           |
| 5470~5725            | 20.05              | 101.158           |

### 802.11ac (VHT20)

| Frequency Band (MHz) | Max. Power         |                   |
|----------------------|--------------------|-------------------|
|                      | Output Power (dBm) | Output Power (mW) |
| 5250~5350            | 21.43              | 138.995           |
| 5470~5725            | 20.53              | 112.980           |

### 802.11ac (VHT40)


| Frequency Band (MHz) | Max. Power         |                   |
|----------------------|--------------------|-------------------|
|                      | Output Power (dBm) | Output Power (mW) |
| 5250~5350            | 20.32              | 107.647           |
| 5470~5725            | 20.17              | 103.992           |

### 802.11ac (VHT80)

| Frequency Band (MHz) | Max. Power         |                   |
|----------------------|--------------------|-------------------|
|                      | Output Power (dBm) | Output Power (mW) |
| 5250~5350            | 5.33               | 3.412             |
| 5470~5725            | 19.52              | 89.536            |

## 4.4 Occupied Bandwidth Measurement

### 4.4.1 Test Setup



### 4.4.2 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.4.3 Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with resolution bandwidth in the range of 1% to 5% of the anticipated emission bandwidth, and a video bandwidth at least 3x the resolution bandwidth and set the detector to sampling. The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 %of the total mean power of a given emission.

#### 4.4.4 Test Result

5G traffic radio (Radio 2)

802.11a

| Chan. | Freq.<br>(MHz)         | Occupied Bandwidth (MHz) |         |
|-------|------------------------|--------------------------|---------|
|       |                        | Chain 0                  | Chain 1 |
| 52    | 5260                   | 16.44                    | 16.44   |
| 60    | 5300                   | 16.44                    | 16.44   |
| 64    | 5320                   | 16.44                    | 16.44   |
| 100   | 5500                   | 16.44                    | 16.44   |
| 116   | 5580                   | 16.44                    | 16.44   |
| 140   | 5700                   | 16.44                    | 16.44   |
| 144   | 5720<br>(For U-NII-2C) | 13.28                    | 13.28   |
| 144   | 5720<br>(For U-NII-3)  | 3.16                     | 3.16    |

For CH144 (U-NII-2C Band): The Occupied bandwidth below 5725MHz = 5725MHz - Marker 1

For CH144 (U-NII-3 Band): The Occupied bandwidth above 5725MHz = Marker 1 + Delta 2 - 5725MHz

802.11ax (HE20)

| Chan. | Freq.<br>(MHz)         | Occupied Bandwidth (MHz) |         |
|-------|------------------------|--------------------------|---------|
|       |                        | Chain 0                  | Chain 1 |
| 52    | 5260                   | 18.96                    | 18.96   |
| 60    | 5300                   | 18.96                    | 18.96   |
| 64    | 5320                   | 18.84                    | 18.96   |
| 100   | 5500                   | 18.96                    | 19.08   |
| 116   | 5580                   | 18.96                    | 18.96   |
| 140   | 5700                   | 18.96                    | 18.96   |
| 144   | 5720<br>(For U-NII-2C) | 14.60                    | 14.60   |
| 144   | 5720<br>(For U-NII-3)  | 4.36                     | 4.36    |

For CH144 (U-NII-2C Band): The Occupied bandwidth below 5725MHz = 5725MHz - Marker 1

For CH144 (U-NII-3 Band): The Occupied bandwidth above 5725MHz = Marker 1 + Delta 2 - 5725MHz

#### 802.11ax (HE40)

| Chan. | Freq.<br>(MHz)         | Occupied Bandwidth (MHz) |         |
|-------|------------------------|--------------------------|---------|
|       |                        | Chain 0                  | Chain 1 |
| 54    | 5270                   | 37.92                    | 37.80   |
| 62    | 5310                   | 38.04                    | 37.92   |
| 102   | 5510                   | 37.92                    | 38.04   |
| 110   | 5550                   | 37.92                    | 37.92   |
| 134   | 5670                   | 38.04                    | 37.92   |
| 142   | 5710<br>(For U-NII-2C) | 34.08                    | 34.08   |
| 142   | 5710<br>(For U-NII-3)  | 3.84                     | 3.84    |

For CH142 (U-NII-2C Band): The Occupied bandwidth below 5725MHz = 5725MHz - Marker 1

For CH142 (U-NII-3 Band): The Occupied bandwidth above 5725MHz = Marker 1 + Delta 2 - 5725MHz

#### 802.11ax (HE80)


| Chan. | Freq.<br>(MHz)         | Occupied Bandwidth (MHz) |         |
|-------|------------------------|--------------------------|---------|
|       |                        | Chain 0                  | Chain 1 |
| 58    | 5290                   | 77.28                    | 77.28   |
| 106   | 5530                   | 77.04                    | 77.04   |
| 122   | 5610                   | 77.28                    | 77.28   |
| 138   | 5690<br>(For U-NII-2C) | 73.64                    | 73.64   |
| 138   | 5690<br>(For U-NII-3)  | 3.64                     | 3.64    |

For CH138 (U-NII-2C Band): The Occupied bandwidth below 5725MHz = 5725MHz - Marker 1


For CH138 (U-NII-3 Band): The Occupied bandwidth above 5725MHz = Marker 1 + Delta 2 - 5725MHz

## Spectrum Plot of Worst Value


### 802.11a




### 802.11ax (HE20)



### 802.11ax (HE40)



### 802.11ax (HE80)



### Scanning radio (Radio 3)

#### 802.11a

| Chan. | Freq.<br>(MHz)         | Occupied Bandwidth (MHz) |
|-------|------------------------|--------------------------|
| 52    | 5260                   | 17.64                    |
| 60    | 5300                   | 18.00                    |
| 64    | 5320                   | 17.16                    |
| 100   | 5500                   | 17.16                    |
| 116   | 5580                   | 22.32                    |
| 140   | 5700                   | 17.28                    |
| 144   | 5720<br>(For U-NII-2C) | 14.24                    |
| 144   | 5720<br>(For U-NII-3)  | 3.64                     |

For CH144 (U-NII-2C Band): The Occupied bandwidth below 5725MHz = 5725MHz - Marker 1

For CH144 (U-NII-3 Band): The Occupied bandwidth above 5725MHz = Marker 1 + Delta 2 - 5725MHz

#### 802.11ac (VHT20)

| Chan. | Freq.<br>(MHz)         | Occupied Bandwidth (MHz) |
|-------|------------------------|--------------------------|
| 52    | 5260                   | 18.48                    |
| 60    | 5300                   | 18.60                    |
| 64    | 5320                   | 18.24                    |
| 100   | 5500                   | 18.24                    |
| 116   | 5580                   | 22.44                    |
| 140   | 5700                   | 18.24                    |
| 144   | 5720<br>(For U-NII-2C) | 14.60                    |
| 144   | 5720<br>(For U-NII-3)  | 4.24                     |

For CH144 (U-NII-2C Band): The Occupied bandwidth below 5725MHz = 5725MHz - Marker 1

For CH144 (U-NII-3 Band): The Occupied bandwidth above 5725MHz = Marker 1 + Delta 2 - 5725MHz

#### 802.11ac (VHT40)

| Chan. | Freq.<br>(MHz)         | Occupied Bandwidth (MHz) |
|-------|------------------------|--------------------------|
| 54    | 5270                   | 37.56                    |
| 62    | 5310                   | 37.20                    |
| 102   | 5510                   | 37.32                    |
| 110   | 5550                   | 38.04                    |
| 134   | 5670                   | 37.44                    |
| 142   | 5710<br>(For U-NII-2C) | 33.60                    |
| 142   | 5710<br>(For U-NII-3)  | 3.84                     |

For CH142 (U-NII-2C Band): The Occupied bandwidth below 5725MHz = 5725MHz - Marker 1

For CH142 (U-NII-3 Band): The Occupied bandwidth above 5725MHz = Marker 1 + Delta 2 - 5725MHz

#### 802.11ac (VHT80)


| Chan. | Freq.<br>(MHz)         | Occupied Bandwidth (MHz) |
|-------|------------------------|--------------------------|
| 58    | 5290                   | 77.28                    |
| 106   | 5530                   | 76.32                    |
| 122   | 5610                   | 76.80                    |
| 138   | 5690<br>(For U-NII-2C) | 73.88                    |
| 138   | 5690<br>(For U-NII-3)  | 3.40                     |

For CH138 (U-NII-2C Band): The Occupied bandwidth below 5725MHz = 5725MHz - Marker 1


For CH138 (U-NII-3 Band): The Occupied bandwidth above 5725MHz = Marker 1 + Delta 2 - 5725MHz

## Spectrum Plot of Worst Value


### 802.11a




### 802.11ac (VHT20)



### 802.11ac (VHT40)



### 802.11ac (VHT80)




## 4.5 Peak Power Spectral Density Measurement

### 4.5.1 Limits of Peak Power Spectral Density Measurement

| Operation Band | EUT Category |                                   | Limit         |
|----------------|--------------|-----------------------------------|---------------|
| U-NII-1        |              | Outdoor Access Point              | 17dBm/ MHz    |
|                |              | Fixed point-to-point Access Point |               |
|                |              | Indoor Access Point               |               |
|                |              | Mobile and Portable client device | 11dBm/ MHz    |
| U-NII-2A       | √            |                                   | 11dBm/ MHz    |
| U-NII-2C       | √            |                                   | 11dBm/ MHz    |
| U-NII-3        | √            |                                   | 30dBm/ 500kHz |

### 4.5.2 Test Setup



### 4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.5.4 Test Procedures

For U-NII-2A and U-NII-2C band:

Using method SA-2

- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 1MHz, Set VBW  $\geq$  3 MHz, Detector = RMS
- Set Channel power measure = 1MHz
- Sweep time = auto, trigger set to "free run".
- Trace average at least 100 traces in power averaging mode.
- Record the max value and add 10 log (1/duty cycle)

For U-NII-3 band:

- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 300 kHz, Set VBW  $\geq$  1 MHz, Detector = RMS
- Use the peak marker function to determine the maximum power level in any 300 kHz band segment within the fundamental EBW.
- Scale the observed power level to an equivalent value in 500 kHz by adjusting (increasing) the measured power by a bandwidth correction factor (BWCF) where  $BWCF = 10\log(500 \text{ kHz} / 300 \text{ kHz})$
- Sweep time = auto, trigger set to "free run".
- Trace average at least 100 traces in power averaging mode.
- Record the max value and add 10 log (1/duty cycle)

#### **4.5.5 Deviation from Test Standard**

No deviation.

#### **4.5.6 EUT Operating Conditions**

Same as 4.3.6.

#### 4.5.7 Test Results

5G traffic radio (Radio 2)

For U-NII-2A and U-NII-2C band:

##### 802.11a

| Chan. | Freq.<br>(MHz)         | PSD w/o Duty Factor (dBm/MHz) |         | Duty<br>Factor<br>(dB) | Total PSD with<br>Duty Factor<br>(dBm/MHz) | Max. Limit<br>(dBm/MHz) | Pass /<br>Fail |
|-------|------------------------|-------------------------------|---------|------------------------|--------------------------------------------|-------------------------|----------------|
|       |                        | Chain 0                       | Chain 1 |                        |                                            |                         |                |
| 52    | 5260                   | 0.41                          | 0.34    | 0.38                   | 3.76                                       | 3.89                    | Pass           |
| 60    | 5300                   | 0.35                          | 0.46    | 0.38                   | 3.79                                       | 3.89                    | Pass           |
| 64    | 5320                   | 0.25                          | 0.27    | 0.38                   | 3.65                                       | 3.89                    | Pass           |
| 100   | 5500                   | 0.05                          | 0.39    | 0.38                   | 3.61                                       | 3.89                    | Pass           |
| 116   | 5580                   | 0.54                          | 0.12    | 0.38                   | 3.72                                       | 3.89                    | Pass           |
| 140   | 5700                   | 0.62                          | 0.15    | 0.38                   | 3.78                                       | 3.89                    | Pass           |
| 144   | 5720<br>(For U-NII-2C) | 0.41                          | 0.00    | 0.38                   | 3.60                                       | 3.89                    | Pass           |

Note:

- Method E) 2) a) of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
- Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 13.11\text{dBi} > 6\text{dBi}$ , so the power density limit shall be reduced to  $11 - (13.11 - 6) = 3.89\text{dBm}$ .
- Refer to section 3.3 for duty cycle spectrum plot.

##### 802.11ax (HE20)

| Chan. | Freq.<br>(MHz)         | PSD w/o Duty Factor (dBm/MHz) |         | Duty<br>Factor<br>(dB) | Total PSD with<br>Duty Factor<br>(dBm/MHz) | Max. Limit<br>(dBm/MHz) | Pass /<br>Fail |
|-------|------------------------|-------------------------------|---------|------------------------|--------------------------------------------|-------------------------|----------------|
|       |                        | Chain 0                       | Chain 1 |                        |                                            |                         |                |
| 52    | 5260                   | 0.35                          | -0.02   | 0.35                   | 3.53                                       | 3.89                    | Pass           |
| 60    | 5300                   | -0.30                         | 0.56    | 0.35                   | 3.52                                       | 3.89                    | Pass           |
| 64    | 5320                   | -0.05                         | 0.59    | 0.35                   | 3.65                                       | 3.89                    | Pass           |
| 100   | 5500                   | 0.71                          | -0.53   | 0.35                   | 3.50                                       | 3.89                    | Pass           |
| 116   | 5580                   | 0.70                          | -0.51   | 0.35                   | 3.50                                       | 3.89                    | Pass           |
| 140   | 5700                   | 0.41                          | 0.21    | 0.35                   | 3.68                                       | 3.89                    | Pass           |
| 144   | 5720<br>(For U-NII-2C) | -0.18                         | 0.40    | 0.35                   | 3.48                                       | 3.89                    | Pass           |

Note:

- Method E) 2) a) of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
- Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 13.11\text{dBi} > 6\text{dBi}$ , so the power density limit shall be reduced to  $11 - (13.11 - 6) = 3.89\text{dBm}$ .
- Refer to section 3.3 for duty cycle spectrum plot.

#### 802.11ax (HE40)

| Chan. | Freq.<br>(MHz)         | PSD w/o Duty Factor (dBm/MHz) |         | Duty<br>Factor<br>(dB) | Total PSD with<br>Duty Factor<br>(dBm/MHz) | Max. Limit<br>(dBm/MHz) | Pass /<br>Fail |
|-------|------------------------|-------------------------------|---------|------------------------|--------------------------------------------|-------------------------|----------------|
|       |                        | Chain 0                       | Chain 1 |                        |                                            |                         |                |
| 54    | 5270                   | -2.22                         | -2.34   | 0.79                   | 1.52                                       | 3.89                    | Pass           |
| 62    | 5310                   | -3.26                         | -2.35   | 0.79                   | 1.02                                       | 3.89                    | Pass           |
| 102   | 5510                   | -1.97                         | -3.01   | 0.79                   | 1.34                                       | 3.89                    | Pass           |
| 110   | 5550                   | -1.99                         | -1.60   | 0.79                   | 2.01                                       | 3.89                    | Pass           |
| 134   | 5670                   | -1.16                         | -2.07   | 0.79                   | 2.21                                       | 3.89                    | Pass           |
| 142   | 5710<br>(For U-NII-2C) | -1.07                         | -1.72   | 0.79                   | 2.41                                       | 3.89                    | Pass           |

Note:

- Method E) 2) a) of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
- Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 13.11\text{dBi} > 6\text{dBi}$ , so the power density limit shall be reduced to  $11 - (13.11 - 6) = 3.89\text{dBm}$ .
- Refer to section 3.3 for duty cycle spectrum plot.

#### 802.11ax (HE80)


| Chan. | Freq.<br>(MHz)         | PSD w/o Duty Factor (dBm/MHz) |         | Duty<br>Factor<br>(dB) | Total PSD with<br>Duty Factor<br>(dBm/MHz) | Max. Limit<br>(dBm/MHz) | Pass /<br>Fail |
|-------|------------------------|-------------------------------|---------|------------------------|--------------------------------------------|-------------------------|----------------|
|       |                        | Chain 0                       | Chain 1 |                        |                                            |                         |                |
| 58    | 5290                   | -6.40                         | -5.57   | 0.34                   | -2.62                                      | 3.89                    | Pass           |
| 106   | 5530                   | -4.75                         | -4.26   | 0.34                   | -1.15                                      | 3.89                    | Pass           |
| 122   | 5610                   | -4.51                         | -3.85   | 0.34                   | -0.82                                      | 3.89                    | Pass           |
| 138   | 5690<br>(For U-NII-2C) | -4.54                         | -3.96   | 0.34                   | -0.89                                      | 3.89                    | Pass           |

Note:


- Method E) 2) a) of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
- Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 13.11\text{dBi} > 6\text{dBi}$ , so the power density limit shall be reduced to  $11 - (13.11 - 6) = 3.89\text{dBm}$ .
- Refer to section 3.3 for duty cycle spectrum plot.

## Spectrum Plot of Worst Value


802.11a / Chain 0 / CH 140




802.11ax (HE20) / Chain 0 / CH 100



802.11ax (HE40) / Chain 0 / CH 142



802.11ax (HE80) / Chain 1 / CH 122



For U-NII-3 band:

#### 802.11a

| TX chain | Chan. | Freq. (MHz)           | PSD W/O Duty Factor |              | 10 log (N=2) dB | Duty Factor (dB) | Total PSD With Duty Factor (dBm/500kHz) | Limit (dBm/500kHz) | Pass / Fail |
|----------|-------|-----------------------|---------------------|--------------|-----------------|------------------|-----------------------------------------|--------------------|-------------|
|          |       |                       | (dBm/300kHz)        | (dBm/500kHz) |                 |                  |                                         |                    |             |
| 0        | 144   | 5720<br>(For U-NII-3) | -7.62               | -5.40        | 3.01            | 0.38             | -2.01                                   | 22.89              | Pass        |
| 1        | 144   | 5720<br>(For U-NII-3) | -7.82               | -5.60        | 3.01            | 0.38             | -2.21                                   | 22.89              | Pass        |

Note:

1. Method E) 2) c) of power density measurement of KDB 662911 is using for calculating total power density, Measure and add 10 log (N<sub>ANT</sub>) dB.
2. Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 13.11\text{dBi} > 6\text{dBi}$ , so the power density limit shall be reduced to 30 - (13.11 - 6) = 22.89dBm.
3. Refer to section 3.3 for duty cycle spectrum plot.

#### 802.11ax (HE20)

| TX chain | Chan. | Freq. (MHz)           | PSD W/O Duty Factor |              | 10 log (N=2) dB | Duty Factor (dB) | Total PSD With Duty Factor (dBm/500kHz) | Limit (dBm/500kHz) | Pass / Fail |
|----------|-------|-----------------------|---------------------|--------------|-----------------|------------------|-----------------------------------------|--------------------|-------------|
|          |       |                       | (dBm/300kHz)        | (dBm/500kHz) |                 |                  |                                         |                    |             |
| 0        | 144   | 5720<br>(For U-NII-3) | -9.09               | -6.87        | 3.01            | 0.35             | -3.51                                   | 22.89              | Pass        |
| 1        | 144   | 5720<br>(For U-NII-3) | -9.19               | -6.97        | 3.01            | 0.35             | -3.61                                   | 22.89              | Pass        |

Note:

1. Method E) 2) c) of power density measurement of KDB 662911 is using for calculating total power density, Measure and add 10 log (N<sub>ANT</sub>) dB.
2. Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 13.11\text{dBi} > 6\text{dBi}$ , so the power density limit shall be reduced to 30 - (13.11 - 6) = 22.89dBm.
3. Refer to section 3.3 for duty cycle spectrum plot.

#### 802.11ax (HE40)

| TX chain | Chan. | Freq. (MHz)           | PSD W/O Duty Factor |              | 10 log (N=2) dB | Duty Factor (dB) | Total PSD With Duty Factor (dBm/500kHz) | Limit (dBm/500kHz) | Pass / Fail |
|----------|-------|-----------------------|---------------------|--------------|-----------------|------------------|-----------------------------------------|--------------------|-------------|
|          |       |                       | (dBm/300kHz)        | (dBm/500kHz) |                 |                  |                                         |                    |             |
| 0        | 142   | 5710<br>(For U-NII-3) | -11.61              | -9.39        | 3.01            | 0.79             | -5.59                                   | 22.89              | Pass        |
| 1        | 142   | 5710<br>(For U-NII-3) | -11.90              | -9.68        | 3.01            | 0.79             | -5.88                                   | 22.89              | Pass        |

Note:


1. Method E) 2) c) of power density measurement of KDB 662911 is using for calculating total power density, Measure and add 10 log (N<sub>ANT</sub>) dB.
2. Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 13.11\text{dBi} > 6\text{dBi}$ , so the power density limit shall be reduced to 30 - (13.11 - 6) = 22.89dBm.
3. Refer to section 3.3 for duty cycle spectrum plot.

## 802.11ax (HE80)

| TX chain | Chan. | Freq. (MHz)           | PSD W/O Duty Factor |              | 10 log (N=2) dB | Duty Factor (dB) | Total PSD With Duty Factor (dBm/500kHz) | Limit (dBm/500kHz) | Pass / Fail |
|----------|-------|-----------------------|---------------------|--------------|-----------------|------------------|-----------------------------------------|--------------------|-------------|
|          |       |                       | (dBm/300kHz)        | (dBm/500kHz) |                 |                  |                                         |                    |             |
| 0        | 138   | 5690<br>(For U-NII-3) | -15.10              | -12.88       | 3.01            | 0.34             | -9.53                                   | 22.89              | Pass        |
| 1        | 138   | 5690<br>(For U-NII-3) | -15.92              | -13.70       | 3.01            | 0.34             | -10.35                                  | 22.89              | Pass        |

Note:

- Method E) 2) c) of power density measurement of KDB 662911 is using for calculating total power density, Measure and add 10 log (N<sub>ANT</sub>) dB.
- Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 13.11\text{dBi} > 6\text{dBi}$ , so the power density limit shall be reduced to  $30 - (13.11 - 6) = 22.89\text{dBm}$ .
- Refer to section 3.3 for duty cycle spectrum plot.



### Scanning radio (Radio 3)

For U-NII-2A and U-NII-2C band:

#### 802.11a

| Chan. | Freq.<br>(MHz)         | PSD w/o Duty<br>Factor<br>(dBm/MHz) | Duty Factor<br>(dB) | PSD with Duty<br>Factor<br>(dBm/MHz) | Max. Limit<br>(dBm/MHz) | Pass / Fail |
|-------|------------------------|-------------------------------------|---------------------|--------------------------------------|-------------------------|-------------|
| 52    | 5260                   | 6.74                                | 0.24                | 6.98                                 | 11.00                   | Pass        |
| 60    | 5300                   | 6.99                                | 0.24                | 7.23                                 | 11.00                   | Pass        |
| 64    | 5320                   | 5.19                                | 0.24                | 5.43                                 | 11.00                   | Pass        |
| 100   | 5500                   | 4.91                                | 0.24                | 5.15                                 | 11.00                   | Pass        |
| 116   | 5580                   | 6.54                                | 0.24                | 6.78                                 | 11.00                   | Pass        |
| 140   | 5700                   | 4.48                                | 0.24                | 4.72                                 | 11.00                   | Pass        |
| 144   | 5720<br>(For U-NII-2C) | 5.35                                | 0.24                | 5.59                                 | 11.00                   | Pass        |

Note: Refer to section 3.3 for duty cycle spectrum plot.

#### 802.11ac (VHT20)

| Chan. | Freq.<br>(MHz)         | PSD w/o Duty<br>Factor<br>(dBm/MHz) | Duty Factor<br>(dB) | PSD with Duty<br>Factor<br>(dBm/MHz) | Max. Limit<br>(dBm/MHz) | Pass / Fail |
|-------|------------------------|-------------------------------------|---------------------|--------------------------------------|-------------------------|-------------|
| 52    | 5260                   | 6.39                                | 0.26                | 6.65                                 | 11.00                   | Pass        |
| 60    | 5300                   | 6.61                                | 0.26                | 6.87                                 | 11.00                   | Pass        |
| 64    | 5320                   | 4.77                                | 0.26                | 5.04                                 | 11.00                   | Pass        |
| 100   | 5500                   | 4.50                                | 0.26                | 4.77                                 | 11.00                   | Pass        |
| 116   | 5580                   | 6.02                                | 0.26                | 6.28                                 | 11.00                   | Pass        |
| 140   | 5700                   | 3.96                                | 0.26                | 4.22                                 | 11.00                   | Pass        |
| 144   | 5720<br>(For U-NII-2C) | 4.90                                | 0.26                | 5.17                                 | 11.00                   | Pass        |

Note: Refer to section 3.3 for duty cycle spectrum plot.

#### 802.11ac (VHT40)


| Chan. | Freq.<br>(MHz)         | PSD w/o Duty<br>Factor<br>(dBm/MHz) | Duty Factor<br>(dB) | PSD with Duty<br>Factor<br>(dBm/MHz) | Max. Limit<br>(dBm/MHz) | Pass / Fail |
|-------|------------------------|-------------------------------------|---------------------|--------------------------------------|-------------------------|-------------|
| 54    | 5270                   | 2.71                                | 0.56                | 3.27                                 | 11.00                   | Pass        |
| 62    | 5310                   | 0.60                                | 0.56                | 1.16                                 | 11.00                   | Pass        |
| 102   | 5510                   | 0.09                                | 0.56                | 0.65                                 | 11.00                   | Pass        |
| 110   | 5550                   | 2.46                                | 0.56                | 3.02                                 | 11.00                   | Pass        |
| 134   | 5670                   | 1.21                                | 0.56                | 1.77                                 | 11.00                   | Pass        |
| 142   | 5710<br>(For U-NII-2C) | 1.57                                | 0.56                | 2.13                                 | 11.00                   | Pass        |

Note: Refer to section 3.3 for duty cycle spectrum plot.

## 802.11ac (VHT80)

| Chan. | Freq. (MHz)            | PSD w/o Duty Factor (dBm/MHz) | Duty Factor (dB) | PSD with Duty Factor (dBm/MHz) | Max. Limit (dBm/MHz) | Pass / Fail |
|-------|------------------------|-------------------------------|------------------|--------------------------------|----------------------|-------------|
| 58    | 5290                   | -15.13                        | 0.36             | -14.77                         | 11.00                | Pass        |
| 106   | 5530                   | -10.38                        | 0.36             | -10.02                         | 11.00                | Pass        |
| 122   | 5610                   | -2.97                         | 0.36             | -2.61                          | 11.00                | Pass        |
| 138   | 5690<br>(For U-NII-2C) | -1.17                         | 0.36             | -0.81                          | 11.00                | Pass        |

Note: Refer to section 3.3 for duty cycle spectrum plot.



For U-NII-3 band:

802.11a

| Chan. | Freq.<br>(MHz)        | PSD w/o Duty Factor |              | Duty<br>Factor<br>(dB) | Total PSD with<br>Duty Factor<br>(dBm/500kHz) | Limit<br>(dBm/500kHz) | Pass<br>/ Fail |
|-------|-----------------------|---------------------|--------------|------------------------|-----------------------------------------------|-----------------------|----------------|
|       |                       | (dBm/300kHz)        | (dBm/500kHz) |                        |                                               |                       |                |
| 144   | 5720<br>(For U-NII-3) | -3.23               | -1.01        | 0.24                   | -0.77                                         | 30.00                 | Pass           |

Note: Refer to section 3.3 for duty cycle spectrum plot.

802.11ac (VHT20)

| Chan. | Freq.<br>(MHz)        | PSD w/o Duty Factor |              | Duty<br>Factor<br>(dB) | Total PSD with<br>Duty Factor<br>(dBm/500kHz) | Limit<br>(dBm/500kHz) | Pass<br>/ Fail |
|-------|-----------------------|---------------------|--------------|------------------------|-----------------------------------------------|-----------------------|----------------|
|       |                       | (dBm/300kHz)        | (dBm/500kHz) |                        |                                               |                       |                |
| 144   | 5720<br>(For U-NII-3) | -3.58               | -1.36        | 0.26                   | -1.10                                         | 30.00                 | Pass           |

Note: Refer to section 3.3 for duty cycle spectrum plot.

802.11ac (VHT40)

| Chan. | Freq.<br>(MHz)        | PSD w/o Duty Factor |              | Duty<br>Factor<br>(dB) | Total PSD with<br>Duty Factor<br>(dBm/500kHz) | Limit<br>(dBm/500kHz) | Pass<br>/ Fail |
|-------|-----------------------|---------------------|--------------|------------------------|-----------------------------------------------|-----------------------|----------------|
|       |                       | (dBm/300kHz)        | (dBm/500kHz) |                        |                                               |                       |                |
| 142   | 5710<br>(For U-NII-3) | -8.03               | -5.81        | 0.56                   | -5.25                                         | 30.00                 | Pass           |

Note: Refer to section 3.3 for duty cycle spectrum plot.


802.11ac (VHT80)

| Chan. | Freq.<br>(MHz)        | PSD w/o Duty Factor |              | Duty<br>Factor<br>(dB) | Total PSD with<br>Duty Factor<br>(dBm/500kHz) | Limit<br>(dBm/500kHz) | Pass<br>/ Fail |
|-------|-----------------------|---------------------|--------------|------------------------|-----------------------------------------------|-----------------------|----------------|
|       |                       | (dBm/300kHz)        | (dBm/500kHz) |                        |                                               |                       |                |
| 138   | 5690<br>(For U-NII-3) | -12.11              | -9.89        | 0.36                   | -9.53                                         | 30.00                 | Pass           |


Note: Refer to section 3.3 for duty cycle spectrum plot.

## Spectrum Plot of Worst Value


### 802.11a




### 802.11ac (VHT20)



### 802.11ac (VHT40)



### 802.11ac (VHT80)




## 4.6 Frequency Stability

### 4.6.1 Limits of Frequency Stability Measurement

The frequency of the carrier signal shall be maintained within band of operation

### 4.6.2 Test Setup



### 4.6.3 Test Instruments

| Description & Manufacturer                          | Model No. | Serial No. | Cal. Date     | Cal. Due      |
|-----------------------------------------------------|-----------|------------|---------------|---------------|
| Spectrum Analyzer<br>ROHDE & SCHWARZ                | FSP40     | 100040     | Sep. 16, 2020 | Sep. 15, 2021 |
| WIT Standard<br>Temperature And Humidity<br>Chamber | TH-4S-C   | W981030    | Jun. 01, 2020 | May 31, 2021  |
| Digital Multimeter<br>Fluke                         | 87-III    | 70360742   | Jun. 23, 2020 | Jun. 22, 2021 |
| DC Power Supply<br>TOPWARD                          | 6306A     | 727263     | NA            | NA            |

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

### 4.6.4 Test Procedure

- The EUT was placed inside the environmental test chamber and powered by nominal DC voltage.
- Turn the EUT on and couple its output to a spectrum analyzer.
- Turn the EUT off and set the chamber to the highest temperature specified.
- Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize, turn the EUT on and measure the operating frequency after 2, 5, and 10 minutes.
- Repeat step d with every 10 degrees reduction until the lowest temperature achieved.
- The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 minutes. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.

#### 4.6.5 Deviation from Test Standard

No deviation.

#### 4.6.6 EUT Operating Condition

Set the EUT transmit at un-modulation mode to test frequency stability.

#### 4.6.7 Test Results

##### 5G traffic radio (Radio 2)

| Frequency Stability Versus Temp. |                          |                                |        |                                |        |                                |        |                                |        |
|----------------------------------|--------------------------|--------------------------------|--------|--------------------------------|--------|--------------------------------|--------|--------------------------------|--------|
| Operating Frequency: 5260MHz     |                          |                                |        |                                |        |                                |        |                                |        |
| Temp.<br>(°C)                    | Power<br>Supply<br>(Vdc) | 0 Minute                       |        | 2 Minute                       |        | 5 Minute                       |        | 10 Minute                      |        |
|                                  |                          | Measured<br>Frequency<br>(MHz) | Result | Measured<br>Frequency<br>(MHz) | Result | Measured<br>Frequency<br>(MHz) | Result | Measured<br>Frequency<br>(MHz) | Result |
| 55                               | 54.0                     | 5259.9785                      | Pass   | 5259.9772                      | Pass   | 5259.9813                      | Pass   | 5259.9772                      | Pass   |
| 50                               | 54.0                     | 5260.0075                      | Pass   | 5260.0051                      | Pass   | 5260.0056                      | Pass   | 5260.0079                      | Pass   |
| 40                               | 54.0                     | 5259.9917                      | Pass   | 5259.9924                      | Pass   | 5259.9954                      | Pass   | 5259.9932                      | Pass   |
| 30                               | 54.0                     | 5259.9797                      | Pass   | 5259.976                       | Pass   | 5259.9787                      | Pass   | 5259.9775                      | Pass   |
| 20                               | 54.0                     | 5260.0239                      | Pass   | 5260.0196                      | Pass   | 5260.0199                      | Pass   | 5260.0238                      | Pass   |
| 10                               | 54.0                     | 5260.0148                      | Pass   | 5260.0119                      | Pass   | 5260.0161                      | Pass   | 5260.0117                      | Pass   |
| 0                                | 54.0                     | 5259.9812                      | Pass   | 5259.9802                      | Pass   | 5259.9799                      | Pass   | 5259.9809                      | Pass   |
| -10                              | 54.0                     | 5260.0024                      | Pass   | 5260.0042                      | Pass   | 5260.0042                      | Pass   | 5260.0057                      | Pass   |
| -20                              | 54.0                     | 5260.0182                      | Pass   | 5260.0197                      | Pass   | 5260.018                       | Pass   | 5260.0179                      | Pass   |

| Frequency Stability Versus Voltage |                          |                                |        |                                |        |                                |        |                                |        |
|------------------------------------|--------------------------|--------------------------------|--------|--------------------------------|--------|--------------------------------|--------|--------------------------------|--------|
| Operating Frequency: 5260MHz       |                          |                                |        |                                |        |                                |        |                                |        |
| Temp.<br>(°C)                      | Power<br>Supply<br>(Vdc) | 0 Minute                       |        | 2 Minute                       |        | 5 Minute                       |        | 10 Minute                      |        |
|                                    |                          | Measured<br>Frequency<br>(MHz) | Result | Measured<br>Frequency<br>(MHz) | Result | Measured<br>Frequency<br>(MHz) | Result | Measured<br>Frequency<br>(MHz) | Result |
| 20                                 | 62.1                     | 5260.0231                      | Pass   | 5260.0199                      | Pass   | 5260.0201                      | Pass   | 5260.0245                      | Pass   |
|                                    | 54.0                     | 5260.0239                      | Pass   | 5260.0196                      | Pass   | 5260.0199                      | Pass   | 5260.0238                      | Pass   |
|                                    | 45.9                     | 5260.0245                      | Pass   | 5260.0188                      | Pass   | 5260.02                        | Pass   | 5260.0239                      | Pass   |

### Scanning radio (Radio 3)

| Frequency Stability Versus Temp. |                          |                                |        |                                |        |                                |        |                                |        |
|----------------------------------|--------------------------|--------------------------------|--------|--------------------------------|--------|--------------------------------|--------|--------------------------------|--------|
| Operating Frequency: 5260MHz     |                          |                                |        |                                |        |                                |        |                                |        |
| Temp.<br>(°C)                    | Power<br>Supply<br>(Vdc) | 0 Minute                       |        | 2 Minute                       |        | 5 Minute                       |        | 10 Minute                      |        |
|                                  |                          | Measured<br>Frequency<br>(MHz) | Result | Measured<br>Frequency<br>(MHz) | Result | Measured<br>Frequency<br>(MHz) | Result | Measured<br>Frequency<br>(MHz) | Result |
| 55                               | 54.0                     | 5259.9959                      | Pass   | 5259.9946                      | Pass   | 5259.9951                      | Pass   | 5259.9969                      | Pass   |
| 50                               | 54.0                     | 5260.0111                      | Pass   | 5260.006                       | Pass   | 5260.0097                      | Pass   | 5260.0068                      | Pass   |
| 40                               | 54.0                     | 5259.9914                      | Pass   | 5259.9902                      | Pass   | 5259.9925                      | Pass   | 5259.99                        | Pass   |
| 30                               | 54.0                     | 5260.0121                      | Pass   | 5260.015                       | Pass   | 5260.0166                      | Pass   | 5260.0148                      | Pass   |
| 20                               | 54.0                     | 5260.0038                      | Pass   | 5260.0016                      | Pass   | 5260.0025                      | Pass   | 5259.9998                      | Pass   |
| 10                               | 54.0                     | 5260.0033                      | Pass   | 5260.0029                      | Pass   | 5260.0051                      | Pass   | 5260.0058                      | Pass   |
| 0                                | 54.0                     | 5260.006                       | Pass   | 5260.0066                      | Pass   | 5260.0058                      | Pass   | 5260.0061                      | Pass   |
| -10                              | 54.0                     | 5259.9786                      | Pass   | 5259.9784                      | Pass   | 5259.9772                      | Pass   | 5259.9785                      | Pass   |
| -20                              | 54.0                     | 5260.0242                      | Pass   | 5260.0238                      | Pass   | 5260.0243                      | Pass   | 5260.0233                      | Pass   |


| Frequency Stability Versus Voltage |                          |                                |        |                                |        |                                |        |                                |        |
|------------------------------------|--------------------------|--------------------------------|--------|--------------------------------|--------|--------------------------------|--------|--------------------------------|--------|
| Operating Frequency: 5260MHz       |                          |                                |        |                                |        |                                |        |                                |        |
| Temp.<br>(°C)                      | Power<br>Supply<br>(Vdc) | 0 Minute                       |        | 2 Minute                       |        | 5 Minute                       |        | 10 Minute                      |        |
|                                    |                          | Measured<br>Frequency<br>(MHz) | Result | Measured<br>Frequency<br>(MHz) | Result | Measured<br>Frequency<br>(MHz) | Result | Measured<br>Frequency<br>(MHz) | Result |
| 20                                 | 62.1                     | 5260.0041                      | Pass   | 5260.0008                      | Pass   | 5260.0019                      | Pass   | 5259.9995                      | Pass   |
|                                    | 54.0                     | 5260.0038                      | Pass   | 5260.0016                      | Pass   | 5260.0025                      | Pass   | 5259.9998                      | Pass   |
|                                    | 45.9                     | 5260.0028                      | Pass   | 5260.0025                      | Pass   | 5260.0022                      | Pass   | 5259.9988                      | Pass   |

## 4.7 6dB Bandwidth Measurement

### 4.7.1 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is 0.5MHz.

### 4.7.2 Test Setup



### 4.7.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.7.4 Test Procedure

- Set resolution bandwidth (RBW) = 100kHz
- Set the video bandwidth (VBW)  $\geq 3 \times$  RBW, Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

### 4.7.5 Deviation from Test Standard

No deviation.

### 4.7.6 EUT Operating Condition

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

#### 4.7.7 Test Results

##### 5G traffic radio (Radio 2)

##### 802.11a

| Channel | Frequency (MHz)       | 6dB Bandwidth (MHz) |         | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------------|---------------------|---------|---------------------|-------------|
|         |                       | Chain 0             | Chain 1 |                     |             |
| 144     | 5720<br>(For U-NII-3) | 2.90                | 2.90    | 0.5                 | Pass        |

For CH144 (UNII-3 Band): The 6dB bandwidth above 5725MHz = Marker 1 + Delta 2 - 5725MHz

##### 802.11ax (HE20)

| Channel | Frequency (MHz)       | 6dB Bandwidth (MHz) |         | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------------|---------------------|---------|---------------------|-------------|
|         |                       | Chain 0             | Chain 1 |                     |             |
| 144     | 5720<br>(For U-NII-3) | 3.81                | 4.11    | 0.5                 | Pass        |

For CH144 (UNII-3 Band): The 6dB bandwidth above 5725MHz = Marker 1 + Delta 2 - 5725MHz

##### 802.11ax (HE40)

| Channel | Frequency (MHz)       | 6dB Bandwidth (MHz) |         | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------------|---------------------|---------|---------------------|-------------|
|         |                       | Chain 0             | Chain 1 |                     |             |
| 142     | 5710<br>(For U-NII-3) | 4.01                | 3.62    | 0.5                 | Pass        |

For CH142 (UNII-3 Band): The 6dB bandwidth above 5725MHz = Marker 1 + Delta 2 - 5725MHz


##### 802.11ax (HE80)

| Channel | Frequency (MHz)       | 6dB Bandwidth (MHz) |         | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------------|---------------------|---------|---------------------|-------------|
|         |                       | Chain 0             | Chain 1 |                     |             |
| 138     | 5690<br>(For U-NII-3) | 3.52                | 2.73    | 0.5                 | Pass        |


For CH138 (UNII-3 Band): The 6dB bandwidth above 5725MHz = Marker 1 + Delta 2 - 5725MHz

## Spectrum Plot of Worst Value


### 802.11a




### 802.11ax (HE20)



### 802.11ax (HE40)



### 802.11ax (HE80)



### Scanning radio (Radio 3)

#### 802.11a

| Chan. | Freq. (MHz)           | 6dB Bandwidth (MHz) | Minimum Limit (MHz) | Pass / Fail |
|-------|-----------------------|---------------------|---------------------|-------------|
| 144   | 5720<br>(For U-NII-3) | 3.13                | 0.50                | Pass        |

For CH144 (UNII-3 Band): The 6dB bandwidth above 5725MHz = Marker 1 + Delta 2 - 5725MHz

#### 802.11ac (VHT20)

| Chan. | Freq. (MHz)           | 6dB Bandwidth (MHz) | Minimum Limit (MHz) | Pass / Fail |
|-------|-----------------------|---------------------|---------------------|-------------|
| 144   | 5720<br>(For U-NII-3) | 3.75                | 0.50                | Pass        |

For CH144 (UNII-3 Band): The 6dB bandwidth above 5725MHz = Marker 1 + Delta 2 - 5725MHz

#### 802.11ac (VHT40)

| Chan. | Freq. (MHz)           | 6dB Bandwidth (MHz) | Minimum Limit (MHz) | Pass / Fail |
|-------|-----------------------|---------------------|---------------------|-------------|
| 142   | 5710<br>(For U-NII-3) | 3.11                | 0.50                | Pass        |

For CH142 (UNII-3 Band): The 6dB bandwidth above 5725MHz = Marker 1 + Delta 2 - 5725MHz


#### 802.11ac (VHT80)

| Chan. | Freq. (MHz)           | 6dB Bandwidth (MHz) | Minimum Limit (MHz) | Pass / Fail |
|-------|-----------------------|---------------------|---------------------|-------------|
| 138   | 5690<br>(For U-NII-3) | 1.60                | 0.50                | Pass        |


For CH138 (UNII-3 Band): The 6dB bandwidth above 5725MHz = Marker 1 + Delta 2 - 5725MHz

## Spectrum Plot of Worst Value


802.11a




802.11ac (VHT20)



802.11ac (VHT40)



802.11ac (VHT80)




## **5 Pictures of Test Arrangements**

Please refer to the attached file (Test Setup Photo).


## Annex A - Band Edge Measurement

### 5G traffic radio (Radio 2)




### 802.11a Channel 100


Horizontal (Peak)




Horizontal (Average)



Vertical (Peak)




Vertical (Average)




### 802.11a Channel 140

Horizontal (Peak)




Vertical (Peak)




### 802.11a Channel 144

Horizontal (Peak)




Vertical (Peak)




### 802.11ax (HE20) Channel 52


Horizontal (Peak)




Horizontal (Average)



Vertical (Peak)




Vertical (Average)




### 802.11ax (HE20) Channel 64


Horizontal (Peak)




Horizontal (Average)



Vertical (Peak)




Vertical (Average)




### 802.11ax (HE20) Channel 100


Horizontal (Peak)




Horizontal (Average)



Vertical (Peak)




Vertical (Average)




### 802.11ax (HE20) Channel 140

Horizontal (Peak)




Vertical (Peak)




### 802.11ax (HE20) Channel 144

Horizontal (Peak)




Vertical (Peak)




### 802.11ax (HE40) Channel 54


Horizontal (Peak)




Horizontal (Average)



Vertical (Peak)




Vertical (Average)




### 802.11ax (HE40) Channel 62


Horizontal (Peak)




Horizontal (Average)



Vertical (Peak)




Vertical (Average)




### 802.11ax (HE40) Channel 102


Horizontal (Peak)




Horizontal (Average)



Vertical (Peak)




Vertical (Average)




### 802.11ax (HE40) Channel 134

Horizontal (Peak)




Vertical (Peak)




### 802.11ax (HE40) Channel 142

Horizontal (Peak)




Vertical (Peak)




### 802.11ax (HE80) Channel 58


Horizontal (Peak)




Horizontal (Average)



Vertical (Peak)




Vertical (Average)




### 802.11ax (HE80) Channel 106


Horizontal (Peak)




Horizontal (Average)



Vertical (Peak)




Vertical (Average)




### 802.11ax (HE80) Channel 122


Horizontal (Peak)




Horizontal (Average)



Vertical (Peak)




Vertical (Average)




### 802.11ax (HE80) Channel 138


Horizontal (Peak)



Vertical (Peak)




### Scanning radio (Radio 3)




### 802.11a Channel 100


Horizontal (Peak)




Horizontal (Average)



Vertical (Peak)




Vertical (Average)




### 802.11a Channel 116

Horizontal (Peak)




Vertical (Peak)




### 802.11a Channel 140

Horizontal (Peak)




Vertical (Peak)




# 802.11a Channel 144

## Horizontal (Peak)




## Vertical (Peak)




### 802.11ac (VHT20) Channel 52


Horizontal (Peak)




Horizontal (Average)



Vertical (Peak)




Vertical (Average)




### 802.11ac (VHT20) Channel 64


Horizontal (Peak)




Horizontal (Average)



Vertical (Peak)




Vertical (Average)




### 802.11ac (VHT20) Channel 100


Horizontal (Peak)




Horizontal (Average)



Vertical (Peak)




Vertical (Average)




### 802.11ac (VHT20) Channel 116

Horizontal (Peak)




Vertical (Peak)




### 802.11ac (VHT20) Channel 140

Horizontal (Peak)




Vertical (Peak)




# 802.11ac (VHT20) Channel 144

## Horizontal (Peak)




## Vertical (Peak)




### 802.11ac (VHT40) Channel 54


Horizontal (Peak)




Horizontal (Average)



Vertical (Peak)




Vertical (Average)




### 802.11ac (VHT40) Channel 62


Horizontal (Peak)




Horizontal (Average)



Vertical (Peak)




Vertical (Average)




### 802.11ac (VHT40) Channel 102


Horizontal (Peak)




Horizontal (Average)



Vertical (Peak)




Vertical (Average)




### 802.11ac (VHT40) Channel 110

Horizontal (Peak)




Vertical (Peak)




### 802.11ac (VHT40) Channel 134

Horizontal (Peak)




Vertical (Peak)




# 802.11ac (VHT40) Channel 142

## Horizontal (Peak)




## Vertical (Peak)




### 802.11ac (VHT80) Channel 58


Horizontal (Peak)




Horizontal (Average)



Vertical (Peak)




Vertical (Average)




### 802.11ac (VHT80) Channel 106


Horizontal (Peak)




Horizontal (Average)



Vertical (Peak)




Vertical (Average)




### 802.11ac (VHT80) Channel 122


Horizontal (Peak)




Horizontal (Average)



Vertical (Peak)




Vertical (Average)




### 802.11ac (VHT80) Channel 138

Horizontal (Peak)



Vertical (Peak)



## Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

### **Lin Kou EMC/RF Lab**

Tel: 886-2-26052180

Fax: 886-2-26051924

### **Hsin Chu EMC/RF/Telecom Lab**

Tel: 886-3-6668565

Fax: 886-3-6668323

### **Hwa Ya EMC/RF/Safety**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.

--- END ---