



RF Exposure Evaluation according to KDB 447498 D01 v06

Report identification number: 1-4813/22-01-06_MPE_FCC

Certification numbers and labeling requirements

FCC ID	TVU-DPCP710
--------	-------------

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

Document authorised:

cn=Thomas Vogler, o=CTC advanced
GmbH, ou=VOG-211118,
email=thomas.vogler@ctcadvanced.com,
c=DE
2023.04.03 09:57:09 +02'00'

Thomas Vogler
Lab Manager
Radio Labs

cn=Marco Scigliano, o=CTC advanced
GmbH, ou=SCI-211118,
email=marco.scigliano@ctcadvanced.com,
c=DE
2023.04.03 09:55:37 +02'00'

Marco Scigliano
Testing Manager
Radio Labs

1. MPE at given distance (KDB 447498 D01 General RF Exposure Guidance v06)

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4\pi R^2$$

where: S = Power density
P = Power input to the antenna
G = Antenna gain
R = Distance to the center of radiation of the antenna
PG = Output Power including antenna gain

The table below is excerpted from Table 1B of 47 CFR 1.1310 titled "Limits for Maximum Permissible Exposure (MPE), Limits for General Population/Uncontrolled Exposure"

Frequency Range (MHz)	Power Density (mW/cm ²)	Averaging Time (minutes)
300 -1500	f/1500	30
1500 - 100000	1.0	30

where f = Frequency (MHz)

2. EUT technologies

Declared minimum safety distance: **20cm**

Referenced Documents:

#	Results from:
A	Test Report 1-4813/22-01-04
B	Test Report 1-4813/22-01-05

SRD Technology	Frequency [MHz]		Reference	Output Power [dBm]			Power Density [mW/cm²]		Share of Limit
	f _{Min}	f _{Max}		P _{ERP}	P _{EIRP}	P _{RF Exp}	S _{Result}	S _{Limit}	
Bluetooth Classic	2402	2480	A	N/A	6.3	6.3	0.00	1.00	0.08%
Bluetooth LE	2402	2480	B	N/A	6.4	6.4	0.00	1.00	0.09%

3. Collocation overview:

Technology	Share of Limit [%]
Bluetooth LE	0.09%
Bluetooth Classic	0.08%
Sum	0.17%

4. Conclusion

This prediction demonstrates the following:

The power density levels for FCC at a distance of 20 cm are below the maximum levels allowed by regulations.

Conclusion: RF exposure evaluation is not required.