

Measurement Report for Device

Device Under Test Properties

Model, Manufacturer	Dimensions [mm]	Software Version	DUT Type
Device,	70.0 x 50.0 x 8.0	3.2.0.1840	5G Verification Source

Exposure Conditions

Phantom Section	Position, Test Distance [mm]	Frequency [MHz]	Conversion Factor
5G	FRONT, 10.00	10000.0	1.0

Hardware Setup


Phantom	Medium	Probe, Calibration Date	DAE, Calibration Date
mmWave – 1109	Air –	EUmmWV4 – SN9461_F1–55GHz, 2024–10–16	DAE4 Sn1424, 2024–12–19

Scans Setup

Scan Type	5G Scan
Grid Extents [mm]	120.0 x 120.0
Grid Steps [lambda]	0.25 x 0.25
Sensor Surface [mm]	10.0

Measurement Results

Date	2025-05-14
Avg. Area [cm ²]	4.00
psPDn+ [W/m ²]	53.0
psPDtot+ [W/m ²]	53.2
H _{max} [A/m]	0.409
E _{max} [V/m]	150
max _(Stot) [W/m ²]	60.8
Power Drift [dB]	0.03
IPDn	97.8



Measurement Report for Device
Device Under Test Properties

Model, Manufacturer	Dimensions [mm]	Software Version	DUT Type
Device,	70.0 x 50.0 x 8.0	3.2.0.1840	5G Verification Source

Exposure Conditions

Phantom Section	Position, Test Distance [mm]	Frequency [MHz]	Conversion Factor
5G	Front, 10.00	10000.0	1.0

Hardware Setup

Phantom	Medium	Probe, Calibration Date	DAE, Calibration Date
mmWave - 1109	Air -	EUmmWV4 - SN9461_F1-55GHz, 2024-10-16	DAE3 Sn577, 2025-03-14

Scans Setup

Scan Type	5G Scan
Grid Extents [mm]	120.0 x 120.0
Grid Steps [lambda]	0.25 x 0.25
Sensor Surface [mm]	10.0

Measurement Results

Date	2025-05-17
Avg. Area [cm ²]	4.00
psPDn+ [W/m ²]	61.4
psPDtot+ [W/m ²]	61.6
H _{max} [A/m]	0.436
E _{max} [V/m]	164
max _(stot) [W/m ²]	69.3
Power Drift [dB]	0.10
IPDn	112

