

ANTENNA INFORMATION

OEM	Lenovo	
ODM	Compal Electronics Inc.	
Platform Model Name	Legion 5 15IAX11	
Intel Platform (ex: Yes, No or NA)	Yes	
Platform Type (ex: regular NB, convertible PC, AIO...etc)	Regular NB	
SAR Minimum Separation (mm)	FCC (1g)	10.89 mm
	ISED (1g)	5 mm
	ISED (10g)	3.8mm

Antenna Manufacturer	Company Name Address	Hua-Cheng Technology Co., Ltd. 17F, No.100, Sec.1, Xintai 5th Rd, Xizhi Dist., New Taipei City 22102, Taiwan
Test Location	Company Name Address	Hua-Cheng Technology Co., Ltd. 17F, No.100, Sec.1, Xintai 5th Rd, Xizhi Dist., New Taipei City 22102, Taiwan
Test Personnel	Name (Full Name)	Max Yang
	E-mail	max_yang@hightek.com.tw
	Tel / Mobile	886-2-2696-1996 EXT:5230
Testing Date	2026/01/26	

Antenna Part Number	Main	0ACMYL25466N (DC330035S00)
	Aux	0ACMYL25466N (DC330035S00)
Antenna Type (ex: PIFA, Dipole...etc)	PIFA	

Antenna Peak Gain w/ Cable Loss (dBi)*										
	2.4GHz 2400-2483.5 MHz	5.2GHz 5150-5250MHz	5.3GHz 5250-5350MHz	5.6GHz 5470-5725MHz	5.8GHz 5725-5850MHz	5.9GHz 5850-5895MHz	6.2GHz 5925-6425MHz	6.5GHz 6425-6525MHz	6.7GHz 6525-6875MHz	7.0 GHz 6875-7125MHz
Main	2.65	2.81	2.81	2.88	2.88	2.82	3.73	3.64	3.62	3.62
Aux	2.89	2.80	2.52	2.85	2.27	2.07	3.75	3.62	3.71	3.84

Cable Assembly Part Number and Information					
	Cable PN	Cable Length(mm)	Cable Diameter(mm)	Impedance(ohm)	Connector Type
Main	XGN113L/50	316	1.13	50	I-PEX MHF 4
Aux	XGN113L/50	94.5	1.13	50	I-PEX MHF 4

* 3D Antenna Peak Gain required being test in system basis.

Cable Loss (dBi)										
	2.4GHz 2400-2483.5 MHz	5.2GHz 5150-5250MHz	5.3GHz 5250-5350MHz	5.6GHz 5470-5725MHz	5.8GHz 5725-5850MHz	5.9GHz 5850-5895MHz	6.2GHz 5925-6425MHz	6.5GHz 6425-6525MHz	6.7GHz 6525-6875MHz	7.0 GHz 6875-7125MHz
Main	0.96	1.36	1.36	1.46	1.48	1.49	1.54	1.56	1.60	1.69
Aux	0.29	0.41	0.41	0.44	0.44	0.45	0.46	0.47	0.48	0.51

Table of Contents

Cover Page..... 1

1. Test & System Description

1.1 Measurement Method and System..... 3

1.2 Test Setup..... 4

1.3 Equipment List..... 5

2. Radiation Characteristics of Antenna Loaded in Host Platform..... 6

Annex A. Photographs

A.1 Setup Photo..... 16

A.2 Test Sample..... 17

Annex B. Antenna Location


B.1 Antenna Host Platform Location Information..... 19

B.2 Antenna Dimensional Information for SAR Evaluation..... 21

1. Test & System Description

1.1 Measurement Method and System

The radiation pattern of antenna is measured in both horizontal polarization and vertical polarization. The radiation pattern measurements are performed in the three-dimensional anechoic chamber. The chamber provides less than -30dB reflectivity from 800MHz through 8GHz . The chamber is calibrated using both standard dipole antenna and horn antenna. The Gain here is expressed as dBi that standardizes the isotropic antenna. The Gain measurements and antenna radiation pattern are also performed in the same chamber described previously. Figure shows the schematic diagram for measuring radiation pattern and Gain.



1.2 Test Setup

1. Frequency Range

2400~2500MHz, for WLAN application.


5150~7125MHz, for WLAN application

2. Antenna Configuration

The antenna basically has two parts; the stamping and the cable assembly with the connector on one side. The detailed drawing is attached.

3. VSWR

The VSWR is measured with network analyzer that support up to 8GHz. All the measurements are performed with the customer provided fixture. Figure 1 shows the typical schematic diagram for measuring VSWR.



1.3 Equipment List

The equipment for the antenna measurement we used is as follows:

- A. Network Analyzer, support up to 8GHz, to measure the VSWR and input impedance of antenna.
- B. Three-dimensional anechoic chamber to measure antenna gain and radiation pattern(Standard horn antenna was used to calibrate the chamber)
- C. Digital caliper to measure the dimensions.
- D. Climatic chamber for mechanical tests.

Radiated Setup

Item	Device	Type/Model	Manufacturer	Cal. Date	Cal. Due Date
1	Anechoic Chamber	AMS-8500	ETS-Lindgren	2025/06/20	2026/06/20
2	Turn Table	ETS	ETS-Lindgren	N/A	N/A
3	Measurement SW	EMQuest1.08	ETS-Lindgren	N/A	N/A
4	Vector Network Analyzer	Agilent E5071B	Agilent	2025/06/20	2026/06/20
5	Receive Antenna Absorber Nested Dual- Polarized Dual-Vivaldi Array Antenna 700MHz to 6GHz	EMCO 3164-08	ETS-Lindgren	N/A	N/A
6	Multi Axis Positioning System (MAPS™)	EMCO 2115CR	ETS-Lindgren	N/A	N/A
7	MAPS™ Controller	MECO 2090	ETS-Lindgren	N/A	N/A
8	Horn antenna	3164-08	ETS-Lindgren	2025/06/20	2026/06/20
9	Cable 0.5m - 700MHz~10GHz	RG316	Senyu	2025/06/20	2026/06/20


N/A : Not Applicable

2. Radiation Characteristics of Antenna Loaded in Host Platform

Main Antenna


Max Antenna 3D Radiation Pattern 2400 – 2483.5 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
2400-2483.5	2.65




Max Antenna 3D Radiation Pattern 5150-5250 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
5150-5250	2.81




Max Antenna 3D Radiation Pattern 5250-5350 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
5250-5350	2.81




Max Antenna 3D Radiation Pattern 5470-5725 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
5470-5725	2.88




Max Antenna 3D Radiation Pattern 5725-5850 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
5725-5850	2.88




Max Antenna 3D Radiation Pattern 5850-5895 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
5850-5895	2.82




Max Antenna 3D Radiation Pattern 5925-6425 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
5925-6425	3.73




Max Antenna 3D Radiation Pattern 6425-6525 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
6425-6525	3.64




Max Antenna 3D Radiation Pattern 6525-6875 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
6525-6875	3.62



Max Antenna 3D Radiation Pattern 6875-7125 MHz


Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
6875-7125	3.62



Auxiliary Antenna


Max Antenna 3D Radiation Pattern 2400 – 2483.5 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
2400-2483.5	2.89




Max Antenna 3D Radiation Pattern 5150-5250 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
5150-5250	2.80




Max Antenna 3D Radiation Pattern 5250-5350 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
5250-5350	2.52




Max Antenna 3D Radiation Pattern 5470-5725 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
5470-5725	2.85




Max Antenna 3D Radiation Pattern 5725-5850 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
5725-5850	2.27




Max Antenna 3D Radiation Pattern 5850-5895 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
5850-5895	2.07




Max Antenna 3D Radiation Pattern 5925-6425 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
5925-6425	3.75




Max Antenna 3D Radiation Pattern 6425-6525 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
6425-6525	3.62



Max Antenna 3D Radiation Pattern 6525-6875 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
6525-6875	3.71



Max Antenna 3D Radiation Pattern 6875-7125 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
6875-7125	3.84

