



# RF TEST REPORT



Report No.: Q190401S002-FCC-R-V1

Supersede Report No.: N/A

|                                                                                                                                      |                                                                                     |                                                                                       |
|--------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| Applicant                                                                                                                            | REMOTE SOLUTION.CO.,LTD                                                             |                                                                                       |
| Product Name                                                                                                                         | REMOTE CONTROL UNIT                                                                 |                                                                                       |
| Model No.                                                                                                                            | P3700                                                                               |                                                                                       |
| Serial No.                                                                                                                           | N/A                                                                                 |                                                                                       |
| Test Standard                                                                                                                        | FCC Part 15.247, ANSI C63.10: 2013                                                  |                                                                                       |
| Test Date                                                                                                                            | April 12&May 08, 2019                                                               |                                                                                       |
| Issue Date                                                                                                                           | May 08, 2019                                                                        |                                                                                       |
| Test Result                                                                                                                          | <input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail              |                                                                                       |
| Equipment complied with the specification <input checked="" type="checkbox"/>                                                        |                                                                                     |                                                                                       |
| Equipment did not comply with the specification <input type="checkbox"/>                                                             |                                                                                     |                                                                                       |
|                                                   |  |  |
| Aaron Liang<br>Test Engineer                                                                                                         | David Huang<br>Checked By                                                           |                                                                                       |
| This test report may be reproduced in full only<br>Test result presented in this test report is applicable to the tested sample only |                                                                                     |                                                                                       |

Issued by:

**SIEMIC (SHENZHEN-CHINA) LABORATORIES**

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao'an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: [China@siemic.com.cn](mailto:China@siemic.com.cn)

## Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

### Accreditations for Conformity Assessment

| Country/Region | Scope                              |
|----------------|------------------------------------|
| USA            | EMC, RF/Wireless, SAR, Telecom     |
| Canada         | EMC, RF/Wireless, SAR, Telecom     |
| Taiwan         | EMC, RF, Telecom, SAR, Safety      |
| Hong Kong      | RF/Wireless, SAR, Telecom          |
| Australia      | EMC, RF, Telecom, SAR, Safety      |
| Korea          | EMI, EMS, RF, SAR, Telecom, Safety |
| Japan          | EMI, RF/Wireless, SAR, Telecom     |
| Singapore      | EMC, RF, SAR, Telecom              |
| Europe         | EMC, RF, SAR, Telecom, Safety      |

|                 |                      |
|-----------------|----------------------|
| Test Report No. | Q190401S002-FCC-R-V1 |
| Page            | 3 of 34              |

This page has been left blank intentionally.

## CONTENTS

|                                                                          |    |
|--------------------------------------------------------------------------|----|
| 1. REPORT REVISION HISTORY.....                                          | 5  |
| 2. CUSTOMER INFORMATION .....                                            | 5  |
| 3. TEST SITE INFORMATION .....                                           | 5  |
| 4. EQUIPMENT UNDER TEST (EUT) INFORMATION .....                          | 6  |
| 5. TEST SUMMARY .....                                                    | 7  |
| 6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS .....                   | 8  |
| 6.1 ANTENNA REQUIREMENT .....                                            | 8  |
| 6.2 DTS (6 DB) CHANNEL BANDWIDTH .....                                   | 9  |
| 6.3 MAXIMUM OUTPUT POWER .....                                           | 12 |
| 6.4 POWER SPECTRAL DENSITY .....                                         | 14 |
| 6.5 BAND-EDGE & UNWANTED EMISSIONS INTO RESTRICTED FREQUENCY BANDS ..... | 16 |
| 6.6 AC POWER LINE CONDUCTED EMISSIONS .....                              | 19 |
| 6.7 RADIATED EMISSIONS & RESTRICTED BAND .....                           | 21 |
| ANNEX A. TEST INSTRUMENT .....                                           | 29 |
| ANNEX B. TEST SETUP AND SUPPORTING EQUIPMENT .....                       | 30 |
| ANNEX C. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST .....       | 33 |
| ANNEX D. DECLARATION OF SIMILARITY .....                                 | 34 |

## 1. Report Revision History

| Report No.           | Report Version | Description                                                                                                                                      | Issue Date      |
|----------------------|----------------|--------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| Q190401S002-FCC-R    | NONE           | Original                                                                                                                                         | May 08, 2019    |
| Q190401S002-FCC-R-V1 | V1             | Corrected and updated the Radiated Emissions & Restricted Band and Band-Edge & Unwanted Emissions into Restricted Frequency Bands in the report. | August 28, 2019 |

## 2. Customer information

|                  |                                                                         |
|------------------|-------------------------------------------------------------------------|
| Applicant Name   | REMOTE SOLUTION.CO.,LTD                                                 |
| Applicant Add    | 92, Chogokri , Nammyun , Kimchon City, Kyungbuk , South Korea , 740-871 |
| Manufacturer     | REMOTE SOLUTION.CO.,LTD                                                 |
| Manufacturer Add | 92, Chogokri , Nammyun , Kimchon City, Kyungbuk , South Korea , 740-871 |

## 3. Test site information

Test Lab A:

|                      |                                                                                                                                             |
|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------|
| Lab performing tests | SIEMIC (Shenzhen-China) LABORATORIES                                                                                                        |
| Lab Address          | Zone A, Floor 1, Building 2 Wan Ye Long Technology Park<br>South Side of Zhoushi Road, Bao'an District, Shenzhen, Guangdong China<br>518108 |
| FCC Test Site No.    | 535293                                                                                                                                      |
| IC Test Site No.     | 4842E-1                                                                                                                                     |
| Test Software        | Radiated Emission Program-To Shenzhen v2.0                                                                                                  |

Test Lab B:

|                      |                                                                                               |
|----------------------|-----------------------------------------------------------------------------------------------|
| Lab performing tests | Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch Laboratories                                |
| Lab Address          | No. 34, Chenwulu Section, Guantai Rd., Houjie Town, Dongguan City,<br>Guangdong 523942, China |
| FCC Test Site No.    | 749762                                                                                        |
| IC Test Site No.     | 5936A-1                                                                                       |
| Test Software        | ADT_Radiated_V7.6.15.9.2                                                                      |

Note: We just perform Radiated Spurious Emission above 18GHz in the test Lab. B.

#### 4. Equipment under Test (EUT) Information

Description of EUT: REMOTE CONTROL UNIT

Main Model: P3700

Serial Model: N/A

Date EUT received: April 04, 2019

Test Date(s): April 12&May 08, 2019

Equipment Category : DTS

Antenna Gain: 2.03dBi

Antenna Type: PCB Antenna

Type of Modulation: BLE: GFSK

RF Operating Frequency (ies): BLE: 2402-2480 MHz

Max. Output Power: 8.81dBm

Number of Channels: BLE: 40CH

Port: Please refer to user's manual

Trade Name : N/A

Input Power: **Battery:**  
Spec: DC 3V

FCC ID: TX4-P3700

## 5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

| FCC Rules                       | Description of Test                                                     | Result     |
|---------------------------------|-------------------------------------------------------------------------|------------|
| §15.203                         | Antenna Requirement                                                     | Compliance |
| §15.247 (a)(2)                  | DTS (6 dB) CHANNEL BANDWIDTH                                            | Compliance |
| §15.247(b)(3)                   | Conducted Maximum Output Power                                          | Compliance |
| §15.247(e)                      | Power Spectral Density                                                  | Compliance |
| §15.247(d)                      | Band-Edge & Unwanted Emissions into Restricted Frequency Bands          | Compliance |
| §15.207 (a),                    | AC Power Line Conducted Emissions                                       | N/A        |
| §15.205, §15.209,<br>§15.247(d) | Radiated Emissions & Unwanted Emissions into Restricted Frequency Bands | Compliance |

### Measurement Uncertainty

| Emissions                                                                                                                                  |                                                                                                                                                 |               |
|--------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| Test Item                                                                                                                                  | Description                                                                                                                                     | Uncertainty   |
| Band-Edge & Unwanted Emissions into Restricted Frequency Bands and Radiated Emissions & Unwanted Emissions into Restricted Frequency Bands | Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m) | +5.6dB/-4.5dB |
| -                                                                                                                                          | -                                                                                                                                               | -             |

## 6. Measurements, Examination And Derived Results

### 6.1 Antenna Requirement

#### **Applicable Standard**

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### **Antenna Connector Construction**

The EUT has 1 antenna:


A permanently attached PCB antenna for BLE, the gain is 2.03dBi for BLE.

**The antenna meets up with the ANTENNA REQUIREMENT.**

**Result:** Compliance.

## 6.2 DTS (6 dB) Channel Bandwidth

|                      |                |
|----------------------|----------------|
| Temperature          | 25°C           |
| Relative Humidity    | 53%            |
| Atmospheric Pressure | 1021mbar       |
| Test date :          | April 12, 2019 |
| Tested By :          | Aaron Liang    |

| Spec           | Item                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Requirement                                     | Applicable                          |
|----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------|-------------------------------------|
| § 15.247(a)(2) | a)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 6dB BW ≥ 500kHz;                                | <input checked="" type="checkbox"/> |
| RSS Gen(4.6.1) | b)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 99% BW: For FCC reference only; required by IC. | <input checked="" type="checkbox"/> |
| Test Setup     |  <p style="text-align: center;">Spectrum Analyzer                      EUT</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                 |                                     |
| Test Procedure | <p>558074 D01 DTS MEAS Guidance v05r02, 8.1 DTS bandwidth<br/>6dB Emission bandwidth measurement procedure</p> <ul style="list-style-type: none"> <li>- Set RBW = 100 kHz.</li> <li>- Set the video bandwidth (VBW) ≥ 3 RBW.</li> <li>- Detector = Peak.</li> <li>- Trace mode = max hold.</li> <li>- Sweep = auto couple.</li> <li>- Allow the trace to stabilize.</li> </ul> <p>Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.</p> |                                                 |                                     |
| Remark         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                 |                                     |
| Result         | <input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                                                 |                                     |

Test Data    ☒ Yes                      ☐ N/A

Test Plot    ☒ Yes (See below)                      ☐ N/A

## 6dB Bandwidth measurement result


### Test Data

| CH   | Frequency (MHz) | 6dB Bandwidth (kHz) | 99% Occupied Bandwidth (MHz) |
|------|-----------------|---------------------|------------------------------|
| Low  | 2402            | 668                 | 1.0563                       |
| Mid  | 2440            | 676                 | 1.0316                       |
| High | 2480            | 656                 | 1.0547                       |


### Test Plots




6dB Bandwidth - Low CH 2402




6dB Bandwidth - Mid CH 2440




6dB Bandwidth - High CH 2480



99% Bandwidth - Low CH 2402



99% Bandwidth - Mid CH 2440




99% Bandwidth - High CH 2480

### 6.3 Maximum Output Power

|                      |              |
|----------------------|--------------|
| Temperature          | 25°C         |
| Relative Humidity    | 50%          |
| Atmospheric Pressure | 1008mbar     |
| Test date :          | May 08, 2019 |
| Tested By :          | Aaron Liang  |

#### Requirement(s):

| Spec                               | Item                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Requirement                                                          | Applicable                          |
|------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------|-------------------------------------|
| §15.247(b)<br>(3),RSS210<br>(A8.4) | a)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | FHSS in 2400-2483.5MHz with $\geq 75$ channels: $\leq 1$ Watt        | <input type="checkbox"/>            |
|                                    | b)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | FHSS in 5725-5850MHz: $\leq 1$ Watt                                  | <input type="checkbox"/>            |
|                                    | c)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | For all other FHSS in the 2400-2483.5MHz band: $\leq 0.125$ Watt.    | <input type="checkbox"/>            |
|                                    | d)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | FHSS in 902-928MHz with $\geq 50$ channels: $\leq 1$ Watt            | <input type="checkbox"/>            |
|                                    | e)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | FHSS in 902-928MHz with $\geq 25$ & $<50$ channels: $\leq 0.25$ Watt | <input type="checkbox"/>            |
|                                    | f)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | DTS in 902-928MHz, 2400-2483.5MHz: $\leq 1$ Watt                     | <input checked="" type="checkbox"/> |
| Test Setup                         |  <p style="text-align: center;"><b>Spectrum Analyzer</b>                      <b>EUT</b></p>                                                                                                                                                                                                                                                                                                        |                                                                      |                                     |
| Test Procedure                     | <p>558074 D01 DTS MEAS Guidance v05r02, 9.1.2 Integrated band power method<br/>Maximum output power measurement procedure</p> <p>a) Set the RBW <math>\geq</math> DTS bandwidth.<br/>b) Set VBW <math>\geq 3 \times</math> RBW.<br/>c) Set span <math>\geq 3 \times</math> RBW<br/>d) Sweep time = auto couple.<br/>e) Detector = peak.<br/>f) Trace mode = max hold.<br/>g) Allow trace to fully stabilize.<br/>h) Use peak marker function to determine the peak amplitude level.</p> |                                                                      |                                     |
| Remark                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                                      |                                     |
| Result                             | <input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail                                                                                                                                                                                                                                                                                                                                                                                                                  |                                                                      |                                     |

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A

## Output Power measurement result

### Test Data

| Type         | CH   | Frequency (MHz) | Conducted Power (dBm) | Limit (dBm) | Result |
|--------------|------|-----------------|-----------------------|-------------|--------|
| Output power | Low  | 2402            | 8.45                  | 30          | Pass   |
|              | Mid  | 2440            | 8.81                  | 30          | Pass   |
|              | High | 2480            | 8.71                  | 30          | Pass   |

### Test Plots




PK Output power - Low CH 2402

PK Output power - Mid CH 2440

PK Output power - High CH 2480

## 6.4 Power Spectral Density

|                      |              |
|----------------------|--------------|
| Temperature          | 25°C         |
| Relative Humidity    | 50%          |
| Atmospheric Pressure | 1008mbar     |
| Test date :          | May 08, 2019 |
| Tested By :          | Aaron Liang  |

| Spec           | Item                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Requirement                                                                                                                                                                              | Applicable                          |
|----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|
| §15.247(e)     | a)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | The power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. | <input checked="" type="checkbox"/> |
| Test Setup     |  <p style="text-align: center;">Spectrum Analyzer                      EUT</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                                                                                          |                                     |
| Test Procedure | <p>558074 D01 DTS MEAS Guidance v05r02, 10.2 power spectral density method power spectral density measurement procedure</p> <ul style="list-style-type: none"> <li>- a) Set analyzer center frequency to DTS channel center frequency.</li> <li>- b) Set the span to 1.5 times the DTS bandwidth.</li> <li>- c) Set the RBW to: <math>3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}</math>.</li> <li>- d) Set the VBW <math>\geq 3 \times \text{RBW}</math>.</li> <li>- e) Detector = peak.</li> <li>- f) Sweep time = auto couple.</li> <li>- g) Trace mode = max hold.</li> <li>- h) Allow trace to fully stabilize.</li> <li>- i) Use the peak marker function to determine the maximum amplitude level within the RBW.</li> <li>- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.</li> </ul> |                                                                                                                                                                                          |                                     |
| Remark         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                                                                                                                          |                                     |
| Result         | <input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                                                                                                                                                                          |                                     |

Test Data    ☒ Yes                      ☐ N/A  
 Test Plot    ☒ Yes (See below)                      ☐ N/A


## Power Spectral Density measurement result

### Test Data


| Type | CH   | Freq (MHz) | Reading (dBm) | Factor (dB) | Result (dBm) | Limit (dBm) | Result |
|------|------|------------|---------------|-------------|--------------|-------------|--------|
| PSD  | Low  | 2402       | -4.065        | -5.23       | -9.295       | 8           | Pass   |
|      | Mid  | 2440       | -3.736        | -5.23       | -8.966       | 8           | Pass   |
|      | High | 2480       | -4.875        | -5.23       | -10.105      | 8           | Pass   |

Note: factor= $10\log(3/10)=-5.23$


### Test Plots



PSD - Low CH 2402



PSD - Mid CH 2440




PSD - High CH 2480

## 6.5 Band-Edge & Unwanted Emissions into Restricted Frequency Bands

|                      |                |
|----------------------|----------------|
| Temperature          | 25°C           |
| Relative Humidity    | 58%            |
| Atmospheric Pressure | 1016mbar       |
| Test date :          | April 16, 2019 |
| Tested By :          | Aaron Liang    |

### Requirement(s):


| Spec           | Item                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Requirement                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Applicable                          |
|----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|
| §15.247(d)     | a)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. | <input checked="" type="checkbox"/> |
| Test Setup     |                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                     |
| Test Procedure | <p>Radiated Method Only</p> <ul style="list-style-type: none"> <li>1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.</li> <li>2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.</li> </ul> |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                     |

|        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|--------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|        | <ul style="list-style-type: none"> <li>- 3. First, set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, check the emission of EUT, if pass then set Spectrum Analyzer as below: <ul style="list-style-type: none"> <li>a. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz.</li> <li>b. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz.</li> <li>c. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz.</li> </ul> </li> <li>- 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.</li> <li>- 5. Repeat above procedures until all measured frequencies were complete.</li> </ul> |
| Remark |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Result | <input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |

Test Data    ☐ Yes                      ☒ N/A  
Test Plot    ☒ Yes (See below)           ☐ N/A

## Test Plots

### Band Edge measurement result




Note: Both Horizontal and vertical polarities were investigated.

## 6.6 AC Power Line Conducted Emissions

|                      |    |
|----------------------|----|
| Temperature          | -- |
| Relative Humidity    | -- |
| Atmospheric Pressure | -- |
| Test date :          | -- |
| Tested By :          | -- |

### Requirement(s):

| Spec                        | Item | Requirement                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Applicable                                                                            |              |         |
|-----------------------------|------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|--------------|---------|
| 47CFR§15.207, RSS210 (A8.1) | a)   | For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu] H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges. |  |              |         |
|                             |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                                       |              |         |
|                             |      | Frequency ranges (MHz)                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                       | Limit (dBµV) |         |
|                             |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                                       | QP           | Average |
|                             |      | 0.15 ~ 0.5                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                                       | 66 – 56      | 56 – 46 |
|                             |      | 0.5 ~ 5                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                       | 56           | 46      |
| 5 ~ 30                      | 60   | 50                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                                                       |              |         |

|            |                                                                                                                                                                                                                                                                         |
|------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Setup |  <p>Note: 1. Support units were connected to second LISN.<br/>2. Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.</p> |
|------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|           |                                                                                                                                                                                                                                                                                                                                                                                                             |
|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Procedure | <ol style="list-style-type: none"> <li>The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table.</li> <li>The power supply for the EUT was fed through a 50W/50mH EUT LISN, connected to filtered mains.</li> <li>The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss</li> </ol> |
|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|--------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|        | <p>coaxial cable.</p> <ol style="list-style-type: none"> <li>All other supporting equipment were powered separately from another main supply.</li> <li>The EUT was switched on and allowed to warm up to its normal operating condition.</li> <li>A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver.</li> <li>High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz.</li> <li>Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power).</li> </ol> |
| Remark | <b>The EUT was powered by battery.</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Result | <input type="checkbox"/> Pass <input type="checkbox"/> Fail <input checked="" type="checkbox"/> N/A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |

Test Data ☐ Yes ☒ N/A

Test Plot ☐ Yes (See below) ☒ N/A


## 6.7 Radiated Emissions & Restricted Band

|                      |                |
|----------------------|----------------|
| Temperature          | 25°C           |
| Relative Humidity    | 58%            |
| Atmospheric Pressure | 1016mbar       |
| Test date :          | April 16, 2019 |
| Tested By :          | Aaron Liang    |

### Requirement(s):

| Spec                                 | Item                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Requirement                                                                                                                                                                                                                                                                                                                                                                           | Applicable                          |                       |                       |             |             |             |              |            |    |         |     |          |     |         |     |           |     |
|--------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|-----------------------|-----------------------|-------------|-------------|-------------|--------------|------------|----|---------|-----|----------|-----|---------|-----|-----------|-----|
| 47CFR§15.247(d),<br>RSS210<br>(A8.5) | a)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges                                         | <input checked="" type="checkbox"/> |                       |                       |             |             |             |              |            |    |         |     |          |     |         |     |           |     |
|                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | <table><tr><th>Frequency range (MHz)</th><th>Field Strength (μV/m)</th></tr><tr><td>0.009~0.490</td><td>2400/F(KHz)</td></tr><tr><td>0.490~1.705</td><td>24000/F(KHz)</td></tr><tr><td>1.705~30.0</td><td>30</td></tr><tr><td>30 – 88</td><td>100</td></tr><tr><td>88 – 216</td><td>150</td></tr><tr><td>216 960</td><td>200</td></tr><tr><td>Above 960</td><td>500</td></tr></table> |                                     | Frequency range (MHz) | Field Strength (μV/m) | 0.009~0.490 | 2400/F(KHz) | 0.490~1.705 | 24000/F(KHz) | 1.705~30.0 | 30 | 30 – 88 | 100 | 88 – 216 | 150 | 216 960 | 200 | Above 960 | 500 |
|                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Frequency range (MHz)                                                                                                                                                                                                                                                                                                                                                                 |                                     | Field Strength (μV/m) |                       |             |             |             |              |            |    |         |     |          |     |         |     |           |     |
|                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 0.009~0.490                                                                                                                                                                                                                                                                                                                                                                           |                                     | 2400/F(KHz)           |                       |             |             |             |              |            |    |         |     |          |     |         |     |           |     |
|                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 0.490~1.705                                                                                                                                                                                                                                                                                                                                                                           |                                     | 24000/F(KHz)          |                       |             |             |             |              |            |    |         |     |          |     |         |     |           |     |
|                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 1.705~30.0                                                                                                                                                                                                                                                                                                                                                                            |                                     | 30                    |                       |             |             |             |              |            |    |         |     |          |     |         |     |           |     |
|                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 30 – 88                                                                                                                                                                                                                                                                                                                                                                               |                                     | 100                   |                       |             |             |             |              |            |    |         |     |          |     |         |     |           |     |
|                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 88 – 216                                                                                                                                                                                                                                                                                                                                                                              |                                     | 150                   |                       |             |             |             |              |            |    |         |     |          |     |         |     |           |     |
|                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 216 960                                                                                                                                                                                                                                                                                                                                                                               |                                     | 200                   |                       |             |             |             |              |            |    |         |     |          |     |         |     |           |     |
|                                      | Above 960                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | 500                                                                                                                                                                                                                                                                                                                                                                                   |                                     |                       |                       |             |             |             |              |            |    |         |     |          |     |         |     |           |     |
| b)                                   | For non-restricted band, In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB or 30dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, determined by the measurement method on output power to be used. Attenuation below the general limits specified in § 15.209(a) is not required | <input checked="" type="checkbox"/>                                                                                                                                                                                                                                                                                                                                                   |                                     |                       |                       |             |             |             |              |            |    |         |     |          |     |         |     |           |     |
|                                      | <input checked="" type="checkbox"/> 20 dB down <input type="checkbox"/> 30 dB down                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                                                                                                                                                                                                                                                                                                                                                                                       |                                     |                       |                       |             |             |             |              |            |    |         |     |          |     |         |     |           |     |
| c)                                   | or restricted band, emission must also comply with the radiated emission limits specified in 15.209                                                                                                                                                                                                                                                                                                                                                                                                                                 | <input checked="" type="checkbox"/>                                                                                                                                                                                                                                                                                                                                                   |                                     |                       |                       |             |             |             |              |            |    |         |     |          |     |         |     |           |     |

## Test Setup



## Procedure

1. The EUT was switched on and allowed to warm up to its normal operating condition.
2. The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner:
  - a. Vertical or horizontal polarization (whichever gave the higher emission level over a full rotation of the EUT) was chosen.
  - b. The EUT was then rotated to the direction that gave the maximum emission.
  - c. Finally, the antenna height was adjusted to the height that gave the maximum emission.
3. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi Peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz.

|        |                                                                                                                                                                                                                                                                                                                 |
|--------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|        | <p>The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz.</p> <p>5. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.</p> |
| Remark |                                                                                                                                                                                                                                                                                                                 |
| Result | <input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail                                                                                                                                                                                                                                          |

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

### Test Result:

|            |                   |
|------------|-------------------|
| Test Mode: | Transmitting Mode |
|------------|-------------------|

Frequency range: 9KHz - 30MHz

| Freq.<br>(MHz) | Detection<br>value | Factor<br>(dB/m) | Reading<br>(dBuV/m) | Result<br>(dBuV/m) | Limit@3m<br>(dBuV/m) | Margin<br>(dB) |
|----------------|--------------------|------------------|---------------------|--------------------|----------------------|----------------|
| --             | --                 | --               | --                  | --                 | --                   | >20            |
| --             | --                 | --               | --                  | --                 | --                   | >20            |

Note:


The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor =  $40 \log (\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits(dBuV) + distance extrapolation factor.

**Test Mode:** Transmitting Mode

**30MHz -1GHz**




*Test Data*

**Horizontal Polarity Plot @3m**

| No. | P/L | Frequency | Reading  | Ant_F  | PA_G  | Cab_L | Result   | Limit    | Margin | Height | Degree |
|-----|-----|-----------|----------|--------|-------|-------|----------|----------|--------|--------|--------|
|     |     | (MHz)     | (dBuV/m) | (dB/m) | (dB)  | (dB)  | (dBuV/m) | (dBuV/m) | (dB)   | (cm)   | ( ° )  |
| 1   | H   | 251.1600  | 42.08    | 11.96  | 22.29 | 1.61  | 33.36    | 46.00    | -12.64 | 100    | 34     |
| 2   | H   | 331.6700  | 33.74    | 14.33  | 22.20 | 1.80  | 27.67    | 46.00    | -18.33 | 100    | 115    |
| 3   | H   | 515.0000  | 28.00    | 19.00  | 21.78 | 2.17  | 27.39    | 46.00    | -18.61 | 100    | 340    |
| 4   | H   | 687.6600  | 31.58    | 21.01  | 21.39 | 2.40  | 33.60    | 46.00    | -12.40 | 100    | 302    |
| 5   | H   | 833.1600  | 27.25    | 22.17  | 21.06 | 2.59  | 30.95    | 46.00    | -15.05 | 100    | 100    |
| 6   | H   | 954.4100  | 28.38    | 23.70  | 20.78 | 2.71  | 34.01    | 46.00    | -11.99 | 100    | 288    |

## 30MHz -1GHz



*Test Data*

### Vertical Polarity Plot @3m

| No. | P/L | Frequency | Reading  | Ant_F  | PA_G  | Cab_L | Result   | Limit    | Margin | Height | Degree |
|-----|-----|-----------|----------|--------|-------|-------|----------|----------|--------|--------|--------|
|     |     | (MHz)     | (dBuV/m) | (dB/m) | (dB)  | (dB)  | (dBuV/m) | (dBuV/m) | (dB)   | (cm)   | ( ° )  |
| 1   | V   | 55.2200   | 35.94    | 7.39   | 22.40 | 0.25  | 21.18    | 40.00    | -18.82 | 100    | 149    |
| 2   | V   | 251.1600  | 35.22    | 11.96  | 22.29 | 1.61  | 26.50    | 46.00    | -19.50 | 100    | 111    |
| 3   | V   | 331.6700  | 32.50    | 14.33  | 22.20 | 1.80  | 26.43    | 46.00    | -19.57 | 100    | 229    |
| 4   | V   | 686.6900  | 30.18    | 20.97  | 21.39 | 2.40  | 32.16    | 46.00    | -13.84 | 100    | 35     |
| 5   | V   | 790.4800  | 28.45    | 22.11  | 21.17 | 2.54  | 31.93    | 46.00    | -14.07 | 100    | 305    |
| 6   | V   | 905.9100  | 27.20    | 23.78  | 20.87 | 2.66  | 32.77    | 46.00    | -13.23 | 100    | 320    |

## Above 1GHz

|            |                   |
|------------|-------------------|
| Test Mode: | Transmitting Mode |
|------------|-------------------|

### Low Channel (2402 MHz)

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                           |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|---------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(mm) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2358.31        | 51.35                         | 74                | -22.65         | 185                       | 305                        | 65                     | -13.65                         |
| 2                                                   | 2355.01        | 37.21                         | 54                | -16.79         | 334                       | 192                        | 50.86                  | -13.65                         |
| 3                                                   | 2402           | 101.27                        |                   |                | 125                       | 5                          | 115.24                 | -13.97                         |
| 4                                                   | 2402           | 100.89                        |                   |                | 122                       | 207                        | 114.86                 | -13.97                         |
| 5                                                   | 4804           | 56.24                         | 74                | -17.76         | 397                       | 221                        | 59.99                  | -3.75                          |
| 6                                                   | 4804           | 52.87                         | 54                | -1.13          | 253                       | 245                        | 56.62                  | -3.75                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                           |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(mm) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2359.21        | 49.95                         | 74                | -24.05         | 331                       | 208                        | 63.6                   | -13.65                         |
| 2                                                   | 2359.21        | 35.24                         | 54                | -18.76         | 340                       | 0                          | 48.89                  | -13.65                         |
| 3                                                   | 2402           | 101.6                         |                   |                | 276                       | 322                        | 115.57                 | -13.97                         |
| 4                                                   | 2402           | 100.32                        |                   |                | 329                       | 226                        | 114.29                 | -13.97                         |
| 5                                                   | 4804           | 55.42                         | 74                | -18.58         | 149                       | 148                        | 59.17                  | -3.75                          |
| 6                                                   | 4804           | 52.18                         | 54                | -1.82          | 104                       | 235                        | 55.93                  | -3.75                          |

### REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.
5. The radiated spurious test above 18GHz is subcontracted to Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch Laboratories and found 30dB below the limit at least.

**Middle Channel (2440 MHz)**

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                           |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|---------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(mm) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2440           | 101.52                        |                   |                | 359                       | 310                        | 114.54                 | -13.02                         |
| 2                                                   | 2440           | 101.13                        |                   |                | 100                       | 174                        | 114.15                 | -13.02                         |
| 3                                                   | 4880           | 56.19                         | 74                | -17.81         | 317                       | 231                        | 60.15                  | -3.96                          |
| 4                                                   | 4880           | 53.08                         | 54                | -0.92          | 343                       | 329                        | 57.04                  | -3.96                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                           |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(mm) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2440           | 101.37                        |                   |                | 128                       | 187                        | 114.39                 | -13.02                         |
| 2                                                   | 2440           | 100.95                        |                   |                | 249                       | 331                        | 113.97                 | -13.02                         |
| 3                                                   | 4880           | 55.85                         | 74                | -18.15         | 180                       | 319                        | 59.81                  | -3.96                          |
| 4                                                   | 4880           | 52.31                         | 54                | -1.69          | 317                       | 106                        | 56.27                  | -3.96                          |

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.
- 5, The radiated spurious test above 18GHz is subcontracted to Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch Laboratories and found 30dB below the limit at least.

### High Channel (2440 MHz)

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                           |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|---------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(mm) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2484.84        | 52.92                         | 74                | -21.08         | 366                       | 265                        | 66.57                  | -13.65                         |
| 2                                                   | 2483.5         | 37.37                         | 54                | -16.63         | 335                       | 324                        | 51.02                  | -13.65                         |
| 3                                                   | 2480           | 101.95                        |                   |                | 144                       | 84                         | 115.92                 | -13.97                         |
| 4                                                   | 2480           | 101.6                         |                   |                | 210                       | 308                        | 115.57                 | -13.97                         |
| 5                                                   | 4960           | 56.35                         | 74                | -17.65         | 321                       | 234                        | 60.1                   | -3.75                          |
| 6                                                   | 4960           | 53.61                         | 54                | -0.39          | 359                       | 75                         | 57.36                  | -3.75                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                           |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(mm) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2483.5         | 50.24                         | 74                | -23.76         | 370                       | 150                        | 63.89                  | -13.65                         |
| 2                                                   | 2483.5         | 36.42                         | 54                | -17.58         | 319                       | 9                          | 50.07                  | -13.65                         |
| 3                                                   | 2480           | 101.15                        |                   |                | 370                       | 246                        | 115.12                 | -13.97                         |
| 4                                                   | 2480           | 100.87                        |                   |                | 248                       | 156                        | 114.84                 | -13.97                         |
| 5                                                   | 4960           | 55.21                         | 74                | -18.79         | 150                       | 67                         | 58.96                  | -3.75                          |
| 6                                                   | 4960           | 52.7                          | 54                | -1.3           | 123                       | 160                        | 56.45                  | -3.75                          |

#### REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.
5. The radiated spurious test above 18GHz is subcontracted to Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch Laboratories and found 30dB below the limit at least.


## Annex A. TEST INSTRUMENT

| Instrument                         | Model         | Serial #               | Cal Date   | Cal Due    |
|------------------------------------|---------------|------------------------|------------|------------|
| <b>AC Line Conducted Emissions</b> |               |                        |            |            |
| EMI test receiver                  | ESCS30        | 8471241027             | 01/04/2019 | 01/03/2020 |
| Artificial Mains Network           | 8127          | 8127713                | 01/04/2019 | 01/03/2020 |
| ISN                                | ISN T800      | 34373                  | 01/04/2019 | 01/03/2020 |
| <b>Radiated Emissions</b>          |               |                        |            |            |
| EMI test receiver                  | ESL6          | 1300.5001K06-100262-eQ | 01/04/2019 | 01/03/2020 |
| Active Antenna                     | AL-130        | 121031                 | 02/07/2019 | 02/06/2020 |
| 3m Semi-anechoic Chamber           | 9m*6m*6m      | N/A                    | 10/18/2018 | 10/17/2019 |
| Signal Amplifier                   | 8447E         | 443008                 | 01/24/2019 | 01/23/2020 |
| MXA signal analyzer                | N9020A        | MY49100060             | 01/04/2019 | 01/03/2020 |
| Horn Antenna                       | HAH-118       | 71259                  | 01/25/2019 | 01/24/2020 |
| Horn Antenna                       | HAH-118       | 71283                  | 02/01/2019 | 01/31/2020 |
| AMPLIFIER                          | EM01G26G      | 60613                  | 01/24/2019 | 01/23/2020 |
| AMPLIFIER                          | Emc012645     | 980077                 | 01/04/2019 | 01/03/2020 |
| Bilog Antenna (30MHz~6GHz)         | JB6           | A110712                | 02/07/2019 | 02/06/2020 |
| <b>RF Conducted</b>                |               |                        |            |            |
| DC Power Supply                    | E3640A        | MY40004013             | 01/04/2019 | 01/03/2020 |
| MXA Signal Analyzer                | N9020A        | MY49100060             | 01/04/2019 | 01/03/2020 |
| MXG Vector Signal Generator        | N5182A        | MY50140530             | 01/04/2019 | 01/03/2020 |
| Series Signal Generator            | E4421B        | US40051152             | 05/12/2018 | 05/11/2019 |
| RF control unit                    | JS0806-0806-2 | 188060112              | 04/25/2018 | 04/24/2019 |
| RF control unit                    | JS0806-0806-2 | 188060112              | 04/24/2019 | 04/23/2020 |
| Wireless Connectivity Tester       | CMW270        | 1201.0002K75-101601-PE | 04/25/2018 | 04/24/2019 |
| Wireless Connectivity Tester       | CMW270        | 1201.0002K75-101601-PE | 04/24/2019 | 04/23/2020 |
| Weinschel                          | 1580-1        | TL177                  | 01/04/2019 | 01/03/2020 |
| Universal Radio Communica          | CMU200        | 121393                 | 02/10/2019 | 02/09/2020 |


## Annex B. TEST SETUP AND SUPPORTING EQUIPMENT

### Annex B.i. TEST SET UP BLOCK

Block Configuration Diagram for Radiated Emissions ( Below 1GHz ) .



**Block Configuration Diagram for Radiated Emissions ( Above 1GHz ) .**



## **Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION**

The following is a description of supporting equipment and details of cables used with the EUT.

### **Supporting Equipment:**

| Manufacturer | Equipment Description | Model        | Serial No |
|--------------|-----------------------|--------------|-----------|
| Lenovo       | Laptop                | E40          | N/A       |
| TELINK       | Burning EVK           | TLSR8266BR56 | TELINK    |

### **Supporting Cable:**

| Cable type | Shield Type  | Ferrite Core | Length | Serial No |
|------------|--------------|--------------|--------|-----------|
| USB Cable  | Un-shielding | No           | 0.5m   | N/A       |

## Annex C. User Manual / Block Diagram / Schematics / Partlist

Please see the attachment

## Annex D. DECLARATION OF SIMILARITY

N/A