

ATTACHMENT O – SAR TEST PLOTS (1 of 3)

Test Laboratory: HCT

MODEL: NX9200(BODY)

Company: CASIO HITACHI Mobile Communications CO.,LTD.

Mode: CDMA 835 / Channel: 1013

Liquid Temperature: 21.5 °C

Date Tested: February 08, 2006

DUT: NX9200; Type: Folder; Serial: #1

Communication System: CDMA 835MHz; Frequency: 824.7 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 825$ MHz; $\sigma = 0.875$ mho/m; $\epsilon_r = 42.6$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1607; ConvF(6.18, 6.18, 6.18); Calibrated: 2005-08-30

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn614; Calibrated: 2005-04-21

- Phantom: SAM 835/900 MHz; Type: SAM

Left touch 1013/Area Scan (61x111x1): Measurement grid: $\Delta x = 15$ mm, $\Delta y = 15$ mm

Maximum value of SAR (interpolated) = 0.936 mW/g


Left touch 1013/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $\Delta x = 8$ mm, $\Delta y = 8$ mm, $\Delta z = 5$ mm

Reference Value = 29.1 V/m; Power Drift = -0.165 dB

Peak SAR (extrapolated) = 1.17 W/kg

SAR(1 g) = 0.846 mW/g; SAR(10 g) = 0.601 mW/g

Maximum value of SAR (measured) = 0.894 mW/g



0 dB = 0.894mW/g

Test Laboratory: HCT

MODEL: NX9200

Company : CASIO HITACHI Mobile Communications CO.,LTD.

Mode : CDMA 835 / Channel : 363

Liquid Temperature : 21.5 °C

Date Tested : February 08, 2006

DUT: NX9200; Type: Folder; Serial: #1

Communication System: CDMA 835MHz; Frequency: 835.89 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 835.89$ MHz; $\sigma = 0.889$ mho/m; $\epsilon_r = 42.4$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1607; ConvF(6.18, 6.18, 6.18); Calibrated: 2005-08-30

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn614; Calibrated: 2005-04-21

- Phantom: SAM 835/900 MHz; Type: SAM

Left touch 363/Area Scan (61x111x1): Measurement grid: $\Delta x = 15$ mm, $\Delta y = 15$ mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (interpolated) = 0.870 mW/g

Left touch 363/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $\Delta x = 8$ mm, $\Delta y = 8$ mm, $\Delta z = 5$ mm


Reference Value = 27.2 V/m; Power Drift = -0.030 dB

Peak SAR (extrapolated) = 1.05 W/kg

SAR(1 g) = 0.762 mW/g; SAR(10 g) = 0.539 mW/g

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.796 mW/g



Test Laboratory: HCT

MODEL: NX9200

Company : CASIO HITACHI Mobile Communications CO.,LTD.

Mode : CDMA 835 / Channel : 777

Liquid Temperature : 21.5 °C

Date Tested : February 08, 2006

DUT: NX9200; Type: Folder; Serial: #1

Communication System: CDMA 835MHz; Frequency: 848.31 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 848.31$ MHz; $\sigma = 0.905$ mho/m; $\epsilon_r = 42.3$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1607; ConvF(6.18, 6.18, 6.18); Calibrated: 2005-08-30

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn614; Calibrated: 2005-04-21

- Phantom: SAM 835/900 MHz; Type: SAM

Left touch 777/Area Scan (61x111x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (interpolated) = 1.04 mW/g

Left touch 777/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm


Reference Value = 29.6 V/m; Power Drift = -0.069 dB

Peak SAR (extrapolated) = 1.31 W/kg

SAR(1 g) = 0.943 mW/g; SAR(10 g) = 0.659 mW/g

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 1.01 mW/g



Test Laboratory: HCT

MODEL: NX9200

Company : CASIO HITACHI Mobile Communications CO.,LTD.

Mode : CDMA 835 / Channel : 1013

Liquid Temperature : 21.5 °C

Date Tested : February 08, 2006

DUT: NX9200; Type: Folder; Serial: #1

Communication System: CDMA 835MHz; Frequency: 824.7 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 825$ MHz; $\sigma = 0.875$ mho/m; $\epsilon_r = 42.6$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1607; ConvF(6.18, 6.18, 6.18); Calibrated: 2005-08-30

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn614; Calibrated: 2005-04-21

- Phantom: SAM 835/900 MHz; Type: SAM

Right touch 1013/Area Scan (61x111x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (interpolated) = 0.966 mW/g


Right touch 1013/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 28.8 V/m; Power Drift = -0.157 dB

Peak SAR (extrapolated) = 1.25 W/kg

SAR(1 g) = 0.903 mW/g; SAR(10 g) = 0.641 mW/g

Maximum value of SAR (measured) = 0.942 mW/g



0 dB = 0.942mW/g

Test Laboratory: HCT

MODEL: NX9200

Company : CASIO HITACHI Mobile Communications CO.,LTD.

Mode : CDMA 835 / Channel : 363

Liquid Temperature : 21.5 °C

Date Tested : February 08, 2006

DUT: NX9200; Type: Folder; Serial: #1

Communication System: CDMA 835MHz; Frequency: 835.89 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 835.89$ MHz; $\sigma = 0.889$ mho/m; $\epsilon_r = 42.4$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1607; ConvF(6.18, 6.18, 6.18); Calibrated: 2005-08-30

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn614; Calibrated: 2005-04-21

- Phantom: SAM 835/900 MHz; Type: SAM

Right touch 363/Area Scan (61x111x1): Measurement grid: $\Delta x = 15$ mm, $\Delta y = 15$ mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (interpolated) = 0.797 mW/g

Right touch 363/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $\Delta x = 8$ mm, $\Delta y = 8$ mm, $\Delta z = 5$ mm


Reference Value = 25.2 V/m; Power Drift = -0.028 dB

Peak SAR (extrapolated) = 1.07 W/kg

SAR(1 g) = 0.751 mW/g; SAR(10 g) = 0.525 mW/g

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.802 mW/g



0 dB = 0.802mW/g

Test Laboratory: HCT

MODEL: NX9200

Company : CASIO HITACHI Mobile Communications CO.,LTD.

Mode : CDMA 835 / Channel : 777

Liquid Temperature : 21.5 °C

Date Tested : February 08, 2006

DUT: NX9200; Type: Folder; Serial: #1

Communication System: CDMA 835MHz; Frequency: 848.31 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 848.31$ MHz; $\sigma = 0.905$ mho/m; $\epsilon_r = 42.3$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1607; ConvF(6.18, 6.18, 6.18); Calibrated: 2005-08-30

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn614; Calibrated: 2005-04-21

- Phantom: SAM 835/900 MHz; Type: SAM

Right touch 777/Area Scan (61x111x1): Measurement grid: $\Delta x = 15$ mm, $\Delta y = 15$ mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (interpolated) = 1.01 mW/g

Right touch 777/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $\Delta x = 8$ mm, $\Delta y = 8$ mm, $\Delta z = 5$ mm


Reference Value = 28.2 V/m; Power Drift = -0.098 dB

Peak SAR (extrapolated) = 1.30 W/kg

SAR(1 g) = 0.926 mW/g; SAR(10 g) = 0.649 mW/g

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.984 mW/g



Test Laboratory: HCT

MODEL: NX9200

Company : CASIO HITACHI Mobile Communications CO.,LTD.

Mode : CDMA 835 / Channel : 363

Liquid Temperature : 21.5 °C

Date Tested : February 08, 2006

DUT: NX9200; Type: Folder; Serial: #1

Communication System: CDMA 835MHz; Frequency: 835.89 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 835.89$ MHz; $\sigma = 0.889$ mho/m; $\epsilon_r = 42.4$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1607; ConvF(6.18, 6.18, 6.18); Calibrated: 2005-08-30

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn614; Calibrated: 2005-04-21

- Phantom: SAM 835/900 MHz; Type: SAM

Left tilt 363/Area Scan (61x111x1): Measurement grid: $\Delta x = 15$ mm, $\Delta y = 15$ mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (interpolated) = 0.403 mW/g

Left tilt 363/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $\Delta x = 8$ mm, $\Delta y = 8$ mm, $\Delta z = 5$ mm


Reference Value = 20.2 V/m; Power Drift = -0.086 dB

Peak SAR (extrapolated) = 0.439 W/kg

SAR(1 g) = 0.375 mW/g; SAR(10 g) = 0.299 mW/g

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.394 mW/g



Test Laboratory: HCT

MODEL: NX9200

Company : CASIO HITACHI Mobile Communications CO.,LTD.

Mode : CDMA 835 / Channel : 363

Liquid Temperature : 21.5 °C

Date Tested : February 08, 2006

DUT: NX9200; Type: Folder; Serial: #1

Communication System: CDMA 835MHz; Frequency: 835.89 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 835.89$ MHz; $\sigma = 0.889$ mho/m; $\epsilon_r = 42.4$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1607; ConvF(6.18, 6.18, 6.18); Calibrated: 2005-08-30

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn614; Calibrated: 2005-04-21

- Phantom: SAM 835/900 MHz; Type: SAM

Right tilt 363/Area Scan (61x111x1): Measurement grid: $\Delta x = 15$ mm, $\Delta y = 15$ mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (interpolated) = 0.400 mW/g

Right tilt 363/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $\Delta x = 8$ mm, $\Delta y = 8$ mm, $\Delta z = 5$ mm

Reference Value = 19.3 V/m; Power Drift = -0.078 dB

Peak SAR (extrapolated) = 0.650 W/kg

SAR(1 g) = 0.361 mW/g; SAR(10 g) = 0.251 mW/g

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.408 mW/g

