

## Cover Letter-Wireless Charger Approval

**FCC ID: U4GJNGSSDLITE**

**Date: 2018-05-04**

Gentlemen:

There's an Wireless Power Pad with Stand that would like to have your authorization as an Inductive wireless power transfer applications approval.

The specific product as below, Wireless Power Pad with Stand, with its designed features and specified description, meets special requirements for KDB 680106 D01 section 5.2 requirements.

|                      |                                         |
|----------------------|-----------------------------------------|
| <b>Company:</b>      | Datalogic S.r.l.                        |
| <b>Product Name:</b> | Joya Touch Single Slot Dock Charge Only |
| <b>Model Number:</b> | Joya Touch Single Slot Dock Charge Only |
| <b>FCC ID:</b>       | U4GJNGSSDLITE                           |

| <b>KDB 680106 D01 Section 5.2 Requirements:</b>                                                                                                                                                                                            | <b>Product Technical Specification :</b>                             | <b>Result:</b> |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------|----------------|
| a) Power transfer frequency is less that 1 MHz                                                                                                                                                                                             | 110-205kHz                                                           | Complied       |
| b) Output power from each primary coil is less than or equal to 15 Watts                                                                                                                                                                   | The output range must be 15W.                                        | Complied       |
| c) The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils | Only one single primary coils.                                       | Complied       |
| d) Client device is placed in in contact with the transmitter                                                                                                                                                                              | The client device is placed directly in contact with the transmitter | Complied       |
| e) Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).                                                                                                                                       | Mobile exposure conditions only                                      | Complied       |
| f) The ggregate leakage fields at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of MPE limit.                                                 | Please refer to the RF exposure report                               | Complied       |




Sincerely,

Print Name: Ruggero Cacioppo

Title: Product Quality Leader

Signature:



On behalf of Company: Datalogic S.r.l.

Telephone: +39 051 3147 393

E-mail: [ruggero.cacioppo@datalogic.com](mailto:ruggero.cacioppo@datalogic.com)

